| RIGHT NOW.ups Mar 1, 2013, 12 (dynm) = Table 34 | Control of an Indight Now. | Control of an Indight

Uses the normal weather.com page. It provides forecast for 10 days. Go to

## http://www.weather.com/

and search for your place's forecast. If found, go to the 10 days forecast and copy the address.

Put the Conky\_WeatherCom(\_metric) folder in your home folder.

Navigate inside the folder and make the script executable: Either by right clicking it or by

chmod +x ~/Conky\_WeatherCom/weath\_com

(chmod +x ~/Conky\_WeatherCom\_metric/weath\_com \_metric)

Open the script with your favourite text editor and replace my location's address at the address variable with yours.

Whether you use the .conkyrc\_weather\_com or the .conkyrc\_weather\_com\_metric config file, you should do a Find&Replace in them to replace

/home/teo

with

## /home/yourusername

(The if\_existing command in the conkyrc files doesn't accept the \$HOME variable – sorry).

You can intergrate the .conkyrc\_weather\_com(\_metric) into your own .conkyrc file or run it individually with

```
conky -c /path/.conkyrc_weather_com
```

or

```
conky -c /path/.conkyrc_weather_com_metric
```

The cookie for the metric script should last for a long time (years?).

The script has a lot of stuff to download from the internet. Initially, it gave me trouble as conky went on before the script had time to finish (even using texeci) and the screen came out missing data.

That's why at the beginning of the script I've put

```
kill -STOP $(pidof conky)
```

to pause **ALL** running instances of conky until the script finishes.

After it's done, conky goes on with

```
kill -CONT $(pidof conky)
```

So, don't be surprised if your other instances of conky pause for a couple of seconds every 10 minutes or so.