




# SandpileExperiment

Mathematics With Computer Science

*Author:* Zewan LYU(999019888)

*Date:* 2026-06-29

# Contents

|          |                                                                   |          |
|----------|-------------------------------------------------------------------|----------|
| <b>1</b> | <b>Basic Setting</b>                                              | <b>2</b> |
| 1.1      | The Abelian Sandpile Model                                        | 2        |
| 1.2      | Implementation of the Sandpile                                    | 2        |
| 1.3      | Experiment Design                                                 | 2        |
| 1.4      | Visualisation                                                     | 3        |
| 1.4.1    | 2D Interactive Viewer ( <code>--view2d</code> )                   | 3        |
| 1.4.2    | 3D Interactive Viewer ( <code>--view3d</code> )                   | 3        |
| <b>2</b> | <b>Classification of Directional Patterns</b>                     | <b>4</b> |
| 2.1      | General Description of Directional Patterns                       | 4        |
| 2.2      | Classification Table for $(n, m)$ , $0 \leq n, m \leq 7$          | 4        |
| 2.3      | Enlarged Classification Table for $(n, m)$ , $0 \leq n, m \leq 3$ | 6        |
| <b>3</b> | <b>Observed Regularities</b>                                      | <b>7</b> |
| 3.1      | Internal Color Periodicity                                        | 7        |
| 3.2      | Frequency of Occurrence                                           | 7        |
| 3.3      | Vector Sum Rule                                                   | 7        |
| 3.3.1    | Explaining the Observed Patterns                                  | 9        |
| 3.4      | Squared-Norm Rule                                                 | 10       |
| 3.4.1    | Trivial Case                                                      | 11       |

# Chapter 1

## Basic Setting

### 1.1 The Abelian Sandpile Model

The Abelian sandpile model is a cellular automaton introduced by Bak, Tang and Wiesenfeld. A  $d$ -dimensional lattice holds a non-negative integer  $h(x)$  at each site  $x$ , the number of grains. A site is *stable* when  $h(x) < T$ , where  $T$  is the toppling threshold; it is *unstable* when  $h(x) \geq T$ . An unstable site *topples*: it loses  $T$  grains and sends one grain to each of its  $2d$  nearest neighbours. Grains that leave the boundary are lost (open boundary condition). Repeated toppling eventually returns every site to a stable configuration; this final configuration is independent of the order of topplings (the Abelian property).

In two dimensions the grid is  $N \times N$ , the threshold is  $T = 4$ , and each site has four orthogonal neighbours. In three dimensions the cube is  $n \times n \times n$ , the threshold is  $T = 6$ , and each site has six neighbours  $(\pm x, \pm y, \pm z)$ .

### 1.2 Implementation of the Sandpile

The model is implemented in Python with NumPy. Two classes, `Sandpile2D` and `Sandpile3D`, share the same structure; we describe the 2D case for brevity. The grid is stored as a NumPy integer array. Stabilisation does not rescan the whole grid each step; instead it keeps a queue of currently unstable sites, so the running time is  $O(N^2 + \text{number of topples})$ . The core routine is:

Listing 1.1: Stabilisation by queue (2D, simplified).

---

```

1 def stabilize(grid, N, T=4):
2     queue = deque(sites where grid >= T)
3     topples = 0
4     while queue:
5         (x, y) = queue.popleft()
6         if grid[x, y] < T:           # already stabilised by a neighbour
7             continue
8         grid[x, y] -= T              # topple
9         topples += 1
10        for (nx, ny) in neighbours(x, y): # up, down, left, right
11            if inside(nx, ny, N):
12                grid[nx, ny] += 1
13                if grid[nx, ny] >= T:
14                    queue.append((nx, ny))
15    return grid, topples

```

---

Each toppling event removes  $T$  grains from a site and distributes one grain to every in-bounds neighbour; any grain crossing the boundary is discarded. The 3D version is identical except that the threshold is 6 and each toppling distributes to six neighbours instead of four.

### 1.3 Experiment Design

The experiments follow the instructions given in the email correspondence that initiated this project. The protocol for a single trial is:

1. Start with an  $N \times N$  (2D) or  $n \times n \times n$  (3D) grid.

2. Put a fixed *background* of grains on every site: 3 grains in 2D, 5 grains in 3D. The background is chosen one below the threshold, so the grid is stable but on the verge of toppling.
3. Select three random distinct sites and add one extra grain to each. At least one site now reaches the threshold and an avalanche begins.
4. Stabilise the grid with the routine of Section 1.2.
5. Save the final stable grid to disk and record statistics: total topplings, number of distinct toppled sites, the grain distribution, the seed, and the perturbed positions.

This trial is repeated many times (10 000 in 2D, 2 000 in 3D). Each trial uses an independent random seed  $s_i = s_0 + i$ , so the perturbation sites differ every trial while the experiment as a whole remains reproducible. A central configuration file (`config.py`) holds all parameters—grid size, threshold, background, number of perturbation sites, number of trials, seed and output directories—so that the whole experiment can be retuned from one place. The driver (`main.py`) reads these parameters, runs the batch, and saves grids and aggregate statistics incrementally so that progress survives an interruption.

After the batch completes, the same driver produces the classification study of Chapter 2: for each direction  $(n, m)$  with  $0 \leq n, m \leq 7$  it extracts the height pattern far from the centre along that direction and arranges the resulting images in a table.

## 1.4 Visualisation

The module `visualize.py` (built on Matplotlib) provides interactive viewers for exploring the saved grids. Each grain count is mapped to a fixed colour via a discrete 7-colour colormap (off-white  $\rightarrow$  yellow  $\rightarrow$  blue  $\rightarrow$  green  $\rightarrow$  orange  $\rightarrow$  brown  $\rightarrow$  red), so that the height pattern is read directly as a coloured image.

### 1.4.1 2D Interactive Viewer (`--view2d`)

The 2D viewer opens a Matplotlib window with a trial slider to browse grid snapshots. Red ★ markers indicate the three perturbation sites for each trial. The title bar displays the trial index, total topple count, and distinct-topped-site count. Keyboard shortcuts  $\leftarrow / \rightarrow$  (or A / D) navigate between trials.

#### Patch Inspection Feature

The 2D viewer includes a local inspection tool: hovering the mouse over any grid cell shows a live  $18 \times 18$  **preview inset** (top-left corner of the window) displaying the local neighbourhood around the cursor. Left-clicking or pressing the S key **saves** the patch as an annotated PNG image. In the saved image every cell is labelled with its exact grain count (black text for  $\leq 2$  grains, white for  $\geq 3$ ), making it possible to read precise height values without squinting at the colour map. Saved patches are written to `outputs/2d/local_patches/` with filenames of the form `patch_trial.NNNNNN.xX.yY.png`.

This feature is the primary tool for examining local periodic colour structures along directional lines (see Chapter 2), inspecting grain-count patterns at intersection points, and capturing exact configurations for inclusion in this report.

### 1.4.2 3D Interactive Viewer (`--view3d`)

The 3D viewer provides two orthogonal sliders—trial index and  $z$ -slice depth—for browsing 3D grids one 2D layer at a time. The grid is cached per trial, so switching  $z$  within the same trial is instantaneous. Keyboard shortcuts:  $\leftarrow / \rightarrow$  navigate  $z$ -slices,  $\uparrow / \downarrow$  (or W / S) navigate trials.

These interactive tools were used both to spot the regularities reported in Chapter 2 and to produce the figures in this report.

## Chapter 2

# Classification of Directional Patterns

After stabilizing 10000 trials of  $301 \times 301$  sandpile grids (each with background 3, plus 3 extra grains at random sites), we examine the pattern formed by cells whose height differs from 3. Far from the center, along a fixed rational direction  $(n, m)$ , a periodic height pattern emerges. We classify these patterns for all directions with  $0 \leq n, m \leq 7$ .

### 2.1 General Description of Directional Patterns

When one examines a stabilised grid far from the centre, the set of sites whose height differs from the background 3 forms a collection of lines. Each line extends outward in a fixed direction and is composed of a minimal periodic unit of coloured cells that repeats many times along that direction, giving every observed direction its own characteristic stripe. All observed directions are rational—that is, the slope of every line is a rational number; no line with an irrational slope appeared in any of the 10 000 trials.

### 2.2 Classification Table for $(n, m)$ , $0 \leq n, m \leq 7$

Table 2.1 shows the directional pattern for each pair  $(n, m)$ . Only seven distinct primitive (coprime) directions were observed across all 10000 trials. When a pair  $(n, m)$  reduces by  $\gcd(n, m)$  to one of these seven primitive directions, the corresponding image is shown; otherwise the entry reads “not found.”

Table 2.1: Directional pattern classification for  $0 \leq n, m \leq 7$ . Rows index  $n$ , columns index  $m$ . Entries show the image of the reduced coprime direction.

| $n \downarrow / m \rightarrow$ | 0                                                                                   | 1                                                                                 | 2                                                                                 | 3                                                                                 | 4                                                                                 | 5                                                                                   | 6                                                                                   | 7                                                                                     |
|--------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 0                              |    |  |  |  |  |  |  |    |
| 1                              |    |  |  |  | not found                                                                         | not found                                                                           | not found                                                                           | not found                                                                             |
| 2                              |    |  |  | not found                                                                         |  | not found                                                                           |  | not found                                                                             |
| 3                              |    |  | not found                                                                         |  | not found                                                                         | not found                                                                           |  | not found                                                                             |
| 4                              |    | not found                                                                         |  | not found                                                                         |  | not found                                                                           | not found                                                                           | not found                                                                             |
| 5                              |    | not found                                                                         | not found                                                                         | not found                                                                         | not found                                                                         |  | not found                                                                           | not found                                                                             |
| 6                              |    | not found                                                                         |  |  | not found                                                                         | not found                                                                           |  | not found                                                                             |
| 7                              |  | not found                                                                         | not found                                                                         | not found                                                                         | not found                                                                         | not found                                                                           | not found                                                                           |  |

The seven observed directions are:














$$(0, 1), (1, 0), (1, 1), (1, 2), (1, 3), (2, 1), (3, 1).$$

Note that  $(n, m)$  and  $(m, n)$  yield symmetric patterns in general (e.g.,  $(1, 2)$  vs.  $(2, 1)$  are symmetric). You can check the folder `images/` for the original images.

## 2.3 Enlarged Classification Table for $(n, m)$ , $0 \leq n, m \leq 3$

Table 2.2 shows the same classification restricted to  $0 \leq n, m \leq 3$ . Because the table is smaller, each image is displayed at a larger size so the periodic structure of every pattern is easier to inspect. The mapping from  $(n, m)$  to its reduced coprime direction is the same as in Table 2.1; entries that do not correspond to any observed primitive direction are marked “not found.”

Table 2.2: Directional pattern classification for  $0 \leq n, m \leq 3$  (enlarged). Rows index  $n$ , columns index  $m$ .

| $n \downarrow / m \rightarrow$ | 0                                                                                   | 1                                                                                   | 2                                                                                   | 3                                                                                     |
|--------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 0                              | —                                                                                   |    |   |    |
| 1                              |    |    |   |    |
| 2                              |   |   |  | not found                                                                             |
| 3                              |  |  | not found                                                                           |  |

All seven primitive directions already appear within this  $0 \leq n, m \leq 3$  range:  $(0, 1)$ ,  $(1, 0)$ ,  $(1, 1)$ ,  $(1, 2)$ ,  $(1, 3)$ ,  $(2, 1)$ , and  $(3, 1)$ . The two remaining pairs,  $(2, 3)$  and  $(3, 2)$ , are coprime but were not observed in any trial.

# Observed Regularities


### 3.1 Internal Color Periodicity

[illegible]


### 3.2 Frequency of Occurrence

### 3.3 Vector Sum Rule

The intersection of  $(1, 0)$  and  $(0, 1)$  yields  $(1, 1)$ .

Figure 3.2: Intersection of  $(1, 0)$  and  $(0, 1)$ , yielding  $(1, 1)$ .

The intersection of  $(1, 1)$  and  $(0, 1)$  yields  $(1, 2)$ .

Figure 3.3: Intersection of  $(1, 1)$  and  $(0, 1)$ , yielding  $(1, 2)$ .

The intersection of  $(1, 2)$  and  $(0, 1)$  yields  $(1, 3)$ .




Figure 3.4: Intersection of  $(1, 2)$  and  $(0, 1)$ , yielding  $(1, 3)$ .

Four lines may also meet at one point. For example,  $(0, 1)$ ,  $(2, 1)$ ,  $(1, 1)$ , and  $(1, 1)$  meet at a point, since  $(0, 1) + (2, 1) = (1, 1) + (1, 1)$ .




Figure 3.5: Four-line intersection:  $(0, 1)$ ,  $(2, 1)$ ,  $(1, 1)$ ,  $(1, 1)$ . The direction vectors balance pairwise.

### 3.3.1 Explaining the Observed Patterns

The zero-sum rule at intersections explains several earlier observations.

**No irrational slopes.** Every directional line is born at an intersection of two existing lines, so its direction vector is an integer sum (or difference) of the two parent vectors. Starting from  $(1, 0)$  and  $(0, 1)$ , repeated addition can only produce integer vectors  $(n, m)$ . Hence every slope  $m/n$  is rational. An irrational slope would require an irrational vector component, which integer arithmetic can never produce. This explains why no line with an irrational slope appeared in any of the 10 000 trials.

**Rarity of near-horizontal or near-vertical lines.** A line with slope  $1/n$  (or  $n$ ) for large  $n$  requires building a direction vector with very different components. Under the zero-sum rule, this means adding the basic vertical direction repeatedly to a nearly horizontal line, which demands several successive intersections along the same path. Each extra intersection is rare, so directions such as  $(1, 3)$  or  $(3, 1)$  appear far less often than  $(1, 1)$ , which results from a single intersection of the two most common lines,  $(1, 0)$  and  $(0, 1)$ . By contrast, the horizontal, vertical, and  $45^\circ$  directions arise from the simplest sums and appear almost everywhere.

### 3.4 Squared-Norm Rule

For each directional line, let  $\mathcal{D}$  be the total height difference from the background over one full period, and let  $v = (n, m)$  with  $\gcd(n, m) = 1$  be its direction vector. Across all trials and all observed directions,

$$\mathcal{D} = |v|^2 = n^2 + m^2. \quad (3.1)$$

We verify this for four representative directions.

For  $v = (0, 1)$ , the repeating unit is a single cell of height 2, so  $\mathcal{D} = 3 - 2 = 1 = 0^2 + 1^2$ .




Figure 3.6: Directional pattern  $(0, 1)$ . Repeating unit: one cell of height 2,  $\mathcal{D} = 1$ .

For  $v = (1, 1)$ , the repeating unit is a single cell of height 1, so  $\mathcal{D} = 3 - 1 = 2 = 1^2 + 1^2$ .




Figure 3.7: Directional pattern  $(1, 1)$ . Repeating unit: one cell of height 1,  $\mathcal{D} = 2$ .

For  $v = (2, 1)$ , the repeating unit consists of three cells of heights 2, 0, 2, so

$$\mathcal{D} = (3 - 2) + (3 - 0) + (3 - 2) = 5 = 2^2 + 1^2.$$




Figure 3.8: Directional pattern (2,1). Repeating unit: heights 2,0,2,  $\mathcal{D} = 5$ .

For  $v = (3, 1)$ , the repeating unit consists of seven cells of heights 2, 2, 0, 3, 0, 2, 2, so

$$\mathcal{D} = (3 - 2) + (3 - 2) + (3 - 0) + (3 - 3) + (3 - 0) + (3 - 2) + (3 - 2) = 10 = 3^2 + 1^2.$$




Figure 3.9: Directional pattern (3,1). Repeating unit: heights 2,2,0,3,0,2,2,  $\mathcal{D} = 10$ .

### 3.4.1 Trivial Case

Each background cell can be viewed as a directional line with vector  $(0, 0)$ , its repeating unit being the cell itself. The difference from the background is  $\mathcal{D} = 3 - 3 = 0 = 0^2 + 0^2$ , which also satisfies the rule.