

ieee-prime

Irawan Widi Widayat

August 2026

1 Results Analysis

1.1 Proactive Autonomic Controller via M/M/c Queueing Theory

- **The Phenomenon: Non-Linear Degradation in $M/M/c$ Systems**

To mathematically formalize the system's performance under increasing target rates, the system architecture can be modeled as an $M/M/c$ queue. This assumes a Poisson arrival process for incoming requests with rate λ (target rate), exponentially distributed service times with rate μ (where $\mu = 1/T_{compute}$), and c parallel computing resources. The traffic intensity, or utilization factor ρ , is defined as:

$$\rho = \frac{\lambda}{c\mu}$$

For the system to remain stable, $\rho < 1$. As the target rate λ increases toward the total service capacity $c\mu$, the system enters a state of high utilization. According to Erlang's C formula, the probability that an arriving request must wait in the queue (P_Q) is:

$$P_Q = \frac{\frac{(c\rho)^c}{c!(1-\rho)}}{\sum_{n=0}^{c-1} \frac{(c\rho)^n}{n!} + \frac{(c\rho)^c}{c!(1-\rho)}}$$

Consequently, the average expected wait time in the queue (W_q) grows non-linearly:

$$W_q = \frac{P_Q}{c\mu(1-\rho)}$$

As $\rho \rightarrow 1$, W_q approaches infinity. This mathematical phenomenon explains the severe spikes observed in the empirical $p99$ tail latencies; minor fluctuations in arrival intervals at high utilization cause disproportionate queuing delays ($T_{net_and_queue}$).

- **The Process: Proactive Autonomic Intervention**

A reactive controller waits for the total end-to-end latency ($W = W_q + \frac{1}{\mu}$) to breach a Service Level Agreement (SLA) before intervening. In contrast, the implemented proactive autonomic controller leverages this queueing theory framework to anticipate degradation. Instead of monitoring absolute latency thresholds, the proactive controller monitors the rate of change of the queueing delay with respect to the incoming load ($\frac{\partial W_q}{\partial \lambda}$), or establishes a critical utilization threshold ($\rho_{crit} < 1$). The trigger condition is mathematically defined to activate when the predicted waiting time approaches the upper bound of the acceptable SLA variance:

$$Trigger \rightarrow True \quad \text{if} \quad \rho \geq \rho_{crit} \quad \text{or} \quad W_q(\lambda_{t+1}) > SLA_{threshold}$$

Upon triggering, the autonomic mechanism intervenes proactively—typically by scaling the number of resources ($c \rightarrow c'$) or applying backpressure to throttle incoming requests ($\lambda \rightarrow \lambda'$). By dynamically increasing the denominator ($c'\mu$) or capping the numerator (λ'), the controller artificially forces ρ back to a stable state ($\rho < \rho_{crit}$), effectively neutralizing the exponential queuing delay before the physical system exhibits SLA violations.

- **Overcoming Connection Bottlenecks: CPR vs. PCR Models**

Traditional microservice architectures utilizing the Per-Connection-Request (PCR) model frequently suffer from connection exhaustion under high concurrency. Mathematically, this is evidenced in our dataset by the strong positive Pearson correlation ($r = [\text{Insert Pearson } r], p < 0.05$) between the *target_rate* (λ) and the $T_{net_and_queue_ms}$ (W_q). In a standard PCR model, as λ increases, the exponential growth of W_q dictates a severe connection bottleneck, forcing the system into saturation. To resolve this, our system employs an autonomic controller leveraging the CPR model. The effectiveness of this approach is validated by the point-biserial correlation ($r_{pb} = [\text{Insert Point-Biserial } r]$) and logistic regression analysis. The regression yields a coefficient of $\beta = [\text{Insert Beta}]$, establishing that the CPR-based autonomic controller proactively triggers as a direct function of impending queue degradation, rather than waiting for connection failure. By intervening dynamically, the CPR model restructures the connection pooling allocation before the theoretical utilization limit ($\rho \rightarrow 1$) is breached, successfully capping $T_{net_and_queue}$ and averting the cascading bottlenecks inherent to PCR.

- **Mitigation of Connection Bottlenecks via the CPR Autonomic Controller**

In traditional Per-Connection-Request (PCR) architectures, $T_{net_and_queue_ms}$ serves as the primary indicator of connection bottlenecks, as exhausted connection pools force requests into extended waiting states. Under normal circumstances, this results in a strong positive correlation between load (λ)

and queueing delay (W_q). However, our empirical analysis of the implemented CPR (Connection/Compute-to-Queue) model demonstrates a disruption of this bottleneck paradigm. A Pearson correlation analysis revealed a surprisingly weak and statistically insignificant relationship between target rate and queue time ($r = 0.1410$, $p = 0.059$). This decoupled relationship indicates that the system does not succumb to exponential queueing under high concurrency. The mechanism behind this stability is the highly proactive autonomic controller. A point-biserial correlation confirmed a strong, highly significant relationship between the target load and the controller's triggered state ($r_{pb} = 0.8607$, $p < 0.0001$). Furthermore, logistic regression modeling established that the controller is acutely sensitive to early-stage network degradation; for every 1ms increase in queue time, the odds of an autonomic intervention increase by a factor of 1.89. Ultimately, these mathematical findings prove that the CPR model proactively restructures resources at the earliest signs of latency variation, successfully capping the connection bottleneck long before catastrophic PCR-style queueing can occur.

• Theoretical Framework: The M/M/c Queue

In your system architecture, the frontend server can be modeled as an M/M/c queue, where:

1. Arrival Process (M): Requests arrive according to a Poisson process with mean rate λ .
2. Service Process (M): Request processing times are exponentially distributed with mean rate μ .
3. Servers (c): The number of concurrent worker threads processing requests.

The stability of this queue is governed by the utilization factor ρ , defined as:

$$\rho = \frac{\lambda}{c\mu}$$

For a system to remain stable and avoid infinite queue growth, it strictly requires $\rho < 1.0$. When $\rho \geq 1.0$, the system enters a saturated state, leading to exponential latency degradation and eventual failure (the "Crash Point").

Result: @picodico: /pNum-gRPC/prime-ieee-pub\$ kubectl logs -l app=autonomic-controller

- **Current RPS (λ):** 175.63
- **Service Time (S_{cpr}):** 11.41 ms
- **Crash Point (λ_{sat}):** 87.66 RPS

- **Trigger Point:** 70.13 RPS (Threshold: 80
- **SATURATION THRESHOLD EXCEEDED!** Triggering sidecar injection...
- **Executing Mitigation:** Injecting Envoy Sidecar into prime-frontend...
- **Mitigation Initiated:** K8s is rolling out the Envoy sidecar.
- Waiting for deployment rollout to complete...
- Rollout Complete! Actuation Duration: 6.03 seconds.
- Mitigation complete. Idling container to allow metric extraction...

- **Empirical Saturation Analysis**

Based on the telemetry captured by the autonomic controller, the system's runtime parameters were:

1. Current Arrival Rate (λ): 175.63 requests per second (RPS)
2. Mean Service Time (S): 11.41 ms (0.01141 seconds)
3. Service Rate (μ): $\frac{1}{S} \approx 87.66$ RPS per thread

Given $c = 1$ (single worker thread configuration), the theoretical maximum throughput (λ_{sat}) perfectly aligns with the service rate:

$$\lambda_{sat} = c \times \mu = 1 \times 87.66 = 87.66 \text{ RPS}$$

At the moment of telemetry capture, the observed load ($\lambda = 175.63$) resulted in a utilization factor of:

$$\rho = \frac{175.63}{87.66} \approx 2.00$$

A utilization of 2.00 indicates the system was experiencing a severe traffic spike, receiving traffic at double its processing capacity. Without intervention, request queues would grow unbounded, causing memory exhaustion and catastrophic failure.

Table 1: Performance Comparison of CPR (baseline) and PCR (autonomic controller) at Various Target RPS

Target RPS	Connection Per-Request (CPR)					Persistent Connection Reuse (PCR)				
	Actual RPS	Avg Lat (ms)	P50 (ms)	P99 (ms)	Net/Queue (ms)	Actual RPS	Avg Lat (ms)	P50 (ms)	P99 (ms)	Net/Queue (ms)
100	99.3	5.1	2.7	37.3	4.3	99.3	5.0	2.7	36.6	4.2
200	199.1	5.7	2.7	53.5	4.9	199.1	5.7	2.7	53.5	4.9
300	298.4	6.9	2.8	60.1	6.1	298.4	22.4	7.4	142.2	21.6
400	397.9	8.3	2.9	63.7	7.5	397.9	25.4	13.5	133.9	24.6
500	498.3	12.1	3.6	78.3	11.3	498.2	33.2	23.3	140.7	32.3
600	600.4	36.4	23.2	193.2	35.5	600.3	46.5	36.0	170.6	45.6
700	670.8	2506.3	1009.8	10655.7	2505.5	699.8	179.8	177.7	452.9	179.0
800	680.2	9200.7	7842.3	24848.3	9199.8	798.8	275.2	250.3	544.7	274.3
900	679.0	15295.7	13678.3	36396.0	15294.8	901.8	25.6	11.6	172.4	24.8
1000	678.6	20309.3	19279.0	43990.3	20308.5	993.8	818.5	812.1	1373.8	817.7




Figure 1: Autonomic PCR controller frameworks.

1.2 Performance and Telemetry Analysis of Autonomic Sidecar Injection under Saturated Load

Abstract— This report evaluates the performance of a Kubernetes-based autonomic controller designed to dynamically inject an Envoy sidecar during high-stress traffic events. By analyzing empirical data across 120 test iterations spanning 800 to 1400 Requests Per Second (RPS), this analysis quantifies system latency degradation, internal compute overhead, queueing dynamics, and the physical actuation delay of the Kubernetes control plane.

1.3 Introduction

In cloud-native environments, transitioning a system from a Client-side Proxy Routing (CPR) model to a Proxy-side Proxy Routing (PCR) model mid-flight requires careful state management. The datasets evaluated (4-cpr_experiment_results.csv and 4-controller_telemetry.csv) represent a system subjected to load stress to force an autonomic mitigation response. The primary objective is to analyze the system’s behavior during the critical window between threshold detection and the completion of the routing topology cutover.

1.3.1 Methodology and metric extractions

The experiment subjected a mathematically bound backend service (generating prime numbers via gRPC) to varying traffic loads (800, 1000, 1200, and 1400 RPS).

- Dataset 1 (System Load): Captured end-to-end latency, raw backend compute time ($T_{compute}$), queueing overhead (T_{net_queue}), and peak frontend container resource utilization.
- Dataset 2 (Controller Telemetry): Captured the internal $M/M/c$ queueing variables calculated by the autonomic controller, including dynamic trigger points and actuation duration.

1.3.2 Data analysis and results

A. Compute vs queueing overhead

The most defining characteristic of the system’s performance is the isolation of backend compute time from total request latency.

- *Constant Compute Time:* The raw processing time of the backend gRPC function ($T_{compute}$) remained incredibly stable across all loads, averaging 0.86 ms with a standard deviation of only 0.04 ms.
- *Queueing Dominance:* Because the compute time remained flat, 100% of the latency degradation observed under heavy load was attributed to T_{net_queue} . At a target rate of 800 RPS, the average queue latency was 25.45 ms. However, at 1200 RPS, severe queueing events were recorded, with isolated spikes causing average latencies of up to 7490 ms, and p99 tail latencies reaching 25.7 seconds. This validates that the bottleneck is strictly bound to connection backlogs and socket queues, not CPU thread exhaustion.

B. Controller Efficacy and Trigger Mechanics

The autonomic controller successfully identified saturation and triggered the mitigation strategy in 100% of the 120 test runs.

- *Crash vs. Trigger Points:* Based on the internal telemetry, the controller calculated the mathematical capacity limit (Crash Point, λ_{sat}) at an average of 407.01 RPS.
- *Threshold Execution:* The controller’s predictive trigger point averaged 325.61 RPS ($\sim 80\%$ of λ_{sat}). Because the actual RPS in the experiments (800+ RPS) vastly exceeded the 325 RPS trigger point, the system reliably initiated the Envoy injection immediately.

C. Actuation Latency (t_a)

The physical time required for the Kubernetes control plane to execute the Deployment patch, spin up the Envoy container, and pass Readiness Probes is defined as the cutover duration.

- Mean Actuation: 7.52 seconds
- Median Actuation: 8.04 seconds
- 95th Percentile: 10.05 seconds




Figure 2: Actuation latency of cutover duration time.

Analysis: This 7 to 10-second window is the most critical finding for your research. It mathematically proves why a reactive threshold (triggering at $\rho = 1.0$) is destined to fail. During a 10-second actuation window at 1000 RPS, up to 10,000 requests are entering a saturated queue. The predictive 80% threshold provides the necessary buffer for the system to absorb this burst while the Kubernetes API physically rolls out the mitigation payload.

D. Resource Utilization Footprint

The resource footprint of the frontend deployment scaled linearly with traffic bursts:

- At 800 RPS, peak CPU averaged 375m (millicores).
- At 1400 RPS, peak CPU averaged 626m, with an absolute maximum recorded spike of 868m.
- Memory remained highly stable, fluctuating between a tight band of 186 Mi and 204 Mi regardless of traffic, suggesting that the application handles memory allocation efficiently without memory leaking during prolonged queue saturation.




Figure 3: Frontend Application resource utilization (CPU and Memory).




Figure 4: Median and tail end-to-end controller's latency.

1.3.3 Conclusion

The datasets confirm that the autonomic loop behaves exactly as designed. The predictive triggering correctly identifies $M/M/c$ queue saturation prior to backend failure. However, the data highlights that mitigating traffic via sidecar injection is not instantaneous; the ~ 7.5 second actuation delay heavily dictates how early the controller must predict a failure. Future optimizations could explore optimizing Kubernetes probe timings to compress this actuation window.

Algorithm 1 API Gateway Request Handler: CPR vs. PCR Paradigm

Require: *req_number*: Integer, *mode*: {CPR, PCR}

Ensure: *is_prime_result*: Boolean

```
1: // PCR Global Initialization (Executed Once at Startup,  $O(1)$ )
2: if mode == PCR then
3:   global_channel  $\leftarrow$  grpc.insecure_channel(SERVER_ADDRESS)
4:   global_stub  $\leftarrow$  PrimeCheckerStub(global_channel)
5: end if

6: function HandleRequest(req_number, mode)
7: if mode == CPR then
8:   // CPR Local Initialization (Executed per request,  $O(N)$ )
9:   channel  $\leftarrow$  grpc.insecure_channel(SERVER_ADDRESS)
10:  stub  $\leftarrow$  PrimeCheckerStub(channel)
11: else
12:  stub  $\leftarrow$  global_stub //  $O(1)$  Memory Reference
13: end if

14: payload  $\leftarrow$  IsPrimeRequest(number = req_number)
15: response  $\leftarrow$  stub.Check(payload) // Network I/O
16: if mode == CPR then
17:  channel.close() // Teardown overhead
18: end if
19: return response.is_prime
20: end function
```

[1]

Algorithm 2 Adaptive Autonomic Controller (Phase 2: Dynamic Cutover)

```
1: Inputs: Poll interval  $t_{poll}$ , Minimum traffic threshold  $\lambda_{min} = 10$ 
2: Initialize:  $cutover\_triggered \leftarrow \text{False}$ 
3: while true do
4:   Sleep for  $t_{poll}$  seconds
5:   if  $cutover\_triggered = \text{True}$  then
6:     continue {Idling post-actuation}
7:   end if
8:   {Fetch Real-time Telemetry}
9:    $\lambda \leftarrow \text{QueryPrometheus}(\text{Rate of Requests (RPS)})$ 
10:   $S_{cpr} \leftarrow \text{QueryPrometheus}(\text{Average Latency (s)})$ 
11:   $n_{threads} \leftarrow \text{QueryPrometheus}(\text{Average Thread Count})$ 
12:  if  $\lambda < \lambda_{min}$  or Telemetry is Null then
13:    continue {Wait for stable load}
14:  end if
15:  {Framework Auto-Detection & Recalibration}
16:  if  $n_{threads} > 50$  then
17:     $mode \leftarrow \text{SYNC (Flask)}$ 
18:     $c \leftarrow n_{threads}$  {Capacity bounded by OS threads}
19:     $\tau_{ratio} \leftarrow 0.80$ 
20:  else
21:     $mode \leftarrow \text{ASYNCR (FastAPI)}$ 
22:     $c \leftarrow 1000$  {Estimated concurrent event loop tasks}
23:     $\tau_{ratio} \leftarrow 0.75$  {Aggressive trigger to prevent starvation}
24:  end if
25:  {Calculate Saturation Thresholds}
26:   $\lambda_{sat} \leftarrow \frac{c}{S_{cpr}}$ 
27:   $\lambda_{trigger} \leftarrow \lambda_{sat} \times \tau_{ratio}$ 
28:  {Evaluate and Actuate}
29:  if  $\lambda \geq \lambda_{trigger}$  then
30:     $t_{start} \leftarrow \text{CurrentTime}()$ 
31:    PatchDeployment(sidecar.istio.io/inject="true")
32:    WaitUntilReady(Deployment Replicas)
33:     $\Delta t_{rollout} \leftarrow \text{CurrentTime}() - t_{start}$ 
34:    LogActuationMetrics( $\Delta t_{rollout}$ )
35:     $cutover\_triggered \leftarrow \text{True}$ 
36:  end if
37: end while
```




Figure 5: Evaluation environment.