

Package ‘rosetteApi’

December 9, 2016

Type Package

Title Rosette API

Version 1.4.2

Date 2016-10-05

Author Sam Hausmann [aut, cre],
Chris Park [ctb],
Hannah Gaudet [ctb]

Maintainer Chris Park <cpark@basistech.com>

Description Rosette is an API for multilingual text analysis and information
extraction. More information can be found at <<https://developer.rosette.com>>.

License file LICENSE

Depends R (>= 3.1.0)

Imports httr,
jsonlite

Suggests knitr,
rmarkdown,
testthat

URL <https://developer.rosette.com>

BugReports <https://developer.rosette.com/support-ticket>

VignetteBuilder knitr

RoxygenNote 5.0.1

R topics documented:

api	2
check_content_parameters	3
check_for_multipart	3
check_morphology	4
check_names	4
create_multipart	5

error_check	5
get_binding_version	6
get_endpoint	6
get_headers	7
post_endpoint	7
serialize_name_parameters	8
serialize_parameters	8
Index	9

api	<i>api wrapper function that checks for a user_key and determines the Rosette API endpoint to be utilized</i>
-----	---

Description

api wrapper function that checks for a user_key and determines the Rosette API endpoint to be utilized

Usage

```
api(user_key, endpoint, parameters = FALSE, custom_headers = NULL,
    url_parameters = NULL, url = "https://api.rosette.com/rest/v1/")
```

Arguments

- user_key - Rosette API authentication key
- endpoint - Rosette API endpoint to be utilized
- parameters - parameters list to be passed to specified Rosette API endpoint
- custom_headers - custom headers for Rosette Api
- url_parameters - query parameters
- url - url for Rosette Api

Value

Returns a list(content, header)

Examples

```
## Not run:
parameters <- list()
parameters[["content"]] <- "Bill Murray will appear in new Ghostbusters film."
response = api(01234567890, "entities", parameters) will return response$content and response$header

## End(Not run)
```

`check_content_parameters`*preemptive check for content/contentUri request parameter errors*

Description

preemptive check for content/contentUri request parameter errors

Usage

`check_content_parameters(parameters)`

Arguments

`parameters` - parameters list to be passed to specified Rosette API endpoint

Value

Returns list of verified parameters to be sent to Rosette API

`check_for_multipart` *Helper to check for file submission*

Description

Helper to check for file submission

Usage

`check_for_multipart(parameters)`

Arguments

`parameters` - JSON parameters

Value

true if multipart

check_morphology	<i>determine which morphology endpoint to use</i>
------------------	---

Description

determine which morphology endpoint to use

Usage

check_morphology(parameters, endpoint)

Arguments

parameters	- parameters list to be passed to specified Rosette API endpoint
endpoint	- Rosette API endpoint to be utilized

Value

Returns the specified morphology function

check_names	<i>check if the required request parameters for either names endpoint are correct</i>
-------------	---

Description

check if the required request parameters for either names endpoint are correct

Usage

check_names(parameters, endpoint)

Arguments

parameters	- parameters list to be passed to specified Rosette API endpoint
endpoint	- Rosette API endpoint to be utilized

Value

Returns list of verified parameters to be sent to Rosette API

create_multipart	<i>create a multipart</i>
------------------	---------------------------

Description

create a multipart

Usage

create_multipart(parameters)

Arguments

parameters - parameters list to be passed to specified Rosette API endpoint

Value

Returns a multipart

error_check	<i>check if Rosette API response includes and error message</i>
-------------	---

Description

check if Rosette API response includes and error message

Usage

error_check(response)

Arguments

response - response from Rosette API

Value

Returns an error if one exists or the Rosette API response

get_binding_version	<i>Provides the binding Version</i>
---------------------	-------------------------------------

Description

Provides the binding Version

Usage

```
get_binding_version()
```

Value

current binding version

get_endpoint	<i>httr::GET request to specified Rosette API endpoint</i>
--------------	--

Description

httr::GET request to specified Rosette API endpoint

Usage

```
get_endpoint(user_key, endpoint, url, custom_headers = NULL,  
             url_parameters = NULL)
```

Arguments

user_key	- Rosette API authentication key
endpoint	- Rosette API endpoint to be utilized
url	- url for Rosette Api
custom_headers	- custom headers for Rosette Api
url_parameters	- url query parameters

Value

Returns the Rosette API response

get_headers	<i>Helper to combine custom headers with the default ones</i>
-------------	---

Description

Helper to combine custom headers with the default ones

Usage

```
get_headers(user_key, content_type = "application/json",  
            custom_headers = NULL)
```

Arguments

user_key - Rosette API authentication key
content_type - Header Content-Type
custom_headers - custom headers for the Rosette API

Value

Returns the combined h

post_endpoint	<i>httr::POST request to specified Rosette API endpoint</i>
---------------	---

Description

httr::POST request to specified Rosette API endpoint

Usage

```
post_endpoint(user_key, parameters, endpoint, url, custom_headers = NULL,  
              url_parameters = NULL)
```

Arguments

user_key - Rosette API authentication key
parameters - parameters list to be passed to specified Rosette API endpoint
endpoint - Rosette API endpoint to be utilized
url - url for Rosette Api
custom_headers - custom headers for Rosette Api
url_parameters - query parameters

Value

Returns the Rosette API response

serialize_name_parameters

serialize Rosette API parameters

Description

serialize Rosette API parameters

Usage

serialize_name_parameters(parameters)

Arguments

parameters - parameters list to be passed to either name-translation or name-similarity

Value

Returns the serialized parameters for the Rosette API

serialize_parameters *serialize Rosette API parameters*

Description

serialize Rosette API parameters

Usage

serialize_parameters(parameters)

Arguments

parameters - parameters list to be passed to specified Rosette API endpoint

Value

Returns the serialized parameters for the Rosette API

Index

api, [2](#)

check_content_parameters, [3](#)

check_for_multipart, [3](#)

check_morphology, [4](#)

check_names, [4](#)

create_multipart, [5](#)

error_check, [5](#)

get_binding_version, [6](#)

get_endpoint, [6](#)

get_headers, [7](#)

post_endpoint, [7](#)

serialize_name_parameters, [8](#)

serialize_parameters, [8](#)