

## Question 1

Correct

Marked out of 1.00

[Flag question](#)

You are given a two-dimensional 3\*3 array starting from A [0][0]. You should add the alternate elements of the array and print its sum. It should print two different numbers the first being sum of A 0 0, A 0 2, A 1 1, A 2 0, A 2 2 and A 0 1, A 1 0, A 1 2, A 2 1.

**Input Format**

First and only line contains the value of array separated by single space.

A 0 0	A 0 1	A 0 2
4	6	9
A 1 0	A 1 1	A 1 2
2	5	8
A 2 0	A 2 1	A 2 2
1	3	7

**Output Format**

First line should print sum of A 0 0, A 0 2, A 1 1, A 2 0, A 2 2

Second line should print sum of A 0 1, A 1 0, A 1 2, A 2 1

A 0 0	A 0 1	A 0 2
4	6	9
A 1 0	A 1 1	A 1 2
2	5	8
A 2 0	A 2 1	A 2 2
1	3	7

## Output Format

First line should print sum of A 0 0, A 0 2, A 1 1, A 2 0, A 2 2

Second line should print sum of A 0 1, A 1 0, A 1 2, A 2 1

## SAMPLE INPUT

1 2 3 4 5 6 7 8 9

## SAMPLE OUTPUT

25

20

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2 int main(){
3     int arr[3][3];
4     for(int i=0;i<3;i++){
5         for(int j=0;j<3;j++){
6             scanf("%d",&arr[i][j]);
7         }
8     }

```

**Answer:** (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main(){
3     int arr[3][3];
4     for(int i=0;i<3;i++){
5         for(int j=0;j<3;j++){
6             scanf("%d",&arr[i][j]);
7         }
8     }
9     int odd=0,even=0;
10
11     for(int i=0;i<3;i++){
12         for(int j=0;j<3;j++){
13             if((i+j)%2!=0) odd+=arr[i][j];
14             else even+=arr[i][j];
15         }
16     }
17     printf("%d\n%d",even,odd);
18
19 }
```

	Input
✓	1 2 3 4 5 6 7 8 9
✓	21 422 423 443 586 645 657 846

Passed all tests! ✓

**Answer:** (penalty regime: 0 %)

```
1 o.h>
2
3 [3];
4 0;i<3;i++){
5 t j=0;j<3;j++){
6   printf("%d",&arr[i][j]);
7
8
9   even=0;
10
11 0;i<3;i++){
12 t j=0;j<3;j++){
13   ((i+j)%2!=0) odd+=arr[i][j];
14   se even+=arr[i][j];
15
16
17   \n%d",even,odd);
18
19
```

	Input
✓	1 2 3 4 5 6 7 8 9
✓	21 422 423 443 586 645 657 846

Passed all tests! ✓

Question **2**

Correct

Marked out of 5.00

[Flag question](#)

Microsoft has come to hire interns from your college.  $N$  students got shortlisted out of which few were males and a few females. All the students have been assigned talent levels. Smaller the talent level, lesser is your chance to be selected. Microsoft wants to create the result list where it wants the candidates sorted according to their talent levels, but there is a catch. This time Microsoft wants to hire female candidates first and then male candidates.

The task is to create a list where first all-female candidates are sorted in a descending order and then male candidates are sorted in a descending order.

**Input Format**

The first line contains an integer  $N$  denoting the number of students. Next,  $N$  lines contain two space-separated integers,  $a_i$  and  $b_i$ .

The first integer,  $a_i$  will be either 1 (for a male candidate) or 0 (for female candidate).

The second integer,  $b_i$  will be the candidate's talent level.

Constraints

$$1 \leq N \leq 10^5$$

$$0 \leq a_i \leq 1$$

$$1 \leq b_i \leq 10^9$$

Output Format

Output space-separated integers, which first contains the talent levels of all female candidates sorted in descending order and then the talent levels of male candidates in descending order.

SAMPLE INPUT

5

0 3

1 6

0 2

0 7

**Answer:** (penalty regime: 0 %)

```
1  #include <stdio.h>
2
3  struct data
4  {
5      int gen;
6      int tal;
7
8  };
9  int main(){
10     int n;
11     scanf("%d",&n);
12
13     struct data a[n];
14     for(int i=0;i<n;i++){
15         scanf("%d %d",&a[i].
16
17     }
18     for(int i=0;i<n-1;i++){
19         for(int j=0;j<n-i-1;
20             if(a[j].tal<a[j+
21                 struct data
22                 a[j]=a[j+1];
23                 a[j+1]=temp;
24             }
25         }
26     }
27     for(int i=0;i<n;i++){
28         if(a[i].gen==0){
29             printf("%d ",a[i
30         }
31     }
32     for(int i=0;i<n;i++){
33         if(a[i].gen == 1){
34             printf("%d ",a[i
35         }
36     }
37
38 }
```



```
4
5
6
7
8
9
10
11 &n);
12
13 a[n];
14 ;i<n;i++){
15 %d %d",&a[i].gen,&a[i].tal);
16
17
18 ;i<n-1;i++){
19 j=0;j<n-i-1;j++){
20 a[j].tal<a[j+1].tal){
21 struct data temp =a[j];
22 a[j]=a[j+1];
23 a[j+1]=temp;
24
25
26
27 ;i<n;i++){
28 .gen==0){
29 ntff("%d ",a[i].tal);
30
31
32 ;i<n;i++){
33 .gen == 1){
34 ntff("%d ",a[i].tal);
35
36
37 ...
38
```



	Input	Expected
✓	5 0 3 1 6 0 2 0 7 1 15	7 3 2 15 6
✓	6 0 1 0 26 0 39 0 37 0 7 0 13	39 37 26 13 7 1
✓	12 1 12 1 14 1 18 1 1 1 2 1 3 1 5 1 8 1 9 1 10 0 29 0 31	31 29 18 14 12 10 9 8 5
✓	12 0 12 1 12 0 12 1 12 0 12 0 12 1 12	12 12 12 12 12 12 12 12



	0 13	
✓	12	31 29 18 14 12 10 9 8 5
	1 12	
	1 14	
	1 18	
	1 1	
	1 2	
	1 3	
	1 5	
	1 8	
	1 9	
	1 10	
	0 29	
	0 31	
✓	12	12 12 12 12 12 12 12 12
	0 12	
	1 12	
	0 12	
	1 12	
	0 12	
	0 12	
	1 12	
	0 12	
	1 12	
	1 12	
	0 12	
	1 12	

Passed all tests! ✓

## Question 3

Correct

Marked out of 1.00

 [Flag question](#)

Shyam Lal, a wealthy landlord from the state of Rajasthan, being an old fellow and tired of doing hard work, decided to sell all his farmland and to live rest of his life with that money. No other farmer is rich enough to buy all his land so he decided to partition the land into rectangular plots of different sizes with different cost per unit area. So, he sold these plots to the farmers but made a mistake. Being illiterate, he made partitions that could be overlapping. When the farmers came to know about it, they ran to him for compensation of extra money they paid to him. So, he decided to return all the money to the farmers of that land which was overlapping with other farmer's land to settle down the conflict. All the portion of conflicted land will be taken back by the landlord.

To decide the total compensation, he has to calculate the total amount of money to return back to farmers with the same cost they had purchased from him. Suppose, Shyam Lal has a total land area of **1000 x 1000** equal square blocks where each block

find the total amount of money, he has to return to the farmers. Help Shyam Lal to accomplish this task.

### Input Format:

The first line of the input contains an integer  **$N$** , denoting the total number of land pieces he had distributed. Next  **$N$**  line contains the **5** space separated integers  **$(X1, Y1), (X2, Y2)$**  to represent a rectangular piece of land, and cost per unit area  **$C$** .

**$(X1, Y1)$**  and  **$(X2, Y2)$**  are the locations of first and last square block on the diagonal of the rectangular region.

### Output Format:

Print the total amount he has to return to farmers to solve the conflict.

### Constraints:

$$1 \leq N \leq 100$$

$$1 \leq X1 \leq X2 \leq 1000$$

$$1 \leq Y1 \leq Y2 \leq 1000$$

$$1 \leq C \leq 1000$$


4 3 0 0 2

2 2 5 4 3

SAMPLE OUTPUT

35

Explanation



For given sample input (see given graph for reference), compensation money for different farmers is as follows:

Farmer with land area A:  $C_1 = 5 * 1 = 5$

Farmer with land area B:  $C_2 = 6 * 2 = 12$

Farmer with land area C:  $C_3 = 6 * 3 = 18$



**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2  int main(){
3      int i,j,n,x1,x2,y1,y2,t=
4      long long total=0;
5      int arr[1001][1001]={0};
6      scanf("%d",&n);
7      while(n--){
8          scanf("%d %d %d %d %
9
10         for(i=x1;i<=x2;i++){
11             for(j=y1;j<=y2;j
12                 if(arr[i][j]
13                 else if(arr[
14                 else if (arr
15             }
16         }
17     }
18
19     for(i=1;i<1001;i++){
20         for(j=1;j<1001;j++){
21             if(arr[i][j]<0){
22                 total+=arr[i
23             }
24         }
25     }
26     printf("%lld\n",(-1)*tot
27 }
```

	Input	Expected	Got
✓	2	25	25



```

3   ,x1,x2,y1,y2,t=0;
4   total=0;
5   001][1001]={0};
6   ",&n);
7   ){
8   ("%d %d %d %d %d",&x1,&y1,&x2
9
10  =x1;i<=x2;i++){
11  or(j=y1;j<=y2;j++){
12      if(arr[i][j]==0)arr[i][j]+
13      else if(arr[i][j]>0) arr[i]
14      else if (arr[i][j]<0) arr[i]
15
16
17
18
19  <1001;i++){
20  =1;j<1001;j++){
21  f(arr[i][j]<0){
22      total+=arr[i][j];
23
24
25
26  lld\n",(-1)*total);
27

```

	Input	Expected	Got
✓	3 1 4 4 6 1 4 3 6 6 2 2 2 5 4 3	35	35
✓	1 48 12 49 27 8	0	0
✓	3 88 34 99 76 44 22 15 24 122 24	10500	1050



```
11  
12 ]+=t;  
13 [i][j] = (-1)*(arr[i][j]+t);  
14 r[i][j]-=t;  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27
```

	Input	Expected	Got
✓	3 1 4 4 6 1 4 3 6 6 2 2 2 5 4 3	35	35
✓	1 48 12 49 27 8	0	0
✓	3 88 34 99 76 44 82 65 94 100 81 58 16 65 66 7	10500	10500

Passed all tests! ✓