In [1]:
```
import os
import warnings
warnings.filterwarnings("ignore")

import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns

from sklearn.model_selection import train_test_split, StratifiedKFold, cross_val
from sklearn.pipeline import Pipeline
from sklearn.impute import SimpleImputer
from sklearn.preprocessing import StandardScaler
from sklearn.linear_model import LogisticRegression
from sklearn.tree import DecisionTreeClassifier
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import (
    accuracy_score, precision_score, recall_score, f1_score,
    confusion_matrix, classification_report, ConfusionMatrixDisplay
)

RANDOM_STATE = 42
sns.set_theme(style="whitegrid")
pd.set_option("display.max_columns", None)
print("Library berhasil diimpor.")
```

```
Library berhasil diimpor.
```

In [2]:
```
file_path = "original.csv"

if not os.path.exists(file_path):
    try:
        from google.colab import files
        uploaded = files.upload()
        file_path = next(iter(uploaded))
    except Exception:
        raise FileNotFoundError(
            "File original.csv tidak ditemukan. Letakkan original.csv satu folde
            "dengan notebook, lalu jalankan ulang sel ini."
        )

df_raw = pd.read_csv(file_path)
print("Dataset berhasil dibaca.")
print("Dimensi awal:", df_raw.shape)
display(df_raw.head())
```

```
Dataset berhasil dibaca.
Dimensi awal: (87, 22)
```

	Gender	Age	POLAR4 Quintile	POLAR3 Quintile	Adult HE 2001 Quintile	Adult HE 2011 Quintile	TUNDRA MSOA Quintile	TUNDRA LSOA Quintile	Gaps GCSE Quintile	Eth Qu
0	0.0	38.0	5.0	5.0	4.0	5.0	4.0	4.0	5.0	
1	0.0	22.0	4.0	2.0	1.0	3.0	4.0	4.0	4.0	
2	0.0	21.0	4.0	5.0	4.0	5.0	4.0	4.0	5.0	
3	0.0	25.0	5.0	4.0	3.0	4.0	3.0	3.0	5.0	
4	0.0	20.0	5.0	4.0	3.0	4.0	3.0	3.0	4.0	

In [3]:
```
print("Informasi tipe data:")
df_raw.info()

print("\\nJumlah nilai hilang per kolom:")
display(df_raw.isna().sum().to_frame("Jumlah Missing Value"))

print("\\nStatistik deskriptif:")
display(df_raw.describe().T)
```

```
Informasi tipe data:
<class 'pandas.DataFrame'>
RangeIndex: 87 entries, 0 to 86
Data columns (total 22 columns):
 #   Column                                Non-Null Count  Dtype  
---  ------                                --------------  -----  
 0   Gender                                80 non-null     float64
 1   Age                                   80 non-null     float64
 2   POLAR4 Quintile                       80 non-null     float64
 3   POLAR3 Quintile                       80 non-null     float64
 4   Adult HE 2001 Quintile                80 non-null     float64
 5   Adult HE 2011 Quintile                80 non-null     float64
 6   TUNDRA MSOA Quintile                  80 non-null     float64
 7   TUNDRA LSOA Quintile                  80 non-null     float64
 8   Gaps GCSE Quintile                    80 non-null     float64
 9   Gaps GCSE Ethnicity Quintile          80 non-null     float64
 10  Uni Connect target ward               80 non-null     float64
 11  attending from home?                  80 non-null     float64
 12  distance to university (km)           80 non-null     float64
 13  Count of Module Area Logins           80 non-null     float64
 14  Total Hours in Module Area            80 non-null     float64
 15  % of Average Hours in Module Area     80 non-null     float64
 16  # of presence                         80 non-null     float64
 17  # of Absence                          78 non-null     float64
 18  Percent Attended                      80 non-null     float64
 19  label (fail=1, pass=0)                80 non-null     float64
 20  Unnamed: 20                           0 non-null      float64
 21  Unnamed: 21                           0 non-null      float64
dtypes: float64(22)
memory usage: 15.1 KB
\nJumlah nilai hilang per kolom:
```

	Jumlah Missing Value
Gender	7
Age	7
POLAR4 Quintile	7
POLAR3 Quintile	7
Adult HE 2001 Quintile	7
Adult HE 2011 Quintile	7
TUNDRA MSOA Quintile	7
TUNDRA LSOA Quintile	7
Gaps GCSE Quintile	7
Gaps GCSE Ethnicity Quintile	7
Uni Connect target ward	7
attending from home?	7
distance to university (km)	7
Count of Module Area Logins	7
Total Hours in Module Area	7
% of Average Hours in Module Area	7
# of presence	7
# of Absence	9
Percent Attended	7
label (fail=1, pass=0)	7
Unnamed: 20	87
Unnamed: 21	87

```
\nStatistik deskriptif:
```

	count	mean	std	min	25%	50%	75%	
Gender	80.0	0.125000	0.332805	0.000000	0.000000	0.000000	0.000000	1
Age	80.0	22.212500	4.451408	19.000000	20.000000	21.000000	22.000000	44
POLAR4 Quintile	80.0	3.575000	1.438837	1.000000	2.000000	4.000000	5.000000	5
POLAR3 Quintile	80.0	3.287500	1.433715	1.000000	2.000000	4.000000	4.250000	5
Adult HE 2001 Quintile	80.0	2.712500	1.203305	1.000000	2.000000	3.000000	4.000000	5
Adult HE 2011 Quintile	80.0	3.275000	1.395971	0.000000	2.000000	4.000000	4.000000	5
TUNDRA MSOA Quintile	80.0	2.850000	1.293606	0.000000	2.000000	3.000000	4.000000	5
TUNDRA LSOA Quintile	80.0	2.850000	1.293606	0.000000	2.000000	3.000000	4.000000	5
Gaps GCSE Quintile	80.0	3.650000	1.543463	0.000000	3.000000	4.000000	5.000000	5
Gaps GCSE Ethnicity Quintile	80.0	4.112500	1.449520	0.000000	4.000000	5.000000	5.000000	5
Uni Connect target ward	80.0	0.100000	0.301893	0.000000	0.000000	0.000000	0.000000	1
attending from home?	80.0	0.662500	0.475840	0.000000	0.000000	1.000000	1.000000	1
distance to university (km)	80.0	29.241366	49.616500	0.000000	3.259523	15.711609	32.451973	317
Count of Module Area Logins	80.0	50.175000	38.903898	1.000000	30.750000	44.500000	62.000000	335
Total Hours in Module Area	80.0	18.626000	20.910481	0.030000	8.550000	14.805000	22.237500	175
% of Average	80.0	1.073753	0.846172	0.002513	0.581920	0.862037	1.286354	5

	count	mean	std	min	25%	50%	75%	
Hours in Module Area								
# of presence	80.0	8.700000	3.016411	0.000000	7.000000	9.000000	11.000000	13
# of Absence	78.0	2.935897	2.870991	0.000000	0.250000	2.000000	4.750000	12
Percent Attended	80.0	74.375042	24.750711	0.000000	58.333333	83.333333	100.000000	100
label (fail=1, pass=0)	80.0	0.150000	0.359324	0.000000	0.000000	0.000000	0.000000	1
Unnamed: 20	0.0	NaN	NaN	NaN	NaN	NaN	NaN	
Unnamed: 21	0.0	NaN	NaN	NaN	NaN	NaN	NaN	

In [4]:
```
df = df_raw.copy()
df.columns = df.columns.astype(str).str.strip()
```

In [5]:
```
df = df.dropna(axis=0, how="all")
df = df.dropna(axis=1, how="all")

target_col = "label (fail=1, pass=0)"
if target_col not in df.columns:
    raise KeyError(f"Kolom target '{target_col}' tidak ditemukan. Kolom tersedia
```

In [6]:
```
df = df.dropna(subset=[target_col]).copy()
df[target_col] = df[target_col].astype(int)


print("Dimensi setelah pembersihan awal:", df.shape)
print("Jumlah duplikat:", df.duplicated().sum())
print("\\nDistribusi label:")
display(df[target_col].value_counts().rename(index={0: "Lulus (0)", 1: "Gagal (1

label_pct = df[target_col].value_counts(normalize=True).sort_index() * 100
plt.figure(figsize=(6, 4))
counts = df[target_col].map({0: "Lulus (0)", 1: "Gagal (1)"}).value_counts().rei
ax = counts.plot(kind="bar", rot=0)
ax.set_title("Distribusi Label Mahasiswa")
ax.set_xlabel("Status mahasiswa")
ax.set_ylabel("Jumlah")
for p in ax.patches:
    ax.annotate(f"{int(p.get_height())}", (p.get_x() + p.get_width()/2, p.get_he
                ha="center", va="bottom")
plt.show()

print("Persentase kelas:")
display(label_pct.rename(index={0: "Lulus (0)", 1: "Gagal (1)"}).to_frame("Perse
print("Interpretasi: kelas tidak seimbang karena jumlah mahasiswa lulus jauh leb
```

```
Dimensi setelah pembersihan awal: (80, 20)
Jumlah duplikat: 0
\nDistribusi label:
```

label (fail=1, pass=0)	Jumlah
Lulus (0)	68
Gagal (1)	12




```
Persentase kelas:
```

label (fail=1, pass=0)	Persentase (%)
Lulus (0)	85.0
Gagal (1)	15.0

```
Interpretasi: kelas tidak seimbang karena jumlah mahasiswa lulus jauh lebih banyak daripada mahasiswa gagal.
```

eda

In [8]:
```
print("Dimensi data:", df.shape)
print("Jumlah baris duplikat:", df.duplicated().sum())
print("Missing value per kolom:")
display(df.isna().sum().to_frame("Missing"))
```


```
Dimensi data: (80, 20)
Jumlah baris duplikat: 0
Missing value per kolom:
```

	Missing
Gender	0
Age	0
POLAR4 Quintile	0
POLAR3 Quintile	0
Adult HE 2001 Quintile	0
Adult HE 2011 Quintile	0
TUNDRA MSOA Quintile	0
TUNDRA LSOA Quintile	0
Gaps GCSE Quintile	0
Gaps GCSE Ethnicity Quintile	0
Uni Connect target ward	0
attending from home?	0
distance to university (km)	0
Count of Module Area Logins	0
Total Hours in Module Area	0
% of Average Hours in Module Area	0
# of presence	0
# of Absence	2
Percent Attended	0
label (fail=1, pass=0)	0

In [9]:
```
df = df.drop_duplicates().copy()
```


In [10]:
```
numeric_cols = df.select_dtypes(include=np.number).columns.tolist()
feature_cols_all = [c for c in numeric_cols if c != target_col]
```


In [11]:
```
hist_cols = [
    "Age", "distance to university (km)", "Count of Module Area Logins",
    "Total Hours in Module Area", "Percent Attended"
]
hist_cols = [c for c in hist_cols if c in df.columns]
df[hist_cols].hist(figsize=(12, 8), bins=15, edgecolor="black")
plt.suptitle("Histogram Fitur Numerik", y=1.02)
plt.tight_layout()
plt.show()
```





In [12]:
```
box_cols = [
    "Percent Attended", "# of presence", "# of Absence",
    "Count of Module Area Logins", "Total Hours in Module Area"
]
box_cols = [c for c in box_cols if c in df.columns]


fig, axes = plt.subplots(len(box_cols), 1, figsize=(9, 3 * len(box_cols)))
if len(box_cols) == 1:
    axes = [axes]
for ax, col in zip(axes, box_cols):
    sns.boxplot(data=df, x=target_col, y=col, ax=ax)
    ax.set_title(f"{col} berdasarkan label (0=Lulus, 1=Gagal)")
    ax.set_xlabel("Label")
plt.tight_layout()
plt.show()
```


Percent Attended berdasarkan label (0=Lulus, 1=Gagal)
Percent Attended
100
80
60
40
20
0
0
1
Label


of presence berdasarkan label (0=Lulus, 1=Gagal)
of presence
12.5
10.0
7.5
5.0
2.5
0.0
0
1
Label


of Absence berdasarkan label (0=Lulus, 1=Gagal)
of Absence
12.5
10.0
7.5
5.0
2.5
0.0
0
1
Label



Count of Module Area Logins berdasarkan label (0=Lulus, 1=Gagal)
Count of Module Area Logins
300
200
100
0
0
1
Label


Total Hours in Module Area berdasarkan label (0=Lulus, 1=Gagal)
Total Hours in Module Area
150
100
50
0
0
1
Label


In [13]:
```
engagement_cols = [
    "Percent Attended", "# of presence", "# of Absence",
    "Count of Module Area Logins", "Total Hours in Module Area",
    "% of Average Hours in Module Area"
]
engagement_cols = [c for c in engagement_cols if c in df.columns]
mean_by_label = df.groupby(target_col)[engagement_cols].mean().T
display(mean_by_label.rename(columns={0: "Lulus (0)", 1: "Gagal (1)"}))

mean_by_label.plot(kind="bar", figsize=(12, 5))
plt.title("Rata-rata Fitur Keterlibatan: Lulus vs Gagal")
plt.ylabel("Rata-rata")
plt.xlabel("Fitur")
plt.xticks(rotation=35, ha="right")
plt.tight_layout()
plt.show()
```

label (fail=1, pass=0)	Lulus (0)	Gagal (1)
Percent Attended	78.553971	50.694444
# of presence	9.161765	6.083333
# of Absence	2.424242	5.750000
Count of Module Area Logins	54.014706	28.416667
Total Hours in Module Area	20.320588	9.023333
% of Average Hours in Module Area	1.186948	0.432312



In [14]:
```
plt.figure(figsize=(14, 10))
corr = df.select_dtypes(include=np.number).corr()
sns.heatmap(corr, cmap="coolwarm", center=0, annot=False, linewidths=0.3)
plt.title("Heatmap Korelasi Antarvariabel")
plt.tight_layout()
plt.show()
```



In [15]:
```
continuous_cols = [
    "Age", "distance to university (km)", "Count of Module Area Logins",
    "Total Hours in Module Area", "% of Average Hours in Module Area",
    "# of presence", "# of Absence", "Percent Attended"
]
continuous_cols = [c for c in continuous_cols if c in df.columns]

outlier_summary = []
for col in continuous_cols:
    series = df[col].dropna()
    q1, q3 = series.quantile([0.25, 0.75])
    iqr = q3 - q1
    lower = q1 - 1.5 * iqr
    upper = q3 + 1.5 * iqr
    count = ((series < lower) | (series > upper)).sum()
    outlier_summary.append([col, lower, upper, int(count)])

outlier_df = pd.DataFrame(outlier_summary, columns=["Fitur", "Batas bawah IQR",
display(outlier_df)
```

	Fitur	Batas bawah IQR	Batas atas IQR	Jumlah outlier
0	Age	17.000000	25.000000	6
1	distance to university (km)	-40.529151	76.240647	7
2	Count of Module Area Logins	-16.125000	108.875000	2
3	Total Hours in Module Area	-11.981250	42.768750	3
4	% of Average Hours in Module Area	-0.474730	2.343004	4
5	# of presence	1.000000	17.000000	2
6	# of Absence	-6.500000	11.500000	2
7	Percent Attended	-4.166667	162.500000	0

In [16]:
```
quintile_cols = [c for c in df.columns if "Quintile" in c]
zero_quintiles = {c: int((df[c] == 0).sum()) for c in quintile_cols}
print("Jumlah nilai 0 pada fitur kuintil:")
display(pd.Series(zero_quintiles, name="Jumlah nilai 0").to_frame())

print("Keputusan: nilai outlier numerik dipertahankan karena belum terbukti sala
print("Nilai 0 pada kolom kuintil diperlakukan sebagai nilai tidak tersedia (NaN
```

```
Jumlah nilai 0 pada fitur kuintil:
```

	Jumlah nilai 0
POLAR4 Quintile	0
POLAR3 Quintile	0
Adult HE 2001 Quintile	0
Adult HE 2011 Quintile	2
TUNDRA MSOA Quintile	2
TUNDRA LSOA Quintile	2
Gaps GCSE Quintile	4
Gaps GCSE Ethnicity Quintile	4

```
Keputusan: nilai outlier numerik dipertahankan karena belum terbukti salah.
Nilai 0 pada kolom kuintil diperlakukan sebagai nilai tidak tersedia (NaN), karen
a dokumen tugas menyatakan maknanya tidak dijelaskan dan mungkin menandakan data
tidak tersedia.
```

persiapan data

In [17]:
```
model_df = df.copy()
```

In [18]:
```
quintile_cols = [c for c in model_df.columns if "Quintile" in c]
for col in quintile_cols:
    model_df.loc[model_df[col] == 0, col] = np.nan
```

In [19]:
```
redundant_cols = ["TUNDRA LSOA Quintile", "Percent Attended"]
drop_cols = [c for c in redundant_cols if c in model_df.columns]
model_df = model_df.drop(columns=drop_cols)

X = model_df.drop(columns=[target_col])
y = model_df[target_col].astype(int)
```

In [20]:
```
X = X.apply(pd.to_numeric, errors="coerce")

print("Fitur yang digunakan:", X.columns.tolist())
print("Jumlah fitur:", X.shape[1])
print("Ukuran X:", X.shape, "| Ukuran y:", y.shape)

X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.20, random_state=RANDOM_STATE, stratify=y
)

print("Data latih:", X_train.shape, "| Data uji:", X_test.shape)
print("\\nDistribusi label data latih:")
display(y_train.value_counts().rename(index={0: "Lulus", 1: "Gagal"}).to_frame("
print("\\nDistribusi label data uji:")
display(y_test.value_counts().rename(index={0: "Lulus", 1: "Gagal"}).to_frame("J
```

```
Fitur yang digunakan: ['Gender', 'Age', 'POLAR4 Quintile', 'POLAR3 Quintile', 'Ad
ult HE 2001 Quintile', 'Adult HE 2011 Quintile', 'TUNDRA MSOA Quintile', 'Gaps GC
SE Quintile', 'Gaps GCSE Ethnicity Quintile', 'Uni Connect target ward', 'attendi
ng from home?', 'distance to university (km)', 'Count of Module Area Logins', 'To
tal Hours in Module Area', '% of Average Hours in Module Area', '# of presence',
'# of Absence']
Jumlah fitur: 17
Ukuran X: (80, 17) | Ukuran y: (80,)
Data latih: (64, 17) | Data uji: (16, 17)
\nDistribusi label data latih:
```

label (fail=1, pass=0)	Jumlah
Lulus	54
Gagal	10

```
\nDistribusi label data uji:
```

label (fail=1, pass=0)	Jumlah
Lulus	14
Gagal	2

modelling

In [22]:
```
cv = StratifiedKFold(n_splits=5, shuffle=True, random_state=RANDOM_STATE)

models = {
    "Logistic Regression": Pipeline([
        ("imputer", SimpleImputer(strategy="median")),
```

```
        ("scaler", StandardScaler()),
        ("model", LogisticRegression(class_weight="balanced", max_iter=2000, ran
    ]),
    "Decision Tree": Pipeline([
        ("imputer", SimpleImputer(strategy="median")),
        ("model", DecisionTreeClassifier(class_weight="balanced", random_state=R
    ]),
    "Random Forest": Pipeline([
        ("imputer", SimpleImputer(strategy="median")),
        ("model", RandomForestClassifier(
            n_estimators=300, class_weight="balanced",
            random_state=RANDOM_STATE, max_depth=4, min_samples_leaf=2
        ))
    ])
}

cv_rows = []
for name, pipeline in models.items():
    scores = cross_validate(
        pipeline, X_train, y_train, cv=cv,
        scoring={"f1": "f1", "recall": "recall", "precision": "precision", "accu
        error_score="raise"
    )
    cv_rows.append({
        "Model": name,
        "CV F1 gagal (rata-rata)": scores["test_f1"].mean(),
        "CV Recall gagal (rata-rata)": scores["test_recall"].mean(),
        "CV Precision gagal (rata-rata)": scores["test_precision"].mean(),
        "CV Accuracy (rata-rata)": scores["test_accuracy"].mean()
    })

cv_results = pd.DataFrame(cv_rows).sort_values("CV F1 gagal (rata-rata)", ascend
display(cv_results)
```

	Model	CV F1 gagal (rata-rata)	CV Recall gagal (rata-rata)	CV Precision gagal (rata-rata)	CV Accuracy (rata-rata)
0	Logistic Regression	0.493333	0.6	0.483333	0.798718
1	Decision Tree	0.413333	0.5	0.416667	0.798718
2	Random Forest	0.360000	0.4	0.383333	0.767949

In [23]:

```
rf_pipeline = Pipeline([
    ("imputer", SimpleImputer(strategy="median")),
    ("model", RandomForestClassifier(class_weight="balanced", random_state=RANDO
])

param_grid = {
    "model__n_estimators": [200, 300],
    "model__max_depth": [None, 3, 5],
    "model__min_samples_leaf": [1, 2, 3]
}

grid_search = GridSearchCV(
    rf_pipeline, param_grid=param_grid, scoring="f1",
    cv=cv, n_jobs=-1, refit=True
```

```
)
grid_search.fit(X_train, y_train)

print("Parameter terbaik:", grid_search.best_params_)
print("F1 CV terbaik untuk kelas gagal:", round(grid_search.best_score_, 4))
```

```
Parameter terbaik: {'model__max_depth': None, 'model__min_samples_leaf': 1, 'mode
l__n_estimators': 200}
F1 CV terbaik untuk kelas gagal: 0.4133
```

In [24]:
```
fitted_models = {}
for name, pipeline in models.items():
    pipeline.fit(X_train, y_train)
    fitted_models[name] = pipeline
fitted_models["Random Forest Tuned"] = grid_search.best_estimator_

print("Semua model berhasil dilatih.")
```

```
Semua model berhasil dilatih.
```

evaluasi model

In [25]:
```
evaluation_rows = []
for name, model in fitted_models.items():
    y_pred = model.predict(X_test)
    evaluation_rows.append({
        "Model": name,
        "Accuracy": accuracy_score(y_test, y_pred),
        "Precision gagal": precision_score(y_test, y_pred, zero_division=0),
        "Recall gagal": recall_score(y_test, y_pred, zero_division=0),
        "F1 gagal": f1_score(y_test, y_pred, zero_division=0)
    })

evaluation = pd.DataFrame(evaluation_rows).sort_values("F1 gagal", ascending=Fal
display(evaluation)

best_model_name = evaluation.loc[0, "Model"]
best_model = fitted_models[best_model_name]
print("Model terbaik berdasarkan F1 kelas gagal pada data uji:", best_model_name
```

	Model	Accuracy	Precision gagal	Recall gagal	F1 gagal
0	Random Forest Tuned	0.9375	1.00	0.5	0.666667
1	Random Forest	0.9375	1.00	0.5	0.666667
2	Logistic Regression	0.7500	0.25	0.5	0.333333
3	Decision Tree	0.8125	0.00	0.0	0.000000


```
Model terbaik berdasarkan F1 kelas gagal pada data uji: Random Forest Tuned
```

In [26]:
```
best_pred = best_model.predict(X_test)
cm = confusion_matrix(y_test, best_pred, labels=[0, 1])

disp = ConfusionMatrixDisplay(
    confusion_matrix=cm,
    display_labels=["Lulus (0)", "Gagal (1)"]
)
```

```
disp.plot(cmap="Blues", values_format="d")
plt.title(f"Confusion Matrix - {best_model_name}")
plt.show()

print("Classification Report:")
print(classification_report(
    y_test, best_pred, labels=[0, 1],
    target_names=["Lulus (0)", "Gagal (1)"],
    zero_division=0
))
```




```
Classification Report:
              precision    recall  f1-score   support

   Lulus (0)       0.93      1.00      0.97        14
   Gagal (1)       1.00      0.50      0.67         2

    accuracy                           0.94        16
   macro avg       0.97      0.75      0.82        16
weighted avg       0.94      0.94      0.93        16
```

In [27]:


```
final_estimator = best_model.named_steps["model"]

if hasattr(final_estimator, "feature_importances_"):
    importance = pd.Series(final_estimator.feature_importances_, index=X.columns
    importance_name = "Feature Importance"
elif hasattr(final_estimator, "coef_"):
    importance = pd.Series(np.abs(final_estimator.coef_[0]), index=X.columns).so
    importance_name = "Nilai absolut koefisien Logistic Regression"
else:
    importance = pd.Series(dtype=float)
    importance_name = "Tidak tersedia"
```

```
if not importance.empty:
    print(importance_name)
    display(importance.to_frame("Nilai").head(10))
    importance.head(10).sort_values().plot(kind="barh", figsize=(8, 5))
    plt.title(f"10 Fitur Teratas - {best_model_name}")
    plt.xlabel(importance_name)
    plt.tight_layout()
    plt.show()
else:
    print("Model ini tidak menyediakan feature importance atau koefisien.")
```

```
Feature Importance
```

	Nilai
% of Average Hours in Module Area	0.258540
Count of Module Area Logins	0.136323
Total Hours in Module Area	0.130199
# of Absence	0.082942
# of presence	0.065965
distance to university (km)	0.062835
POLAR4 Quintile	0.049676
Adult HE 2011 Quintile	0.037699
Age	0.037104
POLAR3 Quintile	0.035377



Tes prediksi dengan data random

In [28]:
```
rng = np.random.default_rng(RANDOM_STATE)
random_students = {}
```

In [29]:
```
discrete_cols = [
    "Gender", "POLAR4 Quintile", "POLAR3 Quintile",
    "Adult HE 2001 Quintile", "Adult HE 2011 Quintile",
    "TUNDRA MSOA Quintile", "Gaps GCSE Quintile",
    "Gaps GCSE Ethnicity Quintile", "Uni Connect target ward",
    "attending from home?"
]
discrete_cols = [c for c in discrete_cols if c in X.columns]

for col in X.columns:
    values = X[col].dropna()
    if values.empty:
        random_students[col] = np.zeros(5)
    elif col in discrete_cols:
        choices = values.unique()
        random_students[col] = rng.choice(choices, size=5, replace=True)
    else:
        low, high = values.min(), values.max()
        random_students[col] = rng.uniform(low, high, size=5)

new_students = pd.DataFrame(random_students, columns=X.columns)
display(new_students.round(2))
```

	Gender	Age	POLAR4 Quintile	POLAR3 Quintile	Adult HE 2001 Quintile	Adult HE 2011 Quintile	TUNDRA MSOA Quintile	Gaps GCSE Quintile	Gaps GCSE Ethnicity Quintile	Co
0	0.0	36.43	2.0	4.0	2.0	4.0	4.0	5.0	2.0	
1	1.0	21.35	3.0	2.0	3.0	3.0	5.0	1.0	1.0	
2	1.0	43.39	5.0	5.0	5.0	5.0	5.0	1.0	2.0	
3	0.0	38.03	2.0	1.0	3.0	4.0	3.0	4.0	3.0	
4	0.0	38.65	3.0	3.0	3.0	2.0	1.0	5.0	3.0	

In [30]:
```
new_predictions = best_model.predict(new_students)
new_probabilities = best_model.predict_proba(new_students)
```

In [32]:
```
class_order = list(best_model.classes_)
fail_index = class_order.index(1)
fail_probability = new_probabilities[:, fail_index]

prediction_result = new_students.copy()
prediction_result["Prediksi label"] = new_predictions
prediction_result["Prediksi status"] = np.where(new_predictions == 1, "GAGAL", "
prediction_result["Probabilitas gagal (%)"] = (fail_probability * 100).round(2)
prediction_result["Probabilitas lulus (%)"] = ((1 - fail_probability) * 100).rou

display(prediction_result.round(2))
```

	Gender	Age	POLAR4 Quintile	POLAR3 Quintile	Adult HE 2001 Quintile	Adult HE 2011 Quintile	TUNDRA MSOA Quintile	Gaps GCSE Quintile	Gaps GCSE Ethnicity Quintile	Co t
0	0.0	36.43	2.0	4.0	2.0	4.0	4.0	5.0	2.0	
1	1.0	21.35	3.0	2.0	3.0	3.0	5.0	1.0	1.0	
2	1.0	43.39	5.0	5.0	5.0	5.0	5.0	1.0	2.0	
3	0.0	38.03	2.0	1.0	3.0	4.0	3.0	4.0	3.0	
4	0.0	38.65	3.0	3.0	3.0	2.0	1.0	5.0	3.0	

In [ ]: