

670 50050 วิชาเน็ต

| Subnet Value | Bit Value |    |    |    |   |   |   |   |
|--------------|-----------|----|----|----|---|---|---|---|
|              | 128       | 64 | 32 | 16 | 8 | 4 | 2 | 1 |
| 255          | 1         | 1  | 1  | 1  | 1 | 1 | 1 | 1 |
| 254          | 1         | 1  | 1  | 1  | 1 | 1 | 1 | 0 |
| 252          | 1         | 1  | 1  | 1  | 1 | 1 | 0 | 0 |
| 248          | 1         | 1  | 1  | 1  | 1 | 0 | 0 | 0 |
| 240          | 1         | 1  | 1  | 1  | 0 | 0 | 0 | 0 |
| 224          | 1         | 1  | 1  | 0  | 0 | 0 | 0 | 0 |
| 192          | 1         | 1  | 0  | 0  | 0 | 0 | 0 | 0 |
| 128          | 1         | 0  | 0  | 0  | 0 | 0 | 0 | 0 |
| 0            | 0         | 0  | 0  | 0  | 0 | 0 | 0 | 0 |

123. 168 .050 .2

```

00110010 . 00000010
11111111 . 00000000
-----
00110010 . 00000000

```

1. Network Address : 123 . 168 . 50 . 0

2. Broadcast Address : 123 . 168 . 50 . 255

ใช้ 192 default gateway, board cat

3. set จำนวน host :  $2^{32-n} = 2^8 = 256 - 11 = 245$

4. default gateway คือ : 123 . 168 . 50 . 1

