```
/** */ package shelley.irish.purchaseOrder.model.purchaseOrder;
import java.util.Date;
import org.eclipse.emf.ecore.EObject;
/** * * A representation of the model object 'Item'. *
   • The following features are supported:
    \bullet \ \{@link\ shelley.irish.purchaseOrder.model.purchaseOrder.Item\#getProductName
     Product Name}
   • {@link shelley.irish.purchaseOrder.model.purchaseOrder.Item#getQuantity
     Quantity}
     {@link shelley.irish.purchaseOrder.model.purchaseOrder.Item#getUSPrice
     US Price}
    \bullet \ \{@ link \ shelley. irish. purchase Order. model. purchase Order. Item \#get Comment
     Comment }
   • {@link shelley.irish.purchaseOrder.model.purchaseOrder.Item#getShipDate
     Ship Date
   \bullet \  \  \{@link\ shelley.irish.purchaseOrder.model.purchaseOrder.Item\#getPartNum
     Part Num}
     @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getItem()
     @model
     @generated */ public interface Item extends EObject { /**
        - Returns the value of the 'Product Name' attribute.
        - If the meaning of the 'Product Name' attribute isn't clear,
        - there really should be more of a description here...
        - @return the value of the 'Product Name' attribute.
        — @see #setProductName(String)
```

```
— @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getItem_ProductNam
- @model
— @generated */ String getProductName();
- Sets the value of the '{@link shelley.irish.purchaseOrder.model.purchaseOrder.Item#getProductName
  Product Name}' attribute.
- @param value the new value of the 'Product Name' attribute.
- @see #getProductName()

    — @generated */ void setProductName(String value);

- Returns the value of the 'Quantity' attribute.
- If the meaning of the 'Quantity' attribute isn't clear,
- there really should be more of a description here...
- @return the value of the 'Quantity' attribute.
— @see #setQuantity(int)
— @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getItem_Quantity()
  @generated */ int getQuantity();
- Sets the value of the '{@link shelley.irish.purchaseOrder.model.purchaseOrder.Item#getQuantity
  Quantity}' attribute.
- @param value the new value of the 'Quantity' attribute.
– @see #getQuantity()
```

```
— @generated */ void setQuantity(int value);
- Returns the value of the 'US Price' attribute.
- If the meaning of the 'US Price' attribute isn't clear,
- there really should be more of a description here...
- @return the value of the 'US Price' attribute.
— @see #setUSPrice(int)
— @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getItem_USPrice()
- @model
— @generated */ int getUSPrice();

    Sets the value of the '{@link shelley.irish.purchaseOrder.model.purchaseOrder.Item#getUSPrice

  US Price}' attribute.

    — @param value the new value of the 'US Price' attribute.

– @see #getUSPrice()

    — @generated */ void setUSPrice(int value);

- Returns the value of the 'Comment' attribute.
- If the meaning of the 'Comment' attribute isn't clear,
- there really should be more of a description here...
- @return the value of the 'Comment' attribute.
```

```
— @see #setComment(String)
- @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getItem Comment()
- @model
— @generated */ String getComment();
      Sets the value of the `\{@link shelley.irish.purchase Order.model.purchase Order.Item \#get Comment the context of the context
       Comment}' attribute.
      @param value the new value of the 'Comment' attribute.
- @see #getComment()

    — @generated */ void setComment(String value);

- Returns the value of the 'Ship Date' attribute.
- If the meaning of the 'Ship Date' attribute isn't clear,
- there really should be more of a description here...
      @return the value of the 'Ship Date' attribute.
      @see #setShipDate(Date)
      @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage\#getItem\_ShipDate()
      @model dataType="shelley.irish.purchaseOrder.model.purchaseOrder.Date"
      @generated */ Date getShipDate();

    Sets the value of the '{@link shelley.irish.purchaseOrder.model.purchaseOrder.Item#getShipDate

      Ship Date}' attribute.
```

- @param value the new value of the 'Ship Date' attribute.

```
- @see #getShipDate()

    — @generated */ void setShipDate(Date value);

                             - Returns the value of the 'Part Num' attribute.
                             - If the meaning of the 'Part Num' attribute isn't clear,
                             - there really should be more of a description here...

    — @return the value of the 'Part Num' attribute.

                             — @see #setPartNum(String)
                             - @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getItem_PartNum()
                             - @model dataType="shelley.irish.purchaseOrder.model.purchaseOrder.SKU"
                             — @generated */ String getPartNum();
                             - \ Sets\ the\ value\ of\ the\ `\{@link\ shelley.irish.purchaseOrder.model.purchaseOrder.Item\#getPartNumples and the `properties and the properties and the properties are also become a supplementation of the properties and the properties are also become a supplementation of th
                                     Part Num}' attribute.
                             - @param value the new value of the 'Part Num' attribute.
                             - @see #getPartNum()

    — @generated */ void setPartNum(String value);

} // Item
```