

```

/** */ package shelley.irish.purchaseOrder.model.purchaseOrder;
import org.eclipse.emf.ecore.EObject;
/** * * A representation of the model object 'US Address'. *
    • The following features are supported:
    •
    •
    • {@link shelley.irish.purchaseOrder.model.purchaseOrder.USAddress#getName
      Name}
    • {@link shelley.irish.purchaseOrder.model.purchaseOrder.USAddress#getStreet
      Street}
    • {@link shelley.irish.purchaseOrder.model.purchaseOrder.USAddress#getCity
      City}
    • {@link shelley.irish.purchaseOrder.model.purchaseOrder.USAddress#getState
      State}
    • {@link shelley.irish.purchaseOrder.model.purchaseOrder.USAddress#getZip
      Zip}
    • {@link shelley.irish.purchaseOrder.model.purchaseOrder.USAddress#getCountry
      Country}
    •
    •
    • @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getUSAddress()
    • @model
    • @generated */ public interface USAddress extends EObject { /**
      – Returns the value of the 'Name' attribute.
      –
      –
      – If the meaning of the 'Name' attribute isn't clear,
      – there really should be more of a description here...
      –
      –
      – @return the value of the 'Name' attribute.
      – @see #setName(String)
      – @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getUSAddress_Name()

```

```

    - @model
    - @generated */ String getName();
/**
    - Sets the value of the '{@link shelley.irish.purchaseOrder.model.purchaseOrder.USAddress#getName
      Name}' attribute.
    -
    -
    - @param value the new value of the 'Name' attribute.
    - @see #getName()
    - @generated */ void setName(String value);
/**
    - Returns the value of the 'Street' attribute.
    -
    -
    - If the meaning of the 'Street' attribute isn't clear,
    - there really should be more of a description here...
    -
    -
    - @return the value of the 'Street' attribute.
    - @see #setStreet(String)
    - @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getUSAddress_Street
    - @model
    - @generated */ String getStreet();
/**
    - Sets the value of the '{@link shelley.irish.purchaseOrder.model.purchaseOrder.USAddress#getStreet
      Street}' attribute.
    -
    -
    - @param value the new value of the 'Street' attribute.
    - @see #getStreet()
    - @generated */ void setStreet(String value);

```

```

/**
    - Returns the value of the ‘City’ attribute.
    -
    -
    - If the meaning of the ‘City’ attribute isn’t clear,
    - there really should be more of a description here...
    -
    -
    - @return the value of the ‘City’ attribute.
    - @see #setCity(String)
    - @see shelly.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getUSAddress__City()
    - @model
    - @generated */ String getCity();
/**
    - Sets the value of the ‘{@link shelly.irish.purchaseOrder.model.purchaseOrder.USAddress#getCity
    City}’ attribute.
    -
    -
    - @param value the new value of the ‘City’ attribute.
    - @see #getCity()
    - @generated */ void setCity(String value);
/**
    - Returns the value of the ‘State’ attribute.
    -
    -
    - If the meaning of the ‘State’ attribute isn’t clear,
    - there really should be more of a description here...
    -
    -
    - @return the value of the ‘State’ attribute.
    - @see #setState(String)

```

```

    - @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getUSAddress_State()
    - @model
    - @generated */ String getState();
/**
    - Sets the value of the '{@link shelley.irish.purchaseOrder.model.purchaseOrder.USAddress#getStateState}' attribute.
    -
    -
    - @param value the new value of the 'State' attribute.
    - @see #getState()
    - @generated */ void setState(String value);
/**
    - Returns the value of the 'Zip' attribute.
    -
    -
    - If the meaning of the 'Zip' attribute isn't clear,
    - there really should be more of a description here...
    -
    -
    - @return the value of the 'Zip' attribute.
    - @see #setZip(int)
    - @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getUSAddress_Zip()
    - @model
    - @generated */ int getZip();
/**
    - Sets the value of the '{@link shelley.irish.purchaseOrder.model.purchaseOrder.USAddress#setZipZip}' attribute.
    -
    -
    - @param value the new value of the 'Zip' attribute.
    - @see #getZip()

```

```

        - @generated */ void setZip(int value);
    /**
        - Returns the value of the 'Country' attribute.
        - The default value is "US".
        -
        -
        - If the meaning of the 'Country' attribute isn't clear,
        - there really should be more of a description here...
        -
        -
        - @return the value of the 'Country' attribute.
        - @see #setCountry(String)
        - @see shelley.irish.purchaseOrder.model.purchaseOrder.PurchaseOrderPackage#getUSAddress__Country()
        - @model default="US"
        - @generated */ String getCountry();
    /**
        - Sets the value of the '{@link shelley.irish.purchaseOrder.model.purchaseOrder.USAddress#getCountry() Country}' attribute.
        -
        -
        - @param value the new value of the 'Country' attribute.
        - @see #getCountry()
        - @generated */ void setCountry(String value);
    } // USAddress

```