



Chapter Three: Basic Control Flow

Slides prepared by Evan Gallagher, New York University

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Chapter Goals

- To be able to implement decisions using `if` statements
- To learn how to compare integers, floating-point numbers, and strings
- To understand the Boolean data type
- To develop strategies for validating user input

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The `if` Statement (3.1)

Decision making

(a necessary thing in non-trivial programs)

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The `if` Statement



We aren't lost!
We just haven't decided which way to go ... yet.

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The `if` Statement

The `if` statement

allows a program to carry out different actions
depending on the nature of the data being processed

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The `if` Statement

The `if` statement is used to implement a decision.

- When a condition is fulfilled,
one set of statements is executed.
- Otherwise, "`else`"
another set of statements is executed.

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement



if it's quicker to the candy mountain,
we'll go that way
else
we go that way

©•• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement

Ex: *The thirteenth floor!*



©•• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement

The thirteenth floor!
It's missing!



©•• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement

The thirteenth floor!
It's missing!

OH NO!



©•• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement

We must write the code
to control the elevator.

How can we skip the
13th floor?



©•• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement

We will model a person choosing
a floor by getting input from the user:

```
int floor;  
cout << "Floor: ";  
cin >> floor;
```

©•• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement

If the user inputs 20,
the program must set the actual floor to 19.
Otherwise,
we simply use the supplied floor number.

We need to decrement the input only under a certain condition.

```
int actual_floor;
if (floor > 13)
{
    actual_floor = floor - 1;
}
else
{
    actual_floor = floor;
}
```

if block
else block

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

The if Statement

SYNTAX 3.1 if Statement

A condition that is true or false.
Often uses relational operators:
== != < <= > >=

Braces are not required
if the branch contains a
single statement, but it's
good to always use them.

Don't put a semicolon here!

Quit the else branch
if there is nothing to do.

Lining up braces
is a good idea.

If the condition is true, the statement(s)
in this branch are executed in sequence;
if the condition is false, they are skipped.

If the condition is false, the statement(s)
in this branch are executed in sequence;
if the condition is true, they are skipped.

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

The if Statement

Sometimes, it happens that there is nothing
to do in the else branch of the statement.

So don't write it.

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

The if Statement


Here is another way to write this code:
We only need to decrement
when the floor is greater than 13.
We can set actual_floor before testing:

```
int actual_floor = floor;
if (floor > 13)
{
    actual_floor--;
} // No else needed
```

(And you'll notice we used the decrement operator this time.)

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

The if Statement – The Flowchart



C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

The if Statement – A Complete Elevator Program

```
#include <iostream>
using namespace std;

int main()
{
    int floor;
    cout << "Floor: ";
    cin >> floor;
    int actual_floor;
    if (floor > 13)
    {
        actual_floor = floor - 1;
    }
    else
    {
        actual_floor = floor;
    }

    cout << "The elevator will travel to the actual floor "
         << actual_floor << endl;

    return 0;
}
```

ch03/elevator1.cpp

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

The if Statement – Brace Layout

- Making your code easy to read is good practice.
- Lining up braces vertically helps.

```
if (floor > 13)
{
    floor--;
}
```

← do this style

©• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement – Brace Layout

- As long as the ending brace clearly shows what it is closing, there is no confusion.

```
if (floor > 13) {
    floor--;
}
```

not this one

Some programmers prefer this style
— it saves a vertical line in the code.

©• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement – Brace Layout

This is a passionate and ongoing argument,
but it is about style, not substance.

©• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement – Brace Layout

It is important that you pick a layout
scheme and stick with it consistently
within a given programming project.

Which scheme you choose may depend on

- your personal preference
- a coding style guide that you need to follow
(that would be your boss' style)

©• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement – Always Use Braces

When the body of an if statement consists of
a single statement, you need not use braces:

```
if (floor > 13)
    floor--;
```

©• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement – Always Use Braces

However, it is a good idea to always include the braces:

- the braces makes your code easier to read, and
- you are less likely to make errors such as ...

©• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement – Common Error – The Do-nothing Statement

Can you see the error?

```
if (floor > 13) ; ERROR
{
    floor--;
}
```

©•• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement – Common Error – The Do-nothing Statement

```
if (floor > 13) ; // ERROR ?
```

```
{
    floor--;
}
```

This is *not* a compiler error.
The compiler does not complain.
It interprets this if statement as follows.

If floor is greater than 13, execute the *do-nothing statement*.
(semicolon by itself is the do nothing statement)

Then *after that* execute the code enclosed in the braces.
Any statements enclosed in the braces are no longer a part of the if statement.

*logical error
you would have
to catch*

The if Statement – Indent when Nesting

Block-structured code has the property that *nested statements* are indented by one or more levels.

```
int main()
{
    int floor;
    ...
    if (floor > 13)
    {
        floor--;
    }
    ...
    return 0;
}
```

Indentation level

each indent is 3 spaces

©•• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement – Indent when Nesting

Using the tab key is a way to get this indentation

but ...

not all tabs are the same width!

Luckily most development environments have
settings to automatically convert all tabs to spaces.

©•• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement – Removing Duplication *efficiency*

```
if (floor > 13)
{
    actual_floor = floor - 1;
    cout << "Actual floor: " << actual_floor << endl;
}
else
{
    actual_floor = floor;
    cout << "Actual floor: " << actual_floor << endl;
}
```

Do you find anything curious in this code?

©•• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement – Removing Duplication

```
if (floor > 13)
{
    actual_floor = floor - 1;
    cout << "Actual floor: " << actual_floor << endl;
}
else
{
    actual_floor = floor;
    cout << "Actual floor: " << actual_floor << endl;
}
```

Hmmm...

©•• for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

The if Statement – Removing Duplication

```
if (floor > 13)
{
    actual_floor = floor - 1;
    cout << "Actual floor: " << actual_floor << endl;
}
else
{
    actual_floor = floor;
    cout << "Actual floor: " << actual_floor << endl;
}
```

Do these depend
on the test?

©++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

The if Statement – Removing Duplication

```
if (floor > 13)
{
    actual_floor = floor - 1;
}
else
{
    actual_floor = floor;
}
cout << "Actual floor: " << actual_floor << endl;
```

move it to a place
where it only needs
to be "coded" once

You should remove
this duplication.

©++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

Relational Operators (3.2)



Which way is quicker to the candy mountain?

©++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

Relational Operators



Let's compare the distances.

©++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

Relational Operators

Relational operators


less than < >= greater than or equal to
greater than > <= less than or equal to
logical equal == != not equal to

are used to compare numbers and strings.

©++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

Relational Operators




SYNTAX 3.2 Comparisons



©++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

Relational Operators

Table 2 Relational Operator Examples

Expression	Value	Comment
<code>3 <= 4</code>	true	3 is less than 4; <= tests for "less than or equal".
 <code>3 <= 4</code>	Error	The "less than or equal" operator is <=, not <=, with the "less than" symbol first.
<code>3 > 4</code>	false	> is the opposite of <=.
<code>4 < 4</code>	false	The left-hand side must be strictly smaller than the right-hand side.
<code>4 <= 4</code>	true	Both sides are equal; <= tests for "less than or equal".
<code>3 == (5 - 2)</code>	true	== tests for equality.
<code>3 != (5 - 1)</code>	true	!= tests for inequality. It is true that 3 is not 5 - 1.
 <code>3 == 6 / 2</code>	Error	Use == to test for equality.
<code>1.0 / 3.0 == 0.33333333</code>	false	Although the values are very close to one another, they are not exactly equal.
 <code>"10" > 5</code>	Error	You cannot compare strings and numbers.

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

Relational Operators – Some Notes

Computer keyboards do not have keys for:

≥
≤
≠

but these operators:

>=
<=
!=

look similar (and you can type them).

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

Relational Operators – Some Notes

The == operator is initially confusing to beginners.

In C++, = already has a meaning, namely assignment

The == operator denotes equality testing:

```
floor = 13; // Assign 13 to floor
// Test whether floor equals 13
if (floor == 13)
```

You can compare strings as well:

```
if (input == "Quit") ...
```

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

Relational Operators – Common Error == vs. =

The C++ language allows the use of = inside tests.

To understand this, we have to go back in time.

The creators of C, the predecessor to C++, were very frugal thus C did not have true and false values.

Instead, they allowed any numeric value inside a condition with this interpretation:

0 denotes false
any non-0 value denotes true.

In C++ you should use the bool values true and false

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

Relational Operators – Common Error == vs. =

Furthermore, in C and C++ assignments have values. The value of the assignment expression `floor = 13` is 13. These two features conspire to make a horrible pitfall:

```
if (floor = 13) ...
```

is legal C++.

the compiler would not complain; would not tell you you have an error

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved.

Relational Operators – Common Error == vs. =

The code sets `floor` to 13, and since that value is not zero, the condition of the `if` statement is *always* true.

← true!
`if (floor = 13) ...`

(and it's really hard to find this error at 3:00am when you've been coding for 13 hours straight)

Relational Operators – Common Error == vs. =

Don't be shell-shocked by this
and go completely the other way:

```
floor == floor - 1; // ERROR
```

This statement tests whether `floor` equals `floor - 1`.

It doesn't do anything with the outcome of the test,
but that is not a compiler error.

Just nothing really happens
(which is probably not what you meant to do
– so that's the error).

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Relational Operators – Common Error == vs. =

You must remember:

Use `==` *inside* tests.

Use `=` *outside* tests.

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Kinds of Error Messages

There are two kinds of errors:

Warnings

Errors

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Kinds of Error Messages

- **Error messages are fatal.**
 - The compiler will not translate a program with one or more errors.
- **Warning messages are advisory.**
 - The compiler will translate the program, but there is a good chance that the program will not do what you expect it to do.

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Kinds of Error Messages

It is a good idea to learn how to activate
warnings in your compiler.

It is a great idea to write code that
emits no warnings at all.

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Kinds of Error Messages

We stated there are two kinds of errors.

Actually there's only one kind:

The ones you must read
(that's all of them!)

C++ for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Kinds of Error Messages

Read all comments and deal with them.

If you understand a warning, and understand why it is happening, and you don't care about that reason – then and only then should you ignore a warning.

and, of course,
you can't ignore an error message!

© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Non-Exact Comparison of Floating-Point Numbers

Round off errors

Floating-point numbers have only a limited precision. Calculations can introduce roundoff errors.

© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Non-Exact Comparison of Floating-Point Numbers

Roundoff errors

if $r = 2$

$(\sqrt{2})^2 = 2$
in math

Does $(\sqrt{r})^2 == 2$?
what about in C++?

Let's see (by writing code, of course) ...

© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Non-Exact Comparison of Floating-Point Numbers

```
double r = sqrt(2.0);  
if (r * r == 2) {  
    cout << "sqrt(2) squared is 2" << endl;  
}  
else {  
    cout << "sqrt(2) squared is not 2 but "  
        << setprecision(18) << r * r << endl;  
}
```

This program displays:

sqrt(2) squared is not 2 but 2.00000000000000044

© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Non-Exact Comparison of Floating-Point Numbers – SOLUTION

Roundoff errors – a solution

Close enough ^{to zero} will do.

$$|x - y| < \epsilon$$

↑
close to 0
 1×10^{-14}

whatever variables/values you want to be equal

© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Non-Exact Comparison of Floating-Point Numbers – SOLUTION

Mathematically, we would write that x and y are close enough if for a very small number, ϵ :

$$|x - y| < \epsilon$$

ϵ is the Greek letter epsilon, a letter used to denote a very small quantity.

© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Non-Exact Comparison of Floating-Point Numbers – SOLUTION

It is common to set ϵ to 10^{-14} when comparing double numbers:

```
const double EPSILON = 1E-14;
double r = sqrt(2.0);
if (fabs(r * r - 2) < EPSILON)
{
    cout << "sqrt(2) squared is approximately ";
}
```

$$r^2 \approx 2$$

Include the `<cmath>` header to use `sqrt` and the `fabs` function which gives the absolute value.

© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Multiple Alternatives (3.3)



if it's quicker to the candy mountain,
we'll go that way
else
we go that way
but what about that way?

© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Multiple Alternatives

Multiple `if` statements can be combined to evaluate complex decisions.

© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Multiple Alternatives

How would we write code to deal with Richter scale values?

© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Multiple Alternatives

Table 3 Richter Scale

Value	Effect
8	Most structures fall
7	Many buildings destroyed
6	Many buildings considerably damaged, some collapse
4.5	Damage to poorly constructed buildings



© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved

Multiple Alternatives

In this case, there are five branches:
one each for the four descriptions of damage,

Value	Effect
8	Most structures fall
7	Many buildings destroyed
6	Many buildings considerably damaged, some collapse
4.5	Damage to poorly constructed buildings

and one for no destruction.

© for Everyone by Cay Horstmann
Copyright © 2008 by John Wiley & Sons. All rights reserved