


Chapter 3

Describing Syntax and Semantics



Chapter 3 Topics

- Introduction
- The General Problem of Describing Syntax
- Formal Methods of Describing Syntax
- Attribute Grammars
- Describing the Meanings of Programs: Dynamic Semantics

Copyright © 2012 Addison-Wesley. All rights reserved.

1-2

3.1 Introduction

- **Syntax**: the form or structure of the expressions, statements, and program units
- **Semantics**: the meaning of the expressions, statements, and program units
- Syntax and semantics provide a language's definition
 - Users of a language definition
 - Other language designers
 - Implementers
 - Programmers (the users of the language)

Could it; 1.3

Copyright © 2012 Addison-Wesley. All rights reserved.

1-3

3.2 The General Problem of Describing Syntax: Terminology

- A **sentence** is a string of characters over some alphabet *allowable in the language*
- A **language** is a set of sentences
- A **lexeme** is the lowest level syntactic unit of a language (e.g., *, sum, begin)
- A **token** is a category of lexemes (e.g., identifier, operator, special words)

Copyright © 2012 Addison-Wesley. All rights reserved.

1-4

Formal Definition of Languages

- **Recognizers**
 - A recognition device reads input strings over the alphabet of the language and decides whether the input strings belong to the language
 - Example: syntax analysis part of a compiler
 - Detailed discussion of syntax analysis appears in Chapter 4
- **Generators**
 - A device that generates sentences of a language
 - One can determine if the syntax of a particular sentence is syntactically correct by comparing it to the structure of the generator

Copyright © 2012 Addison-Wesley. All rights reserved.

1-5

3.3 BNF and Context-Free Grammars

- **Context-Free Grammars**
 - Developed by Noam Chomsky in the mid-1950s
 - Language generators, meant to describe the syntax of natural languages
 - Define a class of languages called context-free languages
- **Backus-Naur Form** (1959) *Peter*
 - Invented by John Backus to describe the syntax of Algol 58 *programming lang.*
 - BNF is equivalent to context-free grammars

Copyright © 2012 Addison-Wesley. All rights reserved.

1-6

BNF Fundamentals

- In BNF, abstractions are used to represent classes of syntactic structures—they act like syntactic variables (also called **nonterminal symbols**, or just **nonterminals**)
- Terminals** are lexemes or tokens
- A rule has a left-hand side (LHS), which is a nonterminal, and a right-hand side (RHS), which is a string of terminals and/or nonterminals

Copyright © 2012 Addison-Wesley. All rights reserved.

1.7

BNF Fundamentals (continued)

- Nonterminals are often enclosed in angle brackets
 - Examples of BNF rules:
 - $\langle \text{ident_list} \rangle \rightarrow \text{identifier} \mid \text{identifier}, \langle \text{ident_list} \rangle$
 - $\langle \text{if_stmt} \rangle \rightarrow \text{if } \langle \text{logic_expr} \rangle \text{ then } \langle \text{stmt} \rangle$
- Grammar: a finite non-empty set of rules
- A **start symbol** is a special element of the nonterminals of a grammar

Copyright © 2012 Addison-Wesley. All rights reserved.

1.8

BNF Rules

- An abstraction (or nonterminal symbol) can have more than one RHS

$\langle \text{stmt} \rangle \rightarrow \langle \text{single_stmt} \rangle$
 $\mid \text{begin } \langle \text{stmt_list} \rangle \text{ end}$

↑
pipe "or"

e.g. $\{ \text{ } \}$ $\{ \text{ } \}$

Copyright © 2012 Addison-Wesley. All rights reserved.

1.9

Describing Lists

- Syntactic lists are described using recursion
 - $\langle \text{ident_list} \rangle \rightarrow \text{ident}$
 $\mid \text{ident}, \langle \text{ident_list} \rangle$
- A **derivation** is a repeated application of rules, starting with the **start symbol** and ending with a sentence (all terminal symbols)

Copyright © 2012 Addison-Wesley. All rights reserved.

1.10

An Example Grammar

$\langle \text{program} \rangle \rightarrow \langle \text{stmts} \rangle$
 $\langle \text{stmts} \rangle \rightarrow \langle \text{stmt} \rangle \mid \langle \text{stmt} \rangle ; \langle \text{stmts} \rangle$
 $\langle \text{stmt} \rangle \rightarrow \langle \text{var} \rangle = \langle \text{expr} \rangle$
 $\langle \text{var} \rangle \rightarrow a \mid b \mid c \mid d$
 $\langle \text{expr} \rangle \rightarrow \langle \text{term} \rangle + \langle \text{term} \rangle \mid \langle \text{term} \rangle - \langle \text{term} \rangle$
 $\langle \text{term} \rangle \rightarrow \langle \text{var} \rangle \mid \text{const}$

complete list of "rules" for this language

Copyright © 2012 Addison-Wesley. All rights reserved.

1.11

example of a derivation

$\langle \text{program} \rangle \Rightarrow \langle \text{stmts} \rangle$
 $\Rightarrow \langle \text{stmt} \rangle$ *made a choice here*
 $\Rightarrow \langle \text{var} \rangle = \langle \text{expr} \rangle$
 $\Rightarrow a = \langle \text{expr} \rangle$
 $\Rightarrow a = \langle \text{term} \rangle + \langle \text{term} \rangle$
 $\Rightarrow a = \langle \text{var} \rangle + \langle \text{term} \rangle$
 $\Rightarrow a = b + \langle \text{term} \rangle$
 $\Rightarrow a = b + \text{const} \checkmark$
 $a = b + \text{const}$

left derivation

An Example Derivation

```

<program> => <stmts> => <stmt>
=> <var> = <expr>
=> a = <expr>
=> a = <term> + <term>
=> a = <var> + <term>
=> a = b + <term>
=> a = b + const
    
```

Copyright © 2012 Addison-Wesley. All rights reserved.

1-12

Derivations

- Every string of symbols in a derivation is a **sentential form**
- A **sentence** is a sentential form that has only terminal symbols *no angle brackets*
- A **leftmost derivation** is one in which the leftmost nonterminal in each sentential form is the one that is expanded
- A derivation may be neither leftmost nor rightmost


Copyright © 2012 Addison-Wesley. All rights reserved.

1-13

Parse Tree

another way to show a derivation

- A hierarchical representation of a derivation



a = b + const

Copyright © 2012 Addison-Wesley. All rights reserved.

1-14

Ambiguity in Grammars

- A grammar is **ambiguous** if and only if it generates a sentential form that has two or more distinct parse trees

basically if you can derive a sentence in more than one way (using a parse tree)

Copyright © 2012 Addison-Wesley. All rights reserved.


1-15

An Ambiguous Expression Grammar

start symbol

```

<expr> → <expr> <op> <expr> | const
<op> → / | -
    
```



Copyright © 2012 Addison-Wesley. All rights reserved.

1-16

An Unambiguous Expression Grammar


- If we use the parse tree to indicate **precedence levels** of the operators, we cannot have ambiguity

introduced more abstractions

```

<expr> → <expr> - <term> | <term>
<term> → <term> / const | const
    
```

the lower an operator is in a parse tree the higher precedence it has



Copyright © 2012 Addison-Wesley. All rights reserved.

1-17

Associativity of operators

$$3 \cdot 12 / 4$$

which operator do we do first?

$$\begin{array}{c} \cdot \\ 36/4 \\ 9 \end{array}$$

$$\begin{array}{c} \cdot \\ 3 \cdot 3 \\ 9 \end{array}$$

AS MID Left \rightarrow RT RULE

for exponents:


rule $\text{Left} \leftarrow \text{RT}$

$$2^3 \overset{5}{\overset{2}{\leftarrow}} = 2^{3^5} = 2^{243} = \dots$$

Associativity of Operators

- Operator associativity can also be indicated by a grammar

$\langle \text{expr} \rangle \rightarrow \langle \text{expr} \rangle + \langle \text{expr} \rangle \mid \text{const}$ (ambiguous)
 $\langle \text{expr} \rangle \rightarrow \langle \text{expr} \rangle + \text{const} \mid \text{const}$ (unambiguous)



Copyright © 2012 Addison-Wesley. All rights reserved.

left most operator is lower
so it is done first

Unambiguous grammar for if-then-else

$\langle \text{if_stmt} \rangle \rightarrow \text{if } \langle \text{logic_expr} \rangle \text{ then } \langle \text{stmt} \rangle$
 $\mid \text{if } \langle \text{logic_expr} \rangle \text{ then } \langle \text{stmt} \rangle \text{ else } \langle \text{stmt} \rangle$

Extended BNF

- Optional parts are placed in brackets **[]**

ex: $\langle \text{proc_call} \rangle \rightarrow \text{ident } [(\langle \text{expr_list} \rangle)]$

- Alternative parts of RHSs are placed inside parentheses and separated via vertical bars

ex: $\langle \text{term} \rangle \rightarrow \langle \text{term} \rangle (+|-) \text{const}$

- Repetitions (0 or more) are placed inside braces **{ }**

ex: $\langle \text{ident} \rangle \rightarrow \text{letter } \{ \text{letter} | \text{digit} \}$

can repeat over and over

Copyright © 2012 Addison-Wesley. All rights reserved.

1-10

BNF and EBNF

same grammar
two diff. ways

- BNF

$\langle \text{expr} \rangle \rightarrow \langle \text{expr} \rangle + \langle \text{term} \rangle$
 $\mid \langle \text{expr} \rangle - \langle \text{term} \rangle$
 $\mid \langle \text{term} \rangle$
 $\langle \text{term} \rangle \rightarrow \langle \text{term} \rangle * \langle \text{factor} \rangle$
 $\mid \langle \text{term} \rangle / \langle \text{factor} \rangle$
 $\mid \langle \text{factor} \rangle$

- EBNF

$\langle \text{expr} \rangle \rightarrow \langle \text{term} \rangle \{ (+ | -) \langle \text{term} \rangle \}$
 $\langle \text{term} \rangle \rightarrow \langle \text{factor} \rangle \{ (* | /) \langle \text{factor} \rangle \}$

Copyright © 2012 Addison-Wesley. All rights reserved.

1-20

Recent Variations in EBNF

- Alternative RHSs are put on separate lines
- Use of a colon instead of \Rightarrow
- Use of $_{opt}$ for optional parts *instead of []*
- Use of $_{oneof}$ for choices *instead ()*

Copyright © 2012 Addison-Wesley. All rights reserved.

1.21

Static Semantics

- Nothing to do with meaning
- Context-free grammars (CFGs) cannot describe all of the syntax of programming languages
- Categories of constructs that are trouble:
 - Context-free, but cumbersome (e.g., types of operands in expressions)
 - Non-context-free (e.g., variables must be declared before they are used)

hard to use BNF to say

Copyright © 2012 Addison-Wesley. All rights reserved.

1.22

3.4 Attribute Grammars

extending CFGs to include static semantics

- Attribute grammars (AGs) have additions to CFGs to carry some semantic info on parse tree nodes
- **Primary value of AGs:**
 - **Static semantics specification**
 - **Compiler design** (static semantics checking)

Copyright © 2012 Addison-Wesley. All rights reserved.

1.23

Attribute Grammars: Definition

- **Def:** An attribute grammar is a context-free grammar $G = (S, N, T, P)$ with the following additions:
 - For each grammar symbol x there is a set $A(x)$ of attribute values
 - Each rule has a set of functions that define certain attributes of the nonterminals in the rule
 - Each rule has a (possibly empty) set of predicates to check for attribute consistency

Copyright © 2012 Addison-Wesley. All rights reserved.

1.24

Attribute Grammars: Definition

$X_0 \rightarrow X_1 X_2 X_3$
 $\langle \text{program} \rangle \rightarrow \langle \text{expr} \rangle + \langle \text{term} \rangle$

- Let $X_0 \rightarrow X_1 \dots X_n$ be a rule
- Functions of the form $S(X_i) = f(A(X_1), \dots, A(X_n))$ define synthesized attributes
- Functions of the form $I(X_i) = f(A(X_0), \dots, A(X_n))$, for $i \leq j \leq n$, define inherited attributes
- Initially, there are intrinsic attributes on the leaves

Copyright © 2012 Addison-Wesley. All rights reserved.

1.25

Attribute Grammars: An Example

- Syntax

	<i>int</i>	<i>float</i>
$\langle \text{assign} \rangle \rightarrow$	$\langle \text{var} \rangle =$	$\langle \text{expr} \rangle$
$\langle \text{expr} \rangle \rightarrow$	$\langle \text{var} \rangle +$	$\langle \text{var} \rangle \mid \langle \text{var} \rangle$
$\langle \text{var} \rangle \rightarrow$	$A \mid B \mid C$	
- actual_type: synthesized for $\langle \text{var} \rangle$ and $\langle \text{expr} \rangle$
- expected_type: inherited for $\langle \text{expr} \rangle$

Copyright © 2012 Addison-Wesley. All rights reserved.

1.26

Attribute Grammar (continued)

- Syntax rule: $\langle \text{expr} \rangle \rightarrow \langle \text{var} \rangle[1] + \langle \text{var} \rangle[2]$
Semantic rules:
 $\langle \text{expr} \rangle.\text{actual_type} \leftarrow \langle \text{var} \rangle[1].\text{actual_type}$
Predicate:
 $\langle \text{var} \rangle[1].\text{actual_type} == \langle \text{var} \rangle[2].\text{actual_type}$
 $\langle \text{expr} \rangle.\text{expected_type} == \langle \text{expr} \rangle.\text{actual_type}$
- Syntax rule: $\langle \text{var} \rangle \rightarrow \text{id}$
Semantic rule:
 $\langle \text{var} \rangle.\text{actual_type} \leftarrow \text{lookup}(\langle \text{var} \rangle.\text{string})$

Copyright © 2012 Addison-Wesley. All rights reserved.

1.27

Attribute Grammars (continued)

- How are attribute values computed?
 - If all attributes were inherited, the tree could be decorated in top-down order.
 - If all attributes were synthesized, the tree could be decorated in bottom-up order.
 - In many cases, both kinds of attributes are used, and it is some combination of top-down and bottom-up that must be used.

Copyright © 2012 Addison-Wesley. All rights reserved.

1.28

Attribute Grammars (continued)

```
 $\langle \text{expr} \rangle.\text{expected\_type} \leftarrow \text{inherited from parent}$   
  
 $\langle \text{var} \rangle[1].\text{actual\_type} \leftarrow \text{lookup}(A)$   
 $\langle \text{var} \rangle[2].\text{actual\_type} \leftarrow \text{lookup}(B)$   
 $\langle \text{var} \rangle[1].\text{actual\_type} == \langle \text{var} \rangle[2].\text{actual\_type}$   
  
 $\langle \text{expr} \rangle.\text{actual\_type} \leftarrow \langle \text{var} \rangle[1].\text{actual\_type}$   
 $\langle \text{expr} \rangle.\text{actual\_type} == \langle \text{expr} \rangle.\text{expected\_type}$ 
```

stop 9/11

Copyright © 2012 Addison-Wesley. All rights reserved.

1.30

3.5 Semantics

- There is no single widely acceptable notation or formalism for describing semantics
- Several needs for a methodology and notation for semantics:
 - Programmers need to know what statements mean
 - Compiler writers must know exactly what language constructs do
 - Correctness proofs would be possible
 - Compiler generators would be possible
 - Designers could detect ambiguities and inconsistencies

Copyright © 2012 Addison-Wesley. All rights reserved.

1.30

Operational Semantics

- Operational Semantics
 - Describe the meaning of a program by executing its statements on a machine, either simulated or actual. The change in the state of the machine (memory, registers, etc.) defines the meaning of the statement
- To use operational semantics for a high-level language, a virtual machine is needed

before $a=2$ $b=5$
change
 $a=a+b$
after $a=7$ $b=5$

Copyright © 2012 Addison-Wesley. All rights reserved.

1.31

Operational Semantics

- A *hardware* pure interpreter would be too expensive
- A *software* pure interpreter also has problems
 - The detailed characteristics of the particular computer would make actions difficult to understand
 - Such a semantic definition would be machine-dependent

Copyright © 2012 Addison-Wesley. All rights reserved.

1.32

Operational Semantics (continued)

- A better alternative: A complete computer simulation
- The process:
 - Build a translator (translates source code to the machine code of an idealized computer)
 - Build a simulator for the idealized computer
- Evaluation of operational semantics:
 - Good if used informally (language manuals, etc.)
 - Extremely complex if used formally (e.g., VDL, it was used for describing semantics of PL/I.

Copyright © 2012 Addison-Wesley. All rights reserved.

1.33

Operational Semantics (continued)

- Uses of operational semantics:
 - Language manuals and textbooks
 - Teaching programming languages
- Two different levels of uses of operational semantics:
 - Natural operational semantics - final result
 - Structural operational semantics - each step
- Evaluation
 - Good if used informally (language manuals, etc.)
 - Extremely complex if used formally (e.g., VDL)

Copyright © 2012 Addison-Wesley. All rights reserved.

1.34

Denotational Semantics

- Based on recursive function theory
- The most abstract semantics description method
- Originally developed by Scott and Strachey (1970)

Copyright © 2012 Addison-Wesley. All rights reserved.

1.35

Denotational Semantics – continued

- The process of building a denotational specification for a language:
 - Define a mathematical object for each language entity
 - Define a function that maps instances of the language entities onto instances of the corresponding mathematical objects
- The meaning of language constructs are defined by only the values of the program's variables

Copyright © 2012 Addison-Wesley. All rights reserved.

1.36

Denotational Semantics: program state

- The state of a program is the values of all its current variables

$$s = \{ \langle i_1, v_1 \rangle, \langle i_2, v_2 \rangle, \dots, \langle i_n, v_n \rangle \}$$
- Let **VARMAP** be a function that, when given a variable name and a state, returns the current value of the variable

$$\text{VARMAP}(i_j, s) = v_j$$

Copyright © 2012 Addison-Wesley. All rights reserved.

1.37

Decimal Numbers

Handwritten notes on the slide:

- name of function $f(x) = 3x + 2$
- inputs $f(-2) = 3(-2) + 2$

Syntax:

```
<dec_num> → '0' | '1' | '2' | '3' | '4' | '5' | '6' | '7' | '8' | '9' |
<dec_num> ('0' | '1' | '2' | '3' | '4' | '5' | '6' | '7' | '8' | '9')
```

Semantics:

```
M_dec('0') = 0, M_dec('1') = 1, ..., M_dec('9') = 9
M_dec(<dec_num> '0') = 10 * M_dec(<dec_num>)
M_dec(<dec_num> '1') = 10 * M_dec(<dec_num>) + 1
...
M_dec(<dec_num> '9') = 10 * M_dec(<dec_num>) + 9
```

Handwritten note: "31" means $10 * 3 + 1 = 30 + 1 = 31$

Copyright © 2012 Addison-Wesley. All rights reserved.

1.38

Expressions

- Map expressions onto $\mathbb{Z} \cup \{\text{error}\}$
- We assume expressions are decimal numbers, variables, or binary expressions having one arithmetic operator and two operands, each of which can be an expression

\mathbb{Z}
↓
 $3 + 7 * 2^3 = 59 \quad \sqrt{-4} = \text{error}$

Copyright © 2012 Addison-Wesley. All rights reserved.

1-30

Expressions

Semantics/meaning (function)

```

Me(⟨expr⟩, s) Δ=
  case ⟨expr⟩ of
    ⟨dec_num⟩ => Mdec(⟨dec_num⟩, s)
    ⟨var⟩ =>
      if VARMAP(⟨var⟩, s) == undef
      then error
      else VARMAP(⟨var⟩, s)
    ⟨binary_expr⟩ =>
      if (Me(⟨binary_expr⟩.⟨left_expr⟩, s) == undef
      OR Me(⟨binary_expr⟩.⟨right_expr⟩, s) ==
        undef)
      then error
      else
        if (⟨binary_expr⟩.⟨operator⟩ == '+' then
          Me(⟨binary_expr⟩.⟨left_expr⟩, s) +
            Me(⟨binary_expr⟩.⟨right_expr⟩, s)
        else Me(⟨binary_expr⟩.⟨left_expr⟩, s) *
            Me(⟨binary_expr⟩.⟨right_expr⟩, s)
        ...

```

eg. of binary expression $25 + 3$
 left_expr operator right_expr

Copyright © 2012 Addison-Wesley. All rights reserved.

1-31

Assignment Statements

- Maps state sets to state sets $U \cup \{\text{error}\}$
- function assign. stmt.*
 $M_a(x := E, s) \Delta=$
 if $M_e(E, s) == \text{error}$ then error
 else $s' = \{ \langle i_1, v_1' \rangle, \langle i_2, v_2' \rangle, \dots, \langle i_n, v_n' \rangle \}$,
 where for $j = 1, 2, \dots, n$,
 if $i_j == x$ then $v_j' = M_e(E, s)$ ← change value of LHS in expr.
 else $v_j' = \text{VARMAP}(i_j, s)$
S = old state of computer
S' = new state of computer

Copyright © 2012 Addison-Wesley. All rights reserved.

1-41

Logical Pretest Loops

- Maps state sets to state sets $U \cup \{\text{error}\}$
- function*
 $M_l(\text{while } B \text{ do } L, s) \Delta=$
 if $M_b(B, s) == \text{undef}$ then error
 then error
 else if $M_b(B, s) == \text{false}$ then s
 else if $M_{s1}(L, s) == \text{error}$ then error
 else $M_l(\text{while } B \text{ do } L, M_{s1}(L, s))$

p. 147

Copyright © 2012 Addison-Wesley. All rights reserved.

1-42

Loop Meaning

- The meaning of the loop is the value of the program variables after the statements in the loop have been executed the prescribed number of times, assuming there have been no errors
- In essence, the loop has been converted from iteration to recursion, where the recursive control is mathematically defined by other recursive state mapping functions
- Recursion, when compared to iteration, is easier to describe with mathematical rigor

Copyright © 2012 Addison-Wesley. All rights reserved.

1-43

Evaluation of Denotational Semantics

- Can be used to prove the correctness of programs
- Provides a rigorous way to think about programs
- Can be an aid to language design
- Has been used in compiler generation systems
- Because of its complexity, it is of little use to language users

Copyright © 2012 Addison-Wesley. All rights reserved.

1-44

Axiomatic Semantics

- Based on formal logic (predicate calculus)
- Original purpose: formal program verification
- Axioms or inference rules are defined for each statement type in the language (to allow transformations of logic expressions into more formal logic expressions)
- The logic expressions are called *assertions*

Copyright © 2012 Addison-Wesley. All rights reserved.

1-46


Axiomatic Semantics (continued)

- An assertion before a statement (a *precondition*) states the relationships and constraints among variables that are true at that point in execution
- An assertion following a statement is a *postcondition*
- A *weakest precondition* is the least restrictive precondition that will guarantee the postcondition

Copyright © 2012 Addison-Wesley. All rights reserved.

1-46

Axiomatic Semantics Form

- Pre-, post form: $\{P\} \text{ statement } \{Q\}$

- An example
 - $a = b + 1 \quad \{a > 1\}$
 - One possible precondition: $\{b > 10\}$
 - Weakest precondition: $\{b > 0\}$

Copyright © 2012 Addison-Wesley. All rights reserved.

1-47

EX: $\underline{\quad? \quad} \overset{\text{stmt}}{a = b + 1} \{a > 1\}$
 What is weakest precondition?
 start w/post cond. $a > 1$ *for assignment stmt*
 use stmt to replace a
 $b + 1 > 1$
 $-1 \quad -1$
 do algebra
 \therefore weakest precondition $b > 0$

Program Proof Process

- The postcondition for the entire program is the desired result *of the program*.
 - Work back through the program to the first statement. If the precondition on the first statement is the same as the program specification, the program is correct.

"correctness proofs"

Copyright © 2012 Addison-Wesley. All rights reserved.

1-48

Axiomatic Semantics: Assignment

- An axiom for assignment statements
 $(x = E) \{Q_{x \rightarrow E}\} x = E \{Q\}$
notation for weakest precondition - don't know what it is yet
- The Rule of Consequence:

$$\text{if } \rightarrow \left(\frac{\{P\} \overset{\text{stmt}}{S} \{Q\}, P' \Rightarrow P, Q \Rightarrow Q'}{\{P'\} S \{Q'\}} \right)$$

$$\text{then } \rightarrow \left(\{P'\} S \{Q'\} \right)$$

Copyright © 2012 Addison-Wesley. All rights reserved.

1-48

EX: $\frac{?}{x = x + y - 3 \quad \{x > 10\}}$

Start w/
post cond.
replace x
w/E

$$x > 10$$

$$x + y - 3 > 10$$

$$x + y > 13$$

$$y > 13 - x$$

$\therefore \{y > 13 - x\}$ is the weakest pre cond.

EX: $\{x > 5\} x = x - 3 \{x > 0\}$

$\{P'\} \quad S \quad \{Q'\}$

side work: $x > 0$
 $x - 3 > 0$
 $x > 3$ should be weakest pre cond.
 but NOTE $x > 5$ means x will be > 3 as well

$P' \Rightarrow P$ $Q' = Q$ $\therefore \{x > 5\} S \{x > 0\}$
 $x > 5 \Rightarrow x > 3$ so $Q \Rightarrow Q'$ $\{P \wedge S \wedge Q'\}$ is true
 $x > 0 \Rightarrow x > 0$

Step 9/13

Axiomatic Semantics: Sequences

- An inference rule for sequences of the form $S1; S2$

$$\frac{\{P1\} S1 \{P2\} \quad \{P2\} S2 \{P3\}}{\{P1\} S1; S2 \{P3\}}$$

if ($\frac{\{P1\} S1 \{P2\}, \{P2\} S2 \{P3\}}{\{P1\} S1; S2 \{P3\}}$) true
 then ($\frac{\{P1\} S1 \{P2\}, \{P2\} S2 \{P3\}}{\{P1\} S1; S2 \{P3\}}$) true

Copyright © 2012 Addison-Wesley. All rights reserved. 1.60

EX: $S1: y = 3 * x + 1;$
 $S2: x = y + 3;$
 $\{P3\}: \{x < 10\}$

the inference rule tells us we can work backwards on S2 then S1 to calculate preconditions

$\{P3\}: x < 10$
 use S2: $y + 3 < 10$

algebra $y < 7 \rightarrow \{P2\}$
 pre cond for S2
 post cond for S1

$\{P2\} \quad y < 7$
 use S1 $3x + 1 < 7$
 algebra $\frac{3x + 1}{3} < \frac{7}{3}$
 $\{x < 2\} \rightarrow \{P1\}$

Axiomatic Semantics: Selection

- An inference rules for selection
- if B then S1 else S2

$$\frac{\{B \text{ and } P\} S1 \{Q\}, \{\text{not } B \text{ and } P\} S2 \{Q\}}{\{P\} \text{ if } B \text{ then } S1 \text{ else } S2 \{Q\}}$$

if... then...

Copyright © 2012 Addison-Wesley. All rights reserved. 1.61

EX: compute precondition for

B if $x > 0$ then

$S1 \rightarrow y = y - 1$

else

$S2 \rightarrow y = y + 1$

$\{Q\}$ $\{y > 0\}$

use the assignment inference rule on then "then" part ($S1$) and on "else" part ($S2$)

$\{Q\}$ $y > 0$

use $S1$ /then $y - 1 > 0$

algebra $y > 1$ maybe this is $\{P\}$

$\{Q\}$ $y > 0$

use $S2$ /else $y + 1 > 0$

algebra $y > -1$ maybe this is $\{P\}$

$\{y > 1\}$ and $\{y > -1\}$ implies $\{y > -1\}$

2, 3, 4, ...

0, 1, 2, 3, ...

since $\{y > 1\} \Rightarrow \{y > -1\}$ we

can use $\{y > 1\}$ as our precondition

$\therefore \{P\} = \{y > 1\}$

Axiomatic Semantics: Loops

- An inference rule for logical pretest loops

$\{P\} \text{ while } B \text{ do } S \text{ end } \{Q\}$

$\frac{\{I \text{ and } B\} S \{I\}}{\{I\} \text{ while } B \text{ do } S \{I \text{ and } (\text{not } B)\}}$

where I is the loop invariant (the inductive hypothesis)

Copyright © 2012 Addison-Wesley. All rights reserved.

1-63

Axiomatic Semantics: Axioms

- Characteristics of the loop invariant: I must meet the following conditions:
 - $P \Rightarrow I$ -- the loop invariant must be true initially
 - $\{I\} B \{I\}$ -- evaluation of the Boolean must not change the validity of I
 - $\{I \text{ and } B\} S \{I\}$ -- I is not changed by executing the body of the loop
 - $(I \text{ and } (\text{not } B)) \Rightarrow Q$ -- if I is true and B is false, Q is implied
 - The loop terminates -- can be difficult to prove

Copyright © 2012 Addison-Wesley. All rights reserved.

1-63

Loop Invariant

- The loop invariant I is a weakened version of the loop postcondition, and it is also a precondition.
- I must be weak enough to be satisfied prior to the beginning of the loop, but when combined with the loop exit condition, it must be strong enough to force the truth of the postcondition

Copyright © 2012 Addison-Wesley. All rights reserved.

1-64

EX: while $y \neq x$ do $y = y + 1$ end $\delta y = x$

Start w/ $\{Q\}$ $y = x$

1st iteration $y + 1 = x$
 $y = x - 1$

2nd iteration $y = x - 1$
 $y + 1 = x - 1$
 $y = x - 2$

3rd it $y = x - 2$
 $y + 1 = x - 2$
 $y = x - 3$

by now obvious that $y < x$ for all iterations

combine $y = x$ (for the B false case)

we get $y \leq x$ for I ... *stopped 9/16*

Evaluation of Axiomatic Semantics

- Developing axioms or inference rules for all of the statements in a language is difficult
- It is a good tool for correctness proofs, and an excellent framework for reasoning about programs, but it is not as useful for language users and compiler writers
- Its usefulness in describing the meaning of a programming language is limited for language users or compiler writers

Copyright © 2012 Addison-Wesley. All rights reserved.

1.66

Denotational Semantics vs Operational Semantics

- In operational semantics, the state changes are defined by coded algorithms
- In denotational semantics, the state changes are defined by rigorous mathematical functions

Copyright © 2012 Addison-Wesley. All rights reserved.

1.67

Summary

- BNF and context-free grammars are equivalent meta-languages
 - Well-suited for describing the syntax of programming languages
- An attribute grammar is a descriptive formalism that can describe both the syntax and the semantics of a language
- Three primary methods of semantics description
 - Operation, axiomatic, denotational

Copyright © 2012 Addison-Wesley. All rights reserved.

1.67

Chapter 3 Homework

- Review Questions

- p.162 1, 7, 12, 27

- Problem Set

- p.163 6a, 7a, 8, 23ab, 24ab, 28