

User Stories & Acceptance Criteria

ChurnGuard — Release 1 backlog

Document ID	US-CG-001
Version	1.0
Author	Shubham Tiwari, Senior Business Analyst
Framework	Scrum · 2-week sprints · INVEST-tested stories
Estimation	Planning poker, modified Fibonacci, team-relative

Definition of Ready

A story enters sprint planning only when it has: a clear user and value statement; acceptance criteria in Given/When/Then form; identified dependencies and test data; UI reference where a screen is affected; a mapped FR ID; and no open question that blocks estimation.

Definition of Done

Code peer-reviewed and merged · unit tests passing · every acceptance criterion demonstrated in the sprint review environment · SIT scenarios executed and passed · RTM updated with test case IDs and status · no open Severity 1 or 2 defects · configuration documented · BA sign-off recorded in Jira.

Epic map

Epic	Title	Stories	FRs covered
E1	Risk scoring foundation	US-01 – US-05	FR-001 – FR-005, FR-010, FR-011, FR-014, FR-016 – FR-020
E2	Data quality safeguards	US-06 – US-07	FR-006 – FR-009, FR-034
E3	Alerting, routing and SLA	US-08 – US-12	FR-021 – FR-030
E4	Explainability	US-13 – US-15	FR-012, FR-031 – FR-034, FR-015
E5	Retention case management	US-16 – US-19	FR-035 – FR-041
E6	Reporting	US-20 – US-22	FR-042 – FR-047
E7	Configuration and governance	US-23 – US-25	FR-048 – FR-058

Epic 1 — Risk scoring foundation

US-01 · Build the in-scope account list

As a scoring engine I need to identify which accounts to score each night so that effort and alerting stay inside the high-value segment.

FR: FR-014, BRule-01, BRule-02 · Points: 3 · Sprint: 1

- Given an account with status Active and segment High-Value, when the nightly cycle builds its list, then the account is included.
- Given an account with a submitted cancellation, when the list is built, then the account is excluded and the exclusion reason is written to the run log.
- Given an account onboarded 40 days ago, when the list is built, then it is included for scoring but flagged as excluded from Critical alerting (BRule-06).
- Given the list is built, when the cycle logs its run, then the log records total in scope, total excluded and the exclusion reasons.

US-02 · Calculate the five signal sub-scores

As a scoring engine I need to convert raw account data into a 0–100 sub-score per signal so that risk is measured consistently across every account.

FR: FR-001 – FR-005, FR-010 · Points: 13 · Sprint: 1–2

- Given an account with active days of 14 against a 90-day average of 38, when S1 is calculated, then the active-day component awards 45 points per FSD \$3.2.
- Given any signal, when its components total more than 100, then the sub-score is capped at 100.
- Given a signal is calculated, when the result is written, then the raw input values and the comparison period are stored with it.
- Given a seasonal-category account inside a configured seasonal window, when S2 is calculated, then GMV decline points are suppressed.
- Given the engine has scored a sample of 50 historical accounts, when results are compared to independently calculated SQL expectations, then all 50 match exactly.

US-03 · Produce the composite score and tier

As a CS Manager I want each account to carry one comparable risk score and tier so that my team works from a single definition of "at risk".

FR: FR-011, FR-013, FR-016 · Points: 5 · Sprint: 2

- Given five sub-scores and the active weight set, when the composite is calculated, then it equals the weighted sum divided by 100, rounded to a whole number between 0 and 100.
- Given a composite of 55, when the tier is assigned, then the tier is Watch.
- Given composites of 39, 40, 69 and 70, when tiers are assigned, then they are Stable, Watch, Watch and Critical respectively.
- Given the composite is calculated, when the record is written, then the dominant driver is the signal with the highest weighted contribution, with ties resolved S1 > S2 > S3 > S4 > S5.

US-04 · Detect tier movement with hysteresis

As a CSM I don't want to be alerted about accounts drifting one point across a boundary so that alerts stay meaningful.

FR: FR-017, FR-018 · Points: 5 · Sprint: 2

- Given an account at Watch scoring 38 with a buffer of 3, when tiering runs, then it remains at Watch.
- Given the same account scores 36, when tiering runs, then it moves to Stable and the movement is recorded as De-escalation.
- Given an account at Stable scores 74, when tiering runs, then it moves to Critical and the movement is recorded as Escalation.
- Given any cycle, when movement is evaluated, then the previous tier is stored on the new record.

US-05 · Retain score history

As a BI analyst I need a dated record of every score so that trends and model accuracy can be analysed.

FR: FR-019, FR-020 · Points: 3 · Sprint: 2

- Given a completed cycle, when history is written, then each account has exactly one record for that date holding composite, five sub-scores, tier, movement, data-quality flag and config version.
- Given the same cycle date is re-run, when history is written, then the existing record is updated, not duplicated.
- Given any application role, when a history record is opened, then it is read-only and cannot be deleted.

Epic 2 — Data quality safeguards

US-06 · Flag insufficient data instead of scoring it

As a CSM I need to know when a score is built on incomplete data so that I can trust the ones that aren't.

FR: FR-006, FR-007, FR-034 · Points: 5 · Sprint: 3

- Given a source feed last received 60 hours ago, when the cycle runs, then that signal is marked Insufficient Data for every account it supplies.
- Given an account where 25% of a signal's inputs are null, when the signal is evaluated, then it is marked Insufficient Data.
- Given a null usage value, when the signal is calculated, then it is treated as missing, never as zero.
- Given a source record that cannot be resolved to a CRM Account ID, when the cycle runs, then it is written to the exception report and the cycle continues.

US-07 · Suppress or redistribute when signals are missing

As a CS Manager I want the system to withhold a score rather than publish a misleading one so that the model keeps its credibility.

FR: FR-008, FR-009 · Points: 5 · Sprint: 3

- Given exactly one signal is insufficient, when the composite is calculated, then that signal's weight is redistributed proportionally across the remaining four and the flag is set to Reduced.
- Given two or more signals are insufficient, when the composite is calculated, then scoring is suppressed, the previous score is retained and the flag is set to Suppressed.
- Given a suppressed account, when tiering runs, then no tier movement is recorded and no alert is generated.
- Given a Reduced or Suppressed account, when a CSM opens the risk panel, then a banner names the affected signals and the date data was last received.

Epic 3 — Alerting, routing and SLA

US-08 · Create a retention task on escalation

As a CSM I want an account that has just become riskier to appear in my task list with the reason attached so that I can act without hunting for context.

FR: FR-021, FR-022, FR-026 · Points: 8 · Sprint: 4

- Given an account escalates from Stable to Watch, when the cycle completes, then a Retention Task is created and assigned to the account's owning CSM.
- Given the task is created, when the CSM opens it, then it shows account name, composite score, previous and new tier, dominant driver, the top three contributing signals with their values, and a link to the risk panel.
- Given an account with an open task already at Watch, when it is scored at Watch again, then no second task is created; the existing task is updated with the new score and a dated note is appended.
- Given an account de-escalates, when the cycle completes, then no task is created.

US-09 · Apply the SLA and escalate the jump cases

As a CS Manager I want every alert to carry a due date, and sudden Critical jumps to reach me too so that the highest-risk accounts are never missed.

FR: FR-023, FR-024, FR-025 · Points: 5 · Sprint: 4

- Given a task created for Critical tier on a Thursday, when the due date is set, then it is the next business day on the CS calendar, skipping weekends and configured public holidays.
- Given a task created for Watch tier, when the due date is set, then it is three business days ahead.
- Given an account moves from Stable to Critical in a single cycle, when the alert is generated, then the CSM's CS Manager is notified in addition to the CSM.
- Given an account with no active owning CSM, when the task is created, then it is assigned to the CS Manager queue for that team and the ownership gap is flagged.

US-10 · Track first touch and breach

As a CS Manager I need to see whether alerts were acted on in time so that the SLA means something.

FR: FR-028, FR-029 · Points: 5 · Sprint: 5

- Given an open task, when the owning CSM logs any activity against the account, then the first-touch timestamp is stamped once and elapsed business time is calculated.
- Given a task passes its due date with no first touch, when the SLA check runs, then the task is marked Breached and the CS Manager is notified.
- Given a task touched before its due date, when the SLA check runs, then the status is Met and no notification is sent.
- Given activity logged by a user other than the owning CSM, when first touch is evaluated, then it still counts and the acting user is recorded.

US-11 · Attach the right playbook

As a CSM I want the recommended play attached to the alert so that I start from an agreed approach rather than improvising.

FR: FR-013, FR-027 · Points: 3 · Sprint: 4

- Given a dominant driver of S1, when the task is created, then the playbook mapped to S1 in the configuration table is attached.
- Given the mapping is changed by a Business Administrator, when the next cycle runs, then new tasks use the new mapping and existing tasks are unchanged.
- Given a driver with no mapped playbook, when the task is created, then it is created without a playbook and the gap is written to the run log.

US-12 · Run in shadow before alerting

As a project sponsor I want to see what the model would have done before it starts messaging CSMs so that we can calibrate without damaging trust.

FR: FR-030 · Points: 3 · Sprint: 5

- Given shadow mode is active, when a cycle completes, then scores, tiers, movements and history are written and no task or notification is generated.
- Given shadow mode is active, when a manager opens the dashboard, then the shadow status and its end date are displayed.
- Given shadow mode is switched off, when the next cycle runs, then alerting begins from that cycle's escalations only, not retrospectively.

Epic 4 — Explainability

US-13 · See the score on the account

As a CSM I want the risk position visible on the account record so that I have it in front of me when I'm preparing for a call.

FR: FR-031 · Points: 5 · Sprint: 6

- Given a scored account, when the CSM opens it, then the risk panel shows composite score, tier label and icon, movement since the last cycle, days in current tier, dominant driver and last scored timestamp.
- Given an out-of-scope account, when the CSM opens it, then the panel shows "Not scored — outside the high-value segment" with the segment rule named.
- Given the panel loads, when measured at the 95th percentile, then it renders within 3 seconds.
- Given a colour-blind user, when the tier is displayed, then it is distinguishable by label and icon without relying on colour.

US-14 · Understand what drove the score

As a CSM I need to see which signals and which values produced the score so that I can have a specific conversation instead of a generic one.

FR: FR-012, FR-032 · Points: 8 · Sprint: 6

- Given the risk panel is open, when the CSM views the breakdown, then all five signals are listed in descending order of weighted contribution with sub-score, contribution and the primary driving value in plain language.
- Given a signal row, when the CSM expands it, then every component is shown with its value, the band matched and the points awarded.
- Given any displayed value, when it is read, then the comparison period is stated alongside it.
- Given a score of 55 built as in FSD \$3.8, when the contributions are summed, then they reconcile to the displayed composite.

US-15 · See the trend and any data gaps

As a CSM I want to know whether risk is building or receding, and whether the data is complete so that I judge urgency correctly.

FR: FR-033, FR-034, FR-015 · Points: 5 · Sprint: 7

- Given an account with at least 14 days of history, when the panel loads, then a 90-day trend of composite score is displayed with tier bands shaded.
- Given an account flagged Reduced or Suppressed, when the panel loads, then the banner states which signals are unavailable and when data was last received.

- **Given** a CSM selects "Rescore now", **when** the request is processed, **then** the score refreshes within 30 seconds.
- **Given** the nightly cycle is running, **when** a rescore is requested, **then** it is queued and the user is told it will complete after the cycle.

Epic 5 — Retention case management

US-16 · Open a case from the alert

As a CSM I **want** to start a structured case in one step **so that** the intervention is recorded without extra admin.

FR: FR-035, FR-036, FR-039 · **Points:** 5 · **Sprint:** 7

- **Given** the risk panel or a retention task, **when** the CSM selects "Open retention case", **then** a case is created pre-populated with opening score, opening tier, dominant driver, mapped playbook and the CSM as owner.
- **Given** an account with an open case, **when** a second case is attempted, **then** creation is blocked and the existing case number is offered as a link.
- **Given** a case is created from a task, **when** it is saved, **then** the task is linked to the case and first touch is stamped.

US-17 · Close a case with an outcome

As a CS Manager I **need** every case closed with a reason from a controlled list **so that** save rate is measurable rather than anecdotal.

FR: FR-037, FR-038 · **Points:** 3 · **Sprint:** 8

- **Given** a case in any open status, **when** the owner selects a Closed status, **then** a closure reason from the controlled list is mandatory.
- **Given** Closed-False Positive is selected, **when** the case is saved, **then** the signal that produced the false reading must also be selected.
- **Given** a case is closed, **when** it is saved, **then** the closure date, outcome, reason and closing user are recorded.

US-18 · Close saved cases automatically

As a CSM I **don't want** to manually close cases where the account has clearly recovered **so that** my case list reflects live work.

FR: FR-040 · **Points:** 3 · **Sprint:** 8

- **Given** an open case whose account has been Stable for 30 consecutive days, **when** the closure job runs, **then** the case is closed as Closed-Saved with reason "Risk resolved — sustained recovery".
- **Given** the same case with Manual Hold set, **when** the job runs, **then** the case remains open.
- **Given** an auto-closure, **when** it is written, **then** the audit entry records the system as the closing actor.

US-19 · Link cases to renewal outcome

As a VP Customer Success I **want** to compare opening risk tier against the eventual renewal result **so that** we can tell whether the model is right.

FR: FR-041 · **Points:** 5 · **Sprint:** 9

- **Given** a closed case, **when** the account's renewal is recorded, **then** the renewal result is linked to the case.
- **Given** a set of cases in a period, **when** the accuracy view is opened, **then** counts of renewed and churned are shown grouped by opening tier.
- **Given** an account that churned without ever reaching Critical, **when** the accuracy view is built, **then** it appears as a missed detection.

Epic 6 — Reporting

US-20 · See the portfolio position

As a VP Customer Success I **want** one view of tier distribution and ARR at risk **so that** I can direct attention where the money is.

FR: FR-042, FR-046 · **Points:** 8 · **Sprint:** 9

- **Given** a completed cycle, **when** the dashboard is opened, **then** it shows accounts by tier, ARR by tier, tier movement in the period, open cases by status, SLA compliance and save rate.
- **Given** each tile, **when** its figure is checked against the source query, **then** the values reconcile exactly.
- **Given** the dashboard is opened, **when** it loads, **then** the last refresh timestamp is displayed.
- **Given** a failed cycle, **when** the dashboard is opened, **then** a banner states the age of the data shown.

US-21 · Work the Critical list

As a CS Manager I **want** a prioritised list of Critical accounts with filters **so that** I can run a weekly review from one screen.

FR: FR-043, FR-044, FR-047 · **Points:** 5 · **Sprint:** 10

- **Given** the dashboard, **when** the Critical worklist is opened, **then** accounts are listed by ARR descending with CSM, score, days in tier and case status.
- **Given** filters for team, CSM, plan, primary marketplace and date range, **when** any are applied, **then** all tiles and the worklist update consistently.
- **Given** a filtered view, **when** the user exports, **then** the export matches the on-screen data and respects the user's access rights.

US-22 · Review model accuracy

As a Business Administrator I **need** to see how predictions compared with outcomes **so that** weights can be tuned on evidence.

FR: FR-045 · **Points:** 5 · **Sprint:** 10

- **Given** a selected period, **when** the accuracy view is opened, **then** accounts whose opening tier was Critical are split by outcome — saved, churned, still open.
- **Given** closed cases, **when** false positives are counted, **then** they are grouped by the signal recorded as responsible.
- **Given** the view, **when** it is exported, **then** the underlying account list is included for analysis.

Epic 7 — Configuration and governance

US-23 · Tune the model without a release

As a Business Administrator I **want** to change weights and thresholds myself, and preview the effect first **so that** the model can adapt without a development cycle.
FR: FR-048 – FR-052 · **Points:** 8 · **Sprint:** 11

- **Given** weights that do not total 100%, **when** save is attempted, **then** it is blocked with the current total shown.
- **Given** tier boundaries that overlap or leave a gap, **when** save is attempted, **then** it is blocked and the offending boundary is named.
- **Given** a proposed configuration, **when** "Preview impact" is selected, **then** the resulting tier distribution and estimated daily alert volume are shown against the last cycle's data, with nothing saved.
- **Given** a saved change, **when** the next cycle runs, **then** it uses the new configuration; historical scores are unchanged and remain linked to the version that produced them.

US-24 · Override a tier with justification

As a CSM I **want** to override a tier when I have context the data doesn't **so that** the system reflects reality without me losing trust in it.
FR: FR-053 – FR-055 · **Points:** 5 · **Sprint:** 11

- **Given** an override, **when** it is saved, **then** a reason from the controlled list, free-text justification and an expiry within 90 days are all mandatory.
- **Given** an active override, **when** the panel is viewed, **then** both the calculated tier and the overridden tier are shown; the calculated score is never replaced.
- **Given** an active override, **when** the cycle runs, **then** no alert is generated for that account.
- **Given** an override reaches its expiry date, **when** the next cycle runs, **then** normal tiering and alerting resume automatically.

US-25 · Audit every change

As an information security reviewer I **need** an immutable record of changes **so that** any historical score and decision can be reconstructed.
FR: FR-051, FR-056 – FR-058 · **Points:** 5 · **Sprint:** 12

- **Given** a configuration change, tier override, case closure or manual rescore, **when** it occurs, **then** an audit entry records user, timestamp, before value and after value.
- **Given** any application role including administrator, **when** an audit entry is opened, **then** it cannot be edited or deleted.
- **Given** a CSM, **when** they attempt to open risk data for an account they do not own and do not manage, **then** access is denied per the role matrix.
- **Given** an authorised user, **when** the audit report is opened, **then** it is filterable by user, object, date range and change type, and exportable.

Backlog summary

Sprint	Stories	Points	Theme
1	US-01, US-02 (start)	16	Foundations, signal extraction
2	US-02 (finish), US-03, US-04, US-05	13	Composite, tiering, history
3	US-06, US-07	10	Data quality safeguards
4	US-08, US-09, US-11	16	Alerting and routing
5	US-10, US-12	8	SLA tracking, shadow mode
6	US-13, US-14	13	Risk panel and explainability
7	US-15, US-16	10	Trend, case creation
8	US-17, US-18	6	Case closure
9	US-19, US-20	13	Outcome linkage, dashboard
10	US-21, US-22	10	Worklist, accuracy
11	US-23, US-24	13	Configuration, overrides
12	US-25 + UAT prep	5	Governance, UAT readiness