IRPA Digital Board Governance System - Software Requirements Specification

Status: Reverse-engineered; owner validation required. Baseline: main @ f20403e6f26c296f9d3aa3cda87588115a0f694d.

Scope and evidence

Source-derived navigation, portal components and Worker entrypoint paths are documented here. Source presence is not proof of live production operation. Dataset Registry, Research Data Collection and Release Readiness are normative standalone portal requirements; their separate top-level navigation is a proposed gap. Grant Intelligence is discovery/analysis only; concept-note advice is internal drafting, not donor submission.

Inventory

- 31 top-level modules; 15 registered sub-portals (6 Meetings, 8 Documents, 1 Induction).
- 41 source page components; 3 standalone portal requirements; 21 component/subsystem screens; 5 shared/workflow screens.
- 72 page-specific wireframes.

Top-level modules

1. IT Operations - MOD-01
2. Dashboard - MOD-02
3. Induction and Orientation - MOD-03
4. Induction Applications - MOD-04
5. Board Members Registration - MOD-05
6. Members & Personnel - MOD-06
7. Invitations - MOD-07
8. Meetings - MOD-08
9. Resolutions - MOD-09
10. Voting - MOD-10
11. Actions - MOD-11
12. Documents - MOD-12
13. Signature Platform - MOD-13
14. Decisions - MOD-14
15. Risk Register - MOD-15
16. Authorization & Approvals - MOD-16
17. Employee Payments - MOD-17
18. Research, Statistics and Knowledge - MOD-18
19. Finance Portfolio - MOD-19
20. Procurement - MOD-20
21. Reports - MOD-21
22. Audit Trail - MOD-22
23. Grant Intelligence & Funding Opportunities - MOD-23
24. Communication & Media - MOD-24
25. Downloads - MOD-25
26. Settings - MOD-26
27. Add Administrator - MOD-27
28. Department and Archive Registry - MOD-28
29. Department Portal Builder - MOD-29
30. External Auditor Portal - MOD-30
31. Auditors & Special Invitees - MOD-31

Registered sub-portals

- Meetings -> Meeting Room - SUB-01
- Meetings -> Participants - SUB-02
- Meetings -> Resolutions - SUB-03
- Meetings -> Voting - SUB-04
- Meetings -> Actions - SUB-05
- Meetings -> Decisions - SUB-06
- Documents -> My Documents - SUB-07
- Documents -> Department Documents - SUB-08
- Documents -> Shared With Me - SUB-09
- Documents -> Signing Workspace - SUB-10

- Documents -> Post-Signature Work - SUB-11
- Documents -> Final Archive - SUB-12
- Documents -> Upload Document - SUB-13
- Documents -> Retrieve Archived Documents - SUB-14
- Induction and Orientation -> Induction Applications - SUB-15

Standalone portals

- Dataset Registry - STD-01; separate top-level navigation is a proposed gap.
- Research Data Collection - STD-02; separate top-level navigation is a proposed gap.
- Release Readiness - STD-03; separate top-level navigation is a proposed gap.

Roles and authorization

Source indicates administrator, board/member, employee, finance, procurement, HR, IT, auditor, signer and invitation/induction capacities. Approved role register and per-record permissions require Board/HR confirmation. UI hiding is not authorization; every protected read/write must be enforced server-side. Actual and Trial environments remain distinct; identity/security records remain in Actual Data as the source gate specifies.

Functional requirements and Given/When/Then criteria

All test IDs are PROPOSED until mapped to executable tests.

MOD-01 - IT Operations

Priority: MUST. Page: it-operations. Test: TEST-PROPOSED-MOD-01 (PROPOSED).
- MOD-01-AC1: Given the caller has the IT Operations role, when the diagnostics view is requested, then the response lists each configured service name, health state and last-checked timestamp, and omits credentials, tokens and secret configuration values.
- MOD-01-AC2: Given a non-IT user calls an IT operation directly, when the protected request is submitted directly to the server, then server-side authorization denies it and records the denial.

MOD-02 - Dashboard

Priority: MUST. Page: dashboard. Test: TEST-PROPOSED-MOD-02 (PROPOSED).
- MOD-02-AC1: Given an authorized user loads the dashboard, when the dashboard page is loaded, then cards contain only role- and environment-scoped data.
- MOD-02-AC2: Given one data source fails, when the dashboard requests data from the unavailable source, then its card shows an error/retry without blocking other cards.

MOD-03 - Induction and Orientation

Priority: MUST. Page: induction-and-orientation. Test: TEST-PROPOSED-MOD-03 (PROPOSED).
- MOD-03-AC1: Given an invited user has an induction record, when the user performs the operation described in this scenario, then required steps and current status appear in sequence.
- MOD-03-AC2: Given all required steps are complete, when the user submits the induction completion request, then server validation is required before status becomes Completed.

MOD-04 - Induction Applications

Priority: MUST. Page: induction-applications. Test: TEST-PROPOSED-MOD-04 (PROPOSED).
- MOD-04-AC1: Given an authorized reviewer opens an application, when the application detail view is requested, then applicant fields, status and review history appear.
- MOD-04-AC2: Given a reviewer approves/rejects, when the reviewer submits the decision, then decision, reviewer, timestamp and required reason are stored.

MOD-05 - Board Members Registration

Priority: MUST. Page: board-members-registration. Test: TEST-PROPOSED-MOD-05 (PROPOSED).
- MOD-05-AC1: Given an authorized administrator submits complete identity/appointment fields, when the create or registration request is submitted, then a unique registration is saved.
- MOD-05-AC2: Given required fields are missing or identity is duplicated, when the invalid form is submitted, then save is blocked with field-level errors.

MOD-06 - Members & Personnel

Priority: MUST. Page: members-and-personnel. Test: TEST-PROPOSED-MOD-06 (PROPOSED).
- MOD-06-AC1: Given HR opens the register, when the user submits the register search, then search returns only personnel records within assigned scope.
- MOD-06-AC2: Given a personnel record changes, when the record update is saved, then actor, timestamp, changed fields and resulting status are audited.

MOD-07 - Invitations

Priority: MUST. Page: invitations. Test: TEST-PROPOSED-MOD-07 (PROPOSED).
- MOD-07-AC1: Given an authorized issuer creates an invitation, when the create or registration request is submitted, then a unique recipient-bound token and expiry are stored.
- MOD-07-AC2: Given a token is expired, revoked, redeemed or mismatched, when the user attempts to activate or use the invitation, then activation is rejected and no identity is provisioned.

MOD-08 - Meetings

Priority: MUST. Page: meetings. Test: TEST-PROPOSED-MOD-08 (PROPOSED).
- MOD-08-AC1: Given a user opens Meetings, when the corresponding portal or register is opened, then only in-scope meetings appear with date, status and participation.
- MOD-08-AC2: Given a secretary supplies meeting title, date/time, agenda and participant list, when the meeting save request is submitted, then the server returns the saved meeting ID and stores the creator UID and creation timestamp in the meeting audit history; missing title, date/time or agenda returns field-level validation errors.

MOD-09 - Resolutions

Priority: MUST. Page: resolutions. Test: TEST-PROPOSED-MOD-09 (PROPOSED).
- MOD-09-AC1: Given a meeting has resolutions, when the user performs the corresponding portal action, then each record shows ID, text, status, owner and source meeting.
- MOD-09-AC2: Given a resolution status changes, when the record update is saved, then previous/new state, actor and timestamp are retained.

MOD-10 - Voting

Priority: MUST. Page: voting. Test: TEST-PROPOSED-MOD-10 (PROPOSED).
- MOD-10-AC1: Given voting is open and a user is eligible, when the user performs the corresponding portal action, then one valid vote is recorded once for that voter/item.
- MOD-10-AC2: Given voting is closed, voter ineligible or vote already exists, when the user submits the vote, then submission is rejected and tally unchanged.

MOD-11 - Actions

Priority: MUST. Page: actions. Test: TEST-PROPOSED-MOD-11 (PROPOSED).
- MOD-11-AC1: Given an action list opens, when the corresponding portal or register is opened, then owner, due date, status, source decision and overdue state appear.
- MOD-11-AC2: Given an assignee updates progress, when the record update is saved, then prior/new state, actor and timestamp are retained.

MOD-12 - Documents

Priority: MUST. Page: documents. Test: TEST-PROPOSED-MOD-12 (PROPOSED).
- MOD-12-AC1: Given a document list is requested, when the user performs the operation described in this scenario, then role, department, ownership and sharing rules filter results server-side.
- MOD-12-AC2: Given an upload passes validation, when the upload is submitted for storage, then metadata, version, uploader and classification are stored.

MOD-13 - Signature Platform

Priority: MUST. Page: signature-platform. Test: TEST-PROPOSED-MOD-13 (PROPOSED).
- MOD-13-AC1: Given a named signer opens a valid envelope, when the signature action is submitted, then only the assigned document and required fields are accessible.
- MOD-13-AC2: Given signing succeeds, when the signature action is submitted, then signer identity, timestamps, evidence and audit events are stored; failure never marks completion.

MOD-14 - Decisions

Priority: MUST. Page: decisions. Test: TEST-PROPOSED-MOD-14 (PROPOSED).
- MOD-14-AC1: Given the decisions register opens, when the reviewer submits the decision, then source meeting, text, owner, date and implementation status appear.
- MOD-14-AC2: Given implementation status changes, when the record update is saved, then decision history and linked action state update consistently.

MOD-15 - Risk Register

Priority: MUST. Page: risk-register. Test: TEST-PROPOSED-MOD-15 (PROPOSED).
- MOD-15-AC1: Given a risk has likelihood, impact, owner and mitigation, when the user performs the operation described in this scenario, then its rating is calculated/displayed by the documented scale.

- MOD-15-AC2: Given a risk is reassessed, when the record update is saved, then previous/current rating, mitigation and reviewer are retained.

MOD-16 - Authorization & Approvals

Priority: MUST. Page: authorization-and-approvals. Test: TEST-PROPOSED-MOD-16 (PROPOSED).
- MOD-16-AC1: Given a request is submitted, when the corresponding save or submit action is sent, then it routes only to an approver authorized for type and amount/scope.
- MOD-16-AC2: Given an unauthorized user attempts approval directly, when the protected request is submitted directly to the server, then server-side authorization denies and audits it.

MOD-17 - Employee Payments

Priority: MUST. Page: employee-payments. Test: TEST-PROPOSED-MOD-17 (PROPOSED).
- MOD-17-AC1: Given finance opens a payment batch, when the user performs the operation described in this scenario, then employee, period, amount, approval and payment state appear per line.
- MOD-17-AC2: Given a batch is submitted, when the corresponding save or submit action is sent, then validation/approvals pass before it locks for processing; transitions are audited.

MOD-18 - Research, Statistics and Knowledge

Priority: MUST. Page: research-statistics-and-knowledge. Test: TEST-PROPOSED-MOD-18 (PROPOSED).
- MOD-18-AC1: Given a research user lists datasets/outputs, when the search filters are submitted, then title, owner, classification, version and access are displayed.
- MOD-18-AC2: Given an output is published, when the user performs the operation described in this scenario, then metadata/approval checks pass and source records retain their classification.

MOD-19 - Finance Portfolio

Priority: MUST. Page: finance-portfolio. Test: TEST-PROPOSED-MOD-19 (PROPOSED).
- MOD-19-AC1: Given finance requests a summary, when the user performs the operation described in this scenario, then totals reflect selected actual/trial environment, period and currency.
- MOD-19-AC2: Given a non-finance user requests a finance endpoint directly, when the protected request is submitted directly to the server, then the server denies access.

MOD-20 - Procurement

Priority: MUST. Page: procurement. Test: TEST-PROPOSED-MOD-20 (PROPOSED).
- MOD-20-AC1: Given a request has valid specifications, budget and requester, when the user performs the operation described in this scenario, then it receives a unique reference and workflow state.
- MOD-20-AC2: Given an approver decides, when the user performs the operation described in this scenario, then decision, justification, approver and timestamp are stored; only valid next states are allowed.

MOD-21 - Reports

Priority: MUST. Page: reports. Test: TEST-PROPOSED-MOD-21 (PROPOSED).
- MOD-21-AC1: Given a user selects report/date filters, when the user performs the operation described in this scenario, then output contains only authorized records matching filters.
- MOD-21-AC2: Given export completes, when the user performs the operation described in this scenario, then report title, generation time, filter scope and classification label are included.

MOD-22 - Audit Trail

Priority: MUST. Page: audit-trail. Test: TEST-PROPOSED-MOD-22 (PROPOSED).
- MOD-22-AC1: Given an authorized auditor searches a period, when the search filters are submitted, then events show actor, action, target, timestamp and outcome.
- MOD-22-AC2: Given the authenticated user lacks the Audit Trail read permission, when the user requests the audit query endpoint directly, then the server returns HTTP 403, returns no audit-event payload and writes a security-denial event containing actor UID, requested action, target and timestamp.

MOD-23 - Grant Intelligence & Funding Opportunities

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-MOD-23 (PROPOSED).
- MOD-23-AC1: Given crawler discovery is ingested, when the user performs the operation described in this scenario, then source URL, timestamp, provenance and Pending Verification state are retained.
- MOD-23-AC2: Given an analyst requests eligibility/alignment, when the user performs the operation described in this scenario, then criterion evidence, IRPA fit, confidence and unknowns appear; no donor contact or application submission occurs.

MOD-24 - Communication & Media

Priority: MUST. Page: communication-and-media. Test: TEST-PROPOSED-MOD-24 (PROPOSED).
- MOD-24-AC1: Given an authorized communications user opens channels/content, when the user performs the operation described in this scenario, then connection status, state and ownership appear without credentials.
- MOD-24-AC2: Given approved content is published, when the user performs the operation described in this scenario, then version, destination, actor, time and provider result are audited; drafts remain unpublished.

MOD-25 - Downloads

Priority: MUST. Page: downloads. Test: TEST-PROPOSED-MOD-25 (PROPOSED).
- MOD-25-AC1: Given Downloads loads, when the user performs the operation described in this scenario, then each resource shows title, type, version and classification.
- MOD-25-AC2: Given protected download is unauthorized, when the protected request is submitted directly to the server, then no bytes are returned and denial is recorded.

MOD-26 - Settings

Priority: MUST. Page: settings. Test: TEST-PROPOSED-MOD-26 (PROPOSED).
- MOD-26-AC1: Given an administrator opens settings, when the user performs the operation described in this scenario, then value, scope and role editability are displayed.
- MOD-26-AC2: Given a setting change passes validation/authorization, when the user performs the operation described in this scenario, then it persists with before/after audit; unauthorized changes fail.

MOD-27 - Add Administrator

Priority: MUST. Page: add-administrator. Test: TEST-PROPOSED-MOD-27 (PROPOSED).
- MOD-27-AC1: Given an authorized administrator provisions an account, when the create or registration request is submitted, then a least-privilege invitation is created after identity/approval checks.
- MOD-27-AC2: Given a non-admin attempts provisioning, when the user performs the operation described in this scenario, then server denies and creates no administrator record.

MOD-28 - Department and Archive Registry

Priority: MUST. Page: department-and-archive-registry. Test: TEST-PROPOSED-MOD-28 (PROPOSED).
- MOD-28-AC1: Given an authorized registry user creates a valid identifier/owner/classification, when the create or registration request is submitted, then a unique registry entry is saved.
- MOD-28-AC2: Given archive search filters are applied, when the search filters are submitted, then lifecycle, retention class and authorized retrieval route are returned.

MOD-29 - Department Portal Builder

Priority: MUST. Page: department-portal-builder. Test: TEST-PROPOSED-MOD-29 (PROPOSED).
- MOD-29-AC1: Given a builder submits unique key, parent, label and access policy, when the corresponding save or submit action is sent, then a portal definition is saved.
- MOD-29-AC2: Given a definition is activated, when the user performs the operation described in this scenario, then only matching users see it and previous configuration is recoverable.

MOD-30 - External Auditor Portal

Priority: MUST. Page: external-auditor-portal. Test: TEST-PROPOSED-MOD-30 (PROPOSED).
- MOD-30-AC1: Given an active auditor invitation is verified, when the user performs the operation described in this scenario, then only assigned audit material and time-bounded access appear.
- MOD-30-AC2: Given access expires/revokes, when the user performs the operation described in this scenario, then every protected request is denied immediately.

MOD-31 - Auditors & Special Invitees

Priority: MUST. Page: auditors-and-special-invitees. Test: TEST-PROPOSED-MOD-31 (PROPOSED).
- MOD-31-AC1: Given an authorized administrator supplies identity, purpose, scope and expiry, when the user performs the operation described in this scenario, then a time-bounded invite is created.
- MOD-31-AC2: Given invite is invalid, expired or out of scope, when the user attempts to activate or use the invitation, then access is denied and logged.

SUB-01 - Meeting Room

Priority: MUST. Page: meetings-meeting-room. Test: TEST-PROPOSED-SUB-01 (PROPOSED).
- SUB-01-AC1: Given a user has access to Meetings and the required child permission, when Meeting Room is selected, when the user performs the operation described in this scenario, then only in-scope records are displayed in the child view.

- SUB-01-AC2: Given child permission is absent or the parent portal is unavailable, when Meeting Room is requested directly, when the user performs the operation described in this scenario, then access is denied and protected content is not returned.

SUB-02 - Participants

Priority: MUST. Page: meetings-participants. Test: TEST-PROPOSED-SUB-02 (PROPOSED).
- SUB-02-AC1: Given a user has access to Meetings and the required child permission, when Participants is selected, when the user performs the operation described in this scenario, then only in-scope records are displayed in the child view.
- SUB-02-AC2: Given child permission is absent or the parent portal is unavailable, when Participants is requested directly, when the user performs the operation described in this scenario, then access is denied and protected content is not returned.

SUB-03 - Resolutions

Priority: MUST. Page: meetings-resolutions. Test: TEST-PROPOSED-SUB-03 (PROPOSED).
- SUB-03-AC1: Given a user has access to Meetings and the required child permission, when Resolutions is selected, when the user performs the operation described in this scenario, then only in-scope records are displayed in the child view.
- SUB-03-AC2: Given child permission is absent or the parent portal is unavailable, when Resolutions is requested directly, when the user performs the operation described in this scenario, then access is denied and protected content is not returned.

SUB-04 - Voting

Priority: MUST. Page: meetings-voting. Test: TEST-PROPOSED-SUB-04 (PROPOSED).
- SUB-04-AC1: Given a user has access to Meetings and the required child permission, when Voting is selected, when the user performs the operation described in this scenario, then only in-scope records are displayed in the child view.
- SUB-04-AC2: Given child permission is absent or the parent portal is unavailable, when Voting is requested directly, when the user performs the operation described in this scenario, then access is denied and protected content is not returned.

SUB-05 - Actions

Priority: MUST. Page: meetings-actions. Test: TEST-PROPOSED-SUB-05 (PROPOSED).
- SUB-05-AC1: Given a user has access to Meetings and the required child permission, when Actions is selected, when the user performs the operation described in this scenario, then only in-scope records are displayed in the child view.
- SUB-05-AC2: Given child permission is absent or the parent portal is unavailable, when Actions is requested directly, when the user performs the operation described in this scenario, then access is denied and protected content is not returned.

SUB-06 - Decisions

Priority: MUST. Page: meetings-decisions. Test: TEST-PROPOSED-SUB-06 (PROPOSED).
- SUB-06-AC1: Given a user has access to Meetings and the required child permission, when Decisions is selected, when the reviewer submits the decision, then only in-scope records are displayed in the child view.
- SUB-06-AC2: Given child permission is absent or the parent portal is unavailable, when Decisions is requested directly, when the reviewer submits the decision, then access is denied and protected content is not returned.

SUB-07 - My Documents

Priority: MUST. Page: documents-my-documents. Test: TEST-PROPOSED-SUB-07 (PROPOSED).
- SUB-07-AC1: Given a user has access to Documents and the required child permission, when My Documents is selected, when the user performs the operation described in this scenario, then only in-scope records are displayed in the child view.
- SUB-07-AC2: Given child permission is absent or the parent portal is unavailable, when My Documents is requested directly, when the user performs the operation described in this scenario, then access is denied and protected content is not returned.

SUB-08 - Department Documents

Priority: MUST. Page: documents-department-documents. Test: TEST-PROPOSED-SUB-08 (PROPOSED).
- SUB-08-AC1: Given a user has access to Documents and the required child permission, when Department Documents is selected, when the user performs the operation described in this scenario, then only in-scope records are displayed in the child view.
- SUB-08-AC2: Given child permission is absent or the parent portal is unavailable, when Department

Documents is requested directly, when the user performs the operation described in this scenario, then access is denied and protected content is not returned.

SUB-09 - Shared With Me

Priority: MUST. Page: documents-shared-with-me. Test: TEST-PROPOSED-SUB-09 (PROPOSED).
- SUB-09-AC1: Given a user has access to Documents and the required child permission, when Shared With Me is selected, when the user performs the operation described in this scenario, then only in-scope records are displayed in the child view.
- SUB-09-AC2: Given child permission is absent or the parent portal is unavailable, when Shared With Me is requested directly, when the user performs the operation described in this scenario, then access is denied and protected content is not returned.

SUB-10 - Signing Workspace

Priority: MUST. Page: documents-signing-workspace. Test: TEST-PROPOSED-SUB-10 (PROPOSED).
- SUB-10-AC1: Given a user has access to Documents and the required child permission, when Signing Workspace is selected, when the signature action is submitted, then only in-scope records are displayed in the child view.
- SUB-10-AC2: Given child permission is absent or the parent portal is unavailable, when Signing Workspace is requested directly, when the signature action is submitted, then access is denied and protected content is not returned.

SUB-11 - Post-Signature Work

Priority: MUST. Page: documents-post-signature-work. Test: TEST-PROPOSED-SUB-11 (PROPOSED).
- SUB-11-AC1: Given a user has access to Documents and the required child permission, when Post-Signature Work is selected, when the signature action is submitted, then only in-scope records are displayed in the child view.
- SUB-11-AC2: Given child permission is absent or the parent portal is unavailable, when Post-Signature Work is requested directly, when the signature action is submitted, then access is denied and protected content is not returned.

SUB-12 - Final Archive

Priority: MUST. Page: documents-final-archive. Test: TEST-PROPOSED-SUB-12 (PROPOSED).
- SUB-12-AC1: Given a user has access to Documents and the required child permission, when Final Archive is selected, when the user performs the operation described in this scenario, then only in-scope records are displayed in the child view.
- SUB-12-AC2: Given child permission is absent or the parent portal is unavailable, when Final Archive is requested directly, when the user performs the operation described in this scenario, then access is denied and protected content is not returned.

SUB-13 - Upload Document

Priority: MUST. Page: documents-upload-document. Test: TEST-PROPOSED-SUB-13 (PROPOSED).
- SUB-13-AC1: Given a user has access to Documents and the required child permission, when Upload Document is selected, when the upload is submitted for storage, then only in-scope records are displayed in the child view.
- SUB-13-AC2: Given child permission is absent or the parent portal is unavailable, when Upload Document is requested directly, when the upload is submitted for storage, then access is denied and protected content is not returned.

SUB-14 - Retrieve Archived Documents

Priority: MUST. Page: documents-retrieve-archived-documents. Test: TEST-PROPOSED-SUB-14 (PROPOSED).
- SUB-14-AC1: Given a user has access to Documents and the required child permission, when Retrieve Archived Documents is selected, when the user performs the operation described in this scenario, then only in-scope records are displayed in the child view.
- SUB-14-AC2: Given child permission is absent or the parent portal is unavailable, when Retrieve Archived Documents is requested directly, when the user performs the operation described in this scenario, then access is denied and protected content is not returned.

SUB-15 - Induction Applications

Priority: MUST. Page: induction-and-orientation-induction-applications. Test: TEST-PROPOSED-SUB-15 (PROPOSED).
- SUB-15-AC1: Given a user has access to Induction and Orientation and the required child permission, when Induction Applications is selected, when the user performs the operation described in this scenario, then only in-scope records are displayed in the child view.
- SUB-15-AC2: Given child permission is absent or the parent portal is unavailable, when Induction

Applications is requested directly, when the user performs the operation described in this scenario, then access is denied and protected content is not returned.

STD-01 - Dataset Registry

Priority: MUST. Page: dataset-registry. Test: TEST-PROPOSED-STD-01 (PROPOSED).
- STD-01-AC1: Given a steward supplies title, owner, source, schema/version, classification, consent/legal basis and access policy, when the user performs the operation described in this scenario, then a versioned metadata record is saved without copying restricted source data.
- STD-01-AC2: Given a user searches datasets, when the search filters are submitted, then only permitted metadata appears with version, steward and lifecycle status.

STD-02 - Research Data Collection

Priority: MUST. Page: research-data-collection. Test: TEST-PROPOSED-STD-02 (PROPOSED).
- STD-02-AC1: Given a collection form has missing required fields or invalid types/ranges, when the user attempts to activate or use the invitation, then submission is blocked with field-level errors.
- STD-02-AC2: Given valid data synchronizes, when the user performs the operation described in this scenario, then collector, time, location precision policy, consent, instrument version and sync state are stored idempotently.

STD-03 - Release Readiness

Priority: MUST. Page: release-readiness. Test: TEST-PROPOSED-STD-03 (PROPOSED).
- STD-03-AC1: Given a release is assessed, when the user performs the operation described in this scenario, then build, tests, security, migration, rollback, support and approval gates show PASS/FAIL/NOT RUN with evidence.
- STD-03-AC2: Given any mandatory gate is FAIL or NOT RUN, when the user performs the operation described in this scenario, then release approval is blocked and unresolved gate IDs are shown.

AI-01 - Crawler isolation

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-AI-01 (PROPOSED).
- AI-01-AC1: Given a crawl runs, when the user performs the operation described in this scenario, then source fetch and writes remain inside the grant-crawler Worker and declared grant datasets, never Drive Gateway or unrelated collections.
- AI-01-AC2: Given a source fails/times out, when the dashboard requests data from the unavailable source, then its failure is recorded, other sources continue within concurrency limits and failed data is not marked verified.

AI-02 - Eligibility

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-AI-02 (PROPOSED).
- AI-02-AC1: Given an official call is available, when the user performs the operation described in this scenario, then applicant/geography/sector/registration/co-funding criteria show PASS/FAIL/UNKNOWN with evidence and timestamp.
- AI-02-AC2: Given a mandatory criterion is UNKNOWN, when the user performs the operation described in this scenario, then eligibility is UNVERIFIED and is not represented as eligible.

AI-03 - Donor alignment

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-AI-03 (PROPOSED).
- AI-03-AC1: Given official donor objectives and approved IRPA profile are selected, when the user performs the operation described in this scenario, then objectives map to IRPA objectives with evidence, mismatch and confidence.
- AI-03-AC2: Given authoritative donor evidence is absent, when the user performs the operation described in this scenario, then alignment is UNKNOWN and no donor priority/score is invented.

AI-04 - Concept note advisor - analysis only

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-AI-04 (PROPOSED).
- AI-04-AC1: Given an analyst supplies verified opportunity and project facts, when the user performs the operation described in this scenario, then an editable draft includes evidence-linked assumptions, missing questions, risks and fit rationale.
- AI-04-AC2: Given a draft is saved, when the user performs the operation described in this scenario, then it remains owner-scoped with audit events; no donor email, portal login, application submission or dispatch occurs.

OFF-01 - Offline/installable app

Priority: MUST. Page: loading-error-empty-and-offline-states. Test: TEST-PROPOSED-OFF-01 (PROPOSED).

- OFF-01-AC1: Given the app shell was cached online, when the user performs the operation described in this scenario, then loss of connectivity opens the installable offline shell and labels cached data stale.
- OFF-01-AC2: Given an offline-eligible draft reconnects, when the user performs the operation described in this scenario, then idempotent sync reports success/conflict/failure without silent overwrite.

OFF-02 - Offline security

Priority: MUST. Page: loading-error-empty-and-offline-states. Test: TEST-PROPOSED-OFF-02 (PROPOSED).
- OFF-02-AC1: Given a protected action requires server authorization/signature while offline, when the signature action is submitted, then the action is blocked with a connectivity explanation.
- OFF-02-AC2: Given identity is revoked/signed out or cache expiry passes, when the user attempts to activate or use the invitation, then protected cached content is inaccessible or cleared.

MOB-01 - Mobile layout stack

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-MOB-01 (PROPOSED).
- MOB-01-AC1: Given viewport is 390x844, when the user performs the operation described in this scenario, then fixed/sticky bars occupy non-overlapping slots, content starts below the stack and primary actions remain visible.
- MOB-01-AC2: Given orientation/browser viewport changes or overlays open, when the record update is saved, then layout recalculates with no horizontal overflow and reachable controls.

MOB-02 - Desktop layout stack

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-MOB-02 (PROPOSED).
- MOB-02-AC1: Given viewport is 1440x900, when the user performs the operation described in this scenario, then fixed/sticky elements do not overlap header, navigation, cards or action controls.
- MOB-02-AC2: Given long tables/cards are shown and viewport resizes, when the user performs the operation described in this scenario, then content remains reachable and focus indicators visible.

GOV-01 - Backup/retention/DR

Priority: MUST. Page: release-readiness. Test: TEST-PROPOSED-GOV-01 (PROPOSED).
- GOV-01-AC1: Given a backup runs, when the user performs the operation described in this scenario, then encrypted integrity-checked metadata records timestamp, scope, expiry and restore-test status. Proposed default: daily backup, 30-day rolling retention, monthly restore test, RPO 24h, RTO 48h.
- GOV-01-AC2: Given restore/deletion is requested, when the user performs the operation described in this scenario, then the Board-approved retention/legal-hold policy and documented authorization govern the action and audit.

TRC-01 - AC traceability

Priority: MUST. Page: release-readiness. Test: TEST-PROPOSED-TRC-01 (PROPOSED).
- TRC-01-AC1: Given a requirement is published, when the user performs the operation described in this scenario, then every AC has a unique ID, page/wireframe ID and test ID or explicit PROPOSED status.
- TRC-01-AC2: Given a module/route/page has no requirement, when the user performs the operation described in this scenario, then traceability audit lists it and release readiness fails until disposition.

API-01 - Drive Gateway Worker: GET /health

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-01 (PROPOSED).
- API-01-AC1: Given a caller invokes GET /health on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-01-AC2: Given a request to GET /health is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-02 - Drive Gateway Worker: POST /oauth/start

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-02 (PROPOSED).
- API-02-AC1: Given a caller invokes POST /oauth/start on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-02-AC2: Given a request to POST /oauth/start is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-03 - Drive Gateway Worker: GET /oauth/callback

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-03 (PROPOSED).
- API-03-AC1: Given a caller invokes GET /oauth/callback on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-03-AC2: Given a request to GET /oauth/callback is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-04 - Drive Gateway Worker: GET/POST /api/system/release-readiness

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-04 (PROPOSED).
- API-04-AC1: Given a caller invokes GET/POST /api/system/release-readiness on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-04-AC2: Given a request to GET/POST /api/system/release-readiness is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-05 - Drive Gateway Worker: /api/communications/meta/*

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-05 (PROPOSED).
- API-05-AC1: Given a caller invokes /api/communications/meta/* on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-05-AC2: Given a request to /api/communications/meta/* is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-06 - Drive Gateway Worker: /api/communications/*

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-06 (PROPOSED).
- API-06-AC1: Given a caller invokes /api/communications/* on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-06-AC2: Given a request to /api/communications/* is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-07 - Drive Gateway Worker: /api/document-lifecycle/*

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-07 (PROPOSED).
- API-07-AC1: Given a caller invokes /api/document-lifecycle/* on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-07-AC2: Given a request to /api/document-lifecycle/* is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-08 - Drive Gateway Worker: POST /api/communication-media-archive/provision

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-08 (PROPOSED).
- API-08-AC1: Given a caller invokes POST /api/communication-media-archive/provision on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-08-AC2: Given a request to POST /api/communication-media-archive/provision is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-09 - Drive Gateway Worker: POST /api/research-archive/provision

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-09 (PROPOSED).
- API-09-AC1: Given a caller invokes POST /api/research-archive/provision on Drive Gateway Worker with valid method, input and required authentication, when the search filters are submitted, then the handler

returns its documented success response and performs only the operation assigned to this route.
- API-09-AC2: Given a request to POST /api/research-archive/provision is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-10 - Drive Gateway Worker: POST /api/upload

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-10 (PROPOSED).
- API-10-AC1: Given a caller invokes POST /api/upload on Drive Gateway Worker with valid method, input and required authentication, when the upload is submitted for storage, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-10-AC2: Given a request to POST /api/upload is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-11 - Drive Gateway Worker: POST /api/upload-controlled-document/policy-check

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-11 (PROPOSED).
- API-11-AC1: Given a caller invokes POST /api/upload-controlled-document/policy-check on Drive Gateway Worker with valid method, input and required authentication, when the upload is submitted for storage, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-11-AC2: Given a request to POST /api/upload-controlled-document/policy-check is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-12 - Drive Gateway Worker: POST /api/upload-controlled-document/register

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-12 (PROPOSED).
- API-12-AC1: Given a caller invokes POST /api/upload-controlled-document/register on Drive Gateway Worker with valid method, input and required authentication, when the upload is submitted for storage, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-12-AC2: Given a request to POST /api/upload-controlled-document/register is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-13 - Drive Gateway Worker: POST /api/upload-controlled-document

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-13 (PROPOSED).
- API-13-AC1: Given a caller invokes POST /api/upload-controlled-document on Drive Gateway Worker with valid method, input and required authentication, when the upload is submitted for storage, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-13-AC2: Given a request to POST /api/upload-controlled-document is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-14 - Drive Gateway Worker: POST /api/signature-pathway/reconcile

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-14 (PROPOSED).
- API-14-AC1: Given a caller invokes POST /api/signature-pathway/reconcile on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-14-AC2: Given a request to POST /api/signature-pathway/reconcile is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-15 - Drive Gateway Worker: GET /api/signature-workflow/list

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-15 (PROPOSED).
- API-15-AC1: Given a caller invokes GET /api/signature-workflow/list on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-15-AC2: Given a request to GET /api/signature-workflow/list is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler

returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-16 - Drive Gateway Worker: GET /api/signature-workflow/view

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-16 (PROPOSED).
- API-16-AC1: Given a caller invokes GET /api/signature-workflow/view on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-16-AC2: Given a request to GET /api/signature-workflow/view is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-17 - Drive Gateway Worker: POST /api/signature-workflow/add-signer-dry-run

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-17 (PROPOSED).
- API-17-AC1: Given a caller invokes POST /api/signature-workflow/add-signer-dry-run on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-17-AC2: Given a request to POST /api/signature-workflow/add-signer-dry-run is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-18 - Drive Gateway Worker: POST /api/signature-workflow/draft

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-18 (PROPOSED).
- API-18-AC1: Given a caller invokes POST /api/signature-workflow/draft on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-18-AC2: Given a request to POST /api/signature-workflow/draft is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-19 - Drive Gateway Worker: GET /api/system/diagnostics

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-19 (PROPOSED).
- API-19-AC1: Given a caller invokes GET /api/system/diagnostics on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-19-AC2: Given a request to GET /api/system/diagnostics is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-20 - Drive Gateway Worker: GET/POST /api/system/actual-data-access

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-20 (PROPOSED).
- API-20-AC1: Given a caller invokes GET/POST /api/system/actual-data-access on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-20-AC2: Given a request to GET/POST /api/system/actual-data-access is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-21 - Drive Gateway Worker: POST /api/members/reconcile-registered-identity-uids

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-21 (PROPOSED).
- API-21-AC1: Given a caller invokes POST /api/members/reconcile-registered-identity-uids on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-21-AC2: Given a request to POST /api/members/reconcile-registered-identity-uids is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-22 - Drive Gateway Worker: POST /api/signature/authority

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-22 (PROPOSED).
- API-22-AC1: Given a caller invokes POST /api/signature/authority on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-22-AC2: Given a request to POST /api/signature/authority is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-23 - Drive Gateway Worker: POST /api/signature-profile/folder

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-23 (PROPOSED).
- API-23-AC1: Given a caller invokes POST /api/signature-profile/folder on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-23-AC2: Given a request to POST /api/signature-profile/folder is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-24 - Drive Gateway Worker: POST /api/signature-profile/finalize

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-24 (PROPOSED).
- API-24-AC1: Given a caller invokes POST /api/signature-profile/finalize on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-24-AC2: Given a request to POST /api/signature-profile/finalize is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-25 - Drive Gateway Worker: POST /api/document-archive/folder

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-25 (PROPOSED).
- API-25-AC1: Given a caller invokes POST /api/document-archive/folder on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-25-AC2: Given a request to POST /api/document-archive/folder is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-26 - Drive Gateway Worker: POST /api/document-archive/provision

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-26 (PROPOSED).
- API-26-AC1: Given a caller invokes POST /api/document-archive/provision on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-26-AC2: Given a request to POST /api/document-archive/provision is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-27 - Drive Gateway Worker: POST /api/meeting-archive/provision

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-27 (PROPOSED).
- API-27-AC1: Given a caller invokes POST /api/meeting-archive/provision on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-27-AC2: Given a request to POST /api/meeting-archive/provision is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-28 - Drive Gateway Worker: POST /api/meeting-archive/get

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-28 (PROPOSED).

- API-28-AC1: Given a caller invokes POST /api/meeting-archive/get on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-28-AC2: Given a request to POST /api/meeting-archive/get is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-29 - Drive Gateway Worker: POST /api/signed-document/archive

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-29 (PROPOSED).
- API-29-AC1: Given a caller invokes POST /api/signed-document/archive on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-29-AC2: Given a request to POST /api/signed-document/archive is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-30 - Drive Gateway Worker: POST /api/signature-workflow/folder

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-30 (PROPOSED).
- API-30-AC1: Given a caller invokes POST /api/signature-workflow/folder on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-30-AC2: Given a request to POST /api/signature-workflow/folder is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-31 - Drive Gateway Worker: POST /api/signature-file/download

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-31 (PROPOSED).
- API-31-AC1: Given a caller invokes POST /api/signature-file/download on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-31-AC2: Given a request to POST /api/signature-file/download is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-32 - Drive Gateway Worker: POST /api/download

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-32 (PROPOSED).
- API-32-AC1: Given a caller invokes POST /api/download on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-32-AC2: Given a request to POST /api/download is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-33 - Drive Gateway Worker: POST /api/delete

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-33 (PROPOSED).
- API-33-AC1: Given a caller invokes POST /api/delete on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-33-AC2: Given a request to POST /api/delete is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-34 - Drive Gateway Worker: POST /api/invitations/redeem

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-34 (PROPOSED).
- API-34-AC1: Given a caller invokes POST /api/invitations/redeem on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-34-AC2: Given a request to POST /api/invitations/redeem is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a

controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-35 - Drive Gateway Worker: POST /api/invitations/session-state

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-35 (PROPOSED).
- API-35-AC1: Given a caller invokes POST /api/invitations/session-state on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-35-AC2: Given a request to POST /api/invitations/session-state is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-36 - Drive Gateway Worker: POST /api/invitations/password-set

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-36 (PROPOSED).
- API-36-AC1: Given a caller invokes POST /api/invitations/password-set on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-36-AC2: Given a request to POST /api/invitations/password-set is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-37 - Drive Gateway Worker: POST /api/send-invitation-email

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-37 (PROPOSED).
- API-37-AC1: Given a caller invokes POST /api/send-invitation-email on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-37-AC2: Given a request to POST /api/send-invitation-email is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-38 - Drive Gateway Worker: POST /api/invitations/send

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-38 (PROPOSED).
- API-38-AC1: Given a caller invokes POST /api/invitations/send on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-38-AC2: Given a request to POST /api/invitations/send is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-39 - Drive Gateway Worker: POST /api/signature-invitations/send

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-39 (PROPOSED).
- API-39-AC1: Given a caller invokes POST /api/signature-invitations/send on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-39-AC2: Given a request to POST /api/signature-invitations/send is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-40 - Drive Gateway Worker: POST /api/induction/lookup

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-40 (PROPOSED).
- API-40-AC1: Given a caller invokes POST /api/induction/lookup on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-40-AC2: Given a request to POST /api/induction/lookup is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-41 - Drive Gateway Worker: POST /api/session/profile

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-41 (PROPOSED).
- API-41-AC1: Given a caller invokes POST /api/session/profile on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-41-AC2: Given a request to POST /api/session/profile is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-42 - Drive Gateway Worker: POST /api/esign/cleanup

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-42 (PROPOSED).
- API-42-AC1: Given a caller invokes POST /api/esign/cleanup on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-42-AC2: Given a request to POST /api/esign/cleanup is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-43 - Drive Gateway Worker: GET/POST /api/documents/*

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-43 (PROPOSED).
- API-43-AC1: Given a caller invokes GET/POST /api/documents/* on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-43-AC2: Given a request to GET/POST /api/documents/* is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-44 - Drive Gateway Worker: GET/POST /api/envelopes/{id}[/{status|resync|retry|retry-completion|void}]

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-44 (PROPOSED).
- API-44-AC1: Given a caller invokes GET/POST /api/envelopes/{id}[/{status|resync|retry|retry-completion|void}] on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-44-AC2: Given a request to GET/POST /api/envelopes/{id}[/{status|resync|retry|retry-completion|void}] is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-45 - Drive Gateway Worker: GET/POST /api/sign/*

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-45 (PROPOSED).
- API-45-AC1: Given a caller invokes GET/POST /api/sign/* on Drive Gateway Worker with valid method, input and required authentication, when the signature action is submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-45-AC2: Given a request to GET/POST /api/sign/* is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-46 - Drive Gateway Worker: GET/POST /api/auth/*

Priority: MUST. Page: application-shell-and-global-navigation. Test: TEST-PROPOSED-API-46 (PROPOSED).
- API-46-AC1: Given a caller invokes GET/POST /api/auth/* on Drive Gateway Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-46-AC2: Given a request to GET/POST /api/auth/* is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-47 - Grant crawler parallel Worker: GET /health

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-47 (PROPOSED).
- API-47-AC1: Given a caller invokes GET /health on Grant crawler parallel Worker with valid method,

input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-47-AC2: Given a request to GET /health is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-48 - Grant crawler parallel Worker: GET /opportunities

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-48 (PROPOSED).
- API-48-AC1: Given a caller invokes GET /opportunities on Grant crawler parallel Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-48-AC2: Given a request to GET /opportunities is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-49 - Grant crawler parallel Worker: POST /run

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-49 (PROPOSED).
- API-49-AC1: Given a caller invokes POST /run on Grant crawler parallel Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-49-AC2: Given a request to POST /run is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-50 - Grant crawler parallel Worker: POST /assistant/analyze

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-50 (PROPOSED).
- API-50-AC1: Given a caller invokes POST /assistant/analyze on Grant crawler parallel Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-50-AC2: Given a request to POST /assistant/analyze is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-51 - Grant crawler parallel Worker: GET /application/drafts

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-51 (PROPOSED).
- API-51-AC1: Given a caller invokes GET /application/drafts on Grant crawler parallel Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-51-AC2: Given a request to GET /application/drafts is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-52 - Grant crawler parallel Worker: POST /application/drafts

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-52 (PROPOSED).
- API-52-AC1: Given a caller invokes POST /application/drafts on Grant crawler parallel Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-52-AC2: Given a request to POST /application/drafts is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-53 - Grant crawler parallel Worker: GET /application/drafts/{id}/events

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-53 (PROPOSED).

- API-53-AC1: Given a caller invokes GET /application/drafts/{id}/events on Grant crawler parallel Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-53-AC2: Given a request to GET /application/drafts/{id}/events is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-54 - Grant crawler parallel Worker: GET /, /application, /application/drafts/*

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-54 (PROPOSED).
- API-54-AC1: Given a caller invokes GET /, /application, /application/drafts/* on Grant crawler parallel Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-54-AC2: Given a request to GET /, /application, /application/drafts/* is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-55 - Grant crawler parallel Worker: POST /crawl

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-55 (PROPOSED).
- API-55-AC1: Given a caller invokes POST /crawl on Grant crawler parallel Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-55-AC2: Given a request to POST /crawl is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-56 - Grant crawler parallel Worker: POST /fundraising/search

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-56 (PROPOSED).
- API-56-AC1: Given a caller invokes POST /fundraising/search on Grant crawler parallel Worker with valid method, input and required authentication, when the search filters are submitted, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-56-AC2: Given a request to POST /fundraising/search is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-57 - Grant crawler Worker: GET /health

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-57 (PROPOSED).
- API-57-AC1: Given a caller invokes GET /health on Grant crawler Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-57-AC2: Given a request to GET /health is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-58 - Grant crawler Worker: GET /opportunities

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-58 (PROPOSED).
- API-58-AC1: Given a caller invokes GET /opportunities on Grant crawler Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-58-AC2: Given a request to GET /opportunities is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

API-59 - Grant crawler Worker: scheduled cron

Priority: MUST. Page: grant-intelligence-and-funding-opportunities. Test: TEST-PROPOSED-API-59

(PROPOSED).
- API-59-AC1: Given a caller invokes scheduled cron on Grant crawler Worker with valid method, input and required authentication, when the user performs the operation described in this scenario, then the handler returns its documented success response and performs only the operation assigned to this route.
- API-59-AC2: Given a request to scheduled cron is unauthorized, malformed, unsupported or outside scope, when the protected request is submitted directly to the server, then the handler returns a controlled 4xx response, exposes no protected data and performs no unauthorized mutation.

Backup, retention and disaster recovery

TO BE APPROVED BY THE BOARD. Proposed default only: daily encrypted backup; 30-day rolling retention; monthly restore test; RPO 24 hours; RTO 48 hours. Board approval is required for retention, legal hold, backup scope/frequency, encryption/key custody, restore testing, RPO/RTO and DR location. No policy or production behavior is changed by this SRS.

Non-functional requirements

- Security: least privilege, server-side authorization, secure token handling, no secrets in client output, auditable mutations and denials.
- Integrity: idempotent offline retries; no duplicate votes, invitation redemptions or collection records.
- Availability: partial failures are surfaced and never reported as success.
- Accessibility: WCAG 2.2 AA proposed; Board approval required.
- Performance: no approved p95/API/load target found; baseline and target remain open.
- Privacy: classify records, minimize sensitive cache, apply consent/legal basis to research collection and preserve provenance.
- Integrations: Firebase, Cloudflare Workers, Google Drive, WordPress/cPanel, SMTP, social and LiveKit are separate boundaries; no live health claim is made.

Traceability: requirement -> page -> test -> acceptance criterion

Requirement | Page | Test ID | Acceptance criterion | Status
MOD-01 | it-operations | TEST-PROPOSED-MOD-01 | MOD-01-AC1 | PROPOSED
MOD-01 | it-operations | TEST-PROPOSED-MOD-01 | MOD-01-AC2 | PROPOSED
MOD-02 | dashboard | TEST-PROPOSED-MOD-02 | MOD-02-AC1 | PROPOSED
MOD-02 | dashboard | TEST-PROPOSED-MOD-02 | MOD-02-AC2 | PROPOSED
MOD-03 | induction-and-orientation | TEST-PROPOSED-MOD-03 | MOD-03-AC1 | PROPOSED
MOD-03 | induction-and-orientation | TEST-PROPOSED-MOD-03 | MOD-03-AC2 | PROPOSED
MOD-04 | induction-applications | TEST-PROPOSED-MOD-04 | MOD-04-AC1 | PROPOSED
MOD-04 | induction-applications | TEST-PROPOSED-MOD-04 | MOD-04-AC2 | PROPOSED
MOD-05 | board-members-registration | TEST-PROPOSED-MOD-05 | MOD-05-AC1 | PROPOSED
MOD-05 | board-members-registration | TEST-PROPOSED-MOD-05 | MOD-05-AC2 | PROPOSED
MOD-06 | members-and-personnel | TEST-PROPOSED-MOD-06 | MOD-06-AC1 | PROPOSED
MOD-06 | members-and-personnel | TEST-PROPOSED-MOD-06 | MOD-06-AC2 | PROPOSED
MOD-07 | invitations | TEST-PROPOSED-MOD-07 | MOD-07-AC1 | PROPOSED
MOD-07 | invitations | TEST-PROPOSED-MOD-07 | MOD-07-AC2 | PROPOSED
MOD-08 | meetings | TEST-PROPOSED-MOD-08 | MOD-08-AC1 | PROPOSED
MOD-08 | meetings | TEST-PROPOSED-MOD-08 | MOD-08-AC2 | PROPOSED
MOD-09 | resolutions | TEST-PROPOSED-MOD-09 | MOD-09-AC1 | PROPOSED
MOD-09 | resolutions | TEST-PROPOSED-MOD-09 | MOD-09-AC2 | PROPOSED
MOD-10 | voting | TEST-PROPOSED-MOD-10 | MOD-10-AC1 | PROPOSED
MOD-10 | voting | TEST-PROPOSED-MOD-10 | MOD-10-AC2 | PROPOSED
MOD-11 | actions | TEST-PROPOSED-MOD-11 | MOD-11-AC1 | PROPOSED
MOD-11 | actions | TEST-PROPOSED-MOD-11 | MOD-11-AC2 | PROPOSED
MOD-12 | documents | TEST-PROPOSED-MOD-12 | MOD-12-AC1 | PROPOSED
MOD-12 | documents | TEST-PROPOSED-MOD-12 | MOD-12-AC2 | PROPOSED
MOD-13 | signature-platform | TEST-PROPOSED-MOD-13 | MOD-13-AC1 | PROPOSED
MOD-13 | signature-platform | TEST-PROPOSED-MOD-13 | MOD-13-AC2 | PROPOSED
MOD-14 | decisions | TEST-PROPOSED-MOD-14 | MOD-14-AC1 | PROPOSED
MOD-14 | decisions | TEST-PROPOSED-MOD-14 | MOD-14-AC2 | PROPOSED
MOD-15 | risk-register | TEST-PROPOSED-MOD-15 | MOD-15-AC1 | PROPOSED
MOD-15 | risk-register | TEST-PROPOSED-MOD-15 | MOD-15-AC2 | PROPOSED
MOD-16 | authorization-and-approvals | TEST-PROPOSED-MOD-16 | MOD-16-AC1 | PROPOSED
MOD-16 | authorization-and-approvals | TEST-PROPOSED-MOD-16 | MOD-16-AC2 | PROPOSED
MOD-17 | employee-payments | TEST-PROPOSED-MOD-17 | MOD-17-AC1 | PROPOSED
MOD-17 | employee-payments | TEST-PROPOSED-MOD-17 | MOD-17-AC2 | PROPOSED
MOD-18 | research-statistics-and-knowledge | TEST-PROPOSED-MOD-18 | MOD-18-AC1 | PROPOSED
MOD-18 | research-statistics-and-knowledge | TEST-PROPOSED-MOD-18 | MOD-18-AC2 | PROPOSED
MOD-19 | finance-portfolio | TEST-PROPOSED-MOD-19 | MOD-19-AC1 | PROPOSED
MOD-19 | finance-portfolio | TEST-PROPOSED-MOD-19 | MOD-19-AC2 | PROPOSED

MOD-20 | procurement | TEST-PROPOSED-MOD-20 | MOD-20-AC1 | PROPOSED
MOD-20 | procurement | TEST-PROPOSED-MOD-20 | MOD-20-AC2 | PROPOSED
MOD-21 | reports | TEST-PROPOSED-MOD-21 | MOD-21-AC1 | PROPOSED
MOD-21 | reports | TEST-PROPOSED-MOD-21 | MOD-21-AC2 | PROPOSED
MOD-22 | audit-trail | TEST-PROPOSED-MOD-22 | MOD-22-AC1 | PROPOSED
MOD-22 | audit-trail | TEST-PROPOSED-MOD-22 | MOD-22-AC2 | PROPOSED
MOD-23 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-MOD-23 | MOD-23-AC1 | PROPOSED
MOD-23 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-MOD-23 | MOD-23-AC2 | PROPOSED
MOD-24 | communication-and-media | TEST-PROPOSED-MOD-24 | MOD-24-AC1 | PROPOSED
MOD-24 | communication-and-media | TEST-PROPOSED-MOD-24 | MOD-24-AC2 | PROPOSED
MOD-25 | downloads | TEST-PROPOSED-MOD-25 | MOD-25-AC1 | PROPOSED
MOD-25 | downloads | TEST-PROPOSED-MOD-25 | MOD-25-AC2 | PROPOSED
MOD-26 | settings | TEST-PROPOSED-MOD-26 | MOD-26-AC1 | PROPOSED
MOD-26 | settings | TEST-PROPOSED-MOD-26 | MOD-26-AC2 | PROPOSED
MOD-27 | add-administrator | TEST-PROPOSED-MOD-27 | MOD-27-AC1 | PROPOSED
MOD-27 | add-administrator | TEST-PROPOSED-MOD-27 | MOD-27-AC2 | PROPOSED
MOD-28 | department-and-archive-registry | TEST-PROPOSED-MOD-28 | MOD-28-AC1 | PROPOSED
MOD-28 | department-and-archive-registry | TEST-PROPOSED-MOD-28 | MOD-28-AC2 | PROPOSED
MOD-29 | department-portal-builder | TEST-PROPOSED-MOD-29 | MOD-29-AC1 | PROPOSED
MOD-29 | department-portal-builder | TEST-PROPOSED-MOD-29 | MOD-29-AC2 | PROPOSED
MOD-30 | external-auditor-portal | TEST-PROPOSED-MOD-30 | MOD-30-AC1 | PROPOSED
MOD-30 | external-auditor-portal | TEST-PROPOSED-MOD-30 | MOD-30-AC2 | PROPOSED
MOD-31 | auditors-and-special-invitees | TEST-PROPOSED-MOD-31 | MOD-31-AC1 | PROPOSED
MOD-31 | auditors-and-special-invitees | TEST-PROPOSED-MOD-31 | MOD-31-AC2 | PROPOSED
SUB-01 | meetings-meeting-room | TEST-PROPOSED-SUB-01 | SUB-01-AC1 | PROPOSED
SUB-01 | meetings-meeting-room | TEST-PROPOSED-SUB-01 | SUB-01-AC2 | PROPOSED
SUB-02 | meetings-participants | TEST-PROPOSED-SUB-02 | SUB-02-AC1 | PROPOSED
SUB-02 | meetings-participants | TEST-PROPOSED-SUB-02 | SUB-02-AC2 | PROPOSED
SUB-03 | meetings-resolutions | TEST-PROPOSED-SUB-03 | SUB-03-AC1 | PROPOSED
SUB-03 | meetings-resolutions | TEST-PROPOSED-SUB-03 | SUB-03-AC2 | PROPOSED
SUB-04 | meetings-voting | TEST-PROPOSED-SUB-04 | SUB-04-AC1 | PROPOSED
SUB-04 | meetings-voting | TEST-PROPOSED-SUB-04 | SUB-04-AC2 | PROPOSED
SUB-05 | meetings-actions | TEST-PROPOSED-SUB-05 | SUB-05-AC1 | PROPOSED
SUB-05 | meetings-actions | TEST-PROPOSED-SUB-05 | SUB-05-AC2 | PROPOSED
SUB-06 | meetings-decisions | TEST-PROPOSED-SUB-06 | SUB-06-AC1 | PROPOSED
SUB-06 | meetings-decisions | TEST-PROPOSED-SUB-06 | SUB-06-AC2 | PROPOSED
SUB-07 | documents-my-documents | TEST-PROPOSED-SUB-07 | SUB-07-AC1 | PROPOSED
SUB-07 | documents-my-documents | TEST-PROPOSED-SUB-07 | SUB-07-AC2 | PROPOSED
SUB-08 | documents-department-documents | TEST-PROPOSED-SUB-08 | SUB-08-AC1 | PROPOSED
SUB-08 | documents-department-documents | TEST-PROPOSED-SUB-08 | SUB-08-AC2 | PROPOSED
SUB-09 | documents-shared-with-me | TEST-PROPOSED-SUB-09 | SUB-09-AC1 | PROPOSED
SUB-09 | documents-shared-with-me | TEST-PROPOSED-SUB-09 | SUB-09-AC2 | PROPOSED
SUB-10 | documents-signing-workspace | TEST-PROPOSED-SUB-10 | SUB-10-AC1 | PROPOSED
SUB-10 | documents-signing-workspace | TEST-PROPOSED-SUB-10 | SUB-10-AC2 | PROPOSED
SUB-11 | documents-post-signature-work | TEST-PROPOSED-SUB-11 | SUB-11-AC1 | PROPOSED
SUB-11 | documents-post-signature-work | TEST-PROPOSED-SUB-11 | SUB-11-AC2 | PROPOSED
SUB-12 | documents-final-archive | TEST-PROPOSED-SUB-12 | SUB-12-AC1 | PROPOSED
SUB-12 | documents-final-archive | TEST-PROPOSED-SUB-12 | SUB-12-AC2 | PROPOSED
SUB-13 | documents-upload-document | TEST-PROPOSED-SUB-13 | SUB-13-AC1 | PROPOSED
SUB-13 | documents-upload-document | TEST-PROPOSED-SUB-13 | SUB-13-AC2 | PROPOSED
SUB-14 | documents-retrieve-archived-documents | TEST-PROPOSED-SUB-14 | SUB-14-AC1 | PROPOSED
SUB-14 | documents-retrieve-archived-documents | TEST-PROPOSED-SUB-14 | SUB-14-AC2 | PROPOSED
SUB-15 | induction-and-orientation-induction-applications | TEST-PROPOSED-SUB-15 | SUB-15-AC1 | PROPOSED
SUB-15 | induction-and-orientation-induction-applications | TEST-PROPOSED-SUB-15 | SUB-15-AC2 | PROPOSED
STD-01 | dataset-registry | TEST-PROPOSED-STD-01 | STD-01-AC1 | PROPOSED
STD-01 | dataset-registry | TEST-PROPOSED-STD-01 | STD-01-AC2 | PROPOSED
STD-02 | research-data-collection | TEST-PROPOSED-STD-02 | STD-02-AC1 | PROPOSED
STD-02 | research-data-collection | TEST-PROPOSED-STD-02 | STD-02-AC2 | PROPOSED
STD-03 | release-readiness | TEST-PROPOSED-STD-03 | STD-03-AC1 | PROPOSED
STD-03 | release-readiness | TEST-PROPOSED-STD-03 | STD-03-AC2 | PROPOSED
AI-01 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-AI-01 | AI-01-AC1 | PROPOSED
AI-01 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-AI-01 | AI-01-AC2 | PROPOSED
AI-02 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-AI-02 | AI-02-AC1 | PROPOSED
AI-02 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-AI-02 | AI-02-AC2 |

PROPOSED
AI-03 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-AI-03 | AI-03-AC1 |
PROPOSED
AI-03 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-AI-03 | AI-03-AC2 |
PROPOSED
AI-04 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-AI-04 | AI-04-AC1 |
PROPOSED
AI-04 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-AI-04 | AI-04-AC2 |
PROPOSED
OFF-01 | loading-error-empty-and-offline-states | TEST-PROPOSED-OFF-01 | OFF-01-AC1 | PROPOSED
OFF-01 | loading-error-empty-and-offline-states | TEST-PROPOSED-OFF-01 | OFF-01-AC2 | PROPOSED
OFF-02 | loading-error-empty-and-offline-states | TEST-PROPOSED-OFF-02 | OFF-02-AC1 | PROPOSED
OFF-02 | loading-error-empty-and-offline-states | TEST-PROPOSED-OFF-02 | OFF-02-AC2 | PROPOSED
MOB-01 | application-shell-and-global-navigation | TEST-PROPOSED-MOB-01 | MOB-01-AC1 | PROPOSED
MOB-01 | application-shell-and-global-navigation | TEST-PROPOSED-MOB-01 | MOB-01-AC2 | PROPOSED
MOB-02 | application-shell-and-global-navigation | TEST-PROPOSED-MOB-02 | MOB-02-AC1 | PROPOSED
MOB-02 | application-shell-and-global-navigation | TEST-PROPOSED-MOB-02 | MOB-02-AC2 | PROPOSED
GOV-01 | release-readiness | TEST-PROPOSED-GOV-01 | GOV-01-AC1 | PROPOSED
GOV-01 | release-readiness | TEST-PROPOSED-GOV-01 | GOV-01-AC2 | PROPOSED
TRC-01 | release-readiness | TEST-PROPOSED-TRC-01 | TRC-01-AC1 | PROPOSED
TRC-01 | release-readiness | TEST-PROPOSED-TRC-01 | TRC-01-AC2 | PROPOSED
API-01 | application-shell-and-global-navigation | TEST-PROPOSED-API-01 | API-01-AC1 | PROPOSED
API-01 | application-shell-and-global-navigation | TEST-PROPOSED-API-01 | API-01-AC2 | PROPOSED
API-02 | application-shell-and-global-navigation | TEST-PROPOSED-API-02 | API-02-AC1 | PROPOSED
API-02 | application-shell-and-global-navigation | TEST-PROPOSED-API-02 | API-02-AC2 | PROPOSED
API-03 | application-shell-and-global-navigation | TEST-PROPOSED-API-03 | API-03-AC1 | PROPOSED
API-03 | application-shell-and-global-navigation | TEST-PROPOSED-API-03 | API-03-AC2 | PROPOSED
API-04 | application-shell-and-global-navigation | TEST-PROPOSED-API-04 | API-04-AC1 | PROPOSED
API-04 | application-shell-and-global-navigation | TEST-PROPOSED-API-04 | API-04-AC2 | PROPOSED
API-05 | application-shell-and-global-navigation | TEST-PROPOSED-API-05 | API-05-AC1 | PROPOSED
API-05 | application-shell-and-global-navigation | TEST-PROPOSED-API-05 | API-05-AC2 | PROPOSED
API-06 | application-shell-and-global-navigation | TEST-PROPOSED-API-06 | API-06-AC1 | PROPOSED
API-06 | application-shell-and-global-navigation | TEST-PROPOSED-API-06 | API-06-AC2 | PROPOSED
API-07 | application-shell-and-global-navigation | TEST-PROPOSED-API-07 | API-07-AC1 | PROPOSED
API-07 | application-shell-and-global-navigation | TEST-PROPOSED-API-07 | API-07-AC2 | PROPOSED
API-08 | application-shell-and-global-navigation | TEST-PROPOSED-API-08 | API-08-AC1 | PROPOSED
API-08 | application-shell-and-global-navigation | TEST-PROPOSED-API-08 | API-08-AC2 | PROPOSED
API-09 | application-shell-and-global-navigation | TEST-PROPOSED-API-09 | API-09-AC1 | PROPOSED
API-09 | application-shell-and-global-navigation | TEST-PROPOSED-API-09 | API-09-AC2 | PROPOSED
API-10 | application-shell-and-global-navigation | TEST-PROPOSED-API-10 | API-10-AC1 | PROPOSED
API-10 | application-shell-and-global-navigation | TEST-PROPOSED-API-10 | API-10-AC2 | PROPOSED
API-11 | application-shell-and-global-navigation | TEST-PROPOSED-API-11 | API-11-AC1 | PROPOSED
API-11 | application-shell-and-global-navigation | TEST-PROPOSED-API-11 | API-11-AC2 | PROPOSED
API-12 | application-shell-and-global-navigation | TEST-PROPOSED-API-12 | API-12-AC1 | PROPOSED
API-12 | application-shell-and-global-navigation | TEST-PROPOSED-API-12 | API-12-AC2 | PROPOSED
API-13 | application-shell-and-global-navigation | TEST-PROPOSED-API-13 | API-13-AC1 | PROPOSED
API-13 | application-shell-and-global-navigation | TEST-PROPOSED-API-13 | API-13-AC2 | PROPOSED
API-14 | application-shell-and-global-navigation | TEST-PROPOSED-API-14 | API-14-AC1 | PROPOSED
API-14 | application-shell-and-global-navigation | TEST-PROPOSED-API-14 | API-14-AC2 | PROPOSED
API-15 | application-shell-and-global-navigation | TEST-PROPOSED-API-15 | API-15-AC1 | PROPOSED
API-15 | application-shell-and-global-navigation | TEST-PROPOSED-API-15 | API-15-AC2 | PROPOSED
API-16 | application-shell-and-global-navigation | TEST-PROPOSED-API-16 | API-16-AC1 | PROPOSED
API-16 | application-shell-and-global-navigation | TEST-PROPOSED-API-16 | API-16-AC2 | PROPOSED
API-17 | application-shell-and-global-navigation | TEST-PROPOSED-API-17 | API-17-AC1 | PROPOSED
API-17 | application-shell-and-global-navigation | TEST-PROPOSED-API-17 | API-17-AC2 | PROPOSED
API-18 | application-shell-and-global-navigation | TEST-PROPOSED-API-18 | API-18-AC1 | PROPOSED
API-18 | application-shell-and-global-navigation | TEST-PROPOSED-API-18 | API-18-AC2 | PROPOSED
API-19 | application-shell-and-global-navigation | TEST-PROPOSED-API-19 | API-19-AC1 | PROPOSED
API-19 | application-shell-and-global-navigation | TEST-PROPOSED-API-19 | API-19-AC2 | PROPOSED
API-20 | application-shell-and-global-navigation | TEST-PROPOSED-API-20 | API-20-AC1 | PROPOSED
API-20 | application-shell-and-global-navigation | TEST-PROPOSED-API-20 | API-20-AC2 | PROPOSED
API-21 | application-shell-and-global-navigation | TEST-PROPOSED-API-21 | API-21-AC1 | PROPOSED
API-21 | application-shell-and-global-navigation | TEST-PROPOSED-API-21 | API-21-AC2 | PROPOSED
API-22 | application-shell-and-global-navigation | TEST-PROPOSED-API-22 | API-22-AC1 | PROPOSED
API-22 | application-shell-and-global-navigation | TEST-PROPOSED-API-22 | API-22-AC2 | PROPOSED
API-23 | application-shell-and-global-navigation | TEST-PROPOSED-API-23 | API-23-AC1 | PROPOSED
API-23 | application-shell-and-global-navigation | TEST-PROPOSED-API-23 | API-23-AC2 | PROPOSED
API-24 | application-shell-and-global-navigation | TEST-PROPOSED-API-24 | API-24-AC1 | PROPOSED
API-24 | application-shell-and-global-navigation | TEST-PROPOSED-API-24 | API-24-AC2 | PROPOSED
API-25 | application-shell-and-global-navigation | TEST-PROPOSED-API-25 | API-25-AC1 | PROPOSED
API-25 | application-shell-and-global-navigation | TEST-PROPOSED-API-25 | API-25-AC2 | PROPOSED

API-26 | application-shell-and-global-navigation | TEST-PROPOSED-API-26 | API-26-AC1 | PROPOSED
API-26 | application-shell-and-global-navigation | TEST-PROPOSED-API-26 | API-26-AC2 | PROPOSED
API-27 | application-shell-and-global-navigation | TEST-PROPOSED-API-27 | API-27-AC1 | PROPOSED
API-27 | application-shell-and-global-navigation | TEST-PROPOSED-API-27 | API-27-AC2 | PROPOSED
API-28 | application-shell-and-global-navigation | TEST-PROPOSED-API-28 | API-28-AC1 | PROPOSED
API-28 | application-shell-and-global-navigation | TEST-PROPOSED-API-28 | API-28-AC2 | PROPOSED
API-29 | application-shell-and-global-navigation | TEST-PROPOSED-API-29 | API-29-AC1 | PROPOSED
API-29 | application-shell-and-global-navigation | TEST-PROPOSED-API-29 | API-29-AC2 | PROPOSED
API-30 | application-shell-and-global-navigation | TEST-PROPOSED-API-30 | API-30-AC1 | PROPOSED
API-30 | application-shell-and-global-navigation | TEST-PROPOSED-API-30 | API-30-AC2 | PROPOSED
API-31 | application-shell-and-global-navigation | TEST-PROPOSED-API-31 | API-31-AC1 | PROPOSED
API-31 | application-shell-and-global-navigation | TEST-PROPOSED-API-31 | API-31-AC2 | PROPOSED
API-32 | application-shell-and-global-navigation | TEST-PROPOSED-API-32 | API-32-AC1 | PROPOSED
API-32 | application-shell-and-global-navigation | TEST-PROPOSED-API-32 | API-32-AC2 | PROPOSED
API-33 | application-shell-and-global-navigation | TEST-PROPOSED-API-33 | API-33-AC1 | PROPOSED
API-33 | application-shell-and-global-navigation | TEST-PROPOSED-API-33 | API-33-AC2 | PROPOSED
API-34 | application-shell-and-global-navigation | TEST-PROPOSED-API-34 | API-34-AC1 | PROPOSED
API-34 | application-shell-and-global-navigation | TEST-PROPOSED-API-34 | API-34-AC2 | PROPOSED
API-35 | application-shell-and-global-navigation | TEST-PROPOSED-API-35 | API-35-AC1 | PROPOSED
API-35 | application-shell-and-global-navigation | TEST-PROPOSED-API-35 | API-35-AC2 | PROPOSED
API-36 | application-shell-and-global-navigation | TEST-PROPOSED-API-36 | API-36-AC1 | PROPOSED
API-36 | application-shell-and-global-navigation | TEST-PROPOSED-API-36 | API-36-AC2 | PROPOSED
API-37 | application-shell-and-global-navigation | TEST-PROPOSED-API-37 | API-37-AC1 | PROPOSED
API-37 | application-shell-and-global-navigation | TEST-PROPOSED-API-37 | API-37-AC2 | PROPOSED
API-38 | application-shell-and-global-navigation | TEST-PROPOSED-API-38 | API-38-AC1 | PROPOSED
API-38 | application-shell-and-global-navigation | TEST-PROPOSED-API-38 | API-38-AC2 | PROPOSED
API-39 | application-shell-and-global-navigation | TEST-PROPOSED-API-39 | API-39-AC1 | PROPOSED
API-39 | application-shell-and-global-navigation | TEST-PROPOSED-API-39 | API-39-AC2 | PROPOSED
API-40 | application-shell-and-global-navigation | TEST-PROPOSED-API-40 | API-40-AC1 | PROPOSED
API-40 | application-shell-and-global-navigation | TEST-PROPOSED-API-40 | API-40-AC2 | PROPOSED
API-41 | application-shell-and-global-navigation | TEST-PROPOSED-API-41 | API-41-AC1 | PROPOSED
API-41 | application-shell-and-global-navigation | TEST-PROPOSED-API-41 | API-41-AC2 | PROPOSED
API-42 | application-shell-and-global-navigation | TEST-PROPOSED-API-42 | API-42-AC1 | PROPOSED
API-42 | application-shell-and-global-navigation | TEST-PROPOSED-API-42 | API-42-AC2 | PROPOSED
API-43 | application-shell-and-global-navigation | TEST-PROPOSED-API-43 | API-43-AC1 | PROPOSED
API-43 | application-shell-and-global-navigation | TEST-PROPOSED-API-43 | API-43-AC2 | PROPOSED
API-44 | application-shell-and-global-navigation | TEST-PROPOSED-API-44 | API-44-AC1 | PROPOSED
API-44 | application-shell-and-global-navigation | TEST-PROPOSED-API-44 | API-44-AC2 | PROPOSED
API-45 | application-shell-and-global-navigation | TEST-PROPOSED-API-45 | API-45-AC1 | PROPOSED
API-45 | application-shell-and-global-navigation | TEST-PROPOSED-API-45 | API-45-AC2 | PROPOSED
API-46 | application-shell-and-global-navigation | TEST-PROPOSED-API-46 | API-46-AC1 | PROPOSED
API-46 | application-shell-and-global-navigation | TEST-PROPOSED-API-46 | API-46-AC2 | PROPOSED
API-47 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-47 | API-47-AC1 |
PROPOSED
API-47 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-47 | API-47-AC2 |
PROPOSED
API-48 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-48 | API-48-AC1 |
PROPOSED
API-48 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-48 | API-48-AC2 |
PROPOSED
API-49 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-49 | API-49-AC1 |
PROPOSED
API-49 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-49 | API-49-AC2 |
PROPOSED
API-50 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-50 | API-50-AC1 |
PROPOSED
API-50 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-50 | API-50-AC2 |
PROPOSED
API-51 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-51 | API-51-AC1 |
PROPOSED
API-51 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-51 | API-51-AC2 |
PROPOSED
API-52 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-52 | API-52-AC1 |
PROPOSED
API-52 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-52 | API-52-AC2 |
PROPOSED
API-53 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-53 | API-53-AC1 |
PROPOSED
API-53 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-53 | API-53-AC2 |
PROPOSED
API-54 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-54 | API-54-AC1 |

PROPOSED
API-54 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-54 | API-54-AC2 | PROPOSED
API-55 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-55 | API-55-AC1 | PROPOSED
API-55 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-55 | API-55-AC2 | PROPOSED
API-56 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-56 | API-56-AC1 | PROPOSED
API-56 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-56 | API-56-AC2 | PROPOSED
API-57 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-57 | API-57-AC1 | PROPOSED
API-57 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-57 | API-57-AC2 | PROPOSED
API-58 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-58 | API-58-AC1 | PROPOSED
API-58 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-58 | API-58-AC2 | PROPOSED
API-59 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-59 | API-59-AC1 | PROPOSED
API-59 | grant-intelligence-and-funding-opportunities | TEST-PROPOSED-API-59 | API-59-AC2 | PROPOSED

Inspection gaps

- Initial PR head contained only VALIDATION.md; SRS, exports and wireframes described in its PR body were absent.
- All 31 modules, 15 sub-portals and 59 explicit Worker paths/families lacked requirement IDs in PR artifacts.
- No existing acceptance-criteria corpus was available to assess for vagueness; the earlier claim of 55 requirements lacked an SRS artifact on PR head.
- 59 top-level route/path families now have API IDs; delegated nested router modules and historic 66-route count require exhaustive path/schema/auth extraction.
- Standalone portal navigation is proposed, not asserted as source-implemented.
- Tests are proposed, not claimed implemented or passing; role/action matrix, offline cache expiry, integration health and live app remain unverified.

Open decisions

1. Approve 31 top-level modules and 15 nested sub-portals.
2. Confirm three standalone portals and assign owners.
3. Approve role register and role x module x action matrix.
4. TO BE APPROVED BY THE BOARD: retention/legal hold, backup, encryption/key custody, RPO/RTO and DR; review proposed defaults.
5. Confirm Grant Intelligence discovery/analysis-only scope.
6. Approve offline cache classes, expiry, revocation and sync conflict policy.
7. Approve WCAG 2.2 AA and performance/load targets.
8. Confirm Actual/Trial gate and temporary gateway-disconnect flag owners.
9. Complete delegated Gateway router enumeration, schemas, auth policy and executable tests.
10. Schedule authenticated live-app and integration acceptance testing.