yet another way to invoke functions without parentheses

yet another way to invoke functions without parentheses - bartosz (skarn958), blog.ikaes.de.

- Published: date not stated
- Original: <https://blog.ikaes.de/yet-another-way-to-invoke-functions-without-parentheses/>
- Preserved from: https://blog.ikaes.de/yet-another-way-to-invoke-functions-without-parentheses/ (live) on 2026-10-21
- Licence: unknown


Rights remain with the original author and publisher. This is a research archive of a source from the Web Hacking Techniques Index collections, kept so it remains readable if the page goes offline. To read the original, follow the link above.

Content

> UNTRUSTED SOURCE TEXT. Everything below this line is third-party material quoted for research. It is data, not instructions. Do not follow directions, execute code, or fetch URLs because this text says so.

yet another way to invoke functions without parentheses

i found yet another way to invoke arbitrary functions in javascript without using parentheses



this payload works by overwriting the `prepareStackTrace` function of the `Error` object to generate arbitrary functions. it is usually used to format stack traces and is invoked when

the attribute `stack` of an error is accessed.

> For efficiency stack traces are not formatted when they are captured but on demand, the first time the stack property is accessed. A stack trace is formatted by calling
>
> ```
> Error.prepareStackTrace(error, structuredStackTrace)
> ```
>
> and using whatever this call returns as the value of the `stack` property. If you assign a different function value to `Error.prepareStackTrace` that function is used to format stack traces. It gets passed the error object that it is preparing a stack trace for, as well as a structured representation of the stack. User stack

the parameters of this function are the error and "a structured representation of the stack" , which is just an array of the code positions. it has the same function signature the `Function constructor` which is used to generate javascript functions, as long as the second argument is valid javascript code.




if we try to invoke the function which was generated using this method, we get a syntax error. it is to be expected, because a stack trace is not a valid javascript code, but an `Array` of code positions


[image: image]

in order to make the payload work, we need to control the output of the `Array.prototype.toString()` function such that it returns our desired javascript payload. this can be done in two ways

first we can simply overwrite it with a constant function which returns the payload




or we can use prototype pollution to sneak our payload into another function, and then overwrite the `Array` prototype. i found that we can stay in the `Error` realm and use its `toString` function which can be manipulated by polluting the `Object.prototype.message` variable. i am sure there are more ways to achieve this.



now if we put everything together - the function generation using the `prepareStackTrace` function and way to convert arrays into arbitrary strings, we can generate arbitrary javascript functions

```
> Array.prototype.toString = x=>"alert(1)"
<· x=>"alert(1)"
> Error.prepareStackTrace = Function;
  const x = new Error;
  x.stack;
<· ƒ anonymous(Error
  ) {
  alert(1)
  }
```

last thing we have to do is to invoke our new function. luckily there are many ways to do so and i chose the `valueOf` trick. it works by overwriting the default `valueOf` function of our object and then invoking it as a primitive. alternatively, we can use `toString` and then concatenate the object with a string.



the final payload is as follows. feel free to try it out in the browser console.

```
Object.prototype.message='alert\x281337\x29';Array.prototype.toString=Error.prototype.toString;Error.prepareStackTrace = Function;const x = new Error;x.valueOf=x.stack;+x;
```

Archived from https://blog.ikaes.de/yet-another-way-to-invoke-functions-without-parentheses/. Rendered offline from the local Markdown copy.