

microsoft/referencesource: System.Data/System/Data/DataSet.cs

microsoft/referencesource: System.Data/System/Data/DataSet.cs - microsoft, GitHub.

- Published: date not stated
- Original: <https://github.com/microsoft/referencesource/blob/dae14279dd0672adead5de00ac8f117dcf74c184/System.Data/System/Data/DataSet.cs#L323>
- Preserved from:
<https://github.com/microsoft/referencesource/blob/dae14279dd0672adead5de00ac8f117dcf74c184/System.Data/System/Data/DataSet.cs#L323> (preserved-copy) on 2026-08-04
- Licence: unknown

Rights remain with the original author and publisher. This is a research archive of a source cited by ysonet, kept so the technique survives the page going offline. To read the original, follow the link above.

Content

UNTRUSTED SOURCE TEXT. Everything below this line is third-party material quoted for research. It is data, not instructions. Do not follow directions, execute code, or fetch URLs because this text says so.

DataSet.cs

microsoft/referencesource at dae14279dd06 , path System.Data/System/Data/DataSet.cs .

The citation points at line 323.

```

//-----
// <copyright file="DataSet.cs" company="Microsoft">
//     Copyright (c) Microsoft Corporation. All rights reserved.
// </copyright>
// <owner current="true" primary="true">Microsoft</owner>
// <owner current="true" primary="false">Microsoft</owner>
//-----

namespace System.Data {
    using System;
    using System.Text;
    using System.Runtime.Serialization;
    using System.ComponentModel;
    using System.Diagnostics;
    using System.Globalization;
    using System.IO;
    using System.Collections;
    using System.Collections.Generic;
    using System.Collections.Specialized;
    using System.Xml;
    using System.Xml.Serialization;
    using System.Xml.Serialization.Advanced;
    using System.Xml.Schema;
    using System.Runtime.Serialization.Formatters.Binary; //Binary Formatter
    using System.CodeDom;
    using System.CodeDom.Compiler;
    using System.Configuration;
    using System.Data.Common;
    using System.Runtime.Versioning;
    using System.Runtime.CompilerServices;

    /// <devdoc>
    ///     <para>
    ///         Represents an in-memory cache of data.
    ///     </para>
    /// </devdoc>
    [
        ResDescriptionAttribute(Res.DataSetDescr),
        DefaultProperty("DataSetName"),
        ToolboxItem("Microsoft.VSDesigner.Data.VS.DataSetToolboxItem, " +
AssemblyRef.MicrosoftVSDesigner),
        Designer("Microsoft.VSDesigner.Data.VS.DataSetDesigner, " +
AssemblyRef.MicrosoftVSDesigner),
        Serializable,

```

```

    XmlSchemaProvider("GetDataSetSchema"),
    XmlRoot("DataSet")
}

public class DataSet : MarshalByValueComponent, System.ComponentModel.IListSource,
IXmlSerializable, ISupportInitializeNotification, ISerializable {

    private DataViewManager defaultManager;

    // Public Collections
    private readonly DataTableCollection tableCollection;
    private readonly DataRelationCollection relationCollection;
    internal PropertyCollection extendedProperties = null;
    private string dataSetName = "NewDataSet";
    private string _datasetPrefix = String.Empty;
    internal string namespaceURI = string.Empty;
    private bool enforceConstraints = true;
    private const String KEY_XMLSCHEMA = "XmlSchema";
    private const String KEY_XMLDIFFGRAM = "XmlDiffGram";

    // globalization stuff
    private bool _caseSensitive;
    private CultureInfo _culture;
    private bool _cultureUserSet;

    // Internal definitions
    internal bool fInReadXml = false;
    internal bool fInLoadDiffgram = false;
    internal bool fTopLevelTable = false;
    internal bool fInitInProgress = false;
    internal bool fEnableCascading = true;
    internal bool fIsSchemaLoading = false;
    private bool fBoundToDocument; // for XmlDataDocument

    // Events
    private PropertyChangedEventHandler onPropertyChangingDelegate;
    private MergeFailedEventHandler onMergeFailed;
    private DataRowCreatedEventHandler onDataRowCreated; // Internal for
    XmlDataDocument only
    private DataSetClearEventHandler onClearFunctionCalled; // Internal for
    XmlDataDocument only
    private System.EventHandler onInitialized;

    internal readonly static DataTable[] zeroTables = new DataTable[0];

```

```

internal string mainTableName = "";

//default remoting format is XML
private SerializationFormat _remotingFormat = SerializationFormat.Xml;

private object _defaultViewManagerLock = new Object();

private static int _objectTypeCount; // Bid counter
private readonly int _objectID = System.Threading.Interlocked.Increment(ref
_objectTypeCount);
private static XmlSchemaComplexType schemaTypeForWSDL = null;

internal bool UseDataSetSchemaOnly; // UseDataSetSchemaOnly , for YUKON
internal bool UdtIsWrapped; // if UDT is wrapped , for YUKON

/// <devdoc>
/// <para>Initializes a new instance of the <see cref='System.Data.DataSet'/>
class.</para>
/// </devdoc>
public DataSet() {
    GC.SuppressFinalize(this);
    Bid.Trace("<ds.DataSet.DataSet|API> %d#\n", ObjectID); // others will call
this constr
    // Set default locale
    this.tableCollection = new DataTableCollection(this);
    this.relationCollection = new
DataRelationCollection.DataSetRelationCollection(this);
    _culture = CultureInfo.CurrentCulture; // Set default locale
}

/// <devdoc>
/// <para>Initializes a new instance of a <see cref='System.Data.DataSet'/>
/// class with the given name.</para>
/// </devdoc>
public DataSet(string dataSetName)
    : this()
{
    this.DataSetName = dataSetName;
}

[
DefaultValue(SerializationFormat.Xml)
]
public SerializationFormat RemotingFormat {

```

```

        get {
            return _remotingFormat;
        }
        set {
            if (value != SerializationFormat.Binary && value !=
SerializationFormat.Xml) {
                throw ExceptionBuilder.InvalidRemotingFormat(value);
            }
            _remotingFormat = value;
            // this property is inherited to DataTable from DataSet. So we set this
value to DataTable also
            for (int i = 0; i < Tables.Count; i++) {
                Tables[i].RemotingFormat = value;
            }
        }
    }

    [BrowsableAttribute(false)]
    [DesignerSerializationVisibility(DesignerSerializationVisibility.Hidden)]
    public virtual SchemaSerializationMode SchemaSerializationMode { //Typed DataSet
calls into this
        get {
            return SchemaSerializationMode.IncludeSchema;
        }
        set {
            if (value != SchemaSerializationMode.IncludeSchema) {
                throw ExceptionBuilder.CannotChangeSchemaSerializationMode();
            }
        }
    }

    //      Check whether the stream is binary serialized.
    // 'static' function that consumes SerializationInfo
    protected bool IsBinarySerialized(SerializationInfo info, StreamingContext
context) {// mainly for typed DS
        // our default remoting format is XML
        SerializationFormat remotingFormat = SerializationFormat.Xml;
        SerializationInfoEnumerator e = info.GetEnumerator();

        while (e.MoveNext()) {
            if (e.Name == "DataSet.RemotingFormat") {//DataSet.RemotingFormat does
not exist in V1/V1.1 versions
                remotingFormat = (SerializationFormat)e.Value;
                break;
            }
        }
    }

```

```

    }
}
return (remotingFormat == SerializationFormat.Binary);
}

//      Should Schema be included during Serialization
// 'static' function that consumes SerializationInfo
protected SchemaSerializationMode
DetermineSchemaSerializationMode(SerializationInfo info, StreamingContext context) {
//Typed DataSet calls into this
    SchemaSerializationMode schemaSerializationMode =
SchemaSerializationMode.IncludeSchema;
    SerializationInfoEnumerator e = info.GetEnumerator();

    while (e.MoveNext()) {
        if (e.Name == "SchemaSerializationMode.DataSet") {
//SchemaSerializationMode.DataSet does not exist in V1/V1.1 versions
            schemaSerializationMode = (SchemaSerializationMode)e.Value;
            break;
        }
    }
    return schemaSerializationMode;
}

protected SchemaSerializationMode DetermineSchemaSerializationMode(XmlReader
reader) { //Typed DataSet calls into this
    SchemaSerializationMode schemaSerializationMode =
SchemaSerializationMode.IncludeSchema;
    reader.MoveToContent();
    if (reader.NodeType == XmlNodeType.Element) {
        if (reader.HasAttributes) {
            string attribValue =
reader.GetAttribute(Keywords.MSD_SCHEMASERIALIZATIONMODE, Keywords.MSDNS);
            if ((String.Compare(attribValue, Keywords.MSD_EXCLUDESCHEMA,
StringComparison.OrdinalIgnoreCase) == 0)) {
                schemaSerializationMode = SchemaSerializationMode.ExcludeSchema;
            }
            else if ((String.Compare(attribValue, Keywords.MSD_INCLUDESCHEMA,
StringComparison.OrdinalIgnoreCase) == 0)) {
                schemaSerializationMode = SchemaSerializationMode.IncludeSchema;
            }
            else if (attribValue != null) { // if attrib does not exist, then
don't throw
                throw

```

```

ExceptionBuilder.InvalidSchemaSerializationMode(typeof(SchemaSerializationMode),
attribValue);
    }
}
}
return schemaSerializationMode;
}

//      Deserialize all the tables data of the dataset from binary/xml stream.
// 'instance' method that consumes SerializationInfo
protected void GetSerializationData(SerializationInfo info, StreamingContext
context) { // mainly for typed DS
    SerializationFormat remotingFormat = SerializationFormat.Xml;
    SerializationInfoEnumerator e = info.GetEnumerator();

    while (e.MoveNext()) {
        if (e.Name == "DataSet.RemotingFormat") { //DataSet.RemotingFormat does
not exist in V1/V1.1 versions
            remotingFormat = (SerializationFormat)e.Value;
            break;
        }
    }
    DeserializeDataSetData(info, context, remotingFormat);
}

//      Deserialize all the tables schema and data of the dataset from binary/xml
stream.
protected DataSet(SerializationInfo info, StreamingContext context)
: this(info, context, true) {
}
protected DataSet(SerializationInfo info, StreamingContext context, bool
ConstructSchema)
: this() {
    SerializationFormat remotingFormat = SerializationFormat.Xml;
    SchemaSerializationMode schemaSerializationMode =
SchemaSerializationMode.IncludeSchema;
    SerializationInfoEnumerator e = info.GetEnumerator();

    while (e.MoveNext()) {
        switch (e.Name) {
            case "DataSet.RemotingFormat": //DataSet.RemotingFormat does not
exist in V1/V1.1 versions

```

```

        remotingFormat = (SerializationFormat)e.Value;
        break;
        case "SchemaSerializationMode.DataSet":
//SchemaSerializationMode.DataSet does not exist in V1/V1.1 versions
        schemaSerializationMode = (SchemaSerializationMode)e.Value;
        break;
    }
}

if (schemaSerializationMode == SchemaSerializationMode.ExcludeSchema) {
    InitializeDerivedDataSet();
}

// adding back this check will fix typed dataset XML remoting, but we have to
fix case that
// a class inherits from DataSet and just relies on DataSet to deserialize
(see SQL BU DT 374717)
// to fix that case also, we need to add a flag and add it to below check so
return (no-op) will be
// conditional (flag needs to be set in TypedDataSet
if (remotingFormat == SerializationFormat.Xml && !ConstructSchema /* &&
this.GetType() != typeof(DataSet)*/) {
    return; //For typed dataset xml remoting, this is a no-op
}
DeserializeDataSet(info, context, remotingFormat, schemaSerializationMode);
}

```

```

[System.Security.Permissions.SecurityPermissionAttribute(System.Security.Permissions.Secu
rityAction.LinkDemand, Flags =
System.Security.Permissions.SecurityPermissionFlag.SerializationFormatter)]

```

```

    public virtual void GetObjectData(SerializationInfo info, StreamingContext
context) {

```

```

        SerializationFormat remotingFormat = RemotingFormat;
        SerializeDataSet(info, context, remotingFormat);
    }

```

```

//      Deserialize all the tables data of the dataset from binary/xml stream.

```

```

protected virtual void InitializeDerivedDataSet() {
    return;
}

```

```

        //      Serialize all the tables.
        private void SerializeDataSet(SerializationInfo info, StreamingContext context,
        SerializationFormat remotingFormat) {
            Debug.Assert(info != null);
            info.AddValue("DataSet.RemotingVersion", new Version(2, 0));

            // SqlHotFix 299, SerializationFormat enumeration types don't exist in V1.1
        SP1
            if (SerializationFormat.Xml != remotingFormat) {
                info.AddValue("DataSet.RemotingFormat", remotingFormat);
            }

            // SqlHotFix 299, SchemaSerializationMode enumeration types don't exist in
        V1.1 SP1
            if (SchemaSerializationMode.IncludeSchema != SchemaSerializationMode) {
                //SkipSchemaDuringSerialization
                info.AddValue("SchemaSerializationMode.DataSet",
        SchemaSerializationMode);
            }

            if (remotingFormat != SerializationFormat.Xml) {
                if (SchemaSerializationMode == SchemaSerializationMode.IncludeSchema) {

                    //DataSet public state properties
                    SerializeDataSetProperties(info, context);

                    //Tables Count
                    info.AddValue("DataSet.Tables.Count", Tables.Count);

                    //Tables, Columns, Rows
                    for (int i = 0; i < Tables.Count; i++) {
                        BinaryFormatter bf = new BinaryFormatter(null, new
        StreamingContext(context.State, false));
                        MemoryStream memStream = new MemoryStream();
                        bf.Serialize(memStream, Tables[i]);
                        memStream.Position = 0;
                        info.AddValue(String.Format(CultureInfo.InvariantCulture,
        "DataSet.Tables_{0}", i), memStream.GetBuffer());
                    }

                    //Constraints
                    for (int i = 0; i < Tables.Count; i++) {
                        Tables[i].SerializeConstraints(info, context, i, true);
                    }
                }
            }
        }
    }

```

```

        //Relations
        SerializeRelations(info, context);

        //Expression Columns
        for (int i = 0; i < Tables.Count; i++) {
            Tables[i].SerializeExpressionColumns(info, context, i);
        }
    }
    else {
        //Serialize DataSet public properties.
        SerializeDataSetProperties(info, context);
    }
    //Rows
    for (int i = 0; i < Tables.Count; i++) {
        Tables[i].SerializeTableData(info, context, i);
    }
} else { // old behaviour

    String strSchema = this.GetXmlSchemaForRemoting(null);

    String strData = null;
    info.AddValue(KEY_XMLSCHEMA, strSchema);

    StringBuilder strBuilder;
    strBuilder = new StringBuilder(EstimatedXmlStringSize() * 2);
    StringWriter strWriter = new StringWriter(strBuilder,
CultureInfo.InvariantCulture);
    XmlTextWriter w = new XmlTextWriter(strWriter);
    WriteXml(w, XmlWriteMode.DiffGram);
    strData = strWriter.ToString();
    info.AddValue(KEY_XMLDIFFGRAM, strData);
}
}

//      Deserialize all the tables - marked internal so that DataTable can call
into this
    internal void DeserializeDataSet(SerializationInfo info, StreamingContext
context, SerializationFormat remotingFormat, SchemaSerializationMode
schemaSerializationMode) {
        // deserialize schema
        DeserializeDataSetSchema(info, context, remotingFormat,
schemaSerializationMode);
        // deserialize data

```

```

        DeserializeDataSetData(info, context, remotingFormat);
    }

    //      Deserialize schema.
    private void DeserializeDataSetSchema(SerializationInfo info, StreamingContext
context, SerializationFormat remotingFormat, SchemaSerializationMode
schemaSerializationMode) {
        if (remotingFormat != SerializationFormat.Xml) {
            if (schemaSerializationMode == SchemaSerializationMode.IncludeSchema) {
                //DataSet public state properties
                DeserializeDataSetProperties(info, context);

                //Tables Count
                int tableCount = info.GetInt32("DataSet.Tables.Count");

                //Tables, Columns, Rows
                for (int i = 0; i < tableCount; i++) {
                    Byte[] buffer =
(Byte[][])info.GetValue(String.Format(CultureInfo.InvariantCulture, "DataSet.Tables_{0}",
i), typeof(Byte[]));

                    MemoryStream memStream = new MemoryStream(buffer);
                    memStream.Position = 0;
                    BinaryFormatter bf = new BinaryFormatter(null, new
StreamingContext(context.State, false));
                    DataTable dt = (DataTable)bf.Deserialize(memStream);
                    Tables.Add(dt);
                }

                //Constraints
                for (int i = 0; i < tableCount; i++) {
                    Tables[i].DeserializeConstraints(info, context, /* table index
*/i, /* serialize all constraints */ true); //
                }

                //Relations
                DeserializeRelations(info, context);

                //Expression Columns
                for (int i = 0; i < tableCount; i++) {
                    Tables[i].DeserializeExpressionColumns(info, context, i);
                }
            } else {
                //DeSerialize DataSet public properties.[Locale, CaseSensitive and
EnforceConstraints]
            }
        }
    }

```

```

        DeserializeDataSetProperties(info, context);
    }
} else {
    string strSchema = (String)info.GetValue(KEY_XMLSCHEMA,
typeof(System.String));

    if (strSchema != null) {
        this.ReadXmlSchema(new XmlTextReader(new StringReader(strSchema)),
true);
    }
}

//      Deserialize all data.
private void DeserializeDataSetData(SerializationInfo info, StreamingContext
context, SerializationFormat remotingFormat) {
    if (remotingFormat != SerializationFormat.Xml) {
        for (int i = 0; i < Tables.Count; i++) {
            Tables[i].DeserializeTableData(info, context, i);
        }
    }
    else {
        string strData = (String)info.GetValue(KEY_XMLDIFFGRAM,
typeof(System.String));

        if (strData != null) {
            this.ReadXml(new XmlTextReader(new StringReader(strData)),
XmlReadMode.DiffGram);
        }
    }
}

//      Serialize just the dataset properties
private void SerializeDataSetProperties(SerializationInfo info, StreamingContext
context) {
    //DataSet basic properties
    info.AddValue("DataSet.DataSetName", DataSetName);
    info.AddValue("DataSet.Namespace", Namespace);
    info.AddValue("DataSet.Prefix", Prefix);
    //DataSet runtime properties
    info.AddValue("DataSet.CaseSensitive", CaseSensitive);
    info.AddValue("DataSet.LocaleLCID", Locale.LCID);
    info.AddValue("DataSet.EnforceConstraints", EnforceConstraints);
}

```

```

        //ExtendedProperties
        info.AddValue("DataSet.ExtendedProperties", ExtendedProperties);
    }

    //      DeSerialize dataset properties
    private void DeserializeDataSetProperties(SerializationInfo info,
StreamingContext context) {
        //DataSet basic properties
        dataSetName = info.GetString("DataSet.DataSetName");
        namespaceURI = info.GetString("DataSet.Namespace");
        _datasetPrefix = info.GetString("DataSet.Prefix");
        //DataSet runtime properties
        _caseSensitive = info.GetBoolean("DataSet.CaseSensitive");
        int lcid = (int)info.GetValue("DataSet.LocaleLCID", typeof(int));
        _culture = new CultureInfo(lcid);
        _cultureUserSet = true;
        enforceConstraints = info.GetBoolean("DataSet.EnforceConstraints");

        //ExtendedProperties
        extendedProperties =
(PropertyCollection)info.GetValue("DataSet.ExtendedProperties",
typeof(PropertyCollection));
    }

    //      Gets relation info from the dataset.
    //      ***Schema for Serializing ArrayList of Relations***
    //      Relations -> [relationName]->[parentTableIndex, parentcolumnIndexes]->
[childTableIndex, childColumnIndexes]->[Nested]->[extendedProperties]
    private void SerializeRelations(SerializationInfo info, StreamingContext context)
    {
        ArrayList relationList = new ArrayList();

        foreach (DataRelation rel in Relations) {
            int[] parentInfo = new int[rel.ParentColumns.Length + 1];

            parentInfo[0] = Tables.IndexOf(rel.ParentTable);
            for (int j = 1; j < parentInfo.Length; j++) {
                parentInfo[j] = rel.ParentColumns[j - 1].Ordinal;
            }

            int[] childInfo = new int[rel.ChildColumns.Length + 1];
            childInfo[0] = Tables.IndexOf(rel.ChildTable);

```

```

        for (int j = 1; j < childInfo.Length; j++) {
            childInfo[j] = rel.ChildColumns[j - 1].Ordinal;
        }

        ArrayList list = new ArrayList();
        list.Add(rel.RelationName);
        list.Add(parentInfo);
        list.Add(childInfo);
        list.Add(rel.Nested);
        list.Add(rel.extendedProperties);

        relationList.Add(list);
    }
    info.AddValue("DataSet.Relations", relationList);
}

/*
    Adds relations to the dataset.
    ***Schema for Serializing ArrayList of Relations***
    Relations -> [relationName]->[parentTableIndex, parentcolumnIndexes]->
    [childTableIndex, childColumnIndexes]->[Nested]->[extendedProperties]
*/
private void DeserializeRelations(SerializationInfo info, StreamingContext
context) {
    ArrayList relationList = (ArrayList)info.GetValue("DataSet.Relations",
typeof(ArrayList));

    foreach (ArrayList list in relationList) {
        string relationName = (string)list[0];
        int[] parentInfo = (int[])list[1];
        int[] childInfo = (int[])list[2];
        bool isNested = (bool)list[3];
        PropertyCollection extendedProperties = (PropertyCollection)list[4];

        //ParentKey Columns.
        DataColumn[] parentkeyColumns = new DataColumn[parentInfo.Length - 1];
        for (int i = 0; i < parentkeyColumns.Length; i++) {
            parentkeyColumns[i] = Tables[parentInfo[0]].Columns[parentInfo[i +
1]];
        }

        //ChildKey Columns.
        DataColumn[] childkeyColumns = new DataColumn[childInfo.Length - 1];
        for (int i = 0; i < childkeyColumns.Length; i++) {

```

```

        childkeyColumns[i] = Tables[childInfo[0]].Columns[childInfo[i + 1]];
    }

    //Create the Relation, without any constraints[Assumption: The
constraints are added earlier than the relations]
    DataRelation rel = new DataRelation(relationName, parentkeyColumns,
childkeyColumns, false);
    rel.CheckMultipleNested = false; // disable the check for multiple nested
parent

    rel.Nested = isNested;
    rel.extendedProperties = extendedProperties;

    Relations.Add(rel);
    rel.CheckMultipleNested = true; // enable the check for multiple nested
parent
    }
}

internal void FailedEnableConstraints() {
    this.EnforceConstraints = false;
    throw ExceptionBuilder.EnforceConstraint();
}

/// <devdoc>
///     <para>
///         Gets or sets a value indicating whether string
///         comparisons within <see cref='System.Data.DataTable' />
///         objects are
///         case-sensitive.
///     </para>
/// </devdoc>
[
    ResCategoryAttribute(Res.DataCategory_Data),
    DefaultValue(false),
    ResDescriptionAttribute(Res.DataSetCaseSensitiveDescr)
]
public bool CaseSensitive {
    get {
        return _caseSensitive;
    }
    set {
        if (_caseSensitive != value)
        {
            bool oldValue = _caseSensitive;

```

```

        _caseSensitive = value;

        if (!ValidateCaseConstraint()) {
            _caseSensitive = oldValue;
            throw ExceptionBuilder.CannotChangeCaseLocale();
        }

        foreach (DataTable table in Tables) {
            table.SetCaseSensitiveValue(value, false, true);
        }
    }
}

bool System.ComponentModel.IListSource.ContainsListCollection {
    get {
        return true;
    }
}

/// <devdoc>
/// <para>Gets a custom view of the data contained by the <see
 cref='System.Data.DataSet' /> , one
///     that allows filtering, searching, and navigating through the custom data
view.</para>
/// </devdoc>
[Browsable(false), ResDescriptionAttribute(Res.DataSetDefaultViewDescr)]
public DataViewManager DefaultViewManager {
    get {
        if (defaultViewManager == null) {
            lock (_defaultViewManagerLock) {
                if (defaultViewManager == null) {
                    defaultViewManager = new DataViewManager(this, true);
                }
            }
        }
        return defaultViewManager;
    }
}

/// <devdoc>
/// <para>Gets or sets a value indicating whether constraint rules are
followed when
///     attempting any update operation.</para>

```

```

/// </devdoc>
[DefaultValue(true), ResDescriptionAttribute(Res.DataSetEnforceConstraintsDescr)]
public bool EnforceConstraints {
    get {
        return enforceConstraints;
    }
    set {
        IntPtr hscp;
        Bid.ScopeEnter(out hscp, "<ds.DataSet.set_EnforceConstraints|API> %d#,
%d{bool}\n", ObjectID, value);
        try {
            if (this.enforceConstraints != value) {
                if (value)
                    EnableConstraints();
                this.enforceConstraints = value;
            }
        }
        finally {
            Bid.ScopeLeave(ref hscp);
        }
    }
}

internal void RestoreEnforceConstraints(bool value) {
    this.enforceConstraints = value;
}

internal void EnableConstraints()
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.EnableConstraints|INFO> %d#\n",
ObjectID);
    try {
        bool errors = false;
        for (ConstraintEnumerator constraints = new ConstraintEnumerator(this);
constraints.Next(); ) {
            Constraint constraint = (Constraint)constraints.GetConstraint();
            errors |= constraint.IsConstraintViolated();
        }

        foreach (DataTable table in Tables) {
            foreach (DataColumn column in table.Columns) {
                if (!column.AllowDBNull) {
                    errors |= column.IsNotAllowDBNullViolated();
                }
            }
        }
    }
}

```

```

        }
        if (column.MaxLength >= 0) {
            errors |= column.IsMaxLengthViolated();
        }
    }
}

if (errors)
    this.FailedEnableConstraints();
}
finally {
    Bid.ScopeLeave(ref hscp);
}
}

/// <devdoc>
///     <para>Gets or
///         sets the name of this <see cref='System.Data.DataSet'/> .</para>
/// </devdoc>
[
    ResCategoryAttribute(Res.DataCategory_Data),
    DefaultValue(""),
    ResDescriptionAttribute(Res.DataSetDataSetNameDescr)
]
public string DataSetName {
    get {
        return dataSetName;
    }
    set {
        Bid.Trace("<ds.DataSet.set_DataSetName|API> %d#, '%ls'\n", ObjectID,
value);

        if (value != dataSetName) {
            if (value == null || value.Length == 0)
                throw ExceptionBuilder.SetDataSetNameToEmpty();
            DataTable conflicting = Tables[value, Namespace];
            if ((conflicting != null) && (!conflicting.fNestedInDataset))
                throw ExceptionBuilder.SetDataSetNameConflicting(value);
            RaisePropertyChanging("DataSetName");
            this.dataSetName = value;
        }
    }
}

/// <devdoc>

```

```

    /// </devdoc>
    [
    DefaultValue(""),
    ResCategoryAttribute(Res.DataCategory_Data),
    ResDescriptionAttribute(Res.DataSetNamespaceDescr)
    ]
    public string Namespace {
        get {
            return namespaceURI;
        }
        set {
            Bid.Trace("<ds.DataSet.set_Namespace|API> %d#, '%ls'\n", ObjectID,
value);

            if (value == null)
                value = String.Empty;
            if (value != namespaceURI) {
                RaisePropertyChanging("Namespace");
                foreach (DataTable dt in Tables) {
                    if (dt.tableNamespace != null)
                        continue;
                    if ((dt.NestedParentRelations.Length == 0) ||
                        (dt.NestedParentRelations.Length == 1 &&
dt.NestedParentRelations[0].ChildTable == dt)) {
                        // dt.SelfNestedWithOneRelation) {
// this is wrong bug it was previous behavior
                        if (Tables.Contains(dt.TableName, value, false, true))
                            throw ExceptionBuilder.DuplicateTableName2(dt.TableName,
value);

                        dt.CheckCascadingNamespaceConflict(value);
                        dt.DoRaiseNamespaceChange();
                    }
                }
                namespaceURI = value;

                if (Common.ADP.IsEmpty(value))
                    _datasetPrefix = String.Empty;
            }
        }
    }

    /// <devdoc>
    ///     <para>[To be supplied.]</para>
    /// </devdoc>

```

```

[
DefaultValue(""),
ResCategoryAttribute(Res.DataCategory_Data),
ResDescriptionAttribute(Res.DataSetPrefixDescr)
]
public string Prefix {
    get { return _datasetPrefix; }
    set {
        if (value == null)
            value = String.Empty;

        if ((XmlConvert.DecodeName(value) == value) &&
            (XmlConvert.EncodeName(value) != value))
            throw ExceptionBuilder.InvalidPrefix(value);

        if (value != _datasetPrefix) {
            RaisePropertyChanging("Prefix");
            _datasetPrefix = value;
        }
    }
}

/// <devdoc>
///     <para>Gets the collection of custom user information.</para>
/// </devdoc>
[
ResCategoryAttribute(Res.DataCategory_Data),
Browsable(false),
ResDescriptionAttribute(Res.ExtendedPropertiesDescr)
]
public PropertyCollection ExtendedProperties {
    get {
        if (extendedProperties == null) {
            extendedProperties = new PropertyCollection();
        }
        return extendedProperties;
    }
}

/// <devdoc>
///     <para>
///         Gets a value indicating whether there are errors in any
///         of the rows in any of the tables of this <see

```

```

    cref='System.Data.DataSet' /> .
    /// </para>
    /// </devdoc>
    [Browsable(false), ResDescriptionAttribute(Res.DataSetHasErrorsDescr)]
    public bool HasErrors {
        get {
            for (int i = 0; i < Tables.Count; i++) {
                if (Tables[i].HasErrors)
                    return true;
            }
            return false;
        }
    }

    [Browsable(false)]
    public bool IsInitialized {
        get {
            return !fInitInProgress;
        }
    }

    /// <devdoc>
    /// <para>
    ///     Gets or sets the locale information used to compare strings within the
table.
    /// </para>
    /// </devdoc>
    [
        ResCategoryAttribute(Res.DataCategory_Data),
        ResDescriptionAttribute(Res.DataSetLocaleDescr)
    ]
    public CultureInfo Locale {
        get {
            // used for comparing not formatting/parsing
            Debug.Assert(null != _culture, "DataSet.Locale: null culture");
            return _culture;
        }
        set {
            IntPtr hscp;
            Bid.ScopeEnter(out hscp, "<ds.DataSet.set_Locale|API> %d#\n", ObjectID);
            try {
                if (value != null) {
                    if (!_culture.Equals(value)) {
                        SetLocaleValue(value, true);
                    }
                }
            }
            finally {
                Bid.ScopeExit(hscp);
            }
        }
    }

```

```

        }
        _cultureUserSet = true;
    }
}
finally {
    Bid.ScopeLeave(ref hscp);
}
}
}

```

```

internal void SetLocaleValue(CultureInfo value, bool userSet) {

```

```

    bool flag = false;

```

```

    bool exceptionThrown = false;

```

```

    int tableCount = 0;

```

```

    CultureInfo oldLocale = _culture;

```

```

    bool oldUserSet = _cultureUserSet;

```

```

    try {

```

```

        _culture = value;

```

```

        _cultureUserSet = userSet;

```

```

        foreach (DataTable table in Tables) {

```

```

            if (!table.ShouldSerializeLocale()) {

```

```

                bool retchk = table.SetLocaleValue(value, false, false);

```

```

                //Debug.Assert(retchk == table.ShouldSerializeLocale(),

```

```

                "unexpected setting of table locale"); may fire with Deserialize

```

```

            }

```

```

        }

```

```

        flag = ValidateLocaleConstraint();

```

```

        if (flag) {

```

```

            flag = false;

```

```

            foreach (DataTable table in Tables) {

```

```

                tableCount++;

```

```

                if (!table.ShouldSerializeLocale()) {

```

```

                    table.SetLocaleValue(value, false, true);

```

```

                }

```

```

            }

```

```

            flag = true;

```

```

        }

```

```

    }

```

```

    catch {

```

```

        exceptionThrown = true;

```

```

        throw;
    }
    finally {
        if (!flag) { // reset old locale if ValidationFailed or exception thrown
            _culture = oldLocale;
            _cultureUserSet = oldUserSet;
            foreach (DataTable table in Tables) {
                if (!table.ShouldSerializeLocale()) {
                    table.SetLocaleValue(oldLocale, false, false);
                }
            }
            try {
                for (int i = 0; i < tableCount; ++i) {
                    if (!Tables[i].ShouldSerializeLocale()) {
                        Tables[i].SetLocaleValue(oldLocale, false, true);
                    }
                }
            }
            catch (Exception e) {
                if (!Common.ADP.IsCatchableExceptionType(e)) {
                    throw;
                }
                Common.ADP.TraceExceptionWithoutRethrow(e);
            }
            if (!exceptionThrown) {
                throw ExceptionBuilder.CannotChangeCaseLocale(null);
            }
        }
    }
}

```

```

internal bool ShouldSerializeLocale() {
    // this method is used design-time scenarios via reflection
    // by the property grid to show the Locale property in bold or not
    // by the code dom for persisting the Locale property or not

    // we always want the locale persisted if set by user or different the
current thread
    // but that logic should be performed by the serialization code
    return _cultureUserSet;
}

```

```

/// <devdoc>
///     <para>[To be supplied.]</para>

```

```

    /// </devdoc>
    [Browsable(false),
    DesignerSerializationVisibility(DesignerSerializationVisibility.Hidden)]
    public override ISite Site {
        get {
            return base.Site;
        }
        set {
            ISite oldSite = Site;
            if (value == null && oldSite != null) {
                IContainer cont = oldSite.Container;

                if (cont != null) {
                    for (int i = 0; i < Tables.Count; i++) {
                        if (Tables[i].Site != null) {
                            cont.Remove(Tables[i]);
                        }
                    }
                }
            }
            base.Site = value;
        }
    }

    /// <devdoc>
    ///     <para>
    ///         Get the collection of relations that link tables and
    ///         allow navigation from parent tables to child tables.
    ///     </para>
    /// </devdoc>
    [
    DesignerSerializationVisibility(DesignerSerializationVisibility.Content),
    ResCategoryAttribute(Res.DataCategory_Data),
    ResDescriptionAttribute(Res.DataSetRelationsDescr)
    ]
    public DataRelationCollection Relations {
        get {
            return relationCollection;
        }
    }
}

    /// <devdoc>

```

```

    /// <para>
    ///     Indicates whether <see cref='Relations'> property should be persisted.
    /// </para>
    /// </devdoc>
    protected virtual bool ShouldSerializeRelations() {
        return true; /*Relations.Count > 0;*/ // VS7 300569
    }

    /// <devdoc>
    /// <para>
    ///     Resets the <see cref='System.Data.DataSet.Relations'> property to its
default state.
    /// </para>
    /// </devdoc>
    private void ResetRelations()
    {
        Relations.Clear();
    }

    /// <devdoc>
    /// <para>Gets the collection of tables contained in the <see
cref='System.Data.DataSet'>.</para>
    /// </devdoc>
    [
        DesignerSerializationVisibility(DesignerSerializationVisibility.Content),
        ResCategoryAttribute(Res.DataCategory_Data),
        ResDescriptionAttribute(Res.DataSetTablesDescr)
    ]
    public DataTableCollection Tables {
        get {
            return tableCollection;
        }
    }

    /// <devdoc>
    /// <para>
    ///     Indicates whether <see cref='System.Data.DataSet.Tables'> property
should be persisted.
    /// </para>
    /// </devdoc>
    protected virtual bool ShouldSerializeTables() {
        return true; /*(Tables.Count > 0);*/ // VS7 300569
    }

```

```

    /// <devdoc>
    ///     <para>
    ///         Resets the <see cref='System.Data.DataSet.Tables'> property to its
default state.
    ///     </para>
    /// </devdoc>
    private void ResetTables()
    {
        Tables.Clear();
    }

    internal bool FBoundToDocument {
        get {
            return fBoundToDocument;
        }
        set {
            fBoundToDocument = value;
        }
    }

    /// <devdoc>
    ///     <para>
    ///         Commits all the changes made to this <see cref='System.Data.DataSet'>
since it was loaded or the last
    ///         time <see cref='System.Data.DataSet.AcceptChanges'> was called.
    ///     </para>
    /// </devdoc>
    public void AcceptChanges()
    {
        IntPtr hscp;
        Bid.ScopeEnter(out hscp, "<ds.DataSet.AcceptChanges|API> %d#\n", ObjectID);
        try {
            for (int i = 0; i < Tables.Count; i++)
                Tables[i].AcceptChanges();
        }
        finally {
            Bid.ScopeLeave(ref hscp);
        }
    }

    internal event PropertyChangedEventHandler PropertyChanging {
        add {
            onPropertyChangingDelegate += value;
        }
    }

```

```

        remove {
            onPropertyChangingDelegate -= value;
        }
    }

    /// <devdoc>
    ///     <para>Occurs when attempting to merge schemas for two tables with the same
    ///         name.</para>
    /// </devdoc>
    [
        ResCategoryAttribute(Res.DataCategory_Action),
        ResDescriptionAttribute(Res.DataSetMergeFailedDescr)
    ]
    public event MergeFailedEventHandler MergeFailed {
        add {
            onMergeFailed += value;
        }
        remove {
            onMergeFailed -= value;
        }
    }

    internal event DataRowCreatedEventHandler DataRowCreated {
        add {
            onDataRowCreated += value;
        }
        remove {
            onDataRowCreated -= value;
        }
    }

    internal event DataSetClearEventHandler ClearFunctionCalled {
        add {
            onClearFunctionCalled += value;
        }
        remove {
            onClearFunctionCalled -= value;
        }
    }

    [
        ResCategoryAttribute(Res.DataCategory_Action),
        ResDescriptionAttribute(Res.DataSetInitializedDescr)
    ]

```

```

public event System.EventHandler Initialized {
    add {
        onInitialized += value;
    }
    remove {
        onInitialized -= value;
    }
}

public void BeginInit() {
    fInitInProgress = true;
}

public void EndInit() {
    Tables.FinishInitCollection();
    for (int i = 0; i < Tables.Count; i++) {
        Tables[i].Columns.FinishInitCollection();
    }

    for (int i = 0; i < Tables.Count; i++) {
        Tables[i].Constraints.FinishInitConstraints();
    }
}

```

```

((DataRelationCollection.DataSetRelationCollection)Relations).FinishInitRelations();

```

```

    fInitInProgress = false;
    OnInitialized();
}

```

```

/// <devdoc>

```

```

/// <para>Clears the <see cref='System.Data.DataSet'/> of any data by removing
all rows in all tables.</para>

```

```

/// </devdoc>

```

```

public void Clear()
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.Clear|API> %d#\n", ObjectID);
    try {
        OnClearFunctionCalled(null);
        bool fEnforce = EnforceConstraints;
        EnforceConstraints = false;
        for (int i = 0; i < Tables.Count; i++)
            Tables[i].Clear();
    }
}

```

```

        EnforceConstraints = fEnforce;
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

/// <devdoc>
/// <para>Clones the structure of the <see cref='System.Data.DataSet'/>,
including all <see cref='System.Data.DataTable'/> schemas, relations, and
///     constraints.</para>
/// </devdoc>
/// Prevent inlining so that reflection calls are not moved to caller that may be
in a different assembly that may have a different grant set.
[MethodImpl(MethodImplOptions.NoInlining)]
public virtual DataSet Clone() {
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.Clone|API> %d#\n", ObjectID);
    try {
        DataSet ds = (DataSet)Activator.CreateInstance(this.GetType(), true);

        if (ds.Tables.Count > 0) // Microsoft : To clean up all the schema in
strong typed dataset.
            ds.Reset();

        //copy some original dataset properties
        ds.DataSetName = DataSetName;
        ds.CaseSensitive = CaseSensitive;
        ds._culture = _culture;
        ds._cultureUserSet = _cultureUserSet;
        ds.EnforceConstraints = EnforceConstraints;
        ds.Namespace = Namespace;
        ds.Prefix = Prefix;
        ds.RemotingFormat = RemotingFormat;
        ds.fIsSchemaLoading = true; //delay expression evaluation

        // ...Tables...
        DataTableCollection tbls = Tables;
        for (int i = 0; i < tbls.Count; i++) {
            DataTable dt = tbls[i].Clone(ds);
            dt.tableNamespace = tbls[i].Namespace; // hardcode the namespace for
a second to not mess up
            // DataRelation cloning.

```

```

        ds.Tables.Add(dt);
    }

    // ...Constraints...
    for (int i = 0; i < tbls.Count; i++) {
        ConstraintCollection constraints = tbls[i].Constraints;
        for (int j = 0; j < constraints.Count; j++) {
            if (constraints[j] is UniqueConstraint)
                continue;

            ForeignKeyConstraint foreign = constraints[j] as
ForeignForeignKeyConstraint;
            if (foreign.Table == foreign.RelatedTable)
                continue; // we have already added this foreign key in while
cloning the datatable

            ds.Tables[i].Constraints.Add(constraints[j].Clone(ds));
        }
    }

    // ...Relations...
    DataRelationCollection rels = Relations;
    for (int i = 0; i < rels.Count; i++) {
        DataRelation rel = rels[i].Clone(ds);
        rel.CheckMultipleNested = false; // disable the check for multiple
nested parent

        ds.Relations.Add(rel);
        rel.CheckMultipleNested = true; // enable the check for multiple
nested parent
    }

    // ...Extended Properties...
    if (this.extendedProperties != null) {
        foreach (Object key in this.extendedProperties.Keys) {
            ds.ExtendedProperties[key] = this.extendedProperties[key];
        }
    }

    foreach (DataTable table in Tables)
        foreach (DataColumn col in table.Columns)
            if (col.Expression.Length != 0)
                ds.Tables[table.TableName,
table.Namespace].Columns[col.ColumnName].Expression = col.Expression;

    for (int i = 0; i < tbls.Count; i++) {
        ds.Tables[i].tableNamespace = tbls[i].tableNamespace; // undo the

```

hardcoding of the namespace

```
    }

    ds.fIsSchemaLoading = false; //reactivate column computations

    return ds;
}
finally {
    Bid.ScopeLeave(ref hscp);
}
}

/// <devdoc>
/// <para>Copies both the structure and data for this <see
cref='System.Data.DataSet' />.</para>
/// </devdoc>
public DataSet Copy()
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.Copy|API> %d#\n", ObjectID);
    try {
        DataSet dsNew = Clone();
        bool fEnforceConstraints = dsNew.EnforceConstraints;
        dsNew.EnforceConstraints = false;
        foreach (DataTable table in this.Tables)
        {
            DataTable destTable = dsNew.Tables[table.TableName, table.Namespace];

            foreach (DataRow row in table.Rows)
                table.CopyRow(destTable, row);
        }

        dsNew.EnforceConstraints = fEnforceConstraints;

        return dsNew;
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

internal Int32 EstimatedXmlStringSize()
{
    Int32 bytes = 100;
```

```

    for (int i = 0; i < Tables.Count; i++) {
        Int32 rowBytes = (Tables[i].TableName.Length + 4) << 2;
        DataTable table = Tables[i];
        for (int j = 0; j < table.Columns.Count; j++) {
            rowBytes += ((table.Columns[j].ColumnName.Length + 4) << 2);
            rowBytes += 20;
        }
        bytes += table.Rows.Count * rowBytes;
    }

    return bytes;
}

/// <devdoc>
/// <para>Returns a copy of the <see cref='System.Data.DataSet'> that contains
all changes made to
///     it since it was loaded or <see cref='System.Data.DataSet.AcceptChanges'>
///     was last called.</para>
/// </devdoc>
public DataSet GetChanges()
{
    return GetChanges(DataRowState.Added | DataRowState.Deleted |
DataRowState.Modified);
}

private struct TableChanges {
    private BitArray _rowChanges;
    private int _hasChanges;

    internal TableChanges(int rowCount) {
        _rowChanges = new BitArray(rowCount);
        _hasChanges = 0;
    }

    internal int HasChanges {
        get { return _hasChanges; }
        set { _hasChanges = value; }
    }

    internal bool this[int index] {
        get { return _rowChanges[index]; }
        set {
            Debug.Assert(value && !_rowChanges[index], "setting twice or to
false");
            _rowChanges[index] = value;
            _hasChanges++;
        }
    }
}

```

```

    }
}

public DataSet GetChanges(DataRowState rowStates)
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.GetChanges|API> %d#",
rowStates=%d{ds.DataRowState}\n", ObjectID, (int)rowStates);
    try {
        DataSet dsNew = null;
        bool fEnforceConstraints = false;
        if (0 != (rowStates & ~(DataRowState.Added | DataRowState.Deleted |
DataRowState.Modified | DataRowState.Unchanged))) {
            throw ExceptionBuilder.InvalidRowState(rowStates);
        }

        // Initialize all the individual table bitmaps.
        TableChanges[] bitMatrix = new TableChanges[Tables.Count];
        for (int i = 0; i < bitMatrix.Length; ++i) {
            bitMatrix[i] = new TableChanges(Tables[i].Rows.Count);
        }

        // find all the modified rows and their parents
        MarkModifiedRows(bitMatrix, rowStates);

        // copy the changes to a cloned table
        for (int i = 0; i < bitMatrix.Length; ++i) {
            Debug.Assert(0 <= bitMatrix[i].HasChanges, "negative change count");
            if (0 < bitMatrix[i].HasChanges) {
                if (null == dsNew) {
                    dsNew = this.Clone();
                    fEnforceConstraints = dsNew.EnforceConstraints;
                    dsNew.EnforceConstraints = false;
                }

                DataTable table = this.Tables[i];
                DataTable destTable = dsNew.Tables[table.TableName,
table.Namespace];

                Debug.Assert(bitMatrix[i].HasChanges <= table.Rows.Count, "to
many changes");

                for (int j = 0; 0 < bitMatrix[i].HasChanges; ++j) { // Loop
through the rows.

```

```

        if (bitMatrix[i][j]) {
            table.CopyRow(destTable, table.Rows[j]);
            bitMatrix[i].HasChanges--;
        }
    }
}

if (null != dsNew) {
    dsNew.EnforceConstraints = fEnforceConstraints;
}
return dsNew;
}
finally {
    Bid.ScopeLeave(ref hscp);
}
}

```

```

private void MarkModifiedRows(TableChanges[] bitMatrix, DataRowState rowStates) {
    // for every table, every row & every relation find the modified rows and for
non-deleted rows, their parents
    for (int tableIndex = 0; tableIndex < bitMatrix.Length; ++tableIndex) {
        DataRowCollection rows = Tables[tableIndex].Rows;
        int rowCount = rows.Count;

        for (int rowIndex = 0; rowIndex < rowCount; ++rowIndex) {
            DataRow row = rows[rowIndex];
            DataRowState rowState = row.RowState;
            Debug.Assert(DataRowState.Added == rowState ||
                DataRowState.Deleted == rowState ||
                DataRowState.Modified == rowState ||
                DataRowState.Unchanged == rowState,
                "unexpected DataRowState");

            // if bit not already set and row is modified
            if ((0 != (rowStates & rowState)) && !bitMatrix[tableIndex]
[roIndex]) {

                bitMatrix[tableIndex][rowIndex] = true;

                if (DataRowState.Deleted != rowState) {
                    MarkRelatedRowsAsModified(bitMatrix, row);
                }
            }
        }
    }
}

```

```

    }
}

private void MarkRelatedRowsAsModified(TableChanges[] bitMatrix, DataRow row) {
    DataRelationCollection relations = row.Table.ParentRelations;
    int relationCount = relations.Count;
    for (int relatedIndex = 0; relatedIndex < relationCount; ++relatedIndex) {
        DataRow[] relatedRows = row.GetParentRows(relations[relatedIndex],
DataRowVersion.Current);

        foreach (DataRow relatedRow in relatedRows) {
            int relatedTableIndex = this.Tables.IndexOf(relatedRow.Table);
            int relatedRowIndex = relatedRow.Table.Rows.IndexOf(relatedRow);

            if (!bitMatrix[relatedTableIndex][relatedRowIndex]) {
                bitMatrix[relatedTableIndex][relatedRowIndex] = true;

                if (DataRowState.Deleted != relatedRow.RowState) {
                    // recurse into related rows
                    MarkRelatedRowsAsModified(bitMatrix, relatedRow);
                }
            }
        }
    }
}
}

```

```

IList System.ComponentModel.IListSource.GetList() {
    return DefaultViewManager;
}

```

```

internal string GetRemotingDiffGram(DataTable table)
{
    StringWriter strWriter = new StringWriter(CultureInfo.InvariantCulture);
    XmlTextWriter writer = new XmlTextWriter(strWriter);
    writer.Formatting = Formatting.Indented;
    if (strWriter != null) {
        // Create and save the updates
        new NewDiffgramGen(table, false).Save(writer, table);
    }

    return strWriter.ToString();
}

```

```

public string GetXml()

```

```

{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.GetXml|API> %d#\n", ObjectID);
    try {

        // StringBuilder strBuilder = new
StringBuilder(EstimatedXmlStringSize());
        // StringWriter strWriter = new StringWriter(strBuilder);
        StringWriter strWriter = new StringWriter(CultureInfo.InvariantCulture);
        if (strWriter != null) {
            XmlTextWriter w = new XmlTextWriter(strWriter);
            w.Formatting = Formatting.Indented;
            new XmlDataTreeWriter(this).Save(w, false);
        }
        return strWriter.ToString();
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

public string GetXmlSchema()
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.GetXmlSchema|API> %d#\n", ObjectID);
    try {
        StringWriter strWriter = new StringWriter(CultureInfo.InvariantCulture);
        XmlTextWriter writer = new XmlTextWriter(strWriter);
        writer.Formatting = Formatting.Indented;
        if (strWriter != null) {
            (new XmlTreeGen(SchemaFormat.Public)).Save(this, writer);
        }

        return strWriter.ToString();
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

internal string GetXmlSchemaForRemoting(DataTable table)
{
    StringWriter strWriter = new StringWriter(CultureInfo.InvariantCulture);
    XmlTextWriter writer = new XmlTextWriter(strWriter);

```

```

        writer.Formatting = Formatting.Indented;
        if (strWriter != null) {
            if (table == null) {
                if (this.SchemaSerializationMode ==
SchemaSerializationMode.ExcludeSchema)
                    (new XmlTreeGen(SchemaFormat.RemotingSkipSchema)).Save(this,
writer);

                else
                    (new XmlTreeGen(SchemaFormat.Remoting)).Save(this, writer);
            }
            else { // no skip schema support for typed datatable
                (new XmlTreeGen(SchemaFormat.Remoting)).Save(table, writer);
            }
        }

        return strWriter.ToString();
    }

    /// <devdoc>
    /// <para>Gets a value indicating whether the <see cref='System.Data.DataSet'>
has changes, including new,
    ///     deleted, or modified rows.</para>
    /// </devdoc>
    public bool HasChanges()
    {
        return HasChanges(DataRowState.Added | DataRowState.Deleted |
DataRowState.Modified);
    }

    /// <devdoc>
    /// <para>Gets a value indicating whether the <see cref='System.Data.DataSet'>
has changes, including new,
    ///     deleted, or modified rows, filtered by <see
cref='System.Data.DataRowState'>.</para>
    /// </devdoc>
    public bool HasChanges(DataRowState rowStates)
    {
        IntPtr hscp;
        Bid.ScopeEnter(out hscp, "<ds.DataSet.HasChanges|API> %d#",
rowStates=%d{ds.DataRowState}\n", ObjectID, (int)rowStates);

        try {
            const DataRowState allRowStates = DataRowState.Detached |

```

```
DataRowState.Unchanged | DataRowState.Added | DataRowState.Deleted |  
DataRowState.Modified;
```

```
        if ((rowStates & (~allRowStates)) != 0) {  
            throw ExceptionBuilder.ArgumentOutOfRange("rowState");  
        }  
  
        for (int i = 0; i < Tables.Count; i++) {  
            DataTable table = Tables[i];  
  
            for (int j = 0; j < table.Rows.Count; j++) {  
                DataRow row = table.Rows[j];  
                if ((row.RowState & rowStates) != 0) {  
                    return true;  
                }  
            }  
        }  
        return false;  
    }  
    finally {  
        Bid.ScopeLeave(ref hscp);  
    }  
}  
  
/// <devdoc>  
/// <para>Infer the XML schema from the specified <see  
cref='System.IO.TextReader' /> into the <see cref='System.Data.DataSet' />.</para>  
/// </devdoc>  
public void InferXmlSchema(XmlReader reader, string[] nsArray)  
{  
    IntPtr hscp;  
    Bid.ScopeEnter(out hscp, "<ds.DataSet.InferXmlSchema|API> %d#\n", ObjectID);  
    try {  
        if (reader == null)  
            return;  
  
        XmlDocument xdoc = new XmlDocument();  
        if (reader.NodeType == XmlNodeType.Element) {  
            XmlNode node = xdoc.ReadNode(reader);  
            xdoc.AppendChild(node);  
        }  
        else  
            xdoc.Load(reader);  
        if (xdoc.DocumentElement == null)
```

```

        return;

        InferSchema(xdoc, nsArray, XmlReadMode.InferSchema);
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

/// <devdoc>
/// <para>Infer the XML schema from the specified <see
 cref='System.IO.TextReader' /> into the <see cref='System.Data.DataSet' />.</para>
/// </devdoc>
public void InferXmlSchema(Stream stream, string[] nsArray)
{
    if (stream == null)
        return;

    InferXmlSchema(new XmlTextReader(stream), nsArray);
}

/// <devdoc>
/// <para>Infer the XML schema from the specified <see
 cref='System.IO.TextReader' /> into the <see cref='System.Data.DataSet' />.</para>
/// </devdoc>
public void InferXmlSchema(TextReader reader, string[] nsArray)
{
    if (reader == null)
        return;

    InferXmlSchema(new XmlTextReader(reader), nsArray);
}

/// <devdoc>
/// <para>Infer the XML schema from the specified file into the <see
 cref='System.Data.DataSet' />.</para>
/// </devdoc>
[ResourceExposure(ResourceScope.Machine)]
[ResourceConsumption(ResourceScope.Machine)]
public void InferXmlSchema(String fileName, string[] nsArray)
{
    XmlTextReader xr = new XmlTextReader(fileName);
    try {
        InferXmlSchema(xr, nsArray);
    }
}

```

```

    }
    finally {
        xr.Close();
    }
}

/// <devdoc>
/// <para>Reads the XML schema from the specified <see
cref='T:System.Xml.XmlReader' /> into the <see cref='System.Data.DataSet' />
/// .</para>
/// </devdoc>
public void ReadXmlSchema(XmlReader reader)
{
    ReadXmlSchema(reader, false);
}

internal void ReadXmlSchema(XmlReader reader, bool denyResolving)
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.ReadXmlSchema|INFO> %d#, reader,
denyResolving=%d{bool}\\n", ObjectID, denyResolving);
    try {
        int iCurrentDepth = -1;

        if (reader == null)
            return;

        if (reader is XmlTextReader)
            ((XmlTextReader)reader).WhitespaceHandling = WhitespaceHandling.None;

        XmlDocument xdoc = new XmlDocument(); // we may need this to infer the
schema

        if (reader.NodeType == XmlNodeType.Element)
            iCurrentDepth = reader.Depth;

        reader.MoveToContent();

        if (reader.NodeType == XmlNodeType.Element) {
            // if reader points to the schema load it...

            if (reader.LocalName == Keywords.XDR_SCHEMA && reader.NamespaceURI ==
Keywords.XDRNS) {
                // load XDR schema and exit

```

```

        ReadXDRSchema(reader);
        return;
    }

    if (reader.LocalName == Keywords.XSD_SCHEMA && reader.NamespaceURI ==
Keywords.XSDNS) {
        // load XSD schema and exit
        ReadXSDSchema(reader, denyResolving);
        return;
    }

    if (reader.LocalName == Keywords.XSD_SCHEMA &&
reader.NamespaceURI.StartsWith(Keywords.XSD_NS_START, StringComparison.Ordinal))
        throw ExceptionBuilder.DataSetUnsupportedSchema(Keywords.XSDNS);

    // ... otherwise backup the top node and all its attributes
    XmlElement topNode = xdoc.CreateElement(reader.Prefix,
reader.LocalName, reader.NamespaceURI);
    if (reader.HasAttributes) {
        int attrCount = reader.AttributeCount;
        for (int i = 0; i < attrCount; i++) {
            reader.MoveToAttribute(i);
            if (reader.NamespaceURI.Equals(Keywords.XSD_XMLNS_NS))
                topNode.SetAttribute(reader.Name,
reader.GetAttribute(i));
            else {
                XmlAttribute attr =
topNode.SetAttributeNode(reader.LocalName, reader.NamespaceURI);
                attr.Prefix = reader.Prefix;
                attr.Value = reader.GetAttribute(i);
            }
        }
    }
    reader.Read();

    while (MoveToElement(reader, iCurrentDepth)) {

        // if reader points to the schema load it...
        if (reader.LocalName == Keywords.XDR_SCHEMA &&
reader.NamespaceURI == Keywords.XDRNS) {
            // load XDR schema and exit
            ReadXDRSchema(reader);
            return;
        }
    }

```

```

        if (reader.LocalName == Keywords.XSD_SCHEMA &&
reader.NamespaceURI == Keywords.XSDNS) {
            // load XSD schema and exit
            ReadXSDSchema(reader, denyResolving);
            return;
        }

        if (reader.LocalName == Keywords.XSD_SCHEMA &&
reader.NamespaceURI.StartsWith(Keywords.XSD_NS_START, StringComparison.Ordinal))
            throw
ExceptionBuilder.DataSetUnsupportedSchema(Keywords.XSDNS);

        XmlNode node = xdoc.ReadNode(reader);
        topNode.AppendChild(node);

    }

    // read the closing tag of the current element
    ReadEndElement(reader);

    // if we are here no schema has been found
    xdoc.AppendChild(topNode);

    // so we InferSchema
    InferSchema(xdoc, null, XmlReadMode.Auto);
}
}
finally {
    Bid.ScopeLeave(ref hscp);
}
}

internal bool MoveToElement(XmlReader reader, int depth) {
    while (!reader.EOF && reader.NodeType != XmlNodeType.EndElement &&
reader.NodeType != XmlNodeType.Element && reader.Depth > depth) {
        reader.Read();
    }
    return (reader.NodeType == XmlNodeType.Element);
}

private static void MoveToElement(XmlReader reader) {
    while (!reader.EOF && reader.NodeType != XmlNodeType.EndElement &&

```

```

reader.NodeType != XmlNodeType.Element) {
    reader.Read();
}
}

internal void ReadEndElement(XmlReader reader) {
    while (reader.NodeType == XmlNodeType.Whitespace) {
        reader.Skip();
    }
    if (reader.NodeType == XmlNodeType.None) {
        reader.Skip();
    }
    else if (reader.NodeType == XmlNodeType.EndElement) {
        reader.ReadEndElement();
    }
}

internal void ReadXSDSchema(XmlReader reader, bool denyResolving) {
    XmlSchemaSet sSet = new XmlSchemaSet();

    int schemaFragmentCount = 1;
    //read from current schmema element
    if (reader.LocalName == Keywords.XSD_SCHEMA && reader.NamespaceURI ==
Keywords.XSDNS) {
        if (reader.HasAttributes) {
            string attribValue = reader.GetAttribute(Keywords.MSD_FRAGMENTCOUNT,
Keywords.MSDNS); // this must not move the position
            if (!Common.ADP.IsEmpty(attribValue)) {
                schemaFragmentCount = int.Parse(attribValue, null);
            }
        }
    }

    while (reader.LocalName == Keywords.XSD_SCHEMA && reader.NamespaceURI ==
Keywords.XSDNS) {
        XmlSchema s = XmlSchema.Read(reader, null);
        sSet.Add(s);
        //read the end tag
        ReadEndElement(reader);

        if (--schemaFragmentCount > 0) {
            MoveToElement(reader);
        }
        while (reader.NodeType == XmlNodeType.Whitespace) {
            reader.Skip();

```

```

    }
}
sSet.Compile();
XSDSchema schema = new XSDSchema();
schema.LoadSchema(sSet, this);
}

internal void ReadXDRSchema(XmlReader reader) {
    XmlDocument xdoc = new XmlDocument(); // we may need this to infer the schema
    XmlNode schNode = xdoc.ReadNode(reader);
    xdoc.AppendChild(schNode);
    XDRSchema schema = new XDRSchema(this, false);
    this.DataSetName = xdoc.DocumentElement.LocalName;
    schema.LoadSchema((XmlElement)schNode, this);
}

/// <devdoc>
/// <para>Reads the XML schema from the specified <see cref='System.IO.Stream'>
into the
/// <see cref='System.Data.DataSet'>.</para>
/// </devdoc>
public void ReadXmlSchema(Stream stream)
{
    if (stream == null)
        return;

    ReadXmlSchema(new XmlTextReader(stream), false);
}

/// <devdoc>
/// <para>Reads the XML schema from the specified <see
cref='System.IO.TextReader'> into the <see cref='System.Data.DataSet'>.</para>
/// </devdoc>
public void ReadXmlSchema(TextReader reader)
{
    if (reader == null)
        return;

    ReadXmlSchema(new XmlTextReader(reader), false);
}

/// <devdoc>
/// <para>Reads the XML schema from the specified file into the <see
cref='System.Data.DataSet'>.</para>

```

```

    /// </devdoc>
    [ResourceExposure(ResourceScope.Machine)]
    [ResourceConsumption(ResourceScope.Machine)]
    public void ReadXmlSchema(String fileName)
    {
        XmlTextReader xr = new XmlTextReader(fileName);
        try {
            ReadXmlSchema(xr, false);
        }
        finally {
            xr.Close();
        }
    }

    #region WriteXmlSchema
    /// <summary>Writes the <see cref='DataSet'> structure as an XML schema to using
    the specified <see cref='Stream'> object.</summary>
    /// <param name="stream">A <see cref='Stream'> object used to write to a file.
    </param>
    public void WriteXmlSchema(Stream stream)
    {
        this.WriteXmlSchema(stream, SchemaFormat.Public, (Converter<Type,
string>)null);
    }

    /// <summary>Writes the <see cref='DataSet'> structure as an XML schema to using
    the specified <see cref='Stream'> object.</summary>
    /// <param name="stream">A <see cref='Stream'> object used to write to a file.
    </param>
    /// <param name="multipleTargetConverter">A delegate used to convert <see
    cref='Type'> into string.</param>
    public void WriteXmlSchema(Stream stream, Converter<Type, string>
multipleTargetConverter)
    {
        ADP.CheckArgumentNull(multipleTargetConverter, "multipleTargetConverter");
        this.WriteXmlSchema(stream, SchemaFormat.Public, multipleTargetConverter);
    }

    /// <summary>Writes the <see cref='DataSet'> structure as an XML schema to a
    file.</summary>
    /// <param name="fileName">The file name (including the path) to which to write.
    </param>
    [ResourceExposure(ResourceScope.Machine)]
    [ResourceConsumption(ResourceScope.Machine)]

```

```

    public void WriteXmlSchema(String fileName)
    {
        this.WriteXmlSchema(fileName, SchemaFormat.Public, (Converter<Type,
string>)null);
    }

    /// <summary>Writes the <see cref='DataSet'> structure as an XML schema to a
file.</summary>
    /// <param name="fileName">The file name (including the path) to which to write.
</param>
    /// <param name="multipleTargetConverter">A delegate used to convert <see
cref='Type'> into string.</param>
    [ResourceExposure(ResourceScope.Machine)]
    [ResourceConsumption(ResourceScope.Machine)]
    public void WriteXmlSchema(String fileName, Converter<Type, string>
multipleTargetConverter)
    {
        ADP.CheckArgumentNull(multipleTargetConverter, "multipleTargetConverter");
        this.WriteXmlSchema(fileName, SchemaFormat.Public, multipleTargetConverter);
    }

    /// <summary>Writes the <see cref='DataSet'> structure as an XML schema to a
<see cref='TextWriter'> object.</summary>
    /// <param name="writer">The <see cref='TextWriter'> object with which to write.
</param>
    public void WriteXmlSchema(TextWriter writer)
    {
        this.WriteXmlSchema(writer, SchemaFormat.Public, (Converter<Type,
string>)null);
    }

    /// <summary>Writes the <see cref='DataSet'> structure as an XML schema to a
<see cref='TextWriter'> object.</summary>
    /// <param name="writer">The <see cref='TextWriter'> object with which to write.
</param>
    /// <param name="multipleTargetConverter">A delegate used to convert <see
cref='Type'> into string.</param>
    public void WriteXmlSchema(TextWriter writer, Converter<Type, string>
multipleTargetConverter)
    {
        ADP.CheckArgumentNull(multipleTargetConverter, "multipleTargetConverter");
        this.WriteXmlSchema(writer, SchemaFormat.Public, multipleTargetConverter);
    }

```

```

    /// <summary>Writes the <see cref='DataSet'/> structure as an XML schema to an
<see cref='XmlWriter'/> object.</summary>
    /// <param name="writer">The <see cref='XmlWriter'/> object with which to write.
</param>
    public void WriteXmlSchema(XmlWriter writer)
    {
        this.WriteXmlSchema(writer, SchemaFormat.Public, (Converter<Type,
string>)null);
    }

    /// <summary>Writes the <see cref='DataSet'/> structure as an XML schema to an
<see cref='XmlWriter'/> object.</summary>
    /// <param name="writer">The <see cref='XmlWriter'/> object with which to write.
</param>
    /// <param name="multipleTargetConverter">A delegate used to convert <see
cref='Type'/> into string.</param>
    public void WriteXmlSchema(XmlWriter writer, Converter<Type, string>
multipleTargetConverter)
    {
        ADP.CheckArgumentNull(multipleTargetConverter, "multipleTargetConverter");
        this.WriteXmlSchema(writer, SchemaFormat.Public, multipleTargetConverter);
    }

    [ResourceExposure(ResourceScope.Machine)]
    [ResourceConsumption(ResourceScope.Machine)]
    private void WriteXmlSchema(String fileName, SchemaFormat schemaFormat,
Converter<Type, string> multipleTargetConverter)
    {
        XmlTextWriter xw = new XmlTextWriter( fileName, null );
        try {
            xw.Formatting = Formatting.Indented;
            xw.WriteStartDocument(true);
            this.WriteXmlSchema(xw, schemaFormat, multipleTargetConverter);
            xw.WriteEndDocument();
        }
        finally {
            xw.Close();
        }
    }

    private void WriteXmlSchema(Stream stream, SchemaFormat schemaFormat,
Converter<Type, string> multipleTargetConverter)
    {
        if (stream == null)

```

```

        return;

        XmlTextWriter w = new XmlTextWriter(stream, null);
        w.Formatting = Formatting.Indented;

        this.WriteXmlSchema(w, schemaFormat, multipleTargetConverter);
    }

    private void WriteXmlSchema(TextWriter writer, SchemaFormat schemaFormat,
Converter<Type, string> multipleTargetConverter)
    {
        if (writer == null)
            return;

        XmlTextWriter w = new XmlTextWriter(writer);
        w.Formatting = Formatting.Indented;

        this.WriteXmlSchema(w, schemaFormat, multipleTargetConverter);
    }

    private void WriteXmlSchema(XmlWriter writer, SchemaFormat schemaFormat,
Converter<Type, string> multipleTargetConverter)
    {
        IntPtr hscp;
        Bid.ScopeEnter(out hscp, "<ds.DataSet.WriteXmlSchema|INFO> %d#,
schemaFormat=%d{ds.SchemaFormat}\n", ObjectID, (int)schemaFormat);
        try {
            // Generate SchemaTree and write it out
            if (writer != null) {
                XmlTreeGen treeGen = null;
                if (schemaFormat == SchemaFormat.WebService &&
SchemaSerializationMode == SchemaSerializationMode.ExcludeSchema
&&
                    writer.WriteState == WriteState.Element) {
                    treeGen = new XmlTreeGen(SchemaFormat.WebServiceSkipSchema);
                }
                else {
                    treeGen = new XmlTreeGen(schemaFormat);
                }

                treeGen.Save(this, (DataTable)null, writer, false,
multipleTargetConverter);
            }
        }
    }

```

```

        finally {
            Bid.ScopeLeave(ref hscp);
        }
    }
#endregion

/// <devdoc>
/// </devdoc>
public XmlReadMode ReadXml(XmlReader reader)
{
    return ReadXml(reader, false);
}

internal XmlReadMode ReadXml(XmlReader reader, bool denyResolving)
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.ReadXml|INFO> %d#,
denyResolving=%d{bool}\n", ObjectID, denyResolving);
    try {

        DataTable.DSRowDiffIdUsageSection rowDiffIdUsage = new
DataTable.DSRowDiffIdUsageSection();
        try {
            bool fDataFound = false;
            bool fSchemaFound = false;
            bool fDiffsFound = false;
            bool fIsXdr = false;
            int iCurrentDepth = -1;
            XmlReadMode ret = XmlReadMode.Auto;
            bool isEmptyDataSet = false;
            bool topNodeIsProcessed = false; // we chance topnode and there is
just one case that we miss to process it
            // it is : <elem attrib1="Attrib">txt</elem>

            // clear the hashtable to avoid conflicts between diffgrams,
SqlHotFix 782

            rowDiffIdUsage.Prepare(this);

            if (reader == null)
                return ret;

            if (Tables.Count == 0) {
                isEmptyDataSet = true;

```

```

    }

    if (reader is XmlTextReader)
        ((XmlTextReader)reader).WhitespaceHandling =
WhitespaceHandling.Significant;

    XmlDocument xdoc = new XmlDocument(); // we may need this to infer
the schema

    XmlDataLoader xmlload = null;

    reader.MoveToContent();

    if (reader.NodeType == XmlNodeType.Element)
        iCurrentDepth = reader.Depth;

    if (reader.NodeType == XmlNodeType.Element) {
        if ((reader.LocalName == Keywords.DIFFGRAM) &&
(reader.NamespaceURI == Keywords.DFFNS)) {
            this.ReadXmlDiffgram(reader);
            // read the closing tag of the current element
            ReadEndElement(reader);
            return XmlReadMode.DiffGram;
        }

        // if reader points to the schema load it
        if (reader.LocalName == Keywords.XDR_SCHEMA &&
reader.NamespaceURI == Keywords.XDRNS) {
            // load XDR schema and exit
            ReadXDRSchema(reader);
            return XmlReadMode.ReadSchema; //since the top level element
is a schema return
        }

        if (reader.LocalName == Keywords.XSD_SCHEMA &&
reader.NamespaceURI == Keywords.XSDNS) {
            // load XSD schema and exit
            ReadXSDSchema(reader, denyResolving);
            return XmlReadMode.ReadSchema; //since the top level element
is a schema return
        }

        if (reader.LocalName == Keywords.XSD_SCHEMA &&
reader.NamespaceURI.StartsWith(Keywords.XSD_NS_START, StringComparison.Ordinal))

```

```

        throw
ExceptionBuilder.DataSetUnsupportedSchema(Keywords.XSDNS);

        // now either the top level node is a table and we load it
        through dataReader...

        // ... or backup the top node and all its attributes because we
        may need to InferSchema
        XmlElement topNode = xdoc.CreateElement(reader.Prefix,
reader.LocalName, reader.NamespaceURI);
        if (reader.HasAttributes) {
            int attrCount = reader.AttributeCount;
            for (int i = 0; i < attrCount; i++) {
                reader.MoveToAttribute(i);
                if (reader.NamespaceURI.Equals(Keywords.XSD_XMLNS_NS))
                    topNode.SetAttribute(reader.Name,
reader.GetAttribute(i));
            }
            else {
                XmlAttribute attr =
topNode.SetAttributeNode(reader.LocalName, reader.NamespaceURI);
                attr.Prefix = reader.Prefix;
                attr.Value = reader.GetAttribute(i);
            }
        }
        reader.Read();
        string rootNodeSimpleContent = reader.Value;

        while (MoveToElement(reader, iCurrentDepth)) {

            if ((reader.LocalName == Keywords.DIFFGRAM) &&
(reader.NamespaceURI == Keywords.DFFNS)) {
                this.ReadXmlDiffgram(reader);
                // read the closing tag of the current element
                // YUKON FIX
                ReadEndElement(reader);

                // return
                XmlReadMode.DiffGram;

                ret = XmlReadMode.DiffGram; // continue reading for
multiple schemas
            }

            // if reader points to the schema load it...

```

```

        if (!fSchemaFound && !fDataFound && reader.LocalName ==
Keywords.XDR_SCHEMA && reader.NamespaceURI == Keywords.XDRNS) {
            // load XDR schema and exit
            ReadXDRSchema(reader);
            fSchemaFound = true;
            fIsXdr = true;
            continue;
        }

        if (reader.LocalName == Keywords.XSD_SCHEMA &&
reader.NamespaceURI == Keywords.XSDNS) {
            // load XSD schema and exit
            ReadXSDSchema(reader, denyResolving);
            fSchemaFound = true;
            continue;
        }

        if (reader.LocalName == Keywords.XSD_SCHEMA &&
reader.NamespaceURI.StartsWith(Keywords.XSD_NS_START, StringComparison.Ordinal))
            throw
ExceptionBuilder.DataSetUnsupportedSchema(Keywords.XSDNS);

        if ((reader.LocalName == Keywords.DIFFGRAM) &&
(reader.NamespaceURI == Keywords.DFFNS)) {
            this.ReadXmlDiffgram(reader);
            fDiffsFound = true;
            ret = XmlReadMode.DiffGram;
        }
        else {
            // We have found data IFF the reader.NodeType == Element
and reader.depth == currentDepth-1
            // if reader.NodeType == whitespace, skip all white
spaces.

            // skip processing i.e. continue if the first non-
whitespace node is not of type element.
            while (!reader.EOF && reader.NodeType ==
XmlNodeType.Whitespace)

                reader.Read();
            if (reader.NodeType != XmlNodeType.Element)
                continue;
            // we found data here
            fDataFound = true;

```

```

        if (!fSchemaFound && Tables.Count == 0) {
            XmlNode node = xdoc.ReadNode(reader);
            topNode.AppendChild(node);
        }
        else {
            if (xmlload == null)
                xmlload = new XmlDataLoader(this, fIsXdr,
topNode, false);

            xmlload.LoadData(reader);
            topNodeIsProcessed = true; // we process the topnode
            if (fSchemaFound)
                ret = XmlReadMode.ReadSchema;
            else
                ret = XmlReadMode.IgnoreSchema;
        }
    }

    // read the closing tag of the current element
    ReadEndElement(reader);
    bool isfTopLevelTableSet = false;
    bool tmpValue = this.fTopLevelTable;
    //While inference we ignore root elements text content
    if (!fSchemaFound && Tables.Count == 0 && !topNode.HasChildNodes)
    { //We shoule not come add SC of root elemnt to topNode if we are not infering
        this.fTopLevelTable = true;
        isfTopLevelTableSet = true;
        if ((rootNodeSimpleContent != null &&
rootNodeSimpleContent.Length > 0))
            topNode.InnerText = rootNodeSimpleContent;
    }
    if (!isEmptyDataSet) {
        if ((rootNodeSimpleContent != null &&
rootNodeSimpleContent.Length > 0))
            topNode.InnerText = rootNodeSimpleContent;
    }

    // now top node contains the data part
    xdoc.AppendChild(topNode);

    if (xmlload == null)
        xmlload = new XmlDataLoader(this, fIsXdr, topNode, false);

    if (!isEmptyDataSet && !topNodeIsProcessed) {

```

```

        XmlElement root = xdoc.DocumentElement;
        Debug.Assert(root.NamespaceURI != null, "root.NamespaceURI
should not be null, it should be empty string");
        // just recognize that below given Xml represents datatable
in toplevel

        //<table attr1="foo" attr2="bar"
table_Text="junk">text</table>
        // only allow root element with simple content, if any
        if (root.ChildNodes.Count == 0 ||
            ((root.ChildNodes.Count == 1) &&
root.FirstChild.GetType() == typeof(System.Xml.XmlText))) {
            bool initfTopLevelTable = this.fTopLevelTable;
            // if root element maps to a datatable
            // ds and dt cant have the same name and ns at the same
time, how to write to xml

            if (this.DataSetName != root.Name && this.namespaceURI !=
root.NamespaceURI &&
                Tables.Contains(root.Name, (root.NamespaceURI.Length
== 0) ? null : root.NamespaceURI, false, true)) {
                this.fTopLevelTable = true;
            }
            try {
                xmlload.LoadData(xdoc);
            }
            finally {
                this.fTopLevelTable = initfTopLevelTable; // this is
not for inference, we have schema and we were skipping
                // topnode where it was a datatable, We must restore
the value
            }
        }
    }
} // above check and below check are orthogonal
// so we InferSchema
if (!fDiffsFound) {
    // Load Data
    if (!fSchemaFound && Tables.Count == 0) {
        InferSchema(xdoc, null, XmlReadMode.Auto);
        ret = XmlReadMode.InferSchema;
        xmlload.FromInference = true;
        try {
            xmlload.LoadData(xdoc);
        }
        finally {
            xmlload.FromInference = false;

```

```

        }
    }

    //We dont need this assignement. Once we set it(where we set
it during inference), it won't be changed
    if (isfTopLevelTableSet)
        this.fTopLevelTable = tmpValue;
    }
}

    return ret;
}
finally {
    rowDiffIdUsage.Cleanup();
}
}
finally {
    Bid.ScopeLeave(ref hscp);
}
}

/// <devdoc>
/// </devdoc>
public XmlReadMode ReadXml(Stream stream)
{
    if (stream == null)
        return XmlReadMode.Auto;

    XmlTextReader xr = new XmlTextReader(stream);

    // Prevent Dtd entity in dataset
    xr.XmlResolver = null;

    return ReadXml(xr, false);
}

/// <devdoc>
/// </devdoc>
public XmlReadMode ReadXml(TextReader reader)
{
    if (reader == null)
        return XmlReadMode.Auto;

    XmlTextReader xr = new XmlTextReader(reader);

```

```

        // Prevent Dtd entity in dataset
        xr.XmlResolver = null;

        return ReadXml(xr, false);
    }

    /// <devdoc>
    /// </devdoc>
    [ResourceExposure(ResourceScope.Machine)]
    [ResourceConsumption(ResourceScope.Machine)]
    public XmlReadMode ReadXml(string fileName)
    {
        XmlTextReader xr = new XmlTextReader(fileName);

        // Prevent Dtd entity in dataset
        xr.XmlResolver = null;

        try
        {
            return ReadXml(xr, false);
        }
        finally {
            xr.Close();
        }
    }

    internal void InferSchema(XmlDocument xdoc, string[] excludedNamespaces,
        XmlReadMode mode) {
        IntPtr hscp;
        Bid.ScopeEnter(out hscp, "<ds.DataSet.InferSchema|INFO> %d#,
mode=%d{ds.XmlReadMode}\n", ObjectID, (int)mode);
        try {
            string ns = xdoc.DocumentElement.NamespaceURI;
            if (null == excludedNamespaces) {
                excludedNamespaces = new string[0];
            }
            XmlNodeReader xnr = new XmlIgnoreNamespaceReader(xdoc,
excludedNamespaces);
            System.Xml.Schema.XmlSchemaInference infer = new
System.Xml.Schema.XmlSchemaInference();

            infer.Occurrence = XmlSchemaInference.InferenceOption.Relaxed;

```

```

        if (mode == XmlReadMode.InferTypedSchema)
            infer.TypeInference = XmlSchemaInference.InferenceOption.Restricted;
        else
            infer.TypeInference = XmlSchemaInference.InferenceOption.Relaxed;

        XmlSchemaSet schemaSet = infer.InferSchema(xnr);
        schemaSet.Compile();

        XSDSchema schema = new XSDSchema();
        schema.FromInference = true;

        try {
            schema.LoadSchema(schemaSet, this);
        }
        finally {
            schema.FromInference = false; // this is always false if you are not
calling from inference
        }
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

private bool IsEmpty() {
    foreach (DataTable table in this.Tables)
        if (table.Rows.Count > 0)
            return false;
    return true;
}

private void ReadXmlDiffgram(XmlReader reader) {
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.ReadXmlDiffgram|INFO> %d#\n",
ObjectID);
    try {
        int d = reader.Depth;
        bool fEnforce = this.EnforceConstraints;
        this.EnforceConstraints = false;
        DataSet newDs;
        bool isEmpty = this.IsEmpty();

        if (isEmpty) {
            newDs = this;

```

```

    }
    else {
        newDs = this.Clone();
        newDs.EnforceConstraints = false;
    }

    foreach (DataTable t in newDs.Tables) {
        t.Rows.nullInList = 0;
    }
    reader.MoveToContent();
    if ((reader.LocalName != Keywords.DIFFGRAM) && (reader.NamespaceURI !=
Keywords.DFFNS))
        return;
    reader.Read();
    if (reader.NodeType == XmlNodeType.Whitespace)
        MoveToElement(reader, reader.Depth - 1 /*iCurrentDepth*/); // skip
over whitespaces.

    newDs.fInLoadDiffgram = true;

    if (reader.Depth > d) {
        if ((reader.NamespaceURI != Keywords.DFFNS) && (reader.NamespaceURI
!= Keywords.MSDNS)) {
            //we should be inside the dataset part
            XmlDocument xdoc = new XmlDocument();
            XmlElement node = xdoc.CreateElement(reader.Prefix,
reader.LocalName, reader.NamespaceURI);
            reader.Read();
            if (reader.NodeType == XmlNodeType.Whitespace) {
                MoveToElement(reader, reader.Depth - 1 /*iCurrentDepth*/); //
skip over whitespaces.
            }
            if (reader.Depth - 1 > d) {
                XmlDataLoader xmlload = new XmlDataLoader(newDs, false, node,
false);

                xmlload.isDiffgram = true; // turn on the special processing
                xmlload.LoadData(reader);
            }
            ReadEndElement(reader);
            if (reader.NodeType == XmlNodeType.Whitespace) {
                MoveToElement(reader, reader.Depth - 1 /*iCurrentDepth*/); //
skip over whitespaces.
            }
        }
    }
}

```

```

        Debug.Assert(reader.NodeType != XmlNodeType.Whitespace, "Should not
be on Whitespace node");

        if (((reader.LocalName == Keywords.SQL_BEFORE) &&
(reader.NamespaceURI == Keywords.DFFNS)) ||
            ((reader.LocalName == Keywords.MSD_ERRORS) &&
(reader.NamespaceURI == Keywords.DFFNS)))

        {
            //this will consume the changes and the errors part
            XMLDiffLoader diffLoader = new XMLDiffLoader();
            diffLoader.LoadDiffGram(newDs, reader);
        }

        // get to the closing diff tag
        while (reader.Depth > d) {
            reader.Read();
        }
        // read the closing tag
        ReadEndElement(reader);
    }

    foreach (DataTable t in newDs.Tables) {
        if (t.Rows.nullInList > 0)
            throw ExceptionBuilder.RowInsertMissing(t.TableName);
    }

    newDs.fInLoadDiffgram = false;

    //terrible performance!
    foreach (DataTable t in newDs.Tables) {
        DataRelation[] nestedParentRelations = t.NestedParentRelations;
        foreach (DataRelation rel in nestedParentRelations) {
            if (rel.ParentTable == t) {
                foreach (DataRow r in t.Rows) {
                    foreach (DataRelation rel2 in nestedParentRelations) {
                        r.CheckForLoops(rel2);
                    }
                }
            }
        }
    }

    if (!isEmpty) {

```

```

        this.Merge(newDs);
        if (this.dataSetName == "NewDataSet")
            this.dataSetName = newDs.dataSetName;
        newDs.EnforceConstraints = fEnforce;
    }
    this.EnforceConstraints = fEnforce;
}
finally {
    Bid.ScopeLeave(ref hscp);
}
}

/// <devdoc>
/// </devdoc>
public XmlReadMode ReadXml(XmlReader reader, XmlReadMode mode)
{
    return ReadXml(reader, mode, false);
}

internal XmlReadMode ReadXml(XmlReader reader, XmlReadMode mode, bool
denyResolving)
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.ReadXml|INFO> %d#,
mode=%d{ds.XmlReadMode}, denyResolving=%d{bool}\n", ObjectID, (int)mode, denyResolving);
    try {

        XmlReadMode ret = mode;

        if (reader == null)
            return ret;

        if (mode == XmlReadMode.Auto) {
            // Dev11 915079: nested ReadXml calls on the same DataSet must be
done outside of RowDiffIdUsage scope
            return ReadXml(reader);
        }

        DataTable.DSRowDiffIdUsageSection rowDiffIdUsage = new
DataTable.DSRowDiffIdUsageSection();
        try {

            bool fSchemaFound = false;

```

```

    bool fDataFound = false;
    bool fIsXdr = false;
    int iCurrentDepth = -1;

    // Dev11 904428: prepare and cleanup rowDiffId hashtable
    rowDiffIdUsage.Prepare(this);

    if (reader is XmlTextReader)
        ((XmlTextReader)reader).WhitespaceHandling =
WhitespaceHandling.Significant;

    XmlDocument xdoc = new XmlDocument(); // we may need this to infer
the schema

    if ((mode != XmlReadMode.Fragment) && (reader.NodeType ==
XmlNodeType.Element))
        iCurrentDepth = reader.Depth;

    reader.MoveToContent();
    XmlDataLoader xmlload = null;

    if (reader.NodeType == XmlNodeType.Element) {
        XmlElement topNode = null;
        if (mode == XmlReadMode.Fragment) {
            xdoc.AppendChild(xdoc.CreateElement("ds_sqlXmlWrappER"));
            topNode = xdoc.DocumentElement;
        }
        else { //handle the top node
            if ((reader.LocalName == Keywords.DIFFGRAM) &&
(reader.NamespaceURI == Keywords.DFFNS)) {
                if ((mode == XmlReadMode.DiffGram) || (mode ==
XmlReadMode.IgnoreSchema)) {
                    this.ReadXmlDiffgram(reader);
                    // read the closing tag of the current element
                    ReadEndElement(reader);
                }
                else {
                    reader.Skip();
                }
                return ret;
            }

            if (reader.LocalName == Keywords.XDR_SCHEMA &&
reader.NamespaceURI == Keywords.XDRNS) {

```

```

        // load XDR schema and exit
        if ((mode != XmlReadMode.IgnoreSchema) && (mode !=
XmlReadMode.InferSchema) &&
            (mode != XmlReadMode.InferTypedSchema))
        {
            ReadXDRSchema(reader);
        }
        else {
            reader.Skip();
        }
        return ret; //since the top level element is a schema
return
    }

    if (reader.LocalName == Keywords.XSD_SCHEMA &&
reader.NamespaceURI == Keywords.XSDNS) {
        // load XSD schema and exit
        if ((mode != XmlReadMode.IgnoreSchema) && (mode !=
XmlReadMode.InferSchema) &&
            (mode != XmlReadMode.InferTypedSchema))
        {
            ReadXSDSchema(reader, denyResolving);
        }
        else
            reader.Skip();
        return ret; //since the top level element is a schema
return
    }

    if (reader.LocalName == Keywords.XSD_SCHEMA &&
reader.NamespaceURI.StartsWith(Keywords.XSD_NS_START, StringComparison.Ordinal))
        throw
ExceptionBuilder.DataSetUnsupportedSchema(Keywords.XSDNS);

    // now either the top level node is a table and we load it
through dataReader...

    // ... or backup the top node and all its attributes
    topNode = xdoc.CreateElement(reader.Prefix, reader.LocalName,
reader.NamespaceURI);

    if (reader.HasAttributes) {
        int attrCount = reader.AttributeCount;
        for (int i = 0; i < attrCount; i++) {
            reader.MoveToAttribute(i);
            if

```

```

(reader.NamespaceURI.Equals(Keywords.XSD_XMLNS_NS))
    topNode.SetAttribute(reader.Name,
reader.GetAttribute(i));

    else {
        XmlAttribute attr =
topNode.SetAttributeNode(reader.LocalName, reader.NamespaceURI);
        attr.Prefix = reader.Prefix;
        attr.Value = reader.GetAttribute(i);
    }
}
}
reader.Read();
}

while (MoveToElement(reader, iCurrentDepth)) {

    if (reader.LocalName == Keywords.XDR_SCHEMA &&
reader.NamespaceURI == Keywords.XDRNS) {
        // load XDR schema
        if (!fSchemaFound && !fDataFound && (mode !=
XmlReadMode.IgnoreSchema) && (mode != XmlReadMode.InferSchema) &&
(mode != XmlReadMode.InferTypedSchema))
        {
            ReadXDRSchema(reader);
            fSchemaFound = true;
            fIsXdr = true;
        }
        else {
            reader.Skip();
        }
        continue;
    }

    if (reader.LocalName == Keywords.XSD_SCHEMA &&
reader.NamespaceURI == Keywords.XSDNS) {
        // load XSD schema and exit
        if ((mode != XmlReadMode.IgnoreSchema) && (mode !=
XmlReadMode.InferSchema) &&
(mode != XmlReadMode.InferTypedSchema))
        {
            ReadXSDSchema(reader, denyResolving);
            fSchemaFound = true;
        }
        else {

```

```

        reader.Skip();
    }
    continue;
}

    if ((reader.LocalName == Keywords.DIFFGRAM) &&
(reader.NamespaceURI == Keywords.DFFNS)) {
        if ((mode == XmlReadMode.DiffGram) || (mode ==
XmlReadMode.IgnoreSchema)) {

            this.ReadXmlDiffgram(reader);
            ret = XmlReadMode.DiffGram;
        }
        else {
            reader.Skip();
        }
        continue;
    }

    if (reader.LocalName == Keywords.XSD_SCHEMA &&
reader.NamespaceURI.StartsWith(Keywords.XSD_NS_START, StringComparison.Ordinal))
        throw
ExceptionBuilder.DataSetUnsupportedSchema(Keywords.XSDNS);

    if (mode == XmlReadMode.DiffGram) {
        reader.Skip();
        continue; // we do not read data in diffgram mode
    }

    // if we are here we found some data
    fDataFound = true;

    if (mode == XmlReadMode.InferSchema || mode ==
XmlReadMode.InferTypedSchema) { //save the node in DOM until the end;
        XmlNode node = xdoc.ReadNode(reader);
        topNode.AppendChild(node);
    }
    else {
        if (xmlload == null)
            xmlload = new XmlDataLoader(this, fIsXdr, topNode,
mode == XmlReadMode.IgnoreSchema);
        xmlload.LoadData(reader);
    }
} //end of the while

```

```

        // read the closing tag of the current element
        ReadEndElement(reader);

        // now top node contains the data part
        xdoc.AppendChild(topNode);
        if (xmlload == null)
            xmlload = new XmlDataLoader(this, fIsXdr, mode ==
XmlReadMode.IgnoreSchema);

        if (mode == XmlReadMode.DiffGram) {
            // we already got the diffs through XmlReader interface
            return ret;
        }

        // Load Data
        if (mode == XmlReadMode.InferSchema || mode ==
XmlReadMode.InferTypedSchema) {
            InferSchema(xdoc, null, mode);
            ret = XmlReadMode.InferSchema;
            xmlload.FromInference = true;
            //
        }
        try {
            xmlload.LoadData(xdoc);
        }
        finally {
            xmlload.FromInference = false;
        }
    }

    return ret;
}
finally {
    // Dev11 904428: prepare and cleanup rowDiffId hashtable
    rowDiffIdUsage.Cleanup();
}
}
finally {
    Bid.ScopeLeave(ref hscp);
}
}

```

```

/// <devdoc>

```

```

/// </devdoc>
public XmlReadMode ReadXml(Stream stream, XmlReadMode mode)
{
    if (stream == null)
        return XmlReadMode.Auto;

    XmlTextReader reader = (mode == XmlReadMode.Fragment) ? new
XmlTextReader(stream, XmlNodeType.Element, null) : new XmlTextReader(stream);
    // Prevent Dtd entity in dataset
    reader.XmlResolver = null;
    return ReadXml(reader, mode, false);
}

/// <devdoc>
/// </devdoc>
public XmlReadMode ReadXml(TextReader reader, XmlReadMode mode)
{
    if (reader == null)
        return XmlReadMode.Auto;

    XmlTextReader xmlreader = (mode == XmlReadMode.Fragment) ? new
XmlTextReader(reader.ReadToEnd(), XmlNodeType.Element, null) : new XmlTextReader(reader);
    // Prevent Dtd entity in dataset
    xmlreader.XmlResolver = null;
    return ReadXml(xmlreader, mode, false);
}

/// <devdoc>
/// </devdoc>
[ResourceExposure(ResourceScope.Machine)]
[ResourceConsumption(ResourceScope.Machine)]
public XmlReadMode ReadXml(string fileName, XmlReadMode mode)
{
    XmlTextReader xr = null;
    if (mode == XmlReadMode.Fragment) {
        FileStream stream = new FileStream(fileName, FileMode.Open);
        xr = new XmlTextReader(stream, XmlNodeType.Element, null);
    }
    else
        xr = new XmlTextReader(fileName);

    // Prevent Dtd entity in dataset
    xr.XmlResolver = null;

```

```

        try
        {
            return ReadXml(xr, mode, false);
        }
        finally {
            xr.Close();
        }
    }

    /// <devdoc>
    ///     Writes schema and data for the DataSet.
    /// </devdoc>
    public void WriteXml(Stream stream)
    {
        WriteXml(stream, XmlWriteMode.IgnoreSchema);
    }

    /// <devdoc>
    /// </devdoc>
    public void WriteXml(TextWriter writer)
    {
        WriteXml(writer, XmlWriteMode.IgnoreSchema);
    }

    /// <devdoc>
    /// </devdoc>
    public void WriteXml(XmlWriter writer)
    {
        WriteXml(writer, XmlWriteMode.IgnoreSchema);
    }

    /// <devdoc>
    ///     <para>[To be supplied.]</para>
    /// </devdoc>
    [ResourceExposure(ResourceScope.Machine)]
    [ResourceConsumption(ResourceScope.Machine)]
    public void WriteXml(String fileName)
    {
        WriteXml(fileName, XmlWriteMode.IgnoreSchema);
    }

    /// <devdoc>
    ///     Writes schema and data for the DataSet.

```

```

/// </devdoc>
public void WriteXml(Stream stream, XmlWriteMode mode)
{
    if (stream != null) {
        XmlTextWriter w = new XmlTextWriter(stream, null);
        w.Formatting = Formatting.Indented;

        WriteXml(w, mode);
    }
}

/// <devdoc>
/// </devdoc>
public void WriteXml(TextWriter writer, XmlWriteMode mode)
{
    if (writer != null) {
        XmlTextWriter w = new XmlTextWriter(writer);
        w.Formatting = Formatting.Indented;

        WriteXml(w, mode);
    }
}

/// <devdoc>
/// </devdoc>
public void WriteXml(XmlWriter writer, XmlWriteMode mode)
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.WriteXml|API> %d#",
mode=%d{ds.XmlWriteMode}\n", ObjectID, (int)mode);
    try {
        // Generate SchemaTree and write it out
        if (writer != null) {

            if (mode == XmlWriteMode.DiffGram) {
                // Create and save the updates
                // new UpdateTreeGen(UpdateTreeGen.UPDATE,
(DataRowState)(-1), this).Save(writer, null);
                new NewDiffgramGen(this).Save(writer);
            }
            else {
                // Create and save xml data
                new XmlDataTreeWriter(this).Save(writer, mode ==
XmlWriteMode.WriteSchema);
            }
        }
    }
}

```

```

        }
    }
}
finally {
    Bid.ScopeLeave(ref hscp);
}
}

/// <devdoc>
///     <para>[To be supplied.]</para>
/// </devdoc>
[ResourceExposure(ResourceScope.Machine)]
[ResourceConsumption(ResourceScope.Machine)]
public void WriteXml(String fileName, XmlWriteMode mode)
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.WriteXml|API> %d#", fileName='%ls',
mode=%d{ds.XmlWriteMode}\n", ObjectID, fileName, (int)mode);
    XmlTextWriter xw = new XmlTextWriter(fileName, null);
    try {
        xw.Formatting = Formatting.Indented;
        xw.WriteStartDocument(true);
        if (xw != null) {
            // Create and save the updates
            if (mode == XmlWriteMode.DiffGram) {
                new NewDiffgramGen(this).Save(xw);
            }
            else {
                // Create and save xml data
                new XmlDataTreeWriter(this).Save(xw, mode ==
XmlWriteMode.WriteSchema);
            }
        }
        xw.WriteEndDocument();
    }
    finally {
        xw.Close();
        Bid.ScopeLeave(ref hscp);
    }
}

/// <devdoc>
///     <para>
///         Gets the collection of parent relations which belong to a

```

```

    ///      specified table.
    ///      </para>
    /// </devdoc>
    internal DataRelationCollection GetParentRelations(DataTable table)
    {
        return table.ParentRelations;
    }

    /// <devdoc>
    ///      <para>
    ///          Merges this <see cref='System.Data.DataSet'/> into a specified <see
    cref='System.Data.DataSet'/>.
    ///      </para>
    /// </devdoc>
    public void Merge(DataSet dataSet)
    {
        IntPtr hscp;
        Bid.ScopeEnter(out hscp, "<ds.DataSet.Merge|API> %d#, dataSet=%d\n",
ObjectID, (dataSet != null) ? dataSet.ObjectID : 0);
        try {
            Merge(dataSet, false, MissingSchemaAction.Add);
        }
        finally {
            Bid.ScopeLeave(ref hscp);
        }
    }

    /// <devdoc>
    ///      <para>
    ///          Merges this <see cref='System.Data.DataSet'/> into a specified <see
    cref='System.Data.DataSet'/> preserving changes according to
    ///          the specified argument.
    ///      </para>
    /// </devdoc>
    public void Merge(DataSet dataSet, bool preserveChanges)
    {
        IntPtr hscp;
        Bid.ScopeEnter(out hscp, "<ds.DataSet.Merge|API> %d#, dataSet=%d,
preserveChanges=%d{bool}\n", ObjectID, (dataSet != null) ? dataSet.ObjectID : 0,
preserveChanges);
        try {
            Merge(dataSet, preserveChanges, MissingSchemaAction.Add);
        }
        finally {

```

```

        Bid.ScopeLeave(ref hscp);
    }
}

/// <devdoc>
///     <para>
///         Merges this <see cref='System.Data.DataSet'/> into a specified <see
cref='System.Data.DataSet'/> preserving changes according to
///         the specified argument, and handling an incompatible schema according
to the
///         specified argument.
///     </para>
/// </devdoc>
public void Merge(DataSet dataSet, bool preserveChanges, MissingSchemaAction
missingSchemaAction) {
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.Merge|API> %d#, dataSet=%d,
preserveChanges=%d{bool}, missingSchemaAction=%d{ds.MissingSchemaAction}\n", ObjectID,
(dataSet != null) ? dataSet.ObjectID : 0, preserveChanges, (int)missingSchemaAction);
    try {

        // Argument checks
        if (dataSet == null)
            throw ExceptionBuilder.ArgumentNull("dataSet");

        switch (missingSchemaAction) { // @perfnote: Enum.IsDefined
            case MissingSchemaAction.Add:
            case MissingSchemaAction.Ignore:
            case MissingSchemaAction.Error:
            case MissingSchemaAction.AddWithKey:
                Merger merger = new Merger(this, preserveChanges,
missingSchemaAction);
                merger.MergeDataSet(dataSet);
                break;
            default:
                throw Common.ADP.InvalidMissingSchemaAction(missingSchemaAction);
        }
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

/// <devdoc>

```

```

    /// <para>
    ///     Merges this <see cref='System.Data.DataTable'/> into a specified <see
    cref='System.Data.DataTable'/>.
    /// </para>
    /// </devdoc>
    public void Merge(DataTable table)
    {
        IntPtr hscp;
        Bid.ScopeEnter(out hscp, "<ds.DataSet.Merge|API> %d#, table=%d\n", ObjectID,
(table != null) ? table.ObjectID : 0);
        try {
            Merge(table, false, MissingSchemaAction.Add);
        }
        finally {
            Bid.ScopeLeave(ref hscp);
        }
    }

    /// <devdoc>
    /// <para>
    ///     Merges this <see cref='System.Data.DataTable'/> into a specified <see
    cref='System.Data.DataTable'/>. with a value to preserve changes
    ///     made to the target, and a value to deal with missing schemas.
    /// </para>
    /// </devdoc>
    public void Merge(DataTable table, bool preserveChanges, MissingSchemaAction
missingSchemaAction)
    {
        IntPtr hscp;
        Bid.ScopeEnter(out hscp, "<ds.DataSet.Merge|API> %d#, table=%d,
preserveChanges=%d{bool}, missingSchemaAction=%d{ds.MissingSchemaAction}\n", ObjectID,
(table != null) ? table.ObjectID : 0, preserveChanges, (int)missingSchemaAction);
        try {
            // Argument checks
            if (table == null)
                throw ExceptionBuilder.ArgumentNull("table");

            switch (missingSchemaAction) { // @perfnote: Enum.IsDefined
                case MissingSchemaAction.Add:
                case MissingSchemaAction.Ignore:
                case MissingSchemaAction.Error:
                case MissingSchemaAction.AddWithKey:
                    Merger merger = new Merger(this, preserveChanges,
missingSchemaAction);

```

```

        merger.MergeTable(table);
        break;
    default:
        throw Common.ADP.InvalidMissingSchemaAction(missingSchemaAction);
    }
}

finally {
    Bid.ScopeLeave(ref hscp);
}
}

/// <devdoc>
///     <para>[To be supplied.]</para>
/// </devdoc>
public void Merge(DataRow[] rows)
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.Merge|API> %d#, rows\n", ObjectID);
    try {
        Merge(rows, false, MissingSchemaAction.Add);
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

/// <devdoc>
///     <para>[To be supplied.]</para>
/// </devdoc>
public void Merge(DataRow[] rows, bool preserveChanges, MissingSchemaAction
missingSchemaAction)
{
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.Merge|API> %d#,
preserveChanges=%d{bool}, missingSchemaAction=%d{ds.MissingSchemaAction}\n", ObjectID,
preserveChanges, (int)missingSchemaAction);
    try {
        // Argument checks
        if (rows == null)
            throw ExceptionBuilder.ArgumentNull("rows");

        switch (missingSchemaAction) { // @perfnote: Enum.IsDefined
            case MissingSchemaAction.Add:

```

```

        case MissingSchemaAction.Ignore:
        case MissingSchemaAction.Error:
        case MissingSchemaAction.AddWithKey:
            Merger merger = new Merger(this, preserveChanges,
missingSchemaAction);
            merger.MergeRows(rows);
            break;
        default:
            throw Common.ADP.InvalidMissingSchemaAction(missingSchemaAction);
    }
}
finally {
    Bid.ScopeLeave(ref hscp);
}
}

protected virtual void OnPropertyChanging(PropertyChangedEventArgs pcevent)
{
    if (onPropertyChangingDelegate != null)
        onPropertyChangingDelegate(this, pcevent);
}

/// <devdoc>
///     Inheriting classes should override this method to handle this event.
///     Call base.OnMergeFailed to send this event to any registered event
///     listeners.
/// </devdoc>
internal void OnMergeFailed(MergeFailedEventArgs mfevent)
{
    if (onMergeFailed != null)
        onMergeFailed(this, mfevent);
    else
        throw ExceptionBuilder.MergeFailed(mfevent.Conflict);
}

internal void RaiseMergeFailed(DataTable table, string conflict,
MissingSchemaAction missingSchemaAction)
{
    if (MissingSchemaAction.Error == missingSchemaAction)
        throw ExceptionBuilder.MergeFailed(conflict);

    MergeFailedEventArgs mfevent = new MergeFailedEventArgs(table, conflict);
    OnMergeFailed(mfevent);
    return;
}

```

```

    }

    internal void OnDataRowCreated(DataRow row) {
        if (onDataRowCreated != null)
            onDataRowCreated(this, row);
    }

    internal void OnClearFunctionCalled(DataTable table) {
        if (onClearFunctionCalled != null)
            onClearFunctionCalled(this, table);
    }

    private void OnInitialized() {
        if (onInitialized != null) {
            onInitialized(this, EventArgs.Empty);
        }
    }

    /// <devdoc>
    /// This method should be overridden by subclasses to restrict tables being
removed.
    /// </devdoc>
    protected internal virtual void OnRemoveTable(DataTable table) {
    }

    internal void OnRemovedTable(DataTable table) {
        DataViewManager viewManager = defaultManager;
        if (null != viewManager) {
            viewManager.DataViewSettings.Remove(table);
        }
    }

    /// <devdoc>
    /// This method should be overridden by subclasses to restrict tables being
removed.
    /// </devdoc>
    protected virtual void OnRemoveRelation(DataRelation relation)
    {
    }

    //
    internal void OnRemoveRelationHack(DataRelation relation)
    {
        OnRemoveRelation(relation);
    }

```

```

}

protected internal void RaisePropertyChanging(string name)
{
    OnPropertyChanging(new PropertyChangedEventArgs(name));
}

internal DataTable[] TopLevelTables()
{
    return TopLevelTables(false);
}

internal DataTable[] TopLevelTables(bool forSchema)
{
    // first let's figure out if we can represent the given dataSet as a tree
using
    // the fact that all connected undirected graphs with n-1 edges are trees.
    List<DataTable> topTables = new List<DataTable>();

    if (forSchema) {
        // prepend the tables that are nested more than once
        for (int i = 0; i < Tables.Count; i++)
        {
            DataTable table = Tables[i];
            if (table.NestedParentsCount > 1 || table.SelfNested)
                topTables.Add(table);
        }
    }
    for (int i = 0; i < Tables.Count; i++)
    {
        DataTable table = Tables[i];
        if (table.NestedParentsCount == 0 && !topTables.Contains(table))
            topTables.Add(table);
    }
    if (topTables.Count == 0)
        return zeroTables;
    return topTables.ToArray();
}

/// <devdoc>
/// This method rolls back all the changes to have been made to this DataSet
since
    /// it was loaded or the last time AcceptChanges was called.

```

```

    /// Any rows still in edit-mode cancel their edits. New rows get removed.
    Modified and
    /// Deleted rows return back to their original state.
    /// </devdoc>
    public virtual void RejectChanges()
    {
        IntPtr hscp;
        Bid.ScopeEnter(out hscp, "<ds.DataSet.RejectChanges|API> %d#\n", ObjectID);
        try {
            bool fEnforce = EnforceConstraints;
            EnforceConstraints = false;
            for (int i = 0; i < Tables.Count; i++)
                Tables[i].RejectChanges();
            EnforceConstraints = fEnforce;
        }
        finally {
            Bid.ScopeLeave(ref hscp);
        }
    }

    /// <devdoc>
    ///     Resets the dataSet back to it's original state. Subclasses should
    override
    ///     to restore back to it's original state.
    ///
    public virtual void Reset()
    {
        IntPtr hscp;
        Bid.ScopeEnter(out hscp, "<ds.DataSet.Reset|API> %d#\n", ObjectID);
        try {
            for (int i = 0; i < Tables.Count; i++) {
                ConstraintCollection cons = Tables[i].Constraints;
                for (int j = 0; j < cons.Count; ) {
                    if (cons[j] is ForeignKeyConstraint) {
                        cons.Remove(cons[j]);
                    }
                    else
                        j++;
                }
            }
            // SQLBU 502734: because of SQLBU 501916, dependent tables need to be
            notified when a table is cleared
            // if relations are removed first, then exceptions happen

```

```

        Clear();
        Relations.Clear();
        Tables.Clear();
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

internal bool ValidateCaseConstraint() {
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.ValidateCaseConstraint|INFO> %d#\n",
ObjectID);
    try {
        DataRelation relation = null;
        for (int i = 0; i < Relations.Count; i++) {
            relation = Relations[i];
            if (relation.ChildTable.CaseSensitive !=
relation.ParentTable.CaseSensitive)
                return false;
        }

        ForeignKeyConstraint constraint = null;
        ConstraintCollection constraints = null;
        for (int i = 0; i < Tables.Count; i++) {
            constraints = Tables[i].Constraints;
            for (int j = 0; j < constraints.Count; j++) {
                if (constraints[j] is ForeignKeyConstraint) {
                    constraint = (ForeignKeyConstraint)constraints[j];
                    if (constraint.Table.CaseSensitive !=
constraint.RelatedTable.CaseSensitive)
                        return false;
                }
            }
        }
        return true;
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

internal bool ValidateLocaleConstraint() {
    IntPtr hscp;

```

```

        Bid.ScopeEnter(out hscp, "<ds.DataSet.ValidateLocaleConstraint|INFO> %d#\n",
ObjectID);
        try {
            DataRelation relation = null;
            for (int i = 0; i < Relations.Count; i++) {
                relation = Relations[i];
                if (relation.ChildTable.Locale.LCID !=
relation.ParentTable.Locale.LCID)
                    return false;
            }

            ForeignKeyConstraint constraint = null;
            ConstraintCollection constraints = null;
            for (int i = 0; i < Tables.Count; i++) {
                constraints = Tables[i].Constraints;
                for (int j = 0; j < constraints.Count; j++) {
                    if (constraints[j] is ForeignKeyConstraint) {
                        constraint = (ForeignKeyConstraint)constraints[j];
                        if (constraint.Table.Locale.LCID !=
constraint.RelatedTable.Locale.LCID)
                            return false;
                    }
                }
            }
            return true;
        }
        finally {
            Bid.ScopeLeave(ref hscp);
        }
    }

    // Microsoft: may be better to rewrite this as nonrecursive?
    internal DataTable FindTable(DataTable baseTable, PropertyDescriptor[] props, int
propStart) {
        if (props.Length < propStart + 1)
            return baseTable;

        PropertyDescriptor currentProp = props[propStart];

        if (baseTable == null) {
            // the accessor is the table name. if we don't find it, return null.
            if (currentProp is DataTablePropertyDescriptor) {
                return FindTable(((DataTablePropertyDescriptor)currentProp).Table,
props, propStart + 1);
            }
        }
    }

```

```

    }
    return null;
}

    if (currentProp is DataRelationPropertyDescriptor) {
        return
FindTable(((DataRelationPropertyDescriptor)currentProp).Relation.ChildTable, props,
propStart + 1);
    }

    return null;
}

    protected virtual void ReadXmlSerializable(XmlReader reader) {
        //WebData 96421 and 104709, this is DataSet side fix for the thrown exception
        // <DataSet xsi:nil="true"> does not mean DataSet is null, but it does not
have any child
        // so dont do anything, ignore the attributes and just return empty DataSet;
        this.UseDataSetSchemaOnly = false;
        this.UdtIsWrapped = false;

        if (reader.HasAttributes) {
            const string xsinill = Keywords.XSI + ":" + Keywords.XSI_NIL;
            if (reader.MoveToAttribute(xsinill)) {
                string nilAttrib = reader.GetAttribute(xsinill);
                if (string.Compare(nilAttrib, "true", StringComparison.Ordinal) == 0)
// case sensitive true comparison
                    MoveToElement(reader, 1);
                    return;
            }
        }

        const string useDataSetSchemaOnlyString = Keywords.MSD + ":" +
Keywords.USEDATASETSHEMAONLY;
        if (reader.MoveToAttribute(useDataSetSchemaOnlyString)) {
            string _useDataSetSchemaOnly =
reader.GetAttribute(useDataSetSchemaOnlyString);
            if (string.Equals(_useDataSetSchemaOnly, "true",
StringComparison.Ordinal) ||
                string.Equals(_useDataSetSchemaOnly, "1",
StringComparison.Ordinal))
            {
                this.UseDataSetSchemaOnly = true;
            }
        }
    }
}

```

```

        else if (!string.Equals(_useDataSetSchemaOnly, "false",
StringComparison.Ordinal) &&
                !string.Equals(_useDataSetSchemaOnly, "0",
StringComparison.Ordinal))
        {
            throw
ExceptionBuilder.InvalidAttributeValue(Keywords.USEDATASETSHEMAONLY,
_useDataSetSchemaOnly);
        }
    }

    const string udtIsWrappedString = Keywords.MSD + ":" +
Keywords.UDTCOLUMNVALUEWRAPPED;
    if (reader.MoveToAttribute(udtIsWrappedString)) {
        string _udtIsWrappedString = reader.GetAttribute(udtIsWrappedString);
        if (string.Equals(_udtIsWrappedString, "true",
StringComparison.Ordinal) ||
            string.Equals(_udtIsWrappedString, "1",
StringComparison.Ordinal))
        {
            this.UdtIsWrapped = true;
        }
        else if (!string.Equals(_udtIsWrappedString, "false",
StringComparison.Ordinal) &&
                !string.Equals(_udtIsWrappedString, "0",
StringComparison.Ordinal))
        {
            throw
ExceptionBuilder.InvalidAttributeValue(Keywords.UDTCOLUMNVALUEWRAPPED,
_udtIsWrappedString);
        }
    }

    ReadXml(reader, XmlReadMode.DiffGram, true);
}

protected virtual System.Xml.Schema.XmlSchema GetSchemaSerializable() {
    return null;
}

/*****
To publish
int_tools\webserviceadmin.exe -install Application Application.dll
*****/

```

To test

`http://localhost/application/service.asmx?wsdl`

or

`wsdl.exe /namespace:UserNamespace http://localhost/Application/Service.asmx?wsdl
/out:Service.cs`

The V1.0 & V1.1 WSDL for Untyped DataSet being returned as a result (no parameters)

```
<s:element name="anyUserSpecifiedMethodName">
  <!-- This is where parameters go -->
  <s:complexType />
</s:element>
<s:element name="anyUserSpecifiedMethodName"+"Response">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1"
name="anyUserSpecifiedMethodName"+"Result">
        <s:complexType>
          <s:sequence>
            <s:element ref="s:schema" />
            <s:any />
          </s:sequence>
        </s:complexType>
      </s:element>
    </s:sequence>
  </s:complexType>
</s:element>
```

The V1.0 & V1.1 WSDL for Untyped DataSet as parameter, string for the result

```
<s:element name="anyUserSpecifiedMethodName">
  <!-- This is where parameters go -->
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="set">
        <s:complexType>
          <s:sequence>
            <s:element ref="s:schema" />
            <s:any />
          </s:sequence>
        </s:complexType>
      </s:element>
    </s:sequence>
  </s:complexType>
```

```

</s:element>
<s:element name="anyUserSpecifiedMethodName"+"Response">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1"
name="anyUserSpecifiedMethodName"+"Result" type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>

```

The V2.0 WSDL for Untyped DataSet being returned as a result (no parameters)

```

<s:element name="anyUserSpecifiedMethodName">
  <!-- This is where parameters go -->
  <s:complexType />
</s:element>
<s:element name="anyUserSpecifiedMethodName"+"Response">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1"
name="anyUserSpecifiedMethodName"+"Result">
        <s:complexType>
          <s:sequence maxOccurs="unbounded">
            <s:any minOccurs="0"
namespace="http://www.w3.org/2001/XMLSchema" processContents="lax" />
            <s:any minOccurs="0" namespace="urn:schemas-microsoft-
com:xml-diffgram-v1" processContents="lax" />
          </s:sequence>
        </s:complexType>
      </s:element>
    </s:sequence>
  </s:complexType>
</s:element>

```

The V2.0 WSDL for Untyped DataSet as a parameter, string for the result

```

<s:element name="anyUserSpecifiedMethodName">
  <!-- This is where parameters go -->
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1"
name="anyUserSpecifiedParameterName">
        <s:complexType>
          <s:sequence maxOccurs="unbounded">
            <s:any minOccurs="0"
namespace="http://www.w3.org/2001/XMLSchema" processContents="lax" />

```

```

        <s:any minOccurs="0" namespace="urn:schemas-microsoft-
com:xml-diffgram-v1" processContents="lax" />
    </s:sequence>
</s:complexType>
</s:element>
</s:sequence>
</s:complexType>
</s:element>
<s:element name="anyUserSpecifiedMethodName"+"Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1"
name="anyUserSpecifiedMethodName"+"Result" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>

```

The V1.0, V1.1 & V2.0 WSDL for Typed DataSet

```

<s:import schemaLocation="http://localhost/application/service.asmx?
schema=typedDataSetName" namespace="typedDataSetName" />
<s:element name="anyUserSpecifiedMethodName">
    <!-- This is where parameters go -->
    <s:complexType />
</s:element>
<s:element name="anyUserSpecifiedMethodName"+"Response">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1"
name="anyUserSpecifiedMethodName"+"Result">
                <s:complexType>
                    <s:sequence>
                        <s:any namespace="typedDataSetName" />
                    </s:sequence>
                </s:complexType>
            </s:element>
        </s:sequence>
    </s:complexType>
</s:element>

```

*****/

```

public static XmlSchemaComplexType GetDataSetSchema(XmlSchemaSet schemaSet) {
    // For performance reasons we are exploiting the fact that config files
content is constant
    // for a given appdomain so we can safely cache the prepared schema complex
type and reuse it

```

```

        if (schemaTypeForWSDL == null) { // to change the config file, appdomain
needs to restart; so it seems safe to cache the schema
            XmlSchemaComplexType tempWSDL = new XmlSchemaComplexType();
            XmlSchemaSequence sequence = new XmlSchemaSequence();

            if (PublishLegacyWSDL())
            { // Default is Version 1.0
                XmlSchemaElement elem = new XmlSchemaElement();
                elem.RefName = new XmlQualifiedName(Keywords.XSD_SCHEMA,
Keywords.XSDNS);

                sequence.Items.Add(elem);
                XmlSchemaAny any = new XmlSchemaAny();
                sequence.Items.Add(any);
            }
            else
            { // this means Version == V2.0 or newer
                XmlSchemaAny any = new XmlSchemaAny();
                any.Namespace = XmlSchema.Namespace;
                any.MinOccurs = 0;
                any.ProcessContents = XmlSchemaContentProcessing.Lax;
                sequence.Items.Add(any);

                any = new XmlSchemaAny();
                any.Namespace = Keywords.DFFNS;
                any.MinOccurs = 0; // when recognizing WSDL - MinOccurs="0" denotes
DataSet, a MinOccurs="1" for DataTable
                any.ProcessContents = XmlSchemaContentProcessing.Lax;
                sequence.Items.Add(any);
                sequence.MaxOccurs = Decimal.MaxValue;
            }
            tempWSDL.Particle = sequence;

            schemaTypeForWSDL = tempWSDL;
        }
        return schemaTypeForWSDL;
    }

    /*****
    <configuration>
      <configSections>
        <section name="system.data.dataset"
type="System.Configuration.NameValueFileSectionHandler, System,
Version=%ASSEMBLY_VERSION%, Culture=neutral, PublicKeyToken=%ECMA_PUBLICKEY%"
restartOnExternalChanges="false" />

```

```

</configSections>
<system.data.dataset>
    <!-- if WSDL_VERSION is missing it will default to 1.0
        <add key="WSDL_VERSION" value="1.0"/>
    -->
    <add key="WSDL_VERSION" value="2.0"/>
</system.data.dataset>
</configuration>
*****/

private static bool PublishLegacyWSDL()
{
    Single version = 1.0f; // Default is Version 1.0
    NameValueCollection settings =
(NameValueCollection)PrivilegedConfigurationManager.GetSection(Keywords.WS_DATASETFULLQNA
ME);

    if (settings != null)
    {
        string[] values = settings.GetValues(Keywords.WS_VERSION);
        if ((null != values) && (0 < values.Length) && (null != values[0]))
        { // will throw FormatException if not a valid number
            version = Single.Parse(values[0], CultureInfo.InvariantCulture);
        }
    }

    return (version < 2.0f); // if config does not exist, Default is Version 1.0
}

XmlSchema IXmlSerializable.GetSchema() {
    if (GetType() == typeof(DataSet)) {
        return null;
    }
    MemoryStream stream = new MemoryStream();
    // WriteXmlSchema(new XmlTextWriter(stream, null));
    XmlWriter writer = new XmlTextWriter(stream, null);
    if (writer != null) {
        (new XmlTreeGen(SchemaFormat.WebService)).Save(this, writer);
    }
    stream.Position = 0;
    return XmlSchema.Read(new XmlTextReader(stream), null);
    // return GetSchemaSerializable();
}

void IXmlSerializable.ReadXml(XmlReader reader) {
    bool fNormalization = true;
    XmlTextReader xmlTextReader = null;

```

```

IXmlTextParser xmlTextParser = reader as IXmlTextParser;
if (xmlTextParser != null) {
    fNormalization = xmlTextParser.Normalized;
    xmlTextParser.Normalized = false;
}
else {
    xmlTextReader = reader as XmlTextReader;
    if (xmlTextReader != null) {
        fNormalization = xmlTextReader.Normalization;
        xmlTextReader.Normalization = false;
    }
}

ReadXmlSerializable(reader);

if (xmlTextParser != null)
    xmlTextParser.Normalized = fNormalization;
else if (xmlTextReader != null)
    xmlTextReader.Normalization = fNormalization;
}

void IXmlSerializable.WriteXml(XmlWriter writer) {
    this.WriteXmlSchema(writer, SchemaFormat.WebService, (Converter<Type,
string>) null);
    this.WriteXml(writer, XmlWriteMode.DiffGram);
}

public virtual void Load(IDataReader reader, LoadOption loadOption,
FillErrorEventHandler errorHandler, params DataTable[] tables) {
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.Load|API> reader,
loadOption=%d{ds.LoadOption}", (int)loadOption);
    try {
        foreach (DataTable dt in tables) {
            Common.ADP.CheckArgumentNull(dt, "tables");
            if (dt.DataSet != this) {
                throw ExceptionBuilder.TableNotInTheDataSet(dt.TableName);
            }
        }
        Common.LoadAdapter adapter = new Common.LoadAdapter();
        adapter.FillLoadOption = loadOption;
        adapter.MissingSchemaAction = MissingSchemaAction.AddWithKey;
        if (null != errorHandler) {
            adapter.FillError += errorHandler;
        }
    }
}

```

```

        }
        adapter.FillFromReader(tables, reader, 0, 0);

        if (!reader.IsClosed && !reader.NextResult()) { //
            reader.Close();
        }
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

public void Load(IDataReader reader, LoadOption loadOption, params DataTable[]
tables) {
    Load(reader, loadOption, null, tables);
}

public void Load(IDataReader reader, LoadOption loadOption, params string[]
tables) {
    Common.ADP.CheckArgumentNull(tables, "tables");
    DataTable[] dataTables = new DataTable[tables.Length];
    for (int i = 0; i < tables.Length; i++) {
        DataTable tempDT = this.Tables[tables[i]];
        if (null == tempDT) {
            tempDT = new DataTable(tables[i]);
            // fxcop: new DataTable should inherit the CaseSensitive, Locale,
Namespace from DataSet
            Tables.Add(tempDT);
        }
        dataTables[i] = tempDT;
    }
    Load(reader, loadOption, null, dataTables);
}

public DataTableReader CreateDataReader() {
    if (Tables.Count == 0)
        throw ExceptionBuilder.CannotCreateDataReaderOnEmptyDataSet();

    DataTable[] dataTables = new DataTable[Tables.Count];
    for (int i = 0; i < Tables.Count; i++) {
        dataTables[i] = Tables[i];
    }
    return CreateDataReader(dataTables);
}

```

```

public DataTableReader CreateDataReader(params DataTable[] dataTables) {
    IntPtr hscp;
    Bid.ScopeEnter(out hscp, "<ds.DataSet.GetDataReader|API> %d#\n", ObjectID);
    try {
        if (dataTables.Length == 0)
            throw ExceptionBuilder.DataTableReaderArgumentIsEmpty();

        for (int i = 0; i < dataTables.Length; i++) {
            if (dataTables[i] == null)
                throw ExceptionBuilder.ArgumentContainsNullValue();
        }

        return new DataTableReader(dataTables);
    }
    finally {
        Bid.ScopeLeave(ref hscp);
    }
}

internal string MainTableName {
    get {
        return mainTableName;
    }
    set {
        this.mainTableName = value;
    }
}

internal int ObjectID {
    get {
        return _objectID;
    }
}
}

```

```

public class DataSetSchemaImporterExtension : SchemaImporterExtension {
    // DataSetSchemaImporterExtension is used for WebServices, it is used to
    recognize the schema of DataSet within wsdl
    // If a non 2.0 enabled DataSetSchemaImporterExtension, wsdl will generate a
    classes that you can't cast to dataset / datatable

    Hashtable importedTypes = new Hashtable();

```

```

    /// <devdoc>
    ///     <para>[To be supplied.]</para>
    /// </devdoc>
    public override string ImportSchemaType(string name, string schemaNamespace,
    XmlSchemaObject context, XmlSchemas schemas, XmlSchemaImporter importer, CodeCompileUnit
    compileUnit, CodeNamespace mainNamespace, CodeGenerationOptions options, CodeDomProvider
    codeProvider) {
        IList values = schemas.GetSchemas(schemaNamespace);
        if (values.Count != 1) {
            return null;
        }
        XmlSchema schema = values[0] as XmlSchema;
        if (schema == null)
            return null;
        XmlSchemaType type = (XmlSchemaType)schema.SchemaTypes[new
    XmlQualifiedName(name, schemaNamespace)];
        return ImportSchemaType(type, context, schemas, importer, compileUnit,
    mainNamespace, options, codeProvider);
    }

    /// <devdoc>
    ///     <para>[To be supplied.]</para>
    /// </devdoc>
    public override string ImportSchemaType(XmlSchemaType type, XmlSchemaObject
    context, XmlSchemas schemas, XmlSchemaImporter importer, CodeCompileUnit compileUnit,
    CodeNamespace mainNamespace, CodeGenerationOptions options, CodeDomProvider codeProvider)
    {
        if (type == null) {
            return null;
        }
        if (importedTypes[type] != null) {
            mainNamespace.Imports.Add(new
    CodeNamespaceImport(typeof(DataSet).Namespace));
            compileUnit.ReferencedAssemblies.Add("System.Data.dll");
            return (string)importedTypes[type];
        }
        if (!(context is XmlSchemaElement))
            return null;

        XmlSchemaElement e = (XmlSchemaElement)context;

        // recognizing the following is important, but not as part of SQLPT
    120015394: Support WSI Compliant WSDL for DataSet

```

```

        // <xs:element name="NewDataSet" msdata:IsDataSet="true">
        // see also SQLBU 338644, 410965, 423446
        //if (IsDataSet(e))
        //{
        //    return GenerateTypedDataSet(e, schemas, mainNamespace,
compileUnit.ReferencedAssemblies, codeProvider);
        //}

        if (type is XmlSchemaComplexType) {
            XmlSchemaComplexType ct = (XmlSchemaComplexType)type;

            if (ct.Particle is XmlSchemaSequence)
            {
                XmlSchemaObjectCollection items =
((XmlSchemaSequence)ct.Particle).Items;
                if ((2 == items.Count) && (items[0] is XmlSchemaAny) && (items[1] is
XmlSchemaAny))
                {
                    XmlSchemaAny any0 = (XmlSchemaAny)items[0];
                    XmlSchemaAny any1 = (XmlSchemaAny)items[1];
                    if ((any0.Namespace == XmlSchema.Namespace) && (any1.Namespace ==
"urn:schemas-microsoft-com:xml-diffgram-v1"))
                    {
                        // new diffgram format
                        string ns = null;
                        foreach (XmlSchemaAttribute a in ct.Attributes)
                        {
                            if (a.Name == "namespace")
                            {
                                ns = a.FixedValue.Trim();
                                break;
                            }
                        }
                        bool isDataSet = false;

                        // check for DataSet or DataTable
                        if (((XmlSchemaSequence)ct.Particle).MaxOccurs ==
Decimal.MaxValue)
                        {
                            isDataSet = true;
                        }
                        else if (any0.MaxOccurs == Decimal.MaxValue)
                        {
                            isDataSet = false;
                        }
                    }
                }
            }
        }
    }
}

```

```

        else
        {
            return null;
        }

        if (ns == null)
        {
            //Un-Typed DataSet / DataTable
            string typeName = isDataSet ? typeof(DataSet).FullName :
typeof(DataTable).FullName;

            importedTypes.Add(type, typeName);
            mainNamespace.Imports.Add(new
CodeNamespaceImport(typeof(DataSet).Namespace));
            compileUnit.ReferencedAssemblies.Add("System.Data.dll");
            return typeName;
        }
        else
        {
            // Typed DataSet / DataTable
            foreach (XmlSchema schema in schemas.GetSchemas(ns))
            {
                if ((schema != null) && (schema.Id != null))
                {
                    XmlSchemaElement ds = FindDataSetElement(schema);
// implement FindDataTableElement(schema)
                    if (ds != null)
                    {
                        return ImportSchemaType(ds.SchemaType, ds,
schemas, importer, compileUnit, mainNamespace, options, codeProvider);
                    }
                    // else return null
                }
            }
            return null;
        }
    }
}

if (ct.Particle is XmlSchemaSequence || ct.Particle is XmlSchemaAll) {
    XmlSchemaObjectCollection items =
((XmlSchemaGroupBase)ct.Particle).Items;
    if (items.Count == 2) {
        if (!(items[0] is XmlSchemaElement && items[1] is XmlSchemaAny))
return null;

        XmlSchemaElement schema = (XmlSchemaElement)items[0];
        if (!(schema.RefName.Name == "schema" && schema.RefName.Namespace

```

```

== XmlSchema.Namespace)) return null;
    string typeName = typeof(DataSet).FullName;
    importedTypes.Add(type, typeName);
    mainNamespace.Imports.Add(new
CodeNamespaceImport(typeof(DataSet).Namespace));
    compileUnit.ReferencedAssemblies.Add("System.Data.dll");
    return typeName;
}
else if (1 == items.Count)
{
    XmlSchemaAny any = items[0] as XmlSchemaAny;
    if ((null != any) &&
        (null != any.Namespace) &&
        (any.Namespace.IndexOfAny(new char[] { '#', ' ' }) < 0)) //
special syntax (##any, ##other, ...) or more than one Uri present
    {
        foreach (XmlSchema schema in
schemas.GetSchemas(any.Namespace))
        {
            if ((null != schema) &&
                (null != schema.Id))
            {
                XmlSchemaElement ds = FindDataSetElement(schema);
                if (ds != null)
                {
                    return ImportSchemaType(ds.SchemaType, ds,
schemas, importer, compileUnit, mainNamespace, options, codeProvider);
                }
                // else return null
            }
            // else return null
        }
    }
    // else return null
}
}
return null;
}

```

```

internal XmlSchemaElement FindDataSetElement(XmlSchema schema) {
    foreach (XmlSchemaObject item in schema.Items) {
        if (item is XmlSchemaElement && IsDataSet((XmlSchemaElement)item)) {

```

```

        return (XmlSchemaElement)item;
    }
}
return null;
}

```

```

internal string GenerateTypedDataSet(XmlSchemaElement element, XmlSchemas
schemas, CodeNamespace codeNamespace, StringCollection references, CodeDomProvider
codeProvider) {

```

```

    if (element == null)
        return null;

    if (importedTypes[element.SchemaType] != null)
        return (string)importedTypes[element.SchemaType];

```

```

    IList values = schemas.GetSchemas(element.QualifiedName.Namespace);
    if (values.Count != 1) {
        return null;
    }
    XmlSchema schema = values[0] as XmlSchema;
    if (schema == null)
        return null;

```

```

    DataSet ds = new DataSet();

    //
    using (MemoryStream stream = new MemoryStream()) {
        schema.Write(stream);
        stream.Position = 0;
        ds.ReadXmlSchema(stream);
    }

```

```

#pragma warning disable 618 // ignore obsolete warning about TypedDataSetGenerator

```

```

    CodeTypeDeclaration dsClass = new TypedDataSetGenerator().GenerateCode(ds,
codeNamespace, codeProvider.CreateGenerator());

```

```

#pragma warning restore 618

    string typeName = dsClass.Name;
    importedTypes.Add(element.SchemaType, typeName);
    references.Add("System.Data.dll");
    return typeName;
}

```

```

internal static bool IsDataSet(XmlSchemaElement e) {
    if (e.UnhandledAttributes != null) {

```

```
        foreach (XmlAttribute a in e.UnhandledAttributes) {
            if (a.LocalName == "IsDataSet" && a.NamespaceURI == Keywords.MSDNS) {
                // currently the msdata:IsDataSet uses its own format for the
boolean values
                if (a.Value == "True" || a.Value == "true" || a.Value == "1")
return true;
            }
        }
        return false;
    }
}
```

Archived from <https://github.com/microsoft/referencesource/blob/dae14279dd0672adead5de00ac8f117dcf74c184/System.Data/System/Data/DataSet.cs>. Rendered offline from the local Markdown copy.