# Binary Search Trees: AVL Tree Implementation

Daniel Kane

Department of Computer Science and Engineering University of California, San Diego

Data Structures
Data Structures and Algorithms

## Learning Objectives

- Implement AVL trees.
- Understand the cases required for rebalancing algorithms.

## Outline


1 AVL Trees

2 Insert


3 Delete

#### **AVL Trees**


Need ensure that children have nearly the same height.



Updates to the tree can destroy this property.




Updates to the tree can destroy this property.



Need to correct this.


#### **Errors**

Heights stay the same except on the insertion path.




Only need to worry about this path.

Which insertion would require the tree to be rebalanced in order to maintain the AVL property?



Which insertion would require the tree to be rebalanced in order to maintain the AVL property?



## Outline

1 AVL Trees

2 Insert

3 Delete

#### Insertion

We need a new insertion algorithm that involves rebalancing the tree to maintain the AVL property.

## Idea

## AVLInsert(k, R)


Insert(k, R) $N \leftarrow \text{Find}(k, R)$ 

Rebalance(N)


# Rebalancing

lf


 $| extbf{\textit{N}}. exttt{Left.Height} - extbf{\textit{N}}. exttt{Right.Height}| \leq 1$  fine.



Difficulty if heights differ by more.



Difficulty if heights differ by more.



Never more than 2.

## Code

#### Rebalance(N)

```
P \leftarrow N.Parent
if N.Left.Height > N.Right.Height +1:
  RebalanceRight(N)
if N.Right.Height > N.Left.Height +1:
  RebalanceLeft(N)
AdjustHeight(N)
if P \neq null:
  Rebalance(P)
```


# Adjust Height

## AdjustHeight(N)

```
	extcolor{N}.	ext{Height} \leftarrow 1 + 	ext{max} 	ext{(} $N.	ext{Left.Height}, $N.	ext{Right.Height} 	ext{)}
```

## Rebalancing

If left subtree too heavy, rotate right:




#### Bad Case

Doesn't work in this case.


Notice this special case. Rotate right creates unbalance when the left node of the node to be rotated right has a heavier right node.

In this case right node of A has weight n+1 as compared to its left node of weight n



## Fix

Must rotate left first.



#### Rebalance

## RebalanceRight(N)

```
M \leftarrow N.Left
if M.Right.Height > M.Left.Height:
RotateLeft(M)
RotateRight(N)
AdjustHeight on affected nodes
```

## Outline


1 AVL Trees

2 Insert

3 Delete

## Delete

Deletions can also change balance.



#### New Delete

## AVLDelete(N)

Delete(N)  $M \leftarrow \text{Left child of node replacing } N$ Rebalance(M)

## Conclusion

#### Summary

AVL trees can implement all of the basic operations in  $O(\log(n))$  time per operation.