

# Preventing Unauthorized Purchases with Receipts

Session 305

James Wilson

Software Engineering

# Using Receipts

# Using Receipts

Know exactly what the customer has paid for

# Using Receipts

Know exactly what the customer has paid for

Within your app, on the device and on your servers


# Using Receipts

Know exactly what the customer has paid for

Within your app, on the device and on your servers


Protect your revenue

# The Receipt




# The Receipt

Trusted record of App and In-App Purchases



# The Receipt

Trusted record of App and In-App Purchases  
Stored on device






# The Receipt

Trusted record of App and In-App Purchases

Stored on device

Issued by the App Store




# The Receipt

Trusted record of App and In-App Purchases

Stored on device

Issued by the App Store

Signed and verifiable



# The Receipt


Trusted record of App and In-App Purchases

Stored on device

Issued by the App Store

Signed and verifiable

For your app, on that device only









# Flexibility

# Flexibility

Apple provides you with

# Flexibility

Apple provides you with

- The receipt format specification

# Flexibility

Apple provides you with

- The receipt format specification
- The receipt itself



# Flexibility

Apple provides you with

- The receipt format specification
- The receipt itself
- Instructions for on-device receipt validation

# Flexibility

Apple provides you with

- The receipt format specification
- The receipt itself
- Instructions for on-device receipt validation
- Online service for server-to-server validation

# Flexibility

Apple provides you with

- The receipt format specification
- The receipt itself
- Instructions for on-device receipt validation
- Online service for server-to-server validation

You chose a security level appropriate for your products

# Flexibility

Apple provides you with

- The receipt format specification
- The receipt itself
- Instructions for on-device receipt validation
- Online service for server-to-server validation

You chose a security level appropriate for your products

You decide the complexity of the implementation

# Decisions

# Decisions

How to verify the signature?

# Decisions

How to verify the signature?

How to verify the device?

# Decisions

How to verify the signature?

How to verify the device?

How to interpret the data in the receipt?





Level of  
Complexity  
and Security

Value of Product




















# Working with Receipts

# The Basics





# The Basics

Stored in the App Bundle

- API to get the path



# The Basics

Stored in the App Bundle

- API to get the path

Single file

- Purchase data
- Signature to check authenticity



# Standards



# Standards

## Signing

- **PKCS#7** Cryptographic Container



# Standards

## Signing

- **PKCS#7** Cryptographic Container

## Data Encoding

- **ASN.1**



# Standards

## Signing

- **PKCS#7** Cryptographic Container

## Data Encoding

- **ASN.1**

## Options for verifying and reading




- OpenSSL, asn1c, etc.
- Create your own



Verify  
Signature

Confirm  
Device




Check  
Purchases



Verify  
Signature

Confirm  
Device

Check  
Purchases








Verify  
Signature

Confirm  
Device

Check  
Purchases




|

Authentic  
and Trusted

Verify  
Signature

Confirm  
Device




Check  
Purchases



Verify  
Signature

Confirm  
Device

Check  
Purchases






|

For This  
Device

Verify  
Signature

Confirm  
Device




Check  
Purchases



Verify  
Signature

Confirm  
Device

Check  
Purchases



|  
What the  
User Paid for

*Demo*




Getting a receipt

Validating on Device

Verify  
Signature

Confirm  
Device

Check  
Purchases








Verify  
Signature

Confirm  
Device




Check  
Purchases



Verify  
Signature

Confirm  
Device

Check  
Purchases



|

Authentic  
and Trusted

# Verify the Signature



# Verify the Signature

Confirms that the receipt



# Verify the Signature

Confirms that the receipt

- Has not been altered



# Verify the Signature

Confirms that the receipt

- Has not been altered
- Came from Apple



# Verify the Signature

Confirms that the receipt

- Has not been altered
- Came from Apple

PKCS#7 Cryptographic Container




# Verify the Signature

Confirms that the receipt

- Has not been altered
- Came from Apple

PKCS#7 Cryptographic Container

Options





# Verify the Signature

Confirms that the receipt

- Has not been altered
- Came from Apple

PKCS#7 Cryptographic Container

Options

- OpenSSL, other frameworks, etc.



# Verify the Signature

Confirms that the receipt

- Has not been altered
- Came from Apple

PKCS#7 Cryptographic Container

Options

- OpenSSL, other frameworks, etc.
- Custom implementation



# Getting Started

Receipt

Purchase Information

Certificates

Signature

# Getting Started

Locate the file



# Getting Started

Locate the file

```
// Locate the Receipt  
[[NSBundle mainBundle] appStoreReceiptURL];
```




# Getting Started

Locate the file

```
// Locate the Receipt  
[[NSBundle mainBundle] appStoreReceiptURL];
```

Read the contents



# Getting Started

Locate the file

```
// Locate the Receipt  
[[NSBundle mainBundle] appStoreReceiptURL];
```

Read the contents

```
// Read the receipt  
[[NSData alloc] initWithContentsOfURL:]
```



# OpenSSL Example

```
BI0 *b_receipt;  
BI0 *b_x509;
```

← Load the Receipt and Apple Root CA Certificate  
Binary data from receipt plus certificate



# OpenSSL Example

```
BI0 *b_receipt;  
BI0 *b_x509;
```

← Load the Receipt and Apple Root CA Certificate  
Binary data from receipt plus certificate

```
// Convert receipt data to PKCS #7 Representation  
PKCS7 *p7 = d2i_PKCS7_bio(b_receipt, NULL);
```

# OpenSSL Example

```
BI0 *b_receipt;  
BI0 *b_x509;
```

← Load the Receipt and Apple Root CA Certificate  
Binary data from receipt plus certificate

```
// Convert receipt data to PKCS #7 Representation  
PKCS7 *p7 = d2i_PKCS7_bio(b_receipt, NULL);  
  
// Create the certificate store  
X509_STORE *store = X509_STORE_new();  
X509 *appleRootCA = d2i_X509_bio(b_x509, NULL);  
X509_STORE_add_cert(store, appleRootCA);
```

# OpenSSL Example

```
BI0 *b_receipt;  
BI0 *b_x509;
```

← Load the Receipt and Apple Root CA Certificate  
Binary data from receipt plus certificate

```
// Convert receipt data to PKCS #7 Representation  
PKCS7 *p7 = d2i_PKCS7_bio(b_receipt, NULL);  
  
// Create the certificate store  
X509_STORE *store = X509_STORE_new();  
X509 *appleRootCA = d2i_X509_bio(b_x509, NULL);  
X509_STORE_add_cert(store, appleRootCA);  
  
// Verify the Signature  
BI0 *b_receiptPayload = BI0_new(BI0_s_mem());  
int result = PKCS7_verify(p7, NULL, store, NULL, b_receiptPayload, 0);  
if (result == 1)  
{  
    // Receipt Signature is VALID  
  
}
```

# OpenSSL Example

```
BI0 *b_receipt;  
BI0 *b_x509;
```

← Load the Receipt and Apple Root CA Certificate  
Binary data from receipt plus certificate

```
// Convert receipt data to PKCS #7 Representation  
PKCS7 *p7 = d2i_PKCS7_bio(b_receipt, NULL);  
  
// Create the certificate store  
X509_STORE *store = X509_STORE_new();  
X509 *appleRootCA = d2i_X509_bio(b_x509, NULL);  
X509_STORE_add_cert(store, appleRootCA);  
  
// Verify the Signature  
BI0 *b_receiptPayload = BI0_new(BI0_s_mem());  
int result = PKCS7_verify(p7, NULL, store, NULL, b_receiptPayload, 0);  
if (result == 1)  
{  
    // Receipt Signature is VALID  
    // b_receiptPayload contains the payload  
}
```

*Demo*

Using OpenSSL for signature verification



# Building OpenSSL

# Building OpenSSL

Build a **static library** (.a file), not a dynamic library

# Building OpenSSL

Build a **static library** (.a file), not a dynamic library

Building for multiple architectures

# Building OpenSSL

Build a **static library** (.a file), not a dynamic library

Building for multiple architectures

- Separate .a per architecture (e.g. arm, arm64, x86\_64, etc.)

# Building OpenSSL

Build a **static library** (.a file), not a dynamic library

Building for multiple architectures

- Separate .a per architecture (e.g. arm, arm64, x86\_64, etc.)
- Use 'lipo' to create a single .a with multiple arch slices



# Building OpenSSL

Build a **static library** (.a file), not a dynamic library

Building for multiple architectures

- Separate .a per architecture (e.g. arm, arm64, x86\_64, etc.)
- Use 'lipo' to create a single .a with multiple arch slices

Configuration script

# Building OpenSSL

Build a **static library** (.a file), not a dynamic library

Building for multiple architectures

- Separate .a per architecture (e.g. arm, arm64, x86\_64, etc.)
- Use 'lipo' to create a single .a with multiple arch slices

Configuration script

- Use darwin64-x86\_64-cc host type for OS X 64bit

# Building OpenSSL

Build a **static library** (.a file), not a dynamic library

Building for multiple architectures

- Separate .a per architecture (e.g. arm, arm64, x86\_64, etc.)
- Use 'lipo' to create a single .a with multiple arch slices

Configuration script

- Use darwin64-x86\_64-cc host type for OS X 64bit
- Use iphoneos-cross host type for iOS

# Building OpenSSL

Build a **static library** (.a file), not a dynamic library

Building for multiple architectures

- Separate .a per architecture (e.g. arm, arm64, x86\_64, etc.)
- Use 'lipo' to create a single .a with multiple arch slices

Configuration script

- Use darwin64-x86\_64-cc host type for OS X 64bit
- Use iphoneos-cross host type for iOS

Lots of examples available online...

# Verification

# Verification

Do not check the expiry date on the certificate



# Verification

Do not check the expiry date on the certificate

Do evaluate trust up to Root CA

# Examples and Samples

# Examples and Samples

Convenience comes at a price

# Examples and Samples

Convenience comes at a price

- Re-using code brings with it bugs and vulnerabilities

# Examples and Samples

Convenience comes at a price

- Re-using code brings with it bugs and vulnerabilities
- Single exploit affects many

# Examples and Samples

Convenience comes at a price

- Re-using code brings with it bugs and vulnerabilities
- Single exploit affects many

It's **your** revenue stream



# Examples and Samples

Convenience comes at a price

- Re-using code brings with it bugs and vulnerabilities
- Single exploit affects many

It's **your** revenue stream

- Make decisions that suit your product

# Examples and Samples

Convenience comes at a price

- Re-using code brings with it bugs and vulnerabilities
- Single exploit affects many




It's **your** revenue stream

- Make decisions that suit your product
- Know and own the risks

Verify  
Signature

Confirm  
Device

Check  
Purchases






|

Authentic  
and Trusted

Verify  
Signature

Confirm  
Device




Check  
Purchases



Verify  
Signature

Confirm  
Device


Check  
Purchases



|

For This  
Device


# Receipt Payload





# Receipt Payload


Series of attributes



# Receipt Payload

Series of attributes


- Type



# Receipt Payload

Series of attributes


- Type
- Value




# Receipt Payload

Series of attributes

- Type
- Value
- (Version)




# Verify Application



# Verify Application

Check the Bundle Identifier






# Verify Application

Check the Bundle Identifier

Check the Bundle Version




# Verify Application

Check the Bundle Identifier

Check the Bundle Version

Use hardcoded values




# Verify Application

Check the Bundle Identifier

Check the Bundle Version


Use hardcoded values

- Not Info.plist values




# Verify Device

ASN.1 format




# Verify Device

ASN.1 format



# Verify Device


ASN.1 format



# Verify Device

ASN.1 format

Attribute 5 is a SHA-1 hash of 3 key values






# Verify Device

## ASN.1 format

Attribute 5 is a SHA-1 hash of 3 key values

- Bundle ID




# Verify Device

## ASN.1 format

Attribute 5 is a SHA-1 hash of 3 key values

- Bundle ID
- Device Identifier




# Verify Device

## ASN.1 format

Attribute 5 is a SHA-1 hash of 3 key values

- Bundle ID
- Device Identifier
- Opaque Value




# Verify Device

## ASN.1 format

Attribute 5 is a SHA-1 hash of 3 key values

- Bundle ID
- Device Identifier
- Opaque Value

The App Store knows these at time of purchase



# Verify Device


## ASN.1 format

Attribute 5 is a SHA-1 hash of 3 key values

- Bundle ID
- Device Identifier
- Opaque Value

The App Store knows these at time of purchase

Your app knows them at time of verification



# Verify Device

## ASN.1 format


Attribute 5 is a SHA-1 hash of 3 key values

- Bundle ID
- Device Identifier
- Opaque Value

The App Store knows these at time of purchase


Your app knows them at time of verification

Unique to your app on this device



# Data Encoding

## ASN.1 Format






# Data Encoding

## ASN.1 Format

Receipt payload format definition



# Data Encoding

## ASN.1 Format


Receipt payload format definition

```
ReceiptModule DEFINITIONS ::=
BEGIN
```

```
ReceiptAttribute ::= SEQUENCE {
    type      INTEGER,
    version   INTEGER,
    value     OCTET STRING
}
```

```
Payload ::= SET OF ReceiptAttribute
```

```
END
```



# Data Encoding

## ASN.1 Format


Receipt payload format definition

```
ReceiptModule DEFINITIONS ::=
BEGIN
```

```
ReceiptAttribute ::= SEQUENCE {
    type      INTEGER,
    version   INTEGER,
    value     OCTET STRING
}
```

```
Payload ::= SET OF ReceiptAttribute
```

```
END
```



# Data Encoding

## ASN.1 Format


Receipt payload format definition

```
ReceiptModule DEFINITIONS ::=
BEGIN
```

```
ReceiptAttribute ::= SEQUENCE {
    type      INTEGER,
    version   INTEGER,
    value     OCTET STRING
}
```

```
Payload ::= SET OF ReceiptAttribute
```

```
END
```



# Working with ASN.1

# Working with ASN.1

Open Standard

# Working with ASN.1

Open Standard

Very widely used



# Working with ASN.1

Open Standard

Very widely used

Options

# Working with ASN.1

Open Standard

Very widely used

Options

- OpenSSL, ASN1C, etc.

# Working with ASN.1

Open Standard

Very widely used

Options

- OpenSSL, ASN1C, etc.
- Create your own parser

# OpenSSL Example

# OpenSSL Example

```
// p7 is the same PKCS7 Structure
```

# OpenSSL Example

```
// p7 is the same PKCS7 Structure  
ASN1_OCTET_STRING *octets = p7->d.sign->contents->d.data;
```

# OpenSSL Example

```
// p7 is the same PKCS7 Structure  
ASN1_OCTET_STRING *octets = p7->d.sign->contents->d.data;  
// Call ASN1_get_object to parse objects
```



# OpenSSL Example

```
// p7 is the same PKCS7 Structure  
ASN1_OCTET_STRING *octets = p7->d.sign->contents->d.data;  
// Call ASN1_get_object to parse objects  
ASN1_get_object(...);
```

# OpenSSL Example

```
// p7 is the same PKCS7 Structure
ASN1_OCTET_STRING *octets = p7->d.sign->contents->d.data;
// Call ASN1_get_object to parse objects
ASN1_get_object(...);
```

```
ReceiptModule
-> Payload
    -> ReceiptAttribute
        -> Type
        -> Version
        -> Value
    -> ReceiptAttribute
        -> Type
        -> Version
        -> Value
```

# OpenSSL Example

```
// p7 is the same PKCS7 Structure
ASN1_OCTET_STRING *octets = p7->d.sign->contents->d.data;
// Call ASN1_get_object to parse objects
ASN1_get_object(...);
```

```
ReceiptModule
-> Payload
    -> ReceiptAttribute
        -> Type
        -> Version
        -> Value
    -> ReceiptAttribute
        -> Type
        -> Version
        -> Value
```

```
ReceiptModule DEFINITIONS ::=
BEGIN

ReceiptAttribute ::= SEQUENCE {
    type      INTEGER,
    version   INTEGER,
    value     OCTET STRING
}

Payload ::= SET OF ReceiptAttribute

END
```

# OpenSSL Example

# OpenSSL Example

```
// Iterate over child objects (Attributes)
```

# OpenSSL Example

```
// Iterate over child objects (Attributes)
while (p < end)
{
```

# OpenSSL Example

```
// Iterate over child objects (Attributes)
while (p < end)
{
    ASN1_get_object(&p, &length, &type, &xclass, end - p);    // Attribute
    const unsigned char *seq_end = p + length;
```

# OpenSSL Example

```
// Iterate over child objects (Attributes)
while (p < end)
{
    ASN1_get_object(&p, &length, &type, &xclass, end - p);    // Attribute
    const unsigned char *seq_end = p + length;

    ASN1_get_object(&p, &length, &type, &xclass, seq_end - p); // Type
    int attr_type = p[0];
    p += length; // Move the pointer to the next object
```



# OpenSSL Example

```
// Iterate over child objects (Attributes)
while (p < end)
{
    ASN1_get_object(&p, &length, &type, &xclass, end - p);    // Attribute
    const unsigned char *seq_end = p + length;

    ASN1_get_object(&p, &length, &type, &xclass, seq_end - p); // Type
    int attr_type = p[0];
    p += length; // Move the pointer to the next object

    ASN1_get_object(&p, &length, &type, &xclass, seq_end - p);
```

# OpenSSL Example

```
// Iterate over child objects (Attributes)
while (p < end)
{
    ASN1_get_object(&p, &length, &type, &xclass, end - p);    // Attribute
    const unsigned char *seq_end = p + length;

    ASN1_get_object(&p, &length, &type, &xclass, seq_end - p); // Type
    int attr_type = p[0];
    p += length; // Move the pointer to the next object

    ASN1_get_object(&p, &length, &type, &xclass, seq_end - p);
    switch (attr_type) {
```

# OpenSSL Example

```
// Iterate over child objects (Attributes)
while (p < end)
{
    ASN1_get_object(&p, &length, &type, &xclass, end - p);    // Attribute
    const unsigned char *seq_end = p + length;

    ASN1_get_object(&p, &length, &type, &xclass, seq_end - p); // Type
    int attr_type = p[0];
    p += length; // Move the pointer to the next object

    ASN1_get_object(&p, &length, &type, &xclass, seq_end - p);
    switch (attr_type) {
        case 2: {
```

# OpenSSL Example

```
// Iterate over child objects (Attributes)
while (p < end)
{
    ASN1_get_object(&p, &length, &type, &xclass, end - p);    // Attribute
    const unsigned char *seq_end = p + length;

    ASN1_get_object(&p, &length, &type, &xclass, seq_end - p); // Type
    int attr_type = p[0];
    p += length; // Move the pointer to the next object

    ASN1_get_object(&p, &length, &type, &xclass, seq_end - p);
    switch (attr_type) {
        case 2: {
            // BundleID (Attribute 2)
```

# OpenSSL Example

```
// Iterate over child objects (Attributes)
while (p < end)
{
    ASN1_get_object(&p, &length, &type, &xclass, end - p);    // Attribute
    const unsigned char *seq_end = p + length;

    ASN1_get_object(&p, &length, &type, &xclass, seq_end - p); // Type
    int attr_type = p[0];
    p += length; // Move the pointer to the next object

    ASN1_get_object(&p, &length, &type, &xclass, seq_end - p);
    switch (attr_type) {
        case 2: {
            // BundleID (Attribute 2)
            // Use ASN_get_object again to get the string
        }
    }
}
```




*Demo*

Using OpenSSL for ASN.1 parsing

Verify  
Signature

Confirm  
Device

Check  
Purchases






|

For This  
Device

Verify  
Signature

Confirm  
Device

Check  
Purchases








Verify  
Signature


Confirm  
Device

Check  
Purchases




|  
What the  
User Paid for


# In-App Purchase Attributes




# In-App Purchase Attributes




# In-App Purchase Attributes




# In-App Purchase Attributes





# In-App Purchase Attributes



# In-App Purchase Attributes



# In-App Purchase Attributes




```
InAppAttribute ::= SEQUENCE {  
    type          INTEGER,  
    version       INTEGER,  
    value         OCTET STRING  
}
```

```
InAppReceipt ::= SET OF InAppAttribute
```




# Transition to Freemium



# Transition to Freemium


Original application version in the receipt



# Transition to Freemium

Original application version in the receipt

Know whether to treat the app as the paid version, or the freemium version



# Transaction Lifecycle

# Transaction Lifecycle

Consumable and non-renewing subscriptions

# Transaction Lifecycle

Consumable and non-renewing subscriptions

- Will only appear once

# Transaction Lifecycle

## Consumable and non-renewing subscriptions

- Will only appear once
- In the receipt issued at time of purchase

# Transaction Lifecycle

## Consumable and non-renewing subscriptions

- Will only appear once
- In the receipt issued at time of purchase
- Will not be present in subsequent receipts issued



# Transaction Lifecycle

## Consumable and non-renewing subscriptions

- Will only appear once
- In the receipt issued at time of purchase
- Will not be present in subsequent receipts issued

## Non-consumable and auto-renewable subscriptions

# Transaction Lifecycle

## Consumable and non-renewing subscriptions

- Will only appear once
- In the receipt issued at time of purchase
- Will not be present in subsequent receipts issued

## Non-consumable and auto-renewable subscriptions

- Always in the receipt

# Transaction Lifecycle

## Consumable and non-renewing subscriptions

- Will only appear once
- In the receipt issued at time of purchase
- Will not be present in subsequent receipts issued

## Non-consumable and auto-renewable subscriptions

- Always in the receipt
- Can be restored via StoreKit API

# Handling Invalid Receipts

# Receipt Refresh on iOS

# Receipt Refresh on iOS

If the receipt doesn't exist or is invalid

# Receipt Refresh on iOS

If the receipt doesn't exist or is invalid

Refresh the receipt using StoreKit

# Receipt Refresh on iOS

If the receipt doesn't exist or is invalid

Refresh the receipt using StoreKit

```
// Refresh the Receipt
SKReceiptRefreshRequest *request = [SKReceiptRefreshRequest alloc] init];
[request setDelegate:self];
[request start];
```



# Receipt Refresh on iOS

If the receipt doesn't exist or is invalid

Refresh the receipt using StoreKit

```
// Refresh the Receipt
SKReceiptRefreshRequest *request = [SKReceiptRefreshRequest alloc] init];
[request setDelegate:self];
[request start];
```

Receipt refresh will require network

# Receipt Refresh on iOS

If the receipt doesn't exist or is invalid

Refresh the receipt using StoreKit

```
// Refresh the Receipt
SKReceiptRefreshRequest *request = [SKReceiptRefreshRequest alloc] init];
[request setDelegate:self];
[request start];
```

Receipt refresh will require network

Store sign-in will be required

# Receipt Refresh on iOS

If the receipt doesn't exist or is invalid

Refresh the receipt using StoreKit

```
// Refresh the Receipt
SKReceiptRefreshRequest *request = [SKReceiptRefreshRequest alloc] init];
[request setDelegate:self];
[request start];
```

Receipt refresh will require network

Store sign-in will be required

Avoid continuous loop of validate-and-refresh

# Receipt Refresh on OS X

# Receipt Refresh on OS X

If the receipt is invalid

# Receipt Refresh on OS X

If the receipt is invalid

Exit with code 173 to refresh receipt

# Receipt Refresh on OS X

If the receipt is invalid

Exit with code 173 to refresh receipt

```
// Receipt is invalid  
exit(173);
```

# Receipt Refresh on OS X

If the receipt is invalid

Exit with code 173 to refresh receipt

```
// Receipt is invalid  
exit(173);
```

Receipt refresh will require network



# Receipt Refresh on OS X

If the receipt is invalid

Exit with code 173 to refresh receipt

```
// Receipt is invalid  
exit(173);
```

Receipt refresh will require network

Store sign-in will be required

# Invalid Receipt User Experience

# Invalid Receipt User Experience

Invalid or missing receipts will happen

# Invalid Receipt User Experience

Invalid or missing receipts will happen

- Receipt refresh may not be possible

# Invalid Receipt User Experience

Invalid or missing receipts will happen

- Receipt refresh may not be possible
- You decide how to handle this

# Invalid Receipt User Experience

Invalid or missing receipts will happen

- Receipt refresh may not be possible
- You decide how to handle this

Match the user experience to the product value

# Invalid Receipt User Experience

Invalid or missing receipts will happen

- Receipt refresh may not be possible
- You decide how to handle this

Match the user experience to the product value

- Allow full access to content and features

# Invalid Receipt User Experience

Invalid or missing receipts will happen

- Receipt refresh may not be possible
- You decide how to handle this

Match the user experience to the product value

- Allow full access to content and features
- Limit access



# Invalid Receipt User Experience

Invalid or missing receipts will happen

- Receipt refresh may not be possible
- You decide how to handle this

Match the user experience to the product value

- Allow full access to content and features
- Limit access
- Block functionality

# Invalid Receipt User Experience

Invalid or missing receipts will happen

- Receipt refresh may not be possible
- You decide how to handle this

Match the user experience to the product value

- Allow full access to content and features
- Limit access
- Block functionality
- Quit app (OS X only)











# Online Validation

Server-to-Server



Your Application

Your Servers

Your Content

Apple  
Validation  
Server



Your Application

Request and Receipt



Your Servers

Your Content

Apple  
Validation  
Server



Request and Receipt

Your Servers

Your Content

Receipt

Apple  
Validation  
Server





Request and Receipt

Your Servers

Your Content

Receipt

Valid Receipt Info

Apple  
Validation  
Server



Request and Receipt  
←  
Response and Content

Your Servers

Your Content

Receipt

←  
Valid Receipt Info

Apple  
Validation  
Server

# Server-to-Server Validation

# Server-to-Server Validation

Allows your servers to validate the receipt before issuing content

# Server-to-Server Validation

Allows your servers to validate the receipt before issuing content

Your app sends the receipt to your servers

# Server-to-Server Validation

Allows your servers to validate the receipt before issuing content

Your app sends the receipt to your servers

- Your server sends the receipt to Apple's server

# Server-to-Server Validation

Allows your servers to validate the receipt before issuing content

Your app sends the receipt to your servers

- Your server sends the receipt to Apple's server
- **Never send the receipt directly from your app to Apple's server**

# Server-to-Server Validation

Allows your servers to validate the receipt before issuing content

Your app sends the receipt to your servers

- Your server sends the receipt to Apple's server
- **Never send the receipt directly from your app to Apple's server**

Response is in JSON



# Test Your Implementation

Using the App Store Test Environment

# Test Thoroughly

# Test Thoroughly

No receipt

# Test Thoroughly

No receipt

Invalid receipt

# Test Thoroughly

No receipt

Invalid receipt

Valid on refresh

# Test Thoroughly

No receipt

Invalid receipt

Valid on refresh

Invalid on refresh

# Test Thoroughly

No receipt

Invalid receipt

Valid on refresh

Invalid on refresh

Volume Purchase Program receipts

# Test Thoroughly

No receipt

Invalid receipt

Valid on refresh

Invalid on refresh

Volume Purchase Program receipts

These are not edge cases!



# Testing on iOS

# Testing on iOS

Run the app from Xcode

# Testing on iOS

Run the app from Xcode

Perform an In-App Purchase to get a receipt

# Testing on iOS

Run the app from Xcode

Perform an In-App Purchase to get a receipt

Must be signed with **Development Certificate**

# Testing on OS X

# Testing on OS X

Build the app in Xcode

# Testing on OS X

Build the app in Xcode

Run the app from Finder

# Testing on OS X

Build the app in Xcode

Run the app from Finder

Exit with code 173 to get a receipt



# Testing on OS X

Build the app in Xcode

Run the app from Finder

Exit with code 173 to get a receipt

Must be signed with **Development Certificate**



Must be signed with Development Certificate

# App Submission

# App Review and Receipts

	Certificate	Receipt Type
Development	Development	Test
For Sale	Production	Production

# App Review and Receipts

	Certificate	Receipt Type
Development	Development	Test
App Review	Production	
For Sale	Production	Production

# App Review and Receipts

	Certificate	Receipt Type
Development	Development	Test
App Review	Production	Test
For Sale	Production	Production

# App Review and Receipts

	Certificate	Receipt Type
Development	Development	Test
App Review	Production	Test
For Sale	Production	Production

Do not invalidate Test Environment receipts—Your app will be rejected



# More Information

Evangelism

[evangelism@apple.com](mailto:evangelism@apple.com)

Documentation

Receipt Validation Programming Guide

<https://developer.apple.com>

Apple Developer Forums

<http://devforums.apple.com>

# Related Sessions

- 
- |  |          |                   |
|--|----------|-------------------|
| ● Optimizing In-App Purchases                  | Nob Hill | Wednesday 3:15PM  |
| ● Designing a Great In-App Purchase Experience | Nob Hill | Wednesday 11:30AM |
-

# Labs

● StoreKit and Receipts Lab	Services Lab	Friday 10:15AM
● Services Open Lab	Services Lab	Friday 2:00PM

