

NPQP - SPECIAL CHARACTERISTICS AND KEY FEATURES DIAGRAM

Project: 3888 (L21C)	Safety Regulation: Nissan Impt A Impt B Impt C Impt D	Doc Ref. No. / Ver.: SCKFD-3888-48430 75FXX-003
Supplier Name: NIHON PLAST MEXICANA S.A DE C.V.	Supplier Code: 1047	Doc. Rev. Date: 27/03/2025
Supplier Plant Name: NIHON PLAST MEXICANA S.A DE C.V.	Author: LUZ M. / OSCAR D.	Doc. Origin Date: 16/04/2024
Part Name: BODY ASSY AIR BAG STRG WHEEL	Remark: PT1	E-mail: g.diaz@nissamex.com.mx
Part No. & Issue Level: 48430 75F0A / 48430 75F1A / 48430 75F2A / 48430 75F3A / 48430 75F4A / 48430 75F5A / 48430 75F6A / 48430 75F7A / 48430 75F3B / 48430 75F4B / 48430 75F5B / 48430 75F7B		
Design Note No. / DEVO: Y5R637 (W-23125)		

特別特性 / 主要特性 Special Characteristic	No.	製品特性 Product Characteristic	仕様/公差 Specification / Tolerance	備考 Remark
	1	General Appearance (Pur)	No damage, no stains, no excess material, no lack of material, no release agent excess, no burrs, no bubbles, no smudged paint, no out-of-spec pin	Visual / Start and restart
		General Appearance (Leather Synthetic)	No damage, no stains, no excess material, no lack of material, no release agent excess, no burrs, no bubbles, no smudged paint, no out-of-spec pin	Visual / Start and restart
	2	Body Assy Air Bag Color	PG05 According to master piece (Pur) PG05 According to master piece (Leather Synthetic)	Visual / Start and restart
	3	Thread color Leather Synthetic	Red "Z336 (283)" Ligh Grey (ZK62)	Visual / Start and restart
	4	Presence of Components	Presence of Switch, Presence of retaining wire, Correctly assembled harness, Presence of back cover y heater ECU according to version	Visual / Start and restart
	5	Harness Routing	According to drawing or annex	Visual / Start and restart
	6	Position and presence of ID Label (QR code)	0F 75F0A 1F 75F1A 2F 75F2A 3F 75F3A 4F 75F4A 5F 75F5A 6F 75F6A 7F 75F7A 8F 75F3B 4B 75F4B 9F 75F5B 7B 75F7B	Visual / Start and restart
(F&F)	7	Outer diameter (vertical)	361.8±3mm	Digital Caliper "Vernier" / Start and restart
(F&F)	8	Outer diameter (horizontal)	372.6±3mm	
(F&F)	9 (a-f)	Gap between Body Strg Wheel and Nodulo	3.0± 0.6 mm	Conical scale / Start and restart
(F&F)	10 (a-l)	Gap between Finisher Bezel y Switch	0.9± 0.23mm	Caliper of Linares / Start and restart
(F&F)	11 (a-c)	Gap between Mid finisher y Back Cover	0.3 ± 0.7/-0.3mm	Caliper of Linares / Start and restart
(F&F)	12 (a-c)	Gap between Mid Fin y Fin Bezel	0.5 ± 0.5mm	Caliper of Linares / Start and restart
(F&F)	13 (a-c)	Gap between Fin Bezel y Back Cover	0.5 ± 0.5mm	Caliper of Linares / Start and restart
(F&F)	14 (a-b)	Gap between PIN Bezel y Body Strg Wheel	0 ± 0.3 mm	Caliper of Linares / Start and restart
(F&F)	15 (a-b)	Gap back cover y body strg wheel	0 ± 0.3 mm	Caliper of Linares / Start and restart
(F&F)	16 (a - d)	Mid Fin Screw Torque	0.4Nm ± 1.37Nm	Torqueometer
(F&F)		Fin Bezel Screw Torque	0.4Nm ± 1.37Nm	Torqueometer
(F&F)	17 (GND A / B)	GND A Screw Torque	1.4 ± 2.8 Nm	Torqueometer
		GND B Screw Torque	1.4 ± 2.8 Nm	Torqueometer
	18	Boss resistance	29.4kN (Min)	Caliper of Linares / Start and restart