```java
import components.simplereader.SimpleReader;

/**
 * Program to convert an XML file stored with RSS feeds (version 2.0) feed from
 * a given URL into an HTML index file, then process all RSS feeds into their
 * own HTML files that are accessible from the index file.
 *
 * @author Isaac Frank
 *
 */
public final class RSSAggregator {

    /**
     * Private constructor so this utility class cannot be instantiated.
     */
    private RSSAggregator() {
    }

    /**
     * Outputs the "opening" tags in the generated HTML file. These are the
     * expected elements generated by this method:
     *
     * <html> <head> <title>the channel tag title as the page title</title>
     * </head> <body>
     * <h1>the page title inside a link to the <channel> link</h1>
     * <p>
     * the channel description
     * </p>
     * <table border="1">
     * <tr>
     * <th>Date</th>
     * <th>Source</th>
     * <th>News</th>
     * </tr>
     *
     * @param channel
     *            the channel element XMLTree
     * @param out
     *            the output stream
```

```
45      * @updates out.content
46      * @requires [the root of channel is a <channel> tag] and
    out.is_open
47      * @ensures out.content = #out.content * [the HTML "opening"
    tags]
48      */
49     private static void outputHeader(XMLTree channel, SimpleWriter
    out) {
50         assert channel != null : "Violation of: channel is not
    null";
51         assert out != null : "Violation of: out is not null";
52         assert channel.isTag() &&
    channel.label().equals("channel") : ""
53                 + "Violation of: the label root of channel is a
    <channel> tag";
54         assert out.isOpen() : "Violation of: out.is_open";
55
56         // Getting indexes of title, link, and description
57         int titleChildIndex = getChildElement(channel, "title");
58         int linkChildIndex = getChildElement(channel, "link");
59         int descriptionChildIndex = getChildElement(channel,
    "description");
60
61         // Html opening tags and printing title
62         out.print("<html> <head> <title>");
63         String title = "Empty Title";
64         if (channel.child(titleChildIndex).numberOfChildren() > 0)
    {
65             title =
    channel.child(titleChildIndex).child(0).label();
66         }
67         out.print(title);
68
69         // Html closing tags
70         out.println("</title> </head> <body>");
71
72         // Html header and page title w/ link
73         out.print("<h1>");
74         out.print(
75                 "<a href = \"" +
    channel.child(linkChildIndex).child(0).label()
76                         + "\">" + title + "</a>");
77         out.println("</h1>");
78
```

```
 79         // Html paragraph w/ channel description
 80         out.println("<p>");
 81         String description = "No description";
 82         if
    (channel.child(descriptionChildIndex).numberOfChildren() > 0) {
 83             description =
    channel.child(descriptionChildIndex).child(0).label();
 84         }
 85         out.println(description);
 86         out.println("</p>");
 87
 88         // Table Headers
 89         out.println("<table border = \"" + 1 + "\">");
 90         out.println("<tr>");
 91         out.println("<th>" + "Date" + "</th>");
 92         out.println("<th>" + "Source" + "</th>");
 93         out.println("<th>" + "News" + "</th>");
 94         out.println("</tr>");
 95     }
 96
 97     /**
 98      * Outputs the "closing" tags in the generated HTML file.
    These are the
 99      * expected elements generated by this method:
100      *
101      * </table>
102      * </body> </html>
103      *
104      * @param out
105      *            the output stream
106      * @updates out.contents
107      * @requires out.is_open
108      * @ensures out.content = #out.content * [the HTML "closing"
    tags]
109      */
110     private static void outputFooter(SimpleWriter out) {
111         assert out != null : "Violation of: out is not null";
112         assert out.isOpen() : "Violation of: out.is_open";
113
114         out.println("</table>");
115         out.println("</body> </html>");
116     }
117
118     /**
```

```
119      * Finds the first occurrence of the given tag among the
    children of the
120      * given {@code XMLTree} and return its index; returns -1 if
    not found.
121      *
122      * @param xml
123      *            the {@code XMLTree} to search
124      * @param tag
125      *            the tag to look for
126      * @return the index of the first child of type tag of the
    {@code XMLTree}
127      *         or -1 if not found
128      * @requires [the label of the root of xml is a tag]
129      * @ensures <pre>
130      * getChildElement =
131      *  [the index of the first child of type tag of the {@code
    XMLTree} or
132      *   -1 if not found]
133      * </pre>
134      */
135     private static int getChildElement(XMLTree xml, String tag) {
136         assert xml != null : "Violation of: xml is not null";
137         assert tag != null : "Violation of: tag is not null";
138         assert xml.isTag() : "Violation of: the label root of xml
    is a tag";
139
140         int index = -1;
141
142         // Iterates through children until a tag is found or all
    children are searched
143         int i = 0;
144         while (i < xml.numberOfChildren() && index < 0) {
145             if (xml.child(i).isTag() &&
    xml.child(i).label().equals(tag)) {
146                 index = i;
147             }
148             i++;
149         }
150
151         return index;
152     }
153
154     /**
155      * Processes one news item and outputs one table row. The row
```

```
    contains three
156      * elements: the publication date, the source, and the title
    (or
157      * description) of the item.
158      *
159      * @param item
160      *            the news item
161      * @param out
162      *            the output stream
163      * @updates out.content
164      * @requires [the label of the root of item is an <item> tag]
    and
165      *           out.is_open
166      * @ensures <pre>
167      * out.content = #out.content *
168      *   [an HTML table row with publication date, source, and
    title of news item]
169      * </pre>
170      */
171     private static void processItem(XMLTree item, SimpleWriter
    out) {
172         assert item != null : "Violation of: item is not null";
173         assert out != null : "Violation of: out is not null";
174         assert item.isTag() && item.label().equals("item") : ""
175                 + "Violation of: the label root of item is an
    <item> tag";
176         assert out.isOpen() : "Violation of: out.is_open";
177
178         // Finding indexes
179         int titleChildIndex = getChildElement(item, "title");
180         int linkChildIndex = getChildElement(item, "link");
181         int descriptionChildIndex = getChildElement(item,
    "description");
182         int pubDateChildIndex = getChildElement(item, "pubDate");
183         int sourceChildIndex = getChildElement(item, "source");
184
185         out.println("<tr>");
186
187         // Printing pubDate table cell
188         String pubDate = "No date available";
189         if (pubDateChildIndex != -1) {
190             pubDate =
    item.child(pubDateChildIndex).child(0).label();
191         }
```

```
192         out.println("<td>" + pubDate + "</td>");
193 
194         // Printing source table cell
195         String source = "No source available";
196         if (sourceChildIndex != -1) {
197             XMLTree src = item.child(sourceChildIndex);
198             if (src.numberOfChildren() > 0) {
199                 String srcAttributeVal =
    src.attributeValue("url");
200                 source = "<a href = \"" + srcAttributeVal;
201                 source += "\">" + src.child(0).label() + "</a>";
202             }
203         }
204         out.println("<td>" + source + "</td>");
205 
206         // Printing title table cell, checking if description and
    link are needed
207         String titleOrDsc = "No title available";
208         String link = "";
209         if (titleChildIndex != -1
210                 && item.child(titleChildIndex).numberOfChildren()
    > 0) {
211             titleOrDsc =
    item.child(titleChildIndex).child(0).label();
212         } else if (descriptionChildIndex != -1
213                 &&
    item.child(descriptionChildIndex).numberOfChildren() > 0) {
214             titleOrDsc =
    item.child(descriptionChildIndex).child(0).label();
215         }
216         if (linkChildIndex != -1) {
217             link = item.child(linkChildIndex).child(0).label();
218         }
219 
220         out.print("<td><a href = \"" + link + "\">" + titleOrDsc +
    "</a></td>");
221 
222         // Ending the row
223         out.println("</tr>");
224     }
225 
226     /**
227      * Processes one XML RSS (version 2.0) feed from a given URL
    converting it
```

```
228      * into the corresponding HTML output file.
229      *
230      * @param url
231      *            the URL of the RSS feed
232      * @param file
233      *            the name of the HTML output file
234      * @param out
235      *            the output stream to report progress or errors
236      * @updates out.content
237      * @requires out.is_open
238      * @ensures <pre>
239      * [reads RSS feed from url, saves HTML document with table of
     news items
240      *   to file, appends to out.content any needed messages]
241      * </pre>
242      */
243     private static void processFeed(String url, String file,
     SimpleWriter out) {
244         SimpleWriter outFile = new SimpleWriter1L(file);
245 
246         // Checking if xml is RSS 2.0
247         XMLTree xml = new XMLTree1(url);
248         if (xml.isTag()) {
249             if (xml.hasAttribute("version")) {
250                 if (xml.attributeValue("version").equals("2.0")) {
251                     XMLTree channel = xml.child(0);
252                     outputHeader(channel, outFile);
253 
254                     // Iterating through all "item" children of
     channel
255                     int i = 0;
256                     while (i < channel.numberOfChildren()) {
257                         if
     (channel.child(i).label().equals("item")) {
258                             processItem(channel.child(i),
     outFile);
259                         }
260                         i++;
261                     }
262 
263                     outputFooter(outFile);
264                 }
265             }
266         } else {
```

```
267             out.println("This is not an RSS 2.0 file");
268         }
269         outFile.close();
270     }
271 
272     /**
273      * Main method.
274      *
275      * @param args
276      *             the command line arguments; unused here
277      *
278      *             Processes XML document with RSS feeds stored
    inside and
279      *             outputs them to an index HTML file
280      */
281     public static void main(String[] args) {
282         SimpleReader in = new SimpleReader1L();
283         SimpleWriter out = new SimpleWriter1L();
284         SimpleWriter outFile = new SimpleWriter1L("index.html");
285 
286         // User input
287         out.print("Enter a URL for an XML Document of RSS feeds:
    ");
288         String url = in.nextLine();
289 
290         XMLTree feeds = new XMLTree1(url);
291 
292         // Outputting HTML headers and starting an unordered list
293         outFile.print("<html> <head> <title>");
294         outFile.print(feeds.attributeValue("title"));
295         outFile.println("</title> </head>");
296         outFile.println("<h1>" + feeds.attributeValue("title") +
    "</h1>");
297         outFile.println("<ul>");
298 
299         // Iterating through all RSS feeds stored in XMLTree feeds
300         int i = 0;
301         int numChildren = feeds.numberOfChildren();
302         while (i < numChildren) {
303             // Creating a new list element with a link to each
    processed RSS feed
304             outFile.print("<li>");
305             XMLTree feed = feeds.child(i);
306             outFile.print("<a href = \"" +
```

```
    feed.attributeValue("file"));
307             outFile.print("\">" + feed.attributeValue("name") +
    "</a>");
308             processFeed(feed.attributeValue("url"),
    feed.attributeValue("file"),
309                         out);
310             outFile.println("</li>");
311             i++;
312         }
313
314         // Outputting HTML footers and closing unordered list
315         outFile.println("</ul>");
316         outFile.println("</body>");
317         outFile.println("</html>");
318
319         // Closing output streams
320         in.close();
321         out.close();
322         outFile.close();
323
324     }
325 }
326
```