

# UML Class Diagrams part 1



**Idaho State  
University**

Computer  
Science

Isaac Griffith

CS 3321  
Department of Computer Science  
Idaho State University

**ROAR**




# Outline

- UML Class Diagrams
- UML Object Diagrams



# Object


- Individuals of a system
- Alternative notations:





# Object Diagrams

- Objects of a system and their relationships (links)
- Snapshot of objects at a specific moment in time




*Link*




# From Object to Class

- Individuals of a system often have identical characteristics and behavior
- A class is a construction plan for a set of similar objects of a system
- Objects are instances of Classes
- Attributes; structural characteristics of a class
  - Different value for each instance (= object)
- Operations: behavior of a class
  - Identical for all objects of a class (not depicted in object diagram)

*Class*



*Object of that class*





# Class

*Class name*

**Course**

*Attributes*


name: String  
semester: SemesterType  
hours: float

*Operations*

getCredits(): int  
getLecturer(): Lecturer  
getGPA(): float




# Attribute Syntax





# Attribute Syntax - Visibility




- Who is permitted to access the attribute
  - + ... public: everybody
  - - ... private: only the object itself
  - # ... protected: class itself and subclasses
  - ~ ... package: classes that are in the same package

Person
<ul style="list-style-type: none"><li>+ firstName: String</li><li>+ lastName: String</li><li>- dob: Date</li><li># address: String[1..*] {unique, ordered}</li><li>- ssNo: String {readOnly}</li><li>- /age: int</li><li>- password: String = "pw123"</li><li>- <u>personsNumber: int</u></li></ul>





# Attribute Syntax - Derived Attributes




- Attribute value is derived from other attributes
  - **age**: calculated from the date of birth

Person
firstName: String lastName: String dob: Date address: String[1..*] {unique, ordered} ssNo: String {readOnly} <b>/age: int</b> password: String = "pw123" <u>personsNumber: int</u>



# Attribute Syntax - Name



- Name of the attribute

Person
<p><b>firstName:</b> String <b>lastName:</b> String <b>dob:</b> Date <b>address:</b> String[1..*] {unique, ordered} <b>ssNo:</b> String {readOnly} <b>/age:</b> int <b>password:</b> String = "pw123" <b>personsNumber:</b> <u>int</u></p>



# Attribute Syntax - Type



- Type

- User-defined classes
- Data type
  - Pre-defined: Boolean, Integer, UnlimitedNatural, String
  - User-defined: «primitive»
  - Composite data type: «datatype»
  - Enumerations: «enumeration»

Person
firstName: String lastName: String dob: Date address: String[1..*] {unique, ordered} ssNo: String {readOnly} /age: int password: String = "pw123" <u>personsNumber: int</u>

«primitive» Float
round(): void

«datatype» Date
day month year

«enumeration» AcademicDegree
bachelor master phd




# Attribute Syntax - Multiplicity




- Number of values an attribute may contain
- Default value: 1
- Notation: **[min..max]**
  - no upper limit: [\*] or [0..\*]

Person
firstName: String lastName: String dob: Date address: String[1..*] {unique, ordered} ssNo: String {readOnly} /age: int password: String = "pw123" <u>personsNumber: int</u>





# Attribute Syntax - Default Value




- Default value
  - Used if the attribute value is not set explicitly by the user

Person
firstName: String lastName: String dob: Date address: String[1..*] {unique, ordered} ssNo: String {readOnly} /age: int password: String = "pw123" <u>personsNumber: int</u>



# Attribute Syntax - Properties




Person
firstName: String lastName: String dob: Date address: String[1..*] {unique, ordered} ssNo: String {readOnly} /age: int password: String = "pw123" <u>personsNumber: int</u>

- Pre-defined Properties
  - {readOnly} ... value cannot be changed
  - {unique} ... no duplicates permitted
  - {non-unique} ... duplicates permitted
  - {ordered} ... fixed order of the values
  - {unordered} ... no fixed order to the values
- Attribute specification
  - Set: {unordered, unique}
  - Multi-set: {unordered, non-unique}
  - Ordered set: {ordered, unique}
  - List: {ordered, non-unique}




# Operation Syntax - Parameters




- Notation similar to attributes
- Direction of the parameter
  - in ... input parameter
    - When the operation is used, a value is expected from this parameter
  - out ... output parameter
    - After the execution of the operation, the parameter has adopted a new value
  - inout ... combined input/output parameter

Person
...
+ getName(out fn: String, out ln: String): void
+ updateLastName(newName: String): boolean
+ getPersonsNumber(): int





# Operation Syntax - Type



- Type of the return value

Person
...
getName(out fn: String, out ln: String): void updateLastName(newName: String): boolean getPersonsNumber(): int





# Class Variable and Class Operation

- Instance variable (= instance attribute): attributes defined on instance level
- Class Variable (= class attribute, static attribute)
  - Defined only once per class, i.e., shared by all instances of the class
  - E.g. counters for the number of instances of a class, constants, etc.
- Class operation (= static operation)
  - Can be used if no instance of the corresponding class was created
  - E.g. constructors, counting operations, math functions ( $\sin(x)$ ), etc.
- Notation: underlining name of class variable/class operation

Class  
variable

Class  
operation





Person
+ firstName: String
+ lastName: String
- dob: Date
# address: String[]
- <u>pNumber: int</u>
+ <u>getPNumber(): int</u>
+ <u>getDob(): Date</u>



```
class Person {  
  
    public String firstName;  
    public String lastName;  
    private Date dob;  
    protected String[] address;  
    private static int pNumber;  
    public static int getPNumber()  
{...}  
  
    public Date getDob() {...}  
}
```





# Specification of Classes






# Association

- Models possible relationships between instances of classes



# Binary Association



- Connects instances of two classes with one another





# Binary Association - Navigation

- Navigability: an object knows its partner objects and can therefore access their visible attributes and operations
  - Indicated by an open arrow head
- Non-navigability
  - Indicated by cross
- Example:
  - **A** can access the visible attributes and operations of **B**
  - **B** cannot access any attributes and operations of **A**
- Navigability undefined
  - Bidirectional navigability is assumed







# Navigability Best Practices

*UML standard*




*Best practice*





# Binary Association as Attribute

*Preferable*



- Java-like notation:



```
class Professor {...}

class Student{
    public Professor[] lecturer;
    ...
}
```




# Multiplicity and Role

- Multiplicity: Number of objects that may be associated with exactly one object of the opposite side



- Role: describes the way in which an object is involved in an association relationship












# xor Constraint

- “exclusive or” constraint
- An object of class **A** is to be associated with an object of class **B** or an object of class **C** but not with both









# Unary Association






# Unary Association



# n-ary Associations

- More than two partner objects are involved in the relationship
- No navigation directions







# n-ary Associations

- Example

- (Student, Exam) -> (Lecturer)
  - One student takes one exam with one or no lecturer
- (Exam, Lecturer) -> '(Student)'
  - One exam with one lecturer can be taken by any number of students
- (Student, Lecturer) -> (Exam)
  - One student can be graded by one **Lecturer** for any number of exams




≠







# Association Class

- Assign attributes to the relationship between classes rather than to a class itself






# Association Class






# Association vs. Regular Classes



≠



A Student can enroll for one particular StudyProgram only once


A Student can have multiple Enrollments for one and the same StudyProgram






# Association Class

- Default: no duplicates



A student can only be granted an exam meeting for a specific exam **once**.



- non-unique: duplicates allowed



A student can have **more than one** exam meetings for a specific exam.



# Association Class





# Aggregation

- Special form of association
- Used to express that a class is part of another class
- Properties of the aggregation association
  - **Transitive:** if B is part of A and C is part of B, C is also part of A
  - **Asymmetric:** It is not possible for A to be part of B and B to be part of A simultaneously.
- Two types;
  - Shared aggregation
  - Composition



**Are there any questions?**