

```
C:\Users\xps-seira\Dropbox\repos\osrm\osrm-backend>osrm-routed  
osrm-routed <base.osrm> [<options>]:
```

#### Options:

-v [ --version ]	Show version
-h [ --help ]	Show this help message
-l [ --verbosity ] arg (=INFO)	Log verbosity level: NONE, ERROR, WARNING, INFO, DEBUG
--trial [=arg(=1)]	Quit after initialization

#### Configuration:

-i [ --ip ] arg (=0.0.0.0)	IP address
-p [ --port ] arg (=5000)	TCP/IP port
-t [ --threads ] arg (=4)	Number of threads to use
-s [ --shared-memory ] [=arg(=1)] (=0)	Load data from shared memory
-a [ --algorithm ] arg (=CH)	Algorithm to use for the data. Can be CH, CoreCH, MLD.
--max-viaroute-size arg (=500)	Max. locations supported in viaroute query
--max-trip-size arg (=100)	Max. locations supported in trip query
--max-table-size arg (=100)	Max. locations supported in distance table query
--max-matching-size arg (=100)	Max. locations supported in map matching query
--max-nearest-size arg (=100)	Max. results supported in nearest query
--max-alternatives arg (=3)	Max. number of alternatives supported in the MLD route query
--max-matching-radius arg (=5)	Max. radius size supported in map matching query