Does the model fit the landscape? Shape and scale in Bayesian optimisation and CMA-ES

Isaac Soong Hong Wei (A0272752B), Paul Ng Yin Chen (A0272249Y)

Repository: https://github.com/isaacsoong055/DSA4212

Abstract

Bayesian optimisation (BO) and CMA-ES both carry an implicit model of the landscape: CMA-ES a Gaussian search distribution with a covariance (its shape) and a step size (its scale), BO a Gaussian-process surrogate whose kernel metric and lengthscales play the same two roles. We test one explanation in two settings: a method succeeds when its model's shape and scale can match the problem, whatever its family. *Part A (multimodality)* asks whether the model's scale lets a method *find* and then *refine* a narrow distant basin: neither default method finds it; CMA-ES's step size cannot do both jobs at once, and BO succeeds once its lengthscale is capped (1/50 to 44/50 on fresh seeds) while acquisition tuning helps far less. *Part B (geometry)* asks whether the model can *tilt*: on rotated, ill-conditioned valleys diagonal CMA-ES, the ARD kernel and TuRBO's axis-aligned trust region all fail, while their tilting counterparts do not, once BO's own fitting failures are removed. In both parts the decisive BO changes were to the model fit, not the acquisition function. All results are in 2-D and pre-registered predictions are reported whether they held or failed.

1 Introduction

1.1 Motivation and the two methods

Many optimisation problems give only function values: tuning a model's hyperparameters, calibrating a simulator, choosing a design. There are no gradients, and each evaluation can cost a training run or a simulation, so a method must decide where to evaluate next from the values it has seen, and its budget is counted in evaluations. Bayesian optimisation (BO) and the covariance matrix adaptation evolution strategy (CMA-ES) are two of the most widely used methods for this setting, and they embody opposite design choices: BO models the function, while CMA-ES adapts a search distribution.

BO [5] fits a Gaussian-process (GP) surrogate to all evaluations so far. Its kernel encodes smoothness and lengthscales, and its posterior gives a prediction and an uncertainty everywhere. An acquisition function, such as expected improvement (EI), turns these into the next point, trading off exploiting good predictions against exploring uncertain regions. *CMA-ES* [7] samples a population of λ candidates from a Gaussian $\mathcal{N}(m, \sigma^2 C)$, ranks them, moves the mean towards the best, and adapts the covariance C and the step size σ from successful steps. It uses only the ranking of the values. The basic trade-off follows: BO is sample-efficient because it uses every value through a global model, but each step is expensive (fitting the GP grows cubically with the number of points) and its success depends on that model being right; CMA-ES needs more evaluations but each step is nearly free, and it learns the *local* geometry of the problem.

1.2 What the literature says, and what it leaves open

Our questions came from the readings. Hansen's tutorial [7] states the invariances CMA-ES is designed to have: to any order-preserving transformation of f, and to rotations and other linear maps of the search space provided the initial conditions are mapped too; its covariance comes to approximate the inverse Hessian on a convex quadratic. This raised the question of which invariances survive in practice and whether a model that cannot rotate pays for it. Restart schemes that grow or mix the population size (IPOP, BIPOP [2, 6]) were introduced for multimodal functions, which raised the question of whether population and restarts help find a narrow basin. TuRBO [4] restricts BO's search to local trust regions whose sides are set per coordinate from the ARD lengthscales, an axis-aligned shape; COCO [9] sets the benchmarking practice we follow (budgets in evaluations, random instances, targets and intervals).

The literature also shows that BO's results depend on settings that are rarely reported. Hvarfner et al. [10] argue that BO's poor high-dimensional performance owes much to its lengthscale prior, and that a dimension-scaled prior makes plain BO competitive. Ament et al. [1] show that EI's values and gradients vanish numerically, so the acquisition optimiser can fail; and Siivola et al. [11] show that GP-based BO over-explores the boundary of the search box. A comparison of "BO against CMA-ES" run with library defaults therefore mixes the family with hidden choices: kernel fitting, lengthscale bounds, noise handling, step size. What remains open is which of those properties actually decides success.

1.3 Problem formulation

Research question. When BO and CMA-ES succeed or fail on a black-box problem, which property of the method decides the outcome, and does it matter more than the choice of family?

Guiding hypothesis. Each method carries an implicit model of the landscape. For CMA-ES it is the search distribution: the covariance sets its *shape* (orientation and relative stretch) and the step size its *scale*. For BO it is the GP: the kernel metric sets the shape (a full metric, or the diagonal ARD metric) and the lengthscales the scale. A method succeeds when its model can match the landscape's shape (orientation, conditioning) and scale (the size of the features it must find and resolve), and fails when a restriction or a fitting failure prevents it, whichever family it belongs to.

1.4 Shared experimental approach

Both parts fix a budget counted in objective evaluations, with initial designs and restarts included; run every variant on the same seeds, so comparisons are paired; change one setting at a time against a baseline; and commit their predictions to the repository before the runs that test them, reporting each as held, partly held or failed. A method's recommendation is its best evaluated point, judged on the true objective: in Part A by whether its regret reaches a success threshold, in Part B by its regret in decades of $\log_{10} f$. With noisy evaluations the recommended point is scored on the noise-free objective, and several recommendation rules are compared. Uncertainty is given as 95% intervals (Wilson and Newcombe intervals for success rates; paired bootstrap intervals over instances for regret). The two parts use different budgets, measures and BO implementations (BoTorch [3]; NumPy/SciPy), so their numbers are never put on common axes.

1.5 The two directions

Part A, multimodality (Isaac Soong), asks whether each method can *find* a narrow, distant global basin and then *refine* it, within 300 evaluations. It varies CMA-ES's population size, restarts and step size, and BO's acquisition function, GP fitting settings and kernel, on a decoy bowl with a narrow Gaussian well (whose width and distance are varied), with a sphere as a unimodal control and Rastrigin and Schwefel as validation functions.

Part B, geometry and parameterisation (Paul Ng), asks whether a method's model can *tilt* to a rotated, ill-conditioned valley, and which theoretical invariances survive the implementation. It varies the conditioning and rotation of the problem and whether each method's model can rotate (full against diagonal covariance; full against ARD kernel metric; a rotated against an axis-aligned trust region), and also tests changes of units, monotone transformations of f, the box boundary and noisy evaluations, on ellipsoids, Rosenbrock (COCO f8/f9 [8]) and a noisy quadratic, within 200 evaluations.

1.6 Preview of findings and contributions

Part A finds that neither default method discovers a narrow, distant basin. For CMA-ES no population size, restart scheme or step size fixes this, because one step size cannot both find the basin and refine it; for BO, capping the GP lengthscale does, while tuning the acquisition function helps far less. Part B finds that, in both families, the version of the method that cannot tilt fails under rotation and the version that can does not; for BO this became visible only after a fitting failure that stalled every run was diagnosed and fixed, and it then held across two kernels, two acquisition searches and a TuRBO-style trust region. CMA-ES keeps its rank invariance exactly; BO keeps neither invariance.

Together the parts contribute a tested account of shape and scale across both families; the shared, unplanned finding that BO's decisive fixes were to the *model fit*, not to the acquisition function; and a set of negative and surprising results reported as such: pre-registered predictions that failed, an initial negative result that turned out to be a fitting failure, a boundary trap, and BO runs that do not repeat bit for bit.

Roadmap. Section 2 presents Part A and Section 3 Part B, each opening with its answer, then setting out the evidence experiment by experiment, and closing with its predictions against outcomes. Section 4 draws the two together and states the limitations.

2 Part A: finding and refining a narrow basin (multimodality)

Answer in brief. Neither default method finds a narrow, distant well within 300 evaluations. For CMA-ES no setting we tried fixes this, because one step size cannot both find the well and refine it; for BO, capping the GP lengthscale does, while changing the acquisition function helps far less.




Figure 1. Part A. Primary landscape: a decoy bowl centred at the origin and a narrow global well at $(3, 3)$, $w = 0.3$.

2.1 Question, set-up and predictions

At a fixed budget of $N = 300$ evaluations, how do population size, restarts, step size and acquisition and surrogate choices change the probability of finding a narrow, distant global basin, and why? Predictions H1–H6 and M1–M3 were committed before any optimiser result was inspected; BO1–BO13 and CMA1–CMA6 were added later, each before the experiment that tested it, except BO1 (post hoc, labelled as such).

The primary landscape is a broad decoy bowl with a narrow, deep Gaussian well, $f(x) = \|x-c\|^2/s - A\exp(-\|x-x_g\|^2/2w^2)$ with $c = 0$, $s = 10$, $A = 4$, width $w = 0.3$, the well at $(3, 3)$ (Fig. 1), on $[-5, 5]^2$. A run succeeds when its regret falls to $\varepsilon = 0.05$, a threshold chosen from random sampling alone. CMA-ES is the `cma` library (default $\lambda = 6$, $\sigma_0 = 2$, start $x_0 \sim U[-4, 4]^2$); BO is BoTorch GP-EI (Matérn-5/2, 10 initial points, refit every 5 evaluations, lengthscale upper bound 20, fixed noise 10^{-6}). Each variant changes one setting and uses seeds 1000–1049; success rates carry Wilson intervals and differences Newcombe intervals.

2.2 Both defaults fail at discovery, not refinement (Exp 0)

Neither default finds the well: CMA-ES 0/50, BO 5/50, random sampling 2/50, with pairwise-overlapping intervals. CMA-ES's σ falls below 0.2 by generation 19 (median) and from evaluation 100 on at least 97.5% of its samples lie within 0.5 of the decoy centre (H1 supported). BO's lengthscale runs to its upper bound in 42 of 50 runs, none of which succeeds, and in the 45 failures no sample ever enters the well. Both fail at *discovery*, not refinement: every BO run that sampled the well succeeded.

2.3 Population and restarts do not help CMA-ES: one step size must both find and refine (Exps 1–3)

A larger population raises the number of runs that touch the well (1, 7 and 13 of 50 for $\lambda = 6, 12, 24$) but success stays 0/50 at every λ, also with five times the budget (H2 contradicted). IPOP and BIPOP [2, 6] are identical at this budget, because only one restart fits, and also give 0/50 (H3 contradicted on success). The step size explains why (Fig. 2): from a start 1.0 from the well, $\sigma_0 = 0.3$ succeeds in 33/50 runs and the default $\sigma_0 = 2$ in 2/50 ($+0.62$ $[+0.45, +0.74]$), while from a random start no σ_0 exceeds 1/50. A mean trace shows the mechanism: with $\sigma_0 = 2$, a single well sample is outvoted by the other selected points on the bowl, which drag the mean back to the decoy. Finding the well needs a large σ and refining it a small one, and the default has to choose.

2.4 BO is held back by its model fit, not its acquisition function (Exps 4–7)

Exploration in EI helps a little: $\xi = 0.1$ reaches 17/50 ($+0.24$ $[+0.08, +0.39]$ over $\xi = 0$), and larger ξ touches the well more often but refines it less (17/45 to 3/42 given a touch). LCB (β from 0.5 to 32), Thompson sampling and BoTorch's default MAP recipe all stay at 3–4/50. The model fit matters far more (Fig. 3): capping the lengthscale at 1 gives 39/50 ($+0.68$ $[+0.51, +0.79]$), because the default fit runs to the bound and the search stays near the bowl centre, while a cap makes it sweep the box (about 100 of 100 grid cells visited, against 10). The cap has an optimum: 0.25 drops back to 6/50. Changing the kernel at the default cap changes nothing; at cap 1 RBF matches Matérn-5/2 (39/50) but the rougher Matérn-3/2 and 1/2 collapse (6 and 3/50) by failing to discover the well.




Figure 2. Part A, Exp 3. CMA-ES success against initial step size from a start 1.0 from the well (a diagnostic of refinement, not a method comparison).




Figure 3. Part A, Exp 6. BO fitting settings changed one at a time: lengthscale cap and noise level (BoTorch, $N = 300$).

2.5 The capped BO holds across widths, costs on a unimodal bowl and transfers only partly (Exps 8–10)

Across well widths (Fig. 4) the capped BO, evaluated on fresh seeds 2000–2049 to avoid selection bias, succeeds in 44/50 at $w = 0.3$ and 50/50 at $w = 0.6$ and 1.0, against 1, 10 and 39/50 for default BO; CMA-ES needs a wide well (35/50 at $w = 1.0$, 0/50 at $w = 0.3$), and the best CMA-ES variant ($\sigma_0 = 1$) gives no gain at any width. On a near well, default CMA-ES beats default BO (30 against 13/50 at $w = 0.3$). The capped BO has a cost on a unimodal sphere (regret 8.9×10^{-4} against 1.2×10^{-6} at evaluation 100), and a larger λ worsens CMA-ES there (H5 supported). On Rastrigin and Schwefel the cap's gain is small and uncertain, and BO is far stronger than CMA-ES on Schwefel (16/20 default, 20/20 capped, against at most 8/50); whether λ helps more on Rastrigin than on Schwefel (H6) could not be distinguished.

2.6 Predictions against outcomes

Prediction (pre-registered)	Exp	Outcome	Evidence
H1: default CMA-ES gets stuck in the decoy basin	0	Held	0/50; $\sigma < 0.2$ by generation 19
H2: a larger λ raises success	1	Failed	0/50 at $\lambda = 6, 12, 24$, also at $N = 1500$
H3: restarts beat a larger λ	2	Failed	IPOP = BIPOP = 0/50
CMA1: near the well, success falls as σ_0 grows	3	Held	33/50 at $\sigma_0 = 0.3$, 2/50 at 2
CMA5: success is set by σ_0/w alone	3	Failed	wide wells prefer a large σ_0
H4: BO finds the well only if it explores enough	4–5	Partly held	$\xi = 0.1$: 17/50, falls beyond; flat in β
BO7: a lengthscale cap does not help	6	Failed	cap 1: 39/50 against 5/50
H5: a larger λ does not help on the sphere	9	Held	regret worse with λ
H6: λ helps more on Rastrigin than Schwefel	10	Not resolved	intervals overlap

Table 1. Part A. Selected pre-registered predictions and how they fared (full list in `multimodality/docs/`).




Figure 4. Part A, Exp 8. Success against well width for the defaults and the best variants (fresh seeds), far and near well.

3 Part B: can the search tilt? (geometry and parameterisation)

Answer in brief. In both families, the version of the method that cannot tilt fails under rotation and the version that can does not; for BO this became visible only after a fitting failure was found and fixed. CMA-ES keeps its rank invariance exactly; BO keeps neither invariance, and its behaviour at the box edge and under noise depends on implementation details.

3.1 Question, set-up and predictions

Near a minimum $f \approx f^* + \frac{1}{2}h^\top Hh$. The Hessian's eigenvalues are the curvatures; their ratio κ is the conditioning (a narrow valley when large); its eigenvectors are the valley's orientation, which a rotation changes without changing κ. A full covariance (CMA-ES) or a full kernel metric $M = LL^\top$ (BO) can align with a rotated valley; a diagonal covariance, the standard ARD kernel and TuRBO's axis-aligned trust region [4] cannot. We predicted that (i) each axis-restricted method pays a penalty under rotation that its tilting counterpart does not, (ii) only when the problem is both ill-conditioned and rotated, and (iii) the tilting version pays a small price when no tilt is needed.

2-D ellipsoids with log-spaced eigenvalues from 1 to κ, the optimum on a radius-2 sphere, aligned or Haar-rotated, 15 instances (COCO-style; seed = instance). CMA-ES follows Hansen's tutorial, with a diagonal ablation. BO is GP-EI (initial design of $2d + 4$, EI over 200 uniform candidates polished by L-BFGS-B, targets log-transformed) with a MAP lengthscale prior on the metric's eigen-lengthscales [10], so that the prior does not favour axis-aligned metrics. Both get the box $[-5, 5]^2$ (BO searches it; CMA-ES starts at its centre with $\sigma_0 = 3$) and 200 evaluations.

3.2 CMA-ES fails under rotation only when it cannot tilt (E1, E7)

At $\kappa = 1{,}000$, diagonal CMA-ES solves every instance at 0° and 90° and none between 30° and 60°; full CMA-ES solves every angle (Fig. 5). The 90° control only swaps the axes, so the rotation, not the conditioning, causes the failure. At $\kappa = 100$ both succeed everywhere (prediction ii). Full CMA-ES is rotation-invariant in distribution (405 against 408 median evaluations under Haar rotation) and costs up to 21.6% more evaluations on aligned problems at $d = 32$ (prediction iii). IPOP-style restarts [2] do not repair the diagonal failure (7% against 20% reaching 10^{-5} at rotated $\kappa = 10^4$): a restarted diagonal run still cannot tilt.

3.3 BO first showed no penalty, because a fitting failure stalled every run (E2, E2e)

Reading the fitted kernel directly, ARD's long axis is off by exactly 45° on 45° problems while the full metric is within 0.2°–4°. Yet the first head-to-head showed *no* rotation penalty for BO-ARD (+0.05 [-0.53, +0.63] decades at $\kappa = 100$), while diagonal CMA-ES paid +1.70 [+0.41, +2.57]. BO was stalling everywhere, near $10^{-2.6}$ even on the round bowl. Per-iteration logs ruled out the target transform's floor and the candidate search, and showed the cause: the GP fitted a noise term to a noise-free function and explained its best points away as noise (fitted noise SD 0.2–0.4; posterior mean at the incumbent 2–2.5× the gap to the second-best point above its observed value), so EI against the observed best underflowed below 10^{-12} in 97–100% of late iterations. Fixing the noise variance at 10^{-6} lifted BO by −1.17 [-1.71, -0.74] decades; LogEI [1], which fixes the underflow but not its cause, changed nothing (+0.01 [-0.79, +0.47]).




Figure 5. Part B, E1. Success of full (solid) and diagonal (dashed) CMA-ES against the angle of a 2-D valley.




Figure 6. Part B. Rotation penalty at 200 evaluations (median, 95% bootstrap interval, 15 instances). Hollow: BO before the noise fix. The axis-restricted variant pays in both families once BO is no longer stalled.

3.4 Once BO works, the axis-restricted version pays in every variant (E2, E8, E10)

Re-running the 180 BO runs with the fix, paired by instance, the negative result reversed (Fig. 6): BO-ARD's rotation penalty became +2.01 [+1.28, +2.97] decades at $\kappa = 10^4$ and BO-full's stayed non-significant. Table 2 repeats the key comparison with a second kernel (Matérn-5/2), a second acquisition search (200 extra candidates around the incumbent) and a TuRBO-style trust region whose box is either axis-aligned with ARD-scaled sides, as published, or rotated to the full metric: in every variant the axis-restricted version ends significantly behind on rotated problems and level on aligned ones. With the trust region, BO also beats full CMA-ES at 200 evaluations on aligned $\kappa = 100$ (−1.36 [-2.02, -0.85]) and rotated $\kappa = 10^4$ (−3.32 [-4.24, -1.82]); with plain EI, CMA-ES wins by 200 evaluations at $\kappa \leq 100$ (1.2–2.7 decades).

3.5 On a bending valley, local orientation and local search decide (E5, E9, E12)

A quadratic has the same orientation everywhere; Rosenbrock (COCO f8/f9 [8]) bends, so its local orientation changes along the path, and even "aligned" f8 is tilted 63.5° near its optimum. With 4,000 evaluations full CMA-ES reaches 10^{-5} in every run (median about 500 evaluations), diagonal in 0% (f8) and 27% (f9): what matters is the local orientation. For BO we compared three versions at 300 evaluations, which differ in where they search and which points they learn the valley's shape from: plain BO (one GP fitted to all points, searching the whole box), a trust region (the same fitting, but searching only a box around the best point that grows and shrinks), and a trust region whose GP is fitted only to the points inside that box (at least 20). The trust region beat plain BO

BO variant (2-D, 15 instances, 200 evaluations)	rotated $\kappa = 10^4$	aligned $\kappa = 10^4$
EI, squared exponential, noise fixed	$+1.40$ [$+0.68, +1.69$]	-0.13 [-1.15, $+0.19$]
EI, Matérn-5/2	$+1.06$ [$+0.59, +1.43$]	-0.13 [-0.70, $+0.54$]
EI + local candidates	$+1.28$ [$+0.12, +2.36$]	-2.96 [-3.44, $+2.61$]
Trust region, ARD box vs rotated box	$+2.92$ [$+1.27, +3.79$]	-0.39 [-3.11, $+4.65$]

Table 2. Part B. Axis-restricted minus tilting version, median $\log_{10} f$ at 200 evaluations, paired by instance (+ = axis-restricted worse). Wide aligned intervals come from the boundary trap (text).

by 3.5–3.7 decades, and its tilted box beat the axis-aligned one by 2.0–2.5 decades, even on f8. Plain BO's kernel does adapt its lengthscales, but it is stationary: one metric for the whole box, which on a curving valley can only average the directions along it, whereas within a small box the valley is close to a straight, tilted one. We predicted that fitting the GP only to the nearby points would follow the bend better still. It did not: it trailed the ordinary trust region by 1.8–2.0 decades (though it stayed about 1.7 decades ahead of plain BO). On a quadratic control, whose shape is the same everywhere so that a local fit can gain nothing, it lost 2.7 decades; the loss therefore comes from fitting the GP to fewer points, not from the geometry. Part of the trust region's lead over plain BO may also come from its denser candidates near the best point (1,000 inside the box against 200 across the whole box), which this experiment does not separate.

3.6 CMA-ES keeps its rank invariance; BO keeps neither, and the box edge can trap it (E3, E4, E11)

CMA-ES runs were bit-identical to the baseline under every monotone transformation of f (120/120); BO is not rank-invariant, and cubing f costs it 1.7 decades through its relative target floor. A change of units hurts every method with default set-ups (CMA-ES about 3.9 decades, BO 1.3–1.4); mapping CMA-ES's initial covariance as Hansen requires ($C_0 = S^{-2}$) restores invariance. BO over-samples the box edge [11]: it is 1.62 / 0.73 decades worse when the optimum lies 0.1 inside an edge and better when it lies on it. Combined with search around the incumbent this produces a *boundary trap*: 4–8 of 15 runs per aligned ill-conditioned cell stall on the valley floor at the box edge. In those runs about two random candidates per iteration are truly better, yet the GP gives them EI near 10^{-34}: a model failure. Reflecting out-of-box candidates instead of clipping them removes the trap for the trust region (6 and 4 stuck runs to 0) but not for local candidates.

3.7 Under noise, the recommendation rule matters as much as the budget split (E5, E6, E6b)

On the $\kappa = 100$ quadratic with additive noise $\sigma \in \{0.01, 0.1, 1\}$ and every recommendation scored on the noise-free f, BO's posterior-mean pick beats its lowest reading by up to 1.08 decades, CMA-ES's mean helps only with a larger population ($\lambda = 24$), and spending evaluations on repeats or a final re-evaluation reserve did not pay at 200 evaluations. With each family's best settings the two are level at every noise level. The one anomaly, a worse model-based pick with replicates, is again the noise-fitting GP: a correctly specified GP on the raw values never does worse than the lowest reading.

3.8 Predictions against outcomes

Prediction (written before the runs)	Exp	Outcome	Evidence
(i) diagonal CMA-ES pays under rotation	E1	Held	0% solved at 30°–60°, $\kappa = 1{,}000$
(i) BO-ARD pays under rotation (first run)	E2	Failed	$+0.05$ [-0.53, $+0.63$]: BO was stalling
(i) BO-ARD pays once BO works	E2, E8, E10	Held	$+1.06$ to $+2.92$ decades, rotated $\kappa = 10^4$
(ii) no penalty on aligned problems	E1, E2, E10	Held	aligned differences not significant
(iii) tilting costs a little when not needed	E1, E10	Held	+21.6% evaluations; ARD box 0.57 better
CMA-ES is exactly invariant to monotone maps of f	E3	Held	120/120 runs bit-identical
BO is nearly invariant to powers of f	E3	Failed	cube of f: +1.7 decades
fixing BO's noise backfires on noisy problems	E5	Failed	fixed noise still better, -0.41
both CMA-ES variants solve Rosenbrock with 4,000 evaluations	E9	Failed	diagonal: 0% (f8), 27% (f9)
a locally fitted trust region follows the bend better	E12	Failed	1.8–2.0 decades worse; control 2.7 worse

Table 3. Part B. Selected predictions and how they fared (all 21 in `geometry/`).

4 Synthesis: what the two parts establish together

Shape and scale both decide success, within each family. Part A shows that a model with the wrong *scale* fails to find or to refine a narrow basin, and Part B that a model restricted in *shape* fails on tilted valleys in both families. In neither part does the family alone predict the outcome: diagonal and full CMA-ES differ by up to 100 percentage points on the same rotated problem, and capped and default BO by 43 successes out of 50 on the same landscape (44 against 1 on fresh seeds).

BO's decisive fixes were to the model fit, not the acquisition. Independently, both parts found BO failing because its GP was mis-fitted, and both found acquisition changes nearly powerless: in Part A the lengthscale ran to its bound (capping it took success from 5 to 39/50; ξ, LCB and Thompson sampling at most 17/50), in Part B the fitted noise absorbed the best points (fixing it gained over a decade; LogEI nothing). In both, BO's results depend on implementation choices that published defaults leave open.

CMA-ES adapts shape well but must commit to a scale. One step size cannot both find a distant basin and refine a narrow one (Part A), but its covariance follows a rotated valley reliably (Part B); population size and restarts, which change only how much is sampled, did not move success on the primary landscape.

Trade-offs. BO leads early in both parts and costs roughly 10^5 times more computation per run; settings that help on the hard landscape cost on easy ones (the cap on the sphere, tilting on aligned problems); and BO's boundary preference appears in both parts (edge sampling under large ξ; the boundary trap).

Limitations. All headline results are 2-D, so dimension effects are inferred (for CMA-ES) rather than measured for BO. Each part rests on few landscapes (ellipsoids and Rosenbrock; one primary landscape plus two validation functions) and 15–50 seeds, which leaves some differences unresolved. BO results reproduce in distribution only: long BO runs are not bit-repeatable even with one BLAS thread. Some follow-ups were added after seeing results and are labelled as such; untested mechanisms are stated as hypotheses.

References

[1] S. Ament, S. Daulton, D. Eriksson, M. Balandat, and E. Bakshy. Unexpected improvements to expected improvement for Bayesian optimization. In *Advances in Neural Information Processing Systems 36*, 2023.

[2] A. Auger and N. Hansen. A restart CMA evolution strategy with increasing population size. In *IEEE Congress on Evolutionary Computation (CEC)*, 2005.

[3] M. Balandat, B. Karrer, D. R. Jiang, S. Daulton, B. Letham, A. G. Wilson, and E. Bakshy. BoTorch: A framework for efficient Monte-Carlo Bayesian optimization. In *Advances in Neural Information Processing Systems 33*, 2020.

[4] D. Eriksson, M. Pearce, J. Gardner, R. D. Turner, and M. Poloczek. Scalable global optimization via local Bayesian optimization. In *Advances in Neural Information Processing Systems 32*, 2019.

[5] P. I. Frazier. A tutorial on Bayesian optimization. *arXiv preprint arXiv:1807.02811*, 2018.

[6] N. Hansen. Benchmarking a BI-population CMA-ES on the BBOB-2009 function testbed. In *Proceedings of the Genetic and Evolutionary Computation Conference (GECCO), Workshop on Black-Box Optimization Benchmarking*, 2009.

[7] N. Hansen. The CMA evolution strategy: A tutorial. *arXiv preprint arXiv:1604.00772*, 2016.

[8] N. Hansen, S. Finck, R. Ros, and A. Auger. Real-parameter black-box optimization benchmarking 2009: Noiseless functions definitions. Technical Report RR-6829, INRIA, 2009.

[9] N. Hansen, A. Auger, R. Ros, O. Mersmann, T. Tušar, and D. Brockhoff. COCO: A platform for comparing continuous optimizers in a black-box setting. *Optimization Methods and Software*, 36(1):114–144, 2021.

[10] C. Hvarfner, E. O. Hellsten, and L. Nardi. Vanilla Bayesian optimization performs great in high dimensions. In *Proceedings of the 41st International Conference on Machine Learning*, 2024.

[11] E. Siivola, A. Vehtari, J. Vanhatalo, J. González, and M. R. Andersen. Correcting boundary over-exploration deficiencies in Bayesian optimization with virtual derivative sign observations. In *IEEE 28th International Workshop on Machine Learning for Signal Processing (MLSP)*, 2018.