

Упражнение

- Given the fact that you have created an object, it can operate in a manner independent of other objects based on the same class.
- The PanelBar displays hierarchical data as a multi-level, expandable component and is stateless, which means that to store its state and configuration options, you must use a high-order component.
- Before taking this course, you are supposed to have completed XX101.
- The STYLE option specifies the style element to use when names of classification variables are used as headings.
- You can set the filterable option to true to enable the Grid

Упражнение

- The Limits window is used to specify the minimum and maximum values.
- Up to 500 files can be stored in the database.
- Up to 256 characters can be typed in this entry field.
- The metadata is exported to the new catalog tables.
- Your document can be divided into as many sections as you want.
- A number of benefits are provided by data hiding.
- The Web pages were uploaded during the installation.
- After reading this tutorial, the roadmap should be created.
- VMDOFF specifies whether metadata verification checking is to be performed on the data model.

Упражнение

- If you want to enable the filtering functionality of the Grid, you can set the filterable option to true.
- As an example, one can use the fas6toyconfig.xml from the dev/config/ directory.
- Writing a use scenario of the unit (function or class) in the form of a test provides a specification that one can execute and see it working (or not) in an isolated, simple way.
- The headerTemplate option specifies the static HTML content, which would be rendered as the popup element header.
- Only 17 characters are available for the table name on a standard tape label.