

2/15/2023

assign 4

vv census: if (y || x) { ?

we for loop \rightarrow to 1

if \rightarrow odd use mod, don't use mod otherwise

check if value is valid (not negative):

if so, add to count

interability test - your code should meet someone else's code
assuming you both followed spec

Bash: dirs - stack of folders

pushd - temporarily leave spot

popd - return to spot

Files: Hard drive, reader head is like an airplane, moves up & down

File extension - means nothing in Unix, can have .c .y .d if u want

- Unix doesn't care about it

- Windows is different, extension is special

Unix, no structure on files

#! is a #, means that it's a script

zip:

header name, etc...

object

header

object

so it can be taken apart

Sequential access, from start to end, cannot rewind

Random access, like RAM

Read has a pointer that goes through file

Unix \uparrow Lseek

accepts long

File Attributes:

Set protections for files on a shared computer

"Functionally Complete" - function can build other functions
ex: NAND, NOR

Originally, directories were files, you can open directories
- you can open a Unix

the name you see for a file is a pointer


If the ~~structures~~ of a directory are specified, they can be fixed even if deleted
a directory read is "atomic" operation, nothing smaller allows first

Unix

Hard link

- directories both have pointers to file
- don't try this on directories

Unix 7 file system



MBR master boot record

Boot block

super-block like an index
free space

Inodes - file pointers

Root directory