

Stateful-Failure Reactive Designs in Isabelle/UTP

Simon Foster James Baxter Ana Cavalcanti Jim Woodcock

October 21, 2021

Abstract

Stateful-Failure Reactive Designs specialise reactive design contracts with failures traces, as present in languages like CSP and Circus. A failure trace consists of a sequence of events and a refusal set. It intuitively represents a quiescent observation, where certain events have previously occurred, and others are currently being accepted. Following the UTP book, we add an observational variable to represent refusal sets, and healthiness conditions that ensure their well-formedness. Using these, we also specialise our theory of reactive relations with operators to characterise both completed and quiescent interactions, and an accompanying equational theory. We use these to define the core operators — including assignment, event occurrence, and external choice — and specialise our proof strategy to support these. We also demonstrate a link with the CSP failures-divergences semantic model.

Contents

1	Introduction	2
2	Stateful-Failure Core Types	3
2.1	SFRD Alphabet	3
2.2	Basic laws	3
2.3	Unrestriction laws	4
3	Stateful-Failure Reactive Relations	5
3.1	Healthiness Conditions	5
3.2	Closure Properties	8
3.3	Introduction laws	13
3.4	UTP Theory	14
3.5	Weakest Precondition	15
3.6	Trace Substitution	16
3.7	Initial Interaction	17
3.8	Enabled Events	18
3.9	Completed Trace Interaction	20
3.10	Assumptions	24
3.11	Downward closure of refusals	25
3.12	Renaming	27
4	Stateful-Failure Healthiness Conditions	28

5	Definitions	28
5.1	Healthiness condition properties	29
5.2	CSP theories	40
5.3	Algebraic laws	41
6	Stateful-Failure Reactive Contracts	42
7	External Choice	44
7.1	Definitions and syntax	44
7.2	Basic laws	44
7.3	Algebraic laws	44
7.4	Reactive design calculations	44
7.5	Productivity and Guardedness	51
7.6	Algebraic laws	52
8	Stateful-Failure Programs	55
8.1	Conditionals	56
8.2	Guarded commands	56
8.3	Alternation	56
8.4	Specification Statement	56
8.5	Assumptions	57
8.6	While Loops	57
8.7	Iteration Construction	58
8.8	Assignment	61
8.9	Assignment with update	62
8.10	State abstraction	63
8.11	Guards	63
8.12	Basic events	67
8.13	Event prefix	69
8.14	Guarded external choice	70
8.15	Input prefix	71
8.16	Renaming	72
8.17	Algebraic laws	73
9	Recursion in Stateful-Failures	75
9.1	Fixed-points	75
9.2	Example action expansion	76
10	Linking to the Failures-Divergences Model	76
10.1	Failures-Divergences Semantics	76
10.2	Circus Operators	78
10.3	Deadlock Freedom	84
11	Meta-theory for Stateful-Failure Reactive Designs	85

1 Introduction

This document contains a mechanisation in Isabelle/UTP [1] of an specialisation of stateful reactive designs with refusal information, as present in languages like Circus [2].

2 Stateful-Failure Core Types

```
theory utp-sfrd-core
  imports UTP-Reactive-Designs.utp-rea-designs
begin
```

2.1 SFRD Alphabet

```
alphabet ('σ, 'φ) sfrd-vars = ('φ list, 'σ) rsp-vars +
  ref :: 'φ set
```

The following two locale interpretations are a technicality to improve the behaviour of the automatic tactics. They enable (re)interpretation of state spaces in order to remove any occurrences of lens types, replacing them by tuple types after the tactics *pred-simp* and *rel-simp* are applied. Eventually, it would be desirable to automate preform these interpretations automatically as part of the **alphabet** command.

```
type-synonym ('σ, 'φ) sfrd = ('σ, 'φ) sfrd-vars
type-synonym ('σ, 'φ) action = ('σ, 'φ) sfrd hrel
type-synonym 'φ csp = (unit, 'φ) sfrd
type-synonym 'φ process = 'φ csp hrel
```

There is some slight imprecision with the translations, in that we don't bother to check if the trace event type and refusal set event types are the same. Essentially this is because its very difficult to construct processes where this would be the case. However, it may be better to add a proper ML print translation in the future.

translations

```
(type) ('σ, 'φ) sfrd <= (type) ('σ, 'φ) sfrd-vars
(type) ('σ, 'φ) action <= (type) ('σ, 'φ) sfrd hrel
(type) 'φ process <= (type) (unit, 'φ) action
```

```
notation sfrd-vars.moreL (ΣC)
```

```
declare des-vars.splits [alpha-splits del]
declare rp-vars.splits [alpha-splits del]
declare des-vars.splits [alpha-splits del]
declare rsp-vars.splits [alpha-splits del]
declare rsp-vars.splits [alpha-splits]
declare rp-vars.splits [alpha-splits]
declare des-vars.splits [alpha-splits]
```

2.2 Basic laws

```
term U($tr = $tr @ [[a]S<])
```

```
lemma R2c-tr-ext: R2c (U($tr = $tr @ [[a]S<])) = U($tr = $tr @ [[a]S<])
  by (rel-auto)
```

```
lemma circus-alpha-bij-lens:
```

```
  bij-lens ({ $ok, $ok, $wait, $wait, $tr, $tr, $st, $st, $ref, $ref }α :: - ⇒ ('s, 'e) sfrd × ('s, 'e) sfrd)
  by (unfold-locales, lens-simp+)
```

2.3 Unrestriction laws

lemma *pre-unrest-ref* [*unrest*]: $\$ref \# P \implies \$ref \# pre_R(P)$
by (*simp add: pre_R-def unrest*)

lemma *peri-unrest-ref* [*unrest*]: $\$ref \# P \implies \$ref \# peri_R(P)$
by (*simp add: peri_R-def unrest*)

lemma *post-unrest-ref* [*unrest*]: $\$ref \# P \implies \$ref \# post_R(P)$
by (*simp add: post_R-def unrest*)

lemma *cmt-unrest-ref* [*unrest*]: $\$ref \# P \implies \$ref \# cmt_R(P)$
by (*simp add: cmt_R-def unrest*)

lemma *st-lift-unrest-ref'* [*unrest*]: $\$ref \# [b]_{S<} \implies$
by (*rel-auto*)

lemma *RHS-design-ref-unrest* [*unrest*]:
 $\llbracket \$ref \# P; \$ref \# Q \rrbracket \implies \$ref \# (\mathbf{R}_s(P \vdash Q)) \llbracket false/\$wait \rrbracket$
by (*simp add: RHS-def R1-def R2c-def R2s-def R3h-def design-def usubst unrest*)

lemma *R1-ref-unrest* [*unrest*]: $\$ref \# P \implies \$ref \# R1(P)$
by (*simp add: R1-def unrest*)

lemma *R2c-ref-unrest* [*unrest*]: $\$ref \# P \implies \$ref \# R2c(P)$
by (*simp add: R2c-def unrest*)

lemma *R1-ref'-unrest* [*unrest*]: $\$ref \# P \implies \$ref \# R1(P)$
by (*simp add: R1-def unrest*)

lemma *R2c-ref'-unrest* [*unrest*]: $\$ref \# P \implies \$ref \# R2c(P)$
by (*simp add: R2c-def unrest*)

lemma *R2s-notin-ref'*: $R2s(\lceil \langle x \rangle \rceil_{S<} \notin_u \$ref) = (\lceil \langle x \rangle \rceil_{S<} \notin_u \$ref)$
by (*pred-auto*)

lemma *unrest-circus-alpha*:
fixes $P :: ('e, 't) \text{ action}$
assumes
 $\$ok \# P \ \$ok \# P \ \$wait \# P \ \$wait \# P \ \$tr \# P$
 $\$tr \# P \ \$st \# P \ \$st \# P \ \$ref \# P \ \$ref \# P$
shows $\Sigma \# P$
by (*rule bij-lens-unrest-all[OF circus-alpha-bij-lens], simp add: unrest assms*)

lemma *unrest-all-circus-vars*:
fixes $P :: ('s, 'e) \text{ action}$
assumes $\$ok \# P \ \$ok \# P \ \$wait \# P \ \$wait \# P \ \$ref \# P \ \Sigma \# r' \ \Sigma \# s \ \Sigma \# s' \ \Sigma \# t \ \Sigma \# t'$
shows $\Sigma \# [\$ref \mapsto_s r', \$st \mapsto_s s, \$st \mapsto_s s', \$tr \mapsto_s t, \$tr \mapsto_s t'] \vdash P$
using *assms*
by (*simp add: bij-lens-unrest-all-eq[OF circus-alpha-bij-lens] unrest-plus-split plus-vwb-lens*)
(simp add: unrest usubst closure)

lemma *unrest-all-circus-vars-st-st'*:
fixes $P :: ('s, 'e) \text{ action}$
assumes $\$ok \# P \ \$ok \# P \ \$wait \# P \ \$wait \# P \ \$ref \# P \ \$ref \# P \ \Sigma \# s \ \Sigma \# s' \ \Sigma \# t \ \Sigma \# t'$
shows $\Sigma \# [\$st \mapsto_s s, \$st \mapsto_s s', \$tr \mapsto_s t, \$tr \mapsto_s t'] \vdash P$

```

using assms
by (simp add: bij-lens-unrest-all-eq[OF circus-alpha-bij-lens] unrest-plus-split plus-vwb-lens)
    (simp add: unrest usubst closure)

lemma unrest-all-circus-vars-st:
  fixes  $P :: ('s, 'e) \text{ action}$ 
  assumes  $\$ok \# P \ \$ok \# P \ \$wait \# P \ \$wait \# P \ \$ref \# P \ \$ref \# P \ \$st \# P \ \Sigma \# s \ \Sigma \# t \ \Sigma \# t'$ 
  shows  $\Sigma \# [\$st \mapsto_s s, \$tr \mapsto_s t, \$tr' \mapsto_s t'] \uparrow P$ 
  using assms
  by (simp add: bij-lens-unrest-all-eq[OF circus-alpha-bij-lens] unrest-plus-split plus-vwb-lens)
      (simp add: unrest usubst closure)

lemma unrest-any-circus-var:
  fixes  $P :: ('s, 'e) \text{ action}$ 
  assumes  $\$ok \# P \ \$ok \# P \ \$wait \# P \ \$wait \# P \ \$ref \# P \ \$ref \# P \ \Sigma \# s \ \Sigma \# s' \ \Sigma \# t \ \Sigma \# t'$ 
  shows  $x \# [\$st \mapsto_s s, \$st' \mapsto_s s', \$tr \mapsto_s t, \$tr' \mapsto_s t'] \uparrow P$ 
  by (simp add: unrest-all-var unrest-all-circus-vars-st-st' assms)

lemma unrest-any-circus-var-st:
  fixes  $P :: ('s, 'e) \text{ action}$ 
  assumes  $\$ok \# P \ \$ok \# P \ \$wait \# P \ \$wait \# P \ \$ref \# P \ \$ref \# P \ \$st \# P \ \Sigma \# s \ \Sigma \# t \ \Sigma \# t'$ 
  shows  $x \# [\$st \mapsto_s s, \$tr \mapsto_s t, \$tr' \mapsto_s t'] \uparrow P$ 
  by (simp add: unrest-all-var unrest-all-circus-vars-st assms)

end

```

3 Stateful-Failure Reactive Relations

```

theory utp-sfrd-rel
  imports utp-sfrd-core
begin

```

3.1 Healthiness Conditions

CSP Reactive Relations

definition $CRR :: ('s, 'e) \text{ action} \Rightarrow ('s, 'e) \text{ action}$ **where**
 $[upred-defs]: CRR(P) = (\exists \$ref \cdot RR(P))$

lemma *CRR-idem*: $CRR(CRR(P)) = CRR(P)$
by (*rel-auto*)

lemma *Idempotent-CRR* [*closure*]: *Idempotent CRR*
by (*simp add: CRR-idem Idempotent-def*)

lemma *Continuous-CRR* [*closure*]: *Continuous CRR*
by (*rel-blast*)

lemma *CRR-intro*:
assumes $\$ref \# P \ P \text{ is } RR$
shows $P \text{ is } CRR$
by (*simp add: CRR-def Healthy-def, simp add: Healthy-if assms ex-unrest*)

lemma *CRR-form*: $CRR(P) = (\exists \{\$ok, \$ok, \$wait, \$wait, \$ref\} \cdot (\exists tt_0 \cdot P[\llbracket \square \rrbracket / \$tr] \llbracket \llbracket tt_0 \rrbracket / \$tr' \rrbracket \wedge \$tr =_u \$tr \hat{=} \llbracket tt_0 \rrbracket))$

by (*rel-auto*; *fastforce*)

lemma *CRR-seqr-form*:

$CRR(P) ;; CRR(Q) =$
 $(\exists tt_1 \cdot \exists tt_2 \cdot ((\exists \{ \$ok, \$ok, \$wait, \$wait, \$ref \} \cdot P) \llbracket \langle \rangle \rrbracket / \$tr \llbracket \langle tt_1 \rangle \rrbracket / \$tr ;;$
 $(\exists \{ \$ok, \$ok, \$wait, \$wait, \$ref \} \cdot Q) \llbracket \langle \rangle \rrbracket / \$tr \llbracket \langle tt_2 \rangle \rrbracket / \$tr \wedge \$tr =_u \$tr \hat{ }_u \langle tt_1 \rangle \hat{ }_u$
 $\langle tt_2 \rangle))$
by (*simp add: CRR-form, rel-auto; fastforce*)

CSP Reactive Finalisers

definition *CRF* :: (*'s, 'e*) *action* \Rightarrow (*'s, 'e*) *action* **where**
 $[upred-defs]: CRF(P) = (\exists \$ref \cdot CRR(P))$

lemma *CRF-idem*: $CRF(CRF(P)) = CRF(P)$
by (*rel-auto*)

lemma *Idempotent-CRF* [*closure*]: *Idempotent CRF*
by (*simp add: CRF-idem Idempotent-def*)

lemma *Continuous-CRF* [*closure*]: *Continuous CRF*
by (*rel-blast*)

lemma *CRF-intro*:
assumes $\$ref \# P \ \$ref \# P$ *P is RR*
shows *P is CRF*
by (*simp add: CRF-def CRR-def Healthy-def, simp add: Healthy-if assms ex-unrest*)

lemma *CRF-implies-CRR* [*closure*]:
assumes *P is CRF* **shows** *P is CRR*

proof –
have $CRR(CRF(P)) = CRF(P)$
by (*rel-auto*)
thus *?thesis*
by (*metis Healthy-def assms*)

qed

definition *crel-skip* :: (*'s, 'e*) *action* (II_c) **where**
 $[upred-defs]: crel-skip = (\$tr =_u \$tr \wedge \$st =_u \$st)$

lemma *crel-skip-CRR* [*closure*]: II_c *is CRF*
by (*rel-auto*)

lemma *crel-skip-via-rrel*: $II_c = CRR(II_r)$
by (*rel-auto*)

lemma *crel-skip-left-unit* [*rpred*]:
assumes *P is CRR*
shows $II_c ;; P = P$

proof –
have $II_c ;; CRR(P) = CRR(P)$ **by** (*rel-auto*)
thus *?thesis* **by** (*simp add: Healthy-if assms*)
qed

lemma *crel-skip-right-unit* [*rpred*]:
assumes *P is CRF*

shows $P \;; \; II_c = P$
proof –
have $CRF(P) \;; \; II_c = CRF(P)$ **by** (*rel-auto*)
thus *?thesis* **by** (*simp add: Healthy-if assms*)
qed

CSP Reactive Conditions

definition $CRC \:: \; ('s, 'e) \text{ action} \Rightarrow ('s, 'e) \text{ action}$ **where**
 $[upred-defs]: CRC(P) = (\exists \ \$ref \cdot RC(P))$

lemma *CRC-intro*:
assumes $\$ref \# P$ P *is RC*
shows P *is CRC*
by (*simp add: CRC-def Healthy-def, simp add: Healthy-if assms ex-unrest*)

lemma *CRC-intro'*:
assumes P *is CRR* P *is RC*
shows P *is CRC*
by (*metis CRC-def CRR-def Healthy-def RC-implies-RR assms*)

lemma *ref-unrest-RR* [*unrest*]: $\$ref \# P \Longrightarrow \$ref \# RR \ P$
by (*rel-auto, blast+*)

lemma *ref-unrest-RC1* [*unrest*]: $\$ref \# P \Longrightarrow \$ref \# RC1 \ P$
by (*rel-auto, blast+*)

lemma *ref-unrest-RC* [*unrest*]: $\$ref \# P \Longrightarrow \$ref \# RC \ P$
by (*simp add: RC-R2-def ref-unrest-RC1 ref-unrest-RR*)

lemma *RR-ex-ref*: $RR \ (\exists \ \$ref \cdot RR \ P) = (\exists \ \$ref \cdot RR \ P)$
by (*rel-auto*)

lemma *RC1-ex-ref*: $RC1 \ (\exists \ \$ref \cdot RC1 \ P) = (\exists \ \$ref \cdot RC1 \ P)$
by (*rel-auto, meson dual-order.trans*)

lemma *ex-ref'-RR-closed* [*closure*]:
assumes P *is RR*
shows $(\exists \ \$ref \cdot P)$ *is RR*

proof –
have $RR \ (\exists \ \$ref \cdot RR(P)) = (\exists \ \$ref \cdot RR(P))$
by (*rel-auto*)
thus *?thesis*
by (*metis Healthy-def assms*)
qed

lemma *CRC-idem*: $CRC(CRC(P)) = CRC(P)$
apply (*simp add: CRC-def ex-unrest unrest*)
apply (*simp add: RC-def RR-ex-ref*)
apply (*metis (no-types, hide-lams) Healthy-def RC1-RR-closed RC1-ex-ref RR-ex-ref RR-idem*)
done

lemma *Idempotent-CRC* [*closure*]: *Idempotent CRC*
by (*simp add: CRC-idem Idempotent-def*)

3.2 Closure Properties

lemma *CRR-implies-RR* [closure]:

assumes *P* is CRR

shows *P* is RR

proof –

have $RR(CRR(P)) = CRR(P)$

by (rel-auto)

thus ?thesis

by (metis Healthy-def' assms)

qed

lemma *CRC-intro''*:

assumes *P* is CRR *P* is RC1

shows *P* is CRC

by (simp add: CRC-intro' CRR-implies-RR RC-intro' assms)

lemma *CRC-implies-RR* [closure]:

assumes *P* is CRC

shows *P* is RR

proof –

have $RR(CRC(P)) = CRC(P)$

by (rel-auto)

(metis (no-types, lifting) Prefix-Order.prefixE Prefix-Order.prefixI append.assoc append-minus)+

thus ?thesis

by (metis Healthy-def assms)

qed

lemma *CRC-implies-RC* [closure]:

assumes *P* is CRC

shows *P* is RC

proof –

have $RC1(CRC(P)) = CRC(P)$

by (rel-auto, meson dual-order.trans)

thus ?thesis

by (simp add: CRC-implies-RR Healthy-if RC1-def RC-intro assms)

qed

lemma *CRR-unrest-ref* [unrest]: P is CRR $\implies \$ref \# P$

by (metis CRR-def CRR-implies-RR Healthy-def in-var-uvar ref-vwb-lens unrest-as-exists)

lemma *CRF-unrest-ref'* [unrest]:

assumes *P* is CRF

shows $\$ref \# P$

proof –

have $\$ref \# CRF(P)$ by (simp add: CRF-def unrest)

thus ?thesis by (simp add: assms Healthy-if)

qed

lemma *CRC-implies-CRR* [closure]:

assumes *P* is CRC

shows *P* is CRR

apply (rule CRR-intro)

apply (simp-all add: unrest assms closure)

apply (metis CRC-def CRC-implies-RC Healthy-def assms in-var-uvar ref-vwb-lens unrest-as-exists)

done

lemma *unrest-ref'-neg-RC* [*unrest*]:
 assumes *P is RR P is RC*
 shows $\$ref \# P$
proof –
 have $P = (\neg_r \neg_r P)$
 by (*simp add: closure rpred assms*)
 also have $\dots = (\neg_r (\neg_r P) ;; true_r)$
 by (*metis Healthy-if RC1-def RC-implies-RC1 assms(2) calculation*)
 also have $\$ref \# \dots$
 by (*rel-auto*)
 finally show *?thesis* .
qed

lemma *rea-true-CRR* [*closure*]: *true_r is CRR*
 by (*rel-auto*)

lemma *rea-true-CRC* [*closure*]: *true_r is CRC*
 by (*rel-auto*)

lemma *false-CRR* [*closure*]: *false is CRR*
 by (*rel-auto*)

lemma *false-CRC* [*closure*]: *false is CRC*
 by (*rel-auto*)

lemma *st-pred-CRR* [*closure*]: *[P]_{S<} is CRR*
 by (*rel-auto*)

lemma *st-post-unrest-ref'* [*unrest*]: $\$ref \# [b]_{S>}$
 by (*rel-auto*)

lemma *st-post-CRR* [*closure*]: *[b]_{S>} is CRR*
 by (*rel-auto*)

lemma *st-cond-CRC* [*closure*]: *[P]_{S<} is CRC*
 by (*rel-auto*)

lemma *st-cond-CRF* [*closure*]: *[b]_{S<} is CRF*
 by (*rel-auto*)

lemma *rea-rename-CRR-closed* [*closure*]:
 assumes *P is CRR*
 shows $P(\lfloor f \rfloor_r)$ *is CRR*
proof –
 have $\$ref \# (CRR P)(\lfloor f \rfloor_r)$
 by (*rel-auto*)
 thus *?thesis*
 by (*rule-tac CRR-intro, simp-all add: closure Healthy-if assms*)
qed

lemma *st-subst-CRR-closed* [*closure*]:
 assumes *P is CRR*
 shows $(\sigma \upharpoonright_S P)$ *is CRR*
 by (*rule CRR-intro, simp-all add: unrest closure assms*)

lemma *st-subst-CRC-closed* [closure]:

assumes P is CRC

shows $(\sigma \uparrow_S P)$ is CRC

by (rule CRC-intro, simp-all add: closure assms unrest)

lemma *conj-CRC-closed* [closure]:

$\llbracket P \text{ is CRC}; Q \text{ is CRC} \rrbracket \implies (P \wedge Q) \text{ is CRC}$

by (rule CRC-intro, simp-all add: unrest closure)

lemma *conj-CRF-closed* [closure]: $\llbracket P \text{ is CRF}; Q \text{ is CRF} \rrbracket \implies (P \wedge Q) \text{ is CRF}$

by (rule CRF-intro, simp-all add: unrest closure)

lemma *disj-CRC-closed* [closure]:

$\llbracket P \text{ is CRC}; Q \text{ is CRC} \rrbracket \implies (P \vee Q) \text{ is CRC}$

by (rule CRC-intro, simp-all add: unrest closure)

lemma *st-cond-left-impl-CRC-closed* [closure]:

$P \text{ is CRC} \implies ([b]_{S<} \Rightarrow_r P) \text{ is CRC}$

by (rule CRC-intro, simp-all add: unrest closure)

lemma *unrest-ref-map-st* [unrest]: $\$ref \# P \implies \$ref \# P \oplus_r \text{map-st}_L[a]$

by (rel-auto)

lemma *unrest-ref'-map-st* [unrest]: $\$ref \# P \implies \$ref \# P \oplus_r \text{map-st}_L[a]$

by (rel-auto)

lemma *unrest-ref-rdes-frame-ext* [unrest]:

$\$ref \# P \implies \$ref \# a:[P]_r^+$

by (rel-blast)

lemma *unrest-ref'-rdes-frame-ext* [unrest]:

$\$ref \# P \implies \$ref \# a:[P]_r^+$

by (rel-blast)

lemma *map-st-ext-CRR-closed* [closure]:

assumes P is CRR

shows $P \oplus_r \text{map-st}_L[a]$ is CRR

by (rule CRR-intro, simp-all add: closure unrest assms)

lemma *map-st-ext-CRC-closed* [closure]:

assumes P is CRC

shows $P \oplus_r \text{map-st}_L[a]$ is CRC

by (rule CRC-intro, simp-all add: closure unrest assms)

lemma *rdes-frame-ext-CRR-closed* [closure]:

assumes P is CRR

shows $a:[P]_r^+$ is CRR

by (rule CRR-intro, simp-all add: closure unrest assms)

lemma *USUP-CRC-closed* [closure]: $\llbracket A \neq \{\}; \bigwedge i. i \in A \implies P \ i \text{ is CRC} \rrbracket \implies (\bigsqcup i \in A \cdot P \ i) \text{ is CRC}$

by (rule CRC-intro, simp-all add: unrest closure)

lemma *UINF-CRR-closed* [closure]: $\llbracket \bigwedge i. i \in A \implies P \ i \text{ is CRR} \rrbracket \implies (\bigsqcap i \in A \cdot P \ i) \text{ is CRR}$

by (rule CRR-intro, simp-all add: unrest closure)

lemma *cond-CRC-closed* [closure]:
 assumes P is CRC Q is CRC
 shows $P \triangleleft b \triangleright_R Q$ is CRC
 by (rule CRC-intro, simp-all add: closure assms unrest)

lemma *shEx-CRR-closed* [closure]:
 assumes $\bigwedge x. P\ x$ is CRR
 shows $(\exists x. P(x))$ is CRR
proof –
 have $CRR(\exists x. CRR(P(x))) = (\exists x. CRR(P(x)))$
 by (rel-auto)
 thus ?thesis
 by (metis Healthy-def assms shEx-cong)
qed

lemma *USUP-ind-CRR-closed* [closure]:
 assumes $\bigwedge i. P\ i$ is CRR
 shows $(\bigsqcup i. P(i))$ is CRR
 by (rule CRR-intro, simp-all add: assms unrest closure)

lemma *UINF-ind-CRR-closed* [closure]:
 assumes $\bigwedge i. P\ i$ is CRR
 shows $(\bigcap i. P(i))$ is CRR
 by (rule CRR-intro, simp-all add: assms unrest closure)

lemma *cond-tt-CRR-closed* [closure]:
 assumes P is CRR Q is CRR
 shows $P \triangleleft \$tr =_u \$tr \triangleright Q$ is CRR
 by (rule CRR-intro, simp-all add: unrest assms closure)

lemma *rea-implies-CRR-closed* [closure]:
 $\llbracket P \text{ is CRR}; Q \text{ is CRR} \rrbracket \implies (P \Rightarrow_r Q) \text{ is CRR}$
 by (simp-all add: CRR-intro closure unrest)

lemma *conj-CRR-closed* [closure]:
 $\llbracket P \text{ is CRR}; Q \text{ is CRR} \rrbracket \implies (P \wedge Q) \text{ is CRR}$
 by (simp-all add: CRR-intro closure unrest)

lemma *disj-CRR-closed* [closure]:
 $\llbracket P \text{ is CRR}; Q \text{ is CRR} \rrbracket \implies (P \vee Q) \text{ is CRR}$
 by (rule CRR-intro, simp-all add: unrest closure)

lemma *rea-not-CRR-closed* [closure]:
 $P \text{ is CRR} \implies (\neg_r P) \text{ is CRR}$
 using false-CRR rea-implies-CRR-closed **by** fastforce

lemma *cond-st-CRR-closed* [closure]:
 $\llbracket P \text{ is CRR}; Q \text{ is CRR} \rrbracket \implies (P \triangleleft b \triangleright_R Q) \text{ is CRR}$
 by (simp-all add: CRR-intro closure unrest)

lemma *seq-CRR-closed* [closure]:
 assumes P is CRR Q is RR
 shows $(P ;; Q) \text{ is CRR}$

by (rule CRR-intro, simp-all add: unrest assms closure)

lemma seq-CRF-closed [closure]:
 assumes P is CRF Q is CRF
 shows $(P ;; Q)$ is CRF
 by (rule CRF-intro, simp-all add: unrest assms closure)

lemma rea-st-cond-CRF [closure]: $[b]_{S<} is CRF$
 by (rel-auto)

lemma conj-CRF [closure]: $\llbracket P is CRF; Q is CRF \rrbracket \implies (P \wedge Q) is CRF$
 by (simp add: CRF-implies-CRR CRF-intro CRF-unrest-ref' CRR-implies-RR CRR-unrest-ref conj-RR unrest-conj)

lemma wp-rea-CRC [closure]: $\llbracket P is CRR; Q is RC \rrbracket \implies P wp_r Q is CRC$
 by (rule CRC-intro, simp-all add: unrest closure)

lemma USUP-ind-CRC-closed [closure]:
 $\llbracket \bigwedge i. P i is CRC \rrbracket \implies (\bigcup i. P i) is CRC$
 by (metis CRC-implies-CRR CRC-implies-RC USUP-ind-CRR-closed USUP-ind-RC-closed false-CRC rea-not-CRR-closed wp-rea-CRC wp-rea-RC-false)

lemma tr-extend-seqr-lit [rdes]:
 fixes $P :: ('s, 'e) action$
 assumes $\$ok \# P \$wait \# P \$ref \# P$
 shows $U(\$tr = \$tr @ \llbracket a \rrbracket) \wedge \$st = \$st) ;; P = P \llbracket U(\$tr @ \llbracket a \rrbracket) / \$tr \rrbracket$
 using assms by (rel-auto, meson)

lemma tr-assign-comp [rdes]:
 fixes $P :: ('s, 'e) action$
 assumes $\$ok \# P \$wait \# P \$ref \# P$
 shows $(\$tr =_u \$tr \wedge \lceil \langle \sigma \rangle_a \rceil_S) ;; P = \lceil \sigma \rceil_{S\sigma} \dagger P$
 using assms by (rel-auto, meson)

lemma RR-msubst-tt: $RR((P t) \llbracket t \rightarrow \&tt \rrbracket) = (RR (P t)) \llbracket t \rightarrow \&tt \rrbracket$
 by (rel-auto)

lemma RR-msubst-ref': $RR((P r) \llbracket r \rightarrow \$ref \rrbracket) = (RR (P r)) \llbracket r \rightarrow \$ref \rrbracket$
 by (rel-auto)

lemma msubst-tt-RR [closure]: $\llbracket \bigwedge t. P t is RR \rrbracket \implies (P t) \llbracket t \rightarrow \&tt \rrbracket is RR$
 by (simp add: Healthy-def RR-msubst-tt)

lemma msubst-ref'-RR [closure]: $\llbracket \bigwedge r. P r is RR \rrbracket \implies (P r) \llbracket r \rightarrow \$ref \rrbracket is RR$
 by (simp add: Healthy-def RR-msubst-ref')

lemma conj-less-tr-RR-closed [closure]:
 assumes $P is CRR$
 shows $(P \wedge \$tr <_u \$tr) is CRR$
proof –
 have $CRR(CRR(P) \wedge \$tr <_u \$tr) = (CRR(P) \wedge \$tr <_u \$tr)$
 apply (rel-auto, blast+)
 using less-le apply fastforce+
 done
 thus ?thesis

by (*metis Healthy-def assms*)
qed

lemma *R4-CRR-closed* [closure]: P is CRR $\implies R_4(P)$ is CRR
by (*simp add: R4-def conj-less-tr-RR-closed*)

lemma *R5-CRR-closed* [closure]:

assumes P is CRR
shows $R_5(P)$ is CRR

proof –

have $R_5(CRR(P))$ is CRR
by (*rel-auto; blast*)
thus ?thesis
by (*simp add: assms Healthy-if*)

qed

lemma *conj-eq-tr-RR-closed* [closure]:

assumes P is CRR
shows $(P \wedge \$tr =_u \$tr)$ is CRR

proof –

have $CRR(CRR(P) \wedge \$tr =_u \$tr) = (CRR(P) \wedge \$tr =_u \$tr)$
by (*rel-auto, blast+*)
thus ?thesis
by (*metis Healthy-def assms*)

qed

lemma *all-ref-CRC-closed* [closure]:

P is CRC $\implies (\forall \$ref \cdot P)$ is CRC
by (*simp add: CRC-implies-CRR CRR-unrest-ref all-unrest*)

lemma *ex-ref-CRR-closed* [closure]:

P is CRR $\implies (\exists \$ref \cdot P)$ is CRR
by (*simp add: CRR-unrest-ref ex-unrest*)

lemma *ex-st'-CRR-closed* [closure]:

P is CRR $\implies (\exists \$st \cdot P)$ is CRR
by (*rule CRR-intro, simp-all add: closure unrest*)

lemma *ex-ref'-CRR-closed* [closure]:

P is CRR $\implies (\exists \$ref \cdot P)$ is CRR
using *CRR-implies-RR CRR-intro CRR-unrest-ref ex-ref'-RR-closed out-in-indep unrest-ex-diff* by
blast

3.3 Introduction laws

Extensionality principles for introducing refinement and equality of Circus reactive relations. It is necessary only to consider a subset of the variables that are present.

lemma *CRR-refine-ext*:

assumes

P is CRR Q is CRR

$\bigwedge t s s' r'. P[\llbracket \langle \rangle, \langle t \rangle, \langle s \rangle, \langle s' \rangle, \langle r' \rangle / \$tr, \$tr, \$st, \$st, \$ref \rrbracket] \sqsubseteq Q[\llbracket \langle \rangle, \langle t \rangle, \langle s \rangle, \langle s' \rangle, \langle r' \rangle / \$tr, \$tr, \$st, \$st, \$ref \rrbracket]$

shows $P \sqsubseteq Q$

proof –

have $\bigwedge t s s' r'. (CRR P)[\llbracket \langle \rangle, \langle t \rangle, \langle s \rangle, \langle s' \rangle, \langle r' \rangle / \$tr, \$tr, \$st, \$st, \$ref \rrbracket]$
 $\sqsubseteq (CRR Q)[\llbracket \langle \rangle, \langle t \rangle, \langle s \rangle, \langle s' \rangle, \langle r' \rangle / \$tr, \$tr, \$st, \$st, \$ref \rrbracket]$

using *assms* by (*simp add: Healthy-if*)
 hence $CRR\ P \sqsubseteq CRR\ Q$
 by (*rel-auto*)
 thus ?thesis
 by (*metis Healthy-if assms(1) assms(2)*)
 qed

lemma *CRR-eq-ext*:

assumes

P is *CRR* Q is *CRR*

$\bigwedge t\ s\ s'\ r'. P[\llbracket \langle \rangle, \langle t \rangle, \langle s \rangle, \langle s' \rangle, \langle r' \rangle \rrbracket / \$tr, \$tr, \$st, \$st, \$ref] = Q[\llbracket \langle \rangle, \langle t \rangle, \langle s \rangle, \langle s' \rangle, \langle r' \rangle \rrbracket / \$tr, \$tr, \$st, \$st, \$ref]$

shows $P = Q$

proof –

have $\bigwedge t\ s\ s'\ r'. (CRR\ P)[\llbracket \langle \rangle, \langle t \rangle, \langle s \rangle, \langle s' \rangle, \langle r' \rangle \rrbracket / \$tr, \$tr, \$st, \$st, \$ref]$
 $= (CRR\ Q)[\llbracket \langle \rangle, \langle t \rangle, \langle s \rangle, \langle s' \rangle, \langle r' \rangle \rrbracket / \$tr, \$tr, \$st, \$st, \$ref]$

using *assms* by (*simp add: Healthy-if*)

hence $CRR\ P = CRR\ Q$

by (*rel-auto*)

thus ?thesis

by (*metis Healthy-if assms(1) assms(2)*)

qed

lemma *CRR-refine-impl-prop*:

assumes P is *CRR* Q is *CRR*

$\bigwedge t\ s\ s'\ r'. 'Q[\llbracket \langle r' \rangle, \langle s \rangle, \langle s' \rangle, \langle \rangle, \langle t \rangle \rrbracket / \$ref, \$st, \$st, \$tr, \$tr]' \implies 'P[\llbracket \langle r' \rangle, \langle s \rangle, \langle s' \rangle, \langle \rangle, \langle t \rangle \rrbracket / \$ref, \$st, \$st, \$tr, \$tr]'$

shows $P \sqsubseteq Q$

by (*rule CRR-refine-ext, simp-all add: assms closure unrest usubst*)

(*rule refine-prop-intro, simp-all add: unrest unrest-all-circus-vars closure assms*)

3.4 UTP Theory

interpretation *crf-theory*: *utp-theory-kleene CRF* II_c

rewrites $P \in \text{carrier } \text{crf-theory.thy-order} \longleftrightarrow P \text{ is CRF}$

and $\text{le } \text{rrel-theory.thy-order} = (\sqsubseteq)$

and $\text{eq } \text{rrel-theory.thy-order} = (=)$

and *crf-top*: *crf-theory.utp-top* = *false*

and *crf-bottom*: *crf-theory.utp-bottom* = *true_r*

proof –

interpret *utp-theory-continuous CRF*

by (*unfold-locales, simp-all add: add: CRF-idem Continuous-CRF*)

show *top:utp-top* = *false*

by (*simp add: healthy-top, rel-auto*)

show *bot:utp-bottom* = *true_r*

by (*simp add: healthy-bottom, rel-auto*)

show *utp-theory-kleene CRF* II_c

by (*unfold-locales, simp-all add: closure rpred top*)

qed (*simp-all*)

abbreviation *crf-star* :: $- \Rightarrow -$ ($-^{*c}$ [999] 999) **where**

$P^{*c} \equiv \text{crf-theory.utp-star } P$

lemma *crf-star-as-rea-star*:

$P \text{ is CRF} \implies P^{*c} = P^{*r} \;;\; II_c$

by (*simp add: crf-theory.Star-alt-def rrel-theory.Star-alt-def closure rpred unrest*)

lemma *crf-star-inductl*: $R \text{ is CRR} \implies Q \sqsubseteq (P \;;\; Q) \sqcap R \implies Q \sqsubseteq P^{*c} \;;\; R$

by (simp add: crel-skip-left-unit crf-theory.utp-star-def upred-semiring.mult-assoc urel-ka.star-inductl)

3.5 Weakest Precondition

lemma *nil-least* [simp]:

$\llbracket \square \rrbracket \leq_u x = \text{true}$ **by** *rel-auto*

lemma *minus-nil* [simp]:

$xs - \llbracket \square \rrbracket = xs$ **by** *rel-auto*

lemma *wp-rea-circus-lemma-1*:

assumes P is CRR $\$ref \# P$

shows $out\alpha \# P \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket$

proof –

have $out\alpha \# (CRR (\exists \$ref \cdot P)) \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket$

by (*rel-auto*)

thus *?thesis*

by (simp add: Healthy-if assms(1) assms(2) ex-unrest)

qed

lemma *wp-rea-circus-lemma-2*:

assumes P is CRR

shows $in\alpha \# P \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket$

proof –

have $in\alpha \# (CRR P) \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket$

by (*rel-auto*)

thus *?thesis*

by (simp add: Healthy-if assms ex-unrest)

qed

The meaning of reactive weakest precondition for Circus. $P \text{ wp}_r Q$ means that, whenever P terminates in a state s_0 having done the interaction trace t_0 , which is a prefix of the overall trace, then Q must be satisfied. This in particular means that the remainder of the trace after t_0 must not be a divergent behaviour of Q .

lemma *wp-rea-circus-form*:

assumes P is CRR $\$ref \# P$ Q is CRC

shows $(P \text{ wp}_r Q) = (\forall (s_0, t_0) \cdot \langle t_0 \rangle \leq_u \$tr \wedge P \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \Rightarrow_r Q \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket)$

proof –

have $(P \text{ wp}_r Q) = (\neg_r (\exists t_0 \cdot P \llbracket \langle t_0 \rangle / \$tr \rrbracket \;; (\neg_r Q) \llbracket \langle t_0 \rangle / \$tr \rrbracket \wedge \langle t_0 \rangle \leq_u \$tr))$

by (simp-all add: wp-rea-def R2-tr-middle closure assms)

also have $\dots = (\neg_r (\exists (s_0, t_0) \cdot P \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \;; (\neg_r Q) \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \wedge \langle t_0 \rangle \leq_u \$tr))$

by (*rel-blast*)

also have $\dots = (\neg_r (\exists (s_0, t_0) \cdot P \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \wedge (\neg_r Q) \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \wedge \langle t_0 \rangle \leq_u \$tr))$

by (simp add: segr-to-conj add: wp-rea-circus-lemma-1 wp-rea-circus-lemma-2 assms closure conj-assoc)

also have $\dots = (\forall (s_0, t_0) \cdot \neg_r P \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \vee \neg_r (\neg_r Q) \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \vee \neg_r \langle t_0 \rangle \leq_u \$tr)$

by (*rel-auto*)

also have $\dots = (\forall (s_0, t_0) \cdot \neg_r P \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \vee \neg_r (\neg_r RR Q) \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \vee \neg_r \langle t_0 \rangle \leq_u \$tr)$

by (simp add: Healthy-if assms closure)

also have $\dots = (\forall (s_0, t_0) \cdot \neg_r P \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \vee (RR Q) \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \vee \neg_r \langle t_0 \rangle \leq_u \$tr)$

by (*rel-auto*)

also have $\dots = (\forall (s_0, t_0) \cdot \langle t_0 \rangle \leq_u \$tr \wedge P \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \Rightarrow_r (RR Q) \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket)$

by (*rel-auto*)

also have $\dots = (\forall (s_0, t_0) \cdot \langle t_0 \rangle \leq_u \$tr \wedge P \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket \Rightarrow_r Q \llbracket \langle s_0 \rangle, \langle t_0 \rangle / \$st, \$tr \rrbracket)$

by (simp add: Healthy-if assms closure)
 finally show ?thesis .
 qed

lemma wp-rea-circus-form-alt:

assumes P is CRR $\$ref \# P$ Q is CRC
 shows $(P \text{ wp}_r Q) = (\forall (s_0, t_0) \cdot \$tr \hat{=}_u \langle t_0 \rangle \leq_u \$tr \wedge P[\langle s_0 \rangle, \langle \square \rangle, \langle t_0 \rangle / \$st, \$tr, \$tr])$
 $\Rightarrow_r R1(Q[\langle s_0 \rangle, \langle \square \rangle, (\&tt - \langle t_0 \rangle) / \$st, \$tr, \$tr])$

proof –

have $(P \text{ wp}_r Q) = R2(P \text{ wp}_r Q)$
 by (simp add: CRC-implies-RR CRR-implies-RR Healthy-if RR-implies-R2 assms wp-rea-R2-closed)
 also have $\dots = R2(\forall (s_0, tr_0) \cdot \langle tr_0 \rangle \leq_u \$tr \wedge (RR P)[\langle s_0 \rangle, \langle tr_0 \rangle / \$st, \$tr] \Rightarrow_r (RR Q)[\langle s_0 \rangle, \langle tr_0 \rangle / \$st, \$tr])$
 by (simp add: wp-rea-circus-form assms closure Healthy-if)
 also have $\dots = (\exists tt_0 \cdot (\forall (s_0, tr_0) \cdot \langle tr_0 \rangle \leq_u \langle tt_0 \rangle \wedge (RR P)[\langle s_0 \rangle, \langle \square \rangle, \langle tr_0 \rangle / \$st, \$tr, \$tr])$
 $\Rightarrow_r (RR Q)[\langle s_0 \rangle, \langle tr_0 \rangle, \langle tt_0 \rangle / \$st, \$tr, \$tr])$
 $\wedge \$tr =_u \$tr \hat{=}_u \langle tt_0 \rangle)$
 by (simp add: R2-form, rel-auto)
 also have $\dots = (\exists tt_0 \cdot (\forall (s_0, tr_0) \cdot \langle tr_0 \rangle \leq_u \langle tt_0 \rangle \wedge (RR P)[\langle s_0 \rangle, \langle \square \rangle, \langle tr_0 \rangle / \$st, \$tr, \$tr])$
 $\Rightarrow_r (RR Q)[\langle s_0 \rangle, \langle \square \rangle, \langle tt_0 - tr_0 \rangle / \$st, \$tr, \$tr])$
 $\wedge \$tr =_u \$tr \hat{=}_u \langle tt_0 \rangle)$
 by (rel-auto)
 also have $\dots = (\exists tt_0 \cdot (\forall (s_0, tr_0) \cdot \$tr \hat{=}_u \langle tr_0 \rangle \leq_u \$tr \wedge (RR P)[\langle s_0 \rangle, \langle \square \rangle, \langle tr_0 \rangle / \$st, \$tr, \$tr])$
 $\Rightarrow_r (RR Q)[\langle s_0 \rangle, \langle \square \rangle, (\&tt - \langle tr_0 \rangle) / \$st, \$tr, \$tr])$
 $\wedge \$tr =_u \$tr \hat{=}_u \langle tt_0 \rangle)$
 by (rel-auto, (metis list-concat-minus-list-concat)+)
 also have $\dots = (\forall (s_0, tr_0) \cdot \$tr \hat{=}_u \langle tr_0 \rangle \leq_u \$tr \wedge (RR P)[\langle s_0 \rangle, \langle \square \rangle, \langle tr_0 \rangle / \$st, \$tr, \$tr])$
 $\Rightarrow_r R1((RR Q)[\langle s_0 \rangle, \langle \square \rangle, (\&tt - \langle tr_0 \rangle) / \$st, \$tr, \$tr])$
 by (rel-auto, blast+)
 also have $\dots = (\forall (s_0, t_0) \cdot \$tr \hat{=}_u \langle t_0 \rangle \leq_u \$tr \wedge P[\langle s_0 \rangle, \langle \square \rangle, \langle t_0 \rangle / \$st, \$tr, \$tr])$
 $\Rightarrow_r R1(Q[\langle s_0 \rangle, \langle \square \rangle, (\&tt - \langle t_0 \rangle) / \$st, \$tr, \$tr])$
 by (simp add: Healthy-if assms closure)
 finally show ?thesis .
 qed

lemma wp-rea-circus-form-alt:

assumes P is CRR $\$ref \# P$ Q is CRC
 shows $(P \text{ wp}_r Q) = (\forall (s_0, t_0) \cdot \$tr \hat{=}_u \langle t_0 \rangle \leq_u \$tr \wedge P[\langle s_0 \rangle, \langle \square \rangle, \langle t_0 \rangle / \$st, \$tr, \$tr])$
 $\Rightarrow_r R1(Q[\langle s_0 \rangle, \langle \square \rangle, (\&tt - \langle t_0 \rangle) / \$st, \$tr, \$tr])$
 oops

3.6 Trace Substitution

definition trace-subst $(\llbracket - \rrbracket_t [999, 0] 999)$

where $[upred-defs]: P[\llbracket v \rrbracket_t] = (P[(\&tt - \lceil v \rceil_{S<}) / \&tt] \wedge \$tr + \lceil v \rceil_{S<} \leq_u \$tr)$

lemma unrest-trace-subst $[unrest]$:

$\llbracket mwb-lens x; x \bowtie (\$tr)_v; x \bowtie (\$tr)_v; x \bowtie (\$st)_v; x \# P \rrbracket \Longrightarrow x \# P[\llbracket v \rrbracket_t]$
 by (simp add: trace-subst-def lens-indep-sym unrest)

lemma trace-subst-RR-closed $[closure]$:

assumes P is RR
 shows $P[\llbracket v \rrbracket_t]$ is RR

proof –

have $(RR P)[\llbracket v \rrbracket_t]$ is RR
 apply (rel-auto)
 apply (metis diff-add-cancel-left' trace-class.add-left-mono)

apply (*metis le-add minus-cancel-le trace-class.add-diff-cancel-left*)
using *le-add order-trans* **apply** *blast*
done
thus *?thesis*
by (*simp add: Healthy-if assms*)
qed

lemma *trace-subst-CRR-closed* [*closure*]:
assumes *P is CRR*
shows $P\llbracket v \rrbracket_t$ *is CRR*
by (*rule CRR-intro, simp-all add: closure assms unrest*)

lemma *tsubst-nil* [*usubst*]:
assumes *P is CRR*
shows $P\llbracket \llbracket \cdot \rrbracket \rrbracket_t = P$
proof –
have (*CRR P*) $\llbracket \llbracket \cdot \rrbracket \rrbracket_t = \text{CRR } P$
by (*rel-auto*)
thus *?thesis*
by (*simp add: Healthy-if assms*)
qed

lemma *tsubst-false* [*usubst*]: $\text{false}\llbracket y \rrbracket_t = \text{false}$
by *rel-auto*

lemma *cond-rea-tt-subst* [*usubst*]:
 $(P \triangleleft b \triangleright_R Q)\llbracket v \rrbracket_t = (P\llbracket v \rrbracket_t \triangleleft b \triangleright_R Q\llbracket v \rrbracket_t)$
by (*rel-auto*)

lemma *tsubst-conj* [*usubst*]: $(P \wedge Q)\llbracket v \rrbracket_t = (P\llbracket v \rrbracket_t \wedge Q\llbracket v \rrbracket_t)$
by (*rel-auto*)

lemma *tsubst-disj* [*usubst*]: $(P \vee Q)\llbracket v \rrbracket_t = (P\llbracket v \rrbracket_t \vee Q\llbracket v \rrbracket_t)$
by (*rel-auto*)

lemma *rea-subst-R1-closed* [*closure*]: $P\llbracket v \rrbracket_t$ *is R1*
apply (*rel-auto*) **using** *le-add order.trans* **by** *blast*

lemma *tsubst-UINF-ind* [*usubst*]: $(\bigcap i \cdot P(i))\llbracket v \rrbracket_t = (\bigcap i \cdot (P(i))\llbracket v \rrbracket_t)$
by (*rel-auto*)

3.7 Initial Interaction

definition *rea-init* :: $'s \text{ upred} \Rightarrow ('t::\text{trace}, 's) \text{ uexpr} \Rightarrow ('s, 't, 'a, 'b) \text{ rel-rsp } (\mathcal{I}'(-,-))$ **where**
 $[\text{upred-defs}]: \mathcal{I}(s,t) = (\lceil s \rceil_{S<} \Rightarrow_r \neg_r \$tr + \lceil t \rceil_{S<} \leq_u \$tr)$

lemma *usubst-rea-init'* [*usubst*]:
 $\sigma \dagger_S \mathcal{I}(s,t) = \mathcal{I}(\sigma \dagger s, \sigma \dagger t)$
by (*rel-auto*)

lemma *unrest-rea-init* [*unrest*]:
 $\llbracket x \bowtie (\$tr)_v; x \bowtie (\$tr)_v; x \bowtie (\$st)_v \rrbracket \Longrightarrow x \# \mathcal{I}(s,t)$
by (*simp add: rea-init-def unrest lens-indep-sym*)

lemma *rea-init-R1* [*closure*]: $\mathcal{I}(s,t)$ *is R1*
by (*rel-auto*)

lemma *rea-init-R2c* [closure]: $\mathcal{I}(s, t)$ is *R2c*
 apply (rel-auto)
 apply (metis le-add minus-cancel-le trace-class.add-diff-cancel-left)
 apply (metis diff-add-cancel-left' trace-class.add-left-mono)
 done

lemma *rea-init-R2* [closure]: $\mathcal{I}(s, t)$ is *R2*
 by (metis Healthy-def R1-R2c-is-R2 rea-init-R1 rea-init-R2c)

lemma *csp-init-RR* [closure]: $\mathcal{I}(s, t)$ is *RR*
 apply (rel-auto)
 apply (metis le-add minus-cancel-le trace-class.add-diff-cancel-left)
 apply (metis diff-add-cancel-left' trace-class.add-left-mono)
 done

lemma *csp-init-CRR* [closure]: $\mathcal{I}(s, t)$ is *CRR*
 by (rule CRR-intro, simp-all add: unrest closure)

lemma *rea-init-RC* [closure]: $\mathcal{I}(s, t)$ is *CRC*
 apply (rel-auto) by fastforce

lemma *rea-init-false* [rpred]: $\mathcal{I}(\text{false}, t) = \text{true}_r$
 by (rel-auto)

lemma *rea-init-nil* [rpred]: $\mathcal{I}(s, \llbracket \cdot \rrbracket) = [\neg s]_{S<}$
 by (rel-auto)

lemma *rea-not-init* [rpred]: $(\neg_r \mathcal{I}(P, \llbracket \cdot \rrbracket)) = \mathcal{I}(\neg P, \llbracket \cdot \rrbracket)$
 by (rel-auto)

lemma *rea-init-conj* [rpred]:
 $(\mathcal{I}(s_1, t) \wedge \mathcal{I}(s_2, t)) = \mathcal{I}(s_1 \vee s_2, t)$
 by (rel-auto)

lemma *rea-init-disj-same* [rpred]: $(\mathcal{I}(s_1, t) \vee \mathcal{I}(s_2, t)) = \mathcal{I}(s_1 \wedge s_2, t)$
 by (rel-auto)

3.8 Enabled Events

definition *csp-enable* :: $'s \text{ upred} \Rightarrow ('e \text{ list}, 's) \text{ uexpr} \Rightarrow ('e \text{ set}, 's) \text{ uexpr} \Rightarrow ('s, 'e) \text{ action } (\mathcal{E}'(-, -, -))$
 where

[upred-defs]: $\mathcal{E}(s, t, E) = ([s]_{S<} \wedge \$tr =_u \$tr \hat{\sim}_u [t]_{S<} \wedge (\forall e \in [E]_{S<} \cdot \llbracket e \rrbracket \notin_u \$ref))$

Predicate $\mathcal{E}(s, t, E)$ states that, if the initial state satisfies predicate s , then t is a possible (failure) trace, such that the events in the set E are enabled after the given interaction.

lemma *csp-enable-R1-closed* [closure]: $\mathcal{E}(s, t, E)$ is *R1*
 by (rel-auto)

lemma *csp-enable-R2-closed* [closure]: $\mathcal{E}(s, t, E)$ is *R2c*
 by (rel-auto)

lemma *csp-enable-RR* [closure]: $\mathcal{E}(s, t, E)$ is *CRR*
 by (rel-auto)

lemma *tsubst-csp-enable* [*usubst*]: $\mathcal{E}(s, t_2, e) \llbracket t_1 \rrbracket_t = \mathcal{E}(s, t_1 \hat{=} t_2, e)$
apply (*rel-auto*)
apply (*metis append.assoc less-eq-list-def prefix-concat-minus*)
apply (*simp add: list-concat-minus-list-concat*)
done

lemma *csp-enable-unrests* [*unrest*]:
 $\llbracket x \bowtie (\$tr)_v; x \bowtie (\$tr')_v; x \bowtie (\$st)_v; x \bowtie (\$ref)_v \rrbracket \implies x \# \mathcal{E}(s, t, e)$
by (*simp add: csp-enable-def R1-def lens-indep-sym unrest*)

lemma *st-unrest-csp-enable* [*unrest*]: $\llbracket \&\mathbf{v} \# s; \&\mathbf{v} \# t; \&\mathbf{v} \# E \rrbracket \implies \$st \# \mathcal{E}(s, t, E)$
by (*simp add: csp-enable-def unrest*)

lemma *csp-enable-tr'-eq-tr* [*rpred*]:
 $\mathcal{E}(s, \llbracket \cdot \rrbracket, r) \triangleleft \$tr =_u \$tr \triangleright false = \mathcal{E}(s, \llbracket \cdot \rrbracket, r)$
by (*rel-auto*)

lemma *csp-enable-st-pred* [*rpred*]:
 $([s_1]_{S<} \wedge \mathcal{E}(s_2, t, E)) = \mathcal{E}(s_1 \wedge s_2, t, E)$
by (*rel-auto*)

lemma *csp-enable-conj* [*rpred*]:
 $(\mathcal{E}(s, t, E_1) \wedge \mathcal{E}(s, t, E_2)) = \mathcal{E}(s, t, E_1 \cup_u E_2)$
by (*rel-auto*)

lemma *csp-enable-cond* [*rpred*]:
 $\mathcal{E}(s_1, t_1, E_1) \triangleleft b \triangleright_R \mathcal{E}(s_2, t_2, E_2) = \mathcal{E}(s_1 \triangleleft b \triangleright s_2, t_1 \triangleleft b \triangleright t_2, E_1 \triangleleft b \triangleright E_2)$
by (*rel-auto*)

lemma *csp-enable-rea-assm* [*rpred*]:
 $[b]^\top_r ;; \mathcal{E}(s, t, E) = \mathcal{E}(b \wedge s, t, E)$
by (*rel-auto*)

lemma *csp-enable-tr-empty*: $\mathcal{E}(true, \llbracket \cdot \rrbracket, \{v\}_u) = (\$tr =_u \$tr \wedge [v]_{S<} \notin_u \$ref)$
by (*rel-auto*)

lemma *csp-enable-nothing*: $\mathcal{E}(true, \llbracket \cdot \rrbracket, \{\}_u) = (\$tr =_u \$tr)$
by (*rel-auto*)

lemma *msubst-nil-csp-enable* [*usubst*]:
 $\mathcal{E}(s(x), t(x), E(x)) \llbracket x \rightarrow \llbracket \cdot \rrbracket \rrbracket = \mathcal{E}(s(x) \llbracket x \rightarrow \llbracket \cdot \rrbracket \rrbracket, t(x) \llbracket x \rightarrow \llbracket \cdot \rrbracket \rrbracket, E(x) \llbracket x \rightarrow \llbracket \cdot \rrbracket \rrbracket)$
by (*pred-auto*)

lemma *msubst-csp-enable* [*usubst*]:
 $\mathcal{E}(s(x), t(x), E(x)) \llbracket x \rightarrow [v]_{S<} \rrbracket = \mathcal{E}(s(x) \llbracket x \rightarrow v \rrbracket, t(x) \llbracket x \rightarrow v \rrbracket, E(x) \llbracket x \rightarrow v \rrbracket)$
by (*rel-auto*)

lemma *csp-enable-false* [*rpred*]: $\mathcal{E}(false, t, E) = false$
by (*rel-auto*)

lemma *conj-csp-enable* [*rpred*]: $(\mathcal{E}(b_1, t, E_1) \wedge \mathcal{E}(b_2, t, E_2)) = \mathcal{E}(b_1 \wedge b_2, t, E_1 \cup_u E_2)$
by (*rel-auto*)

lemma *refine-csp-enable*: $\mathcal{E}(b_1, t, E_1) \sqsubseteq \mathcal{E}(b_2, t, E_2) \longleftrightarrow (b_2 \Rightarrow b_1 \wedge E_1 \subseteq_u E_2)$
by (*rel-blast*)

lemma *USUP-csp-enable* [*rpred*]:
 $(\sqcup x \cdot \mathcal{E}(s, t, A(x))) = \mathcal{E}(s, t, (\bigvee x \cdot A(x)))$
by (*rel-auto*)

lemma *R4-csp-enable-nil* [*rpred*]:
 $R4(\mathcal{E}(s, \langle \square \rangle, E)) = false$
by (*rel-auto*)

lemma *R5-csp-enable-nil* [*rpred*]:
 $R5(\mathcal{E}(s, \langle \square \rangle, E)) = \mathcal{E}(s, \langle \square \rangle, E)$
by (*rel-auto*)

lemma *R4-csp-enable-Cons* [*rpred*]:
 $R4(\mathcal{E}(s, \text{bop } Cons \ x \ xs, E)) = \mathcal{E}(s, \text{bop } Cons \ x \ xs, E)$
by (*rel-auto*, *simp add: Prefix-Order.strict-prefixI'*)

lemma *R5-csp-enable-Cons* [*rpred*]:
 $R5(\mathcal{E}(s, \text{bop } Cons \ x \ xs, E)) = false$
by (*rel-auto*)

lemma *rel-aext-csp-enable* [*alpha*]:
 $vwb\text{-}lens \ a \implies \mathcal{E}(s, t, E) \oplus_r \text{map-st}_L[a] = \mathcal{E}(s \oplus_p a, t \oplus_p a, E \oplus_p a)$
by (*rel-auto*)

3.9 Completed Trace Interaction

definition *csp-do* :: $'s \text{ upred} \Rightarrow ('s \text{ usubst}) \Rightarrow ('e \text{ list}, 's) \text{ uexpr} \Rightarrow ('s, 'e) \text{ action } (\Phi'(-, -, -))$ **where**
 $[upred\text{-}defs]: \Phi(s, \sigma, t) = ([s]_{S<} \wedge \$tr =_u \$tr \hat{^}_u [t]_{S<} \wedge [\langle \sigma \rangle_a]_S)$

lemma *csp-do-eq-intro*:
assumes $s_1 = s_2 \ \sigma_1 = \sigma_2 \ t_1 = t_2$
shows $\Phi(s_1, \sigma_1, t_1) = \Phi(s_2, \sigma_2, t_2)$
by (*simp add: assms*)

Predicate $\Phi(s, \sigma, t)$ states that if the initial state satisfies s , and the trace t is performed, then afterwards the state update σ is executed.

lemma *unrest-csp-do* [*unrest*]:
 $\llbracket x \bowtie (\$tr)_v; x \bowtie (\$tr)_v; x \bowtie (\$st)_v; x \bowtie (\$st)_v \rrbracket \implies x \# \Phi(s, \sigma, t)$
by (*simp-all add: csp-do-def alpha-in-var alpha-out-var prod-as-plus unrest lens-indep-sym*)

lemma *csp-do-CRF* [*closure*]: $\Phi(s, \sigma, t)$ *is CRF*
by (*rel-auto*)

lemma *csp-do-R4-closed* [*closure*]:
 $\Phi(b, \sigma, \text{bop } Cons \ x \ xs)$ *is R4*
by (*rel-auto*, *simp add: Prefix-Order.strict-prefixI'*)

lemma *st-pred-conj-csp-do* [*rpred*]:
 $([b]_{S<} \wedge \Phi(s, \sigma, t)) = \Phi(b \wedge s, \sigma, t)$
by (*rel-auto*)

lemma *trea-subst-csp-do* [*usubst*]:
 $(\Phi(s, \sigma, t_2)) \llbracket t_1 \rrbracket_t = \Phi(s, \sigma, t_1 \hat{^}_u t_2)$
apply (*rel-auto*)

apply (*metis append.assoc less-eq-list-def prefix-concat-minus*)
apply (*simp add: list-concat-minus-list-concat*)
done

lemma *st-subst-csp-do* [*usubst*]:
 $\lceil \sigma \rceil_{S\sigma} \uparrow \Phi(s, \varrho, t) = \Phi(\sigma \uparrow s, \varrho \circ_s \sigma, \sigma \uparrow t)$
by (*rel-auto*)

lemma *csp-do-nothing*: $\Phi(\text{true}, \text{id}_s, \llbracket \cdot \rrbracket) = II_c$
by (*rel-auto*)

lemma *csp-do-nothing-0*: $\Phi(\text{true}, \text{id}_s, 0) = II_c$
by (*rel-auto*)

lemma *csp-do-false* [*rpred*]: $\Phi(\text{false}, s, t) = \text{false}$
by (*rel-auto*)

lemma *subst-state-csp-enable* [*usubst*]:
 $\lceil \sigma \rceil_{S\sigma} \uparrow \mathcal{E}(s, t_2, e) = \mathcal{E}(\sigma \uparrow s, \sigma \uparrow t_2, \sigma \uparrow e)$
by (*rel-auto*)

lemma *csp-do-assign-enable* [*rpred*]:
 $\Phi(s_1, \sigma, t_1) ;; \mathcal{E}(s_2, t_2, e) = \mathcal{E}(s_1 \wedge \sigma \uparrow s_2, t_1 \hat{\sim}_u(\sigma \uparrow t_2), (\sigma \uparrow e))$
by (*rel-auto*)

lemma *csp-do-assign-do* [*rpred*]:
 $\Phi(s_1, \sigma, t_1) ;; \Phi(s_2, \varrho, t_2) = \Phi(s_1 \wedge (\sigma \uparrow s_2), \varrho \circ_s \sigma, t_1 \hat{\sim}_u(\sigma \uparrow t_2))$
by (*rel-auto*)

lemma *csp-do-cond* [*rpred*]:
 $\Phi(s_1, \sigma, t_1) \triangleleft b \triangleright_R \Phi(s_2, \varrho, t_2) = \Phi(s_1 \triangleleft b \triangleright s_2, \sigma \triangleleft b \triangleright \varrho, t_1 \triangleleft b \triangleright t_2)$
by (*rel-auto*)

lemma *rea-assm-csp-do* [*rpred*]:
 $\lceil b \rceil_r^\top ;; \Phi(s, \sigma, t) = \Phi(b \wedge s, \sigma, t)$
by (*rel-auto*)

lemma *csp-do-comp*:
assumes *P is CRR*
shows $\Phi(s, \sigma, t) ;; P = (\lceil s \rceil_{S<} \wedge (\sigma \uparrow_S P)) \llbracket t \rrbracket_t$

proof –
have $\Phi(s, \sigma, t) ;; (CRR P) = (\lceil s \rceil_{S<} \wedge ((\sigma \uparrow_S CRR P)) \llbracket t \rrbracket_t)$
by (*rel-auto; blast*)
thus *?thesis*
by (*simp add: Healthy-if assms*)
qed

lemma *wp-rea-csp-do-lemma*:
fixes *P :: ('σ, 'φ) action*
assumes $\$ok \# P \ \$wait \# P \ \$ref \# P$
shows $(\lceil \langle \sigma \rangle_a \rceil_S \wedge \$tr \hat{=}_u \$tr \hat{\sim}_u \lceil t \rceil_{S<}) ;; P = (\lceil \sigma \rceil_{S\sigma} \uparrow P) \llbracket \$tr \hat{\sim}_u \lceil t \rceil_{S<} / \$tr \rrbracket$
using *assms* **by** (*rel-auto, meson*)

This operator sets an upper bound on the permissible traces, when starting from a particular state

lemma *wp-rea-csp-do* [wp]:

$\Phi(s_1, \sigma, t_1) \text{ wp}_r \mathcal{I}(s_2, t_2) = \mathcal{I}(s_1 \wedge \sigma \dagger s_2, t_1 \hat{\wedge}_u \sigma \dagger t_2)$
by (*rel-auto*)

lemma *wp-rea-csp-do-false'* [wp]:

$\Phi(s_1, \sigma, t_1) \text{ wp}_r \text{false} = \mathcal{I}(s_1, t_1)$
by (*rel-auto*)

lemma *st-pred-impl-csp-do-wp* [rpred]:

$([s_1]_{S<} \Rightarrow_r \Phi(s_2, \sigma, t) \text{ wp}_r P) = \Phi(s_1 \wedge s_2, \sigma, t) \text{ wp}_r P$
by (*rel-auto*)

lemma *csp-do-seq-USUP-distl* [rpred]:

assumes $\bigwedge i. i \in A \implies P(i) \text{ is CRR } A \neq \{\}$
shows $\Phi(s, \sigma, t) ;; (\bigwedge i \in A \cdot P(i)) = (\bigwedge i \in A \cdot \Phi(s, \sigma, t) ;; P(i))$

proof –

from *assms(2)* **have** $\Phi(s, \sigma, t) ;; (\bigsqcup i \in A \cdot \text{CRR}(P(i))) = (\bigsqcup i \in A \cdot \Phi(s, \sigma, t) ;; \text{CRR}(P(i)))$
by (*rel-blast*)

thus *?thesis*

by (*simp cong: USUP-cong add: assms(1) Healthy-if*)

qed

lemma *csp-do-seq-conj-distl*:

assumes *P is CRR Q is CRR*
shows $\Phi(s, \sigma, t) ;; (P \wedge Q) = (\Phi(s, \sigma, t) ;; P \wedge \Phi(s, \sigma, t) ;; Q)$

proof –

have $\Phi(s, \sigma, t) ;; (\text{CRR}(P) \wedge \text{CRR}(Q)) = ((\Phi(s, \sigma, t) ;; (\text{CRR } P)) \wedge (\Phi(s, \sigma, t) ;; (\text{CRR } Q)))$
by (*rel-blast*)

thus *?thesis*

by (*simp add: assms Healthy-if*)

qed

lemma *csp-do-power-Suc* [rpred]:

$\Phi(\text{true}, id_s, t) \hat{\wedge} (\text{Suc } i) = \Phi(\text{true}, id_s, \text{iter}[\text{Suc } i](t))$
by (*induct i, (rel-auto)+*)

lemma *csp-power-do-comp* [rpred]:

assumes *P is CRR*
shows $\Phi(\text{true}, id_s, t) \hat{\wedge} i ;; P = \Phi(\text{true}, id_s, \text{iter}[i](t)) ;; P$
apply (*cases i*)
apply (*simp-all add: csp-do-comp rpred usubst assms closure*)
done

lemma *csp-do-id* [rpred]:

P is CRR $\implies \Phi(b, id_s, \llbracket \cdot \rrbracket) ;; P = ([b]_{S<} \wedge P)$
by (*simp add: csp-do-comp usubst*)

lemma *csp-do-id-wp* [wp]:

P is CRR $\implies \Phi(b, id_s, \llbracket \cdot \rrbracket) \text{ wp}_r P = ([b]_{S<} \Rightarrow_r P)$
by (*metis (no-types, lifting) CRR-implies-RR RR-implies-R1 csp-do-id rea-impl-conj rea-impl-false rea-not-CRR-closed rea-not-not wp-rea-def*)

lemma *wp-rea-csp-do-st-pre* [wp]: $\Phi(s_1, \sigma, t_1) \text{ wp}_r [s_2]_{S<} = \mathcal{I}(s_1 \wedge \neg \sigma \dagger s_2, t_1)$

by (*rel-auto*)

lemma *wp-rea-csp-do-skip* [*wp*]:

fixes $Q :: ('\sigma, '\varphi)$ *action*

assumes P *is CRR*

shows $\Phi(s, \sigma, t) \text{ wp}_r P = (\mathcal{I}(s, t) \wedge (\sigma \uparrow_S P) \llbracket t \rrbracket_t)$

apply (*simp add: wp-rea-def*)

apply (*subst csp-do-comp*)

apply (*simp-all add: closure assms usubst*)

oops

lemma *msubst-csp-do* [*usubst*]:

$\Phi(s(x), \sigma, t(x)) \llbracket x \rightarrow \lceil v \rceil_{S \leftarrow} \rrbracket = \Phi(s(x) \llbracket x \rightarrow v \rrbracket, \sigma, t(x) \llbracket x \rightarrow v \rrbracket)$

by (*rel-auto*)

lemma *rea-frame-ext-csp-do* [*frame*]:

$\text{vwb-lens } a \implies a: [\Phi(s, \sigma, t)]_r^+ = \Phi(s \oplus_p a, \sigma \oplus_s a, t \oplus_p a)$

by (*rel-auto*)

lemma *R5-csp-do-nil* [*rpred*]: $R5(\Phi(s, \sigma, \llbracket \cdot \rrbracket)) = \Phi(s, \sigma, \llbracket \cdot \rrbracket)$

by (*rel-auto*)

lemma *R5-csp-do-Cons* [*rpred*]: $R5(\Phi(s, \sigma, x \#_u xs)) = \text{false}$

by (*rel-auto*)

Iterated do relations

fun *titr* :: $\text{nat} \Rightarrow 's \text{ usubst} \Rightarrow ('a \text{ list}, 's) \text{ uexpr} \Rightarrow ('a \text{ list}, 's) \text{ uexpr}$ **where**

titr 0 σ $t = 0 \mid$

titr (*Suc* n) σ $t = (\text{titr } n \sigma t) + (\sigma \hat{\sim}_s n) \uparrow t$

lemma *titr-as-list-sum*: $\text{titr } n \sigma t = \text{list-sum } (\text{map } (\lambda i. (\sigma \hat{\sim}_s i) \uparrow t) [0..<n])$

apply (*induct n*)

apply (*auto simp add: usubst fold-plus-sum-list-rev foldr-conv-fold*)

done

lemma *titr-as-foldr*: $\text{titr } n \sigma t = \text{foldr } (\lambda i e. (\sigma \hat{\sim}_s i) \uparrow t + e) [0..<n] 0$

by (*simp add: titr-as-list-sum foldr-map comp-def*)

lemma *list-sum-uexpr-rep-eq*: $\llbracket \text{list-sum } xs \rrbracket_e s = \text{list-sum } (\text{map } (\lambda e. \llbracket e \rrbracket_e s) xs)$

apply (*induct xs*)

apply (*simp-all*)

apply (*pred-simp+*)

done

lemma *titr-rep-eq*: $\llbracket \text{titr } n \sigma t \rrbracket_e s = \text{foldr } (@) (\text{map } (\lambda x. \llbracket t \rrbracket_e ((\llbracket \sigma \rrbracket_e \hat{\sim} x) s)) [0..<n]) []$

by (*simp add: titr-as-list-sum list-sum-uexpr-rep-eq comp-def, rel-simp*)

update-uexpr-rep-eq-thms

lemma *titr-lemma*:

$t + (\sigma \uparrow \text{titr } n \sigma t) + (\sigma \hat{\sim}_s n \circ_s \sigma) \uparrow t = (\text{titr } n \sigma t + (\sigma \hat{\sim}_s n) \uparrow t) + (\sigma \circ_s \sigma \hat{\sim}_s n) \uparrow t$

by (*induct n, simp-all add: usubst add.assoc,metis subst-monoid.power-Suc subst-monoid.power-Suc2*)

lemma *csp-do-power* [*rpred*]:

$\Phi(s, \sigma, t) \hat{\sim} (\text{Suc } n) = \Phi(\bigwedge i \in \{0..n\} \cdot (\sigma \hat{\sim}_s i) \uparrow s, \sigma \hat{\sim}_s \text{Suc } n, \text{titr } (\text{Suc } n) \sigma t)$

apply (*induct n*)

apply (*rel-auto*)

```

apply (simp add: power.power.power-Suc rpred usubst)
apply (thin-tac -)
apply (rule csp-do-eq-intro)
  apply (rel-auto)
  apply (case-tac x=0)
apply (simp-all add: titr-lemma)
apply (metis Suc-le-mono funpow-simps-right(2) gr0-implies-Suc o-def)
apply force
apply (metis Suc-leI funpow-simps-right(2) less-Suc-eq-le o-apply)
apply (metis subst-monoid.power-Suc subst-monoid.power-Suc2)
apply (metis add.assoc plus-list-def plus-ueq-def titr-lemma)
done

```

lemma *csp-do-rea-star* [rpred]:

$\Phi(s, \sigma, t)^{*r} = II_r \sqcap (\bigsqcap n \cdot \Phi(\bigwedge i \in \{0..n\} \cdot (\sigma \hat{\ }_s i) \dagger s, \sigma \hat{\ }_s \text{Suc } n, \text{titr } (\text{Suc } n) \sigma t))$
by (simp add: rrel-theory.Star-alt-def closure uplus-power-def rpred)

lemma *csp-do-csp-star* [rpred]:

$\Phi(s, \sigma, t)^{*c} = (\bigsqcap n \cdot \Phi(\bigsqcup i \in \{0..<n\} \cdot (\sigma \hat{\ }_s i) \dagger s, \sigma \hat{\ }_s n, \text{titr } n \sigma t))$
(is ?lhs = ($\bigsqcap n \cdot ?G(n)$))

proof –

have ?lhs = $II_c \sqcap (\bigsqcap n \cdot \Phi(\bigwedge i \in \{0..n\} \cdot (\sigma \hat{\ }_s i) \dagger s, \sigma \hat{\ }_s \text{Suc } n, \text{titr } (\text{Suc } n) \sigma t))$
(is - = $II_c \sqcap (\bigsqcap n \cdot ?F(n))$)

by (simp add: crf-theory.Star-alt-def closure uplus-power-def rpred)

also have ... = $II_c \sqcap (\bigsqcap n \in \{1..\} \cdot ?F(n - 1))$

by (simp add: UINF-atLeast-Suc)

also have ... = $II_c \sqcap (\bigsqcap n \in \{1..\} \cdot \Phi(\bigsqcup i \in \{0..<n\} \cdot (\sigma \hat{\ }_s i) \dagger s, \sigma \hat{\ }_s n, \text{titr } n \sigma t))$

proof –

have ($\bigsqcap n \in \{1..\} \cdot ?F(n - 1)$) = ($\bigsqcap n \in \{1..\} \cdot ?G(n)$)

by (rule UINF-cong, simp, metis (no-types, lifting) Suc-diff-le atLeastLessThanSuc-atLeastAtMost cancel-comm-monoid-add-class.diff-zero diff-Suc-Suc)

thus ?thesis by simp

qed

also have ... = $?G(0) \sqcap (\bigsqcap n \in \{1..\} \cdot ?G(n))$

by (simp add: usubst csp-do-nothing-0)

also have ... = ($\bigsqcap n \in \text{insert } 0 \{1..\} \cdot ?G(n)$)

by (simp)

also have ... = ($\bigsqcap n \cdot ?G(n)$)

proof –

have $\text{insert } (0::\text{nat}) \{1..\} = \{0..\}$ **by** auto

thus ?thesis

by simp

qed

finally show ?thesis .

qed

3.10 Assumptions

abbreviation *crf-assume* :: 's upred \Rightarrow ('s, 'e) action ($[-]_c$) **where**

$[b]_c \equiv \Phi(b, id_s, \llbracket \cdot \rrbracket)$

lemma *crf-assume-true* [rpred]: $P \text{ is CRR} \Longrightarrow [true]_c \;; P = P$

by (simp add: crel-skip-left-unit csp-do-nothing)

3.11 Downward closure of refusals

We define downward closure of the pericondition by the following healthiness condition

definition $CDC :: ('s, 'e) \text{ action} \Rightarrow ('s, 'e) \text{ action}$ **where**
 $[upred-defs]: CDC(P) = (\exists \text{ ref}_0 \cdot P \llbracket \langle \text{ref}_0 \rangle / \$ref \rrbracket \wedge \$ref \subseteq_u \langle \text{ref}_0 \rangle)$

lemma $CDC\text{-idem}: CDC(CDC(P)) = CDC(P)$
by $(rel\text{-auto})$

lemma $CDC\text{-Continuous}$ $[closure]: \text{Continuous } CDC$
by $(rel\text{-auto})$

lemma $CDC\text{-RR-commute}: CDC(RR(P)) = RR(CDC(P))$
by $(rel\text{-blast})$

lemma $CDC\text{-RR-closed}$ $[closure]: P \text{ is } RR \implies CDC(P) \text{ is } RR$
by $(metis \text{ CDC-RR-commute Healthy-def})$

lemma $CDC\text{-CRR-commute}: CDC(CRR P) = CRR(CDC P)$
by $(rel\text{-blast})$

lemma $CDC\text{-CRR-closed}$ $[closure]:$
assumes $P \text{ is } CRR$
shows $CDC(P) \text{ is } CRR$
by $(rule \text{ CRR-intro, simp add: CDC-def unrest assms closure, simp add: unrest assms closure})$

lemma $CDC\text{-unrest}$ $[unrest]: \llbracket vwb\text{-lens } x; (\$ref)_v \bowtie x; x \nmid P \rrbracket \implies x \nmid CDC(P)$
by $(simp \text{ add: CDC-def unrest usubst lens-indep-sym})$

lemma $CDC\text{-R4-commute}: CDC(R4(P)) = R4(CDC(P))$
by $(rel\text{-auto})$

lemma $R4\text{-CDC-closed}$ $[closure]: P \text{ is } CDC \implies R4(P) \text{ is } CDC$
by $(simp \text{ add: CDC-R4-commute Healthy-def})$

lemma $CDC\text{-R5-commute}: CDC(R5(P)) = R5(CDC(P))$
by $(rel\text{-auto})$

lemma $R5\text{-CDC-closed}$ $[closure]: P \text{ is } CDC \implies R5(P) \text{ is } CDC$
by $(simp \text{ add: CDC-R5-commute Healthy-def})$

lemma $rea\text{-true-CDC}$ $[closure]: true_r \text{ is } CDC$
by $(rel\text{-auto})$

lemma $false\text{-CDC}$ $[closure]: false \text{ is } CDC$
by $(rel\text{-auto})$

lemma $CDC\text{-UINF-closed}$ $[closure]:$
assumes $\bigwedge i. i \in I \implies P \ i \text{ is } CDC$
shows $(\bigcap i \in I \cdot P \ i) \text{ is } CDC$
using $assms$ **by** $(rel\text{-blast})$

lemma $CDC\text{-disj-closed}$ $[closure]:$
assumes $P \text{ is } CDC \ Q \text{ is } CDC$
shows $(P \vee Q) \text{ is } CDC$

proof –
 have $CDC(P \vee Q) = (CDC(P) \vee CDC(Q))$
 by (*rel-auto*)
 thus ?thesis
 by (*metis Healthy-def assms(1) assms(2)*)
qed

lemma *CDC-USUP-closed* [closure]:
 assumes $\bigwedge i. i \in I \implies P\ i\ is\ CDC$
 shows $(\bigsqcup i \in I. P\ i)\ is\ CDC$
 using *assms* by (*rel-blast*)

lemma *CDC-conj-closed* [closure]:
 assumes $P\ is\ CDC\ Q\ is\ CDC$
 shows $(P \wedge Q)\ is\ CDC$
 using *assms* by (*rel-auto, blast, meson*)

lemma *CDC-rea-impl* [*rpred*]:
 $\$ref \# P \implies CDC(P \Rightarrow_r Q) = (P \Rightarrow_r CDC(Q))$
 by (*rel-auto*)

lemma *rea-impl-CDC-closed* [closure]:
 assumes $\$ref \# P\ Q\ is\ CDC$
 shows $(P \Rightarrow_r Q)\ is\ CDC$
 using *assms* by (*simp add: CDC-rea-impl Healthy-def*)

lemma *seq-CDC-closed* [closure]:
 assumes $Q\ is\ CDC$
 shows $(P ;; Q)\ is\ CDC$
proof –
 have $CDC(P ;; Q) = P ;; CDC(Q)$
 by (*rel-blast*)
 thus ?thesis
 by (*metis Healthy-def assms*)
qed

lemma *st-subst-CDC-closed* [closure]:
 assumes $P\ is\ CDC$
 shows $(\sigma \upharpoonright_S P)\ is\ CDC$
proof –
 have $(\sigma \upharpoonright_S CDC\ P)\ is\ CDC$
 by (*rel-auto*)
 thus ?thesis
 by (*simp add: assms Healthy-if*)
qed

lemma *rea-st-cond-CDC* [closure]: $[g]_{S<} is\ CDC$
 by (*rel-auto*)

lemma *csp-enable-CDC* [closure]: $\mathcal{E}(s, t, E)\ is\ CDC$
 by (*rel-auto*)

lemma *state-srea-CDC-closed* [closure]:
 assumes $P\ is\ CDC$
 shows $state\ 'a \cdot P\ is\ CDC$

proof –

have *state* 'a • CDC(P) is CDC
 by (rel-blast)
 thus ?thesis
 by (simp add: Healthy-if assms)

qed

3.12 Renaming

abbreviation *pre-image* $f B \equiv \{x. f(x) \in B\}$

definition *csp-rename* :: ('s, 'e) action \Rightarrow ('e \Rightarrow 'f) \Rightarrow ('s, 'f) action $((-)\llbracket - \rrbracket_c [999, 0] 999)$ **where**
 [upred-defs]: $P\llbracket f \rrbracket_c = R2((\$tr =_u \llbracket \cdot \rrbracket \gg \$st =_u \$st) ;; P ;; (\$tr =_u \text{map}_u \llbracket f \rrbracket \$tr \wedge \$st =_u \$st \wedge uop$
 (pre-image f) \$ref \subseteq_u \$ref))

lemma *csp-rename-CRR-closed* [closure]:

assumes *P is CRR*
 shows $P\llbracket f \rrbracket_c$ *is CRR*

proof –

have (CRR P) $\llbracket f \rrbracket_c$ *is CRR*
 by (rel-auto)
 thus ?thesis **by** (simp add: assms Healthy-if)

qed

lemma *csp-rename-disj* [rpred]: $(P \vee Q)\llbracket f \rrbracket_c = (P\llbracket f \rrbracket_c \vee Q\llbracket f \rrbracket_c)$

by (rel-blast)

lemma *csp-rename-UINF-ind* [rpred]: $(\bigcap i \cdot P i)\llbracket f \rrbracket_c = (\bigcap i \cdot (P i)\llbracket f \rrbracket_c)$

by (rel-blast)

lemma *csp-rename-UINF-mem* [rpred]: $(\bigcap i \in A \cdot P i)\llbracket f \rrbracket_c = (\bigcap i \in A \cdot (P i)\llbracket f \rrbracket_c)$

by (rel-blast)

Renaming distributes through conjunction only when both sides are downward closed

lemma *csp-rename-conj* [rpred]:

assumes *inj f P is CRR Q is CRR P is CDC Q is CDC*
 shows $(P \wedge Q)\llbracket f \rrbracket_c = (P\llbracket f \rrbracket_c \wedge Q\llbracket f \rrbracket_c)$

proof –

from assms(1) **have** $((CDC (CRR P)) \wedge (CDC (CRR Q)))\llbracket f \rrbracket_c = ((CDC (CRR P))\llbracket f \rrbracket_c \wedge (CDC$
 $(CRR Q))\llbracket f \rrbracket_c)$

apply (rel-auto)

apply blast

apply blast

apply (meson order-refl order-trans)

done

thus ?thesis

by (simp add: assms Healthy-if)

qed

lemma *csp-rename-seq* [rpred]:

assumes *P is CRR Q is CRR*

shows $(P ;; Q)\llbracket f \rrbracket_c = P\llbracket f \rrbracket_c ;; Q\llbracket f \rrbracket_c$

oops

lemma *csp-rename-R4* [rpred]:

$(R4(P))\llbracket f \rrbracket_c = R4(P\llbracket f \rrbracket_c)$

```

apply (rel-auto, blast)
using less-le apply fastforce
apply (metis (mono-tags, lifting) Prefix-Order.Nil-prefix append-Nil2 diff-add-cancel-left' less-le list.simps(8)
plus-list-def)
done

```

```

lemma csp-rename-R5 [rpred]:
   $(R5(P))(\llbracket f \rrbracket)_c = R5(P(\llbracket f \rrbracket)_c)$ 
apply (rel-auto, blast)
using less-le apply fastforce
done

```

```

lemma csp-rename-do [rpred]:  $\Phi(s, \sigma, t)(\llbracket f \rrbracket)_c = \Phi(s, \sigma, \text{map}_u \llbracket f \rrbracket t)$ 
by (rel-auto)

```

```

lemma csp-rename-enable [rpred]:  $\mathcal{E}(s, t, E)(\llbracket f \rrbracket)_c = \mathcal{E}(s, \text{map}_u \llbracket f \rrbracket t, \text{uop}(\text{image } f) E)$ 
by (rel-auto)

```

```

lemma st'-unrest-csp-rename [unrest]:  $\$st \# P \implies \$st \# P(\llbracket f \rrbracket)_c$ 
by (rel-blast)

```

```

lemma ref'-unrest-csp-rename [unrest]:  $\$ref \# P \implies \$ref \# P(\llbracket f \rrbracket)_c$ 
by (rel-blast)

```

```

lemma csp-rename-CDC-closed [closure]:
   $P \text{ is CDC} \implies P(\llbracket f \rrbracket)_c \text{ is CDC}$ 
by (rel-blast)

```

```

lemma csp-do-CDC [closure]:  $\Phi(s, \sigma, t) \text{ is CDC}$ 
by (rel-auto)

```

end

4 Stateful-Failure Healthiness Conditions

```

theory utp-sfrd-healths
imports utp-sfrd-rel
begin

```

5 Definitions

We here define extra healthiness conditions for stateful-failure reactive designs.

```

abbreviation CSP1 ::  $((\sigma, \varphi) \text{ sfrd} \times (\sigma, \varphi) \text{ sfrd}) \text{ health}$ 
where  $\text{CSP1}(P) \equiv \text{RD1}(P)$ 

```

```

abbreviation CSP2 ::  $((\sigma, \varphi) \text{ sfrd} \times (\sigma, \varphi) \text{ sfrd}) \text{ health}$ 
where  $\text{CSP2}(P) \equiv \text{RD2}(P)$ 

```

```

abbreviation CSP ::  $((\sigma, \varphi) \text{ sfrd} \times (\sigma, \varphi) \text{ sfrd}) \text{ health}$ 
where  $\text{CSP}(P) \equiv \text{SRD}(P)$ 

```

```

definition STOP ::  $\varphi \text{ process}$  where
 $[\text{upred-defs}]: \text{STOP} = \text{CSP1}(\$ok \wedge R3c(\$tr =_u \$tr \wedge \$wait))$ 

```

definition $SKIP :: ('σ, 'φ) \text{ process where}$
 $[upred-defs]: SKIP = \mathbf{R}_s(\exists \$ref \cdot CSP1(II))$

definition $Stop :: ('σ, 'φ) \text{ action where}$
 $[upred-defs]: Stop = \mathbf{R}_s(true \vdash (\$tr =_u \$tr \wedge \$wait))$

definition $Skip :: ('σ, 'φ) \text{ action where}$
 $[upred-defs]: Skip = \mathbf{R}_s(true \vdash (\$tr =_u \$tr \wedge \neg \$wait \wedge \$st =_u \$st))$

definition $CSP3 :: (('σ, 'φ) \text{ sfrd} \times ('σ, 'φ) \text{ sfrd}) \text{ health where}$
 $[upred-defs]: CSP3(P) = (Skip ;; P)$

definition $CSP4 :: (('σ, 'φ) \text{ sfrd} \times ('σ, 'φ) \text{ sfrd}) \text{ health where}$
 $[upred-defs]: CSP4(P) = (P ;; Skip)$

definition $NCSP :: (('σ, 'φ) \text{ sfrd} \times ('σ, 'φ) \text{ sfrd}) \text{ health where}$
 $[upred-defs]: NCSP = CSP3 \circ CSP4 \circ CSP$

Productive and normal processes

abbreviation $PCSP \equiv Productive \circ NCSP$

Instantaneous and normal processes

abbreviation $ICSP \equiv ISRD1 \circ NCSP$

5.1 Healthiness condition properties

$SKIP$ is the same as $Skip$, and $STOP$ is the same as $Stop$, when we consider stateless CSP processes. This is because any reference to the st variable degenerates when the alphabet type coerces its type to be empty. We therefore need not consider $SKIP$ and $STOP$ actions.

theorem $SKIP\text{-is-Skip}$ $[simp]: SKIP = Skip$
by $(rel\text{-auto})$

theorem $STOP\text{-is-Stop}$ $[simp]: STOP = Stop$
by $(rel\text{-auto})$

theorem $Skip\text{-UTP-form}$: $Skip = \mathbf{R}_s(\exists \$ref \cdot CSP1(II))$
by $(rel\text{-auto})$

lemma $Skip\text{-is-CSP}$ $[closure]$:
 $Skip \text{ is CSP}$
by $(simp \text{ add: } Skip\text{-def RHS-design-is-SRD unrest})$

lemma $Skip\text{-RHS-tri-design}$:
 $Skip = \mathbf{R}_s(true \vdash (false \diamond (\$tr =_u \$tr \wedge \$st =_u \$st)))$
by $(rel\text{-auto})$

lemma $Skip\text{-RHS-tri-design}'$ $[rdes-def]$:
 $Skip = \mathbf{R}_s(true_r \vdash (false \diamond \Phi(true, id_s, \llbracket \cdot \rrbracket)))$
by $(rel\text{-auto})$

lemma $Skip\text{-frame}$ $[frame]$: $vwb\text{-lens } a \implies a:[Skip]_R^+ = Skip$
by $(rdes\text{-eq})$

lemma $Stop\text{-is-CSP}$ $[closure]$:

Stop is CSP
by (*simp add: Stop-def RHS-design-is-SRD unrest*)

lemma *Stop-RHS-tri-design*: $Stop = \mathbf{R}_s(true \vdash (\$tr =_u \$tr) \diamond false)$
by (*rel-auto*)

lemma *Stop-RHS-rdes-def* [*rdes-def*]: $Stop = \mathbf{R}_s(true_r \vdash \mathcal{E}(true, \llbracket \cdot \rrbracket, \{\}_u) \diamond false)$
by (*rel-auto*)

lemma *preR-Skip* [*rdes*]: $pre_R(Skip) = true_r$
by (*rel-auto*)

lemma *periR-Skip* [*rdes*]: $peri_R(Skip) = false$
by (*rel-auto*)

lemma *postR-Skip* [*rdes*]: $post_R(Skip) = \Phi(true, id_s, \llbracket \cdot \rrbracket)$
by (*rel-auto*)

lemma *Productive-Stop* [*closure*]:
Stop is Productive
by (*simp add: Stop-RHS-tri-design Healthy-def Productive-RHS-design-form unrest closure*)

lemma *Skip-left-lemma*:
assumes *P is CSP*
shows $Skip ;; P = \mathbf{R}_s((\forall \$ref \cdot pre_R P) \vdash (\exists \$ref \cdot cmt_R P))$
proof –
have $Skip ;; P =$
 $\mathbf{R}_s((\$tr =_u \$tr \wedge \$st =_u \$st) \wp_r pre_R P \vdash$
 $(\$tr =_u \$tr \wedge \$st =_u \$st) ;; peri_R P \diamond$
 $(\$tr =_u \$tr \wedge \$st =_u \$st) ;; post_R P)$
by (*simp add: SRD-composition-wp alpha rdes closure wp assms rpred C1, rel-auto*)
also have $\dots = \mathbf{R}_s((\forall \$ref \cdot pre_R P) \vdash$
 $(\$tr =_u \$tr \wedge \neg \$wait \wedge \$st =_u \$st) ;; ((\exists \$st \cdot \lceil II \rceil_D) \triangleleft \$wait \triangleright cmt_R P))$
by (*rule cong[of $\mathbf{R}_s \mathbf{R}_s$], simp, rel-auto*)
also have $\dots = \mathbf{R}_s((\forall \$ref \cdot pre_R P) \vdash (\exists \$ref \cdot cmt_R P))$
by (*rule cong[of $\mathbf{R}_s \mathbf{R}_s$], simp, rel-auto*)
finally show *?thesis* .
qed

lemma *Skip-left-unit-ref-unrest*:
assumes *P is CSP* $\$ref \# P \llbracket false/\$wait \rrbracket$
shows $Skip ;; P = P$
using *assms*
by (*simp add: Skip-left-lemma*)
(metis SRD-reactive-design-alt all-unrest cmt-unrest-ref cmt-wait-false ex-unrest pre-unrest-ref pre-wait-false)

lemma *CSP3-intro*:
 $\llbracket P \text{ is CSP}; \$ref \# P \llbracket false/\$wait \rrbracket \rrbracket \implies P \text{ is CSP3}$
by (*simp add: CSP3-def Healthy-def' Skip-left-unit-ref-unrest*)

lemma *ref-unrest-RHS-design*:
assumes $\$ref \# P \ \$ref \# Q_1 \ \$ref \# Q_2$
shows $\$ref \# (\mathbf{R}_s(P \vdash Q_1 \diamond Q_2))_f$
by (*simp add: RHS-def R1-def R2c-def R2s-def R3h-def design-def unrest usubst assms*)

lemma *CSP3-SRD-intro*:

assumes P is CSP $\$ref \# pre_R(P) \$ref \# peri_R(P) \$ref \# post_R(P)$
 shows P is CSP3

proof –

have $P: \mathbf{R}_s(pre_R(P) \vdash peri_R(P) \diamond post_R(P)) = P$
 by (simp add: SRD-reactive-design-alt assms(1) wait'-cond-peri-post-cmt[THEN sym])
 have $\mathbf{R}_s(pre_R(P) \vdash peri_R(P) \diamond post_R(P))$ is CSP3
 by (rule CSP3-intro, simp add: assms P, simp add: ref-unrest-RHS-design assms)
 thus ?thesis
 by (simp add: P)

qed

lemma *Skip-unrest-ref* [unrest]: $\$ref \# Skip\llbracket false/\$wait \rrbracket$

by (simp add: Skip-def RHS-def R1-def R2c-def R2s-def R3h-def design-def usubst unrest)

lemma *Skip-unrest-ref'* [unrest]: $\$ref \# Skip\llbracket false/\$wait \rrbracket$

by (simp add: Skip-def RHS-def R1-def R2c-def R2s-def R3h-def design-def usubst unrest)

lemma *CSP3-iff*:

assumes P is CSP
 shows P is CSP3 $\longleftrightarrow (\$ref \# P\llbracket false/\$wait \rrbracket)$

proof

assume 1: P is CSP3
 have $\$ref \# (Skip ;; P)\llbracket false/\$wait \rrbracket$
 by (simp add: usubst unrest)
 with 1 show $\$ref \# P\llbracket false/\$wait \rrbracket$
 by (metis CSP3-def Healthy-def)

next

assume 1: $\$ref \# P\llbracket false/\$wait \rrbracket$
 show P is CSP3
 by (simp add: 1 CSP3-intro assms)

qed

lemma *CSP3-unrest-ref* [unrest]:

assumes P is CSP P is CSP3
 shows $\$ref \# pre_R(P) \$ref \# peri_R(P) \$ref \# post_R(P)$

proof –

have $a: (\$ref \# P\llbracket false/\$wait \rrbracket)$
 using CSP3-iff assms by blast
 from a show $\$ref \# pre_R(P)$
 by (rel-blast)
 from a show $\$ref \# peri_R(P)$
 by (rel-blast)
 from a show $\$ref \# post_R(P)$
 by (rel-blast)

qed

lemma *CSP3-rdes*:

assumes P is RR Q is RR R is RR
 shows $CSP3(\mathbf{R}_s(P \vdash Q \diamond R)) = \mathbf{R}_s((\forall \$ref \cdot P) \vdash (\exists \$ref \cdot Q) \diamond (\exists \$ref \cdot R))$
 by (simp add: CSP3-def Skip-left-lemma closure assms rdes, rel-auto)

lemma *CSP3-form*:

assumes P is CSP

shows $CSP3(P) = \mathbf{R}_s((\forall \$ref \cdot pre_R(P)) \vdash (\exists \$ref \cdot peri_R(P)) \diamond (\exists \$ref \cdot post_R(P)))$
by (*simp add: CSP3-def Skip-left-lemma assms, rel-auto*)

lemma *CSP3-Skip [closure]*:

Skip is CSP3

by (*rule CSP3-intro, simp add: Skip-is-CSP, simp add: Skip-def unrest*)

lemma *CSP3-Stop [closure]*:

Stop is CSP3

by (*rule CSP3-intro, simp add: Stop-is-CSP, simp add: Stop-def unrest*)

lemma *CSP3-Idempotent [closure]*: *Idempotent CSP3*

by (*metis (no-types, lifting) CSP3-Skip CSP3-def Healthy-if Idempotent-def seqr-assoc*)

lemma *CSP3-Continuous: Continuous CSP3*

by (*simp add: Continuous-def CSP3-def seq-Sup-distl*)

lemma *Skip-right-lemma*:

assumes *P is CSP*

shows $P ;; Skip = \mathbf{R}_s((\neg_r pre_R P) wp_r false \vdash ((\exists \$st \cdot cmt_R P) \triangleleft \$wait \triangleright (\exists \$ref \cdot cmt_R P)))$

proof –

have $P ;; Skip = \mathbf{R}_s((\neg_r pre_R P) wp_r false \vdash (\exists \$st \cdot peri_R P) \diamond post_R P ;; (\$tr =_u \$tr \wedge \$st =_u \$st))$

by (*simp add: SRD-composition-wp closure assms wp rdes rpred, rel-auto*)

also have $\dots = \mathbf{R}_s((\neg_r pre_R P) wp_r false \vdash$

$((cmt_R P ;; (\exists \$st \cdot [II]_D)) \triangleleft \$wait \triangleright (cmt_R P ;; (\$tr =_u \$tr \wedge \neg \$wait \wedge \$st =_u \$st))))$

by (*rule cong[of $\mathbf{R}_s \mathbf{R}_s$], simp, rel-auto*)

also have $\dots = \mathbf{R}_s((\neg_r pre_R P) wp_r false \vdash$

$((\exists \$st \cdot cmt_R P) \triangleleft \$wait \triangleright (cmt_R P ;; (\$tr =_u \$tr \wedge \neg \$wait \wedge \$st =_u \$st))))$

by (*rule cong[of $\mathbf{R}_s \mathbf{R}_s$], simp, rel-auto*)

also have $\dots = \mathbf{R}_s((\neg_r pre_R P) wp_r false \vdash ((\exists \$st \cdot cmt_R P) \triangleleft \$wait \triangleright (\exists \$ref \cdot cmt_R P)))$

by (*rule cong[of $\mathbf{R}_s \mathbf{R}_s$], simp, rel-auto*)

finally show *?thesis* .

qed

lemma *Skip-right-tri-lemma*:

assumes *P is CSP*

shows $P ;; Skip = \mathbf{R}_s((\neg_r pre_R P) wp_r false \vdash ((\exists \$st \cdot peri_R P) \diamond (\exists \$ref \cdot post_R P)))$

proof –

have $((\exists \$st \cdot cmt_R P) \triangleleft \$wait \triangleright (\exists \$ref \cdot cmt_R P)) = ((\exists \$st \cdot peri_R P) \diamond (\exists \$ref \cdot post_R P))$

by (*rel-auto*)

thus *?thesis* **by** (*simp add: Skip-right-lemma[OF assms]*)

qed

lemma *CSP4-intro*:

assumes *P is CSP* $(\neg_r pre_R(P)) ;; R1(true) = (\neg_r pre_R(P))$

$\$st \# (cmt_R P) \llbracket true/\$wait \rrbracket \$ref \# (cmt_R P) \llbracket false/\$wait \rrbracket$

shows *P is CSP4*

proof –

have $CSP4(P) = \mathbf{R}_s((\neg_r pre_R P) wp_r false \vdash ((\exists \$st \cdot cmt_R P) \triangleleft \$wait \triangleright (\exists \$ref \cdot cmt_R P)))$

by (*simp add: CSP4-def Skip-right-lemma assms(1)*)

also have $\dots = \mathbf{R}_s(pre_R(P) \vdash ((\exists \$st \cdot cmt_R P) \llbracket true/\$wait \rrbracket \triangleleft \$wait \triangleright (\exists \$ref \cdot cmt_R P) \llbracket false/\$wait \rrbracket))$

by (*simp add: wp-rea-def assms(2) rpred closure cond-var-subst-left cond-var-subst-right*)

also have $\dots = \mathbf{R}_s(pre_R(P) \vdash ((\exists \$st \cdot (cmt_R P) \llbracket true/\$wait \rrbracket) \triangleleft \$wait \triangleright (\exists \$ref \cdot (cmt_R$

$P) \llbracket \text{false} / \$wait \rrbracket \rangle \rangle \rangle$
 by (simp add: usubst unrest)
 also have ... = $\mathbf{R}_s (pre_R P \vdash ((cmt_R P) \llbracket \text{true} / \$wait \rrbracket \triangleleft \$wait \triangleright (cmt_R P) \llbracket \text{false} / \$wait \rrbracket))$
 by (simp add: ex-unrest assms)
 also have ... = $\mathbf{R}_s (pre_R P \vdash cmt_R P)$
 by (simp add: cond-var-split)
 also have ... = P
 by (simp add: SRD-reactive-design-alt assms(1))
 finally show ?thesis
 by (simp add: Healthy-def')
 qed

lemma *CSP4-RC-intro:*

assumes P is CSP $pre_R(P)$ is RC
 $\$st \# (cmt_R P) \llbracket \text{true} / \$wait \rrbracket \$ref \# (cmt_R P) \llbracket \text{false} / \$wait \rrbracket$
 shows P is CSP4

proof –

have $(\neg_r pre_R(P)) \;; R1(\text{true}) = (\neg_r pre_R(P))$
 by (metis (no-types, lifting) R1-seqr-closure assms(2) rea-not-R1 rea-not-false rea-not-not wp-rea-RC-false wp-rea-def)
 thus ?thesis
 by (simp add: CSP4-intro assms)
 qed

lemma *CSP4-rdes:*

assumes P is RR Q is RR R is RR
 shows $CSP4(\mathbf{R}_s(P \vdash Q \diamond R)) = \mathbf{R}_s ((\neg_r P) wp_r \text{false} \vdash ((\exists \$st \cdot Q) \diamond (\exists \$ref \cdot R)))$
 by (simp add: CSP4-def Skip-right-lemma closure assms rdes, rel-auto, blast+)

lemma *CSP4-form:*

assumes P is CSP
 shows $CSP4(P) = \mathbf{R}_s ((\neg_r pre_R P) wp_r \text{false} \vdash ((\exists \$st \cdot peri_R P) \diamond (\exists \$ref \cdot post_R P)))$
 by (simp add: CSP4-def Skip-right-tri-lemma assms)

lemma *Skip-srdes-right-unit:*

$(\text{Skip} \;; (\sigma, \varphi) \text{ action}) \;; II_R = \text{Skip}$
 by (rdes-simp)

lemma *Skip-srdes-left-unit:*

$II_R \;; (\text{Skip} \;; (\sigma, \varphi) \text{ action}) = \text{Skip}$
 by (rdes-eq)

lemma *CSP4-right-subsumes-RD3:* $RD3(CSP4(P)) = CSP4(P)$

by (metis (no-types, hide-lams) CSP4-def RD3-def Skip-srdes-right-unit seqr-assoc)

lemma *CSP4-implies-RD3:* P is CSP4 $\implies P$ is RD3

by (metis CSP4-right-subsumes-RD3 Healthy-def)

lemma *CSP4-tri-intro:*

assumes P is CSP $(\neg_r pre_R(P)) \;; R1(\text{true}) = (\neg_r pre_R(P)) \$st \# peri_R(P) \$ref \# post_R(P)$
 shows P is CSP4
 using assms
 by (rule-tac CSP4-intro, simp-all add: pre_R-def peri_R-def post_R-def usubst cmt_R-def)

lemma *CSP4-NSRD-intro:*

assumes P is NSRD $\$ref \# post_R(P)$
shows P is CSP4
by (*simp add: CSP4-tri-intro NSRD-is-SRD NSRD-neg-pre-unit NSRD-st'-unrest-peri assms*)

lemma *CSP3-commutes-CSP4*: $CSP3(CSP4(P)) = CSP4(CSP3(P))$
by (*simp add: CSP3-def CSP4-def seqr-assoc*)

lemma *NCSP-implies-CSP* [closure]: P is NCSP $\implies P$ is CSP
by (*metis (no-types, hide-lams) CSP3-def CSP4-def Healthy-def NCSP-def SRD-idem SRD-seqr-closure Skip-is-CSP comp-apply*)

lemma *NCSP-elim* [RD-elim]:
 $\llbracket X \text{ is NCSP}; P(\mathbf{R}_s(pre_R(X) \vdash peri_R(X) \diamond post_R(X))) \rrbracket \implies P(X)$
by (*simp add: SRD-reactive-tri-design closure*)

lemma *NCSP-implies-CSP3* [closure]:
 P is NCSP $\implies P$ is CSP3
by (*metis (no-types, lifting) CSP3-def Healthy-def' NCSP-def Skip-is-CSP Skip-left-unit-ref-unrest Skip-unrest-ref comp-apply seqr-assoc*)

lemma *NCSP-implies-CSP4* [closure]:
 P is NCSP $\implies P$ is CSP4
by (*metis (no-types, hide-lams) CSP3-commutes-CSP4 Healthy-def NCSP-def NCSP-implies-CSP NCSP-implies-CSP3 comp-apply*)

lemma *NCSP-implies-RD3* [closure]: P is NCSP $\implies P$ is RD3
by (*metis CSP3-commutes-CSP4 CSP4-right-subsumes-RD3 Healthy-def NCSP-def comp-apply*)

lemma *NCSP-implies-NSRD* [closure]: P is NCSP $\implies P$ is NSRD
by (*simp add: NCSP-implies-CSP NCSP-implies-RD3 SRD-RD3-implies-NSRD*)

lemma *NCSP-subset-implies-CSP* [closure]:
 $A \subseteq \llbracket NCSP \rrbracket_H \implies A \subseteq \llbracket CSP \rrbracket_H$
using *NCSP-implies-CSP* **by** *blast*

lemma *NCSP-subset-implies-NSRD* [closure]:
 $A \subseteq \llbracket NCSP \rrbracket_H \implies A \subseteq \llbracket NSRD \rrbracket_H$
using *NCSP-implies-NSRD* **by** *blast*

lemma *CSP-Healthy-subset-member*: $\llbracket P \in A; A \subseteq \llbracket CSP \rrbracket_H \rrbracket \implies P$ is CSP
by (*simp add: is-Healthy-subset-member*)

lemma *CSP3-Healthy-subset-member*: $\llbracket P \in A; A \subseteq \llbracket CSP3 \rrbracket_H \rrbracket \implies P$ is CSP3
by (*simp add: is-Healthy-subset-member*)

lemma *CSP4-Healthy-subset-member*: $\llbracket P \in A; A \subseteq \llbracket CSP4 \rrbracket_H \rrbracket \implies P$ is CSP4
by (*simp add: is-Healthy-subset-member*)

lemma *NCSP-Healthy-subset-member*: $\llbracket P \in A; A \subseteq \llbracket NCSP \rrbracket_H \rrbracket \implies P$ is NCSP
by (*simp add: is-Healthy-subset-member*)

lemma *NCSP-intro*:
assumes P is CSP P is CSP3 P is CSP4
shows P is NCSP
by (*metis Healthy-def NCSP-def assms comp-eq-dest-lhs*)

lemma *Skip-left-unit*: P is NCSP \implies Skip ;; $P = P$
 by (metis (full-types) CSP3-def Healthy-if NCSP-implies-CSP3)

lemma *Skip-right-unit*: P is NCSP \implies P ;; Skip = P
 by (metis (full-types) CSP4-def Healthy-if NCSP-implies-CSP4)

lemma *NCSP-NSRD-intro*:
 assumes P is NSRD $\$ref \# pre_R(P) \ \$ref \# peri_R(P) \ \$ref \# post_R(P) \ \$ref \# post_R(P)$
 shows P is NCSP
 by (simp add: CSP3-SRD-intro CSP4-NSRD-intro NCSP-intro NSRD-is-SRD assms)

lemma *CSP4-neg-pre-unit*:
 assumes P is CSP P is CSP4
 shows $(\neg_r pre_R(P))$;; $R1(true) = (\neg_r pre_R(P))$
 by (simp add: CSP4-implies-RD3 NSRD-neg-pre-unit SRD-RD3-implies-NSRD assms(1) assms(2))

lemma *NSRD-CSP4-intro*:
 assumes P is CSP P is CSP4
 shows P is NSRD
 by (simp add: CSP4-implies-RD3 SRD-RD3-implies-NSRD assms(1) assms(2))

lemma *NCSP-form*:
 $NCSP\ P = \mathbf{R}_s ((\forall \$ref \cdot (\neg_r pre_R(P))\ wp_r\ false) \vdash ((\exists \$ref \cdot \exists \$st \cdot peri_R(P)) \diamond (\exists \$ref \cdot \exists \$ref \cdot post_R(P))))$
proof –
 have $NCSP\ P = CSP3\ (CSP4\ (NSRD\ P))$
 by (metis (no-types, hide-lams) CSP4-def NCSP-def NSRD-alt-def RA1 RD3-def Skip-srdes-left-unit o-apply)
 also
 have $\dots = \mathbf{R}_s ((\forall \$ref \cdot (\neg_r pre_R\ (NSRD\ P))\ wp_r\ false) \vdash ((\exists \$ref \cdot \exists \$st \cdot peri_R\ (NSRD\ P)) \diamond (\exists \$ref \cdot \exists \$ref \cdot post_R\ (NSRD\ P))))$
 by (simp add: CSP3-form CSP4-form closure unrest rdes, rel-auto)
 also have $\dots = \mathbf{R}_s ((\forall \$ref \cdot (\neg_r pre_R(P))\ wp_r\ false) \vdash ((\exists \$ref \cdot \exists \$st \cdot peri_R(P)) \diamond (\exists \$ref \cdot \exists \$ref \cdot post_R(P))))$
 by (simp add: NSRD-form rdes closure, rel-blast)
 finally show ?thesis .
qed

lemma *CSP4-st'-unrest-peri* [unrest]:
 assumes P is CSP P is CSP4
 shows $\$st \# peri_R(P)$
 by (simp add: NSRD-CSP4-intro NSRD-st'-unrest-peri assms)

lemma *CSP4-healthy-form*:
 assumes P is CSP P is CSP4
 shows $P = \mathbf{R}_s ((\neg_r pre_R\ P)\ wp_r\ false \vdash ((\exists \$st \cdot peri_R(P)) \diamond (\exists \$ref \cdot post_R(P))))$
proof –
 have $P = \mathbf{R}_s ((\neg_r pre_R\ P)\ wp_r\ false \vdash ((\exists \$st \cdot cmt_R\ P) \triangleleft \$wait \triangleright (\exists \$ref \cdot cmt_R\ P)))$
 by (metis CSP4-def Healthy-def Skip-right-lemma assms(1) assms(2))
 also have $\dots = \mathbf{R}_s ((\neg_r pre_R\ P)\ wp_r\ false \vdash ((\exists \$st \cdot cmt_R\ P) \llbracket true/\$wait \rrbracket \triangleleft \$wait \triangleright (\exists \$ref \cdot cmt_R\ P) \llbracket false/\$wait \rrbracket))$
 by (metis (no-types, hide-lams) subst-wait'-left-subst subst-wait'-right-subst wait'-cond-def)
 also have $\dots = \mathbf{R}_s ((\neg_r pre_R\ P)\ wp_r\ false \vdash ((\exists \$st \cdot peri_R(P)) \diamond (\exists \$ref \cdot post_R(P))))$

by (simp add: wait'-cond-def usubst peri_R-def post_R-def cmt_R-def unrest)
 finally show ?thesis .
 qed

lemma CSP₄-ref'-unrest-pre [unrest]:

assumes P is CSP P is CSP₄

shows $\$ref \# pre_R(P)$

proof –

have $pre_R(P) = pre_R(\mathbf{R}_s((\neg_r pre_R P) wp_r false \vdash ((\exists \$st \cdot peri_R(P)) \diamond (\exists \$ref \cdot post_R(P)))))$

using CSP₄-healthy-form assms(1) assms(2) by fastforce

also have $\dots = (\neg_r pre_R P) wp_r false$

by (simp add: rea-pre-RHS-design wp-rea-def usubst unrest
 CSP₄-neg-pre-unit R1-rea-not R2c-preR R2c-rea-not assms)

also have $\$ref \# \dots$

by (simp add: wp-rea-def unrest)

finally show ?thesis .

qed

lemma NCSP-set-unrest-pre-wait':

assumes $A \subseteq \llbracket NCSP \rrbracket_H$

shows $\bigwedge P. P \in A \implies \$wait \# pre_R(P)$

proof –

fix P

assume $P \in A$

hence P is NSRD

using NCSP-implies-NSRD assms by auto

thus $\$wait \# pre_R(P)$

using NSRD-wait'-unrest-pre by blast

qed

lemma CSP₄-set-unrest-pre-st':

assumes $A \subseteq \llbracket CSP \rrbracket_H$ $A \subseteq \llbracket CSP_4 \rrbracket_H$

shows $\bigwedge P. P \in A \implies \$st \# pre_R(P)$

proof –

fix P

assume $P \in A$

hence P is NSRD

using NSRD-CSP₄-intro assms(1) assms(2) by blast

thus $\$st \# pre_R(P)$

using NSRD-st'-unrest-pre by blast

qed

lemma CSP₄-ref'-unrest-post [unrest]:

assumes P is CSP P is CSP₄

shows $\$ref \# post_R(P)$

proof –

have $post_R(P) = post_R(\mathbf{R}_s((\neg_r pre_R P) wp_r false \vdash ((\exists \$st \cdot peri_R(P)) \diamond (\exists \$ref \cdot post_R(P)))))$

using CSP₄-healthy-form assms(1) assms(2) by fastforce

also have $\dots = R1 (R2c ((\neg_r pre_R P) wp_r false \Rightarrow_r (\exists \$ref \cdot post_R P)))$

by (simp add: rea-post-RHS-design usubst unrest wp-rea-def)

also have $\$ref \# \dots$

by (simp add: R1-def R2c-def wp-rea-def unrest)

finally show ?thesis .

qed

lemma *CSP3-Chaos* [closure]: *Chaos is CSP3*
 by (simp add: *Chaos-def*, rule *CSP3-intro*, simp-all add: *RHS-design-is-SRD unrest*)

lemma *CSP4-Chaos* [closure]: *Chaos is CSP4*
 by (rule *CSP4-tri-intro*, simp-all add: *closure rdes unrest*)

lemma *NCSP-Chaos* [closure]: *Chaos is NCSP*
 by (simp add: *NCSP-intro closure*)

lemma *CSP3-Miracle* [closure]: *Miracle is CSP3*
 by (simp add: *Miracle-def*, rule *CSP3-intro*, simp-all add: *RHS-design-is-SRD unrest*)

lemma *CSP4-Miracle* [closure]: *Miracle is CSP4*
 by (rule *CSP4-tri-intro*, simp-all add: *closure rdes unrest*)

lemma *NCSP-Miracle* [closure]: *Miracle is NCSP*
 by (simp add: *NCSP-intro closure*)

lemma *NCSP-seqr-closure* [closure]:
 assumes *P is NCSP Q is NCSP*
 shows *P ;; Q is NCSP*
 by (metis (no-types, lifting) *CSP3-def CSP4-def Healthy-def' NCSP-implies-CSP NCSP-implies-CSP3 NCSP-implies-CSP4 NCSP-intro SRD-seqr-closure assms(1) assms(2) seqr-assoc*)

lemma *CSP4-Skip* [closure]: *Skip is CSP4*
 apply (rule *CSP4-intro*, simp-all add: *Skip-is-CSP*)
 apply (simp-all add: *Skip-def rea-pre-RHS-design rea-cmt-RHS-design usubst unrest R2c-true*)
 done

lemma *NCSP-Skip* [closure]: *Skip is NCSP*
 by (metis *CSP3-Skip CSP4-Skip Healthy-def NCSP-def Skip-is-CSP comp-apply*)

lemma *CSP4-Stop* [closure]: *Stop is CSP4*
 apply (rule *CSP4-intro*, simp-all add: *Stop-is-CSP*)
 apply (simp-all add: *Stop-def rea-pre-RHS-design rea-cmt-RHS-design usubst unrest R2c-true*)
 done

lemma *NCSP-Stop* [closure]: *Stop is NCSP*
 by (metis *CSP3-Stop CSP4-Stop Healthy-def NCSP-def Stop-is-CSP comp-apply*)

lemma *CSP4-Idempotent*: *Idempotent CSP4*
 by (metis (no-types, lifting) *CSP3-Skip CSP3-def CSP4-def Healthy-if Idempotent-def seqr-assoc*)

lemma *CSP4-Continuous*: *Continuous CSP4*
 by (simp add: *Continuous-def CSP4-def seq-Sup-distr*)

lemma *rdes-frame-ext-NCSP-closed* [closure]:
 assumes *vwb-lens a P is NCSP*
 shows *a:[P]_R⁺ is NCSP*
 by (metis (no-types, lifting) *CSP3-def CSP4-def Healthy-intro NCSP-Skip NCSP-implies-NSRD NCSP-intro NSRD-is-SRD Skip-frame Skip-left-unit Skip-right-unit assms(1) assms(2) rdes-frame-ext-NSRD-closed seq-srea-frame*)

lemma *preR-Stop* [rdes]: *pre_R(Stop) = true_r*
 by (simp add: *Stop-def Stop-is-CSP rea-pre-RHS-design unrest usubst R2c-true*)

lemma *periR-Stop* [rdes]: $\text{peri}_R(\text{Stop}) = \mathcal{E}(\text{true}, \llbracket \cdot \rrbracket, \{\}_u)$
by (*rel-auto*)

lemma *postR-Stop* [rdes]: $\text{post}_R(\text{Stop}) = \text{false}$
by (*rel-auto*)

lemma *cmtR-Stop* [rdes]: $\text{cmt}_R(\text{Stop}) = (\$tr =_u \$tr \wedge \$wait)$
by (*rel-auto*)

lemma *NCSP-Idempotent* [closure]: *Idempotent NCSP*
by (*clarsimp simp add: NCSP-def Idempotent-def*)
 (*metis (no-types, hide-lams) CSP3-Idempotent CSP3-def CSP4-Idempotent CSP4-def Healthy-def*
Idempotent-def SRD-idem SRD-seqr-closure Skip-is-CSP seqr-assoc)

lemma *NCSP-Continuous* [closure]: *Continuous NCSP*
by (*simp add: CSP3-Continuous CSP4-Continuous Continuous-comp NCSP-def SRD-Continuous*)

lemma *preR-CRR* [closure]: $P \text{ is NCSP} \implies \text{pre}_R(P) \text{ is CRR}$
by (*rule CRR-intro, simp-all add: closure unrest*)

lemma *periR-CRR* [closure]: $P \text{ is NCSP} \implies \text{peri}_R(P) \text{ is CRR}$
by (*rule CRR-intro, simp-all add: closure unrest*)

lemma *postR-CRR* [closure]: $P \text{ is NCSP} \implies \text{post}_R(P) \text{ is CRR}$
by (*rule CRR-intro, simp-all add: closure unrest*)

lemma *NCSP-rdes-intro* [closure]:
assumes $P \text{ is CRC } Q \text{ is CRR } R \text{ is CRR}$
 $\$st \# Q \$ref \# R$
shows $\mathbf{R}_s(P \vdash Q \diamond R) \text{ is NCSP}$
apply (*rule NCSP-intro*)
apply (*simp-all add: closure assms*)
apply (*rule CSP3-SRD-intro*)
apply (*simp-all add: rdes closure assms unrest*)
apply (*rule CSP4-tri-intro*)
apply (*simp-all add: rdes closure assms unrest*)
apply (*metis (no-types, lifting) CRC-implies-RC R1-seqr-closure assms(1) rea-not-R1 rea-not-false*
rea-not-not wp-rea-RC-false wp-rea-def)
done

lemma *NCSP-preR-CRC* [closure]:
assumes $P \text{ is NCSP}$
shows $\text{pre}_R(P) \text{ is CRC}$
by (*rule CRC-intro, simp-all add: closure assms unrest*)

lemma *NCSP-postR-CRF* [closure]: $P \text{ is NCSP} \implies \text{post}_R P \text{ is CRF}$
by (*rule CRF-intro, simp-all add: unrest closure*)

lemma *CSP3-Sup-closure* [closure]:
 $A \subseteq \llbracket \text{CSP3} \rrbracket_H \implies (\bigcap A) \text{ is CSP3}$
apply (*auto simp add: CSP3-def Healthy-def seq-Sup-distl*)
apply (*rule cong[of Sup]*)
apply (*simp*)
using *image-iff* **apply** *force*

done

lemma *CSP₄-Sup-closure* [closure]:
 $A \subseteq \llbracket \text{CSP}_4 \rrbracket_H \implies (\bigwedge A) \text{ is } \text{CSP}_4$
apply (auto simp add: CSP₄-def Healthy-def seq-Sup-distr)
apply (rule cong[of Sup])
apply (simp)
using image-iff **apply** force
done

lemma *NCSP-Sup-closure* [closure]: $\llbracket A \subseteq \llbracket \text{NCSP} \rrbracket_H; A \neq \{\} \rrbracket \implies (\bigwedge A) \text{ is } \text{NCSP}$
apply (rule NCSP-intro, simp-all add: closure)
apply (metis (no-types, lifting) Ball-Collect CSP₃-Sup-closure NCSP-implies-CSP₃)
apply (metis (no-types, lifting) Ball-Collect CSP₄-Sup-closure NCSP-implies-CSP₄)
done

lemma *NCSP-SUP-closure* [closure]: $\llbracket \bigwedge i. P(i) \text{ is } \text{NCSP}; A \neq \{\} \rrbracket \implies (\bigwedge i \in A. P(i)) \text{ is } \text{NCSP}$
by (metis (mono-tags, lifting) Ball-Collect NCSP-Sup-closure image-iff image-is-empty)

lemma *PCSP-implies-NCSP* [closure]:
assumes $P \text{ is } \text{PCSP}$
shows $P \text{ is } \text{NCSP}$

proof –

have $P = \text{Productive}(\text{NCSP}(\text{NCSP } P))$
by (metis (no-types, hide-lams) Healthy-def' Idempotent-def NCSP-Idempotent assms comp-apply)

also have $\dots = \mathbf{R}_s ((\forall \$ref \cdot (\neg_r \text{pre}_R(\text{NCSP } P)) \text{ wp}_r \text{ false}) \vdash$
 $(\exists \$ref \cdot \exists \$st \cdot \text{peri}_R(\text{NCSP } P)) \diamond$
 $((\exists \$ref \cdot \exists \$ref \cdot \text{post}_R(\text{NCSP } P)) \wedge \$tr <_u \$tr))$
by (simp add: NCSP-form Productive-RHS-design-form unrest closure)

also have $\dots \text{ is } \text{NCSP}$
apply (rule NCSP-rdes-intro)
apply (rule CRC-intro)
apply (simp-all add: unrest ex-unrest all-unrest closure)
done

finally show ?thesis .

qed

lemma *PCSP-elim* [RD-elim]:
assumes $X \text{ is } \text{PCSP}$ $P (\mathbf{R}_s ((\text{pre}_R X) \vdash \text{peri}_R X \diamond (R_4(\text{post}_R X))))$
shows $P X$
by (metis R₄-def Healthy-if NCSP-implies-CSP PCSP-implies-NCSP Productive-form assms comp-apply)

lemma *R5-alt-def*: $R_5(P) = (P \wedge \$tr =_u \$tr)$
by rel-auto

lemma *ICSP-implies-NCSP* [closure]:
assumes $P \text{ is } \text{ICSP}$
shows $P \text{ is } \text{NCSP}$

proof –

have $P = \text{ISRDI}(\text{NCSP}(\text{NCSP } P))$
by (metis (no-types, hide-lams) Healthy-def' Idempotent-def NCSP-Idempotent assms comp-apply)

also have $\dots = \text{ISRDI} (\mathbf{R}_s ((\forall \$ref \cdot (\neg_r \text{pre}_R(\text{NCSP } P)) \text{ wp}_r \text{ false}) \vdash$
 $(\exists \$ref \cdot \exists \$st \cdot \text{peri}_R(\text{NCSP } P)) \diamond$
 $(\exists \$ref \cdot \exists \$ref \cdot \text{post}_R(\text{NCSP } P))))$

by (simp add: NCSP-form)
 also have ... = $\mathbf{R}_s ((\forall \$ref \cdot (\neg_r pre_R(NCSP P)) wp_r false) \vdash$
 $false \diamond$
 $((\exists \$ref \cdot \exists \$ref \cdot post_R(NCSP P)) \wedge \$tr =_u \$tr))$
 by (simp-all add: ISRD1-RHS-design-form R5-alt-def closure rdes unrest)
 also have ... is NCSP
 apply (rule NCSP-rdes-intro)
 apply (rule CRC-intro)
 apply (simp-all add: unrest ex-unrest all-unrest closure)
 done
 finally show ?thesis .
 qed

lemma ICSP-implies-ISRD [closure]:
 assumes P is ICSP
 shows P is ISRD
 by (metis (no-types, hide-lams) Healthy-def ICSP-implies-NCSP ISRD-def NCSP-implies-NSRD assms comp-apply)

lemma ICSP-elim [RD-elim]:
 assumes X is ICSP $P (\mathbf{R}_s ((pre_R X) \vdash false \diamond R5(post_R X)))$
 shows $P X$
 by (metis Healthy-if NCSP-implies-CSP ICSP-implies-NCSP ISRD1-form assms comp-apply)

lemma ICSP-Stop-right-zero-lemma:
 $(P \wedge (\$tr =_u \$tr)) ;; true_r = true_r \implies (P \wedge (\$tr =_u \$tr)) ;; (\$tr =_u \$tr) = (\$tr =_u \$tr)$
 by (rel-blast)

lemma ICSP-Stop-right-zero:
 assumes P is ICSP $pre_R(P) = true_r post_R(P) ;; true_r = true_r$
 shows $P ;; Stop = Stop$
proof –
 from assms(3) have 1: $(post_R P \wedge \$tr =_u \$tr) ;; true_r = true_r$
 by (rel-auto, metis (full-types, hide-lams) dual-order.antisym order-refl)
 show ?thesis
 by (rdes-simp cls: assms(1), simp add: R5-alt-def csp-enable-nothing assms(2) ICSP-Stop-right-zero-lemma[OF 1])
 qed

lemma ICSP-intro: $\llbracket P \text{ is NCSP}; P \text{ is ISRD1} \rrbracket \implies P \text{ is ICSP}$
 using Healthy-comp by blast

lemma seq-ICSP-closed [closure]:
 assumes P is ICSP Q is ICSP
 shows $P ;; Q$ is ICSP
 by (meson ICSP-implies-ISRD ICSP-implies-NCSP ICSP-intro ISRD-implies-ISRD1 NCSP-seqr-closure assms seq-ISRD-closed)

lemma Miracle-ICSP [closure]: *Miracle is ICSP*
 by (rule ICSP-intro, simp add: closure, simp add: ISRD1-rdes-intro rdes-def closure)

5.2 CSP theories

lemma NCSP-false: $NCSP \text{ false} = \text{Miracle}$
 by (simp add: NCSP-def srdes-theory.healthy-top[THEN sym], simp add: closure Healthy-if)

lemma *NCSP-true*: *NCSP true = Chaos*

by (*simp add: NCSP-def srdes-theory.healthy-bottom[THEN sym]*, *simp add: closure Healthy-if*)

interpretation *csp-theory*: *utp-theory-kleene NCSP Skip*

rewrites $P \in \text{carrier } \text{csp-theory.thy-order} \longleftrightarrow P \text{ is NCSP}$

and $\text{carrier } \text{csp-theory.thy-order} \rightarrow \text{carrier } \text{csp-theory.thy-order} \equiv \llbracket \text{NCSP} \rrbracket_H \rightarrow \llbracket \text{NCSP} \rrbracket_H$

and $\text{le } \text{csp-theory.thy-order} = (\sqsubseteq)$

and $\text{eq } \text{csp-theory.thy-order} = (=)$

and *csp-top*: *csp-theory.utp-top = Miracle*

and *csp-bottom*: *csp-theory.utp-bottom = Chaos*

proof –

have *utp-theory-continuous NCSP*

by (*unfold-locales*, *simp-all add: Healthy-Idempotent Healthy-if NCSP-Idempotent NCSP-Continuous*)

then **interpret** *utp-theory-continuous NCSP*

by *simp*

show *t*: *utp-top = Miracle* and *b*:*utp-bottom = Chaos*

by (*simp-all add: healthy-top healthy-bottom NCSP-false NCSP-true*)

show *utp-theory-kleene NCSP Skip*

by (*unfold-locales*, *simp-all add: closure Skip-left-unit Skip-right-unit Miracle-left-zero t*)

qed (*simp-all*)

abbreviation *TestC* (*test_C*) **where**

test_C P $\equiv \text{csp-theory.utp-test } P$

definition *StarC* :: (σ , φ) *action* \Rightarrow (σ , φ) *action* ($^{-\star C}$ [999] 999) **where**

StarC P $\equiv \text{csp-theory.utp-star } P$

lemma *StarC-unfold*: $P \text{ is NCSP} \Longrightarrow P^{\star C} = \text{Skip} \sqcap (P ;; P^{\star C})$

by (*simp add: StarC-def csp-theory.Star-unfoldl-eq*)

lemma *sfrd-star-as-rdes-star*:

$P \text{ is NCSP} \Longrightarrow P^{\star R} ;; \text{Skip} = P^{\star C}$

by (*simp add: csp-theory.Star-alt-def nsrdes-theory.Star-alt-def StarC-def StarR-def closure unrest Skip-srdes-left-unit csp-theory.Unit-Right*)

lemma *sfrd-star-as-rdes-star'*:

$P \text{ is NCSP} \Longrightarrow \text{Skip} ;; P^{\star R} = P^{\star C}$

by (*simp add: csp-theory.Star-alt-def nsrdes-theory.Star-alt-def StarC-def StarR-def closure unrest Skip-srdes-right-unit csp-theory.Unit-Left upred-semiring.distrib-left*)

theorem *csp-star-rdes-def* [*rdes-def*]:

assumes $P \text{ is CRC } Q \text{ is CRR } R \text{ is CRF } \$st \# Q$

shows $(\mathbf{R}_s(P \vdash Q \diamond R))^{\star C} = \mathbf{R}_s(R^{\star c} \text{ wp}_r P \vdash (R^{\star c} ;; Q) \diamond R^{\star c})$

apply (*simp add: wp-rea-def sfrd-star-as-rdes-star[THEN sym] crf-star-as-rea-star assms seqr-assoc rpred closure unrest StarR-rdes-def*)

apply (*simp add: rdes-def assms closure unrest wp-rea-def[THEN sym]*)

apply (*simp add: wp rpred assms closure*)

apply (*simp add: csp-do-nothing*)

done

5.3 Algebraic laws

lemma *Stop-left-zero*:

assumes $P \text{ is CSP}$

shows $\text{Stop} ;; P = \text{Stop}$

by (*simp add: NSRD-seq-post-false assms NCSP-implies-NSRD NCSP-Stop postR-Stop*)

end

6 Stateful-Failure Reactive Contracts

theory *utp-sfrd-contracts*
imports *utp-sfrd-healths*
begin

definition *mk-CRD* :: '*s upred* \Rightarrow ('*e list* \Rightarrow '*e set* \Rightarrow '*s upred*) \Rightarrow ('*e list* \Rightarrow '*s hrel*) \Rightarrow ('*s*, '*e*) *action*
where
[rdes-def]: *mk-CRD* *P Q R* = $\mathbf{R}_s([P]_{S<} \vdash [Q \ x \ r]_{S<} \llbracket x \rightarrow \&tt \rrbracket \llbracket r \rightarrow \$ref \rrbracket \diamond [R(x)]_S' \llbracket x \rightarrow \&tt \rrbracket)$

syntax
-ref-var :: *logic*
-mk-CRD :: *logic* \Rightarrow *logic* \Rightarrow *logic* \Rightarrow *logic* (*[-/* \vdash *-/* $|$ *-]*_{*C*})

parse-translation \langle
let
fun *ref-var-tr* [] = *Syntax.free refs*
| ref-var-tr - = *raise Match*;
in
[@{syntax-const -ref-var}, K ref-var-tr]
end
 \rangle

translations
-mk-CRD *P Q R* \Rightarrow *CONST mk-CRD* *P* (λ *-trace-var -ref-var.* *Q*) (λ *-trace-var.* *R*)
-mk-CRD *P Q R* \Leftarrow *CONST mk-CRD* *P* (λ *x r.* *Q*) (λ *y.* *R*)

lemma *CSP-mk-CRD* [*closure*]: $[P \vdash Q \text{ trace refs} \mid R(\text{trace})]_C$ is *CSP*
by (*simp add: mk-CRD-def closure unrest*)

lemma *preR-mk-CRD* [*rdes*]: $\text{pre}_R([P \vdash Q \text{ trace refs} \mid R(\text{trace})]_C) = [P]_{S<}$
by (*simp add: mk-CRD-def rea-pre-RHS-design usubst unrest R2c-not R2c-lift-state-pre rea-st-cond-def, rel-auto*)

lemma *periR-mk-CRD* [*rdes*]: $\text{peri}_R([P \vdash Q \text{ trace refs} \mid R(\text{trace})]_C) = ([P]_{S<} \Rightarrow_r ([Q \text{ trace refs}]_{S<} \llbracket (\text{trace}, \text{refs}) \rightarrow (\&tt, \$ref) \rrbracket))$
by (*simp add: mk-CRD-def rea-peri-RHS-design usubst unrest R2c-not R2c-lift-state-pre impl-alt-def R2c-disj R2c-msubst-tt R1-disj, rel-auto*)

lemma *postR-mk-CRD* [*rdes*]: $\text{post}_R([P \vdash Q \text{ trace refs} \mid R(\text{trace})]_C) = ([P]_{S<} \Rightarrow_r ([R(\text{trace})]_S' \llbracket \text{trace} \rightarrow \&tt \rrbracket))$
by (*simp add: mk-CRD-def rea-post-RHS-design usubst unrest R2c-not R2c-lift-state-pre impl-alt-def R2c-disj R2c-msubst-tt R1-disj, rel-auto*)

Refinement introduction law for contracts

lemma *CRD-contract-refine*:

assumes
 Q is *CSP* ' $[P_1]_{S<} \Rightarrow \text{pre}_R Q$ '
 $'[P_1]_{S<} \wedge \text{peri}_R Q \Rightarrow [P_2 \ t \ r]_{S<} \llbracket t \rightarrow \&tt \rrbracket \llbracket r \rightarrow \$ref \rrbracket'$
 $'[P_1]_{S<} \wedge \text{post}_R Q \Rightarrow [P_3 \ x]_S \llbracket x \rightarrow \&tt \rrbracket'$
shows $[P_1 \vdash P_2 \text{ trace refs} \mid P_3(\text{trace})]_C \sqsubseteq Q$
proof –
have $[P_1 \vdash P_2 \text{ trace refs} \mid P_3(\text{trace})]_C \sqsubseteq \mathbf{R}_s(\text{pre}_R(Q) \vdash \text{peri}_R(Q) \diamond \text{post}_R(Q))$
using *assms* **by** (*simp add: mk-CRD-def, rule-tac sdes-tri-refine-intro, rel-auto+*)

thus *?thesis*
 by (simp add: SRD-reactive-tri-design assms(1))
 qed

lemma CRD-contract-refine':

assumes
 Q is CSP $\lceil P_1 \rceil_{S<} \Rightarrow pre_R Q$
 $\lceil P_2 \ x \ r \rceil_{S<} \llbracket t \rightarrow \& tt \rrbracket \llbracket r \rightarrow \$ref \rrbracket \sqsubseteq (\lceil P_1 \rceil_{S<} \wedge peri_R Q)$
 $\lceil P_3 \ x \rceil_S \llbracket x \rightarrow \& tt \rrbracket \sqsubseteq (\lceil P_1 \rceil_{S<} \wedge post_R Q)$
 shows $\lceil P_1 \rceil \vdash P_2 \text{ trace refs } \mid P_3(\text{trace}) \rceil_C \sqsubseteq Q$
 using assms by (rule-tac CRD-contract-refine, simp-all add: refBy-order)

lemma CRD-refine-CRD:

assumes
 $\lceil P_1 \rceil_{S<} \Rightarrow (\lceil Q_1 \rceil_{S<} :: ('e, 's) \text{ action})$
 $(\lceil P_2 \ x \ r \rceil_{S<} \llbracket x \rightarrow \& tt \rrbracket \llbracket r \rightarrow \$ref \rrbracket) \sqsubseteq (\lceil P_1 \rceil_{S<} \wedge \lceil Q_2 \ x \ r \rceil_{S<} \llbracket x \rightarrow \& tt \rrbracket \llbracket r \rightarrow \$ref \rrbracket :: ('e, 's) \text{ action})$
 $\lceil P_3 \ x \rceil_S \llbracket x \rightarrow \& tt \rrbracket \sqsubseteq (\lceil P_1 \rceil_{S<} \wedge \lceil Q_3 \ x \rceil_S \llbracket x \rightarrow \& tt \rrbracket :: ('e, 's) \text{ action})$
 shows $(\lceil P_1 \rceil \vdash P_2 \text{ trace refs } \mid P_3 \text{ trace}) \rceil_C :: ('e, 's) \text{ action} \sqsubseteq \lceil Q_1 \rceil \vdash Q_2 \text{ trace refs } \mid Q_3 \text{ trace} \rceil_C$
 using assms
 by (simp add: mk-CRD-def, rule-tac srdes-tri-refine-intro, rel-auto+)

lemma CRD-refine-rdes:

assumes
 $\lceil P_1 \rceil_{S<} \Rightarrow Q_1$
 $(\lceil P_2 \ x \ r \rceil_{S<} \llbracket x \rightarrow \& tt \rrbracket \llbracket r \rightarrow \$ref \rrbracket) \sqsubseteq (\lceil P_1 \rceil_{S<} \wedge Q_2)$
 $\lceil P_3 \ x \rceil_S \llbracket x \rightarrow \& tt \rrbracket \sqsubseteq (\lceil P_1 \rceil_{S<} \wedge Q_3)$
 shows $(\lceil P_1 \rceil \vdash P_2 \text{ trace refs } \mid P_3 \text{ trace}) \rceil_C :: ('e, 's) \text{ action} \sqsubseteq \mathbf{R}_s(Q_1 \vdash Q_2 \diamond Q_3)$
 using assms
 by (simp add: mk-CRD-def, rule-tac srdes-tri-refine-intro, rel-auto+)

lemma CRD-refine-rdes':

assumes
 Q_2 is RR
 Q_3 is RR
 $\lceil P_1 \rceil_{S<} \Rightarrow Q_1$
 $\bigwedge t. (\lceil P_2 \ t \ r \rceil_{S<} \llbracket r \rightarrow \$ref \rrbracket) \sqsubseteq (\lceil P_1 \rceil_{S<} \wedge Q_2 \llbracket \llbracket \cdot \rrbracket, \llbracket t \rrbracket / \$tr, \$tr \rrbracket)$
 $\bigwedge t. \lceil P_3 \ t \rceil_{S'} \sqsubseteq (\lceil P_1 \rceil_{S<} \wedge Q_3 \llbracket \llbracket \cdot \rrbracket, \llbracket t \rrbracket / \$tr, \$tr \rrbracket)$
 shows $(\lceil P_1 \rceil \vdash P_2 \text{ trace refs } \mid P_3 \text{ trace}) \rceil_C :: ('e, 's) \text{ action} \sqsubseteq \mathbf{R}_s(Q_1 \vdash Q_2 \diamond Q_3)$
 proof (simp add: mk-CRD-def, rule srdes-tri-refine-intro)
 show $\lceil P_1 \rceil_{S<} \Rightarrow Q_1$ by (fact assms(3))

have $\bigwedge t. (\lceil P_2 \ t \ r \rceil_{S<} \llbracket r \rightarrow \$ref \rrbracket) \sqsubseteq (\lceil P_1 \rceil_{S<} \wedge (RR \ Q_2) \llbracket \llbracket \cdot \rrbracket, \llbracket t \rrbracket / \$tr, \$tr \rrbracket)$
 by (simp add: assms Healthy-if)
 hence $\lceil P_1 \rceil_{S<} \wedge RR(Q_2) \Rightarrow \lceil P_2 \ x \ r \rceil_{S<} \llbracket x \rightarrow \& tt \rrbracket \llbracket r \rightarrow \$ref \rrbracket$
 by (rel-simp; meson)
 thus $\lceil P_1 \rceil_{S<} \wedge Q_2 \Rightarrow \lceil P_2 \ x \ r \rceil_{S<} \llbracket x \rightarrow \& tt \rrbracket \llbracket r \rightarrow \$ref \rrbracket$
 by (simp add: Healthy-if assms)

have $\bigwedge t. \lceil P_3 \ t \rceil_{S'} \sqsubseteq (\lceil P_1 \rceil_{S<} \wedge (RR \ Q_3) \llbracket \llbracket \cdot \rrbracket, \llbracket t \rrbracket / \$tr, \$tr \rrbracket)$
 by (simp add: assms Healthy-if)
 hence $\lceil P_1 \rceil_{S<} \wedge (RR \ Q_3) \Rightarrow \lceil P_3 \ x \rceil_S \llbracket x \rightarrow \& tt \rrbracket$
 by (rel-simp; meson)
 thus $\lceil P_1 \rceil_{S<} \wedge Q_3 \Rightarrow \lceil P_3 \ x \rceil_S \llbracket x \rightarrow \& tt \rrbracket$

by (simp add: Healthy-if assms)
qed
end

7 External Choice

theory utp-sfrd-extchoice
imports
 utp-sfrd-healths
 utp-sfrd-rel
begin

7.1 Definitions and syntax

definition *EXTCHOICE* :: 'a set \Rightarrow ('a \Rightarrow (' σ , ' φ) action) \Rightarrow (' σ , ' φ) action **where**
ExtChoice-def [upred-defs]: *EXTCHOICE* A F = $\mathbf{R}_s((\bigsqcup P \in A \cdot \text{pre}_R(F P)) \vdash ((\bigsqcup P \in A \cdot \text{cmt}_R(F P)) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\bigsqcup P \in A \cdot \text{cmt}_R(F P))))$

abbreviation *ExtChoice* :: (' σ , ' φ) action set \Rightarrow (' σ , ' φ) action **where**
ExtChoice A \equiv *EXTCHOICE* A id

syntax

-*ExtChoice* :: ptnr \Rightarrow 'a set \Rightarrow 'b \Rightarrow 'b (($\exists \square \text{ -- } \cdot / \text{ --}$) [0, 0, 10] 10)
-*ExtChoice-simp* :: ptnr \Rightarrow 'b \Rightarrow 'b (($\exists \square \text{ -- } \cdot / \text{ --}$) [0, 10] 10)

translations

$\square P \in A \cdot B \quad \Rightarrow \quad \text{CONST } \text{EXTCHOICE } A (\lambda P. B)$
 $\square P \cdot B \quad \Rightarrow \quad \text{CONST } \text{EXTCHOICE } (\text{CONST UNIV}) (\lambda P. B)$

definition *extChoice* ::

(' σ , ' φ) action \Rightarrow (' σ , ' φ) action \Rightarrow (' σ , ' φ) action (**infixl** \square 59) **where**
[upred-defs]: $P \square Q \equiv \text{ExtChoice } \{P, Q\}$

Small external choice as an indexed big external choice.

lemma *extChoice-alt-def*:

$P \square Q = (\square i :: \text{nat} \in \{0, 1\} \cdot P \triangleleft \langle i = 0 \rangle \triangleright Q)$
by (simp add: extChoice-def ExtChoice-def)

7.2 Basic laws

7.3 Algebraic laws

lemma *ExtChoice-empty*: *EXTCHOICE* {} F = Stop
by (simp add: ExtChoice-def cond-def Stop-def)

lemma *ExtChoice-single*:

$P \text{ is CSP} \Rightarrow \text{ExtChoice } \{P\} = P$
by (simp add: ExtChoice-def usup-and uinf-or SRD-reactive-design-alt)

7.4 Reactive design calculations

lemma *ExtChoice-rdes*:

assumes $\bigwedge i. \$ok \nmid P(i) \ A \neq \{\}$
shows $(\square i \in A \cdot \mathbf{R}_s(P(i) \vdash Q(i))) = \mathbf{R}_s((\bigsqcup i \in A \cdot P(i)) \vdash ((\bigsqcup i \in A \cdot Q(i)) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\bigsqcup i \in A \cdot Q(i))))$

proof –

have $(\Box i \in A \cdot \mathbf{R}_s(P(i) \vdash Q(i))) =$
 $\mathbf{R}_s((\Box i \in A \cdot \text{pre}_R(\mathbf{R}_s(P(i) \vdash Q(i)))) \vdash$
 $((\Box i \in A \cdot \text{cmt}_R(\mathbf{R}_s(P(i) \vdash Q(i))))$
 $\triangleleft \$tr =_u \$tr \wedge \$wait \triangleright$
 $(\Box i \in A \cdot \text{cmt}_R(\mathbf{R}_s(P(i) \vdash Q(i))))$
 by (simp add: ExtChoice-def)
 also have ... =
 $\mathbf{R}_s((\Box i \in A \cdot R1(R2c(\text{pre}_s \dagger P(i)))) \vdash$
 $((\Box i \in A \cdot R1(R2c(\text{cmt}_s \dagger (P(i) \Rightarrow Q(i))))$
 $\triangleleft \$tr =_u \$tr \wedge \$wait \triangleright$
 $(\Box i \in A \cdot R1(R2c(\text{cmt}_s \dagger (P(i) \Rightarrow Q(i))))$
 by (simp add: rea-pre-RHS-design rea-cmt-RHS-design)
 also have ... =
 $\mathbf{R}_s((\Box i \in A \cdot R1(R2c(\text{pre}_s \dagger P(i)))) \vdash$
 $R1(R2c$
 $((\Box i \in A \cdot R1(R2c(\text{cmt}_s \dagger (P(i) \Rightarrow Q(i))))$
 $\triangleleft \$tr =_u \$tr \wedge \$wait \triangleright$
 $(\Box i \in A \cdot R1(R2c(\text{cmt}_s \dagger (P(i) \Rightarrow Q(i))))$
 by (metis (no-types, lifting) RHS-design-export-R1 RHS-design-export-R2c)
 also have ... =
 $\mathbf{R}_s((\Box i \in A \cdot R1(R2c(\text{pre}_s \dagger P(i)))) \vdash$
 $R1(R2c$
 $((\Box i \in A \cdot (\text{cmt}_s \dagger (P(i) \Rightarrow Q(i))))$
 $\triangleleft \$tr =_u \$tr \wedge \$wait \triangleright$
 $(\Box i \in A \cdot (\text{cmt}_s \dagger (P(i) \Rightarrow Q(i))))$
 by (simp add: R2c-UNIF R2c-cond R1-cond R1-idem R1-R2c-commute R2c-idem R1-UNIF assms
 R1-USUP R2c-USUP)
 also have ... =
 $\mathbf{R}_s((\Box i \in A \cdot R1(R2c(\text{pre}_s \dagger P(i)))) \vdash$
 $\text{cmt}_s \dagger$
 $((\Box i \in A \cdot (\text{cmt}_s \dagger (P(i) \Rightarrow Q(i))))$
 $\triangleleft \$tr =_u \$tr \wedge \$wait \triangleright$
 $(\Box i \in A \cdot (\text{cmt}_s \dagger (P(i) \Rightarrow Q(i))))$
 by (metis (no-types, lifting) RHS-design-export-R1 RHS-design-export-R2c rdes-export-cmt)
 also have ... =
 $\mathbf{R}_s((\Box i \in A \cdot R1(R2c(\text{pre}_s \dagger P(i)))) \vdash$
 $\text{cmt}_s \dagger$
 $((\Box i \in A \cdot (P(i) \Rightarrow Q(i))))$
 $\triangleleft \$tr =_u \$tr \wedge \$wait \triangleright$
 $(\Box i \in A \cdot (P(i) \Rightarrow Q(i))))$
 by (simp add: usubst)
 also have ... =
 $\mathbf{R}_s((\Box i \in A \cdot R1(R2c(\text{pre}_s \dagger P(i)))) \vdash$
 $((\Box i \in A \cdot (P(i) \Rightarrow Q(i))) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\Box i \in A \cdot (P(i) \Rightarrow Q(i))))$
 by (simp add: rdes-export-cmt)
 also have ... =
 $\mathbf{R}_s((R1(R2c(\Box i \in A \cdot (\text{pre}_s \dagger P(i)))) \vdash$
 $((\Box i \in A \cdot (P(i) \Rightarrow Q(i))) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\Box i \in A \cdot (P(i) \Rightarrow Q(i))))$
 by (simp add: not-UNIF R1-UNIF R2c-UNIF assms)
 also have ... =
 $\mathbf{R}_s((R2c(\Box i \in A \cdot (\text{pre}_s \dagger P(i)))) \vdash$
 $((\Box i \in A \cdot (P(i) \Rightarrow Q(i))) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\Box i \in A \cdot (P(i) \Rightarrow Q(i))))$
 by (simp add: R1-design-R1-pre)
 also have ... =

$\mathbf{R}_s ((\sqcup i \in A \cdot (pre_s \uparrow P(i))) \vdash$
 $(\sqcup i \in A \cdot (P(i) \Rightarrow Q(i))) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\sqcap i \in A \cdot (P(i) \Rightarrow Q(i))))$
 by (*metis (no-types, lifting) RHS-design-R2c-pre*)
 also have ... =
 $\mathbf{R}_s (([\$ok \mapsto_s true, \$wait \mapsto_s false] \uparrow (\sqcup i \in A \cdot P(i))) \vdash$
 $(\sqcup i \in A \cdot (P(i) \Rightarrow Q(i))) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\sqcap i \in A \cdot (P(i) \Rightarrow Q(i))))$
 proof –
 from *assms* have $\bigwedge i. pre_s \uparrow P(i) = [\$ok \mapsto_s true, \$wait \mapsto_s false] \uparrow P(i)$
 by (*rel-auto*)
 thus ?thesis
 by (*simp add: usubst*)
 qed
 also have ... =
 $\mathbf{R}_s ((\sqcup i \in A \cdot P(i)) \vdash ((\sqcup i \in A \cdot (P(i) \Rightarrow Q(i))) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\sqcap i \in A \cdot (P(i) \Rightarrow Q(i))))$
 by (*simp add: rdes-export-pre not-UINF*)
 also have ... = $\mathbf{R}_s ((\sqcup i \in A \cdot P(i)) \vdash ((\sqcup i \in A \cdot Q(i)) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\sqcap i \in A \cdot Q(i))))$
 by (*rule cong[of $\mathbf{R}_s \mathbf{R}_s$], simp, rel-auto, blast+*)

finally show ?thesis .

qed

lemma *ExtChoice-tri-rdes*:

assumes $\bigwedge i. \$ok \nmid P_1(i) \ A \neq \{\}$
 shows $(\sqcap i \in A \cdot \mathbf{R}_s(P_1(i) \vdash P_2(i) \diamond P_3(i))) =$
 $\mathbf{R}_s ((\sqcup i \in A \cdot P_1(i)) \vdash ((\sqcup i \in A \cdot P_2(i)) \triangleleft \$tr =_u \$tr \triangleright (\sqcap i \in A \cdot P_2(i))) \diamond (\sqcap i \in A \cdot P_3(i)))$

proof –

have $(\sqcap i \in A \cdot \mathbf{R}_s(P_1(i) \vdash P_2(i) \diamond P_3(i))) =$
 $\mathbf{R}_s ((\sqcup i \in A \cdot P_1(i)) \vdash ((\sqcup i \in A \cdot P_2(i) \diamond P_3(i)) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\sqcap i \in A \cdot P_2(i) \diamond$
 $P_3(i))))$
 by (*simp add: ExtChoice-rdes assms*)

also

have ... =

$\mathbf{R}_s ((\sqcup i \in A \cdot P_1(i)) \vdash ((\sqcup i \in A \cdot P_2(i) \diamond P_3(i)) \triangleleft \$wait \wedge \$tr =_u \$tr \triangleright (\sqcap i \in A \cdot P_2(i) \diamond$
 $P_3(i))))$
 by (*simp add: conj-comm*)

also

have ... =

$\mathbf{R}_s ((\sqcup i \in A \cdot P_1(i)) \vdash (((\sqcup i \in A \cdot P_2(i) \diamond P_3(i)) \triangleleft \$tr =_u \$tr \triangleright (\sqcap i \in A \cdot P_2(i) \diamond P_3(i))) \diamond$
 $(\sqcap i \in A \cdot P_2(i) \diamond P_3(i))))$
 by (*simp add: cond-conj wait'-cond-def*)

also

have ... = $\mathbf{R}_s ((\sqcup i \in A \cdot P_1(i)) \vdash (((\sqcup i \in A \cdot P_2(i)) \triangleleft \$tr =_u \$tr \triangleright (\sqcap i \in A \cdot P_2(i))) \diamond (\sqcap i \in A \cdot$
 $P_3(i))))$
 by (*rule cong[of $\mathbf{R}_s \mathbf{R}_s$], simp, rel-auto*)

finally show ?thesis .

qed

lemma *ExtChoice-tri-rdes' [rdes-def]*:

assumes $\bigwedge i. \$ok \nmid P_1(i) \ A \neq \{\}$
 shows $(\sqcap i \in A \cdot \mathbf{R}_s(P_1(i) \vdash P_2(i) \diamond P_3(i))) =$
 $\mathbf{R}_s ((\sqcup i \in A \cdot P_1(i)) \vdash (((\sqcup i \in A \cdot R5(P_2(i))) \vee (\sqcap i \in A \cdot R4(P_2(i)))) \diamond (\sqcap i \in A \cdot P_3(i))))$
 by (*simp add: ExtChoice-tri-rdes assms, rel-auto, simp-all add: less-le assms*)

lemma *ExtChoice-tri-rdes-def*:

assumes $\bigwedge i. i \in A \implies F \ i \text{ is CSP}$

shows $(\Box i \in A \cdot F i) = \mathbf{R}_s ((\Box P \in A \cdot pre_R (F P)) \vdash (((\Box P \in A \cdot peri_R (F P)) \triangleleft \$tr =_u \$tr \triangleright (\Box P \in A \cdot peri_R (F P))) \diamond (\Box P \in A \cdot post_R (F P))))$

proof –

have $((\Box P \in A \cdot cmt_R (F P)) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\Box P \in A \cdot cmt_R (F P))) =$
 $((\Box P \in A \cdot cmt_R (F P)) \triangleleft \$tr =_u \$tr \triangleright (\Box P \in A \cdot cmt_R (F P))) \diamond (\Box P \in A \cdot cmt_R (F P))$
by *(rel-auto)*
also have $\dots = (((\Box P \in A \cdot peri_R (F P)) \triangleleft \$tr =_u \$tr \triangleright (\Box P \in A \cdot peri_R (F P))) \diamond (\Box P \in A \cdot post_R (F P)))$
by *(rel-auto)*
finally show *?thesis*
by *(simp add: ExtChoice-def)*
qed

lemma *extChoice-rdes*:

assumes $\$ok \nmid P_1 \ \$ok \nmid Q_1$
shows $\mathbf{R}_s(P_1 \vdash P_2) \Box \mathbf{R}_s(Q_1 \vdash Q_2) = \mathbf{R}_s((P_1 \wedge Q_1) \vdash ((P_2 \wedge Q_2) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (P_2 \vee Q_2)))$
proof –
have $(\Box i :: nat \in \{0, 1\} \cdot \mathbf{R}_s(P_1 \vdash P_2) \triangleleft \langle i = 0 \rangle \triangleright \mathbf{R}_s(Q_1 \vdash Q_2)) = (\Box i :: nat \in \{0, 1\} \cdot \mathbf{R}_s((P_1 \vdash P_2) \triangleleft \langle i = 0 \rangle \triangleright (Q_1 \vdash Q_2)))$
by *(simp only: RHS-cond R2c-lit)*
also have $\dots = (\Box i :: nat \in \{0, 1\} \cdot \mathbf{R}_s((P_1 \triangleleft \langle i = 0 \rangle \triangleright Q_1) \vdash (P_2 \triangleleft \langle i = 0 \rangle \triangleright Q_2)))$
by *(simp add: design-cond)*
also have $\dots = \mathbf{R}_s((P_1 \wedge Q_1) \vdash ((P_2 \wedge Q_2) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (P_2 \vee Q_2)))$
by *(subst ExtChoice-rdes, simp-all add: assms unrest uinf-or usup-and)*
finally show *?thesis* **by** *(simp add: extChoice-alt-def)*
qed

lemma *extChoice-tri-rdes*:

assumes $\$ok \nmid P_1 \ \$ok \nmid Q_1$
shows $\mathbf{R}_s(P_1 \vdash P_2 \diamond P_3) \Box \mathbf{R}_s(Q_1 \vdash Q_2 \diamond Q_3) =$
 $\mathbf{R}_s((P_1 \wedge Q_1) \vdash (((P_2 \wedge Q_2) \triangleleft \$tr =_u \$tr \triangleright (P_2 \vee Q_2)) \diamond (P_3 \vee Q_3)))$
proof –
have $\mathbf{R}_s(P_1 \vdash P_2 \diamond P_3) \Box \mathbf{R}_s(Q_1 \vdash Q_2 \diamond Q_3) =$
 $\mathbf{R}_s((P_1 \wedge Q_1) \vdash ((P_2 \diamond P_3 \wedge Q_2 \diamond Q_3) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (P_2 \diamond P_3 \vee Q_2 \diamond Q_3)))$
by *(simp add: extChoice-rdes assms)*
also
have $\dots = \mathbf{R}_s((P_1 \wedge Q_1) \vdash ((P_2 \diamond P_3 \wedge Q_2 \diamond Q_3) \triangleleft \$wait \wedge \$tr =_u \$tr \triangleright (P_2 \diamond P_3 \vee Q_2 \diamond Q_3)))$
by *(simp add: conj-comm)*
also
have $\dots = \mathbf{R}_s((P_1 \wedge Q_1) \vdash$
 $((P_2 \diamond P_3 \wedge Q_2 \diamond Q_3) \triangleleft \$tr =_u \$tr \triangleright (P_2 \diamond P_3 \vee Q_2 \diamond Q_3)) \diamond (P_2 \diamond P_3 \vee Q_2 \diamond Q_3))$
by *(simp add: cond-conj wait'-cond-def)*
also
have $\dots = \mathbf{R}_s((P_1 \wedge Q_1) \vdash (((P_2 \wedge Q_2) \triangleleft \$tr =_u \$tr \triangleright (P_2 \vee Q_2)) \diamond (P_3 \vee Q_3)))$
by *(rule cong[of $\mathbf{R}_s \ \mathbf{R}_s$], simp, rel-auto)*
finally show *?thesis* .
qed

lemma *extChoice-rdes-def*:

assumes $P_1 \text{ is } RR \ Q_1 \text{ is } RR$
shows $\mathbf{R}_s(P_1 \vdash P_2 \diamond P_3) \Box \mathbf{R}_s(Q_1 \vdash Q_2 \diamond Q_3) =$
 $\mathbf{R}_s((P_1 \wedge Q_1) \vdash (((P_2 \wedge Q_2) \triangleleft \$tr =_u \$tr \triangleright (P_2 \vee Q_2)) \diamond (P_3 \vee Q_3)))$
by *(subst extChoice-tri-rdes, simp-all add: assms unrest)*

lemma *extChoice-rdes-def'* [rdes-def]:

assumes P_1 is RR Q_1 is RR

shows $\mathbf{R}_s(P_1 \vdash P_2 \diamond P_3) \sqcap \mathbf{R}_s(Q_1 \vdash Q_2 \diamond Q_3) =$

$\mathbf{R}_s((P_1 \wedge Q_1) \vdash ((R5(P_2 \wedge Q_2) \vee R4(P_2 \vee Q_2)) \diamond (P_3 \vee Q_3)))$

by (*simp add: extChoice-rdes-def assms, rel-auto, simp-all add: less-le*)

lemma *CSP-ExtChoice* [closure]:

EXTCHOICE A F is CSP

by (*simp add: ExtChoice-def RHS-design-is-SRD unrest*)

lemma *CSP-extChoice* [closure]:

$P \sqcap Q$ is CSP

by (*simp add: CSP-ExtChoice extChoice-def*)

lemma *preR-EXTCHOICE* [rdes]:

assumes $A \neq \{\}$ $\bigwedge i. i \in A \implies F i$ is NCSP

shows $\text{pre}_R(\text{EXTCHOICE } A F) = (\bigsqcup P \in A \cdot \text{pre}_R(F P))$

by (*simp add: ExtChoice-tri-rdes-def closure rdes assms*)

lemma *preR-ExtChoice*:

assumes $A \neq \{\}$ $\forall P \in A. P$ is NCSP

shows $\text{pre}_R(\text{ExtChoice } A) = (\bigsqcup P \in A \cdot \text{pre}_R(P))$

using *assms* **by** (*auto simp add: preR-EXTCHOICE*)

lemma *periR-ExtChoice* [rdes]:

assumes $A \neq \{\}$ $\bigwedge i. i \in A \implies F i$ is NCSP

shows $\text{peri}_R(\text{EXTCHOICE } A F) = (((\bigsqcup P \in A \cdot \text{pre}_R(F P)) \Rightarrow_r (\bigsqcup P \in A \cdot \text{peri}_R(F P))) \triangleleft U(\$tr = \$tr) \triangleright (\bigsqcup P \in A \cdot \text{peri}_R(F P)))$

(*is ?lhs = ?rhs*)

proof –

have *?lhs* = $((\bigsqcup P \in A \cdot \text{pre}_R(F P)) \Rightarrow_r (\bigsqcup P \in A \cdot \text{peri}_R(F P)) \triangleleft U(\$tr = \$tr) \triangleright (\bigsqcup P \in A \cdot \text{peri}_R(F P)))$

by (*simp add: ExtChoice-tri-rdes-def closure rdes assms*)

also have ... = $((\bigsqcup P \in A \cdot \text{pre}_R(F P)) \Rightarrow_r (\bigsqcup P \in A \cdot \text{pre}_R(F P) \Rightarrow_r \text{peri}_R(F P)) \triangleleft U(\$tr = \$tr) \triangleright (\bigsqcup P \in A \cdot \text{peri}_R(F P) \Rightarrow_r \text{peri}_R(F P)))$

by (*simp add: NSRD-peri-under-pre assms closure cong: UINF-cong USUP-cong*)

also have ... = $((\bigsqcup P \in A \cdot \text{RR}(\text{pre}_R(F P))) \Rightarrow_r (\bigsqcup P \in A \cdot \text{RR}(\text{pre}_R(F P)) \Rightarrow_r \text{RR}(\text{peri}_R(F P))) \triangleleft U(\$tr = \$tr) \triangleright (\bigsqcup P \in A \cdot \text{RR}(\text{pre}_R(F P)) \Rightarrow_r \text{RR}(\text{peri}_R(F P))))$

by (*simp add: Healthy-if assms closure cong: UINF-cong USUP-cong*)

also from *assms*(1) **have** ... = $((\bigsqcup P \in A \cdot \text{RR}(\text{pre}_R(F P))) \Rightarrow_r (\bigsqcup P \in A \cdot \text{RR}(\text{pre}_R(F P)) \Rightarrow_r \text{RR}(\text{peri}_R(F P)))) \triangleleft U(\$tr = \$tr) \triangleright ((\bigsqcup P \in A \cdot \text{RR}(\text{pre}_R(F P)) \Rightarrow_r \text{RR}(\text{peri}_R(F P))))$

by (*rel-auto*)

finally show *?thesis*

by (*simp add: Healthy-if NSRD-peri-under-pre assms closure cong: UINF-cong USUP-cong*)

qed

lemma *periR-ExtChoice'*:

assumes $A \neq \{\}$ $\bigwedge i. i \in A \implies F i$ is NCSP

shows $\text{peri}_R(\text{EXTCHOICE } A F) = (R5((\bigsqcup P \in A \cdot \text{pre}_R(F P)) \Rightarrow_r (\bigsqcup P \in A \cdot \text{peri}_R(F P))) \vee R4(\bigsqcup P \in A \cdot \text{peri}_R(F P)))$

by (*simp add: periR-ExtChoice assms, rel-auto*)

lemma *postR-ExtChoice* [rdes]:

assumes $A \neq \{\}$ $\bigwedge i. i \in A \implies F i$ is NCSP

shows $\text{post}_R(\text{EXTCHOICE } A F) = (\bigsqcap P \in A \cdot \text{post}_R(F P))$

(is ?lhs = ?rhs)

proof –

have ?lhs = $((\bigsqcup P \in A \cdot \text{pre}_R(F P)) \Rightarrow_r (\bigsqcup P \in A \cdot \text{post}_R(F P)))$

by (simp add: ExtChoice-tri-rdes-def closure rdes assms)

also have ... = $((\bigsqcup P \in A \cdot \text{pre}_R(F P)) \Rightarrow_r (\bigsqcup P \in A \cdot \text{pre}_R(F P) \Rightarrow_r \text{post}_R(F P)))$

by (simp add: NSRD-post-under-pre assms closure cong: UINF-cong)

also have ... = $(\bigsqcup P \in A \cdot \text{pre}_R(F P) \Rightarrow_r \text{post}_R(F P))$

by (rel-auto)

finally show ?thesis

by (simp add: NSRD-post-under-pre assms closure cong: UINF-cong)

qed

lemma preR-extChoice' [rdes]:

assumes P is NCSP Q is NCSP

shows $\text{pre}_R(P \sqcap Q) = (\text{pre}_R(P) \wedge \text{pre}_R(Q))$

by (simp add: extChoice-def preR-ExtChoice assms closure usup-and)

lemma periR-extChoice [rdes]:

assumes P is NCSP Q is NCSP

shows $\text{peri}_R(P \sqcap Q) = ((\text{pre}_R(P) \wedge \text{pre}_R(Q) \Rightarrow_r \text{peri}_R(P) \wedge \text{peri}_R(Q)) \triangleleft \$tr =_u \$tr \triangleright (\text{peri}_R(P) \vee \text{peri}_R(Q)))$

using assms

by (simp add: extChoice-def, subst periR-ExtChoice, auto simp add: usup-and uinf-or)

lemma postR-extChoice [rdes]:

assumes P is NCSP Q is NCSP

shows $\text{post}_R(P \sqcap Q) = (\text{post}_R(P) \vee \text{post}_R(Q))$

using assms

by (simp add: extChoice-def, subst postR-ExtChoice, auto simp add: usup-and uinf-or)

lemma ExtChoice-cong:

assumes $\bigwedge P. P \in A \implies F(P) = G(P)$

shows $(\bigsqcup P \in A \cdot F(P)) = (\bigsqcup P \in A \cdot G(P))$

by (simp add: ExtChoice-def assms cong: UINF-cong USUP-cong)

lemma ref-unrest-ExtChoice:

assumes

$\bigwedge P. P \in A \implies \$ref \# \text{pre}_R(P)$

$\bigwedge P. P \in A \implies \$ref \# \text{cmt}_R(P)$

shows $\$ref \# (\text{ExtChoice } A) \llbracket \text{false} / \$wait \rrbracket$

proof –

have $\bigwedge P. P \in A \implies \$ref \# \text{pre}_R(P \llbracket 0 / \$tr \rrbracket)$

using assms **by** (rel-blast)

with assms **show** ?thesis

by (simp add: ExtChoice-def RHS-def R1-def R2c-def R2s-def R3h-def design-def usubst unrest)

qed

lemma CSP4-ExtChoice:

assumes $\bigwedge i. i \in A \implies F i$ is NCSP

shows EXTCHOICE $A F$ is CSP4

proof (cases $A = \{\}$)

case True **thus** ?thesis

by (simp add: ExtChoice-empty Healthy-def CSP4-def, simp add: Skip-is-CSP Stop-left-zero)

next

case False

```

have 1: (¬r (¬r preR (EXTCHOICE A F)) ;;h R1 true) = preR (EXTCHOICE A F)
proof -
  have ∧ P. P ∈ A ⇒ (¬r preR(F P)) ;; R1 true = (¬r preR(F P))
    by (simp add: NCSP-Healthy-subset-member NCSP-implies-NSRD NSRD-neg-pre-unit assms)
  thus ?thesis
    apply (simp add: False preR-EXTCHOICE closure NCSP-set-unrest-pre-wait' assms not-UINF
seq-UINF-distr not-USUP)
    apply (rule USUP-cong)
    apply (simp add: rpred assms closure)
    done
qed
have 2: $st # periR (EXTCHOICE A F)
proof -
  have a: ∧ P. P ∈ A ⇒ $st # preR(F P)
    by (simp add: NCSP-Healthy-subset-member NCSP-implies-NSRD NSRD-st'-unrest-pre assms)
  have b: ∧ P. P ∈ A ⇒ $st # periR(F P)
    by (simp add: NCSP-Healthy-subset-member NCSP-implies-NSRD NSRD-st'-unrest-peri assms)
  from a b show ?thesis
    apply (subst periR-ExtChoice)
    apply (simp-all add: assms closure unrest CSP4-set-unrest-pre-st' NCSP-set-unrest-pre-wait'
False)
    done
qed
have 3: $ref # postR (EXTCHOICE A F)
proof -
  have a: ∧ P. P ∈ A ⇒ $ref # preR(F P)
    by (simp add: CSP4-ref'-unrest-pre assms closure)
  have b: ∧ P. P ∈ A ⇒ $ref # postR(F P)
    by (simp add: CSP4-ref'-unrest-post assms closure)
  from a b show ?thesis
    by (subst postR-ExtChoice, simp-all add: assms CSP4-set-unrest-pre-st' NCSP-set-unrest-pre-wait'
unrest False)
qed
show ?thesis
  by (rule CSP4-tri-intro, simp-all add: 1 2 3 assms closure)
  (metis 1 R1-seqr-closure rea-not-R1 rea-not-not rea-true-R1)
qed

lemma CSP4-extChoice [closure]:
  assumes P is NCSP Q is NCSP
  shows P □ Q is CSP4
  by (simp add: extChoice-def, rule CSP4-ExtChoice, auto simp add: assms)

lemma NCSP-ExtChoice [closure]:
  assumes ∧ i. i ∈ A ⇒ F i is NCSP
  shows EXTCHOICE A F is NCSP
proof (cases A = {})
  case True
  then show ?thesis by (simp add: ExtChoice-empty closure)
next
  case False
  show ?thesis
  proof (rule NCSP-intro)
    show 1: EXTCHOICE A F is CSP
      by (metis (mono-tags) CSP-ExtChoice)
  end
end

```

show *EXTCHOICE A F is CSP3*
by (*rule-tac CSP3-SRD-intro, simp-all add: CSP-Healthy-subset-member CSP3-Healthy-subset-member*
closure rdes unrest assms 1 False)
show *EXTCHOICE A F is CSP4*
by (*simp add: CSP4-ExtChoice assms*)
qed
qed

lemma *ExtChoice-NCSP-closed [closure]:*
assumes $\bigwedge i. i \in I \implies P(i) \text{ is NCSP}$
shows $(\bigwedge i \in I. P(i)) \text{ is NCSP}$
by (*simp add: NCSP-ExtChoice assms image-subset-iff*)

lemma *NCSP-extChoice [closure]:*
assumes *P is NCSP Q is NCSP*
shows $P \sqsubseteq Q \text{ is NCSP}$
unfolding *extChoice-def*
by (*auto intro: NCSP-ExtChoice simp add: assms*)

7.5 Productivity and Guardedness

lemma *Productive-ExtChoice [closure]:*
assumes $\bigwedge i. i \in I \implies P(i) \text{ is NCSP} \wedge i. i \in I \implies P(i) \text{ is Productive}$
shows *EXTCHOICE I P is Productive*

proof (*cases I = {}*)

case *True*

then show *?thesis*

by (*simp add: ExtChoice-empty Productive-Stop*)

next

case *False*

have $1: \bigwedge i. i \in I \implies \$wait \nmid pre_R(P i)$

using *NCSP-implies-NSRD NSRD-wait'-unrest-pre assms(1)* **by** *blast*

show *?thesis*

proof (*rule Productive-intro, simp-all add: assms closure rdes unrest 1 False*)

have $((\bigwedge i \in I. pre_R(P i)) \wedge (\bigwedge i \in I. post_R(P i))) =$
 $((\bigwedge i \in I. pre_R(P i)) \wedge (\bigwedge i \in I. (pre_R(P i) \wedge post_R(P i))))$

by (*rel-auto*)

moreover have $(\bigwedge i \in I. (pre_R(P i) \wedge post_R(P i))) = (\bigwedge i \in I. ((pre_R(P i) \wedge post_R(P i)) \wedge$
 $\$tr <_u \$tr))$

by (*rule UINF-cong, metis (no-types, lifting) 1 NCSP-implies-CSP Productive-post-refines-tr-increase*
assms utp-pred-laws.inf.absorb1)

ultimately show $U(\$tr < \$tr) \sqsubseteq ((\bigwedge i \in I. pre_R(P i)) \wedge (\bigwedge i \in I. post_R(P i)))$

by (*rel-auto*)

qed

qed

lemma *Productive-extChoice [closure]:*
assumes *P is NCSP Q is NCSP P is Productive Q is Productive*
shows $P \sqsubseteq Q \text{ is Productive}$
unfolding *extChoice-def*
by (*auto intro: Productive-ExtChoice simp add: assms*)

lemma *ExtChoice-Guarded [closure]:*
assumes $\bigwedge P. P \in A \implies \text{Guarded } P$

```

shows Guarded ( $\lambda X. \Box P \in A \cdot P(X)$ )
proof (rule GuardedI)
  fix  $X\ n$ 
  have  $\bigwedge Y. ((\Box P \in A \cdot P\ Y) \wedge \text{gvert}(n+1)) = ((\Box P \in A \cdot (P\ Y \wedge \text{gvert}(n+1))) \wedge \text{gvert}(n+1))$ 
  proof –
    fix  $Y$ 
    let  $?lhs = ((\Box P \in A \cdot P\ Y) \wedge \text{gvert}(n+1))$  and  $?rhs = ((\Box P \in A \cdot (P\ Y \wedge \text{gvert}(n+1))) \wedge \text{gvert}(n+1))$ 
    have  $a: ?lhs \llbracket \text{false} / \$ok \rrbracket = ?rhs \llbracket \text{false} / \$ok \rrbracket$ 
      by (rel-auto)
    have  $b: ?lhs \llbracket \text{true} / \$ok \rrbracket \llbracket \text{true} / \$wait \rrbracket = ?rhs \llbracket \text{true} / \$ok \rrbracket \llbracket \text{true} / \$wait \rrbracket$ 
      by (rel-auto)
    have  $c: ?lhs \llbracket \text{true} / \$ok \rrbracket \llbracket \text{false} / \$wait \rrbracket = ?rhs \llbracket \text{true} / \$ok \rrbracket \llbracket \text{false} / \$wait \rrbracket$ 
      by (simp add: ExtChoice-def RHS-def R1-def R2c-def R2s-def R3h-def design-def usubst unrest, rel-blast)
    show  $?lhs = ?rhs$ 
      using  $a\ b\ c$ 
      by (rule-tac bool-eq-splitI[of in-var ok], simp, rule-tac bool-eq-splitI[of in-var wait], simp-all)
  qed
  moreover have  $((\Box P \in A \cdot (P\ X \wedge \text{gvert}(n+1))) \wedge \text{gvert}(n+1)) = ((\Box P \in A \cdot (P\ (X \wedge \text{gvert}(n))) \wedge \text{gvert}(n+1))) \wedge \text{gvert}(n+1))$ 
  proof –
    have  $(\Box P \in A \cdot (P\ X \wedge \text{gvert}(n+1))) = (\Box P \in A \cdot (P\ (X \wedge \text{gvert}(n)) \wedge \text{gvert}(n+1)))$ 
    proof (rule ExtChoice-cong)
      fix  $P$  assume  $P \in A$ 
      thus  $(P\ X \wedge \text{gvert}(n+1)) = (P\ (X \wedge \text{gvert}(n)) \wedge \text{gvert}(n+1))$ 
        using Guarded-def assms by blast
    qed
    thus  $?thesis$  by simp
  qed
  ultimately show  $((\Box P \in A \cdot P\ X) \wedge \text{gvert}(n+1)) = ((\Box P \in A \cdot (P\ (X \wedge \text{gvert}(n)))) \wedge \text{gvert}(n+1))$ 
    by simp
qed

```

lemma *ExtChoice-image*: $\text{ExtChoice } (P \text{ ‘ } A) = \text{EXTCHOICE } A\ P$
by (*rel-auto*)

lemma *extChoice-Guarded* [*closure*]:
assumes *Guarded* P *Guarded* Q
shows *Guarded* ($\lambda X. P(X) \Box Q(X)$)
proof –
have *Guarded* ($\lambda X. \Box F \in \{P, Q\} \cdot F(X)$)
by (*rule ExtChoice-Guarded, auto simp add: assms*)
thus $?thesis$
by (*subst (asm) ExtChoice-image[THEN sym], simp add: extChoice-def*)
qed

7.6 Algebraic laws

lemma *extChoice-comm*:
 $P \Box Q = Q \Box P$
by (*unfold extChoice-def, simp add: insert-commute*)

lemma *extChoice-idem*:
 $P \text{ is CSP} \implies P \Box P = P$
by (*unfold extChoice-def, simp add: ExtChoice-single*)

lemma *extChoice-assoc*:

assumes *P is CSP Q is CSP R is CSP*

shows $P \sqcap Q \sqcap R = P \sqcap (Q \sqcap R)$

proof –

have $P \sqcap Q \sqcap R = \mathbf{R}_s(\text{pre}_R(P) \vdash \text{cmt}_R(P)) \sqcap \mathbf{R}_s(\text{pre}_R(Q) \vdash \text{cmt}_R(Q)) \sqcap \mathbf{R}_s(\text{pre}_R(R) \vdash \text{cmt}_R(R))$

by (*simp add: SRD-reactive-design-alt assms(1) assms(2) assms(3)*)

also have ... =

$\mathbf{R}_s(((\text{pre}_R P \wedge \text{pre}_R Q) \wedge \text{pre}_R R) \vdash$
 $((\text{cmt}_R P \wedge \text{cmt}_R Q) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\text{cmt}_R P \vee \text{cmt}_R Q) \wedge \text{cmt}_R R)$
 $\triangleleft \$tr =_u \$tr \wedge \$wait \triangleright$
 $((\text{cmt}_R P \wedge \text{cmt}_R Q) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\text{cmt}_R P \vee \text{cmt}_R Q) \vee \text{cmt}_R R)))$

by (*simp add: extChoice-rdes unrest*)

also have ... =

$\mathbf{R}_s(((\text{pre}_R P \wedge \text{pre}_R Q) \wedge \text{pre}_R R) \vdash$
 $((\text{cmt}_R P \wedge \text{cmt}_R Q) \wedge \text{cmt}_R R)$
 $\triangleleft \$tr =_u \$tr \wedge \$wait \triangleright$
 $((\text{cmt}_R P \vee \text{cmt}_R Q) \vee \text{cmt}_R R)))$

by (*rule cong[of $\mathbf{R}_s \mathbf{R}_s$], simp, rel-auto*)

also have ... =

$\mathbf{R}_s((\text{pre}_R P \wedge \text{pre}_R Q \wedge \text{pre}_R R) \vdash$
 $((\text{cmt}_R P \wedge (\text{cmt}_R Q \wedge \text{cmt}_R R))$
 $\triangleleft \$tr =_u \$tr \wedge \$wait \triangleright$
 $(\text{cmt}_R P \vee (\text{cmt}_R Q \vee \text{cmt}_R R))))$

by (*simp add: conj-assoc disj-assoc*)

also have ... =

$\mathbf{R}_s((\text{pre}_R P \wedge \text{pre}_R Q \wedge \text{pre}_R R) \vdash$
 $((\text{cmt}_R P \wedge (\text{cmt}_R Q \wedge \text{cmt}_R R)) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\text{cmt}_R Q \vee \text{cmt}_R R))$
 $\triangleleft \$tr =_u \$tr \wedge \$wait \triangleright$
 $(\text{cmt}_R P \vee (\text{cmt}_R Q \wedge \text{cmt}_R R) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\text{cmt}_R Q \vee \text{cmt}_R R))))$

by (*rule cong[of $\mathbf{R}_s \mathbf{R}_s$], simp, rel-auto*)

also have ... = $\mathbf{R}_s(\text{pre}_R(P) \vdash \text{cmt}_R(P)) \sqcap (\mathbf{R}_s(\text{pre}_R(Q) \vdash \text{cmt}_R(Q)) \sqcap \mathbf{R}_s(\text{pre}_R(R) \vdash \text{cmt}_R(R)))$

by (*simp add: extChoice-rdes unrest*)

also have ... = $P \sqcap (Q \sqcap R)$

by (*simp add: SRD-reactive-design-alt assms(1) assms(2) assms(3)*)

finally show *?thesis* .

qed

lemma *extChoice-Stop*:

assumes *Q is CSP*

shows $\text{Stop} \sqcap Q = Q$

using *assms*

proof –

have $\text{Stop} \sqcap Q = \mathbf{R}_s(\text{true} \vdash (\$tr =_u \$tr \wedge \$wait)) \sqcap \mathbf{R}_s(\text{pre}_R(Q) \vdash \text{cmt}_R(Q))$

by (*simp add: Stop-def SRD-reactive-design-alt assms*)

also have ... = $\mathbf{R}_s(\text{pre}_R Q \vdash (((\$tr =_u \$tr \wedge \$wait) \wedge \text{cmt}_R Q) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\$tr =_u \$tr \wedge \$wait \vee \text{cmt}_R Q)))$

by (*simp add: extChoice-rdes unrest*)

also have ... = $\mathbf{R}_s(\text{pre}_R Q \vdash (\text{cmt}_R Q \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright \text{cmt}_R Q))$

by (*metis (no-types, lifting) cond-def eq-upred-sym neg-conj-cancel1 utp-pred-laws.inf.left-idem*)

also have ... = $\mathbf{R}_s(\text{pre}_R Q \vdash \text{cmt}_R Q)$

by (*simp add: cond-idem*)

also have ... = Q

by (*simp add: SRD-reactive-design-alt assms*)

finally show *?thesis* .

qed

lemma *extChoice-Chaos*:

assumes Q is CSP

shows $\text{Chaos} \sqcap Q = \text{Chaos}$

proof –

have $\text{Chaos} \sqcap Q = \mathbf{R}_s(\text{false} \vdash \text{true}) \sqcap \mathbf{R}_s(\text{pre}_R(Q) \vdash \text{cmt}_R(Q))$
 by (simp add: Chaos-def SRD-reactive-design-alt assms)
 also have $\dots = \mathbf{R}_s(\text{false} \vdash (\text{cmt}_R Q \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright \text{true}))$
 by (simp add: extChoice-rdes unrest)
 also have $\dots = \mathbf{R}_s(\text{false} \vdash \text{true})$
 by (rule cong[of $\mathbf{R}_s \mathbf{R}_s$], simp, rel-auto)
 also have $\dots = \text{Chaos}$
 by (simp add: Chaos-def)
 finally show ?thesis .

qed

lemma *extChoice-Dist*:

assumes P is CSP $S \subseteq \llbracket \text{CSP} \rrbracket_H S \neq \{\}$

shows $P \sqcap (\bigsqcup S) = (\bigsqcup_{Q \in S} P \sqcap Q)$

proof –

let $?S1 = \text{pre}_R \text{ ' } S$ and $?S2 = \text{cmt}_R \text{ ' } S$
 have $P \sqcap (\bigsqcup S) = P \sqcap (\bigsqcup_{Q \in S} \mathbf{R}_s(\text{pre}_R(Q) \vdash \text{cmt}_R(Q)))$
 by (simp add: SRD-as-reactive-design[THEN sym] Healthy-SUPREMUM UINF-as-Sup-collect assms)
 also have $\dots = \mathbf{R}_s(\text{pre}_R(P) \vdash \text{cmt}_R(P)) \sqcap \mathbf{R}_s((\bigsqcup_{Q \in S} \text{pre}_R(Q)) \vdash (\bigsqcup_{Q \in S} \text{cmt}_R(Q)))$
 by (simp add: RHS-design-USUP SRD-reactive-design-alt assms)
 also have $\dots = \mathbf{R}_s((\text{pre}_R(P) \wedge (\bigsqcup_{Q \in S} \text{pre}_R(Q))) \vdash$
 $((\text{cmt}_R(P) \wedge (\bigsqcup_{Q \in S} \text{cmt}_R(Q)))$
 $\triangleleft \$tr =_u \$tr \wedge \$wait \triangleright$
 $(\text{cmt}_R(P) \vee (\bigsqcup_{Q \in S} \text{cmt}_R(Q))))$
 by (simp add: extChoice-rdes unrest)
 also have $\dots = \mathbf{R}_s((\bigsqcup_{Q \in S} \text{pre}_R P \wedge \text{pre}_R Q) \vdash$
 $(\bigsqcup_{Q \in S} (\text{cmt}_R P \wedge \text{cmt}_R Q) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\text{cmt}_R P \vee \text{cmt}_R Q)))$
 by (simp add: conj-USUP-dist conj-UINF-dist disj-UINF-dist cond-UINF-dist assms)
 also have $\dots = (\bigsqcup_{Q \in S} \mathbf{R}_s((\text{pre}_R P \wedge \text{pre}_R Q) \vdash$
 $((\text{cmt}_R P \wedge \text{cmt}_R Q) \triangleleft \$tr =_u \$tr \wedge \$wait \triangleright (\text{cmt}_R P \vee \text{cmt}_R Q))))$
 by (simp add: assms RHS-design-USUP)
 also have $\dots = (\bigsqcup_{Q \in S} \mathbf{R}_s(\text{pre}_R(P) \vdash \text{cmt}_R(P)) \sqcap \mathbf{R}_s(\text{pre}_R(Q) \vdash \text{cmt}_R(Q)))$
 by (simp add: extChoice-rdes unrest)
 also have $\dots = (\bigsqcup_{Q \in S} P \sqcap \text{CSP}(Q))$
 by (simp add: UINF-as-Sup-collect, metis (no-types, lifting) Healthy-if SRD-as-reactive-design
 assms(1))
 also have $\dots = (\bigsqcup_{Q \in S} P \sqcap Q)$
 by (rule SUP-cong, simp-all add: Healthy-subset-member[OF assms(2)])
 finally show ?thesis .

qed

lemma *extChoice-dist*:

assumes P is CSP Q is CSP R is CSP

shows $P \sqcap (Q \sqcap R) = (P \sqcap Q) \sqcap (P \sqcap R)$

using assms extChoice-Dist[of $P \{Q, R\}$] by simp

lemma *ExtChoice-seq-distr*:

assumes $\bigwedge i. i \in A \implies P \text{ i is PCSP } Q \text{ is NCSP}$

shows $(\bigsqcup_{i \in A} P \text{ i}) ;; Q = (\bigsqcup_{i \in A} P \text{ i}) ;; Q$

proof (cases $A = \{\}$)

```

case True
then show ?thesis
  by (simp add: ExtChoice-empty NCSP-implies-CSP Stop-left-zero assms(2))
next
case False
show ?thesis
proof –
  have 1: ( $\Box i \in A \cdot P i$ ) = ( $\Box i \in A \cdot (\mathbf{R}_s ((pre_R (P i)) \vdash peri_R (P i) \diamond (R4(post_R (P i)))))$ )
    (is ?X = ?Y)
  by (rule ExtChoice-cong, metis (no-types, hide-lams) R4-def Healthy-if NCSP-implies-CSP PCSP-implies-NCSP
Productive-form assms(1) comp-apply)
  have 2: ( $\Box i \in A \cdot P i ;; Q$ ) = ( $\Box i \in A \cdot (\mathbf{R}_s ((pre_R (P i)) \vdash peri_R (P i) \diamond (R4(post_R (P i))))) ;; Q$ )
    (is ?X = ?Y)
  by (rule ExtChoice-cong, metis (no-types, hide-lams) R4-def Healthy-if NCSP-implies-CSP PCSP-implies-NCSP
Productive-form assms(1) comp-apply)
  show ?thesis
  by (simp add: 1 2, rdes-eq cls: assms False cong: ExtChoice-cong USUP-cong)
qed
qed

lemma extChoice-seq-distr:
assumes P is PCSP Q is PCSP R is NCSP
shows ( $P \Box Q$ ) ;;  $R = (P ;; R \Box Q ;; R)$ 
by (rdes-eq' cls: assms)

lemma extChoice-seq-distl:
assumes P is ICSP Q is ICSP R is NCSP
shows  $P ;; (Q \Box R) = (P ;; Q \Box P ;; R)$ 
by (rdes-eq cls: assms)

lemma extchoice-StateInvR-refine:
assumes
  P is NCSP Q is NCSP
   $sinv_R(b) \sqsubseteq P sinv_R(b) \sqsubseteq Q$ 
shows  $sinv_R(b) \sqsubseteq P \Box Q$ 
proof –
  have P is R2 Q is R2 by (simp-all add: closure assms)
  hence 1:
     $pre_R P \sqsubseteq [b]_{S<} [b]_{S>} \sqsubseteq ([b]_{S<} \wedge post_R P)$ 
     $pre_R Q \sqsubseteq [b]_{S<} [b]_{S>} \sqsubseteq ([b]_{S<} \wedge post_R Q)$ 
  by (metis (no-types, lifting) CRR-implies-RR NCSP-implies-CSP RHS-tri-design-refine SRD-reactive-tri-design
StateInvR-def assms periR-RR postR-RR preR-CRR rea-st-cond-RR rea-true-RR refBy-order st-post-CRR) +
  show ?thesis
  by (rdes-refine-split cls: assms(1–2), simp-all add: 1 closure assms truer-bottom-rpred utp-pred-laws.inf-sup-distrib1)
qed

end

```

8 Stateful-Failure Programs

```

theory utp-sfrd-prog
imports
  UTP.utp-full
  utp-sfrd-extchoice
begin

```

8.1 Conditionals

lemma *NCSP-cond-srea* [closure]:
assumes P is NCSP Q is NCSP
shows $P \triangleleft b \triangleright_R Q$ is NCSP
by (rule NCSP-NSRD-intro, simp-all add: closure rdes assms unrest)

8.2 Guarded commands

lemma *GuardedCommR-NCSP-closed* [closure]:
assumes P is NCSP
shows $g \rightarrow_R P$ is NCSP
by (simp add: gcmd-def closure assms)

8.3 Alternation

lemma *AlternateR-NCSP-closed* [closure]:
assumes $\bigwedge i. i \in A \implies P(i)$ is NCSP Q is NCSP
shows $(\text{if}_R i \in A \cdot g(i) \rightarrow P(i) \text{ else } Q \text{ fi})$ is NCSP
proof (cases $A = \{\}$)
case *True*
then show ?thesis
by (simp add: assms)
next
case *False*
then show ?thesis
by (simp add: AlternateR-def closure assms)
qed

lemma *AlternateR-list-NCSP-closed* [closure]:
assumes $\bigwedge b P. (b, P) \in \text{set } A \implies P$ is NCSP Q is NCSP
shows $(\text{AlternateR-list } A \ Q)$ is NCSP
apply (simp add: AlternateR-list-def)
apply (rule AlternateR-NCSP-closed)
apply (auto simp add: assms)
apply (metis assms(1) eq-snd-iff nth-mem)
done

8.4 Specification Statement

definition *SpecC* :: $('a \implies 's) \Rightarrow 's \text{ upred} \Rightarrow 's \text{ upred} \Rightarrow ('s, 'e) \text{ action } (-: [-, -]_C [999, 0, 0] \ 999)$ **where**
 $[rdes\text{-}def]: \text{SpecC } frm \ pre \ post = \mathbf{R}_s([pre]_{S<} \vdash false \diamond [frm:[post^>]]_S)$

lemma *SpecC-is-NCSP* [closure]: $frm:[pre, post]_C$ is NCSP
apply (simp add: SpecC-def)
apply (rule NCSP-rdes-intro)
apply (simp-all add: closure unrest)
apply (rel-auto)+
done

lemma *SpecC-skip*: $\{\}_v:[true, true]_C = \text{Skip}$
by (rdes-eq)

lemma *SpecC-false-pre*: $a:[false, q]_C = \text{Chaos}$
by (rdes-eq)

lemma *SpecC-false-post*: $a:[true,false]_C = \text{Miracle}$
by (*rdes-eq*)

lemma *SpecC-refine-seq*:
 $vwb\text{-}lens\ a \implies a:[p,q]_C \sqsubseteq a:[p,r]_C \;;\; a:[r,q]_C$
by ((*rdes-refine-split*; *rel-simp*), *metis vwb-lens.put-eq*)

8.5 Assumptions

definition *AssumeCircus* $([-]_C)$ **where**
 $[b]_C = b \rightarrow_R \text{Skip}$

lemma *AssumeCircus-rdes-def* [*rdes-def*]: $[b]_C = \mathbf{R}_s(true_r \vdash false \diamond [b]_C)$
unfolding *AssumeCircus-def* **by** *rdes-eq*

lemma *AssumeCircus-NCSP* [*closure*]: $[b]_C$ *is NCSP*
by (*simp add: AssumeCircus-def GuardedCommR-NCSP-closed NCSP-Skip*)

lemma *AssumeCircus-AssumeR*: $\text{Skip} \;;\; [b]^\top_R = [b]_C [b]^\top_R \;;\; \text{Skip} = [b]_C$
by (*rdes-eq*)+

lemma *AssumeR-comp-AssumeCircus*: $P \text{ is NCSP} \implies P \;;\; [b]^\top_R = P \;;\; [b]_C$
by (*metis (no-types, hide-lams) AssumeCircus-AssumeR(1) RA1 Skip-right-unit*)

lemma *gcmd-AssumeCircus*:
 $P \text{ is NCSP} \implies b \rightarrow_R P = [b]_C \;;\; P$
by (*simp add: AssumeCircus-def NCSP-implies-NSRD Skip-left-unit gcmd-seq-distr*)

lemma *rdes-assume-pre-refine*:
assumes $P \text{ is NCSP}$
shows $P \sqsubseteq [b]_C \;;\; P$
by (*rdes-refine cls: assms*)

8.6 While Loops

lemma *NSRD-coerce-NCSP*:
 $P \text{ is NSRD} \implies \text{Skip} \;;\; P \;;\; \text{Skip} \text{ is NCSP}$
by (*metis (no-types, hide-lams) CSP3-Skip CSP3-def CSP4-def Healthy-def NCSP-Skip NCSP-implies-CSP NCSP-intro NSRD-is-SRD RA1 SRD-seqr-closure*)

definition *WhileC* :: $'s \text{ upred} \Rightarrow ('s, 'e) \text{ action} \Rightarrow ('s, 'e) \text{ action}$ (*whileC* - *do* - *od*) **where**
 $\text{while}_C\ b\ \text{do}\ P\ \text{od} = \text{Skip} \;;\; \text{while}_R\ b\ \text{do}\ P\ \text{od} \;;\; \text{Skip}$

lemma *WhileC-NCSP-closed* [*closure*]:
assumes $P \text{ is NCSP}$ $P \text{ is Productive}$
shows $\text{while}_C\ b\ \text{do}\ P\ \text{od} \text{ is NCSP}$
by (*simp add: WhileC-def NSRD-coerce-NCSP assms closure*)

theorem *WhileC-iter-form*:
assumes $P \text{ is NCSP}$ $P \text{ is Productive}$
shows $\text{while}_C\ b\ \text{do}\ P\ \text{od} = ([b]_C \;;\; P)^{\star C} \;;\; [\neg b]_C$
by (*simp add: WhileC-def WhileR-iter-form assms closure*)
(metis (no-types, lifting) StarC-def AssumeCircus-AssumeR(2) AssumeCircus-NCSP RA1 assms(1) csp-theory.Healthy-Sequence csp-theory.Star-Healthy csp-theory.Unit-Left sfrd-star-as-rdes-star)

theorem *WhileC-rdes-def* [*rdes-def*]:

assumes P is CRC Q is CRR R is CRF $\$st \# Q R$ is R4
shows $while_C b \text{ do } \mathbf{R}_s(P \vdash Q \diamond R) \text{ od} =$
 $\mathbf{R}_s([b]_C ;; R)^{*c} \text{ wp}_r ([b]_{S<} \Rightarrow_r P) \vdash ([b]_C ;; R)^{*c} ;; [b]_C ;; Q) \diamond ([b]_C ;; R)^{*c} ;; [\neg b]_C)$
(is ?lhs = ?rhs)
proof –
have $?lhs = ([b]_C ;; \mathbf{R}_s(P \vdash Q \diamond R))^{*C} ;; [\neg b]_C$
by (*simp add: WhileC-iter-form assms closure unrest Productive-rdes-RR-intro*)
also have $\dots = ?rhs$
by (*simp add: rdes-def assms closure unrest rpred wp del: rea-star-wp*)
finally show $?thesis$.
qed

lemma *WhileC-false:*

P is NCSP $\implies WhileC \text{ false } P = Skip$

by (*simp add: NCSP-implies-NSRD Skip-srdes-left-unit WhileC-def WhileR-false*)

lemma *WhileC-unfold:*

assumes P is NCSP P is Productive

shows $WhileC b P = (P ;; WhileC b P) \triangleleft b \triangleright_R Skip$

proof –

have $WhileC b P = (Skip \vee [b]_C ;; P ;; ([b]_C ;; P)^{*C}) ;; [\neg b]_C$

by (*simp add: WhileC-iter-form assms closure*)

(*metis (no-types, lifting) AssumeCircus-NCSP RA1 StarC-unfold assms(1) csp-theory.Healthy-Sequence disj-upred-def*)

also have $\dots = ([\neg b]_C \vee [b]_C ;; P ;; ([b]_C ;; P)^{*C}) ;; [\neg b]_C$

by (*metis (no-types, lifting) AssumeCircus-AssumeR(1) RA1 csp-theory.Unit-self seqr-or-distl*)

also have $\dots = (P ;; WhileC b P) \triangleleft b \triangleright_R Skip$

by (*metis (no-types, lifting) AssumeCircus-AssumeR(2) NCSP-implies-NSRD RA1 WhileC-NCSP-closed WhileC-iter-form assms(1) assms(2) cond-srea-AssumeR-form csp-theory.Healthy-Sequence csp-theory.Healthy-Unit csp-theory.Unit-Left uinf-or utp-pred-laws.sup-commute*)

finally show $?thesis$.

qed

8.7 Iteration Construction

definition $IterateC :: 'a \text{ set} \Rightarrow ('a \Rightarrow 's \text{ upred}) \Rightarrow ('a \Rightarrow ('s, 'e) \text{ action}) \Rightarrow ('s, 'e) \text{ action}$

where [*upred-defs, ndes-simp*]: $IterateC A g P = while_C (\bigvee i \in A \cdot g(i)) \text{ do } (if_R i \in A \cdot g(i) \rightarrow P(i) \text{ fi}) \text{ od}$

lemma *IterateC-IterateR-def:* $IterateC A g P = Skip ;; IterateR A g P ;; Skip$

by (*simp add: IterateC-def IterateR-def WhileC-def*)

definition $IterateC\text{-list} :: ('s \text{ upred} \times ('s, 'e) \text{ action}) \text{ list} \Rightarrow ('s, 'e) \text{ action}$ **where**

[*upred-defs, ndes-simp*]:

$IterateC\text{-list } xs = IterateC \{0..<\text{length } xs\} (\lambda i. \text{map fst } xs ! i) (\lambda i. \text{map snd } xs ! i)$

syntax

$\text{-iter-}C \quad :: \text{pttrn} \Rightarrow \text{logic} \Rightarrow \text{logic} \Rightarrow \text{logic} \Rightarrow \text{logic} \text{ (do}_C \text{ -}\in\text{-} \cdot \text{ -} \rightarrow \text{- od)}$

$\text{-iter-gcomm}C \quad :: \text{gcomms} \Rightarrow \text{logic} \text{ (do}_C \text{ / - /od)}$

translations

$\text{-iter-}C x A g P \Rightarrow \text{CONST } IterateC A (\lambda x. g) (\lambda x. P)$

$\text{-iter-}C x A g P \Leftarrow \text{CONST } IterateC A (\lambda x. g) (\lambda x'. P)$

$\text{-iter-gcomm}C cs \multimap \text{CONST } IterateC\text{-list } cs$

$\text{-iter-gcomm}C \text{ (-gcomm-show } cs) \leftarrow \text{CONST } IterateC\text{-list } cs$

lemma *IterateC-NCSP-closed* [closure]:

assumes

$\bigwedge i. i \in I \implies P(i) \text{ is NCSP}$

$\bigwedge i. i \in I \implies P(i) \text{ is Productive}$

shows $do_C i \in I \cdot g(i) \rightarrow P(i) \text{ od is NCSP}$

by (*simp add: IterateC-IterateR-def IterateR-NSRD-closed NCSP-implies-NSRD NSRD-coerce-NCSP*
assms(1) assms(2))

lemma *IterateC-list-NCSP-closed* [closure]:

assumes

$\bigwedge b P. (b, P) \in \text{set } A \implies P \text{ is NCSP}$

$\bigwedge b P. (b, P) \in \text{set } A \implies P \text{ is Productive}$

shows *IterateC-list* *A* *is NCSP*

apply (*simp add: IterateC-list-def, rule IterateC-NCSP-closed*)

apply (*metis assms atLeastLessThan-iff nth-map nth-mem prod.collapse*)
done

lemma *IterateC-list-alt-def*:

IterateC-list *xs* = *while_C* ($\bigvee b \in \text{set}(\text{map fst } xs) \cdot b$) *do* *AlternateR-list* *xs* *Chaos* *od*

proof –

have ($\bigvee i \in \{0..<\text{length}(xs)\} \cdot (\text{map fst } xs) ! i = (\bigvee b \in \text{set}(\text{map fst } xs) \cdot b)$)

by (*rel-auto, metis fst-conv in-set-conv-nth nth-map*)

thus *?thesis*

by (*simp add: IterateC-list-def IterateC-def AlternateR-list-def*)

qed

lemma *IterateC-empty*:

$do_C i \in \{\} \cdot g(i) \rightarrow P(i) \text{ od} = \text{Skip}$

by (*simp add: IterateC-IterateR-def IterateR-empty closure Skip-srdes-left-unit*)

lemma *IterateC-singleton*:

assumes *P k is NCSP* *P k is Productive*

shows $do_C i \in \{k\} \cdot g(i) \rightarrow P(i) \text{ od} = \text{while}_C g(k) \text{ do } P(k) \text{ od}$ (*is ?lhs = ?rhs*)

by (*simp add: IterateC-IterateR-def IterateR-singleton NCSP-implies-NSRD WhileC-def assms*)

lemma *IterateC-outer-refine-intro*:

assumes $I \neq \{\}$ $\bigwedge i. i \in I \implies P i \text{ is NCSP}$ $\bigwedge i. i \in I \implies P i \text{ is Productive}$

$\bigwedge i. i \in I \implies S \sqsubseteq (b i \rightarrow_R P i ;; S) \text{ } S \text{ is NCSP}$

$S \sqsubseteq [\neg (\bigvee i \in I \cdot b i)]^\top_R$

shows $S \sqsubseteq do_C i \in I \cdot b(i) \rightarrow P(i) \text{ od}$

proof –

have $S \sqsubseteq do_R i \in I \cdot b(i) \rightarrow P(i) \text{ od}$

by (*simp add: IterateR-outer-refine-intro NCSP-implies-NSRD assms*)

thus *?thesis*

unfolding *IterateC-IterateR-def*

by (*metis (full-types) Skip-left-unit Skip-right-unit assms(5) urel-diod.mult-isol urel-diod.mult-isor*)

qed

lemma *IterateC-outer-refine-init-intro*:

assumes

$\bigwedge i. i \in A \implies P i \text{ is NCSP}$

$\bigwedge i. i \in A \implies P i \text{ is Productive}$

S is NCSP *I is NCSP*

$S \sqsubseteq I ;; [\neg (\bigvee i \in A \cdot b i)]^\top_R$

$\bigwedge i. i \in A \implies S \sqsubseteq S ;; b i \rightarrow_R P i$

$\bigwedge i. i \in A \implies S \sqsubseteq I ;; b\ i \rightarrow_R P\ i$
shows $S \sqsubseteq I ;; do_C\ i \in A \cdot b(i) \rightarrow P(i)\ od$
proof (*cases* $A = \{\}$)
 case *True*
 with *assms(5)* **show** *?thesis*
 by (*simp add: IterateC-empty assms closure Skip-right-unit AssumeR-true NSRD-right-unit*)
next
 case *False*
 have $S \sqsubseteq I ;; do_R\ i \in A \cdot b(i) \rightarrow P(i)\ od$
 by (*simp add: IterateR-outer-refine-init-intro NCSP-implies-NSRD assms False*)
 thus *?thesis*
 unfolding *IterateC-IterateR-def*
 by (*metis (no-types, hide-lams) RA1 Skip-right-unit assms(3) assms(4) urel-dioid.mult-isor*)
qed

lemma *IterateC-list-outer-refine-intro:*

assumes
 $A \neq []\ S\ is\ NCSP$
 $\bigwedge b\ P. (b, P) \in set\ A \implies P\ is\ NCSP$
 $\bigwedge b\ P. (b, P) \in set\ A \implies P\ is\ Productive$
 $\bigwedge b\ P. (b, P) \in set\ A \implies S \sqsubseteq (b \rightarrow_R P ;; S)$
 $S \sqsubseteq [\neg (\bigwedge (b, P) \in set\ A \cdot b)]^\top_R$
shows $S \sqsubseteq IterateC-list\ A$
proof –
have $(\bigwedge i \in \{0..<length(A)\} \cdot (map\ fst\ A) ! i) = (\bigwedge (b, P) \in set\ A \cdot b)$
by (*rel-auto, metis nth-mem prod.exhaust-sel, metis fst-conv in-set-conv-nth nth-map*)
thus *?thesis*
 apply (*simp add: IterateC-list-def*)
 apply (*rule IterateC-outer-refine-intro*)
 apply (*simp-all add: closure assms*)
 apply (*metis assms(3) nth-mem prod.collapse*)
 apply (*metis assms(4) nth-mem prod.collapse*)
 done
qed

lemma *IterateC-list-outer-refine-init-intro:*

assumes
 $S\ is\ NCSP\ I\ is\ NCSP$
 $\bigwedge b\ P. (b, P) \in set\ A \implies P\ is\ NCSP$
 $\bigwedge b\ P. (b, P) \in set\ A \implies P\ is\ Productive$
 $S \sqsubseteq I ;; [\neg (\bigwedge (b, P) \in set\ A \cdot b)]^\top_R$
 $\bigwedge b\ P. (b, P) \in set\ A \implies S \sqsubseteq S ;; b \rightarrow_R P$
 $\bigwedge b\ P. (b, P) \in set\ A \implies S \sqsubseteq I ;; b \rightarrow_R P$
shows $S \sqsubseteq I ;; IterateC-list\ A$
proof –
have $(\bigwedge i \in \{0..<length(A)\} \cdot (map\ fst\ A) ! i) = (\bigwedge (b, P) \in set\ A \cdot b)$
by (*rel-auto, metis nth-mem prod.exhaust-sel, metis fst-conv in-set-conv-nth nth-map*)
thus *?thesis*
 apply (*simp add: IterateC-list-def*)
 apply (*rule IterateC-outer-refine-init-intro*)
 apply (*simp-all add: closure assms*)
 apply (*metis assms(3) nth-mem prod.collapse*)
 apply (*metis assms(4) nth-mem prod.collapse*)
 done

qed

8.8 Assignment

definition *AssignsCSP* :: $\sigma \text{ usubst} \Rightarrow (\sigma, \varphi) \text{ action } (\langle - \rangle_C)$ **where**
 $[upred-defs]: \text{AssignsCSP } \sigma = \mathbf{R}_s(\text{true} \vdash \text{false} \diamond (\$tr =_u \$tr \wedge \lceil \langle \sigma \rangle_a \rceil_s))$

abbreviation *AssignCSP* $x \ v \equiv \mathbf{R}_s([\&\mathbf{v} \in_u \langle \mathcal{S}_x \rangle]_{S<} \vdash \text{false} \diamond \Phi(\text{true}, [x \mapsto_s v], \langle [] \rangle))$

syntax

-*assigns-csp* :: $svids \Rightarrow uexprs \Rightarrow logic \quad ('(-) :=_C '(-))$
 -*assigns-csp* :: $svids \Rightarrow uexprs \Rightarrow logic \quad (\mathbf{infixr} :=_C 64)$

translations

-*assigns-csp* $xs \ vs \Rightarrow \text{CONST AssignsCSP } (-mk-usubst \ id_s \ xs \ vs)$
 -*assigns-csp* $x \ v \leq \text{CONST AssignsCSP } (\text{CONST subst-upd } id_s \ x \ v)$
 -*assigns-csp* $x \ v \leq -assigns-csp \ (-spvar \ x) \ v$
 $x, y :=_C u, v \leq \text{CONST AssignsCSP } (\text{CONST subst-upd } (\text{CONST subst-upd } (id_s) (\text{CONST pr-var } x) u) (\text{CONST pr-var } y) v)$

lemma *preR-AssignsCSP* $[rdes]: \text{pre}_R(\langle \sigma \rangle_C) = \text{true}_r$
by (*rel-auto*)

lemma *periR-AssignsCSP* $[rdes]: \text{peri}_R(\langle \sigma \rangle_C) = \text{false}$
by (*rel-auto*)

lemma *postR-AssignsCSP* $[rdes]: \text{post}_R(\langle \sigma \rangle_C) = \Phi(\text{true}, \sigma, \langle [] \rangle)$
by (*rel-auto*)

lemma *AssignsCSP-rdes-def* $[rdes-def]: \langle \sigma \rangle_C = \mathbf{R}_s(\text{true}_r \vdash \text{false} \diamond \Phi(\text{true}, \sigma, \langle [] \rangle))$
by (*rel-auto*)

lemma *AssignsCSP-CSP* $[closure]: \langle \sigma \rangle_C \text{ is CSP}$
by (*simp add: AssignsCSP-def RHS-tri-design-is-SRD unrest*)

lemma *AssignsCSP-CSP3* $[closure]: \langle \sigma \rangle_C \text{ is CSP3}$
by (*rule CSP3-intro, simp add: closure, rel-auto*)

lemma *AssignsCSP-CSP4* $[closure]: \langle \sigma \rangle_C \text{ is CSP4}$
by (*rule CSP4-intro, simp add: closure, rel-auto+*)

lemma *AssignsCSP-NCSP* $[closure]: \langle \sigma \rangle_C \text{ is NCSP}$
by (*simp add: AssignsCSP-CSP AssignsCSP-CSP3 AssignsCSP-CSP4 NCSP-intro*)

lemma *AssignsCSP-ICSP* $[closure]: \langle \sigma \rangle_C \text{ is ICSP}$
apply (*rule ICSP-intro, simp add: closure, simp add: rdes-def*)
apply (*rule ISRDI-rdes-intro*)
apply (*simp-all add: closure*)
apply (*rel-auto*)
done

lemma *unproductive-AssignsCSP*: $\neg (\langle \sigma \rangle_C \text{ is Productive})$
unfolding *rdes-def* **by** (*rule unproductive-form, simp-all add: closure, rel-auto+*)

lemma *AssignsCSP-as-AssignsR*: $\langle \sigma \rangle_R ;; \text{Skip} = \langle \sigma \rangle_C$
by (*rdes-eq*)

lemma *AssignC-init-refine-intro*:

assumes

vwb-lens $x \ \$st:x \# P_2 \ \$st:x \# P_3$

P_2 *is* *RR* P_3 *is* *RR* Q *is* *NCSP*

$\mathbf{R}_s([\&x =_u \langle k \rangle]_{S<} \vdash P_2 \diamond P_3) \sqsubseteq Q$

shows $\mathbf{R}_s(\text{true}_r \vdash P_2 \diamond P_3) \sqsubseteq (x :=_C \langle k \rangle) ;; Q$

by (*simp add: AssignsCSP-as-AssignsR[THEN sym] assms seqr-assoc Skip-left-unit AssignR-init-refine-intro closure*)

lemma *AssignsCSP-refines-sinv*:

assumes $\sigma \dagger b$

shows $\text{invs}_R(b) \sqsubseteq \langle \sigma \rangle_C$

apply (*rdes-refine-split*)

apply (*simp-all*)

apply (*metis rea-st-cond-true st-cond-conj utp-pred-laws.inf.absorb-iff2 utp-pred-laws.inf-top-left*)

using *assms* **apply** (*rel-auto*)

done

8.9 Assignment with update

There are different collections that we would like to assign to, but they all have different types and perhaps more importantly different conditions on the update being well defined. For example, for a list well-definedness equates to the index being less than the length etc. Thus we here set up a polymorphic constant for CSP assignment updates that can be specialised to different types.

definition *AssignCSP-update* ::

$(f \Rightarrow k \text{ set}) \Rightarrow (f \Rightarrow k \Rightarrow v \Rightarrow f) \Rightarrow (f \Rightarrow \sigma) \Rightarrow$

$(k, \sigma) \text{ uexpr} \Rightarrow (v, \sigma) \text{ uexpr} \Rightarrow (\sigma, \varphi) \text{ action}$ **where**

[*upred-defs, rdes-def*]: *AssignCSP-update* *domf* *updatef* $x \ k \ v =$

$\mathbf{R}_s([k \in_u \text{uop domf } (\&x)]_{S<} \vdash \text{false} \diamond \Phi(\text{true}, [x \mapsto_s \text{trop updatef } (\&x) \ k \ v], \langle [] \rangle))$

All different assignment updates have the same syntax; the type resolves which implementation to use.

syntax

-csp-assign-upd :: *svid* \Rightarrow *logic* \Rightarrow *logic* \Rightarrow *logic* $([-] :=_C - [61, 0, 62] \ 62)$

translations

-csp-assign-upd $x \ k \ v == \text{CONST } \text{AssignCSP-update } (\text{CONST dom}) (\text{CONST upd}) \ x \ k \ v$

lemma *AssignCSP-update-CSP* [*closure*]:

AssignCSP-update *domf* *updatef* $x \ k \ v$ *is* *CSP*

by (*simp add: AssignCSP-update-def RHS-tri-design-is-SRD unrest*)

lemma *preR-AssignCSP-update* [*rdes*]:

$\text{pre}_R(\text{AssignCSP-update } \text{domf } \text{updatef } x \ k \ v) = [k \in_u \text{uop domf } (\&x)]_{S<}$

by (*rel-auto*)

lemma *periR-AssignCSP-update* [*rdes*]:

$\text{peri}_R(\text{AssignCSP-update } \text{domf } \text{updatef } x \ k \ v) = [k \notin_u \text{uop domf } (\&x)]_{S<}$

by (*rel-simp*)

lemma *post-AssignCSP-update* [*rdes*]:

$\text{post}_R(\text{AssignCSP-update } \text{domf } \text{updatef } x \ k \ v) =$

$(\Phi(\text{true}, [x \mapsto_s \text{trop updatef } (\&x) \ k \ v], \llbracket \cdot \rrbracket)) \triangleleft (k \in_u \text{uop domf } (\&x)) \triangleright_R R1(\text{true}))$
by (*rel-auto*)

lemma *AssignCSP-update-NCSP* [*closure*]:

(*AssignCSP-update domf updatef x k v*) is NCSP

proof (*rule NCSP-intro*)

show (*AssignCSP-update domf updatef x k v*) is CSP

by (*simp add: closure*)

show (*AssignCSP-update domf updatef x k v*) is CSP3

by (*rule CSP3-SRD-intro, simp-all add: csp-do-def closure rdes unrest*)

show (*AssignCSP-update domf updatef x k v*) is CSP4

by (*rule CSP4-tri-intro, simp-all add: csp-do-def closure rdes unrest, rel-auto*)

qed

8.10 State abstraction

lemma *ref-unrest-abs-st* [*unrest*]:

$\$ref \# P \implies \$ref \# \langle P \rangle_S$

$\$ref \# P \implies \$ref \# \langle P \rangle_S$

by (*rel-simp*)⁺

lemma *NCSP-state-srea* [*closure*]: P is NCSP \implies state $'a \cdot P$ is NCSP

apply (*rule NCSP-NSRD-intro*)

apply (*simp-all add: closure rdes*)

apply (*simp-all add: state-srea-def unrest closure*)

done

8.11 Guards

definition *GuardCSP* ::

$'\sigma \text{ cond} \Rightarrow$

$(' \sigma, ' \varphi) \text{ action} \Rightarrow$

$(' \sigma, ' \varphi) \text{ action}$ **where**

[*upred-defs*]: $\text{GuardCSP } g \ A = \mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r \text{pre}_R(A)) \vdash ((\lceil g \rceil_{S<} \wedge \text{cmt}_R(A)) \vee (\lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait)))$

syntax

-*GuardCSP* :: $\text{logic} \Rightarrow \text{logic} \Rightarrow \text{logic}$ (**infixr** $\&_C$ 60)

translations

-*GuardCSP* $b \ P == \text{CONST } \text{GuardCSP } b \ P$

lemma *Guard-tri-design*:

$g \ \&_C \ P = \mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r \text{pre}_R(P)) \vdash (\text{peri}_R(P) \triangleleft \lceil g \rceil_{S<} \triangleright (\$tr =_u \$tr)) \diamond (\lceil g \rceil_{S<} \wedge \text{post}_R(P)))$

proof –

have $(\lceil g \rceil_{S<} \wedge \text{cmt}_R(P) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait) = (\text{peri}_R(P) \triangleleft \lceil g \rceil_{S<} \triangleright (\$tr =_u \$tr)) \diamond (\lceil g \rceil_{S<} \wedge \text{post}_R(P))$

by (*rel-auto*)

thus *?thesis* **by** (*simp add: GuardCSP-def*)

qed

lemma *csp-do-cond-conj*:

assumes P is CRR

shows $(\lceil b \rceil_{S<} \wedge P) = \Phi(b, id_s, \llbracket \cdot \rrbracket) ;; P$

proof –

have $(\lceil b \rceil_{S<} \wedge \text{CRR}(P)) = \Phi(b, id_s, \llbracket \cdot \rrbracket) ;; \text{CRR}(P)$

by (rel-auto)
 thus ?thesis
 by (simp add: Healthy-if assms)
 qed

lemma Guard-rdes-def [rdes-def]:

assumes P is RR Q is CRR R is CRR
 shows $g \&_C \mathbf{R}_s(P \vdash Q \diamond R) = \mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r P) \vdash ((\Phi(g, id_s, \llbracket \cdot \rrbracket) ;; Q) \vee \mathcal{E}(\neg g, \llbracket \cdot \rrbracket, \{ \}_u)) \diamond (\Phi(g, id_s, \llbracket \cdot \rrbracket) ;; R))$
 (is ?lhs = ?rhs)

proof –

have ?lhs = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r P) \vdash ((P \Rightarrow_r Q) \triangleleft \lceil g \rceil_{S<} \triangleright (\$tr =_u \$tr)) \diamond (\lceil g \rceil_{S<} \wedge (P \Rightarrow_r R)))$
 by (simp add: Guard-tri-design rdes assms closure)
 also have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r P) \vdash ((\lceil g \rceil_{S<} \wedge Q) \vee \mathcal{E}(\neg g, \llbracket \cdot \rrbracket, \{ \}_u)) \diamond (\lceil g \rceil_{S<} \wedge R))$
 by (rel-auto)
 also have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r P) \vdash ((\Phi(g, id_s, \llbracket \cdot \rrbracket) ;; Q) \vee \mathcal{E}(\neg g, \llbracket \cdot \rrbracket, \{ \}_u)) \diamond (\Phi(g, id_s, \llbracket \cdot \rrbracket) ;; R))$
 by (simp add: assms(2) assms(3) csp-do-cond-conj)
 finally show ?thesis .

qed

lemma Guard-rdes-def':

assumes $\$ok \nmid P$
 shows $g \&_C (\mathbf{R}_s(P \vdash Q)) = \mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r P) \vdash (\lceil g \rceil_{S<} \wedge Q \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$

proof –

have $g \&_C (\mathbf{R}_s(P \vdash Q)) = \mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r pre_R (\mathbf{R}_s(P \vdash Q))) \vdash (\lceil g \rceil_{S<} \wedge cmt_R (\mathbf{R}_s(P \vdash Q)) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (simp add: GuardCSP-def)
 also have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r R1(R2c(pre_s \dagger P))) \vdash (\lceil g \rceil_{S<} \wedge R1(R2c(cmt_s \dagger (P \Rightarrow Q))) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (simp add: rea-pre-RHS-design rea-cmt-RHS-design)
 also have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r R1(R2c(pre_s \dagger P))) \vdash R1(R2c(\lceil g \rceil_{S<} \wedge R1(R2c(cmt_s \dagger (P \Rightarrow Q)))) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (metis (no-types, lifting) RHS-design-export-R1 RHS-design-export-R2c)
 also have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r R1(R2c(pre_s \dagger P))) \vdash R1(R2c(\lceil g \rceil_{S<} \wedge (cmt_s \dagger (P \Rightarrow Q)) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (simp add: R1-R2c-commute R1-disj R1-extend-conj' R1-idem R2c-and R2c-disj R2c-idem)
 also have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r R1(R2c(pre_s \dagger P))) \vdash (\lceil g \rceil_{S<} \wedge (cmt_s \dagger (P \Rightarrow Q)) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (metis (no-types, lifting) RHS-design-export-R1 RHS-design-export-R2c)
 also have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r R1(R2c(pre_s \dagger P))) \vdash cmt_s \dagger (\lceil g \rceil_{S<} \wedge (cmt_s \dagger (P \Rightarrow Q)) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (simp add: rdes-export-cmt)
 also have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r R1(R2c(pre_s \dagger P))) \vdash cmt_s \dagger (\lceil g \rceil_{S<} \wedge (P \Rightarrow Q) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (simp add: usubst)
 also have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r R1(R2c(pre_s \dagger P))) \vdash (\lceil g \rceil_{S<} \wedge (P \Rightarrow Q) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (simp add: rdes-export-cmt)
 also from assms have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r (pre_s \dagger P)) \vdash (\lceil g \rceil_{S<} \wedge (P \Rightarrow Q) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (rel-auto)
 also have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r pre_s \dagger P) \llbracket true, false / \$ok, \$wait \rrbracket \vdash (\lceil g \rceil_{S<} \wedge (P \Rightarrow Q) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (simp add: rdes-export-pre)
 also from assms have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r P) \llbracket true, false / \$ok, \$wait \rrbracket \vdash (\lceil g \rceil_{S<} \wedge (P \Rightarrow Q) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$

$\wedge \$tr =_u \$tr \wedge \$wait))$
 by (rel-auto)
 also from *assms* have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r P) \vdash (\lceil g \rceil_{S<} \wedge (P \Rightarrow Q) \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (simp add: rdes-export-pre)
 also have ... = $\mathbf{R}_s((\lceil g \rceil_{S<} \Rightarrow_r P) \vdash (\lceil g \rceil_{S<} \wedge Q \vee \lceil \neg g \rceil_{S<} \wedge \$tr =_u \$tr \wedge \$wait))$
 by (rule cong[of \mathbf{R}_s \mathbf{R}_s], simp, rel-auto)
 finally show ?thesis .
 qed

lemma *CSP-Guard [closure]: $b \&_C P$ is CSP*
 by (simp add: GuardCSP-def, rule RHS-design-is-SRD, simp-all add: unrest)

lemma *preR-Guard [rdes]: P is CSP $\Rightarrow pre_R(b \&_C P) = (\lceil b \rceil_{S<} \Rightarrow_r pre_R P)$*
 by (simp add: Guard-tri-design rea-pre-RHS-design usubst unrest R2c-preR R2c-lift-state-pre R2c-rea-impl R1-rea-impl R1-preR Healthy-if, rel-auto)

lemma *periR-Guard [rdes]:*
 assumes P is NCSP
 shows $peri_R(b \&_C P) = (peri_R P \triangleleft b \triangleright_R \mathcal{E}(true, \langle \rangle, \{ \}_u))$
proof –
 have $peri_R(b \&_C P) = ((\lceil b \rceil_{S<} \Rightarrow_r pre_R P) \Rightarrow_r (peri_R P \triangleleft \lceil b \rceil_{S<} \triangleright (\$tr =_u \$tr)))$
 by (simp add: assms Guard-tri-design rea-peri-RHS-design usubst unrest R1-rea-impl R2c-rea-not R2c-rea-impl R2c-preR R2c-periR R2c-tr'-minus-tr R2c-lift-state-pre R2c-condr closure Healthy-if R1-cond R1-tr'-eq-tr)
 also have ... = $((pre_R P \Rightarrow_r peri_R P) \triangleleft \lceil b \rceil_{S<} \triangleright (\$tr =_u \$tr))$
 by (rel-auto)
 also have ... = $(peri_R P \triangleleft \lceil b \rceil_{S<} \triangleright (\$tr =_u \$tr))$
 by (simp add: SRD-peri-under-pre add: unrest closure assms)
 finally show ?thesis
 by rel-auto
 qed

lemma *postR-Guard [rdes]:*
 assumes P is NCSP
 shows $post_R(b \&_C P) = (\lceil b \rceil_{S<} \wedge post_R P)$
proof –
 have $post_R(b \&_C P) = ((\lceil b \rceil_{S<} \Rightarrow_r pre_R P) \Rightarrow_r (\lceil b \rceil_{S<} \wedge post_R P))$
 by (simp add: Guard-tri-design rea-post-RHS-design usubst unrest R2c-rea-not R2c-and R2c-rea-impl R2c-preR R2c-postR R2c-tr'-minus-tr R2c-lift-state-pre R2c-condr R1-rea-impl R1-extend-conj' R1-post-SRD closure assms)
 also have ... = $(\lceil b \rceil_{S<} \wedge (pre_R P \Rightarrow_r post_R P))$
 by (rel-auto)
 also have ... = $(\lceil b \rceil_{S<} \wedge post_R P)$
 by (simp add: SRD-post-under-pre add: unrest closure assms)
 also have ... = $(\lceil b \rceil_{S<} \wedge post_R P)$
 by (metis CSP-Guard R1-extend-conj R1-post-SRD calculation rea-st-cond-def)
 finally show ?thesis .
 qed

lemma *CSP3-Guard [closure]:*
 assumes P is CSP P is CSP3
 shows $b \&_C P$ is CSP3
proof –
 from *assms* have $1:\$ref \nmid P \llbracket false/\$wait \rrbracket$

by (simp add: CSP-Guard CSP3-iff)
 hence $\$ref \# pre_R (P \llbracket 0/\$tr \rrbracket) \$ref \# pre_R P \$ref \# cmt_R P$
 by (pred-blast)+
 hence $\$ref \# (b \&_C P) \llbracket false/\$wait \rrbracket$
 by (simp add: CSP3-iff GuardCSP-def RHS-def R1-def R2c-def R2s-def R3h-def design-def unrest
 usubst)
 thus ?thesis
 by (metis CSP3-intro CSP-Guard)
 qed

lemma CSP4-Guard [closure]:
 assumes P is NCSP
 shows $b \&_C P$ is CSP4
proof (rule CSP4-tri-intro[OF CSP-Guard])
 show $(\neg_r pre_R (b \&_C P)) ;; R1 \text{ true} = (\neg_r pre_R (b \&_C P))$
proof –
 have $a: (\neg_r pre_R P) ;; R1 \text{ true} = (\neg_r pre_R P)$
 by (simp add: CSP4-neg-pre-unit assms closure)
 have $(\neg_r ([b]_{S<} \Rightarrow_r pre_R P)) ;; R1 \text{ true} = (\neg_r ([b]_{S<} \Rightarrow_r pre_R P))$
proof –
 have $1: (\neg_r ([b]_{S<} \Rightarrow_r pre_R P)) = ([b]_{S<} \wedge (\neg_r pre_R P))$
 by (rel-auto)
 also have $2: \dots = ([b]_{S<} \wedge ((\neg_r pre_R P) ;; R1 \text{ true}))$
 by (simp add: a)
 also have $3: \dots = (\neg_r ([b]_{S<} \Rightarrow_r pre_R P)) ;; R1 \text{ true}$
 by (rel-auto)
 finally show ?thesis ..
 qed
 thus ?thesis
 by (simp add: preR-Guard periR-Guard NSRD-CSP4-intro closure assms unrest)
 qed
 show $\$st \# peri_R (b \&_C P)$
 by (simp add: preR-Guard periR-Guard NSRD-CSP4-intro closure assms unrest)
 show $\$ref \# post_R (b \&_C P)$
 by (simp add: preR-Guard postR-Guard NSRD-CSP4-intro closure assms unrest)
 qed

lemma NCSP-Guard [closure]:
 assumes P is NCSP
 shows $b \&_C P$ is NCSP
proof –
 have P is CSP
 using NCSP-implies-CSP assms by blast
 then show ?thesis
 by (metis (no-types) CSP3-Guard CSP3-commutes-CSP4 CSP4-Guard CSP4-Idempotent CSP-Guard
 Healthy-Idempotent Healthy-def NCSP-def assms comp-apply)
 qed

lemma Productive-Guard [closure]:
 assumes P is CSP P is Productive $\$wait \# pre_R(P)$
 shows $b \&_C P$ is Productive
proof –
 have $b \&_C P = b \&_C \mathbf{R}_s(pre_R(P) \vdash peri_R(P) \diamond (post_R(P) \wedge \$tr <_u \$tf))$
 by (metis Healthy-def Productive-form assms(1) assms(2))
 also have ... =

$\mathbf{R}_s \left(([b]_{S<} \Rightarrow_r pre_R P) \vdash \right.$
 $\left. ((pre_R P \Rightarrow_r peri_R P) \triangleleft [b]_{S<} \triangleright (\$tr =_u \$tr)) \diamond ([b]_{S<} \wedge (pre_R P \Rightarrow_r post_R P \wedge \$tr >_u \$tr)) \right)$
by (*simp add: Guard-tri-design rea-pre-RHS-design rea-peri-RHS-design rea-post-RHS-design unrest*
assms
usubst R1-preR Healthy-if R1-rea-impl R1-peri-SRD R1-extend-conj' R2c-preR R2c-not R2c-rea-impl
R2c-periR R2c-postR R2c-and R2c-tr-less-tr' R1-tr-less-tr')
also have ... = $\mathbf{R}_s \left(([b]_{S<} \Rightarrow_r pre_R P) \vdash (peri_R P \triangleleft [b]_{S<} \triangleright (\$tr =_u \$tr)) \diamond (([b]_{S<} \wedge post_R P) \wedge \$tr >_u \$tr) \right)$
by (*rel-auto*)
also have ... = *Productive(b &_C P)*
by (*simp add: Productive-def Guard-tri-design RHS-tri-design-par unrest*)
finally show ?thesis
by (*simp add: Healthy-def'*)
qed

lemma *Guard-refines-sinv*:

assumes *P is NCSP* *sinv_R(b) ⊆ P*

shows *sinv_R(b) ⊆ g &_C P*

proof –

from *assms*

have $\mathbf{R}_s([b]_{S<} \vdash R1 \text{ true} \diamond [b]_{S>}) \subseteq \mathbf{R}_s(pre_R(P) \vdash peri_R(P) \diamond post_R(P))$

by (*simp add: rdes-def NCSP-implies-CSP SRD-reactive-tri-design*)

thus ?thesis

apply (*simp add: RHS-tri-design-refine' closure unrest assms*)

apply (*safe*)

apply (*rdes-refine cls: assms(1)*)

done

qed

8.12 Basic events

definition *do_u* ::

('φ, 'σ) uexpr ⇒ ('σ, 'φ) action where

[*upred-defs*]: *do_u e = ((\\$tr =_u \\$tr ∧ [e]_{S<} ∉_u \\$ref) < \\$wait > U(\\$tr = \\$tr @ [[e]_{S<}] ∧ \\$st = \\$st))*

definition *DoCSP* :: *('φ, 'σ) uexpr ⇒ ('σ, 'φ) action (do_C) where*

[*upred-defs*]: *DoCSP a = R_s(true ⊢ do_u a)*

lemma *R1-DoAct*: *R1(do_u(a)) = do_u(a)*

by (*rel-auto*)

lemma *R2c-DoAct*: *R2c(do_u(a)) = do_u(a)*

by (*rel-auto*)

lemma *DoCSP-alt-def*: *do_C(a) = R3h(CSP1(\\$ok ∧ do_u(a)))*

apply (*simp add: DoCSP-def RHS-def design-def impl-alt-def R1-R3h-commute R2c-R3h-commute R2c-disj*

R2c-not R2c-ok R2c-ok' R2c-and R2c-DoAct R1-disj R1-extend-conj' R1-DoAct)

apply (*rel-auto*)

done

lemma *DoAct-unrests* [*unrest*]:

\\$ok # do_u(a) \\$wait # do_u(a)

by (*pred-auto*)**+**

lemma *DoCSP-RHS-tri* [*rdes-def*]:

$do_C(a) = \mathbf{R}_s(true_r \vdash (\mathcal{E}(true, \llbracket \cdot \rrbracket, \{a\}_u) \diamond \Phi(true, id_s, U(\llbracket a \rrbracket))))$
by (*simp add: DoCSP-def do_u-def wait'-cond-def, rel-auto*)

lemma *CSP-DoCSP* [*closure*]: $do_C(a)$ is CSP

by (*simp add: DoCSP-def do_u-def RHS-design-is-SRD unrest*)

lemma *preR-DoCSP* [*rdes*]: $pre_R(do_C(a)) = true_r$

by (*simp add: DoCSP-def rea-pre-RHS-design unrest usubst R2c-true*)

lemma *periR-DoCSP* [*rdes*]: $peri_R(do_C(a)) = \mathcal{E}(true, \llbracket \cdot \rrbracket, \{a\}_u)$

by (*rel-auto*)

lemma *postR-DoCSP* [*rdes*]: $post_R(do_C(a)) = \Phi(true, id_s, U(\llbracket a \rrbracket))$

by (*rel-auto*)

lemma *CSP3-DoCSP* [*closure*]: $do_C(a)$ is CSP3

by (*rule CSP3-intro[OF CSP-DoCSP]*)

(*simp add: DoCSP-def do_u-def RHS-def design-def R1-def R2c-def R2s-def R3h-def unrest usubst*)

lemma *CSP4-DoCSP* [*closure*]: $do_C(a)$ is CSP4

by (*rule CSP4-tri-intro[OF CSP-DoCSP], simp-all add: preR-DoCSP periR-DoCSP postR-DoCSP unrest*)

lemma *NCSP-DoCSP* [*closure*]: $do_C(a)$ is NCSP

by (*metis CSP3-DoCSP CSP4-DoCSP CSP-DoCSP Healthy-def NCSP-def comp-apply*)

lemma *Productive-DoCSP* [*closure*]:

($do_C a :: ('σ, 'ψ) \text{ action}$) is Productive

proof –

have ($(\Phi(true, id_s, U(\llbracket a \rrbracket)) \wedge \$tr >_u \$tr) :: ('σ, 'ψ) \text{ action}$)
 $= (\Phi(true, id_s, U(\llbracket a \rrbracket)))$

by (*rel-auto, simp add: Prefix-Order.strict-prefixI'*)

hence $Productive(do_C a) = do_C a$

by (*simp add: Productive-RHS-design-form DoCSP-RHS-tri unrest*)

thus *?thesis*

by (*simp add: Healthy-def*)

qed

lemma *PCSP-DoCSP* [*closure*]:

($do_C a :: ('σ, 'ψ) \text{ action}$) is PCSP

by (*simp add: Healthy-comp NCSP-DoCSP Productive-DoCSP*)

lemma *wp-rea-DoCSP-lemma*:

fixes $P :: ('σ, 'φ) \text{ action}$

assumes $\$ok \# P \ \$wait \# P$

shows $U(\$tr = \$tr @ \llbracket a \rrbracket_{S<} \wedge \$st = \$st) ;; P = (\exists \$ref \cdot P \llbracket U(\$tr @ \llbracket a \rrbracket_{S<}) / \$tr \rrbracket)$

using *assms*

by (*rel-auto, meson*)

lemma *wp-rea-DoCSP*:

assumes P is NCSP

shows $U(\$tr = \$tr @ \llbracket a \rrbracket_{S<} \wedge \$st = \$st) \ wp_r \ pre_R \ P =$

$(\neg_r (\neg_r \ pre_R \ P) \llbracket U(\$tr @ \llbracket a \rrbracket_{S<}) / \$tr \rrbracket)$

by (*simp add: wp-rea-def wp-rea-DoCSP-lemma unrest usubst ex-unrest assms closure*)

lemma *wp-rea-DoCSP-alt*:

assumes P is NCSP

shows $U(\$tr = \$tr @ [[a]_{S<}] \wedge \$st = \$st) \text{ wp}_r \text{ pre}_R P =$

$U(\$tr \geq \$tr @ [[a]_{S<}] \Rightarrow_r (\text{pre}_R P)[\$tr @ [[a]_{S<}]/\$tr])$

by (*simp add: wp-rea-DoCSP assms rea-not-def R1-def usubst unrest, rel-auto*)

lemma *DoCSP-refine-sinv*: $\text{sinv}_R(b) \sqsubseteq \text{do}_C(a)$

by (*rdes-refine*)

8.13 Event prefix

definition *PrefixCSP* ::

$(' \varphi, ' \sigma) \text{ uexpr} \Rightarrow$

$(' \sigma, ' \varphi) \text{ action} \Rightarrow$

$(' \sigma, ' \varphi) \text{ action} (- \rightarrow_C - [81, 80] \ 80) \text{ where}$

[*upred-defs*]: *PrefixCSP* $a \ P = (\text{do}_C(a) ;; \text{CSP}(P))$

abbreviation *OutputCSP* $c \ v \ P \equiv \text{PrefixCSP} (c.v)_u \ P$

lemma *CSP-PrefixCSP [closure]*: *PrefixCSP* $a \ P$ is CSP

by (*simp add: PrefixCSP-def closure*)

lemma *CSP3-PrefixCSP [closure]*:

PrefixCSP $a \ P$ is CSP3

by (*metis (no-types, hide-lams) CSP3-DoCSP CSP3-def Healthy-def PrefixCSP-def seqr-assoc*)

lemma *CSP4-PrefixCSP [closure]*:

assumes P is CSP P is CSP4

shows *PrefixCSP* $a \ P$ is CSP4

by (*metis (no-types, hide-lams) CSP4-def Healthy-def PrefixCSP-def assms(1) assms(2) seqr-assoc*)

lemma *NCSP-PrefixCSP [closure]*:

assumes P is NCSP

shows *PrefixCSP* $a \ P$ is NCSP

by (*metis (no-types, hide-lams) CSP3-PrefixCSP CSP3-commutes-CSP4 CSP4-Idempotent CSP4-PrefixCSP CSP-PrefixCSP Healthy-Idempotent Healthy-def NCSP-def NCSP-implies-CSP assms comp-apply*)

lemma *Productive-PrefixCSP [closure]*: P is NCSP \implies *PrefixCSP* $a \ P$ is Productive

by (*simp add: Healthy-if NCSP-DoCSP NCSP-implies-NSRD NSRD-is-SRD PrefixCSP-def Productive-DoCSP Productive-seq-1*)

lemma *PCSP-PrefixCSP [closure]*: P is NCSP \implies *PrefixCSP* $a \ P$ is PCSP

by (*simp add: Healthy-comp NCSP-PrefixCSP Productive-PrefixCSP*)

lemma *PrefixCSP-Guarded [closure]*: *Guarded* (*PrefixCSP* a)

proof –

have *PrefixCSP* $a = (\lambda X. \text{do}_C(a) ;; \text{CSP}(X))$

by (*simp add: fun-eq-iff PrefixCSP-def*)

thus ?thesis

using *Guarded-if-Productive NCSP-DoCSP NCSP-implies-NSRD Productive-DoCSP* **by** *auto*

qed

lemma *PrefixCSP-type [closure]*: *PrefixCSP* $a \in \llbracket H \rrbracket_H \rightarrow \llbracket \text{CSP} \rrbracket_H$

using *CSP-PrefixCSP* **by** *blast*

lemma *PrefixCSP-Continuous [closure]: Continuous (PrefixCSP a)*
by (*simp add: Continuous-def PrefixCSP-def ContinuousD[OF SRD-Continuous] seq-Sup-distl*)

lemma *PrefixCSP-RHS-tri-lemma1:*
 $R1 (R2s (U(\$tr = \$tr @ \llbracket a \rrbracket_{S<}) \wedge \llbracket II \rrbracket_R)) = (U(\$tr = \$tr @ \llbracket a \rrbracket_{S<}) \wedge \llbracket II \rrbracket_R)$
by (*rel-auto*)

lemma *PrefixCSP-RHS-tri-lemma2:*
fixes $P :: ('σ, 'φ) \text{ action}$
assumes $\$ok \# P \$wait \# P$
shows $(U(\$tr = \$tr @ \llbracket a \rrbracket_{S<}) \wedge \$st = \$st) \wedge \neg \$wait ;; P = (\exists \$ref \cdot P \llbracket U(\$tr @ \llbracket a \rrbracket_{S<}) / \$tr \rrbracket)$
using *assms*
by (*rel-auto, meson, fastforce*)

lemma *tr-extend-seqr:*
fixes $P :: ('σ, 'φ) \text{ action}$
assumes $\$ok \# P \$wait \# P \$ref \# P$
shows $U(\$tr = \$tr @ \llbracket a \rrbracket_{S<}) \wedge \$st = \$st ;; P = P \llbracket U(\$tr @ \llbracket a \rrbracket_{S<}) / \$tr \rrbracket$
using *assms* **by** (*simp add: wp-rea-DoCSP-lemma assms unrest ex-unrest*)

lemma *trace-ext-R1-closed [closure]: P is R1 \implies P $\hat{\sim}_u$ e / \$tr is R1*
by (*rel-blast*)

lemma *preR-PrefixCSP-NCSP [rdes]:*
assumes $P \text{ is NCSP}$
shows $pre_R(PrefixCSP a P) = (\Phi(true, id_s, U(\llbracket a \rrbracket)) \wp_r pre_R P)$
by (*simp add: PrefixCSP-def assms closure rdes rpred Healthy-if wp usubst unrest*)

lemma *PrefixCSP-RHS-tri:*
assumes $P \text{ is NCSP}$
shows $PrefixCSP a P = \mathbf{R}_s (\Phi(true, id_s, U(\llbracket a \rrbracket)) \wp_r pre_R P \vdash (\mathcal{E}(true, \llbracket \cdot \rrbracket, \{a\}_u) \vee \Phi(true, id_s, U(\llbracket a \rrbracket)))$
 $;; peri_R P \diamond \Phi(true, id_s, U(\llbracket a \rrbracket)) ;; post_R P$
by (*simp add: PrefixCSP-def Healthy-if unrest assms closure NSRD-composition-wp rdes rpred usubst wp*)

For prefix, we can chose whether to propagate the assumptions or not, hence there are two laws.

lemma *PrefixCSP-rdes-def-1 [rdes-def]:*
assumes $P \text{ is CRC } Q \text{ is CRR } R \text{ is CRR}$
 $\$st \# Q \$ref \# R$
shows $PrefixCSP a (\mathbf{R}_s (P \vdash Q \diamond R)) =$
 $\mathbf{R}_s (\Phi(true, id_s, U(\llbracket a \rrbracket)) \wp_r P \vdash (\mathcal{E}(true, \llbracket \cdot \rrbracket, \{a\}_u) \vee \Phi(true, id_s, U(\llbracket a \rrbracket))) ;; Q \diamond$
 $\Phi(true, id_s, U(\llbracket a \rrbracket)) ;; R$
by (*simp add: PrefixCSP-def Healthy-if assms closure, rdes-simp cls: assms*)

8.14 Guarded external choice

abbreviation *GuardedChoiceCSP* $:: 'v \text{ set} \Rightarrow ('v \Rightarrow ('σ, 'v) \text{ action}) \Rightarrow ('σ, 'v) \text{ action}$ **where**
 $GuardedChoiceCSP A P \equiv (\Box x \in A \cdot PrefixCSP \llbracket x \rrbracket (P(x)))$

syntax

-GuardedChoiceCSP $:: logic \Rightarrow logic \Rightarrow logic \Rightarrow logic (\Box - \in - \rightarrow - [0, 0, 85] 86)$

translations

$\Box x \in A \rightarrow P == CONST \text{ GuardedChoiceCSP } A (\lambda x. P)$

lemma *GuardedChoiceCSP* [rdes-def]:
assumes $\bigwedge x. P(x)$ is NCSP $A \neq \{\}$
shows $(\square x \in A \rightarrow P(x)) =$
 $\mathbf{R}_s ((\square x \in A \cdot \Phi(\text{true}, id_s, \llbracket x \rrbracket) \text{ } wp_r \text{ } pre_R (P \ x)) \vdash$
 $((\square x \in A \cdot \mathcal{E}(\text{true}, \llbracket \cdot \rrbracket, \{\llbracket x \rrbracket\}_u)) \triangleleft \$tr =_u \$tr \triangleright (\square x \in A \cdot \Phi(\text{true}, id_s, \llbracket x \rrbracket) \text{ } ;; \text{ } peri_R$
 $(P \ x))) \diamond$
 $(\square x \in A \cdot \Phi(\text{true}, id_s, \llbracket x \rrbracket) \text{ } ;; \text{ } post_R (P \ x)))$
by (simp add: PrefixCSP-RHS-tri assms ExtChoice-tri-rdes closure unrest, rel-auto)

8.15 Input prefix

definition *InputCSP* ::
 $('a, ' \vartheta) \text{ chan} \Rightarrow ('a \Rightarrow ' \sigma \text{ upred}) \Rightarrow ('a \Rightarrow (' \sigma, ' \vartheta) \text{ action}) \Rightarrow (' \sigma, ' \vartheta) \text{ action}$ **where**
[upred-defs]: *InputCSP* $c \ A \ P = (\square x \in UNIV \cdot A(x) \ \&_C \ \text{PrefixCSP} \ (c \cdot \llbracket x \rrbracket)_u \ (P \ x))$

definition *InputVarCSP* :: $('a, ' \vartheta) \text{ chan} \Rightarrow ('a \Longrightarrow ' \sigma) \Rightarrow ('a \Rightarrow ' \sigma \text{ upred}) \Rightarrow (' \sigma, ' \vartheta) \text{ action}$ **where**
[upred-defs, rdes-def]: *InputVarCSP* $c \ x \ A = \text{InputCSP} \ c \ A \ (\lambda v. \llbracket x \mapsto_s \llbracket v \rrbracket \rrbracket_C)$

definition *do_I* ::
 $('a, ' \vartheta) \text{ chan} \Rightarrow$
 $('a \Longrightarrow (' \sigma, ' \vartheta) \text{ sfrd}) \Rightarrow$
 $('a \Rightarrow (' \sigma, ' \vartheta) \text{ action}) \Rightarrow$
 $(' \sigma, ' \vartheta) \text{ action}$ **where**
do_I $c \ x \ P =$
 $(\$tr =_u \$tr \wedge \{e \mid P(e) \cdot (c \cdot \llbracket e \rrbracket)_u\} \cap_u \$ref =_u \{\}_u)$
 $\triangleleft \$wait \triangleright$
 $((\$tr - \$tr) \in_u \{e \mid P(e) \cdot U([\llbracket c \cdot \llbracket e \rrbracket \rrbracket])\} \wedge (c \cdot \$x)_u =_u \text{last}_u(\$tr)))$

lemma *InputCSP-CSP* [closure]: *InputCSP* $c \ A \ P$ is CSP
by (simp add: CSP-ExtChoice InputCSP-def)

lemma *InputCSP-NCSP* [closure]: $\llbracket \bigwedge v. P(v) \text{ is NCSP} \rrbracket \Longrightarrow \text{InputCSP} \ c \ A \ P \text{ is NCSP}$
apply (simp add: InputCSP-def)
apply (rule NCSP-ExtChoice)
apply (simp add: NCSP-Guard NCSP-PrefixCSP image-Collect-subsetI top-set-def)
done

lemma *InputVarCSP-NCSP* [closure]: *InputVarCSP* $c \ x \ A$ is NCSP
by (simp add: AssignsCSP-NCSP InputCSP-NCSP InputVarCSP-def)

lemma *Productive-InputCSP* [closure]:
 $\llbracket \bigwedge v. P(v) \text{ is NCSP} \rrbracket \Longrightarrow \text{InputCSP} \ x \ A \ P \text{ is Productive}$
by (auto simp add: InputCSP-def unrest closure intro: Productive-ExtChoice)

lemma *Productive-InputVarCSP* [closure]: *InputVarCSP* $c \ x \ A$ is Productive
by (simp add: InputVarCSP-def closure)

lemma *R4-st-pred-conj-do* [rpred]:
 $((R4 \ [s_1]_{s<}) \wedge \Phi(s_2, \sigma, t) \text{ } ;; \ P) = R4(\Phi(s_1 \wedge s_2, \sigma, t) \text{ } ;; \ P)$
by (rel-auto)

lemma *unrest-ref'-R4* [unrest]: $\$ref \ \# \ P \Longrightarrow \$ref \ \# \ R4(P)$
by (simp add: R4-def unrest)

lemma *st-pred-conj-seq* [*rpred*]:

$\llbracket P \text{ is } RR; Q \text{ is } RR \rrbracket \implies ([s]_{S<} \wedge P ;; Q) = ([s]_{S<} \wedge P) ;; Q$
by (*metis* (*no-types*, *lifting*) *R1-seqr-closure* *RR-implies-R1* *cond-st-distr* *cond-st-miracle* *seqr-left-zero*)

lemma *InputCSP-rdes-def* [*rdes-def*]:

assumes $\bigwedge v. P(v) \text{ is } CRC \bigwedge v. Q(v) \text{ is } CRR \bigwedge v. R(v) \text{ is } CRR$

$\bigwedge v. \$st \nmid Q(v) \bigwedge v. \$ref \nmid R(v)$

shows *InputCSP* *a* *A* $(\lambda v. \mathbf{R}_s(P(v) \vdash Q(v) \diamond R(v))) =$

$\mathbf{R}_s((\bigsqcup x \cdot \Phi(A x, id_s, U([(a \cdot \langle x \rangle)_u]))) \text{ wp}_r P x) \vdash$

$((\bigsqcup x \cdot \mathcal{E}(A x, \langle \square \rangle, \{(a \cdot \langle x \rangle)_u\}_u) \vee \mathcal{E}(\neg A x, \langle \square \rangle, \{\}_u)) \vee (\bigsqcup x \cdot \Phi(A x, id_s, U([(a \cdot \langle x \rangle)_u]))) ;;$

$Q x) \diamond$

$(\bigsqcup x \cdot \Phi(A x, id_s, U([(a \cdot \langle x \rangle)_u]))) ;; R x)$

by (*simp* *add*: *InputCSP-def*, *rdes-simp* *cls*: *assms*)

8.16 Renaming

definition *RenameCSP* $:: ('s, 'e) \text{ action} \Rightarrow ('e \Rightarrow 'f) \Rightarrow ('s, 'f) \text{ action } ((-) \Downarrow_C [999, 0] 999) \text{ where}$
[upred-defs]: *RenameCSP* *P* *f* $= \mathbf{R}_s((\neg_r (\neg_r \text{pre}_R(P)) \Downarrow_c ;; \text{true}_r) \vdash ((\text{peri}_R(P)) \Downarrow_c) \diamond ((\text{post}_R(P)) \Downarrow_c))$

lemma *RenameCSP-rdes-def* [*rdes-def*]:

assumes *P* *is* *CRC* *Q* *is* *CRR* *R* *is* *CRR*

shows $(\mathbf{R}_s(P \vdash Q \diamond R)) \Downarrow_c = \mathbf{R}_s((\neg_r (\neg_r P) \Downarrow_c ;; \text{true}_r) \vdash Q \Downarrow_c \diamond R \Downarrow_c)$ (*is* *?lhs* = *?rhs*)

proof –

have *?lhs* $= \mathbf{R}_s((\neg_r (\neg_r P) \Downarrow_c ;; \text{true}_r) \vdash (P \Rightarrow_r Q) \Downarrow_c \diamond (P \Rightarrow_r R) \Downarrow_c)$

by (*simp* *add*: *RenameCSP-def* *rdes* *closure* *assms*)

also have $\dots = \mathbf{R}_s((\neg_r (\neg_r \text{CRC}(P)) \Downarrow_c ;; \text{true}_r) \vdash (\text{CRC}(P) \Rightarrow_r \text{CRR}(Q)) \Downarrow_c \diamond (\text{CRC}(P) \Rightarrow_r \text{CRR}(R)) \Downarrow_c)$

by (*simp* *add*: *Healthy-if* *assms*)

also have $\dots = \mathbf{R}_s((\neg_r (\neg_r \text{CRC}(P)) \Downarrow_c ;; \text{true}_r) \vdash (\text{CRR}(Q)) \Downarrow_c \diamond (\text{CRR}(R)) \Downarrow_c)$

by (*rel-auto*, (*metis* *order-refl*)+)

also have $\dots = \text{?rhs}$

by (*simp* *add*: *Healthy-if* *assms*)

finally show *?thesis* .

qed

lemma *RenameCSP-pre-CRC-closed*:

assumes *P* *is* *CRR*

shows $\neg_r (\neg_r P) \Downarrow_c ;; R1 \text{ true is } CRC$

apply (*rule* *CRC-intro''*)

apply (*simp* *add*: *unrest* *closure* *assms*)

apply (*simp* *add*: *Healthy-def*, *simp* *add*: *RC1-def* *rpred* *closure* *CRC-idem* *assms* *seqr-assoc*)

done

lemma *RenameCSP-NCSP-closed* [*closure*]:

assumes *P* *is* *NCSP*

shows $P \Downarrow_c \text{ is } NCSP$

by (*simp* *add*: *RenameCSP-def* *RenameCSP-pre-CRC-closed* *closure* *assms* *unrest*)

lemma *csp-rename-false* [*rpred*]:

$\text{false} \Downarrow_c = \text{false}$

by (*rel-auto*)

lemma *umap-nil* [*simp*]: $\text{map}_u f \langle \square \rangle = \langle \square \rangle$

by (*rel-auto*)

lemma *rename-Skip*: $Skip(\lfloor f \rfloor)_C = Skip$
by (*rdes-eq*)

lemma *rename-Chaos*: $Chaos(\lfloor f \rfloor)_C = Chaos$
by (*rdes-eq-split*; *rel-simp*; *force*)

lemma *rename-Miracle*: $Miracle(\lfloor f \rfloor)_C = Miracle$
by (*rdes-eq*)

lemma *rename-DoCSP*: $(do_C(a))(\lfloor f \rfloor)_C = do_C(\langle f \rangle(a)_a)$
by (*rdes-eq*)

8.17 Algebraic laws

lemma *AssignCSP-conditional*:
assumes *vwb-lens* *x*
shows $x :=_C e \triangleleft b \triangleright_R x :=_C f = x :=_C (e \triangleleft b \triangleright f)$
by (*rdes-eq cls: assms*)

lemma *AssignsCSP-id*: $\langle id_s \rangle_C = Skip$
by (*rel-auto*)

lemma *Guard-comp*:
 $g \&_C h \&_C P = (g \wedge h) \&_C P$
by (*rule antisym*, *rel-blast*, *rel-blast*)

lemma *Guard-false* [*simp*]: $false \&_C P = Stop$
by (*simp add: GuardCSP-def Stop-def rpred closure alpha R1-design-R1-pre*)

lemma *Guard-true* [*simp*]:
 $P \text{ is CSP} \implies true \&_C P = P$
by (*simp add: GuardCSP-def alpha SRD-reactive-design-alt closure rpred*)

lemma *Guard-conditional*:
assumes *P is NCSP*
shows $b \&_C P = P \triangleleft b \triangleright_R Stop$
by (*rdes-eq cls: assms*)

lemma *Guard-expansion*:
assumes *P is NCSP*
shows $(g_1 \vee g_2) \&_C P = (g_1 \&_C P) \sqcap (g_2 \&_C P)$
apply (*rdes-eq-split cls: assms*)
apply (*rel-simp'*, *fastforce simp add: dual-order.order-iff-strict*)
apply (*rel-simp'*, *simp add: dual-order.order-iff-strict, fastforce*)
apply (*rel-simp'*, *simp add: dual-order.order-iff-strict, fastforce*)
done

lemma *Conditional-as-Guard*:
assumes *P is NCSP* *Q is NCSP*
shows $P \triangleleft b \triangleright_R Q = b \&_C P \sqcap (\neg b) \&_C Q$
by (*rdes-eq' cls: assms; simp add: le-less*)

lemma *PrefixCSP-dist*:
 $PrefixCSP\ a\ (P \sqcap Q) = (PrefixCSP\ a\ P) \sqcap (PrefixCSP\ a\ Q)$
using *Continuous-Disjunctous Disjunctuous-def PrefixCSP-Continuous* **by** *auto*

lemma *DoCSP-is-Prefix*:

$do_C(a) = PrefixCSP\ a\ Skip$

by (*simp add: PrefixCSP-def Healthy-if closure, metis CSP4-DoCSP CSP4-def Healthy-def*)

lemma *PrefixCSP-seq*:

assumes $P\ is\ CSP\ Q\ is\ CSP$

shows $(PrefixCSP\ a\ P) \;;\ Q = (PrefixCSP\ a\ (P \;;\ Q))$

by (*simp add: PrefixCSP-def seqr-assoc Healthy-if assms closure*)

lemma *PrefixCSP-extChoice-dist*:

assumes $P\ is\ NCSP\ Q\ is\ NCSP\ R\ is\ NCSP$

shows $((a \rightarrow_C P) \sqcap (b \rightarrow_C Q)) \;;\ R = (a \rightarrow_C P \;;\ R) \sqcap (b \rightarrow_C Q \;;\ R)$

by (*simp add: PCSP-PrefixCSP assms(1) assms(2) assms(3) extChoice-seq-distr*)

lemma *GuardedChoiceCSP-dist*:

assumes $\bigwedge i. i \in A \implies P(i)\ is\ NCSP\ Q\ is\ NCSP$

shows $\square x \in A \rightarrow P(x) \;;\ Q = \square x \in A \rightarrow (P(x) \;;\ Q)$

by (*simp add: ExtChoice-seq-distr PrefixCSP-seq closure assms cong: ExtChoice-cong*)

Alternation can be re-expressed as an external choice when the guards are disjoint

declare *ExtChoice-tri-rdes* [*rdes-def*]

declare *ExtChoice-tri-rdes'* [*rdes-def del*]

declare *extChoice-rdes-def* [*rdes-def*]

declare *extChoice-rdes-def'* [*rdes-def del*]

lemma *AlternateR-as-ExtChoice*:

assumes

$\bigwedge i. i \in A \implies P(i)\ is\ NCSP\ Q\ is\ NCSP$

$\bigwedge i\ j. \llbracket i \in A; j \in A; i \neq j \rrbracket \implies (g\ i \wedge g\ j) = false$

shows $(if_R\ i \in A \cdot g(i) \rightarrow P(i)\ else\ Q\ fi) =$

$(\square i \in A \cdot g(i) \ \&_C\ P(i)) \sqcap (\bigwedge i \in A \cdot \neg g(i) \ \&_C\ Q)$

proof (*cases* $A = \{\}$)

case *True*

then show *?thesis* **by** (*simp add: ExtChoice-empty extChoice-Stop closure assms*)

next

case *False*

show *?thesis*

proof –

have $1: (\square i \in A \cdot g\ i \rightarrow_R P\ i) = (\square i \in A \cdot g\ i \rightarrow_R \mathbf{R}_s(pre_R(P\ i) \vdash peri_R(P\ i) \diamond post_R(P\ i)))$

by (*rule UINF-cong, simp add: NCSP-implies-CSP SRD-reactive-tri-design assms(1)*)

have $2: (\square i \in A \cdot g(i) \ \&_C\ P(i)) = (\square i \in A \cdot g(i) \ \&_C\ \mathbf{R}_s(pre_R(P\ i) \vdash peri_R(P\ i) \diamond post_R(P\ i)))$

by (*rule ExtChoice-cong, simp add: NCSP-implies-NSRD NSRD-is-SRD SRD-reactive-tri-design assms(1)*)

from *assms(3)* **show** *?thesis*

by (*simp add: AlternateR-def 1 2*)

(*rdes-eq' cls: assms(1–2)_simps: False cong: UINF-cong USUP-cong ExtChoice-cong*)

qed

qed

declare *ExtChoice-tri-rdes* [*rdes-def del*]

declare *ExtChoice-tri-rdes'* [*rdes-def*]

declare *extChoice-rdes-def* [*rdes-def del*]

declare *extChoice-rdes-def'* [*rdes-def*]

find-theorems *R4*

end

9 Recursion in Stateful-Failures

theory *utp-sfrd-recursion*

imports *utp-sfrd-contracts utp-sfrd-prog*

begin

9.1 Fixed-points

The CSP weakest fixed-point is obtained simply by precomposing the body with the CSP healthiness condition.

abbreviation *mu-CSP* :: $((\sigma, \varphi) \text{ action} \Rightarrow (\sigma, \varphi) \text{ action}) \Rightarrow (\sigma, \varphi) \text{ action}$ (μ_C) **where**
 $\mu_C F \equiv \mu (F \circ \text{CSP})$

syntax

-mu-CSP :: *pttrn* \Rightarrow *logic* \Rightarrow *logic* (μ_C - · - [0, 10] 10)

translations

$\mu_C X \cdot P == \text{CONST } \text{mu-CSP } (\lambda X. P)$

lemma *mu-CSP-equiv*:

assumes *Monotonic F* $F \in \llbracket \text{CSP} \rrbracket_H \rightarrow \llbracket \text{CSP} \rrbracket_H$

shows $(\mu_R F) = (\mu_C F)$

by (*simp add: srd-mu-equiv assms comp-def*)

lemma *mu-CSP-unfold*:

P is CSP $\implies (\mu_C X \cdot P ;; X) = P ;; (\mu_C X \cdot P ;; X)$

apply (*subst gfp-unfold*)

apply (*simp-all add: closure Healthy-if*)

done

lemma *mu-csp-expand* [*rdes*]: $(\mu_C ((;;) Q)) = (\mu X \cdot Q ;; \text{CSP } X)$

by (*simp add: comp-def*)

lemma *mu-csp-basic-refine*:

assumes

P is CSP Q is NCSP Q is Productive $\text{pre}_R(P) = \text{true}_r$ $\text{pre}_R(Q) = \text{true}_r$

$\text{peri}_R P \sqsubseteq \text{peri}_R Q$

$\text{peri}_R P \sqsubseteq \text{post}_R Q ;; \text{peri}_R P$

shows $P \sqsubseteq (\mu_C X \cdot Q ;; X)$

proof (*rule SRD-refine-intro', simp-all add: closure usubst alpha rpred rdes unrest wp seq-UINF-distr assms*)

show $\text{peri}_R P \sqsubseteq (\bigcap i \cdot \text{post}_R Q \wedge i ;; \text{peri}_R Q)$

proof (*rule UINF-refines'*)

fix *i*

show $\text{peri}_R P \sqsubseteq \text{post}_R Q \wedge i ;; \text{peri}_R Q$

proof (*induct i*)

case 0

then show ?*case* **by** (*simp add: assms*)

```

next
  case (Suc i)
  then show ?case
    by (meson assms(6) assms(7) semilattice-sup-class.le-sup-iff upower-inductl)
qed
qed
qed

```

lemma *CRD-mu-basic-refine*:

fixes $P :: 'e \text{ list} \Rightarrow 'e \text{ set} \Rightarrow 's \text{ upred}$

assumes

$Q \text{ is NCSP } Q \text{ is Productive } \text{pre}_R(Q) = \text{true}_r$

$[P \ t \ r]_{S<} \llbracket (t, r) \rightarrow (\&tt, \$ref)_u \rrbracket \sqsubseteq \text{peri}_R \ Q$

$[P \ t \ r]_{S<} \llbracket (t, r) \rightarrow (\&tt, \$ref)_u \rrbracket \sqsubseteq \text{post}_R \ Q \ ;\ ;_h \ [P \ t \ r]_{S<} \llbracket (t, r) \rightarrow (\&tt, \$ref)_u \rrbracket$

shows $[\text{true} \vdash P \text{ trace refs} \mid R]_C \sqsubseteq (\mu_C \ X \cdot Q \ ;\ ; \ X)$

proof (rule *mu-csp-basic-refine*, *simp-all add: msubst-pair assms closure alpha rdes rpred Healthy-if R1-false*)

show $[P \text{ trace refs}]_{S<} \llbracket \text{trace} \rightarrow \&tt \rrbracket \llbracket \text{refs} \rightarrow \$ref \rrbracket \sqsubseteq \text{peri}_R \ Q$

using *assms* **by** (*simp add: msubst-pair*)

show $[P \text{ trace refs}]_{S<} \llbracket \text{trace} \rightarrow \&tt \rrbracket \llbracket \text{refs} \rightarrow \$ref \rrbracket \sqsubseteq \text{post}_R \ Q \ ;\ ; \ [P \text{ trace refs}]_{S<} \llbracket \text{trace} \rightarrow \&tt \rrbracket \llbracket \text{refs} \rightarrow \$ref \rrbracket$

using *assms* **by** (*simp add: msubst-pair*)

qed

9.2 Example action expansion

lemma *mu-example1*: $(\mu \ X \cdot \langle a \rangle \rightarrow_C \ X) = (\bigcap i \cdot \text{do}_C(\langle a \rangle) \wedge (i+1)) \ ;\ ; \ \text{Miracle}$

by (*simp add: PrefixCSP-def mu-csp-form-1 closure*)

lemma *preR-mu-example1* [*rdes*]: $\text{pre}_R(\mu \ X \cdot \langle a \rangle \rightarrow_C \ X) = \text{true}_r$

by (*simp add: mu-example1 rdes closure unrest wp*)

lemma *periR-mu-example1* [*rdes*]:

$\text{peri}_R(\mu \ X \cdot \langle a \rangle \rightarrow_C \ X) = (\bigcap i \cdot \mathcal{E}(\text{true}, \text{iter}[i](U([\langle a \rangle])), \{ \langle a \rangle \}_u))$

by (*simp add: mu-example1 rdes rpred closure unrest wp seq-UNF-distr alpha usubst*)

lemma *postR-mu-example1* [*rdes*]:

$\text{post}_R(\mu \ X \cdot \langle a \rangle \rightarrow_C \ X) = \text{false}$

by (*simp add: mu-example1 rdes closure unrest wp*)

end

10 Linking to the Failures-Divergences Model

theory *utp-sfrd-fdsem*

imports *utp-sfrd-recursion*

begin

10.1 Failures-Divergences Semantics

The following functions play a similar role to those in Roscoe's CSP semantics, and are calculated from the Circus reactive design semantics. A major difference is that these three functions account for state. Each divergence, trace, and failure is subject to an initial state. Moreover, the traces are terminating traces, and therefore also provide a final state following the given interaction. A more subtle difference from the Roscoe semantics is that the set of traces do not

include the divergences. The same semantic information is present, but we construct a direct analogy with the pre-, peri- and postconditions of our reactive designs.

definition *divergences* :: (σ, φ) action $\Rightarrow \sigma \Rightarrow \varphi$ list set $(dv[-] - [0,100] \ 100)$ **where**
 $[upred-defs]:$ *divergences* $P \ s = \{t \mid t. (\neg_r \ pre_R(P)) \llbracket \langle s \rangle, \langle [] \rangle, \langle t \rangle / \$st, \$tr, \$tr \rrbracket \}$

definition *traces* :: (σ, φ) action $\Rightarrow \sigma \Rightarrow (\varphi \text{ list} \times \sigma)$ set $(tr[-] - [0,100] \ 100)$ **where**
 $[upred-defs]:$ *traces* $P \ s = \{(t, s') \mid t \ s'. (\pre_R(P) \wedge \text{post}_R(P)) \llbracket \langle s \rangle, \langle s' \rangle, \langle [] \rangle, \langle t \rangle / \$st, \$st, \$tr, \$tr \rrbracket \}$

definition *failures* :: (σ, φ) action $\Rightarrow \sigma \Rightarrow (\varphi \text{ list} \times \varphi \text{ set})$ set $(fl[-] - [0,100] \ 100)$ **where**
 $[upred-defs]:$ *failures* $P \ s = \{(t, r) \mid t \ r. (\pre_R(P) \wedge \text{peri}_R(P)) \llbracket \langle r \rangle, \langle s \rangle, \langle [] \rangle, \langle t \rangle / \$ref, \$st, \$tr, \$tr \rrbracket \}$

lemma *trace-divergence-disj*:

assumes P is NCSP $(t, s') \in tr \llbracket P \rrbracket s \ t \in dv \llbracket P \rrbracket s$
shows *False*
using *assms(2,3)*
by (*simp add: traces-def divergences-def, rdes-simp cls:assms, rel-auto*)

lemma *preR-refine-divergences*:

assumes P is NCSP Q is NCSP $\wedge s. dv \llbracket P \rrbracket s \subseteq dv \llbracket Q \rrbracket s$
shows $\pre_R(P) \sqsubseteq \pre_R(Q)$
proof (*rule CRR-refine-impl-prop, simp-all add: assms closure usubst unrest*)
fix $t \ s$
assume $a: \llbracket \$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle \rrbracket \dagger \pre_R Q$
with a **show** $\llbracket \$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle \rrbracket \dagger \pre_R P$
proof (*rule-tac ccontr*)
from *assms(3)[of s]* **have** $b: t \in dv \llbracket P \rrbracket s \implies t \in dv \llbracket Q \rrbracket s$
by (*auto*)
assume $\neg \llbracket \$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle \rrbracket \dagger \pre_R P$
hence $\neg \llbracket \$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle \rrbracket \dagger CRC(\pre_R P)$
by (*simp add: assms closure Healthy-if*)
hence $\llbracket \$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle \rrbracket \dagger (\neg_r CRC(\pre_R P))$
by (*rel-auto*)
hence $\llbracket \$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle \rrbracket \dagger (\neg_r \pre_R P)$
by (*simp add: assms closure Healthy-if*)
with $a \ b$ **show** *False*
by (*rel-auto*)
qed
qed

lemma *preR-eq-divergences*:

assumes P is NCSP Q is NCSP $\wedge s. dv \llbracket P \rrbracket s = dv \llbracket Q \rrbracket s$
shows $\pre_R(P) = \pre_R(Q)$
by (*metis assms dual-order.antisym order-refl preR-refine-divergences*)

lemma *periR-refine-failures*:

assumes P is NCSP Q is NCSP $\wedge s. fl \llbracket Q \rrbracket s \subseteq fl \llbracket P \rrbracket s$
shows $(\pre_R(P) \wedge \text{peri}_R(P)) \sqsubseteq (\pre_R(Q) \wedge \text{peri}_R(Q))$
proof (*rule CRR-refine-impl-prop, simp-all add: assms closure unrest subst-unrest-3*)
fix $t \ s \ r'$
assume $a: \llbracket \$ref \mapsto_s \langle r' \rangle, \$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle \rrbracket \dagger (\pre_R Q \wedge \text{peri}_R Q)$
from *assms(3)[of s]* **have** $b: (t, r') \in fl \llbracket Q \rrbracket s \implies (t, r') \in fl \llbracket P \rrbracket s$
by (*auto*)
with a **show** $\llbracket \$ref \mapsto_s \langle r' \rangle, \$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle \rrbracket \dagger (\pre_R P \wedge \text{peri}_R P)$
by (*simp add: failures-def*)
qed

lemma *periR-eq-failures*:

assumes P is NCSP Q is NCSP $\wedge s. fl[P]s = fl[Q]s$

shows $(pre_R(P) \wedge peri_R(P)) = (pre_R(Q) \wedge peri_R(Q))$

by (*metis* (*full-types*) *assms dual-order.antisym order-refl periR-refine-failures*)

lemma *postR-refine-traces*:

assumes P is NCSP Q is NCSP $\wedge s. tr[Q]s \subseteq tr[P]s$

shows $(pre_R(P) \wedge post_R(P)) \sqsubseteq (pre_R(Q) \wedge post_R(Q))$

proof (*rule CRR-refine-impl-prop, simp-all add: assms closure unrest subst-unrest-5*)

fix $t s s'$

assume $a: \langle \$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle \rangle \dagger (pre_R Q \wedge post_R Q)'$

from *assms*(3)[*of s*] **have** $b: (t, s') \in tr[Q]s \implies (t, s') \in tr[P]s$

by (*auto*)

with a **show** $\langle \$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle \rangle \dagger (pre_R P \wedge post_R P)'$

by (*simp add: traces-def*)

qed

lemma *postR-eq-traces*:

assumes P is NCSP Q is NCSP $\wedge s. tr[P]s = tr[Q]s$

shows $(pre_R(P) \wedge post_R(P)) = (pre_R(Q) \wedge post_R(Q))$

by (*metis assms dual-order.antisym order-refl postR-refine-traces*)

lemma *circus-fd-refine-intro*:

assumes P is NCSP Q is NCSP $\wedge s. dv[Q]s \subseteq dv[P]s \wedge s. fl[Q]s \subseteq fl[P]s \wedge s. tr[Q]s \subseteq tr[P]s$

shows $P \sqsubseteq Q$

proof (*rule SRD-refine-intro', simp-all add: closure assms*)

show $a: pre_R P \Rightarrow pre_R Q'$

using *assms*(1) *assms*(2) *assms*(3) *preR-refine-divergences refBy-order* **by** *blast*

show $peri_R P \sqsubseteq (pre_R P \wedge peri_R Q)$

proof –

have $peri_R P \sqsubseteq (pre_R Q \wedge peri_R Q)$

by (*metis* (*no-types*) *assms*(1) *assms*(2) *assms*(4) *periR-refine-failures utp-pred-laws.le-inf-iff*)

then show *?thesis*

by (*metis a refBy-order utp-pred-laws.inf.order-iff utp-pred-laws.inf-assoc*)

qed

show $post_R P \sqsubseteq (pre_R P \wedge post_R Q)$

proof –

have $post_R P \sqsubseteq (pre_R Q \wedge post_R Q)$

by (*meson assms*(1) *assms*(2) *assms*(5) *postR-refine-traces utp-pred-laws.le-inf-iff*)

then show *?thesis*

by (*metis a refBy-order utp-pred-laws.inf.absorb-iff1 utp-pred-laws.inf-assoc*)

qed

qed

10.2 Circus Operators

lemma *traces-Skip*:

$tr[Skip]s = \{([], s)\}$

by (*simp add: traces-def rdes alpha closure, rel-simp*)

lemma *failures-Skip*:

$fl[Skip]s = \{\}$

by (*simp add: failures-def, rdes-calc*)

lemma *divergences-Skip*:

$dv\llbracket Skip \rrbracket s = \{\}$
by (*simp add: divergences-def, rdes-calc*)

lemma *traces-Stop*:
 $tr\llbracket Stop \rrbracket s = \{\}$
by (*simp add: traces-def, rdes-calc*)

lemma *failures-Stop*:
 $fl\llbracket Stop \rrbracket s = \{(\llbracket \cdot \rrbracket, E) \mid E. True\}$
by (*simp add: failures-def, rdes-calc, rel-auto*)

lemma *divergences-Stop*:
 $dv\llbracket Stop \rrbracket s = \{\}$
by (*simp add: divergences-def, rdes-calc*)

lemma *traces-AssignsCSP*:
 $tr\llbracket \langle \sigma \rangle_C \rrbracket s = \{(\llbracket \cdot \rrbracket, \llbracket \sigma \rrbracket_e s)\}$
by (*simp add: traces-def rdes closure usubst alpha, rel-auto*)

lemma *failures-AssignsCSP*:
 $fl\llbracket \langle \sigma \rangle_C \rrbracket s = \{\}$
by (*simp add: failures-def, rdes-calc*)

lemma *divergences-AssignsCSP*:
 $dv\llbracket \langle \sigma \rangle_C \rrbracket s = \{\}$
by (*simp add: divergences-def, rdes-calc*)

lemma *failures-Miracle*: $fl\llbracket Miracle \rrbracket s = \{\}$
by (*simp add: failures-def rdes closure usubst*)

lemma *divergences-Miracle*: $dv\llbracket Miracle \rrbracket s = \{\}$
by (*simp add: divergences-def rdes closure usubst*)

lemma *failures-Chaos*: $fl\llbracket Chaos \rrbracket s = \{\}$
by (*simp add: failures-def rdes, rel-auto*)

lemma *divergences-Chaos*: $dv\llbracket Chaos \rrbracket s = UNIV$
by (*simp add: divergences-def rdes, rel-auto*)

lemma *traces-Chaos*: $tr\llbracket Chaos \rrbracket s = \{\}$
by (*simp add: traces-def rdes closure usubst*)

lemma *divergences-cond*:
assumes P is NCSP Q is NCSP
shows $dv\llbracket P \triangleleft b \triangleright_R Q \rrbracket s = (if (\llbracket b \rrbracket_e s) then dv\llbracket P \rrbracket s else dv\llbracket Q \rrbracket s)$
by (*rdes-simp cls: assms, simp add: divergences-def traces-def rdes closure rpred assms, rel-auto*)

lemma *traces-cond*:
assumes P is NCSP Q is NCSP
shows $tr\llbracket P \triangleleft b \triangleright_R Q \rrbracket s = (if (\llbracket b \rrbracket_e s) then tr\llbracket P \rrbracket s else tr\llbracket Q \rrbracket s)$
by (*rdes-simp cls: assms, simp add: divergences-def traces-def rdes closure rpred assms, rel-auto*)

lemma *failures-cond*:
assumes P is NCSP Q is NCSP
shows $fl\llbracket P \triangleleft b \triangleright_R Q \rrbracket s = (if (\llbracket b \rrbracket_e s) then fl\llbracket P \rrbracket s else fl\llbracket Q \rrbracket s)$

by (rdes-simp cls: assms, simp add: divergences-def failures-def rdes closure rpred assms, rel-auto)

lemma *divergences-guard*:
 assumes P is NCSP
 shows $dv\llbracket g \&_C P \rrbracket s = (\text{if } (\llbracket g \rrbracket_e s) \text{ then } dv\llbracket g \&_C P \rrbracket s \text{ else } \{\})$
 by (rdes-simp cls: assms, simp add: divergences-def traces-def rdes closure rpred assms, rel-auto)

lemma *traces-do*: $tr\llbracket do_C(e) \rrbracket s = \{(\llbracket e \rrbracket_e s, s)\}$
 by (rdes-simp, simp add: traces-def rdes closure rpred, rel-auto)

lemma *failures-do*: $fl\llbracket do_C(e) \rrbracket s = \{(\llbracket, E \rrbracket \mid E. \llbracket e \rrbracket_e s \notin E)\}$
 by (rdes-simp, simp add: failures-def rdes closure rpred usubst, rel-auto)

lemma *divergences-do*: $dv\llbracket do_C(e) \rrbracket s = \{\}$
 by (rel-auto)

lemma *divergences-seq*:
 fixes $P :: ('s, 'e) \text{ action}$
 assumes P is NCSP Q is NCSP
 shows $dv\llbracket P ;; Q \rrbracket s = dv\llbracket P \rrbracket s \cup \{t_1 @ t_2 \mid t_1 \ t_2 \ s_0. (t_1, s_0) \in tr\llbracket P \rrbracket s \wedge t_2 \in dv\llbracket Q \rrbracket s_0\}$
 (is ?lhs = ?rhs)
 oops

lemma *traces-seq*:
 fixes $P :: ('s, 'e) \text{ action}$
 assumes P is NCSP Q is NCSP
 shows $tr\llbracket P ;; Q \rrbracket s =$

$$\{(t_1 @ t_2, s') \mid t_1 \ t_2 \ s_0 \ s'. (t_1, s_0) \in tr\llbracket P \rrbracket s \wedge (t_2, s') \in tr\llbracket Q \rrbracket s_0$$

$$\wedge (t_1 @ t_2) \notin dv\llbracket P \rrbracket s$$

$$\wedge (\forall (t, s_1) \in tr\llbracket P \rrbracket s. t \leq t_1 @ t_2 \longrightarrow (t_1 @ t_2) - t \notin dv\llbracket Q \rrbracket s_1)\}$$

 (is ?lhs = ?rhs)

proof
 show ?lhs \subseteq ?rhs
proof (rdes-expand cls: assms, simp add: traces-def divergences-def rdes closure assms rdes-def unrest rpred usubst, auto)
 fix $t :: 'e \text{ list}$ and $s' :: 's$
 let $?\sigma = [\$st \mapsto_s \llbracket s \rrbracket, \$st' \mapsto_s \llbracket s' \rrbracket, \$tr \mapsto_s \llbracket \rrbracket, \$tr' \mapsto_s \llbracket t \rrbracket]$
 assume
 a1: $?\sigma \vdash (post_R P ;; post_R Q)'$ and
 a2: $[\$st \mapsto_s \llbracket s \rrbracket, \$tr \mapsto_s \llbracket \rrbracket, \$tr' \mapsto_s \llbracket t \rrbracket] \vdash pre_R P'$ and
 a3: $[\$st \mapsto_s \llbracket s \rrbracket, \$tr \mapsto_s \llbracket \rrbracket, \$tr' \mapsto_s \llbracket t \rrbracket] \vdash (post_R P \text{ wp}_r pre_R Q)'$
 from a1 have $?\sigma \vdash (\exists \ tr_0 \cdot ((post_R P)\llbracket \llbracket tr_0 \rrbracket / \$tr \rrbracket ;; (post_R Q)\llbracket \llbracket tr_0 \rrbracket / \$tr \rrbracket) \wedge \llbracket tr_0 \rrbracket \leq_u \tr'
 by (simp add: R2-tr-middle assms closure)
 then obtain tr_0 where $p1: ?\sigma \vdash ((post_R P)\llbracket \llbracket tr_0 \rrbracket / \$tr \rrbracket ;; (post_R Q)\llbracket \llbracket tr_0 \rrbracket / \$tr \rrbracket)'$ and $tr0: tr_0 \leq t$
 apply (simp add: usubst)
 apply (erule taut-shEx-elim)
 apply (simp add: unrest-all-circus-vars-st-st' closure unrest assms)
 apply (rel-auto)
 done
 from p1 have $?\sigma \vdash (\exists \ st_0 \cdot (post_R P)\llbracket \llbracket tr_0 \rrbracket / \$tr \rrbracket \llbracket \llbracket st_0 \rrbracket / \$st \rrbracket ;; (post_R Q)\llbracket \llbracket tr_0 \rrbracket / \$tr \rrbracket \llbracket \llbracket st_0 \rrbracket / \$st \rrbracket)'$
 by (simp add: seqr-middle[of st, THEN sym])
 then obtain s_0 where $?\sigma \vdash ((post_R P)\llbracket \llbracket s_0 \rrbracket, \llbracket tr_0 \rrbracket / \$st, \$tr \rrbracket ;; (post_R Q)\llbracket \llbracket s_0 \rrbracket, \llbracket tr_0 \rrbracket / \$st, \$tr \rrbracket)'$
 apply (simp add: usubst)
 apply (erule taut-shEx-elim)
 apply (simp add: unrest-all-circus-vars-st-st' closure unrest assms)

apply (rel-auto)
 done
 hence ‘ $([\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle tr_0 \rangle] \dagger post_R P) ;;$
 $([\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle tr_0 \rangle, \$tr \mapsto_s \langle t \rangle] \dagger post_R Q))'$
 by (rel-auto)
 hence ‘ $([\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle tr_0 \rangle] \dagger post_R P) \wedge$
 $([\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle tr_0 \rangle, \$tr \mapsto_s \langle t \rangle] \dagger post_R Q))'$
 by (simp add: segr-to-conj unrest-any-circus-var assms closure unrest)
 hence postP: ‘ $([\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle tr_0 \rangle] \dagger post_R P)'$ and
 postQ': ‘ $([\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle tr_0 \rangle, \$tr \mapsto_s \langle t \rangle] \dagger post_R Q)'$
 by (rel-auto)+
 from postQ' have ‘ $[\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle] \dagger [\$tr \mapsto_s \langle tr_0 \rangle, \$tr \mapsto_s \langle tr_0 \rangle + (\langle t \rangle - \langle tr_0 \rangle)] \dagger$
 $post_R Q'$
 using tr0 by (rel-auto)
 hence ‘ $[\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle] \dagger [\$tr \mapsto_s 0, \$tr \mapsto_s \langle t \rangle - \langle tr_0 \rangle] \dagger post_R Q'$
 by (simp add: R2-subst-tr closure assms)
 hence postQ: ‘ $[\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t - tr_0 \rangle] \dagger post_R Q'$
 by (rel-auto)
 have preP: ‘ $[\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle tr_0 \rangle] \dagger pre_R P'$
 proof –
 have $(pre_R P)[[0, \langle tr_0 \rangle] / \$tr, \$tr] \sqsubseteq (pre_R P)[[0, \langle t \rangle] / \$tr, \$tr]$
 by (simp add: RC-prefix-refine closure assms tr0)
 hence $[\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle tr_0 \rangle] \dagger pre_R P \sqsubseteq [\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle]$
 $\dagger pre_R P$
 by (rel-auto)
 thus ?thesis
 by (simp add: taut-refine-impl a2)
 qed

 have preQ: ‘ $[\$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t - tr_0 \rangle] \dagger pre_R Q'$
 proof –
 from postP a3 have ‘ $[\$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle tr_0 \rangle, \$tr \mapsto_s \langle t \rangle] \dagger pre_R Q'$
 apply (simp add: wp-rea-def)
 apply (rel-auto)
 using tr0 apply blast+
 done
 hence ‘ $[\$st \mapsto_s \langle s_0 \rangle] \dagger [\$tr \mapsto_s \langle tr_0 \rangle, \$tr \mapsto_s \langle tr_0 \rangle + (\langle t \rangle - \langle tr_0 \rangle)] \dagger pre_R Q'$
 by (rel-auto)

 hence ‘ $[\$st \mapsto_s \langle s_0 \rangle] \dagger [\$tr \mapsto_s 0, \$tr \mapsto_s \langle t \rangle - \langle tr_0 \rangle] \dagger pre_R Q'$
 by (simp add: R2-subst-tr closure assms)
 thus ?thesis
 by (rel-auto)
 qed

 from a2 have ndiv: $\neg [\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle] \dagger (\neg_r pre_R P)'$
 by (rel-auto)

 have t-minus-tr0: $tr_0 @ (t - tr_0) = t$
 using append-minus tr0 by blast

 from a3
 have wpr: $\bigwedge t_0 s_1.$
 $[\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_0 \rangle] \dagger pre_R P' \implies$
 $[\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_0 \rangle] \dagger post_R P' \implies$

$t_0 \leq t \implies [\$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t - t_0 \rangle] \dagger (\neg_r \text{pre}_R Q)' \implies \text{False}$
proof –
fix $t_0 \ s_1$
assume b :
 $[\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_0 \rangle] \dagger \text{pre}_R P'$
 $[\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_0 \rangle] \dagger \text{post}_R P'$
 $t_0 \leq t$
 $[\$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t - t_0 \rangle] \dagger (\neg_r \text{pre}_R Q)'$

from $a3$ **have** c : $\forall (s_0, t_0) \cdot \langle t_0 \rangle \leq_u \langle t \rangle$
 $\wedge [\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_0 \rangle] \dagger \text{post}_R P$
 $\implies [\$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle - \langle t_0 \rangle] \dagger \text{pre}_R Q'$
by (*simp add: wp-rea-circus-form-alt[of post_R P pre_R Q] closure assms unrest usubst*)
(rel-simp)

from $c \ b(2-4)$ **show** *False*
by (*rel-auto*)
qed

show $\exists t_1 \ t_2$.
 $t = t_1 @ t_2 \wedge$
 $(\exists s_0. [\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_1 \rangle] \dagger \text{pre}_R P \wedge$
 $[\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_1 \rangle] \dagger \text{post}_R P' \wedge$
 $[\$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_2 \rangle] \dagger \text{pre}_R Q \wedge$
 $[\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_2 \rangle] \dagger \text{post}_R Q' \wedge$
 $\neg [\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_1 @ t_2 \rangle] \dagger (\neg_r \text{pre}_R P)' \wedge$
 $(\forall t_0 \ s_1. [\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_0 \rangle] \dagger \text{pre}_R P \wedge$
 $[\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_0 \rangle] \dagger \text{post}_R P' \longrightarrow$
 $t_0 \leq t_1 @ t_2 \longrightarrow \neg [\$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle (t_1 @ t_2) - t_0 \rangle] \dagger (\neg_r$
 $\text{pre}_R Q)'))$
apply (*rule-tac x=tr₀ in exI*)
apply (*rule-tac x=(t - tr₀) in exI*)
apply (*auto*)
using $tr0$ **apply** *auto*[I]
apply (*rule-tac x=s₀ in exI*)
apply (*auto intro:wpr simp add: taut-conj preP preQ postP postQ ndiv wpr t-minus-tr0*)
done
qed

show $?rhs \subseteq ?lhs$
proof (*rdes-expand cls: assms, simp add: traces-def divergences-def rdes closure assms rdes-def unrest*
rpred usubst, auto)
fix $t_1 \ t_2 :: 'e \text{ list}$ **and** $s_0 \ s' :: 's$
assume
 $a1: \neg [\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_1 @ t_2 \rangle] \dagger (\neg_r \text{pre}_R P)'$ **and**
 $a2: [\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_1 \rangle] \dagger \text{pre}_R P'$ **and**
 $a3: [\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_1 \rangle] \dagger \text{post}_R P'$ **and**
 $a4: [\$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_2 \rangle] \dagger \text{pre}_R Q'$ **and**
 $a5: [\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_2 \rangle] \dagger \text{post}_R Q'$ **and**
 $a6: \forall t \ s_1. [\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle] \dagger \text{pre}_R P \wedge$
 $[\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle] \dagger \text{post}_R P' \longrightarrow$
 $t \leq t_1 @ t_2 \longrightarrow \neg [\$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle (t_1 @ t_2) - t \rangle] \dagger (\neg_r \text{pre}_R Q)'$

from $a1$ **have** $\text{pre}_R P$: $[\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_1 @ t_2 \rangle] \dagger (\text{pre}_R P)'$
by (*simp add: taut-not unrest-all-circus-vars-st assms closure unrest, rel-auto*)

have $[\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle t_1 \rangle, \$tr \mapsto_s \langle t_1 \rangle + \langle t_2 \rangle] \vdash post_R Q'$
 proof –
 have $[\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_2 \rangle] \vdash post_R Q =$
 $[\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle] \vdash [\$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_2 \rangle] \vdash post_R Q$
 by *rel-auto*
 also have ... = $[\$st \mapsto_s \langle s_0 \rangle, \$st \mapsto_s \langle s' \rangle] \vdash [\$tr \mapsto_s \langle t_1 \rangle, \$tr \mapsto_s \langle t_1 \rangle + \langle t_2 \rangle] \vdash post_R Q$
 by (*simp add: R2-subst-tr assms closure, rel-auto*)
 finally show *?thesis* using *a5*
 by (*rel-auto*)
 qed
 with *a3*
 have *postPQ*: $[\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_1 @ t_2 \rangle] \vdash (post_R P ;; post_R Q)'$
 by (*rel-auto, meson Prefix-Order.prefixI*)

 have $[\$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle t_1 \rangle, \$tr \mapsto_s \langle t_1 \rangle + \langle t_2 \rangle] \vdash pre_R Q'$
 proof –
 have $[\$st \mapsto_s \langle s_0 \rangle, \$tr \mapsto_s \langle t_1 \rangle, \$tr \mapsto_s \langle t_1 \rangle + \langle t_2 \rangle] \vdash pre_R Q =$
 $[\$st \mapsto_s \langle s_0 \rangle] \vdash [\$tr \mapsto_s \langle t_1 \rangle, \$tr \mapsto_s \langle t_1 \rangle + \langle t_2 \rangle] \vdash pre_R Q$
 by *rel-auto*
 also have ... = $[\$st \mapsto_s \langle s_0 \rangle] \vdash [\$tr \mapsto_s 0, \$tr \mapsto_s \langle t_2 \rangle] \vdash pre_R Q$
 by (*simp add: R2-subst-tr assms closure*)
 finally show *?thesis* using *a4*
 by (*rel-auto*)
 qed

 from *a6*
 have *a6'*: $\bigwedge t s_1. [t \leq t_1 @ t_2; [\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle] \vdash pre_R P'; [\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t \rangle] \vdash post_R P'] \implies$
 $[\$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle (t_1 @ t_2) - t \rangle] \vdash pre_R Q'$
 apply (*subst (asm) taut-not*)
 apply (*simp add: unrest-all-circus-vars-st assms closure unrest*)
 apply (*rel-auto*)
 done

 have *wpR*: $[\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_1 @ t_2 \rangle] \vdash (post_R P wp_r pre_R Q)'$
 proof –
 have $\bigwedge s_1 t_0. [t_0 \leq t_1 @ t_2; [\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_0 \rangle] \vdash post_R P']$
 $\implies [\$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle (t_1 @ t_2) - t_0 \rangle] \vdash pre_R Q'$
 proof –
 fix $s_1 t_0$
 assume $c: t_0 \leq t_1 @ t_2$ $[\$st \mapsto_s \langle s \rangle, \$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_0 \rangle] \vdash post_R P'$

 have *preP'*: $[\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_0 \rangle] \vdash pre_R P'$
 proof –
 have $(pre_R P)[[0, \langle t_0 \rangle] / \$tr, \$tr] \sqsubseteq (pre_R P)[[0, \langle t_1 @ t_2 \rangle] / \$tr, \$tr]$
 by (*simp add: RC-prefix-refine closure assms c*)
 hence $[\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_0 \rangle] \vdash pre_R P \sqsubseteq [\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr \mapsto_s \langle t_1 @ t_2 \rangle] \vdash pre_R P$
 by (*rel-auto*)
 thus *?thesis*
 by (*simp add: taut-refine-impl preP*)
 qed

 by (*rel-auto*)
 thus *?thesis*
 by (*simp add: taut-refine-impl preP*)
 qed

Q' **with** $c \text{ a3 } preP \text{ a6' [of } t_0 \text{ } s_1]$ **show** $[\$st \mapsto_s \langle s_1 \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr' \mapsto_s \langle (t_1 @ t_2) - t_0 \rangle] \uparrow pre_R$
 by (*simp*)
qed

thus *?thesis*
 apply (*simp-all add: wp-rea-circus-form-alt assms closure unrest usubst rea-impl-alt-def*)
 apply (*simp add: R1-def usubst tcontr-alt-def*)
 apply (*auto intro!: taut-shAll-intro-2*)
 apply (*rule taut-impl-intro*)
 apply (*simp add: unrest-all-circus-vars-st-st' unrest closure assms*)
 apply (*rel-simp*)
done
qed
show $[\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr' \mapsto_s \langle t_1 @ t_2 \rangle] \uparrow pre_R P \wedge$
 $[\$st \mapsto_s \langle s \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr' \mapsto_s \langle t_1 @ t_2 \rangle] \uparrow (post_R P \text{ wp}_r pre_R Q) \wedge$
 $[\$st \mapsto_s \langle s \rangle, \$st' \mapsto_s \langle s' \rangle, \$tr \mapsto_s \langle [] \rangle, \$tr' \mapsto_s \langle t_1 @ t_2 \rangle] \uparrow (post_R P ;; post_R Q)$
 by (*auto simp add: taut-conj preP postPQ wpR*)
qed
qed

lemma *Cons-minus [simp]: (a # t) - [a] = t*
 by (*metis append-Cons append-Nil append-minus*)

lemma *traces-prefix:*
 assumes P *is NCSP*
 shows $tr[\langle a \rangle \rightarrow_C P]s = \{(a \# t, s') \mid t \text{ s'}. (t, s') \in tr[P]s\}$
 apply (*auto simp add: PrefixCSP-def traces-seq traces-do divergences-do lit.rep-eq assms closure*
Healthy-if trace-divergence-disj)
 apply (*meson assms trace-divergence-disj*)
done

10.3 Deadlock Freedom

The following is a specification for deadlock free actions. In any intermediate observation, there must be at least one enabled event.

definition $CDF :: ('s, 'e) \text{ action where}$
 $[rdes-def]: CDF = \mathbf{R}_s(true_r \vdash (\bigwedge (s, t, E, e) \cdot \mathcal{E}(\langle s \rangle, \langle t \rangle, \langle insert\ e\ E \rangle)) \diamond true_r)$

lemma *CDF-NCSP [closure]: CDF is NCSP*
 apply (*simp add: CDF-def*)
 apply (*rule NCSP-rdes-intro*)
 apply (*simp-all add: closure unrest*)
done

lemma *CDF-seq-idem: CDF ;; CDF = CDF*
 by (*rdes-eq*)

lemma *CDF-refine-intro: CDF \sqsubseteq P \implies CDF \sqsubseteq (CDF ;; P)*
 by (*metis CDF-seq-idem urel-dioid.mult-isol*)

lemma *Skip-deadlock-free: CDF \sqsubseteq Skip*
 by (*rdes-refine*)

lemma *CDF-ext-st [alpha]: CDF $\oplus_p abs-st_L$ = CDF*

```
by (rdes-eq)
end
```

11 Meta-theory for Stateful-Failure Reactive Designs

```
theory utp-sf-rdes
imports
  utp-sfrd-core
  utp-sfrd-rel
  utp-sfrd-healths
  utp-sfrd-contracts
  utp-sfrd-extchoice
  utp-sfrd-prog
  utp-sfrd-recursion
  utp-sfrd-fdsem
begin end
```

References

- [1] S. Foster, F. Zeyda, and J. Woodcock. Unifying heterogeneous state-spaces with lenses. In *ICTAC*, LNCS 9965. Springer, 2016.
- [2] M. V. M. Oliveira. *Formal Derivation of State-Rich Reactive Programs using Circus*. PhD thesis, Department of Computer Science - University of York, UK, 2006. YCST-2006-02.