

Paper Title*

*Note: Sub-titles are not captured in Xplore and should not be used

Isaac Sacramento

Department of Informatic and Statistics
Federal University of Santa Catarina
Florianopolis, Brazil
isaac.sacramento@posgrad.ufsc.br

Mauro Roisenberg

dept. name of organization (of Aff.)
name of organization (of Aff.)
Florianopolis, Brazil
email address

Rodrigo Exterkoetter

Departament of Computer Science
Federal University of Santa Catarina
Florianopolis, Brazil
email address

Leando P. de Figueiredo

Departament of Physics
Federal University of Santa Catarina
Florianopolis, Brazil
email address

5th Given Name Surname

dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address

6th Given Name Surname

dept. name of organization (of Aff.)
name of organization (of Aff.)
City, Country
email address

Abstract—This document is a model and instructions for L^AT_EX. This and the IEEEtran.cls file define the components of your paper [title, text, heads, etc.]. *CRITICAL: Do Not Use Symbols, Special Characters, Footnotes, or Math in Paper Title or Abstract.

Index Terms—component, formatting, style, styling, insert

I. INTRODUCTION

Deblurring is the task of estimating a sharp latent image, given a blurry image as input. It is not observable in the literature an algorithm for deblurring all objects. Thus, methods that exploit domain-specific knowledge have emerged for deblurring categories of objects, e.g., text, faces and motion images [1]. In oil exploration field, the seismic data acquisition and its inversion to acoustic impedance attribute typically generates blurry images of the subsurface, in such a way that it is not clearly observe the interfaces between different rock layers, geological structures such as channels, etc. Obtaining high resolution acoustic impedance images, through seismic inversion methods, is a critical part in oil reservoir characterization. Despite the notorious efficiency of the inversion methods, post-inversion images deblurring has not received much attention.

Reservoir characterization aims to determine a multidimensional structure and properties of an oil field. To achieve this goal, it is essential to combine, through an inversion algorithm, the informations, knowledges and available data about the field, in such a way that it is possible to make the quantitative predictions about the reservoir behavior [2]. The seismic data is widely used in inversion processes because of its facility and precision in interpreting the acoustic impedance property. To succeed in seismic inversion, it is necessary to include strategies to deal with multiple sources of uncertainties. Specifically, the limited band-width of the seismic data leads to a misinterpretation of the resulting acoustic impedance

models. According to [3], improving the resolution of seismic inversion is possible by adding high frequency in acquisition and processing seismic data. However, the earth attenuation, high-frequency noise and other sources, cause the lack of high and low frequencies in seismic data. Thus, deblurring the acoustic impedance models, as a post-inversion refinement process, should lead to a more accurate interpretation of the impedance models.

We approach the acoustic impedance deblurring through a CNN model. CNN is a framework of deep learning which has been used in a wide sort of machine learning tasks. The availability of benchmarks [4] and the advances in Graphical Processing Unit (GPU) [5] allowed CNN to outperform state-of-the-art techniques in detection [45], [46], model-free tracking [6], classification [7]. With excellence in feature learning, CNN achieved notorious success in image and video classification [8], [9], action and speech recognition [10], [11]. Under the perspective of the reservoir characterization, CNN has been applied to lithofacies recognition [12] and calculation [13]. However, there is a lack of researches on improving the resolution of images resulting from inversion processes.

In this paper, we propose a new multilayer convolution network model to perform deblurring in post-inversion acoustic impedance. Each network layer maps higher level features originated in the previews layers through convolutional blur kernels. To perform this mapping, the kernels, also named weights, are adjusted by minimizing a loss function. The model enhances the resolution of acoustic impedance images, resulting in sharp images with increased high-frequency bandwidth and lower noise. In order to train the model, we blur a set of the synthetic acoustic impedance images to create a dictionary of images of high and low resolution. Then, the pairs of blur and latent images are normalized and presented to the network as input and target, respectively. The core concept of our architecture is the combination of the convolution layers with regression layers, thus the convolutional layers learn

the spatial structures existing in different acoustic impedance images, while the regression layer proceed the prediction of the property values.

II. THEORETICAL FOUNDATIONS AND RELATED WORKS

Inversion theory is used in several areas to infer parameters values related to physical processes based on experimental data. Inversion modeling refers to using the current measurements of observable physical parameters in order to infer the current model parameters (not observable). The inversion problem is described as (1)

$$m = F^{-1}(d) \quad (1)$$

where, F is the investigated physical system, and relates a set of model parameters $m = (m_1, m_2, \dots, m_n) \subset R^n$ estimated through the observed data $d \in R^s$. Geophysical methods frequently involve the solution and assessment of inversion problems. Studying these problems allow inferring physical properties distributions in the earth subsurface, using measured data. Among these data, the seismic data is mainly used in seismic inversion, which plays an important role in reservoir characterization. From a practical perspective, solving seismic inversion problems improves the exploration and management in oil industry, once the seismic data is highly correlated to petrophysical properties, e.g., density and porosity in subsurface.

The offshore seismic data is the main observable data used in seismic inversion. To perform seismic acquisition, one sends pulses through a controlled artificial source and captures the vertical component responses in function of time. The seismic data is a composition of the wave pulse used in the acquisition, named wavelet, and the characteristic of the interfaces between rock layers, on which the wavelet reflects. This rock layer characteristic is called reflectivity coefficient and it is calculated as (2)

$$r(t) = \frac{z(t + \delta t) - z(t)}{z(t + \delta t) + z(t)}, \quad (2)$$

where, $z(t)$ is the acoustic impedance, in function of time t , defined as $z(t) = \rho(t)v(t)$, where $\rho(t)$ is the rock density and $v(t)$ the propagation velocity of acoustic wave. Therefore, the seismic data $d(t)$ is modeled as a discrete convolution operation $*$ of the wavelet s with the reflectivity coefficient r as (3)

$$d(t) = s(\tau) * \sum_{j=1}^N r(t - t_j) \delta(t - t_j) + e_d(t) \quad (3)$$

where, N is the number of subsurface layers, $e_d(t)$ is a random noise in function of time. One ideal wavelet is a delta pulse with all the frequency band-width, however, in practice wavelets have their band-width generally limited from $6Hz$ to $65Hz$. By consequence, the images resulting from the seismic inversion will keep their frequency spectrum limited.

According to [14], a good acoustic impedance model contains more information than the seismic data, because the

inversion process contains additional information originated from well-logs, for exemple, a low-frequency model. The well-logs are real data measured in wells spread along the field. With the local acoustic impedance it is possible to calculate the low-frequency model by interpolation between wells [15], [16]. Despite of the low-frequency model, the final model for acoustic impedance still lacks of high resolution details.

Deblurring is generally modeled as the convolution of a blur kernel k with a latent image I :

$$y = k \otimes I + n \quad (4)$$

where n is the noise. Since k , I and n are unknown, the problem is highly ill-posed and admits infinity solutions for k and I . Several works have developed different deblurring methods for specific purposes. Blind deconvolution methods are widely investigated in image processing [17]. For the last six years, considerable effort has been employed in single image [18]–[21] and multi-image [22], [23] blind deconvolutions. Applying blind deconvolution generally implies in making assumptions on blur kernels and/or on latent images. For example, assuming sparsity of blur kernel or that natural images have super-Gaussian statistics. The second assumption leads to the use of image priors on inference process and, consequently, to the maximum *a posteriori* (MAP) estimation [18]. However, [24] show that deblurring methods based on this prior tend to favor blurry images over original latent images.

The Bayesian inference approach [24] outperforms the MAP based methods. It marginalizes the image from the optimization step, while estimating the unknown blur. The authors show that it is possible to define a class of prior image based on natural image statistics, suitable enough to represent sharp images features. This prior formulation makes possible to use Bayesian inference in the estimation of the unknown image and the blur kernel. According to [25], defining a gradient prior, by itself, is not sufficient to reach a sharp image, instead, they search in a dataset for a prior that densely correspond to the blurry image similar to a sharp image. This search is an iteratively optimization over the correspondence between the images, the kernel and the sharp image estimation. Although [26] suggest a generalization for the method proposed by [25], it still requires a similar reference image, which is not always available.

The optimization methods previously described use a set of priors based on generic image statistics or domain-specific priors. It has been demonstrated that these methods work properly on synthetic blurs. However, newly studies show that they failure when applied to real world blurry images [27] and take a severe computational cost [28]. In contrast, the learning-based methods have gained attention with the resumption and recent advances in neural networks. The adequate hyper-parameter adjustment allows neural network to learn non-linear function or blur kernels. Thus, deblurring becomes a function of a blurry image I and a set of parameters p as (5)

$$y = \sigma(I, p) \quad (5)$$

Learning-based methods focus on developing a model to learn the function σ [29] and to perform non-blind deblurring [28]. [30] learn a convolution neural networks (CNN) to recognize motion kernels and performs non-blind deconvolution in dense motion field estimate, in addition, [29] minimize regularized l_2 in order to perform text deblurring.

III. DATA AND METHODS

A. Acoustic Impedance Inversion

The experiments described in this paper perform on a set of synthetic acoustic impedance images. Using synthetic models to test and parametrize algorithms is a common practice in reservoir characterization [31]. It allows studying the results of the algorithms without external interferences and performing efficient interpretations and assessments. According to [32], wedge shaped models is a straight way to analysis the seismic model and inversion processes. It reproduces reservoir contexts such as stratigraphic refinements, edges and channel structures in a realistic manner.

The training set generation occurs in two steps. The first step creates a set of wedge shapes represented by images with size 32×32 . The wedge shapes represent the reservoir and they randomly vary in width and length. The second step fills the lithology with values of petrophysical properties. In order to simplify the assessments and conclusions, we fill the lithology structures with constant reference values of rock densities and compressional velocity observed in the literature [33]. The acoustic impedance is calculated using the density and velocity models and the images in high resolution model are obtained, as illustrated in Fig. ??.

In a real scenario, the blurry acoustic impedance is the result of an acoustic inversion method, such as Maximum *a posteriori* [15], [16], Sparse Spike [34] and Recursive Inversion [35], using seismic data with limited band-width. However, for experimental purpose, the acoustic impedance models were filtered and the high frequencies were removed to obtain the blurry images, as illustrated in Fig. ?. This way, the supervised learning is performed with the high resolution images and blurred images. To increase the number of examples in the training dataset we rotate the impedance models to establish the wedge structure in four different angles (0° , 90° , 180° and 270°). This approach allows the model learning an wide edge variabilities in wedges images.

IV. EASE OF USE

A. Maintaining the Integrity of the Specifications

The IEEEtran class file is used to format your paper and style the text. All margins, column widths, line spaces, and text fonts are prescribed; please do not alter them. You may note peculiarities. For example, the head margin measures proportionately more than is customary. This measurement and others are deliberate, using specifications that anticipate your paper as one part of the entire proceedings, and not as an independent document. Please do not revise any of the current designations.

V. PREPARE YOUR PAPER BEFORE STYLING

Before you begin to format your paper, first write and save the content as a separate text file. Complete all content and organizational editing before formatting. Please note sections V-A–V-E below for more information on proofreading, spelling and grammar.

Keep your text and graphic files separate until after the text has been formatted and styled. Do not number text heads— \LaTeX will do that for you.

A. Abbreviations and Acronyms

Define abbreviations and acronyms the first time they are used in the text, even after they have been defined in the abstract. Abbreviations such as IEEE, SI, MKS, CGS, ac, dc, and rms do not have to be defined. Do not use abbreviations in the title or heads unless they are unavoidable.

B. Units

- Use either SI (MKS) or CGS as primary units. (SI units are encouraged.) English units may be used as secondary units (in parentheses). An exception would be the use of English units as identifiers in trade, such as “3.5-inch disk drive”.
- Avoid combining SI and CGS units, such as current in amperes and magnetic field in oersteds. This often leads to confusion because equations do not balance dimensionally. If you must use mixed units, clearly state the units for each quantity that you use in an equation.
- Do not mix complete spellings and abbreviations of units: “Wb/m²” or “webers per square meter”, not “webers/m²”. Spell out units when they appear in text: “. . . a few henries”, not “. . . a few H”.
- Use a zero before decimal points: “0.25”, not “.25”. Use “cm³”, not “cc”).

C. Equations

Number equations consecutively. To make your equations more compact, you may use the solidus (/), the exp function, or appropriate exponents. Italicize Roman symbols for quantities and variables, but not Greek symbols. Use a long dash rather than a hyphen for a minus sign. Punctuate equations with commas or periods when they are part of a sentence, as in:

$$a + b = \gamma \quad (6)$$

Be sure that the symbols in your equation have been defined before or immediately following the equation. Use “(6)”, not “Eq. (6)” or “equation (6)”, except at the beginning of a sentence: “Equation (6) is . . .”

D. \LaTeX -Specific Advice

Please use “soft” (e.g., $\text{\textbackslash eqref}\{Eq\}$) cross references instead of “hard” references (e.g., (1)). That will make it possible to combine sections, add equations, or change the order of figures or citations without having to go through the file line by line.

Please don't use the `{eqnarray}` equation environment. Use `{align}` or `{IEEEeqnarray}` instead. The `{eqnarray}` environment leaves unsightly spaces around relation symbols.

Please note that the `{subequations}` environment in \LaTeX will increment the main equation counter even when there are no equation numbers displayed. If you forget that, you might write an article in which the equation numbers skip from (17) to (20), causing the copy editors to wonder if you've discovered a new method of counting.

\LaTeX does not work by magic. It doesn't get the bibliographic data from thin air but from `.bib` files. If you use \LaTeX to produce a bibliography you must send the `.bib` files.

\LaTeX can't read your mind. If you assign the same label to a subsubsection and a table, you might find that Table I has been cross referenced as Table IV-B3.

\LaTeX does not have precognitive abilities. If you put a `\label` command before the command that updates the counter it's supposed to be using, the label will pick up the last counter to be cross referenced instead. In particular, a `\label` command should not go before the caption of a figure or a table.

Do not use `\nonumber` inside the `{array}` environment. It will not stop equation numbers inside `{array}` (there won't be any anyway) and it might stop a wanted equation number in the surrounding equation.

E. Some Common Mistakes

- The word "data" is plural, not singular.
- The subscript for the permeability of vacuum μ_0 , and other common scientific constants, is zero with subscript formatting, not a lowercase letter "o".
- In American English, commas, semicolons, periods, question and exclamation marks are located within quotation marks only when a complete thought or name is cited, such as a title or full quotation. When quotation marks are used, instead of a bold or italic typeface, to highlight a word or phrase, punctuation should appear outside of the quotation marks. A parenthetical phrase or statement at the end of a sentence is punctuated outside of the closing parenthesis (like this). (A parenthetical sentence is punctuated within the parentheses.)
- A graph within a graph is an "inset", not an "insert". The word alternatively is preferred to the word "alternately" (unless you really mean something that alternates).
- Do not use the word "essentially" to mean "approximately" or "effectively".
- In your paper title, if the words "that uses" can accurately replace the word "using", capitalize the "u"; if not, keep using lower-cased.
- Be aware of the different meanings of the homophones "affect" and "effect", "complement" and "compliment", "discreet" and "discrete", "principal" and "principle".
- Do not confuse "imply" and "infer".
- The prefix "non" is not a word; it should be joined to the word it modifies, usually without a hyphen.

- There is no period after the "et" in the Latin abbreviation "et al."
- The abbreviation "i.e." means "that is", and the abbreviation "e.g." means "for example".

An excellent style manual for science writers is [42].

F. Authors and Affiliations

The class file is designed for, but not limited to, six authors. A minimum of one author is required for all conference articles. Author names should be listed starting from left to right and then moving down to the next line. This is the author sequence that will be used in future citations and by indexing services. Names should not be listed in columns nor group by affiliation. Please keep your affiliations as succinct as possible (for example, do not differentiate among departments of the same organization).

G. Identify the Headings

Headings, or heads, are organizational devices that guide the reader through your paper. There are two types: component heads and text heads.

Component heads identify the different components of your paper and are not topically subordinate to each other. Examples include Acknowledgments and References and, for these, the correct style to use is "Heading 5". Use "figure caption" for your Figure captions, and "table head" for your table title. Run-in heads, such as "Abstract", will require you to apply a style (in this case, italic) in addition to the style provided by the drop down menu to differentiate the head from the text.

Text heads organize the topics on a relational, hierarchical basis. For example, the paper title is the primary text head because all subsequent material relates and elaborates on this one topic. If there are two or more sub-topics, the next level head (uppercase Roman numerals) should be used and, conversely, if there are not at least two sub-topics, then no subheads should be introduced.

H. Figures and Tables

a) *Positioning Figures and Tables:* Place figures and tables at the top and bottom of columns. Avoid placing them in the middle of columns. Large figures and tables may span across both columns. Figure captions should be below the figures; table heads should appear above the tables. Insert figures and tables after they are cited in the text. Use the abbreviation "Fig. ??", even at the beginning of a sentence.

TABLE I
TABLE TYPE STYLES

Table Head	Table Column Head		
	<i>Table column subhead</i>	<i>Subhead</i>	<i>Subhead</i>
copy	More table copy ^a		

^aSample of a Table footnote.

Figure Labels: Use 8 point Times New Roman for Figure labels. Use words rather than symbols or abbreviations when

writing Figure axis labels to avoid confusing the reader. As an example, write the quantity “Magnetization”, or “Magnetization, M”, not just “M”. If including units in the label, present them within parentheses. Do not label axes only with units. In the example, write “Magnetization (A/m)” or “Magnetization {A[m(1)]}”, not just “A/m”. Do not label axes with a ratio of quantities and units. For example, write “Temperature (K)”, not “Temperature/K”.

ACKNOWLEDGMENT

The preferred spelling of the word “acknowledgment” in America is without an “e” after the “g”. Avoid the stilted expression “one of us (R. B. G.) thanks ...”. Instead, try “R. B. G. thanks...”. Put sponsor acknowledgments in the unnumbered footnote on the first page.

REFERENCES

Please number citations consecutively within brackets [36]. The sentence punctuation follows the bracket [37]. Refer simply to the reference number, as in [38]—do not use “Ref. [38]” or “reference [38]” except at the beginning of a sentence: “Reference [38] was the first ...”

Number footnotes separately in superscripts. Place the actual footnote at the bottom of the column in which it was cited. Do not put footnotes in the abstract or reference list. Use letters for table footnotes.

Unless there are six authors or more give all authors’ names; do not use “et al.”. Papers that have not been published, even if they have been submitted for publication, should be cited as “unpublished” [39]. Papers that have been accepted for publication should be cited as “in press” [40]. Capitalize only the first word in a paper title, except for proper nouns and element symbols.

For papers published in translation journals, please give the English citation first, followed by the original foreign-language citation [41].

REFERENCES

- [1] G. G. Chrysos, and S. Zafeiriou, “Deep Face Deblurring.” pp. 2015-2024, 10.1109/CVPRW.2017.252, 2017.
- [2] J.M. Buiting, M. Bacon, “Using geophysical, geological, and petrophysical data to characterize reservoirs in the North Sea.” in 5th Conference on Petroleum Geology of NW Europe, London. CD-ROM.
- [3] X. Xiaoyu, L. Yun, S. Desheng, G. Xiangyu, and W. Huifeng, “Studying the effect of expanding low or high frequency on post-stack seismic inversion,” in SEG Technical Program Expanded Abstracts 2012, pp. 1-5, September 2012.
- [4] O. Russakovsky, J. Deng, H. Su, J. Krause, S. Satheesh, S. Ma, Z. Huang, A. Karpathy, A. Khosla, M. Bernstein, “Imagenet large scale visual recognition challenge,” in International Journal of Computer Vision (IJCV), pp. 211252, 2015.
- [5] N. Buduma, “ Fundamentals of Deep Learning,” Academic Press, in O’Reilly Media, 2015.
- [6] H. Nam and B. Han, “Learning multi-domain convolutional neural networks for visual tracking,” In IEEE Proceedings of International Conference on Computer Vision and Pattern Recognition (CVPR) IEEE, 2016.
- [7] K. He, X. Zhang, S. Ren, and J. Sun, “Deep residual learning for image recognition,” In IEEE Proceedings of International Conference on Computer Vision and Pattern Recognition (CVPR). IEEE, 2016.
- [8] A. Krizhevsky, I. Sutskever, G. E. Hinton, “Imagenet classification with deep convolutional neural networks: Advances in neural information processing systems,” 2012, pp. 10971105.

- [9] O. Abdel-Hamid, A.-r. Mohamed, H. Jiang, L. Deng, G. Penn, and D. Yu, “Convolutional neural networks for speech recognition,” in IEEE/ACM Transactions on audio, speech, and language processing, num. 22, pp. 15331545, 2014.
- [10] S. S. Farfade, M. J. Saberian, and L.-J. Li, 2015, “Multi-view face detection using deep convolutional neural networks,” in Proceedings of the 5th ACM on International Conference on Multimedia Retrieval, ACM, pp. 643650.
- [11] S. Ji, W. Xu, M. Yang, K. Yu, 2013, “3d convolutional neural networks for human action recognition,” in IEEE transactions on pattern analysis and machine intelligence, num. 35, p. 221231.
- [12] Q. Feng, Y. Miao, S. Ming-Jun, W. Yaojun, H. Guangmin, “Seismic facies recognition based on prestack data using deep convolutional autoencoder,”.
- [13] L. Lihui, L. Rong, L. Jianhai, Y. Wenkui, “Seismic Lithofacies Computation Method Based on Deep Learning,” in International Geophysical Conference, pp. 649-652, April 2017.
- [14] R. B. Latimer, R. Davidson, P. van Riel, “An interpreter’s guide to understanding and working with seismic-derived acoustic impedance data,” in The Leading Edge, pp. 242-256, vol. 19, num. 3, 2017.
- [15] A. Buland, and H. Omre, “Bayesian linearized avo inversion,” In Geophysics, 2003, pp. 185198.
- [16] L. P. Figueiredo, M. Santos, M. Roisenberg, G. Neto, and W. Figueiredo, “Bayesian framework to wavelet estimation and linearized acoustic inversion,” in Geoscience and Remote Sensing Letters, pp. 15, 2012.
- [17] T.E. Bishop, S.D. Babacan, Amizic, T. Chan, R. Molina, and A. Katsaggelos, “Blind image deconvolution: problem formulation and existing approaches.” in. Blindimage deconvolution: theory and applications, CRC press, 2007.
- [18] S. D. Babacan, R. Molina, M. N. Do, and A. K. Katsaggelos, “Bayesian blind deconvolution with general sparse image priors.” in Proceedings of European Conference on Computer Vision (ECCV), pp. 341355, 2012.
- [19] D. Krishnan, T. Tay, and R. Fergus, “Blind deconvolution using anormalized sparsity measure.” In CVPR, 2011.
- [20] A. Levin, Y. Weiss, F. Durand, and W. T. Freeman. “Efficient marginal likelihood optimization in blind deconvolution.” In CVPR, 2011.
- [21] H. Zhang, J. Yang, Y. Zhang, N. M. Nasrabadi, and T. S. Huang, “Close the loop: Joint blind image restoration and recognition with sparse representation prior.” in ICCV, 2011.
- [22] F. Sroubek and P. Milanfar, “Robust multichannel blind deconvolution via fast alternating minimization.” in IEEE Trans. on Image Processing, pp. 16871700, 2012.
- [23] X. Zhu, F. Sroubek, P. Milanfar, “Deconvolving PSFs for a better motion deblurring using multiple images.” in ECCV, 2012.
- [24] A. Levin, Y. Weiss, F. Durand, and W. T. Freeman. “Understanding and evaluating blind deconvolution algorithms.” In IEEE Proceedings of International Conference on Computer Vision and Pattern Recognition (CVPR), pp. 19641971.
- [25] Y. Hachohen, E. Shechtman, and D. Lischinski, “Deblurring by example using dense correspondence.” In IEEE Proceedings of International Conference on Computer Vision (ICCV), pp. 23842391, 2013.
- [26] J. Pan, Z. Hu, Z. Su, and M. H. Yang, “Deblurring face images with exemplars.” In Proceedings of European Conference on Computer Vision (ECCV), pp. 4762. Springer, 2014.
- [27] W.S. Lai, J. B. Huang, Z. Hu, N. Ahuja, and M. H. Yang, “A comparative study for single image blind deblurring.” In IEEE Proceedings of International Conference on Computer Vision and Pattern Recognition (CVPR). IEEE, 2016.
- [28] A. Chakrabarti, “A neural approach to blind motion deblurring.” In Proceedings of European Conference on Computer Vision (ECCV), pp. 221235. Springer, 2016.
- [29] M. Hradis, J. Kotera, P. Zemck, and F. Sroubek, “Convolutional neural networks for direct text deblurring.” In Proceedings of British Machine Vision Conference (BMVC), 2015.
- [30] J. Sun, W. Cao, Z. Xu, and J. Ponce, “Learning a convolutional neural network for non-uniform motion blur removal.” In IEEE Proceedings of International Conference on Computer Vision and Pattern Recognition (CVPR), pp. 769777, 2015.
- [31] S. S. Sancevero, A. Z. Remacre, R. S. Portugal, “O papel da inverso para a impedncia no processo de caracterizao ssmica de reservatrios.” in Revista Brasileira de Geofisica, p. 495-512, v. 24, 2006.
- [32] P. J. Harvey, and D. J. MacDONALD, “Seismic modelling of porosity within the jurassic aged carbonate bank, offshore Nova Scotia,” in Canadian Journal of Exploration Geophysics, num. 26, pp. 5471.

- [33] G. Mavko, T. Mukerji, and J. Dvorkin, "The Rock Physics Handbook: Tools for Seismic Analysis of Porous Media." Cambridge: Cambridge University Press, pp. 359-369, 2009.
- [34] H. DEBEYE, and P. RIEL van, "Lp-norm deconvolution." 1990, Geophysical Prospecting, pp. 381-403
- [35] S. Chopra, "Integrating coherence cube imaging and seismic inversion." The Leading Edge, pp. 354-362, 2001.
- [36] G. Eason, B. Noble, and I. N. Sneddon, "On certain integrals of Lipschitz-Hankel type involving products of Bessel functions," Phil. Trans. Roy. Soc. London, vol. A247, pp. 529-551, April 1955.
- [37] J. Clerk Maxwell, A Treatise on Electricity and Magnetism, 3rd ed., vol. 2. Oxford: Clarendon, 1892, pp.68-73.
- [38] I. S. Jacobs and C. P. Bean, "Fine particles, thin films and exchange anisotropy," in Magnetism, vol. III, G. T. Rado and H. Suhl, Eds. New York: Academic, 1963, pp. 271-350.
- [39] K. Elissa, "Title of paper if known," unpublished.
- [40] R. Nicole, "Title of paper with only first word capitalized," J. Name Stand. Abbrev., in press.
- [41] Y. Yorozu, M. Hirano, K. Oka, and Y. Tagawa, "Electron spectroscopy studies on magneto-optical media and plastic substrate interface," IEEE Transl. J. Magn. Japan, vol. 2, pp. 740-741, August 1987 [Digests 9th Annual Conf. Magnetism Japan, p. 301, 1982].
- [42] M. Young, The Technical Writer's Handbook. Mill Valley, CA: University Science, 1989.
- [43] G. G. Chrysos, S. Zafeiriou, "Deep Face Deblurring," 2017 IEEE Conference on Computer Vision and Pattern Recognition Workshops (CVPRW), Honolulu, HI, 2017, pp. 2015-2024.
- [44] P. van Riel, "The past, present and future of quantitative reservoir characterization." in The Leading Edge, 19, pp. 878-881.
- [45] R. Girshick, "Fast r-cnn," In IEEE Proceedings of International Conference on Computer Vision (ICCV), pp. 1440-1448, 2015.
- [46] S. Bell, C. L. Zitnick, K. Bala, and R. Girshick, "Inside-outside net: Detecting objects in context with skip pooling and recurrent neural networks," in arXiv preprint arXiv:1512.04143, 2015.
- [47] S. Narayana, and P. K. Thiruvikraman, "Image similarity using fourier transform," in International Journal of Computer Engineering and Technology, 2015, num. 6, pp. 2937.
- [48] N. Qian, "On the momentum term in gradient descent learning algorithms," in Neural Networks, vol. 12, pp. 145-151, 1999.
- [49] V. Nair, and G. E. Hinton. "Rectified linear units improve restricted boltzmann machines." In Proc. 27th International Conference on Machine Learning, 2010.
- [50] R. Dahl, M. Norouzi, and J. Shlens, "Pixel recursive super resolution" CoRR, 2017,