

Intro to R

Part 3: Visualization

Prof. Bisbee

Vanderbilt University

Lecture Date: 2023/01/23

Slides Updated: 2023-01-03

Agenda

1. Recap of last lecture

- Using packages: `install.packages()` & `require()`
- Loading and manipulating data: `readRDS()` and `%>%`

2. Plotting in R

- `ggplot` (+ instead of `%>%`)

Loading Packages & Data

- Create an `.Rmd` file and save to your `code` folder
 - Accept defaults, Save As... (with a good name), then `knit`
- Load the `tidyverse` package


```
require(tidyverse)
```

- Download `sc_debt.Rds` from [GitHub](#) and save to your `./data` folder
- Now load the data with `readRDS("[PATH TO DATA]/sc_debt.Rds")`
 - We **create** an "object" to store the data using a left-arrow: `<-`

```
df <- readRDS("../data/sc_debt.Rds")
```

- NB: `../` means "go up one folder"

The Two Camps



The Research Camp

- RQ: How might admissions and SAT scores be **related**?
 - Theory: selective schools have stricter criteria
 - Hypothesis: admissions and SAT scores should be **negatively** related
- How can we test this hypothesis?

Previously: `summarise()`

- We can combine base R functions with `tidyverse` functions!
 - Base R: `mean()`
 - `tidyverse`: `summarise()` (aka `summarize()`)
- Overall average SAT scores

```
df %>%  
  summarise(mean_sat = mean(sat_avg, na.rm=T))
```

```
## # A tibble: 1 × 1  
##   mean_sat  
##   <dbl>  
## 1    1141.
```

Previously: `summarise()`

- Let's unpack this

```
df %>%  
  summarise(mean_sat = mean(sat_avg, na.rm=T))
```

- Create new variable `mean_sat` that contains the `mean()` of every school's average SAT score
- `na.rm=T` means we want to ignore missing data. If not?

```
df %>%  
  summarise(mean_sat = mean(sat_avg))
```

```
## # A tibble: 1 × 1  
##   mean_sat  
##   <dbl>  
## 1      NA
```

Previously: `summarise()` + `filter()`

- Recall we want see if more selective schools have higher SAT scores

```
df %>%  
  filter(adm_rate < .1) %>%  
  summarise(mean_sat_LT10 = mean(sat_avg, na.rm=T))
```

```
## # A tibble: 1 × 1  
##   mean_sat_LT10  
##           <dbl>  
## 1          1510.
```

```
df %>%  
  filter(adm_rate > .1 & adm_rate < .2) %>%  
  summarise(mean_sat_1020 = mean(sat_avg, na.rm=T))
```

```
## # A tibble: 1 × 1  
##   mean_sat_1020  
##           <dbl>  
## 1          1424
```



Plotting data

- Let's plot the data instead of writing many of these `summarise()` functions
- Visualization in R uses `ggplot()` function
 - Inputs: `aes(x,y,...)` (elipses `...` indicates many more inputs)
 - `x` is the x-axis (horizontal)
 - `y` is the y-axis (vertical)

ggplot()

- Attach `ggplot()` to your data with `%>%`

```
df %>%  
  ggplot()
```




ggplot()

- Then tell it what to put in the x-axis and y-axis
- What should go on these axes?
- **Theory**: Selective schools choose higher scoring students
 - Selective schools **explain** higher scores
 - Selective schools: **independent variable** / **explanatory variable** / **predictor** / X
 - Higher scores: **dependent variable** / **outcome variable** / Y
- Selective schools go on the x-axis, SAT scores go on the y-axis

ggplot()

```
df %>%  
  ggplot(aes(x = adm_rate, y = sat_avg))
```



ggplot()


- This gives us an empty plot
- We have the correct variables on the correct axes...
- ...but we need to choose how to display them
- There are many different `ggplot()` functions to choose from
 - `geom_point()` creates one point for each x and y coordinate
 - `geom_bar()` creates a barplot
 - `geom_histogram()` creates a histogram
 - `geom_density()` creates a density plot
 - `geom_boxplot()` creates a box-and-whisker plot

ggplot()

- We **add** a second `ggplot()` function to the first with a plus sign +
 - **NB:** This is JUST LIKE THE PIPE OPERATOR `%>%` in `tidyverse`!
- Since `adm_rate` (the x-axis variable) and `sat_avg` (the y-axis variable) are both numeric ("continuous") measures, we will use `geom_point()`
 - We will come back to **variable types** and how to visualize them later

ggplot()

```
df %>%  
  ggplot(aes(x = adm_rate, y = sat_avg)) +  
  geom_point()
```




Plotting data

- Let's unpack this
 - `aes(x,y)` sets the basic aesthetics for the plot
 - `geom_point()` tells `ggplot()` how to visualize those aesthetics
 - These two parts are linked with the `+`. Similar to...?
 - ...the `%>%` in `tidyverse`!
 - We can force aesthetics by setting code outside the `aes()`

```
df %>%  
  ggplot(aes(x = adm_rate_pct, y = sat_avg)) +  
  geom_point(color = 'red')
```


Plotting data




Plotting data

- Or we can make more aesthetics dependent on the data

```
df %>%  
  ggplot(aes(x = adm_rate, y = sat_avg,  
             color = stabbr)) +  
  geom_point()
```


Plotting data



Interpreting the plot

- We **hypothesized** that admissions and SAT scores are negatively related
 - Is this supported in the data?
- Let's add a line of best fit with `geom_smooth()`

```
df %>%  
  ggplot(aes(x = adm_rate, y = sat_avg)) +  
  geom_point() +  
  geom_smooth(method = 'lm', se = F)
```



Plotting data

- Which school is most selective but also with the lowest SAT?
 - This is an **outlier**
 - This school is the **furthest** from our [theory](#)

```
df %>%  
  mutate(out = ifelse(adm_rate < .25 & sat_avg < 1000,  
                      instnm, # Value if TRUE  
                      NA)) %>% # Value if FALSE  
  filter(!is.na(out)) %>%  
  select(instnm, adm_rate, sat_avg)
```


```
## # A tibble: 1 × 3  
##   instnm      adm_rate sat_avg  
##   <chr>      <dbl>   <int>  
## 1 Dallas Christian College 0.130     917
```

Plotting data

- We can add this as a label!

```
df %>%  
  mutate(out = ifelse(adm_rate < .25 & sat_avg < 1000,  
                      instnm,  
                      NA)) %>%  
  ggplot(aes(x = adm_rate, y = sat_avg,  
            label = out)) +  
  geom_point() +  
  geom_text()
```

Plotting data




Plotting data

- Let's accentuate the outlier more with color

```
df %>%  
  mutate(out = ifelse(adm_rate < .25 & sat_avg < 1000,  
                      instnm,  
                      NA)) %>%  
  ggplot(aes(x = adm_rate, y = sat_avg,  
             color = out, label = out)) +  
  geom_point() +  
  scale_color_manual(name = "Outlier", values = c('red', 'black')) +  
  geom_text(hjust = 0, vjust = 1, color = 'black', size = 3)
```

Plotting data



Conclusion

- What to take away
 1. Which variables go on which axes
 2. How to put these on a `ggplot()` figure
 3. How to create a visualization of these variables
- This wraps up the crash course in R
 - **REMEMBER:** This class is *inherently* challenging because of R
 - The course is graded leniently to reflect the inherent difficulty of the material

Quiz & Homework

- Go to Brightspace and take the fourth quiz
 - The password to take the quiz is 3326
- **Homework:**
 1. Work through Lecture_2023_01_23_hw.Rmd
 2. Complete Problem Set 1