Index

Note: Page numbers followed by "f" indicate figures; "t" tables.

A

Abuse loads, 206–207, 245
  kerb impact, 248t
  pothole impact, 248t, 252f–254f, 253
  3g bump, 248t, 252
  2g rebound, 248t
Acceleration
  analysis, 53–58, 54f–56f, 298–310
  centripetal, 6–7, 6f
  lateral, 6–8, 6f, 11
  yaw, 9, 11–12
Accident avoidance, 199, 590–591
Ackermann, Rudolph, 543–544
  Ackermann angle, 543–544, 544f, 557
  Ackermann fraction, 544–545
ACSL (Automatic Continuous Simulation Language), 22
Action–reaction torque, 136–137, 137f
Active safety KPIs, 270–274
Active systems, 603–630
  active camber systems, 621
  active steering systems, 620–621
  active suspension, 605–611
  active torque distribution, 621–628
  brake-based systems, 611–620
  variable damping, 605–611
ADAC avoidance test, 2f
ADAMS/Car, 19, 182, 183f, 209f, 216, 404–405, 437–439, 483–484
ADAMS/Chassis, 20, 182, 184f
ADAMS/Linear, 263, 281t
ADAMS/Pre, 20, 182
ADAMS/Solver, 214t
ADAMS/Tire, 391–393
ADAMS/Vehicle, 181–182
ADAMS/View, 453
Adaptive controllers, 506–507
Aerodynamic effects, 475–478
Aeroelastic flutter, 476
Aerofoil case, 155
Agility, 555–556, 582
Akima spline method, 140
Aligning moment, generation of, 365
Aligning torque, 217, 234, 236, 236f–237f
  steer and camber compliance, 236
Allen, R.W., 23
Altair Hyperstudy, 15–16, 400–401
AMC Javelin, 22–23
Amesim, 21
AMIGO, 20
Analysis capabilities, 160–172
  integration methods, 168–172
  linear equations, solving, 161–165
  nonlinear equations, 165–168
  overview of, 160–161
Analytical process, 13–17, 15f
  analysis, 15–16
  aspiration, 14
  composition, 16
  confirmation, 17
  decomposition, 16
  definition, 14–15
  review, 17
  simulation, 16–17
  synthesis, 16
Anderson, R.J., 24–25
Ando, K., 394
Angel, J.C., 20
Angular constraint element, 126, 126f
Angular momentum, 66–69
ANSI C, 89, 92
ANSYS, 24
Anti-dive fraction, 200–201
Anti-lock braking system (ABS), 171, 361, 398, 451, 478, 611–616, 612f, 618–619
Anti-pitch
  angle, 203
  behaviour, 202–203
Anti-roll, 203, 608f
  angle, 203, 205, 206f
  bars, 468–471, 468f–470f
    roll stiffness due to, 474–475, 474f
  elements, 206
  fraction, 203
  geometry, 459–460
Anti-squat, 200
Apollo Guidance Computer (AGC), 1, 21
Aquaplaning. *See also* Tyres, 362, 363f
ARAS 360, 23
ArcSim, 460–462
Aston Martin Vanquish, 186f
Astro Spiral Jump, 22–23, 23f
Atpoint constraint element, 123, 124f
Audi, 20, 182, 611

Austin, A., 22
AUTOSIM, 22

B

Backwards differentiation formula method, 168
Bakker, E., 405, 409
Bartlett, W., 589–590
Bath model, 25
Bayle, P., 404
Beams
  definition of, 157–158
  element, massless, 156f
  modelling of, 156–157
Bell crank, 215, 217f
Benchmarking exercises, 14–15, 24–26
Besselink, I.J.M., 407
Bicycle model (2DOF), 198
BikeSim, 22
Bishop Technologies, 555–556
Blinchikoff, 608–610
Blundell, M.V., 21
BMW, 182, 566–567
  Active Front Steer system, 555–556, 621
  Active Roll Stabilisation system, 607
  Dynamic Cornering Performance systems, 624
  M5, 567, 582
  X5, 607
  X6, 607
  X7, 607
BNPS model, 404
Body isolation, 191–197, 259–283
Body slip angle, 456–457, 456f, 551
  rate of change (beta-dot), 580–583, 586–587
Body slip angle control, 511–514
Boeing 747, 155
Bosch
  Anti-Blockier System, 611
  Electronic Stability Program (ESP), 619–622
Box, George, 256
Boyle's law, 436
Brake slip control model, 615f
Brake-based systems, 611–620
Braking, 478–482
  proportioning of, 478
  weight transfer due to, 478f
Braking force, 359–363, 360f
  road contamination, effect of, 362–363, 363f
  versus slip ratio, 361–362, 362f, 393f
Bugatti Type 35, 204–205
Buick, 503
Bump, 47–48, 139–140, 142
Bump movement (BM), 223, 224f
  camber angle with, 242f
  castor angle with, 242f
  half-track change with, 244f
  roll centre height with, 243f
  steer angle with, 243f
  vertical force with, 244f
Bump stops, 142–143, 143f
Bushes, 131–133
  modelling of, 144, 145f, 146
  modelling suspension system using, 211–212, 211f, 212t, 237–240, 239f
Butterworth filter, 610, 610f

C

C++, 182–183
CAE methods, 320
CAE tools, 241–245
Camber angle, 8–9, 204–205, 223, 225f, 334f
  combined with slip angle, 372–373, 373f
  effect on tyre force and moments, 368–372, 370f–372f
  plotted with bump movement, 242f
  at right wheel due to unit aligning torques, 236, 237f
Camber change, 204–205
Camber compensation, 204–205
Camber forces, 9, 12, 427
CarSim, 460–462
Cartesian systems, 96
Castor angle, 223–224, 226f
  plotted with bump movement, 242f
CDTire, 394, 395f
Centre fleeing, 6–7
Centre seeking, 6–7
Centrifugal force, 5–7
Centripetal acceleration, 6–7, 6f
Centripetal force, 6–7
Chace, M.A., 20
Chrono::Engine, 25
Circuit racing, 589
Citroën
  Activa system, 607
  C5 model, 607
  Hydrative II, 607
  Xantia, 607
Classical methods, 13
COMMEND (Computer-Orientated Mechanical Engineering Design), 20
Commercial computer packages, 20–24
Complex conjugates, 179
Compliance matrix approach, 222, 234–237

Compliant wheel plane control, 203–204, 216–217
Component loading environment, 206–208
Component method, 136
Component mode synthesis, 93
Comprehensive (combined) slip, 374–378, 375f–376f, 378f
Computational fluid dynamics (CFD), 155, 476–478
Computational methods, 17–18
Computer-based tools, 18–19
Concept suspension approach, 460–465, 463f–464f
Concurrent engineering, 14
Constraints, 92
  basic, 122–126, 123f–126f, 127t
  degrees of freedom, 132t
    removed by, 131t
  equations, 105
  holonomic, 122
  joint, 127–129, 128f
  nonholonomic, 122
  redundant, 131–133
Cooper, D.W., 20
Coordinate systems, 96–105
  grounded reference frame, 97–98, 100f–101f
  local part reference frame, 99–100, 100f–101f
  other frames, 100–105, 100f–103f
Coriolis acceleration, 33, 57, 308
Cornell Aeronautical Laboratory (CAL), 18–19
Cornering
  free body diagram roll stiffness model during, 571f
  inertial force representation during, 540f
  at low speed, 541f
  pseudo static, 540f
Cornish, R.H., 22
Co-simulation, 508–509
Cosin, 400–401, 433
Costa, A.N., 22
Coulomb, Charles-Augustin de, 343
Coulomb friction, 149, 344, 345f
Couplers, degrees of freedom removed by, 131t
Coventry University, 215, 217f
Cranfield Impact Centre, 114–116
Cray-II computers, 21
Critical slip angle, 12
Crolla, D.A., 18–19, 21–22, 610–611
Cross (vector) product, 31–32, 31f
  differentiation of, 40
  triple, 32
C-Springs, 186
Curved Rectangular Grid, 401

D

D'Alembert force, 7, 539, 540f
DADS, 404
Daimler Group, 401
DAMN (Dynamic Analysis of Mechanical Networks), 20
Dampers
  modelling leaf springs, 465–468
  treatment in simple models, 465
Data set preparation, 89
Davis, D.C., 391–393
Degrees of freedom (DOF), 91–94, 129–135, 130f
  balance equation, for tyre rig model, 441
  calculation of, in system (Gruebler equation), 130
  constrained, 132t
  double wishbone suspension system with bushes, 212, 212t
  examples of, 522, 533
  four-bar linkage problem, 133–134, 133f, 135f
  joint, 132t
  overconstraints, 133f, 135f
  removed by constraint elements, 131t
Delft Tyre 97, 403–404
Design loads, 245
Differentiation of vectors, 37–39
Direction cosines, 29f
Dixon, J.C., 25
Dot (scalar) product, 30–31, 30f–31f
  differentiation of, 39
  triple, 32
Double wishbone suspension system, 96, 98f, 185, 210f
  comparison with multibody systems, 315, 316f
  example geometry data, 284, 284f
  instant centre, 227–231, 227f
  modelling:
    with bushes, 211–212, 211f, 212t
    with joints, 212, 213f
  mount modelling strategies, 313–315, 314f
  roll centre positions, 227–231, 227f
  static force analysis, free body diagram for, 312f
DRAM (Dynamic Response of Articulated Machinery), 20
Drive torque model, 484f
Driveline components, 485–488
Driver behaviour, 12, 500–514
  body slip angle control, 511–514
  closed-loop feedback, 12

Driver behaviour (*Continued*)
pilot-induced oscillation, 500–501, 501f
steering controllers, 501–507
adaptive controllers, 506–507
fuzzy logic, 505
logic controller, 504
moment-by-moment feedback models, 504–507
neural networks, 505–506
optimum control models, 501–503
path following controller model, 508–510
PID controller, 504–505
system identification, 506
two-loop driver model, 514, 515f
Driving force, 363–365, 364f
D'Souza, A.F., 64
Drop links
anti-roll bars modelling using, 468–469, 469f
Dunlop Tyres, 444
Durability analysis, tyre models for, 428–437
Durability studies (component loading), 241–259
dynamic durability loadcase, 254–259
overview of, 241–251
static durability loadcase, 251–254, 252f–254f
Dymola Vehicle Dynamics, 19, 21, 182
Dynamic analysis, 160, 321–329
Dynamic equilibrium, 161
Dynamic index (DI), 454, 582
centre of rotation of the vehicle, 582f
Dynamics of a particle, 64–65

E

Eigensolution, 17, 172–180
Eigenvalues, 179
Einstein, Albert, 1
Elk Test, 2
Equal transit times principle, 155
Equations of motions, 82–86, 82f, 84f
Euler equations of, 548
for part, 117–121
Equivalent ground plane model, 391–393
Equivalent rectangular prism, 107
Equivalent roll stiffness model, 458–460, 459f, 524f, 526f–528f
roll stiffness, determination of, 471–475
Euler angle method, 101–102, 101f–102f, 112, 118–120, 322, 323f
Euler-axis frame, 118–119
European Tyre and Rim Technical Organisation (ETRTO), 408–409
Extreme service loads, 206–207

F

Fast Fourier transform (FFT), 282
Fatigue, 207, 241–245, 249, 428
Ferrari, 503
Fiala tyre model, 420–422
Fiat
MG-F, 582
X/1-9, 582
Fiat Research Centre, 22
Fidelity, 4
Finite element model, 249f, 454–455, 455f
FISITA Congress, 19
Flat bed tyre test machine, 383f, 439–441, 441f
Fonda, A.G., 603–604
Force
centrifugal, 5–7
centripetal, 6–7
d'Alembert, 7
Force elements, 136–158
action-only, 136–137, 137f
beams, 156–157
bump stops, 142–143, 143f
bushes, 144, 145f, 146
component method, 136
dampers, 139–141, 139f–142f
line-of-sight, 136, 136f
rebound stops, 142
spring, 137–139, 138f
Ford, 20, 25, 182
Cortina, 555–556
Focus, 569–575
Formula Student, 215, 217f
FORTRAN, 89, 92, 182–183
for Harty tyre model, 422
roll centre height, calculation of, 232t
Forward braking free body diagram, 250, 250f
Four-bar linkage problem
overconstrained, 133, 133f
zero degrees of freedom, 134, 135f
Frames, 105–117
Free rolling tyre
contact patch, lateral distortion of, 358f
longitudinal force in, 355–359
rolling resistance in, 359f
slip generation in, 357f
French, T., 335
Frequency response, 587–589
Friction, 343–348, 344f
adhesion, 347, 348f
coefficient of, 343, 348, 362

Coulomb, 344, 345f
hysteresis, 346–347, 346f.
See also Tyres
Front end roll stiffness, 471–473, 472f–473f
FTire, 11, 394, 395f, 433, 437
Full vehicle, modelling and assembly of, 451–534, 521f
aerodynamic effects, 475–478
braking, 478–482
driveline components, 485–488
driver behaviour. *See* Driver behaviour
measured outputs, 455–457
models comparison, 519–533
NATO lane change, trajectory preparation for, 514–519
steering system, 488–500
inputs, 492–500
mechanism, modelling, 488–489
steering ratio, 490–492
subsystems integration, 452f
suspension system representation, 457–465
concept suspension approach, 460–465, 463f–464f
dampers, 465–468
equivalent roll stiffness model, 458–460, 459f, 471–475, 524f, 526f–528f
linkage model, 460, 462f, 524f, 526f–528f
lumped mass model, 457–458, 458f, 523f
overview of, 457
springs, 465–468
swing arm model, 460, 461f, 523f
traction, 483–485
vehicle body, 453–455
Functions
arithmetic IF, 92, 143–144, 220, 257
step function, 144, 254–255, 257, 486–487, 493
for a bump stop force, 144f
use with:
cubic spline, 140, 256–257, 354, 493
motion statement, 129, 220, 252, 282
variable statement, 230–231
Fuzzy logic, 505

G

Gain scheduling, 506–507
Garg, V.K., 64
Garrett, T.K., 206–207
Gaussian elimination, 114, 191
Gears, degrees of freedom removed by, 131t
General Motors, 18–19
General purpose program with other information, interaction of, 90f
Generalised coordinates, 119–120, 126
Generic control system, 494f
Geometry analysis, 44–48
suspension analysis, 47–48, 48f–50f
three point method, 44–47, 44f
Geometry analysis, 329–334
g–g diagram, 377
Gillespie, T.D., 194
Graphical user interface (GUI), 94, 95f
ADAMS/Car, 183f
ADAMS/Chassis, 184f
Gravitational constant (GC), 180–181, 480–481
Ground level offset (GO), 224–225, 226f
inclination, 224–225, 226f
Grounded reference frame (GRF), 99–100, 100f–101f, 397–398
Gruebler equation, 130
Gstiff integrator, 171
Gyroscopic torque, 9–10

H

Hales, F.D., 194
Half track change (HTC), 223, 224f
plotted with bump movement, 208, 244f
Half-vehicle suspension model, 216, 218f, 235–236, 235f
Handling
load control, 197–203
transient, 8–10
Handwheel, 5–6, 6f
Hanna, D.M., 24–25
Harmonic, 192, 195, 196f
Harty, D., 10–11, 23–24, 271
Harty tyre model, 422–427
He, J., 621
Heave, 129–130
Heeds, 15–16
Higher speed linear region behaviour, 546–554
Hollars, M.G., 22
Holt, M.J., 22
Honda, 620, 626–627
Prelude, 620, 625
Super Handling All Wheel Drive (SH-AWD), 624–625
Horne, W.B., 354, 374
Hucho, W.R., 475
Hudi, J., 20
HVOSM (Highway-Vehicle-Object Simulation Model), 22–23
Hysteretic damping, 150

I

Iltis vehicle, 24
IME Papers, 19, 535–536, 551
IMechE Papers, 19, 21
Inclination angle, 8–9, 204–205
Inifiniti, 605–606
Inplane constraint element, 124, 124f
Inplane joint primitive, 123f
Instant centre, 227–231, 227f
Intec Dynamics, 400–401
Integration methods, 168–172
Integration of vectors, 39
Interconnected finite element beams, anti-roll bars modelling using, 469, 470f
International Association for Vehicle System Dynamics (IAVSD), 24
  benchmarking study, 25
Interpolation methods, 402–403
Interpolation tyre model, 10
IPG Carmaker, 22
ISO3888 Lane Change, 2f
Issigonis Mini, 569–575
van der Jagt, P., 618

J

Jaguar Cars, 566–567
Jeantaud, C., 543–544, 544f
Joint(s)
  initial conditions, 128–129
  degrees of freedom, 132t
    removed by, 131t
  modelling suspension system using, 212, 213f, 240, 241f
  primitives:
    angular, 126, 126f
    anti-roll bars modelling using, 468, 468f
    atpoint, 123, 124f
    degrees of freedom removed by, 131t
    inplane, 124, 124f
    perpendicular, 125, 125f
  standard, 127–129, 128f, 128t

K

KAM (Kinematic Analysis Method), 20
Kaminski, S., 20
Karlsson, Kawagoe, K., 153, 587
Kelvin–Voigt model, 153
Kepler, Johannes, 1
Key performance indicator (KPI), 269–270
  active safety, 270–274
  ride, 274–283
Kim, 620
Kinematic analysis, 160
Kinematic wheel plane control, 204–206, 216–217
Kinematics and Compliance (K&C) rig, 203, 219–220
Kinetic energy, 120–121
Kisielewicz, L.T., 394
Knappe, L.F., 20
Kortum, W., 24, 211
Korybalski, K.E., 20

L

Lagrange, J.-L., 1
  equations, 86, 126
Lambda, L., 457–458
Lancia Thema 8.32, 610
Land Rover
  Active Cornering Enhancement, 607
  Discoveries, 607
Lateral acceleration, 6–8, 6f, 11
Lateral acceleration gain (AyG), 555–557, 556f, 559f, 561–562
Lateral force, generation of, 365
Lateral head toss, 475
Leaf springs, 465–468, 467f
Lee, 621
Leeds University, 22, 460–462
Leva, A., 500–501
Limpert, R., 482, 612
Linear Damage Accumulation Hypothesis, 207
Linear equations
  condition of matrix, 164–165
  forward–backward substitution, 164
  matrix decomposition, 162, 164
  pivots, 164–165
  refactorisation, 164–165
  solving, 161–165
  sparsity of matrix, 162
Linear momentum, of rigid body, 65–66, 65f
Linear Quadratic Regulators, 502
Linearity, 5, 6f
Linkage model, 460, 462f, 524f, 526f–528f
LMS DADS, 20
Loadpath
  sprung, 200, 201f–202f, 202
  unsprung, 200, 201f–202f
Local part reference frame (LPRF), 97–98, 100–101, 100f–101f
Loeb, J.S., 378–379
Logic controller, 504
Lotus, 605–606

Elan, 582
SID research vehicle, 605–606
Low speed behaviour, 541–546
Lumped mass model, 457–458, 458f, 523f
LVDS (light vehicle dynamics simulation), 23

M

M-151 jeep, 24–25
Madsen, 25
MADYMO, 21
Magic Formula tyre model, 10, 388–390, 403–420, 444
Makita, M., 413
Makkar, 345–346
Marker reference frame, 100–104, 103f
MATLAB, 18, 21–22, 404, 409, 433, 508–509, 529, 533
MBDyn, 21
McHenry, R., 22–23
McPherson strut suspension system, 208–209, 210f, 221, 227, 229, 229f
Mercedes, 566–567
A Class, 2
Active Body Control system, 605, 606f
Magic Body control, 606–607, 607f
S-Class, 611, 619
F400 Carving, 621
MESA VERDE, 22
Metex, 21
MF-Tyre 5.0, 403–404
Michelin, 404, 437
Milan, 21
Milliken Research Associates, 234, 460–462
active camber Corvette, 621
MRA Moment Method, 588
VDMS program, 22
Milliken, D.L., 369, 531, 540, 603–604
Milliken, W.F., 369, 531, 540, 603–604
Miner's rule, 207
Minitab, 15–16, 594–595
MIRA, 203, 273, 274f, 275
Mitsubishi, 620
Active Yaw Control (AYC), 624, 627
Super Active Yaw Control (S-AYC), 624, 627
Super All Wheel Control (S-AWC), 624, 627
Modal analysis, 161
Mode Frontier, 15–16
Model Reference Adaptive Scheme (MRAS), 506–507, 533
Modelica, 433
Modelica endeavour, 21
Modern multibody systems. *See* Multibody systems simulation (MBS) software, 27, 35, 58, 86
MOGESSA, 20
Moment-by-moment feedback models, 504–507
Moments of inertia, 69–73
parallel axes theorem, 73–75, 74f–75f
for plane motion, 69f
principal axes, 76–82, 76f–77f, 80f
for rectangle, 72f
for ring, 72f
Momentum
angular, 66–69
linear, of rigid body, 65–66, 65f
Moore, D.F., 343, 352
Moose Test, 2
Motion ratio, 278–280
Motion sickness, 195–196, 276
Motion statement, 220, 252
Motorcycles, 203
Motoring Press, 2
MSC ADAMS program, 20, 22, 25, 35, 86–87, 91–92, 100–101, 112, 115f, 117–119, 136, 140, 159, 181–182, 249, 253f–254f, 257, 257f–258f, 262f, 265, 278, 281, 284, 310, 311t, 315, 321, 396, 420, 429, 433, 438–439, 460–462, 480, 493, 508, 508t, 510, 522, 531, 532f, 607–608, 609t
MSC Insight, 15–16
Multibody systems simulation (MBS) software, 21–22, 24, 87–184
analysis capabilities, 160–172
integration methods, 168–172
linear equations, solving, 161–165
nonlinear equations, 165–168
overview of, 160–161
comparison with wishbone mounting models, 315, 316f
eigensolutions, 172–180
modelling features, 94–160
basic constraints, 122–126, 123f–126f, 127t
basic model components, 105
coordinate systems, 96–105, 100f–103f
degrees of freedom, 129–135, 130f, 131t–132t, 133f, 135f
force elements, 136–158
forces and moments, summation of, 158–160
part, equations of motion for, 117–121
parts and frames, 105–117
planning, 94–96
standard joints, 127–129, 128f, 128t

Multibody systems simulation (MBS) software (*Continued*)
overview of, 87–94
pre- and postprocessing, 181–184
systems of units, 180–181
MX-5, 566–567

N

NAFEMS (National Agency for Finite Elements and Standards), 24
NASTRAN, 24
National Advisory Committee for Aeronautics (NASA), 155
NATO lane change, trajectory preparation for, 514–519
.NET, 89
Neural networks, 505–506
Neural steering, 557, 560
Newman/Hass Indy Car, 181–182
Newton, Isaac, 1
Newton-Raphson iteration, 165–168, 165f–167f
Newton's Second Law, 64, 106, 180, 613
Newton's Third Law, 60, 311–312, 323–324
Nissan
ATTESA-ETS, 621–622
Full Active Suspension, 605–606
High Capacity Active Steering (HICAS) system, 620
Inifiniti, 605–606
R31 Skyline Coupé, 620–622
Super-HICAS, 620
No-dive suspension, 200, 201f
Nonlinear equations, 165–168
backwards differentiation formula method, 168
Gstiff integrator, 171
integration methods, 168–172
Newton-Raphson iteration, 165–168, 165f–167f
Nordsieck vector, 171
Pascal triangle matrix, 171
predictor–corrector, 168, 170
Taylor expansion, 171
Non-rolling tyre, stiffness in, 353f
Nordsieck vector, 171
No-roll suspension, 201f, 202
No-slip yaw rate, 510, 580

O

Octave, 409
Odhams, 495, 498f, 499–500
von der Ohe, 211
Ohio State University, 23
Olley, M., 365, 540
van Oosten, 409
Operating shape, 260
Optimum control models, 501–503
Orlandea, N., 20, 172, 211
Overrotation, 561–562
Oversteer, 558, 561–575, 628
Overturning moment, 373–374, 374f
Ozdalyan, B., 612–614

P

PAC2002, 404
Pacejka, H.B., 10–11, 363, 382, 387–390, 403–406, 409, 420–421
Palmer, D., 509–510
Parallel axes theorem, 73–75, 74f–75f
Parts, 105–117
equations of motion for, 117–121
location and orientation of, 117f
summation of forces and moments on, 158–160
Pascal triangle matrix, 171
Path error, 495, 497–499, 502
alternative calculation scheme, 499f
calculation, 500
Path following controller model, 508–510
Pavé or Belgian Block, 272–273, 274f, 275
Pendulum, 174–175, 175f
Perpendicular constraint element, 125, 125f
Persson, 153
Phillips, B.D.A., 339, 359, 362, 377
PID controller, 504–505
Pilot-induced oscillation (PIO), 500–501, 501f
Plane motion, moments of inertia for, 69f
Playstation, 23–24
Porsche 911, 567–569
Position vectors, 27–30, 28f
components, resolution of, 28f
Pre- and postprocessing, 181–184
Predictive methods, 13, 16–17
Predictor–corrector approach, 168, 170
Pressure distribution, in tyre contact patch, 348–350, 349f
Principal axes, 76–82, 76f–77f, 80f
Protean Electric Ltd, 627–628
Prototyping, 16
PushRod, 217f
Python, 89

Q

Quarter vehicle
body vertical acceleration time history, 283f
dynamic performance analysis, 261–270, 261f–262f

model, 185, 191, 192f, 206–207, 211–216, 222–223, 231–233, 255f, 271, 279f, 282

R

Racing kart frame flexibility, influence of, 188, 189f
Radial spring terrain enveloping tyre model, 394f
Rai, N.S., 249
Rake, 203
Rallying, 589–590
RASNA Applied Motion Software, 22
Rectangle, moments of inertia for, 72f
Reference frames
  Euler-axis frame, 118–119
  grounded reference frame, 99–100, 100f–101f, 397–398
  local part reference frame, 97–98, 100–101, 100f–101f
  marker reference frame, 100–104, 103f
Reference load, 408–409
Refinement, 3–4
Relative position vectors, 27–30, 29f
Relaxation length, 378–381, 416
Renault, 182
Resonic, 114–116
Response
  frequency, 587–589
  presumed, 595, 596f
Rice, R.C., 207
Ride, 3–4, 195
  frequency sweep 'chirp', 281–282, 282f
  harshness, 260
  noise and vibration, 260
  primary, 260, 274
  quarter vehicle dynamic performance analysis, 261–270, 261f–262f
  rate, 279–280
  secondary, 260, 274
  studies (body isolation), 259–283
  wheel hop, 266
Ride KPIs, 274–283
Rigid bodies
  kinematics and dynamics of, 27–86
    acceleration analysis, 53–58, 54f–56f
    angular momentum, 66–69
    dynamics of a particle, 64–65
    geometry analysis, 44–48
    moments of inertia, 69–73, 69f, 72f
    parallel axes theorem, 73–75, 74f–75f
    principal axes, 76–82, 76f–77f, 80f
    rigid body, linear momentum of, 65–66, 65f
    static force and moment definition, 58–64, 59f–60f, 62f–63f
    suspension analysis, 47–48, 48f–50f
    three point method, 44–47, 44f
    theory of vectors. *See* Vectors
    velocity analysis, 48–53, 50f, 53f
  linear momentum of, 65–66, 65f
  motion, 82f
  six particle concept for, 106, 106f
Ring, moments of inertia for, 72f
Ro, 620
Road springs, roll stiffness due to, 473–474, 474f
Road surface, 194, 400–402
  frequency content, 193–194, 194f
Road wheel angle, 558
Robust design, 593, 594f
Roll, as objective and subjective modifier, 585–587
Roll centre, 185, 200, 202, 219, 458–459
  height, 203, 229–230, 231t–232t
    plotted with bump movement, 243f
  McPherson strut suspension system, 229, 229f
  positions, 227–231, 227f
Roll lock, 475
Roll stiffness, 25
  due to anti-roll bar, 474–475, 474f
  determination, for equivalent roll stiffness model, 471–475
  front end, 471–473, 472f–473f
  due to road springs, 473–474, 474f
Roll understeer, 204
Rolling resistance, 355–359
Rotation of vectors, 32–35, 33f–35f

S

SAE (Society of Automotive Engineers), 19, 219, 351–353, 352f, 356
SARAH (Suspension Analyses Reduced ADAMS Handling), 22
Sayers, M.W., 22
Scalar product. *See* Dot (scalar) product
Scapaticci, D., 22, 460–462, 464
SDFAST, 22
Seat, 611
Segel, L., 2–3, 18–19, 540
Self-tuning regulator, 506–507, 533
Service loads, 245
Sharp, R.S., 14, 24, 387–390, 503
Signal-to-noise ratio approach, 591–602
Sign-off testing, 17, 207
Simpack, 19, 21, 91, 96, 100, 182, 209f, 216, 404–405, 433, 437–439

SimTK, 21
Simulation output and interpretation, 535–602
  accident avoidance, 590–591
  circuit racing, 589
  classical treatment, 540–558
    higher speed linear region behaviour, 546–554
    low speed behaviour, 541–546
    nonlinear region, 554–558
  frequency response, 587–589
  rallying, 589–590
  roll, as objective and subjective modifier, 585–587
  signal-to-noise ratio approach, 591–602
  steering feel, as subjective modifier, 583–585
  subjective/objective problem, 558–562
  transient effects, 576–583
  travel on a curved path, 539
  variation in measured data, 537–538
  understeer/oversteer, 562–575
    50/50 vehicle, 566–567
    nose heavy vehicle, 569–575
    tail heavy vehicle, 567–569
Simulink, 508–509, 529, 533
Six sigma, 538
Six-mass method, 107, 108f
Skoda, 611
Sleeping policeman speed bump, road profile for, 256, 256f
Sliding pillar, 457–458
Slip angle, 8–9, 12, 205
  combined with camber angle, 372–373, 373f
  critical, 12
  effect on tyre force and moments, 365–368, 366f–368f
Slip ratio, 9
  versus braking force, 361–362, 362f
Smithers Scientific Services Inc., 404
Soloman, A.R., 249
Springs, 137–139, 138f, 465–468
  leaf, 465–468, 467f
  treatment in simple models, 465
Sprung loadpath, 200, 201f–202f, 202
Stability, 4
Static analysis, 160
Static force and moment definition, 58–64, 59f–60f, 62f–63f
Static indeterminacy, 187–188, 188f
Steady state, 5–6, 8
Steer (toe) angle, 223, 225f, 334f
  plotted with bump movement, 243f
  at right wheel due to unit aligning torques, 236, 236f
Steer angle geometry definitions, 545f
Steer axes, of suspension system, 221–223, 222f
  inclination, 224–225, 226f
Steering feel, as subjective modifier, 583–585
Steering ratio, 490–492
Steering system, 487f, 488–500
  inputs, 492–500
  mechanism, modelling, 488–489
  steering ratio, 490–492
Stengel, 155
Stribeck effects, 345–346
Student race car, anti-roll bar mechanism in, 471, 471f
Student race vehicle, anti-roll bar mechanism in, 469–470, 471f
Subjective/objective problem, 558–562
Suspension model, redundant constraints in, 133f
Suspension systems, 185–334
  bump movement, 223, 224f
  camber angle, 223, 225f
  castor angle, 223–224, 226f
  characteristics, determination of, 215–219
  compliance matrix approach, 234–237
  design process, 187t
    body isolation, 191–197
    compliant wheel plane control, 203–204, 216–217
    component loading environment, 206–208
    handling load control, 197–203
    kinematic wheel plane control, 204–206, 216–217
    wheel load variation, 187–191
  double wishbone, 185, 210f
    comparison with multibody systems, 315, 316f
    example geometry data, 284, 284f
    geometry analysis, 330f, 332f
    instant centre, 227–231, 227f
    modelling with bushes, 211–212, 211f, 212t
    modelling with joints, 212, 213f
    mount modelling strategies, 313–315, 314f
    roll centre positions, 227–231, 227f
    static force analysis, free body diagram for, 312f
  durability studies of, 241–251
    data requirements for, 216t
    example of, 251–259
  dynamic analysis of:
    data requirements for, 216t
    example of, 254–259
  ground level offset, 224–225, 226f
  half track change, 223, 224f
  instant centre, 227–231, 227f

kinematic analysis of:
data requirements for, 216t
example of, 237–241, 238f
McPherson strut, 208–209, 210f, 221, 227, 229, 229f
measured outputs, 219–220
modelling of, 457–465
concept approach, 460–465, 463f–464f
equivalent roll stiffness model, 458–460, 459f, 471–475, 524f, 526f–528f
linkage model, 460, 462f, 524f, 526f–528f
lumped mass model, 457–458, 458f, 523f
overview of, 457
swing arm model, 460, 461f, 523f
need for, 186–208
quarter vehicle dynamic performance analysis, 261–270, 261f–262f
quarter vehicle modelling approaches, 211–215
ride studies (body isolation), 259–283
roll centre positions, 227–231, 227f
static (quasi-static) analysis of:
data requirements for, 216t
example of, 251–254
steer (toe) angle, 223
steer axes, 221–223, 222f
steering axes inclination, 224–225, 226f
trade-offs, 611f
trail, 223–224, 226f
types of, 208–209
vector analysis comparison with MBS, 283–334
acceleration analysis, 298–310
dynamic analysis, 321–329
geometry analysis, 329–334
problem definition, 283–284
stability analysis, 310–321
velocity analysis, 285–297, 285f, 287f, 291f
wheel rate, 231–234
wheel recession, 223, 224f
SWIFT (short wavelength intermediate frequency tyre), 403–404, 429
Swing arm model, 460, 461f, 523f
Swing arm suspension dynamics, 84, 84f
System identification, 506
System model, overconstrained loop in, 135f
Systems of units, 180–181
units consistency factor, 180–181
Systems Technology, Inc., 23

T

Taguchi principle, 594
Tail heavy vehicle, 567–569
TAME tyre model, 11, 437
Tandy, K., 23
TeimOrbit®, 400–401
Terlinden, M.W., 20
Terrain definition, 400–402
Three point method, 44–47, 44f
Timoshenko beam theory, 156–158
TIRSUB, 438
TNO, 21, 429
Road-Vehicles Research Institute, 409
Toe change, 204
Toe-out, 204
Topology map
implementation of, 97f
text-based, 96f
Traction, 483–485
Transformation matrix, 104
Transformation of vectors, 36–37, 36f
Transient effects, 576–583
Transient handling, 8–10
Travel on a curved path, 539
Tripod structure, 59, 59f
force body diagram of, 59, 60f
TruckSim, 22
Turbocharger, 485, 486t, 488f
Two-and-a-half DOF (2½ DOF) model, 566
Two-degree-of-freedom (2DOF) mode. *See* Bicycle model (2DOF)
Two-loop driver model, 514, 515f
TYDEX, 338, 386, 438
TYR5012 subroutine, 438
Tyres, 335–450
asymmetry, 341–343
conicity, 341–343, 341f
plysteer, 342–343, 342f
axis frames (SAE J2047 & ISO 8855), 336–338, 337f
camber angle, 8–9
contact patch, 343–350
friction, 343–348
length, 349, 350f
pressure distribution in, 348–350
road loads application at, 246, 248f
critical slip angle, 12
deflection under hard cornering, 336f
experimental testing, 381–386
forces and moments, 351–381
aligning moment, 365
braking force, 359–363
camber angle, effect of, 368–372
camber–slip angle combination, effect of, 372–373

Tyres (*Continued*)
comprehensive (combined) slip, 374−378
driving force, 363−365
lateral force, 365
overturning moment, 373−374
rolling resistance, 355−359
slip angle, effect of, 365−368
stiffness, 351−352, 353f
vertical force, 352−355, 354f
Gough plot, 386f
implementation with multibody systems, 437−442
virtual tyre rig model, 438−442
lag, 378
-model architecture, 335−336
model data, examples of, 442−444
modelling of, 10−11, 387−437
durability analysis, 428−437
Fiala tyre model, 420−422
geometry and velocities, calculation of, 396−400
Harty tyre model, 422−427
interpolation methods, 402−403
Magic Formula tyre model, 403−420
overview of, 387−396
road surface/terrain definition, 400−402
models comparison, 445−450
radii, 338−341, 338f
effective radius, 339
loaded radius, 339, 341
relaxation length, 378−381, 416
rolling, deformation of, 339f
slip angle, 8−9, 12, 205
slip ratio, 9, 361−362, 362f
-specific model, 335−336
stiffness, 351−352, 353f
aligning moment, 352, 368, 369f
aligning moment camber, 372, 372f
camber, 369, 370f, 391f−392f
cornering, 352, 367−368, 368f, 386, 387f, 406, 408, 408f, 412−413, 416−419
lateral, 353f
longitudinal, 352, 353f, 362−363, 362f, 369, 371−372
torsional, 353f

U

Understeer, 554−555, 557−558, 560−575, 628
gradient, 557f
technical, 554
transient, 580
Units consistency, 180−181, 181t
Units consistency factor (UCF), 180−181, 323−324
University of Bath, 25
University of Leeds, 22, 460−462
University of Michigan, 460−462
University of Missouri, 23
Unsprung loadpath, 200, 201f−202f

V

Variable damping, 605−611
VDANL (vehicle dynamics analysis non-linear simulation), 23
VDAS (Vehicle Dynamics Analysis Software), 22, 460−462
VDMS (Vehicle Dynamic Modelling System), 22, 234, 460−462
Vectors
cross (vector) product, 31−32, 31f
differentiation of, 40
differentiation of, 37−40
dot (scalar) product, 30−31, 30f−31f
differentiation of, 39
integration of, 39
position, 27−30, 28f
relative position, 27−30, 29f
rotating with constant velocity, 38f
rotation of, 32−35, 33f−35f
scalar triple product, 32
suspension analysis with, 283−334
theory of, 27−43
transformation of, 36−37, 36f
vector triple product, 32
Vehicle behaviour, geometric approximations of, 5, 5f
Vehicle body, 453−455
coordinate system, 80f
reference frame, 454, 454f
Vehicle dynamics, 3f
defined, 3−12
interactions, 4f
Vehicle manoeuvring, in ground plane, 198f
Vehicle suspension geometry analysis, 47−48, 48f−50f
Velocity analysis, 48−53, 50f, 53f, 285−297, 285f, 287f, 291f
Vertical force, plotted with bump movement, 243f
da Vinci, Leonardo, 95f
Virtual motion, 20
Virtual prototypes, 89
Virtual tyre rig model, 438−442
Volkswagen, 20, 611
Volvo, 182

VW Beetle, 567–569
VW Polo, 569–575

W

Weigh transfer, 563–565
  due to lateral force, 574f
  due to roll moment, 572f
Wenzel, T.A., 529, 531
Wheel centre (WC)
  equivalent spring acting at, 231–233, 233f
  input of vertical motion at, 220, 221f
  instant centre construction points on, position of, 227, 228f
Wheel envelope, 218–219, 218f
Wheel load
  reaction problem, 189f
  variation, 187–191
Wheel plane control
  compliant, 203–204, 216–217
  kinematic, 204–206, 216–217
Wheel rate calculation, 231–234
Wheel recession (WR), 223, 224f
Whitehead, J., 25, 219–220
Will, A.B., 529–530
Wong, J.Y., 529–530
WOODS, 20
Word cloud diagram, 3, 3f

X

X-point-Z-point method, 102–104, 103f

Y

Yaw acceleration, 9, 11–12
Yaw rate, 7–8
  demand, 5, 539
  geometric, 559
Yaw rate gain (YRG), 553–554, 555f, 556–557, 560–562, 566

Z

Zak, S.H., 529–530
Zverev, 608–610