


ID2207 – Fourth Tutorial

Amirhossein Layegh

amlk@kth.se

2025-09-23



Object Constraint Language OCL

Object Constraint Language OCL

- Constraint-> is a rule that allows you to specify some **limits** on **model elements**.
- It can also be defined as a **restriction** on one or more values of (part of) an object-oriented model or system.
- OCL -> A **language** that express the constraints.

Object Constraint Language OCL

- Three types of constraints:
 - Invariant ->
 - -
 - -

Object Constraint Language OCL

- Three types of constraints:
 - Invariant -> A property that **must remain true** throughout the life of an object.
 - Pre-condition ->
 - -

Object Constraint Language OCL

- Three types of constraints:
 - Invariant -> A property that **must remain true** throughout the life of an object.
 - Pre-condition -> Something that must be true **before** a particular part of the system is **executed**. **Prevent** the system to enter **illegal state**.
 - Post-condition ->

Object Constraint Language OCL

- Three types of constraints:
 - Invariant -> A property that **must remain true** throughout the life of an object.
 - Pre-condition -> Something that must be true **before** a particular part of the system is **executed**.
 - Post-condition -> Something that must be true **after** a particular part of the system is **executed**.

Invariant Example

- The age of a car sharer that we analysed in Tutorial 2, must be over 21:

Context

Invariant Example

- The age of a car sharer that we analysed in Tutorial 2, must be over 21:

Context CarSharer **inv**:

age > 21

The keyword **context** introduces a **model element** to which the invariant applies (the class name in this example), and **inv** introduces the constraint as an **invariant**.

Pre-condition Example

- Making sure that enough money is in a savings account before making a withdrawal:

Pre-condition Example

- Making sure that enough money is in a savings account before making a withdrawal:

Context Account::withdraw (amount:Integer)
pre: balance >= amount

Post-condition Example

- An account's balance must be reduced by the amount withdrawn after a withdrawal


Context Account::withdraw (amount:Integer)

post: balance = balance@pre - amount

@pre shows the initial value of a property that is changed by an operation

Navigation

- Navigate to an element of a model.




- To refer to a car sharer's account balance:
 - the balance should be no more than 100\$ overdrawn

Context Carsharer **inv:**

Account.balance >= -100

Navigation

- Navigate to an element of a model.




- To refer to a car sharer's account balance:
 - the balance should be no more than 100\$ overdrawn

Context Carsharer **inv:**
Account.balance >= -100

If the expression is complex, and you want to avoid ambiguity, the word **self** can be used to refer to the instance of the class that is named as the context.

Navigation

- Navigate to an element of a model.



- To refer to a car sharer's account balance:
 - the balance should be no more than 100\$ overdrawn

Context Carsharer inv:

`Account.balance >= -100`




Context Carsharer inv:

`self.Account.balance >= -100`

If the expression is complex, and you want to avoid ambiguity, the word **self** can be used to refer to the instance of the class that is named as the context.


Navigation Example

- Suppose there are two types of accounts: membership and insurance and you want to indicate that the insurance account must not be overdrawn by more than 500\$.



Navigation Example

- Suppose there are two types of accounts: membership and insurance and you want to indicate that the insurance account must not be overdrawn by more than 500\$.




Context Carsharer **inv:**

`Insurance.balance >= -500`


Navigation Example

- It is also possible to navigate across a number of associations.
- The driver in a journey has paid the insurance:



Navigation Example

- It is also possible to navigate across a number of associations.
- The driver in a journey has paid the insurance:




Context Journey inv:

`driver.insurance.balance >= 0`


Navigation Example

- express that the distance of any journey is two miles or more:



Navigation Example


- express that the distance of any journey is two miles or more:



Context Journey **inv:**


`startAddress.distanceTo(self.destinationAddress) >= 2.0`

Exercise One: Insurance Policies




Exercise One: Insurance Policies

Membership must be fully paid before taking out insurance.




Exercise One: Insurance Policies

Membership must be fully paid **before** taking out insurance.




Exercise One: Insurance Policies

The first payment of the payment schedule must be made before cover is granted



Exercise One: Insurance Policies

The first payment of the payment schedule must be made before cover is granted




Context SPCControl::createPaymentSchedule(startDate, regularDate, amount, frequency)

pre: PaymentSchedule.startDate.before(policy.startDate)

Exercise One: Insurance Policies

Two policies must not be in force at the same time for a given car sharer



Collections


- The situation that association can refer to many objects.
 - **Sets**: consists of distinct instances and there are no repetitions in the set (NO ordering)
 - **Sequences**: an ordered collection that allows repetition
 - **Bags**: an unordered collection that allows repetition
- Example:
- Select - picks out a subset of elements from a collection that meet a particular condition, the syntax: **collection -> select(v | boolean-expression-with-v)**

OCL provides many operations for accessing collections. The most often used are

- `size`, which returns the number of elements in the collection
- `includes(object)`, which returns `True` if `object` is in the collection
- `select(expression)`, which returns a collection that contains only the elements of the original collection for which `expression` is `True`
- `union(collection)`, which returns a collection containing elements from both the original collection and the collection specified as parameter
- `intersection(collection)`, which returns a collection that contains only the elements that are part of both the original collection and the collection specified as parameter
- `asSet(collection)`, which returns a set containing each element of the collection.


Exercise One: Insurance Policies

Two policies must not be in force at the same time for a given car sharer




Exercise One: Insurance Policies

The renewal day of policy is always after its start day




Exercise One: Insurance Policies

The renewal day of policy is always after its start day




Context Policy inv:
startDate.before(renewalDate)

Exercise Two: Students and Exams




Exercise Two: Students and Exams

Modules can be taken if they have more than seven students registered



Exercise Two: Students and Exams


Modules can be taken if they have more than seven students registered




Context Module inv:
taken_by.size > 7

Exercise Two: Students and Exams

The assessments for a module must total 100%



Exercise Two: Students and Exams




The assessments
for a module must
total 100%

Context Module inv:
set_work.weight -> sum() = 100


Context Module inv:
sum(set_work.weight) = 100

Exercise Two: Students and Exams

In the assessments of modules that students take exams must be at least 4 hours



Exercise Two: Students and Exams



In the assessments of modules that students take exams must be at least 4 hours

Context Students inv:
takes.set_work.hours -> forall(h| h>=4)