Review: Net-Ev^2: A Generative Simulator for Network Event Evolution

November 11, 2026

Authors: Guangyu Wang, Zhonan Wang
Published: 32nd ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.2
Link: http://arxiv.org/abs/2606.12494
Citation: [5]

1 Abstract

Reducing real-world trial and error has long been a central goal of decision making, and generative simulators advance this goal by modeling the evolution of future states. An even more challenging yet meaningful task is simulating how disturbance events (e.g., accidents) propagate their impacts across real-world networks. The existing approaches fall short of modeling both structured attributes and unstructured semantics of events, and capturing topological structures in simulating network event evolution. Therefore, we are motivated to propose Net-Ev2 (Network Event Evolution), a novel generative simulator that jointly leverages event cues while preserving network topology in simulations. Specifically, the framework consists of two stages, namely structure-guided masked pretraining and topology-aware diffusion process, which is achieved by U-Net-like graph downsampling and upsampling during denoising. At inference time, Net-Ev2can generate simulations using natural-language event input only, with greater flexibility for practical usage. Furthermore, we introduce Net-Ev2-6.5M, a multimodal benchmark of aligned event and network traffic data across four large-scale road networks, as well as a new topology-aware metric, namely JL-MMD, to evaluate topological fidelity in generated network dynamics. Extensive experiments demonstrate the state-of-the-art performance and strong generalization ability of Net-Ev2. Code is made available at https://github.com/Guangyu4/Net-Ev-2

2 Keywords

Generative Simulator, Network Event Evolution, Diffusion Models, Johnson-Lindenstrauss Lemma

3 Introduction

- Generative simulators → state evolution over time → closed-loop evaluation → scalable data generation
- Generative models come in two design paradigms:




Figure 1: Generative simulation for network event evolution

1. Network to visual-like representations for diffusion models: line graphs, field transforms, or data rendered as RGB images. Struggles to capture full complexity of network evolution
2. Diffusion architechtures: flow matching, denoising diffusion probabilistic models. Better fit for variable length sequences, multivariate dependencies, long-term trends etc.

- Network evolution poses challenges for existing methods, and events can have textual and quantitative modalities
- **Example:** unstructured text (I-8 Eastbound and Significant Traffic), quantitiative attributes such as node indices and timespans
- Problematic to combine modalities, language encoders such as BERT struggle with numerical data as input
- Structured data harder to obtain than unstructured data in real-wordld applications, and ideally model should use structure information for training but perform well in the absence of it
- Networks have graph topology, events propogate on edges. Denoiser models fail to capture propogation details
- This issue rarely considered in evaluation, topology-aware metrics are largely missing

- Paper proposes Net-Ev^2 generative simulator for network event evolution and associated multimodel benchmark (6.5M events)
- introduce topology aware metric JL-MMD, inspired by Johnson-Lindenstrauss lemma

Contributions:

- Problem: simulating evolution of network states under textual event conditions
- Propose the Net-Ev^2 generative model, which combines masked pretraiing with a topology-aware denoiser
- Net-Ev^2-6.5M a multi-modal benchmark of aligned event text and network traffic data
- JL-MMD a metric based on Johnson-Lindenstrauss random projection to evaluate topological fidelity on generated network dynamics

4 Preliminaries

Model a network graph as $G = (V, A)$ where V is a set of N sensor nodes and $A \in \mathbb{R}^{N \times N}$ is the adjacency matrix representing the network topology. $X \in \mathbf{R}^{T \times N}$ denote a sequence of network snapshots (e.g. traffic volume) over T steps. For each efvent X is represented by a set of multi-structural attributes $E = E_{i_{i=1}}^{M}$, including a textual description E_d and structured properties. Given these conditions as an initial state, the problem is to simulate realistic future states $\hat{X}$ that reflects how an even evolves and propogates over the network topology.

$$E = E_{i_{i=1}}^{M} \overset{G}{\rightarrow} \hat{X} \in \mathbf{R}^{T \times N}$$

E is comprised of $E = (E_d, E_n, E_t)$, corresponding to the textual description, spatial context, and impacted nodes in the egocentric subgraph (whatever that means), and temporal context, respectively.

5 Net-Ev2-6.5M Benchmark

New multimodal benchmark integrating signal observations from LargeST [3] and event records from LSTW [4]. Covers San Diegeo, Greated Bay Area, Greater Los Angeles, and California. Previous little work combining traffic and event datasets, so matched using the following conditions

1. *Event-traffic alignment* Align sensor readings to incident reports and weather events
2. *Event descriptions* Attach weather descriptions to weather events using LLMs matching style as LSTW incident events
3. *Multi-structural sample organization* 6.5M samples consisting of (1) textual description E_d, event descrioptoin encoded by text encoder; (2) network snapshots $X \in \mathbf{R}^{T \times N}$, the subsequent time steps, (3) Spatial context E_n, the target node and its n-hop neighbors over the network; Teemporat context E_t the event's start and end timestamp

Table 1: Summary of Net-Ev2-6.5M benchmark (*no detailed incident types are reported for GLA and GBA in LSTW).

		Incident Events							Weather Events					
Subset	Total	Accident	Broken-Vehicle	Congestion	Construction	Event	Lane-Blocked	Flow-Incident	Severe-Cold	Fog	Hail	Rain	Snow	Storm
SD	836,694	5,804	2,049	33,933	2,676	2	3,847	3,536	440,186	740	82,308	265,359	810	561
GLA	654,420	*51,086	0	0	0	0	0	0	237,202	1,536	243,411	125,394	1,328	99
GBA	1,201,201	*22,639	0	0	0	0	0	0	329,502	3,442	383,211	462,014	3,888	83
CA	3,824,877	33,427	9,709	189,586	11,195	33	23,216	15,919	1,252,645	3,252	338,278	1,965,992	15,980	8,145
Total	6,517,192	112,956	11,758	223,519	13,871	35	27,063	19,455	2,259,535	8,970	1,047,208	2,818,759	22,006	8,888

6 Methodology

Input is a network snapshot sequence X, fed into encoder with spatio-temporal and structure guided masks, following a masked autoencoder design. Noise added to hidden representations during training, and topology aware denoiser removes it using pooling/unpooling operations to preserve network topology. Unstructured even conditions are injected vis AdaLN [1]




Figure 2: Net-Ev^2 framework: the upper illustrates the structure-guided masked pre-training; the lower depicts the topologyaware diffusion process

6.1 Structure guided MAE

MAE compresses traffic observations to latent space where diffusion operates efficiently. During training use multi-structural event information to guide masking strategies. Apparently a better method than encoding as special tokens.

6.1.1 Spatio-temporal masking

Binary masks $\mathbf{M}^{(t)}, \mathbf{M}^{(s)} \in \{-0, 1\}^{T \times N}$ by selecting random subsets of $\mathcal{T}\lfloor \rho \cdot T$ and $\mathcal{S}\lfloor \rho \cdot S$ and setting masks to zero for both.

6.1.2 Structure-guided masking

Masking nodes E_n and corresponding time windows E_t:

$$\mathbf{M}^{(e)}_{:,j} = 0 \text{ for } j \in E_n \qquad \mathbf{M}^{(e)}_{i,:} = 0 \text{ for } i < \max(E_t)$$

where E_t denotes the events of temporal span, and i $<$ max(E_t) masks teh entire event duration

6.1.3 Variational encoder-decoder architechture

adopts a variational formulation [2] for generalizability. Encode masked input to latent representation where decoder reconstructs from original signal. The encoder projects the input to latent space then applies transformer layers:

$$[\mu, \log\sigma^2] = \text{TransformerEncoder}(\text{Linear}(X \odot M))$$

Where we then sample $z = \mu + \sigma \odot \xi$ with $\xi \sim \mathcal{N}(0, \mathbf{I})$ during training, and use $z = \mu$ at inference. The decoder then maps back z to original space $\hat{X} \in \mathbf{R}^{T \times N}$

References

[1] Yunfeng Ge, Jiawei Li, Yiji Zhao, Haomin Wen, Zhao Li, Meikang Qiu, Hongyan Li, Ming Jin, and Shirui Pan. T2s: High-resolution time series generation with text-to-series diffusion models. *arXiv preprint arXiv:2505.02417*, 2025.

[2] Richard Jordan, David Kinderlehrer, and Felix Otto. The variational formulation of the fokker–planck equation. *SIAM journal on mathematical analysis*, 29(1):1–17, 1998.

[3] Xu Liu, Yutong Xia, Yuxuan Liang, Junfeng Hu, Yiwei Wang, Lei Bai, Chao Huang, Zhenguang Liu, Bryan Hooi, and Roger Zimmermann. Largest: A benchmark dataset for large-scale traffic forecasting. *Advances in neural information processing systems*, 36:75354–75371, 2023.

[4] Sobhan Moosavi, Mohammad Hossein Samavatian, Arnab Nandi, Srinivasan Parthasarathy, and Rajiv Ramnath. Short and long-term pattern discovery over large-scale geo-spatiotemporal data. In *Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining*, pages 2905–2913, 2019.

[5] Guangyu Wang and Zhaonan Wang. Net-Ev^2: A Generative Simulator for Network Event Evolution. In *Proceedings of the 32nd ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.2*, pages 4836–4847, August 2026. doi: 10.1145/3770855.3817972. URL `http://arxiv.org/abs/2606.12494`. arXiv:2606.12494 [cs.LG].