

Site Experience #6.00

Site Experience #6.00	1
Brief	1
Reflective - What did I learn?	1
End to End test	2
The figure of eight test	2
The figure of eight test we conduct the following two tests:	2
For example, if the R1 and RN = 0.40 ohms. Then we expect R1 and R2 = 0.668 ohms.	2
Comparatively, R1 and R2 should be 1.67 times higher than the R1 and RN wire. This is because 2.5mm^2 divide by $1.5\text{mm}^2 = 1.67$.	2
Loop impedance test	2

Brief

On this day I was based the entire day in Oakham the whole day as I worked on an installation project.

Reflective - What did I learn?

- Ring circuits were introduced after World War Two because there was a copper shortage.
- Sockets are always on a ring final circuit.
- In the rose ceiling circuit we placed all the red wires into the Loop section.
- The **cooker** is on a radial circuit.
- **Lights** are on a radial circuit.

End to End test

Is a continuity test which ensures that the wire is connected the whole way around.

The figure of eight test

The figure of eight test we conduct the following two tests:

R1 and **R2**
R1 and **RN**.

For example, if the **R1** and **RN** = 0.40 ohms. Then we expect
R1 and **R2** = 0.668 ohms.

Comparatively, **R1** and **R2** should be **1.67 times** higher than the **R1** and **RN** wire. This is because 2.5mm^2 divided by $1.5\text{mm}^2 = 1.67$.

Loop impedance test

He performed a test in which no modifications were made to the fuse board. On the tester there are two sections: Live testing and Dead testing.

He plugged the chords into Live, Earth and Neutral. Then on the opposite end he plugged a three pin plug into the sockets.

He mentioned that this is a Live test and checks the Earth Fault Loop impedance.

On the ring circuit there were for plugs the readings were as follows:

First socket: 0.30
Second socket: 0.32
third socket:0.30
Fourth socket: 0.30

SiteVisit: 30th November 2025
Written:04/12/2025
IWA

Photographic content



Connecting a humidistat time fan