

(Q1)

Write the difference between Java & JavaScript.

Java:

- Java is an object-oriented programming language used for building standalone applications, web apps, Android apps, etc.
- Java is compiled (into bytecode using JVM).
- Java runs on JVM (Java Virtual Machine).
- Strongly typed (you must define data types).
- Used for backend development, enterprise applications, Android, desktop applications.
- Syntax is similar to C/C++ and is more complex.

JavaScript:

- JavaScript is a scripting language used mainly for making web pages interactive and dynamic.
- JavaScript is interpreted by web browsers.
- JavaScript runs directly on the browser or on Node.js.
- Loosely typed (no need to specify data types).
- Used for frontend development, web animations, validations, backend (Node.js), etc.
- Syntax is simpler and more flexible.

(Q2)

Why do we use JavaScript? Why is it so popular? (Advantages)

Uses of JavaScript:

- To make web pages interactive (buttons, forms, animations).
- To validate form input before sending to the server.
- To update content without refreshing the page (AJAX).
- To build frontend frameworks (React, Angular, Vue).
- To build backend servers using Node.js.

Advantages:

- Fast execution - Runs directly in the browser without needing compilation.
- Easy to learn - Simple and beginner-friendly syntax.
- Platform independent - Works on all browsers and devices.
- Huge community support - Many libraries and frameworks.
- Full-stack development -
Frontend: React, Angular, Vue
Backend: Node.js
- Rich interfaces - Allows animations, sliders, popups, dynamic content.

(Q3)

```
<!DOCTYPE html>
<html lang="en">
<head> <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Outputs: Console, Alert, Document</title>
</head>
<body>
  <script>
    function q3() {
      console.log("This shows in console");
      alert("This is a popup box");
      document.write("This shows on the page");
    }
    q3();
  </script>
</body>
</html>
```

(Q4)

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Var Let Const</title>
</head>
<body>
  <script>
    function q4() {
      var a = 10;
      {
        let b = 20;
        const c = 30;
        alert("Block scoped variables: b=" + b + ", c=" + c);
      }
      alert("Global/Function scoped: a=" + a);
    }
    q4();
  </script>
</body>
</html>
```

(Q5)

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Addition</title>
</head>
<body>
  <script>
    function q5() {
      let n1 = Number(prompt("Enter first number"));
      let n2 = Number(prompt("Enter second number"));
      let sum = n1 + n2;
      console.log(sum);
      alert("The sum is: " + sum);
    }
    q5();
  </script>
</body>
</html>
```

(Q6)

```

<!DOCTYPE html>
<html lang="en">
  <head><meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>Most Significant Number</title>
  </head><body>
    <script>
      function q6() {
        let n1 = Number(prompt("Enter number 1"));
        let n2 = Number(prompt("Enter number 2"));
        let n3 = Number(prompt("Enter number 3"));
        if (n1 < 10 || n2 < 10 || n3 < 10) {
          alert("Please enter numbers with 2 digits or more");
        } else {
          let max = n1;
          if (n2 > max)
            max = n2;
          if (n3 > max)
            max = n3;
          document.write("Largest number is " + max);
        }
      }
      q6();
    </script>
  </body>
</html>

```

(Q7)

```

<!DOCTYPE html>
<html lang="en">
  <head><meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>Fibonacci Series</title>
  </head>
  <body>
    <script>
      function q7() {
        let limit = Number(prompt("Enter the nth term:"));
        let n1 = 0, n2 = 1, nextTerm;
        let i = 0;
        document.write("Fibonacci: ");
        while (i < limit) {
          document.write(n1 + " ");
          nextTerm = n1 + n2;
          n1 = n2;
          n2 = nextTerm;
          i++;
        }
      }
      q7();
    </script>
  </body>
</html>

```

(Q8)

```

<!DOCTYPE html>
<html lang="en">
<head><meta charset="UTF-8" />
  <meta name="viewport" content="width=device-width, initial-scale=1.0" />
  <title>Prime Number</title>
</head><body>
  <script>
    function q8() {
      let num = Number(prompt("Enter a number"));
      let isPrime = true;
      if (num <= 1) {
        isPrime = false;
      }
      for (let i = 2; i < num; i++) {
        if (num % i === 0) {
          isPrime = false;
          break;
        }
      }
      if (isPrime) {
        document.write(num + " is Prime.");
      }
      else {
        document.write(num + " is not Prime.");
      }
    }
    q8();
  </script>
</body>
</html>

```

(Q9)

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Factorial Number</title>
</head>
<body>
  <script>
    function q9() {
      function findFactorial(n) {
        let fact = 1;
        for (let i = 1; i <= n; i++) {
          fact = fact * i;
        }
        return fact;
      }
      let num = Number(prompt("Enter number for factorial"));
      alert("Factorial is: " + findFactorial(num));
    }
    q9();
  </script>
</body>
</html>

```

(Q10)

```

<!DOCTYPE html>
<html lang="en">
<head><meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>forEachArray</title>
</head><body>
  <script>
    function q10() {
      let arr = [];
      let size = Number(prompt("HEnter the number of Elements"));
      for (let i = 0; i < size; i++) {
        let val = prompt("Enter value for index " + i);
        arr.push(val);
      }
      document.write("<b>Array Items:</b><br>");
      arr.forEach(function(item) {
        document.write(item + "<br>");
      });
    }
    q10();
  </script>
</body>
</html>

```

(Q11)

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Pallindrome</title>
</head>
<body>
  <script>
    function q11() {
      let str = prompt("Enter a string");
      let len = str.length;
      let check = "Palindrome";

      for (let i = 0; i < len / 2; i++) {
        if (str[i] !== str[len - 1 - i]) {
          check = "Not Palindrome";
        }
      }
      document.write(str + " is " + check);
    }
    q11();
  </script>
</body>
</html>

```

(Q12)

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>JS Methods</title>
</head>
<body>
  <script>
    function q12() {
      let text = "Hello JavaScript Welcome to SoA University";
      document.write("Original: " + text + "<br>");
      document.write("Index of 'Java': " + text.indexOf("Java") + "<br>");
      document.write("Last Index of 'a': " + text.lastIndexOf("a") + "<br>");
      document.write("Slice(0,5): " + text.slice(0, 5) + "<br>");
      document.write("Replace: " + text.replace("Hello", "Hi") + "<br>");
      document.write("ReplaceAll: " + text.replaceAll("a", "X") + "<br>");
    }
    q12();
  </script>
</body>
</html>
```