SYSTEM AND METHOD FOR SECURE ASYNCHRONOUS DATA COMMUNICATION

Reinaldo Javier Aguiar Marcano

March 21, 2026

Title: SYSTEM AND METHOD FOR SECURE ASYNCHRONOUS DATA COMMUNICATION

Inventor: Reinaldo Javier Aguiar Marcano, a citizen of the United States, residing at 2302 Britton Ridge Drive, Katy, TX 77494.

Abstract

A system and method for a secure data communication protocol that defeats timing-based correlation and Man-in-the-Middle (MITM) attacks by introducing temporal decoupling between a client's request, the acknowledgment of the request, and the retrieval of the final response. Unlike conventional synchronous protocols where a request is immediately followed by a response, the present invention allows a client to submit a request in a first session, receive a unique identifier, and then retrieve the corresponding data payload in a separate, later session at an unpredictable time. The protocol also makes notoriously persistent tracking headers, such as the User-Agent and Cookie headers, optional, thereby frustrating cryptographic analysis that relies on these stable anchors. The method is designed to be layered over existing transport protocols but to fundamentally alter the communication pattern to enhance user security and privacy.

Background of the Invention

The foundational protocols of the modern internet, such as TCP/IP and HTTP, were designed for reliability and efficiency in a relatively trusted environment. A key characteristic of these protocols is their synchronous nature: a client sends a request, and the server sends a response within the same communication session. This predictability is a significant vulnerability. An adversary capable of monitoring a user's network traffic can easily correlate requests and responses in time and space. This is particularly dangerous in radio-frequency (RF) based communications like cellular or satellite internet, where an adversary can position a MITM attacker to intercept the response based on the timing of the request.

Furthermore, conventional protocols leak significant amounts of metadata that serve as stable cryptographic anchors for attackers. The HTTP 'User-Agent' string, for example, is a long, static identifier that effectively partitions global internet traffic by browser and version, simplifying large-scale analysis. Similarly, HTTP 'Cookies' are persistent identifiers used for tracking that also provide a stable, per-user anchor for long-term cryptographic attacks. These vulnerabilities are exploited by sophisticated state-level actors to compromise user security. There is a need for a communication protocol that breaks these fundamental assumptions of synchronicity and stable metadata.

Summary of the Invention

The present invention provides a system and method for asynchronous data communication that enhances security by introducing temporal ambiguity and reducing metadata leakage. The protocol severs the predictable link between a data request and its corresponding response.

In the proposed system, a client initiates a transaction by sending a request to a compliant server. The server, instead of immediately processing the request and returning the data, registers the request and returns only a small, unique transaction identifier. This concludes the first communication session. At a later, arbitrary time, the client can initiate a second, completely separate communication session to poll the server using the transaction identifier. If the data is ready, the server transmits it and the session is terminated. A third session can be used to pick up an acknowledgement. This asynchronous, multi-session approach makes it extraordinarily difficult for a MITM attacker to predict when or from where a response will be retrieved, defeating timing-based interception.

A further aspect of the invention is the deliberate rejection of mandatory, stable client-side headers. All headers, including the ‘User-Agent‘ and ‘Cookie‘ headers, are treated as optional within the protocol. This starves adversaries of the stable cryptographic anchors needed to efficiently mount certain types of cryptanalytic and traffic analysis attacks. The invention can be implemented as a new application-layer protocol, inspired by HTTP but designed with these core security principles. The protocol may optionally include status codes, such as ‘1000‘ or ‘2222‘, for compatibility or humorous effect.

Statement of License Grant to the United States Government

The inventor, Reinaldo Javier Aguiar Marcano, hereby grants to the United States Federal Government and its military and defense agencies a perpetual, royalty-free, non-exclusive license to practice and use the invention described herein for any and all governmental, defense, and non-commercial purposes. This license explicitly excludes any and all state and local governments.

Brief Description of the Drawings

FIG. 1 is a diagram contrasting a conventional, synchronous communication protocol with the asynchronous protocol of the present invention, highlighting the temporal decoupling of request and response.
FIG. 2 is a flowchart illustrating the operational sequence of the asynchronous communication method from the client's perspective.

Detailed Description of the Invention

Referring to **FIG. 1**, the vulnerability of conventional synchronous protocols (100) is shown. A client (101) sends a request (102) over a network, and an adversary (103) observes this request. Due to the synchronous nature, the adversary can predict the timing and path of the subsequent response (104), allowing for a Man-in-the-Middle (MITM) attack. In contrast, the asynchronous protocol of the present invention (110) breaks this predictability. The client (111) sends a request (112) in a first session. The server returns only a request ID (113). At a much later, unpredictable time, the client initiates a new session to retrieve the

response (114). The adversary (115) cannot correlate the request with the response in time, frustrating the MITM attack.

The operational flow for a client is detailed in **FIG. 2**. The process begins with the client composing a data request (201). The client then establishes a first connection to the server and transmits the request (202). The server validates the request and, if accepted, returns a unique Request ID (203). The first connection is then closed (204). The client stores this Request ID. After an arbitrary and variable delay (205), the client initiates a new, second connection to the server to poll for the response, using the stored Request ID (206). The server checks the status. If the response is not ready, it returns a "pending" status (207), and the client repeats the polling process after another delay. If the response is ready, the server transmits the data payload (208), which the client receives. The connection is closed, and the transaction is complete (209). This multi-stage, temporally decoupled process provides the core security benefit of the invention.

Claims

What is claimed is:

1. A method for asynchronous data communication, comprising the steps of:
    - transmitting, from a client device to a server device in a first communication session, a request for a data resource;
    - receiving, from the server device in said first communication session, a unique identifier corresponding to the request, whereupon the first communication session is terminated; and
    - transmitting, from the client device to the server device in a second communication session initiated at an arbitrary later time, the unique identifier to request the data resource;
    - receiving the data resource from the server device in the second communication session.
2. The method of claim 1, wherein the communication protocol between the client and server does not require the client to transmit a User-Agent header.
3. The method of claim 1, wherein the communication protocol between the client and server does not require the client to transmit a Cookie header.

4. The method of claim 1, wherein the time delay between the termination of the first session and the initiation of the second session is varied to prevent correlation.

5. A system for secure data communication, comprising:

    - a client device configured to:
        - transmit a request in a first session and receive a unique identifier;
        - and transmit the unique identifier in a second, temporally decoupled session to retrieve a data payload;
    - a server device configured to:
        - receive the request in the first session and respond with the unique identifier;
        - and, upon receiving the unique identifier in the second session, return the corresponding data payload.

6. The system of claim 5, wherein the server is configured to process requests that omit User-Agent and Cookie headers.

7. The system of claim 5, wherein the server is configured to return a status code of 1000 or 2222.

DRAWINGS




Figure 1: Diagram contrasting synchronous and asynchronous communication protocols.




Figure 2: Flowchart of the asynchronous communication method.