



2017 中国互联网安全大会  
China Internet Security Conference

# **Towards Efficient Heap Overflow Discovery**

**Chao Zhang** Assoc. Prof.  
Tsinghua University



中国互联网安全大会



360互联网安全中心

# About Me

## Experience

- Tsinghua University, Assoc. Prof., 2016/11-present
- UC Berkeley, Postdoc, 2013/9-2016/9, Advisor: Dawn Song
- Peking University, Ph.D., 2008/9-2013/7, Advisors: 邹维, 韦韬
- Peking University, Undergraduate, 2004/9-2008/7, Math

## Honors

- Young Elite Scientists Sponsorship Program by CAST
- DARPA CGC, Captain of Team CodeJitsu
  - Defense #1 in 2015 CQE, Attack #2 in 2016 CFE
- Microsoft BlueHat Prize Contest 2012
  - Special Recognition Award
- DEFCON CTF 2015 (#5), 2016 (#2), 2017 (#5)
- GeekPwn 2017/5/12

# Agenda



中国互联网安全大会



360互联网安全中心

- Basics of Fuzzing
- Studies on Fuzzing
- HOTracer: Offline Dynamic Solution
- Conclusion



# Vulnerability Detection Solutions



中国互联网安全大会



360互联网安全中心

- Static Analysis
- Taint Analysis
- Fuzzing
  - mutation, generation
  - blackbox, greybox, whitebox
  - smart, dumb
- Symbolic Execution
- Dynamic Detection
  - online
  - offline


# Basics of Fuzzing




中国互联网安全大会



360互联网安全中心



# Basics of Fuzzing: AFL



- Secret ingredient of AFL:

- Throughput
- Code Coverage
- Exception Capturing



# Key Questions of Fuzzing



中国互联网安全大会



360互联网安全中心

- How to get initial inputs?
- How to select seed from the pool?
- How to generate new testcases?
  - How to mutate seeds? Location and value.
- How to efficiently test target application?
- How to track the testing?
  - Code coverage, Security violation, ...?
- How do we update the seed pool?
  - identify good testcases, shrink seed pool...

# How to get initial inputs?

- Why is it important?
  - cpu time
  - complex data structure
  - hard-to-reach code
  - reusable between fuzzings
- Solutions
  - standard benchmarks
  - crawling from the Internet
- Extra step
  - distill the corpus



# How to select seed from the pool?

- Why is it important?
  - prioritize seeds which are more helpful,
    - e.g., cover more code, more likely to trigger vulnerabilities
  - save computing resources
  - faster to identify hidden vulnerabilities
- Solutions
  - AFLFast (CCS' 16): seeds being picked fewer or exercising less-frequent paths
  - Vuzzer (NDSS' 17): seeds exercising deeper paths
  - QTEP (FSE' 17): seeds covering more faulty code
  - AFLgo (CCS' 17): seeds closer to target vulnerable paths
  - SlowFuzz (CCS' 17): seeds consuming more resources

# How to generate new testcases?

- Why is it important?
  - explore more code in a shorter time
  - target potential vulnerable locations
- Solutions
  - Vuzzer (NDSS' 17):
    - where to mutate: bytes related to branches
    - what value to use: tokens used in the code.
  - Skyfire (Oakland' 17):
    - learn Probabilistic Context-Sensitive Grammar from crawled inputs
  - Learn&Fuzz (Microsoft):
    - learn RNN from valid inputs

# How to track the testing?



中国互联网安全大会



360互联网安全中心

- Why is it important?
  - Code coverage: leading to thorough program states exploring
  - Security violations: capturing bugs that have no explicit results
- Solutions
  - Code coverage:
    - AFL bitmap, SanitizerCoverage
  - Security violations:
    - AddressSanitizer
    - UBSan
    - MemorySanitizer
    - ThreadSanitizer
    - DataFlowsanitizer
    - LeakSanitizer
    - ...



# Agenda



中国互联网安全大会




360互联网安全中心


- Basics of Fuzzing
- Studies on Fuzzing
- HOTracer: Offline Dynamic Solution
- Conclusion

# Motivation: Heap Overflow

- Stack overflow exploits are rare
  - Defenses: ASLR, shadow stack, Stackguard, StackArmor, etc.
  - Compiler efforts
- Heap overflows become dominant
  - exploit techniques become reliable: heap spray, heap fengshui, etc.




Microsoft RCE exploitation trend (2008-2014)



Heap overflow vulnerabilities in NVD (2014-2017)

# Why Fuzzing Fails?

- Value sensitive, not only path sensitive






# Root cause : Spatial inconsistency

- Example of a heap overflow
  - Heap allocation operations  
(obj, size<sub>allocation</sub>)
  - Heap access operations  
(ptr, offset<sub>ptr</sub>, size<sub>access</sub>)
- Heap overflow happens
  - When input size = SIZE

```
1 #define SIZE (1024-4)
2 struct OBJ{
3     char name[SIZE];
4     void set_name(char* src, size_t size){
5         if(size > SIZE) exit(-2);
6         memcpy(name, src, size);
7         // off-by-one, when size == SIZE
8         name[size]=0;
9     }
10 };
11 int main(){
12     OBJ* p1 = new OBJ();
13     OBJ* p2 = new OBJ();
14     // tainted: size and input
15     input = get_input(&size);
16     // Vul #1: off-by-one if size=SIZE
17     p1->set_name(input, size);
18     // coalesce p1 and p2, causing p1 free.
19     free(p2);
20     // Vul #2: use after free
21     printf("p1 name: %s\n", p1->name);
22     return 0;
23 }
```

Heap overflow condition:  $\text{Range}_{\text{access}} > \text{Range}_{\text{obj}}$

# Root Cause: Controllability (Taint)




An Example Call Graph

	Alloc controllable	Access controllable	How to overflow
S1	N	N	inherent errors (N/A)
S2	N	Y	Access out of bound
S3	Y	N	Allocate small buffer
S4	Y (bytes_1)	Y (bytes_2)	Change the value of two sides independently
S5	Y (bytes_0)	Y (bytes_0)	Check IO2BO (e.g., (x+2, x+1))

# Our solution

- Get execution traces
- Identify heap operations
  - group into pairs <alloc, access>
- Track spatial attributes
- Track taint attributes
- Build vulnerability conditions
- Generate PoC inputs



Xiangkun Jia, **Chao Zhang**, Purui Su, Yi Yang, Huafeng Huang, Dengguo Feng,  
Towards Efficient Heap Overflow Discovery, USENIX Security 2017



# Implementation Choices

- Get execution traces
- Identify heap operations
  - group into pairs <alloc, access>
- Track spatial attributes
- Track taint attributes
- Build vulnerability conditions
- Generate PoC inputs
- representative inputs
- custom heap managers
  - lineage analysis
- fine-grained taint tracking
- symbolic execution
- spatial inconsistency
- constraint optimization & solving

# Bug Finding Results



中国互联网安全大会



360互联网安全中心

ID (count)	Application	version	input	bug status
new (1)	Feiq	3.0.0.2	tcp	reported
new (1)	WMPlayer	12.0.7601	mp4	reported
new (3)	VLC	2.2.1	mp4	fixed
new (1)	VLC	2.2.4	mp4	reported
new (2)	iTunes	12.4.3.1	mp4	reviewing
new (1)	ffmpeg	c0cb53c	mp4	CVE
new (6)	QQPlayer	3.9(936)	mp4	rewarded
new (1)	QQMusic	11.5	m4a	rewarded
new (1)	BaiduPlayer	5.2.1.3	mp4	reviewing
new (2)	RealPlayer	16.0.6.2	mp4	CVE
new (1)	MPlayer	r37802	mp4	reported
new (3)	KMPlayer	3.9.1.138	mp4	fixed
new (4)	KMPlayer	4.1.1.5	mp4	reported
new (7)	Potplayer	1.6.60136	mp4	fixed
new (2)	Potplayer	1.6.62949	mp4	reported
new (5)	Splayer	3.7	mp4	reported
new (2)	MS Word	2007,10,16	rtf	reviewing
new (1)	WPS Word	10.1.0.5803	doc	reported
new (2)	OpenOffice	4.1.2	doc	reviewing
new (1)	IrfanView	4.41	m3u	fixed

47 vulnerabilities in 17 applications

# Case Studies

- Tainted access offset
  - offset is influenced by input

```
Dst = Object + tainted_offset  
memcpy(Dst, Src)
```

- Implicit taint:
  - Allocation size is based on the input length
  - Access size implicitly depends on input

```
while (input != '\0' ) length++;  
buffer = malloc(length);
```

```
while(input == val){  
    memcpy();  
}
```

- Multiple vulnerabilities in one trace
  - Two extra vulnerable points in the same trace as CVE-2014-1761
- Long testing time
  - A VLC vulnerability occurred only after several minutes



# Conclusions



- Fuzzing is still the most popular vulnerability discovery solution.
- Fuzzers could be improved in several ways.
- We point out that fuzzers may miss heap overflow vulnerabilities (and other type of vulnerabilities) due to its value insensitivity.
- We propose a new solution HOTracer, able to identify potential heap overflows in a given trace.
- We found 47 vulnerabilities in 17 real world applications, including 2 vulnerable points in Microsoft Word.

# THANKS



中国互联网安全大会



360互联网安全中心