

Shiram System SMS API Documentation (version 1.70)

According to BTRC Regulation, All messages must be in Bangla.

Url: https://smsapi.shiramssystem.com/user_api/

Request Method [POST]

The server only handles “POST” (HTTP FORM URL) request and nothing more. So to send request you must send a “POST” request with its associated parameter.

Parameters

The api contains only these parameters given below.

- email (string)
- password (string)
- method (string: available values are get_balance, send_sms, send_multi_sms, account_recharge and report)
- mask (string: Mask name, dedicated number or ‘Non-Masking’ for without masking)
- mobile (array: starts with 88, ie: 8801711000000, 8801811000000 etc)
- message (string: message body plain English or bangla)
- ids (array: sent SMSs’ ids)
- data (string in format of JSON text)
- amount (decimal number)
- recharge_email (string)

To get balance you need only 3parameter: email, password & method (get_balance)

To send sms you need 6 parameters: email, password, method (send_sms), mask, mobile & message.

Return:

It always returns JSON encoded data from the server. The returned json parameter has several keys & values in it. Details are given below with example with output value.

Restrictions:

- Maximum 100 mobile numbers can be added in a request.
- Maximum 100 ids can be added in a request to retrieve report.
- Only POST is allowed.
- Return format will always be in JSON format.
- Mobile number is 13 Digits meaning you've to add 88 at the beginning of every number.
- Minimum recharge amount is 1,000 tk and maximum recharge amount is 20,000tk

Error Code List:

Error Code	Message
0	Success
11	Only POST is allowed.
12	All parameter not given.
13	Invalid method parameter given.
14	Maximum number of data exceeded for one request.
15	Invalid Mask name given.
16	Invalid mobile number given. Please check. Only Mobile number allowed with 88 and 13 digits.
17	Message length exceeds the maximum allowed length.
21	No user found with that email address.
22	Invalid password given.
23	Not sufficient balance is available to send sms. Please recharge.
24	User status is not active.
25	Not sufficient balance is available to send sms. Please contact admin.
26	System error while calculating cost. Please contact admin.
31	Invalid parameter exists in the request.
32	Parameter data type didn't match.
33	Invalid JSON data format in data parameter.
41	The given credential is not a parent company credential.
42	Invalid recharge amount given. The given amount is not a decimal/float number.
43	Minimum recharge amount is 1,000 and maximum is 20,000.
44	No account found with given recharge email address.
45	Given recharge account is not active.
46	Given recharge account is not a rechargeable company account through api.
47	Given recharge email account does not belong to a company under your company.
100	Database error. Please try later.
101	No data found for rate.

102	System error. Contact admin.
103	Data inserted but cannot provide associated ids. Please check portal for this campaign.
111	SMS must be unicode (Bangla).

Get Balance:

Url: https://smsapi.shiramsystem.com/user_api/

Method: POST

Fields:

email : something@something.com (your email address used for account)

password: XXXXXXXXXXXX (your password)

method: get_balance

Return Parameter:

status: (bool) true/False

error_code: (int) any error code

message: (string)message associated with code

balance: (float) balance amount (if all ok)

Return Value: JSON response

{“status”:true,“error_code”:0, “message”:”Success”,“balance”:14.12} **if all is ok**

or

{“status”:false,“error_code”:13,“message”: “Invalid method parameter given “} **if error occurred.**

Example:

```
<?php
$url = "https://smsapi.shiramsystem.com/user_api/";
$post = array(
    "email" => "example@example.com",
    "password" => "XXXXXX",
    "method" => "get_balance",
);
$ch = curl_init($url);
curl_setopt($ch, CURLOPT_FOLLOWLOCATION, 1);
curl_setopt($ch, CURLOPT_POST, 1);
curl_setopt($ch, CURLOPT_POSTFIELDS, http_build_query($post));
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_FAILONERROR, true);
curl_setopt($ch, CURLOPT_SSL_VERIFYPEER, false);
$result = curl_exec($ch);

echo $result;

?>
```

This code will give you this output given below:

```
{"status":true,"error_code":0,"balance":916.06,"message":"Success"}
```

Send SMS:

Url: https://smsapi.shiramsystem.com/user_api/

Method: POST

Fields:

email : something@something.com (your email address used for account)

password: XXXXXXXXXXX (your password)

method: send_sms

mask: (Mask name, dedicated number or 'Non-Masking' for without masking)

mobile: array of mobile numbers with leading 88 with it(ie: 8801711000000, 8801811000000 etc.) **(Maximum 100 number at a time).**

message: message text (Plain English or Bangla) **(Maximum 5 sms length)**

Return Parameter:

status: (bool) true/false

error_code: (int) any error code

message: (string) message associated with the code

ids: (array) array of mobile number and its server id

cost: (float) Cost of sms

sms_count: (int) number of sms has sent

Return Value: JSON response

`{"status":true,"error_code":0,"ids":{"8801914201317":"6105"},"cost":0.3,"sms_count":1,"message":"Success"}` **if all is ok**

or

`{"status":false,"error_code":13,"message": "Invalid method parameter given "}` **if error occurred.**

Example:

```
<?php
$url = "https://smsapi.shiramsystem.com/user_api/";
$post = array(
    "email" => "razin223@gmail.com",
    "password" => "XXXXXXX",
    "method" => "send_sms",
    "mobile" => array("8801914201317"),
    "mask" => "Non-Masking",
    "message"=>"Test sms",
);
$ch = curl_init($url);
curl_setopt($ch, CURLOPT_FOLLOWLOCATION, 1);
curl_setopt($ch, CURLOPT_POST, 1);
curl_setopt($ch, CURLOPT_POSTFIELDS, http_build_query($post));
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_FAILONERROR, true);
curl_setopt($ch, CURLOPT_SSL_VERIFYPEER, false);
$result = curl_exec($ch);
echo $result;
?>
```

This code will give you this output given below:

```
{"status":true,"error_code":0,"ids":{"8801914201317":"6106"},"cost":0.3,"sms_count":1,
"message":"Success"}
```

Send Multiple SMS To Multiple Numbers:

Url: https://smsapi.shiramssystem.com/user_api/

Method: POST

Fields:

email : something@something.com (your email address used for account)

password: XXXXXXXXXXX (your password)

method: send_multi_sms

mask: (Mask name, dedicated number or 'Non-Masking' for without masking)

data: JSON encoded string data with mobile and sms in it. Data format is like this

```
[{"mobile":"8801914201317","sms":"Test sms  
1"}, {"mobile":"8801711409023","sms":"Test sms 2"}]
```

Here “**mobile**” field is 13 digits of mobile number including **88 at front**. “**sms**” field is string of **max length of 5 character length** SMS. **The maximum SMS at a time can be send via “data” parameter is 100.**

Return Parameter:

status: (bool) true/false

error_code: (int) any error code

message: (string) message associated with the code

ids: (array) array of mobile number and its server id

cost: (float) Cost of sms

sms_count: (int) number of sms has sent

Return Value: JSON response

```
{"status":true,"error_code":0,"ids":{"8801914201317":"6105"},"cost":0.3,"sms_count":1,  
"message":"Success"} if all is ok or
```

{“status”:false,”error_code”:13,”message”: “Invalid method parameter given “} **if error occurred.**

Example:

```
<?php
```

```
$Data = array("email" => "example@example.com", "password" => "XXXXXXXX",  
"method" => "send_multi_sms", "mask" => "Non-Masking");
```

```
$Message[] = array("mobile" => "8801914201317", "sms" => "Test sms 1");
```

```
$Message[] = array("mobile" => "8801711409023", "sms" => "Test sms 2");
```

```
$Data['data'] = json_encode($Message);
```

```
$url = "https://smsapi.shiramssystem.com/user_api/";
```

```
$ch = curl_init($url);
```

```
curl_setopt($ch, CURLOPT_FOLLOWLOCATION, 1);
```

```
curl_setopt($ch, CURLOPT_POST, 1);
```

```
curl_setopt($ch, CURLOPT_POSTFIELDS, http_build_query($Data));
```

```
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
```

```
curl_setopt($ch, CURLOPT_FAILONERROR, true);
```

```
curl_setopt($ch, CURLOPT_SSL_VERIFYPEER, false);
```

```
$result = curl_exec($ch);
```

```
echo $result;
```

```
?>
```

This code will give you this output given below:

```
{"status":true,"error_code":0,"ids":{"8801914201317":"6106"},"cost":0.3,"sms_count":1,  
"message":"Success"}
```


SMS Report

Url: https://smsapi.shiramsystem.com/user_api/

Method: POST

Fields:

email : something@something.com (your email address used for account)

password: XXXXXXXXXXX (your password)

method: report

ids: array of Ids of the server provided when sms sent vai api.

Return Parameter:

status: (bool) true/false

error_code: (int) any error code

message: (string) message associated with the code

no_of_result_found: (int) No of result found with that request.

details: (array) Contains the details of the ids given on the request.

id: message id

mobile: mobile no

status: message send status (Send/Failed, Queued etc)

time: Time when execution worked.

Return Value: JSON response

```
{"status":true,"error_code":0,"no_of_result_found":1,"details":[{"id":"6105","mobile":"8801914201317","status":"Sent","time":"2018-03-26 03:58:52"}],"message":"Success"}
```

if all is ok or

```
{"status":false,"error_code":13,"message": "Invalid method parameter given "} if error occurred.
```

Example:

```
<?php
$url = "https://smsapi.shiramsystem.com/user_api/";
$post = array(
    "email" => "razin223@gmail.com",
    "password" => "XXXXXXX",
    "method" => "report",
    "ids" => array("5412"),
);
$ch = curl_init($url);
curl_setopt($ch, CURLOPT_FOLLOWLOCATION, 1);
curl_setopt($ch, CURLOPT_POST, 1);
curl_setopt($ch, CURLOPT_POSTFIELDS, http_build_query($post));
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);
curl_setopt($ch, CURLOPT_FAILONERROR, true);
curl_setopt($ch, CURLOPT_SSL_VERIFYPEER, false);
$result = curl_exec($ch);
echo $result;
?>
```

This code will give you this output given below:

```
{
  "status": true,
  "error_code": 0,
  "no_of_result_found": 1,
  "details": [
    {
      "id": "6105",
      "mobile": "8801914201317",
      "status": "Sent",
      "time": "2018-03-26 03:58:52"
    }
  ],
  "message": "Success"
}
```

Other Language Example

Java

Dependencies:

'org.apache.httpcomponents:httpclient:4.5.13'

'com.google.code.gson:gson:2.8.6'

```
import java.util.ArrayList;
import java.util.List;
import org.apache.http.NameValuePair;
import org.apache.http.client.methods.HttpPost;
import org.apache.http.impl.client.HttpClients;
import org.apache.http.client.methods.CloseableHttpResponse;
import org.apache.http.impl.client.CloseableHttpClient;
import org.apache.http.util.EntityUtils;
import org.apache.http.client.entity.UrlEncodedFormEntity;
import org.apache.http.message.BasicNameValuePair;
import com.google.gson.Gson;
```

```
public class sendSMS {

    private class MultipleSMSData
    {
        public String mobile;
        public String sms;
        public MultipleSMSData(String mobile, String sms)
        {
            this.mobile = mobile;
            this.sms = sms;
        }
    }

    public String sendMultiSMS()
    {
        String str = "";

        MultipleSMSData[] multipleSMSData = new MultipleSMSData[3];
        multipleSMSData[0] = new MultipleSMSData("8801711409022", "L`vK L`vK L`vK");
        multipleSMSData[1] = new MultipleSMSData("8801613671066", "L`vK L`vK L`vKL`vK L`vK L`vK");
        multipleSMSData[2] = new MultipleSMSData("8801911046898", "L`vK L`");
    }
}
```

```

//System.out.println(new Gson().toJson(multipleSMSData));

try {

    String url = "https://smsapi.shiramsystem.com/user_api/";
    HttpPost post = new HttpPost(url);

    List<NameValuePair> urlParameters = new ArrayList<>();
    urlParameters.add(new BasicNameValuePair("email", "//TODO your registered email at shiram system"));
    urlParameters.add(new BasicNameValuePair("password", "//TODO your api password from shiram
system"));
    urlParameters.add(new BasicNameValuePair("method", "send_multi_sms")); //its hardcoded
    urlParameters.add(new BasicNameValuePair("mask", "your registered masking at shiram system"));
    urlParameters.add(new BasicNameValuePair("data", new Gson().toJson(multipleSMSData)));

    post.setEntity(new UrlEncodedFormEntity(urlParameters,"UTF-8"));
    post.setHeader("Content-type", "application/x-www-form-urlencoded");
    post.setHeader("User-Agent", "Mozilla");
    try ( CloseableHttpClient httpClient = HttpClients.createDefault(); CloseableHttpResponse response =
httpClient.execute(post)) {

        str += EntityUtils.toString(response.getEntity());
    }

} catch (Exception a) {
    str = "F";
    a.printStackTrace();
}

System.out.println(str);
return str;
}

public String sendSMS(java.lang.String mobile, java.lang.String text) {
    String str = "";
    try {

        String url = "https://smsapi.shiramsystem.com/user_api/";
        HttpPost post = new HttpPost(url);

        List<NameValuePair> urlParameters = new ArrayList<>();
        urlParameters.add(new BasicNameValuePair("email", "//TODO your registered email at shiram system"));
        urlParameters.add(new BasicNameValuePair("password", "TODO your api password from shiram
system"));
        urlParameters.add(new BasicNameValuePair("method", "send_sms")); //its hardcoded
        urlParameters.add(new BasicNameValuePair("mask", "your registered masking at shiram system"));
        urlParameters.add(new BasicNameValuePair("mobile[]", mobile));
        urlParameters.add(new BasicNameValuePair("message", text));
    }
}

```

```

        post.setEntity(new UrlEncodedFormEntity(urlParameters,"UTF-8"));
        post.setHeader("Content-type", "application/x-www-form-urlencoded");
        post.setHeader("User-Agent", "Mozilla");
        try ( CloseableHttpClient httpClient = HttpClients.createDefault(); CloseableHttpResponse response =
httpClient.execute(post)) {

            str += EntityUtils.toString(response.getEntity());
        }

    } catch (Exception a) {
        str = "F";
        a.printStackTrace();
    }

    return str;
}
}

```

NodeJS

Dependencies:

Axios (npm install axios)
QS (npm install qs)

Balance

```
const axios = require('axios');
const qs = require('qs');
const data = {
  email: 'abc@xyz.com',
  password: 'xxxxx',
  method: 'get_balance'
};

axios.post('https://smsapi.shiramsystem.com/user_api/', qs.stringify(data))
  .then((res) => {
    console.log(`Status: ${res.status}`);
    console.log('Body: ', res.data);
  }).catch((err) => {
    console.error(err);
  });
```

Send Single Message

```
const axios = require('axios');
const qs = require('qs');
var Mobile = [];
Mobile.push();

const data = {
  email: 'abc@gmail.com',
  password: 'xxxxx',
  method: 'send_sms',
  mobile: ['8801914201317'],
  mask: "Non-Masking",
  message: "মাংস বেচতে গুনতে হবে ১৫ হাজার টাকা",
};

axios.post('https://smsapi.shiramsystem.com/user_api/', qs.stringify(data))
  .then((res) => {
    console.log(`Status: ${res.status}`);
    console.log('Body: ', res.data);
  }).catch((err) => {
    console.error(err);
  });
```

```
});
```

Send Multiple Message to Multiple Number

```
const axios = require('axios');
const qs = require('qs');
var MessageBody = [];
MessageBody.push({mobile:'8801914201317',sms:'মাংস বেচতে গুনতে হবে ১৫ হাজার টাকা'});
MessageBody.push({mobile:'8801711409023',sms:'১৫ হাজার টাকা মাংস বেচতে গুনতে হবে'});

const data = {
  email: 'abc@gmail.com',
  password: 'xxx',
  method:'send_multi_sms',
  mask:"Non-Masking",
  data: JSON.stringify(MessageBody),
};

axios.post('https://smsapi.shiramsystem.com/user_api/', qs.stringify(data))
  .then((res) => {
    console.log(`Status: ${res.status}`);
    console.log('Body: ', res.data);
  }).catch((err) => {
    console.error(err);
  });
```

C#

Dependencies:

You'll be need to use **System.Net** for using this code. So import that library before use this code. for supporting the JSON download the u need to add a dll file named Newtonsoft.Json.dll. You can download it from <https://www.newtonsoft.com/json>

Send Single SMS to Multiple/Single Number

```
string mail = "email_address";
string pass = "Password";
string method_ = "send_sms";
string mask_ = "SEL SCHOOL";
string mobileno = "8801711409022";
string message = "test message";

string URI = "https://smsapi.shiramsystem.com/user\_api/";

string myParameters = "email=" + mail + "&password=" + pass + "&method=" + method_ + "&mobile[]" + mobileno + "&mask=" + mask_ + "&message=" + message;

using (WebClient wc = new WebClient())
{
    wc.Headers[HttpRequestHeader.ContentType] = "application/x-www-form-urlencoded";
    string HtmlResult = wc.UploadString(URI, myParameters);
    MessageBox.Show(HtmlResult);
}
```

Send Multiple SMS to multiple Number

```
using System;

using System.Net;

using Newtonsoft.Json;

private class MultipleSMSData
{
    public string mobile;
    public string sms;
    public MultipleSMSData(string mobile, string sms)
    {
        this.mobile = mobile;
    }
}
```



```

        this.sms = sms;
    }
}

private void method_name()
{

    string mail = "useremail@gmail.com";
    string pass = "123456";
    string method_ = "send_multi_sms";
    string mask_ = "SEL SCHOOL ";

    MultipleSMSData[] multipleSMSData = new MultipleSMSData[3];
    multipleSMSData[0] = new MultipleSMSData("8801711409022", "হাবিজাবি");
    multipleSMSData[1] = new MultipleSMSData("8801613671066", "খ্যাক খ্যাক");
    multipleSMSData[2] = new MultipleSMSData("8801911046898", "hi 6898");

    string URI = "https://smsapi.shiramsystem.com/user_api/";

    string myParameters = "email=" + mail + "&password=" + pass + "&method=" + method_
        + "&mask=" + mask_ + "&data=" +
WebUtility.UrlEncode(JsonConvert.SerializeObject(multipleSMSData));
    using (WebClient wc = new WebClient())
    {
        wc.Headers[HttpRequestHeader.ContentType] = "application/x-www-form-urlencoded";
        string HtmlResult = wc.UploadString(URI, myParameters);
        MessageBox.Show(HtmlResult);
    }
}
}

```