

Transition based dependency parsing

Parsing
ISCL-BA-06

Çağrı Çöltekin
ccoltekin@sfs.uni-tuebingen.de

University of Tübingen
Seminar für Sprachwissenschaft

Winter Semester 2020/21

Dependency parsing

an overview

- Dependency parsing has many similarities with context-free parsing (e.g., the result is a tree)
- They also have some different properties (e.g., number of edges and depth of trees are limited)
- The process involves discovering the relations between words in a sentence
 - Determine the head of each word
 - Determine the relation type
- Dependency parsing can be
 - grammar-driven (hand crafted rules or constraints)
 - data-driven (rules/model is learned from a treebank)

Grammar-driven dependency parsing

- Grammar-driven dependency parsers typically based on
 - lexicalized CF parsing
 - constraint satisfaction problem
 - start from fully connected graph, eliminate trees that do not satisfy the constraints
 - exact solution is intractable, often employ heuristics, approximate methods
 - sometimes ‘soft’, or weighted, constraints are used
 - Practical implementations exist
- Our focus will be on data-driven methods

Dependency parsing

common methods for data-driven parsers

- Almost any modern/practical dependency parser is statistical
- There are two main approaches:

Graph-based search for the best tree structure, for example

- find minimum spanning tree (MST)
- adaptations of CF chart parser (e.g., CKY)

(in general, computationally more expensive)

Transition-based similar to shift-reduce (LR(k)) parsing

- Single pass over the sentence, determine an operation (shift or reduce) at each step
- Linear time complexity
- We need an approximate method to determine the best operation

Shift-Reduce parsing

a refresher through an example

Grammar

$$S \rightarrow P \mid S + P \mid S - P$$

$$P \rightarrow \text{Num} \mid P \times \text{Num} \mid P / \text{Num}$$

Parser states/actions

Stack	Input buffer	Action
	2 + 3 × 4	shift
2	+ 3 × 4	reduce ($P \rightarrow \text{Num}$)
P	+ 3 × 4	reduce ($S \rightarrow P$)
S	+ 3 × 4	shift
S +	3 × 4	shift
S + 3	× 4	reduce ($P \rightarrow \text{Num}$)
S + P	× 4	shift
S + P ×	4	shift
S + P × 4		reduce ($P \rightarrow P \times \text{Num}$)
S + P		reduce ($S \rightarrow S + P$)
S		accept

Transition-based parsing


differences from shift-reduce parsing

- The shift-reduce (LR) parsers for formal languages are deterministic, actions are determined by a table lookup
- Natural language sentences are ambiguous, a dependency parser's actions cannot be made deterministic
- Operations are (somewhat) different: instead of reduce (using phrase-structure rules) we use *arc* operations connecting two words with a labeled arc
- More operations may be defined (e.g., to deal with non-projectivity)

Transition based parsing

- Use a *stack* and a *buffer* of unprocessed words
- Parsing as predicting a sequence of transitions like
 - LEFT-ARC: mark current word as the head of the word on top of the stack
 - RIGHT-ARC: mark current word as a dependent of the word on top of the stack
 - SHIFT: push the current word on to the stack
- Algorithm terminates when all words in the input are processed
- The transitions are not naturally deterministic, best transition is predicted using a machine learning method

A typical transition system



LEFT-ARC_r: $(\sigma \mid w_i, w_j \mid \beta, A) \Rightarrow (\sigma \quad, w_j \mid \beta, A \cup \{(w_j, r, w_i)\})$

- pop w_i ,
- add arc (w_j, r, w_i) to A (keep w_j in the buffer)


RIGHT-ARC_r: $(\sigma \mid w_i, w_j \mid \beta, A) \Rightarrow (\sigma \quad, w_i \mid \beta, A \cup \{(w_i, r, w_j)\})$

- pop w_i ,
- add arc (w_i, r, w_j) to A ,
- move w_i to the buffer


SHIFT: $(\sigma \quad, w_j \mid \beta, A) \Rightarrow (\sigma \mid w_j, \quad \beta, A)$

- push w_j to the stack
- remove it from the buffer


Transition based parsing: example




Transition based parsing: example



Transition based parsing: example




Transition based parsing: example




Note: We need SHIFT for NP attachment.


Transition based parsing: example




Transition based parsing: example




Transition based parsing: example




Transition based parsing: example




Transition based parsing: example



Transition based parsing: example



Transition based parsing: example



Making transition decisions


- In LR(k) parsing, the actions are deterministic: there is only one action to take on every parser state
- In transition-based dependency parsing, we have to choose the best among multiple actions
- The typical method is to train a (discriminative) classifier on features extracted from gold-standard *transition sequences*
- Almost any machine learning (classification) method is applicable

Classification

- Classification refers to *supervised* machine learning methods that predict categorical variables (e.g., POS tags or parser actions)
- The predictions are based on statistics extracted from a *training set*
- There are a large number of classification methods, just a few examples:
 - Logistic regression
 - Decision trees
 - Support vector machines
 - Memory-based learning
 - (Deep) neural networks

Supervised learning


with a picture



Types of supervised learning


- If we want to predict a numeric value, the problem is called *regression*
 - Age of the author
 - Frequency of a word
 - Reaction time to a stimuli
- If we want to predict a label, or category, the problem is called *classification*
 - Part of Speech of a word
 - Whether document is spam or not
 - The translation of a word
 - The action to take during transition-based parsing

Supervised learning: regression




- We want to predict y from x

Supervised learning: regression




- We want to predict y from x
- Our model is the linear equation with least error

Supervised learning: regression




- We want to predict y from x
- Our model is the linear equation with least error
- The idea is to reduce the error on the training set

Supervised learning: classification




- We want to predict the class (+, or -) from the features (x_1 and x_2)

Supervised learning: classification




- We want to predict the class (+, or -) from the features (x_1 and x_2)
- A possible solution: find a function that separates the classes

Supervised learning: classification



- We want to predict the class (+, or -) from the features (x_1 and x_2)
- A possible solution: find a function that separates the classes
- Another solution: predict the probabilities (*logistic regression*)



A note on generalization

- An important concern in machine learning is to learn to *generalize*
- A common issue with (complex) ML methods is *overfitting* – the system may learn ‘memorize’ the training data, rather than learning generalizations
- There are methods to prevent overfitting, e.g., *regularization*
- To make sure that there is no overfitting, you need to test your system on a separate data set

A note on generalization

- An important concern in machine learning is to learn to *generalize*
- A common issue with (complex) ML methods is *overfitting* – the system may learn ‘memorize’ the training data, rather than learning generalizations
- There are methods to prevent overfitting, e.g., *regularization*
- To make sure that there is no overfitting, you need to test your system on a separate data set

This is a very superficial introduction. You need to know more about the methods you are using so that you get the best out of these methods.

Features for transition-based parsing

- The features come from the parser configurations, for example
 - The word at the top of the stack, (peeking towards the bottom of the stack is also fine)
 - The first/second word on the buffer
 - Right/left dependents of the word on top of the stack/buffer
- For each possible ‘address’, we can make use of features like
 - Word form, lemma, POS tag, morphological features, word embeddings
 - Dependency relations – (w_i, r, w_j) triples
- Note that some ‘address’–‘feature’ combinations may not be defined

Features for transition-based parsing

examples

- In transition-based parsing, transition decisions come from a classifier
- At each step during parsing, we have features like

– <code>form[Stack]</code> = saw	– <code>form[Buff]</code> = her
– <code>lemma[Stack]</code> = see	– <code>lemma[Buff]</code> = she
– <code>POS[Stack]</code> = VERB	– <code>POS[Buf]</code> = PRON

- We need to make a transition decision such as

– SHIFT	– RIGHT-ARC(OBL)
– RIGHT-ARC(OBJ)	– LEFT-ARC(ACL)

- We can use any multi-class classifier, examples in the literature include
 - SVMs
 - Neural networks
 - Decision Trees
 - ...

The training data

- We want features like,
 - lemma[Stack] = duck
 - POS[Stack] = NOUN
 - ...
- But treebank gives us:

1	Read	read	VERB	VB	Mood=Imp VerbForm=Fin	0	root
2	on	on	ADV	RB	-	1	advmod
3	to	to	PART	TO	-	4	mark
4	learn	learn	VERB	VB	VerbForm=Inf	1	xcomp
5	the	the	DET	DT	Definite=Def	6	det
6	facts	fact	NOUN	NNS	Number=Plur	4	obj
7	.	.	PUNCT	.	-	1	punct

- The treebank has the outcome of the parser, but none of the features we expect



The training data

- The features for transition-based parsing have to be from *parser configurations*
- The data (treebanks) need to be preprocessed for obtaining the training data
- The general idea is to construct a transition sequence by performing a ‘mock’ parsing by using treebank annotations as an ‘oracle’
- There may be multiple sequences that yield the same dependency tree, this procedure defines a ‘canonical’ transition sequence
- For example,
 - LEFT-ARC_T if $(\beta[0], r, \sigma[0]) \in A$
 - RIGHT-ARC_T if $(\sigma[0], r, \beta[0]) \in A$
 - and all dependents of $\beta[0]$ are attached
 - SHIFT otherwise

Non-projective parsing

- The transition-based parsing we defined so far works only for projective dependencies
- One way to achieve (limited) non-projective parsing is to add special operations:
 - SWAP operation that swaps tokens in swap and buffer
 - LEFT-ARC and RIGHT-ARC transitions to/from non-top words from the stack
- Another method is pseudo-projective parsing:
 - preprocessing to ‘projectivize’ the trees before training
 - The idea is to attach the dependents to a higher level head that preserves projectivity, while marking it on the new dependency label
 - post-processing for restoring the projectivity after parsing
 - Re-introduce projectivity for the marked dependencies

Pseudo-projective parsing



Transition based parsing: summary/notes

- Linear time, greedy, projective parsing
- Can be extended to non-projective dependencies
- We need some extra work for generating gold-standard transition sequences from treebanks
- Early errors propagate, transition-based parsers make more mistakes on long-distance dependencies
- The greedy algorithm can be extended to beam search for better accuracy (still linear time complexity)
- Reading suggestion: Jurafsky and Martin (2009, draft chapter 14):
<https://web.stanford.edu/~jurafsky/slp3/14.pdf>, Kübler, McDonald, and Nivre (2009)

Transition based parsing: summary/notes

- Linear time, greedy, projective parsing
- Can be extended to non-projective dependencies
- We need some extra work for generating gold-standard transition sequences from treebanks
- Early errors propagate, transition-based parsers make more mistakes on long-distance dependencies
- The greedy algorithm can be extended to beam search for better accuracy (still linear time complexity)
- Reading suggestion: Jurafsky and Martin (2009, draft chapter 14): <https://web.stanford.edu/~jurafsky/slp3/14.pdf>, Kübler, McDonald, and Nivre (2009)

Next:

- Graph-based parsing: the MST

Acknowledgments, references, additional reading material



Grune, Dick and Ceriel J.H. Jacobs (2007). *Parsing Techniques: A Practical Guide*. second. Monographs in Computer Science. The first edition is available at http://dickgrune.com/Books/PTAPG_1st_Edition/BookBody.pdf. Springer New York. ISBN: 9780387689548.



Jurafsky, Daniel and James H. Martin (2009). *Speech and Language Processing: An Introduction to Natural Language Processing, Computational Linguistics, and Speech Recognition*. second. Pearson Prentice Hall. ISBN: 978-0-13-504196-3. URL: <http://web.stanford.edu/~jurafsky/slp3/>.



Kübler, Sandra, Ryan McDonald, and Joakim Nivre (2009). *Dependency Parsing*. Synthesis lectures on human language technologies. Morgan & Claypool. ISBN: 9781598295962.

