

Pro Angular 5th Edition

Chapter 07: SportsStore: Administration

INSTRUCTOR: MD. HABIBUL HAQ
domain.habib@gmail.com

10 Nov 2022

Q1 How dynamically loading of modules are managed?

- A. By using the routing configuration
- B. By using selector
- C. By using router component
- D. By using Route object

Answer: A

Q2. JWT stands for _____

- A. Java Web Token
- B. JavaScript Web Token
- C. JSON Web Token
- D. JSON Web Token

Answer: C

Q3. Why do you use JWT?

- A. In SPA, for authentication via third-party like facebook or google
- B. In SPA, for role-based authentication only
- C. In SPA, for authentication in RESTful services
- D. In SPA, for Azure Active Directory based authentication

Answer: C

Q4. What is the format of header that must be sent to RESTful services that implements JWT bearer token for security?

- A. Authorization: token-string
- B. Authorization: Bearer token-string
- C. Authorization: Bearer: token-string
- D. Bearer: token-string

Answer: B

Q5. What is required to prevent users from navigating to certain components without login?

- A. Route configuration
- B. Route guard
- C. JWT
- D. ActivatedRoute

Answer: B

Q6. Which one should you use at minimum for data from a RESTful service?

- A. `import { HttpClient } from "@angular/common/http";`
- B. `import { HttpHeaders } from '@angular/common/http';`
- C. `import { Router } from "@angular/router";`
- D. `import { FormsModule } from "@angular/forms";`

Answer: A

[With earlier version (<6)

`import { Http } from "@angular/http"`

Now new improved HttpClient is introduced]

Q7. You have a RESTful at url `http://remoteserver:9110/products`

You have the service like below

`@Injectable()`

```
export class MyService {  
    constructor(private http: HttpClient) {  
    }  
}
```

Which one is the correct way to call for fetching data from the REST service?

- A. `getProducts():any{ return this.http("http://remoteserver:9110/products");}`
- B. `getProducts():any{ return this.http.get("http://remoteserver:9110/products");}`
- C. `getProducts():any{ return this.http("GET", "http://remoteserver:9110/products");}`
- D. All of the above

Answer: B

Q8. What is the correct way of calling the get method of HttpClient of the HttpClient class with headers?

- A. `get(url)`
- B. `get(url, httpOptions)`
- C. `get(httpOptions, url)`
- D. `get(url, data, httpOptions)`

Answer: B

Q9. What is the correct way of calling the get method of HttpClient of the HttpClient class with data?

- A. `post(url, data)`
- B. `post(data, url)`
- C. `post(url, {data})`
- D. `post(url, data,format)`

Answer: A