GODSHAND Starter Manual

The practical reader's guide to the cinematic AI film kit

COVER PLACEHOLDER ? upload a full wrap cover to Kindle Direct Publishing

GODSHAND Starter Manual
The practical reader's guide to the cinematic AI film kit

First Edition

© 2026 LifeDocs Press
All rights reserved.

No part of this book may be reproduced, stored in a retrieval system, or transmitted in any form or by any means without the prior written permission of the publisher.

LifeDocs Press

ISBN 979-8-XXXXXXX-XX-X (paperback)
ISBN 978-0-XXXXXX-XX-X (ebook)

Printed on demand via Kindle Direct Publishing.
Source materials compiled from the LifeDocs Archive.

Contents

Build Map and Source of Truth 6

Creator Guide 16

Demo Film: The Beholder's Truce 26

Kit Listing and Setup Sheet 32

Project Tutorials 44

Build Map and Source of Truth

The canonical orientation document and conceptual foundation of the kit.

GODSHAND Kit · Build Map &
Source of Truth
Correction to my earlier note on this page · you were right.
My first
pass said "every file is byte-identical, nothing was lost."
That was
wrong, and I am fixing the record. The core rendering engine
(all of
src/ , every workflow, run.py , the configs) is byte-for-byte
identical in
every build · that part is safe. But the builds are NOT all
equal: two
builds dropped whole features, and one build's launcher was
silently
regressed to an inferior version. Your instinct that "we lost
more than the
folder" was correct.
· What is safe (identical in every build)
The actual engine never changed. These are byte-for-byte
identical across
FINAL_, TUNED_AK, and FINAL_AK:
All of src/ (render_motion.py , forge_character.py ,
voice_pass.py , score_gen.py ,
stitch.py , postprocess.sh , ·)
All workflows/*.json , run.py , and every config_*.yaml /
shots_*.json
All character reference images in refs/<name>/face and /body
Nothing about how your film actually renders was corrupted.
The damage is only
in the launchers, docs, and scaffolding that wrap the engine.
·· Feature audit · what was DROPPED or
OVERRIDDEN (25 Jul 2026)
Compared file-by-file by content hash, with packaging nesting
normalized.
GODSHAND Kit · Build Map & Source of Truth

Feature
FINAL_ (your
Downloads)
TUNED_AK

FINAL_AK
:--
:-:
:-:
:-:
NEW_STORY_TEMPLATE/ (author
any new film)
·
· dropped
· dropped
GODSHAND_ONECLICK.sh (main
launcher)
· full (10,565 B)
· dropped
·· regressed
(9,120 B)
README_L4.md
· full (3,437 B)
· dropped
·· regressed
(3,129 B)
l4_model_setup.py (WAN 2.2
downloader)
·
· dropped
·
notebooks/ (2 Kaggle
notebooks)
·
· dropped
·
RUN_TUNED.sh (one-command
tuned launcher)
·
· only here
·
The important one: the launcher was REGRESSED in
FINAL_AK
GODSHAND_ONECLICK.sh exists in two versions. The good one is
in your Downloads

(FINAL_). The FINAL_AK copy is 1,445 bytes smaller and was rewritten in a way
that reintroduces the exact "wrong folder" behavior you have been fighting:
Good version (FINAL_ / Downloads):
Story is selectable · KIT_CONFIG picks any film (not just the confrontation).
Characters are read dynamically from the config's character_forge.targets .
Character photos are OPTIONAL · if kit/refs/<name>/face has images it uses
them, otherwise it auto-forges a consistent face, logging the choice per
character.
GODSHAND_ANCHORS images are copied into kit/refs/ (the correct home).
Explicitly states: "There is no kit/anchors/ folder · the real location is
kit/refs/<name>/ ."
Regressed version (FINAL_AK):
GODSHAND Kit · Build Map & Source of Truth

Hardcoded to the confrontation film + "26 shots" · loses the any-story
engine.
Drops the per-character auto-forge detection.
Reintroduces a phantom kit/anchors/ folder and dumps anchor images into
ComfyUI/input/ and the kit root · this is the stray-image / wrong-location
behavior that caused the Spider-Man / Joker contamination.
Its README_L4.md tells you to use the non-existent kit/anchors/ .
·· Use the launcher and README from FINAL_ (Downloads). Do not use the
FINAL_AK versions.
· Which build to use (corrected)
GODSHAND_FINAL_ in your Downloads is your MASTER build. It has the correct
launcher, NEW_STORY_TEMPLATE/ , the notebooks,

l4_model_setup.py , and the full README
· everything, in its correct form.
The only thing it lacks is RUN_TUNED.sh (one-command tuned
launcher), and you do
not strictly need it · its tuned values are already baked
into
NEW_STORY_TEMPLATE/config_newstory.yaml (denoise: 0.55 ,
codeformer_fidelity: 0.5 ,
active_profile: lightning_l4). To also get the one-command
launcher, copy it in:
cp GODSHAND_TUNED_AK/RUN_TUNED.sh GODSHAND_FINAL/kit/
Correction: I earlier told you to use TUNED_AK as the
"richest" build. That was
wrong · TUNED_AK actually dropped the launcher,
l4_model_setup.py , the
notebooks, and NEW_STORY_TEMPLATE/ . FINAL_ (Downloads) is
the right master.
· Root cause · why Spider-Man / Joker appeared as
·jack· (the original question)
Three things had to line up. All three are now confirmed in
the code:
1. Two stray images were sitting in jack·s staging folder.
refs/jack/_inbox/jack_preface.jpg is a Spider-Man (Tobey
Maguire) still;
refs/jack/_inbox/joker.png is a Joker still. _inbox/ is a
·dump a pile of candidate
GODSHAND Kit · Build Map & Source of Truth

photos here· staging area that cull_photos.py is meant to
sort into face/ and
body/ · but it was never run on jack, so the strays stayed.
2. The reference loader reads recursively.
comfy_client.py and render_motion.py
collect refs with glob("refs/jack/**/*", recursive=True) · so
they reach into
_inbox/ instead of reading only refs/jack/face/ .
3. _inbox sorts first, and only the first 5 refs are used. An
underscore sorts
before letters, so the recursive list starts with the two
_inbox images. The code

keeps refs[:5] , so Spider-Man and Joker became jack·s top-two identity
anchors, ahead of his real face.
And the safety net failed too: the identity-check gate (_identity_score) uses the
same recursive glob, so it scored rendered frames against Spider-Man as if that
were jack · it did not just miss the drift, it approved it.
Net effect: the blueprint still was conditioned on Spider-Man/Joker · jack
animated as Spider-Man · the QC gate rubber-stamped it.
The fix
Immediate (done):
GODSHAND_MASTER.zip has every refs/*/_inbox/ folder deleted, so the recursive glob can only find real face/body images.
Permanent (one-line, recommended): restrict the ref globs to the face/body
folders, never the parent. In comfy_client.py , render_motion.py (_identity_score),
and refs_for() , read refs/<char>/face/* (and /body/*) instead of refs/<char>/**/* .
Then even if junk lands in _inbox again, it can never reach a render.
Where the key things live (never search blind again)
Main launcher (correct version):
GODSHAND_ONECLICK.sh · in FINAL_ / your Downloads
Tuned launcher:
RUN_TUNED.sh · TUNED_AK only
Model download:
l4_model_setup.py
Author a new film:
NEW_STORY_TEMPLATE/ (two files: a shots JSON + a config YAML)
GODSHAND Kit · Build Map & Source of Truth

Confrontation story + render config:
config_confrontation.yaml + shots_confrontation.json
Character images (real):

refs/<name>/face/ and /body/ · cast: jack, julie,
kunal, kunal_40s, kunal_young, gunja, observer,
original_identity
The correct anchor location is kit/refs/<name>/ · there is NO
kit/anchors/
folder.
Junk to delete:
refs/<name>/_inbox/ · the stray Spider-Man / Joker / Scarlett
placeholders live here. The clean design never reads from
here.
· Tuning baked into RUN_TUNED.sh
kaggle_2xt4 profile (2× Tesla T4 · Kaggle has NO L4) ·
KIT_MOTION_DENOISE=0.55
(motion freedom, was 0.25) · KIT_FLF2V_ENDFRAME=1 (shot-to-
shot morph ON) ·
KIT_FACE_ENHANCE=0 (skip plasticky face composite) · softened
temporal denoise ·
codeformer 0.9 · 0.5
Renders 4 proof shots: confr_caught , confr_allblades ,
confr_dare , confr_dontouch .
On the sandbox (why your originals were never at
risk)
I only ever held a read-only, throwaway copy of the kits you
uploaded. I never had
write access to your Kaggle kit, your datasets, or your
machine. Any differences
above already existed in the builds you sent me · I did not
create them.
· Change Log (newest first)
25 Jul 2026, ~7:57 AM IST · Fixed the recurring L4 mistake ·
the proof
render now targets Kaggle 2× Tesla T4, not L4 (which Niloy
does not have).
config_confrontation.yaml and
NEW_STORY_TEMPLATE/config_newstory.yaml were both
pinned to active_profile: lightning_l4 ; switched both to
kaggle_2xt4 (num_gpus:
2, Q8, xformers, 1280×720, rate ·0). Added a KIT_PROFILE env
override in
src/cfgutil.py so the hardware profile can be forced

explicitly (prevents silent
wrong-GPU runs). Rewrote RUN_TUNED.sh for Kaggle 2×T4 (sets
KIT_PROFILE=kaggle_2xt4 , removed the Lightning-only sudo
shutdown billing step,
replaced with a Kaggle 'Stop session' note). Verified no
config points at L4
GODSHAND Kit · Build Map & Source of Truth

anymore; cfgutil.py passes py_compile . Reshipped
GODSHAND_MASTER.zip (239
files).
25 Jul 2026, ~7:52 AM IST · Enforced ·everything from the
master folder.·
Verified in code that every script roots to the master folder
(root = parent of
src/) and reads all inputs from there · story (shots_file
), characters (refs/),
workflows, grade targets. The only outside doorways are the
opt-in
GODSHAND_ANCHORS launcher copy (copies INTO kit/refs/) and
lipsync.py ·s lookup
for the external LatentSync tool repo (not identity).
Hardened preflight.py
(already stage 1/10 of every run) to (a) print MASTER FOLDER:
<root> and ·all inputs
read ONLY from this folder,· and (b) warn about any stray ref
image outside
face/ body/ costume/ . Reshipped GODSHAND_MASTER.zip (239
files); py_compile clean.
25 Jul 2026, ~7:48 AM IST · Applied the permanent code fix
for the Spider-
Man bug and reshipped GODSHAND_MASTER.zip (238 files).
Patched
comfy_client.py._first_image() (the real render-conditioning
leak · it fed the first
image, which was the _inbox Spider-Man) and
render_motion.py._identity_score()
(the QC gate) to skip any underscore-prefixed staging folder
(_inbox) while
still reading face/ and body/ . Both files pass py_compile ;

behaviourally proven
· with junk dropped back into _inbox , the loader now picks
body/jack_body_0.jpg instead of _inbox/spiderman.jpg . Junk
can no longer reach a
render even if it reappears.
25 Jul 2026, ~7:25 AM IST · Traced and documented the Spider-
Man/Joker
root cause in code: recursive ref glob (refs/jack/**/*)
reaching into _inbox/ ,
_inbox sorting first, refs[:5] keeping the strays, and the
identity-check gate
using the same contaminated glob so it approved the drift.
Added the ·why
Spider-Man appeared· section plus the permanent one-line fix
(glob
refs/<char>/face/* , not the parent).
25 Jul 2026, ~7:22 AM IST · Built the clean master kit
GODSHAND_MASTER.zip (237
files) and delivered it to you as a download. Base = FINAL_
(correct full
launcher, 10,565 B); added RUN_TUNED.sh ; removed every
refs/*/_inbox/ folder
(the stray Spider-Man / Joker / Scarlett images). Verified
cast faces intact
(jack 5, julie 5, kunal 7, observer 5) and
NEW_STORY_TEMPLATE/ , l4_model_setup.py ,
and the notebooks all present.
25 Jul 2026, ~7:15 AM IST · Ran a full file-by-file audit
(content hashes,
nesting normalized). Corrected the earlier "nothing was lost"
claim on this
GODSHAND Kit · Build Map & Source of Truth

page. Documented: NEW_STORY_TEMPLATE/ dropped from TUNED_AK &
FINAL_AK;
launcher dropped from TUNED_AK and regressed in FINAL_AK;
l4_model_setup.py and notebooks/ dropped from TUNED_AK;
README_L4.md
dropped from TUNED_AK and regressed in FINAL_AK; RUN_TUNED.sh
only in

TUNED_AK. Changed the recommended master build from TUNED_AK
.
FINAL_ (Downloads).
25 Jul 2026, ~7:00 AM IST · Created this page as the durable
build map
after the four kit builds were first compared.
GODSHAND Engine Audit · Code + Real Run Evidence (25 Jul
2026)
Session Log · 25 Jul 2026, Evening (End-to-End Audit
Completion)
GODSHAND Kit · Build Map & Source of Truth

Creator Guide

The clearest creative-operational explanation of how the system turns story into output.

GODSHAND · Creator Guide
(Story, Voice, Music & Multi-
Character)
Two inputs only: a STORY_YAML block and one image per
character.
From those, the kit renders the video, voices the dialogue,
and scores
the music · no audio files needed.
What you provide vs. what the kit makes
You provide
The kit generates
STORY_YAML · story, shot list, spoken
line: text, and song: mood labels (all
text)
Video from character anchors + each shot's
action: (Wan image-to-video)
One face image per character
Voice · Kokoro TTS reads the line: text
you typed in the YAML
(nothing else)
Music · MusicGen composes a bed from
the song: label, auto-ducked under the
voice
The one seam: STORY_YAML
The setup cell has a single variable, STORY_YAML . On run it
compiles:
STORY_YAML · _build_shots_from_story() · shots_confrontat
ion.json · render loop
To change the film, you edit only this block. Nothing else.
GODSHAND · Creator Guide (Story, Voice, Music & Multi-
Character)

Top-level keys
Key
What it is
film
title string
note
one-line logline
look

global style, applied to every shot unless a shot overrides
it
avoid
global negative prompt
characters
map of name · { look, anchor }
shots
the list · each entry is one render unit
Do not add a render: block · the validated Wan quality
settings live in the
notebook config, and overriding them risks the melt/rainbow
regression.
Shot fields
Field
Meaning
id
unique string, e.g. scene01_shot_03
secs
duration in seconds (default 4)
who
list of character names (must match characters keys)
camera
camera move, e.g. "slow push-in", "low-angle crane up"
action
the main description: subject + emotion + camera, ending with
the
anti-melt tail
line
the spoken words (also accepts say: / dialogue:)
talking /
voiceover
booleans
song
music mood label (shots sharing a label share one bed)
palette
color mood
look
per-shot style override (optional)
takes
optional, overrides rejection_samples for that shot

Every action: must end with the anti-melt tail · it is what holds the image
together: smooth steady camera movement, gentle natural motion, subtle drifting atmosphere
and soft shifting light, stable coherent shapes, solid consistent forms, a living breathing
cinematic shot, no freeze
GODSHAND · Creator Guide (Story, Voice, Music & Multi-Character)

Generating a story with an LLM (Grok)
Paste your prose story into this prompt and drop the YAML it returns into
STORY_YAML :
You are a shot-list compiler for an image-to-video AI film kit.
I will give you a story in prose. Convert it into YAML in EXACTLY this schema.
Rules:
- Output ONLY valid YAML, no commentary, no code fences.
- Top-level keys: film, note, look, avoid, characters, shots.
- characters: give each person a name, a `look:` description, and an `anchor:`
filename like name_anchor.png. Reuse jack (man_anchor.png) and julie
(woman_anchor.png) for the two shipped faces.
- Every shot needs a UNIQUE id like scene01_shot_01.
- secs: 4 (keep all shots 4 seconds).
- who: list only character names defined above.
- Put spoken dialogue in `line:` and set talking: true (or voiceover: true).
- Give each shot a `song:` mood label; reuse the same label across a scene.
- action: describe the moment cinematically (subject + emotion + camera move),
then ALWAYS end the action with this exact tail:
"smooth steady camera movement, gentle natural motion, subtle drifting
atmosphere and soft shifting light, stable coherent shapes, solid consistent

forms, a living breathing cinematic shot, no freeze"
- Do NOT include a `render:` block. Do NOT change resolution/steps/model.
Here is the story:
<PASTE YOUR STORY HERE>
Voice + music
Voice · Kokoro TTS (English), set up in the audio step. It reads the line: text
from each shot. Voice is synthetic narration/dialogue, not a specific person's
cloned voice.
Music · MusicGen (facebook/musicgen-medium), keyed by the per-shot song:
label. Shots sharing a label get one continuous bed. It is a generated
instrumental score, not a licensed track.
Mixing · stitch.py ducks music to ·4dB under the voice and fixes the stereo
layout automatically.
Tip · for a clean demo, use one or two song: labels for the whole piece rather
than a new one per shot.
GODSHAND · Creator Guide (Story, Voice, Music & Multi-Character)

Multi-character support (patched notebook)
The patched notebook (rainman-wan-multichar.ipynb) adds two things:
1. N-character ingestion · after the jack/julie bind, it loops over every character
in STORY_YAML that declares an anchor: , finds that image anywhere under
/kaggle/input , and installs it to refs/<name>/face/ so it is identity-locked.
Characters with no matching image fall back to text-forge (unchanged
behavior). The original 2-character path is untouched.
2. Spoken-line fields · every shot now carries line / vo_text into
shots_confrontation.json .

To add a character: give it a name in characters: with a
look: and an anchor:
filename, then upload an image with that exact filename (e.g.
elder_anchor.png) to
the Kaggle dataset. No image = text-forged from the look
tokens.
Example: THE LANTERN KEEPER (runs as-is)
Validated against the real patched builder · 3 characters,
dialogue, and music all
parse through:
film: THE LANTERN KEEPER
note: Demo - multi-character story with voice and music. Runs
on the kit as-is.
look: warm analog neon twilight, soft synth-wave glow, magent
a and amber haze, gentle grain, nostalgic hush, 35mm
avoid: warped faces, extra fingers, duplicate limbs, morphin
g, flicker, text, watermark, jitter, plastic skin
characters:
jack:
anchor: man_anchor.png
look: a weary man in his forties, olive field jacket over
a white tee, short dark hair, tired honest eyes, faint stubbl
e
julie:
GODSHAND · Creator Guide (Story, Voice, Music & Multi-
Character)

anchor: woman_anchor.png
look: a calm luminous woman, soft dark hair, gentle stead
y gaze, pale scarf, quiet warmth like an angel in human form
elder:
anchor: elder_anchor.png
look: an old lantern keeper, deep-lined kind face, silver
beard, worn brown coat, holding a small brass lantern, patien
t eyes
shots:
- id: lantern_01
secs: 4
who: [jack]
camera: slow push-in

song: prelude
talking: true
line: I kept the light because someone had to.
palette: amber lamp glow
action: a slow push-in on the weary man standing in a dim d
oorway holding a small brass lantern, speaking softly to hims
elf, warm lamplight on his face, smooth steady camera movemen
t, gentle natural motion, subtle drifting atmosphere and soft
shifting light, stable coherent shapes, solid consistent form
s, a living breathing cinematic shot, no freeze
- id: lantern_02
secs: 4
who: [jack, julie]
camera: slow orbit
song: prelude
talking: true
line: You never had to carry it alone.
palette: magenta and amber haze
action: a slow orbit around the man and the luminous woman
facing each other in the neon haze as she reaches toward the
lantern between them, tender recognition, smooth steady camer
GODSHAND · Creator Guide (Story, Voice, Music & Multi-
Character)

a movement, gentle natural motion, subtle drifting atmosphere
and soft shifting light, stable coherent shapes, solid consis
tent forms, a living breathing cinematic shot, no freeze
- id: lantern_03
secs: 4
who: [elder]
camera: low-angle crane up
song: hymn
voiceover: true
talking: false
line: Every keeper passes the flame; none of us owns it.
palette: quiet neon fade
action: a low-angle crane up on the old lantern keeper rais
ing his brass lantern into the twilight as embers drift upwar
d, quiet reverence, smooth steady camera movement, gentle nat
ural motion, subtle drifting atmosphere and soft shifting lig

ht, stable coherent shapes, solid consistent forms, a living breathing cinematic shot, no freeze
Creator workflow
1. Write or generate the story (use the Grok prompt above), defining each
character in characters: .
2. Upload one face image per character to the Kaggle dataset, named to match
each anchor: (jack/julie use man_anchor.png / woman_anchor.png).
3. Paste the YAML into STORY_YAML . Add line: + talking / voiceover for speech and
a song: label for mood.
4. Run the setup cell · the kit compiles the shots and reports which characters
are identity-locked vs text-forged.
5. Render a short chunk (KIT_CHUNK_SIZE small), inspect frames, then scale.
6. Package · the stitched clip + zip drop out automatically.
GODSHAND · Creator Guide (Story, Voice, Music & Multi-Character)

Honest limits (don't oversell)
Voice is synthetic TTS (Kokoro, English) · not a specific person's cloned
voice unless voice-cloning is wired later.
Music is a generated instrumental bed · mood-matched, not a bespoke
human score or licensed song.
Lip-sync is approximate · talking: true drives mouth motion but is not frame-
perfect to the words. Good for cinematic VO/ambient dialogue, not a talking-
head substitute.
Voice last-mile · the line: text is captured into the shots JSON, but Kokoro
actually speaking it depends on one wire in src/render_motion.py , confirmed on
the next live run. Music and video work today.
Multi-character-in-one-frame is the hard case for any image-

to-video engine
· identity holds strongest for the character whose anchor seeds a shot.
For demo recording
Show the loop small: 2·3 characters, 2·3 shots, one song: label, one spoken
line: . That demonstrates the three selling points live · your own cast, your own
story, voice + music baked in · without a long render wait.
Say the "scales to a
full cast and feature length" claim; show the short multi-character clip.
GODSHAND · Creator Guide (Story, Voice, Music & Multi-Character)

Demo Film: The Beholder's Truce

The proof-of-concept film brief that explains the emotional sales logic of the kit.

.

GODSHAND Demo Film · ·THE BEHOLDER'S TRUCE· (micro-memoir, ~30 min render)

·Your first job after the current run finishes. A tiny, self-contained proof film built from the anchors you already have · 3·4 shots, ~30 minutes of render. This becomes the clip that sells the kit and headlines every post. No new film. Just this.

Logline

At the end of a long road, a weary man of forty-seven meets the angel who has walked every mile beside him · and finds his truce. A wordless 30-second memoir, distilled from The Saga of the Beholder (Chapter V · The Beholder's Truce).

Why this works as a demo

It's short enough to actually finish · 3·4 shots, one render session.

It proves the hard stuff in 30 seconds: a consistent human face, a second consistent character, a real film grade, and an emotional hold (not just a moving filter).

It's emotional, not technical · buyers feel it before they analyze it. That feeling is what sells.

It uses only what you already have: man_anchor.png (the man) and woman_anchor.png (the angel), current engine, current grade.

The film (shot list)

#	Anchor	What we see	Motion	~Len	What it shows off
Man		Wide: a lone			

figure on an
empty desert
road at dusk,
long shadow,
drifting dust
Slow push-in,
heat shimmer
4s
Environment +
motion + warm
Kodachrome
grade
GODSHAND Demo Film · ·THE BEHOLDER'S TRUCE· (micro-memoir,
~30 min render)

#
Anchor
What we see
Motion
~Len
What it shows
off

Man
Extreme close-
up: the
weathered 47-
year-old face,
dust on skin, a
slow blink and
breath
Micro head-
turn, eyes
settle toward
camera
5s
Face
consistency +
skin detail +
film grain ·

the shot that silences AI skeptics				
Angel	Backlit figure of the angel in soft haze, light blooming around her	Gentle drift forward, hair/cloth motion	4s	Second consistent character · halation/bloom + ethereal grade
Man	The man lifts his eyes; a faint exhale of acceptance as warm light breaks over him	Slow tilt up, lighting shift	5s	Emotional hold + a real lighting change (proves it's rendered, not filtered)
5 (optional) Man				

Final wide: he
walks on,
smaller in
frame; title
fades in
Locked / slow
drift
4s
Closes the arc;
carries the title
card
Grade & sound
Grade: your current look · Kodachrome warmth, halation on the
highlights, fine film grain,
slightly desaturated shadows. Don't change the pipeline; the
demo should look exactly like
what buyers will get.
Sound: silence + wind, and a single held piano note under
shots 3·4. Let the image
breathe.
Title card: THE BEHOLDER'S TRUCE · then small: rendered
entirely on a free GPU.
Render budget
Core film = 4 shots × ~8·9 min · 32 min. That's your
~30-minute target.
Shot 5 is optional (+~8 min) if quota allows.
GODSHAND Demo Film · ·THE BEHOLDER'S TRUCE· (micro-memoir,
~30 min render)

Edit + grade assembly afterward is minutes, not hours · the
grade is already baked per
shot.
How it plugs into the current setup
Uses the existing anchors and the notebook you already have
(streaming grade fix baked
in).
Render each shot as its own short clip, then stitch in any
editor (or the kit's stitch step).
The moment it's exported: it's your proof asset (listing) and
the raw material for the

walkthrough's before/after and the 60·90s sales cut.
GODSHAND Demo Film · ·THE BEHOLDER'S TRUCE· (micro-memoir, ~30 min render)

Kit Listing and Setup Sheet

Commercial-facing packaging copy and setup positioning for the offer.

GODSHAND · Cinematic AI Film
Kit (·499 Listing + Setup Sheet)
Turn a single portrait into a cinematic AI film shot · on a
free GPU.
GODSHAND is the exact pipeline used to render The Saga of the
Beholder. You bring a character image; the kit gives you
graded, HD,
motion-consistent film frames without a render farm.
Draft listing copy · rename "GODSHAND" freely. Everything
below is written to
be pasted into Topmate / Razorpay / Gumroad. The second half
is the honesty
sheet buyers should read before paying.
The one-liner
GODSHAND Cinematic AI Film Kit · a guided notebook that
renders film-grade
AI video shots from your own character images, running
entirely on free Kaggle
dual-T4 GPUs. No render farm, no paid cloud, no melt.
What it does
Takes your anchor image(s) (a face/character) and animates
them into short
cinematic shots.
Runs a hardened Wan 2.2 image-to-video pipeline (with a
working LTXV
fallback engine).
Applies a full film grade · Kodachrome-style color, halation,
film grain,
sharpening · automatically.
Upscales to HD (1536×1024) and interpolates for smooth
motion.
GODSHAND · Cinematic AI Film Kit (·499 Listing + Setup Sheet)

Renders in shot batches so you can build a whole film across
multiple free-
GPU sessions.
Why it's different (the hard-won part)
This isn't a fresh ComfyUI workflow you have to debug. It's a
kit where the painful
failures are already solved:

· Anti-melt / anti-rainbow fix · the render-schedule desync that turns AI
video into noise soup is patched.
· Memory-safe streaming grade · the postprocess step no longer OOM-
crashes on HD footage (bounded RAM, tunable).
· Fits free 14 GB T4 GPUs · quantized models chosen so it actually runs
where you don't pay.
· Shot/chunk system · render 435-shot films in resumable batches.
What's inside
The full rainman-wan.ipynb Kaggle notebook (drop-in, guided).
The GODSHAND source kit (render, grade, upscale, face-enhance, stitch).
A quick-start guide + the recommended settings that actually work.
A full video walkthrough · the entire process screen-recorded end to end,
so nothing is left to guesswork.
Sample anchor images and a demo shot list.
Proof
The film speaks for the kit. The Saga of the Beholder · every frame rendered on
free GPUs with this exact pipeline. The demo clips are the use-case: film
entertains, the kit empowers.
Price
·499 · one-time, lifetime access. Includes the full kit, the notebook, the quick-
start guide, and a complete step-by-step video walkthrough of the entire
GODSHAND · Cinematic AI Film Kit (·499 Listing + Setup Sheet)

process · recorded end to end so you just follow along, click for click.
·· Read before you buy · honest setup requirements
This is a guided notebook, not a one-click app. If you follow steps and
have a little patience, it works. If you expect a magic "make

my movie"
button, this isn't that · and I'd rather you know now.
You will need
A free Kaggle account, phone-verified (required to unlock GPUs).
Kaggle's free dual-T4 GPU quota (~30 hrs/week · enough for real work, not
unlimited).
A free HuggingFace account + access token (to download the open models).
Your own character/anchor images (or use the samples included).
Basic comfort with: opening a notebook, pasting a token, clicking Run. No
coding required.
Time & expectations
Rendering is slow on free GPUs · roughly 8·9 minutes per shot. A full film is
many sessions, not one afternoon.
Output is stylized AI video. Expect occasional imperfections (hands, tiny
details, rare artifacts). The kit minimizes them; it doesn't make them
impossible.
What this kit does NOT do
· It's not a hosted service · you run it on your own free Kaggle account.
· It won't run well on random low-VRAM setups; it's tuned for Kaggle T4s.
· It doesn't include a commercial-use guarantee for the underlying open
models · check each model's license if you plan to sell what you render.
GODSHAND · Cinematic AI Film Kit (·499 Listing + Setup Sheet)

· It's not a chatbot or a script writer · it renders shots from images you
provide.
FAQ
Do I need a registered business or GST to buy?

No · it's a digital download. You just need a way to pay.
Can I use my own faces/characters?
Yes. Drop in your own anchor images. Sample images are included to start.
Will it work on Google Colab?
It's built and tested for Kaggle dual-T4. Colab may work with tweaks but isn't
supported out of the box.
Can I sell videos I make with it?
The kit code is yours to use, but the underlying AI models have their own licenses.
Verify commercial terms for the models before selling output.
What support do I get?
Best-effort help via the setup guide + a contact channel.
This is a solo-built kit,
not a company helpdesk · priced accordingly.
Refund policy (suggested)
Because this is an instant digital download with a complete video walkthrough
included, all sales are final once the files are accessed.
There's no "I couldn't set
it up" gap · the video shows every single step. If you still get stuck, reach out
and I'll help you get running.
Pre-launch checklist
Finish + export the film (your #1 proof asset).
Pick a payment rail (Topmate / Razorpay individual / Gumroad).
Record a 60·90s screen demo of the kit rendering one shot.
Zip the kit + guide; test the download on a clean account.
GODSHAND · Cinematic AI Film Kit (·499 Listing + Setup Sheet)

Publish listing · share proof clips · get first paying stranger.
Video walkthrough · recording script
Record on a clean, fresh Kaggle account (new login, no pre-setup). The
buyer must see the exact path they'll walk · not your already-
configured machine. Timelapse the slow render parts. Aim for

12·18 min
with chapter markers.
0. Cold open (10·20s) · the hook
Open on a finished graded shot from the film. Voiceover:
·This was rendered on a
free GPU, no paid cloud. In the next few minutes I'll show
you exactly how · step
by step, nothing skipped.·
1. What you need (30s)
On screen: a browser, a free Kaggle account, a free
HuggingFace account. ·No
installs. No coding. If you can paste a code and click Run,
you can do this.·
2. Kaggle account + GPU unlock (1·2 min)
Sign in · phone-verify · show where to enable the dual-T4 GPU
accelerator. Call
out the ~30 hrs/week free quota honestly.
3. HuggingFace token (1 min)
Create account · Settings · Access Tokens · create a read
token · copy it.
·This lets the notebook download the models.·
4. Load the notebook + kit (1·2 min)
Import rainman-wan.ipynb · attach the GODSHAND kit dataset ·
add the token as a
Kaggle Secret named HF_TOKEN . Show exactly where each field
goes.
5. Add your character + story (2·3 min) · the magic moment
Upload your anchor image(s) · open the shot-list / story file
· edit one shot's
prompt so viewers see their story is what drives the render.
This is the ·it's my
film· hook.
6. Run it (1 min + timelapse)
GODSHAND · Cinematic AI Film Kit (·499 Listing + Setup Sheet)

Click Run All. Narrate what's happening: models downloading,
both experts
loading, sampling starting. Timelapse the wait so it never
feels slow.
7. First shot renders (1·2 min)

Show the raw base shot. Then the HD upscale and the film grade · cut a quick
before/after so the color + grain ·wow· lands.
8. Export + download (1 min)
Show the final .mp4 and where to download it. ·That's one shot. Repeat for your
whole film · the kit resumes across sessions.·
9. Outro (30s)
Recap the 3 things they needed. Point to the quick-start guide + how to get help.
End on the finished film clip again. ·That's the whole thing. Go make yours.·
Recording tips
Screen-record at 1080p; a small webcam bubble builds trust but is optional.
Cut dead air ruthlessly; every model-download wait gets timelapsed.
Add chapter markers matching the steps above · buyers rewatch specific
parts.
A 60·90s cut of steps 0, 5, 7 = your sales demo. Film both in one sitting.
How to record it (free)
Screen recorder: OBS Studio (free, all platforms) · or zero-install built-ins:
Windows Win+G, Mac Cmd+Shift+5. Record at 1080p.
Don't film the slow render live. Record the setup steps · stop during the ~8·9
min render · resume for the result. Splice the segments (or drop a ·rendering··
timelapse card) in editing.
Audio: narrate live with any headset/phone mic, or record silent and add captions
+ voiceover after · less pressure on take one.
Editing (free): CapCut, DaVinci Resolve, or iMovie / Clipchamp. Import the actual
film .mp4 clips for beats 0 and 7 · don't screen-record them, or they'll look soft.
Before you hit record: use a clean browser profile (bookmarks hidden, no

personal tabs) and the fresh Kaggle account, so viewers see the real from-
GODSHAND · Cinematic AI Film Kit (·499 Listing + Setup Sheet)

scratch path.
Where to find buyers
Honest targeting note: the kit still needs a Kaggle account + HF token, so
the real sweet spot isn't literally zero-tech · it's the budget AI-creator
who'll happily follow a video. The faceless-YouTube / AI-video crowd is
perfect: hungry, tutorial-native, allergic to paying for expensive tools.
Demand is real: creators already pay for faceless-video workflows (one
builder even got an $8K offer to buy their pipeline). Your edge is a one-
time ·499 kit that runs free on Kaggle · it directly beats the monthly
SaaS tools this crowd resents.
Communities to target
Platform
Community
Why / rules to respect
Discord
Faceless Incubator (~38k)
Largest faceless-creator hub · biggest pool. Watch promo rules.
Discord
YouTube Faceless (~20.7k)
The #1 faceless community, but strictly no self-promo · value first, DM only if invited.
Discord
AI Forum for India (~7.5k)
India-focused AI hub · your budget-creator base.
Discord
AI Filmmakers server (invite

pinned in r/aifilmmaking)
Craft-focused, platform-independent;
share the film as proof.
Discord
Wan (official) / ComfyUI
servers
The exact models your kit uses;
showcase channels welcome results.
Reddit
r/aitubers
Small AI-video creators, tutorial-hungry.
Showcase-friendly.
Reddit
r/aifilmmaking
Exactly your craft; people asking ·how
was this made?·
GODSHAND · Cinematic AI Film Kit (·499 Listing + Setup Sheet)

Platform
Community
Why / rules to respect
Reddit
r/comfyui, r/StableDiffusion
Technical AI-video crowd; best for ·built
on free GPUs· proof clips. No
paywalled-workflow spam.
Reddit
r/FacelessAICreators,
r/Seedance_AI
More faceless / AI-video subs;
showcase-friendly.
India
AI Learners India (Hindi, no-
code Discord)
Zero-tech-background, limited-funds
beginners · your ideal buyer.
India
AI Video Generators
(Telegram)
Active AI-video channel comparing

tools; warm audience.
Facebook
·Faceless YouTube· creator
groups
Older/less-technical creators on tight
budgets.
How to find more (server-finder sites)
Search these by tag (comfyui , filmmaking , ai-video ,
faceless) to surface fresh
servers: Disboard, Discadia, top.gg, DigitalOcean's AI-
Discord roundup, and
aixploria's AI-Discord list.
The value-first playbook (don't get banned)
1. Lead with the film, not the link. Post a stunning clip:
·Rendered this entirely
on a free Kaggle GPU.· Let people ask how.
2. Answer generously in public. When someone asks about
setup, actually help.
You become ·the free-GPU AI-film person.·
3. Soft-mention, don't spam. ·I packaged my exact pipeline +
a full walkthrough
video if anyone wants the shortcut · happy to DM.·
4. Use showcase channels where self-promo is allowed; respect
the no-promo
rule everywhere else.
5. Let the walkthrough clip do the selling · people who see
the whole process
work are pre-sold and won't refund.
Ready-to-post templates
Reddit showcase post (r/aifilmmaking, r/StableDiffusion,
r/aitubers)
GODSHAND · Cinematic AI Film Kit (·499 Listing + Setup Sheet)

Title: I rendered a short film entirely on a free GPU · no
paid cloud, no render
farm
Body: I spent months fighting the usual AI-video curse ·
melting faces,
rainbow noise, characters that change identity every frame. I
finally got a

pipeline that holds a consistent face and grades like real
film (Kodachrome
warmth, grain, halation), running entirely on free Kaggle T4
GPUs.
Here's a ~30-second piece from a longer memoir project I'm
building.
Ask me anything about how it's built · happy to share the
setup. What would
you want to see it render next?
(Attach the clip. No link in the post body · let people ask.
Reply to ·how?· with
the soft-mention below.)
Discord showcase-channel message
Made this on a free Kaggle GPU Took forever to kill the melt
+ rainbow
noise, but it finally holds a real face and a proper film
grade. Everything's open
models on a free T4 · happy to answer setup questions
(Drop the clip. Only post in channels that allow showcases.)
Soft-mention reply (when someone asks ·how did you do this?·)
Sure · it's Wan 2.2 image-to-video on ComfyUI, quantized to
fit a free T4, with
a custom grade + upscale pass. I packaged my exact notebook +
a full step-by-
step walkthrough video so people don't have to relive the
debugging pain ·
happy to DM the link if that's useful, otherwise glad to
explain any part here.
GODSHAND · Cinematic AI Film Kit (·499 Listing + Setup Sheet)

Project Tutorials

Step-by-step material that makes the kit and related bundle easier to follow end to end.

Project Tutorials · Step by
Step (All Projects + Kit)
Your complete, follow-along setup guide for all four products · the
GODSHAND film kit plus the three software projects (Convergence,
SafeScreen, Solana Sniper). Each section goes top to bottom, click by
click, so you · or a buyer · never have to guess.
Note on the Google Drive link: I couldn't open the Drive folder you shared ·
Drive folder links load their file list in the browser and can't be read from a
share URL, and I don't have a Drive connector. This guide is built from your own
project pages in this workspace instead, which are accurate and current. If you
want any project's exact file names/folder layout baked in, paste that project's
file list here (or drop the project's .zip into our chat) and I'll fold it in.
How to use this guide
Each project is self-contained · jump straight to the one you need.
What you need lists prerequisites · get those first.
Steps are in order. Don't skip; each unlocks the next.
Honest limits is what the product does not do. Keep it in every listing · it's
your refund shield.
1) GODSHAND · Cinematic AI Film Kit
Open the listing + setup sheet
What it is: turns your character image into graded, HD, motion-consistent film
shots · running on a free Kaggle GPU. This is the exact pipeline we set up
Project Tutorials · Step by Step (All Projects + Kit)

together for the 2-minute cut of The Saga of the Beholder.
What you need
A free Kaggle account, phone-verified (unlocks GPUs)

A free HuggingFace account + a read access token (optional, but gives faster
model downloads)
The GODSHAND kit uploaded as a Kaggle Dataset · it must contain a src/
folder with render_motion.py inside
Your character/anchor images as a Kaggle Dataset (or use the samples)
Step by step
1. Upload the kit as a Kaggle Dataset. Take the kit ZIP (GODSHAND_KIT_AUTOPILOT.zip)
· Kaggle · Datasets · New Dataset · upload. Kaggle auto-extracts it, so
the src/ folder is detected automatically.
2. Create/import the notebook. New Notebook · File · Import Notebook ·
upload rainman-wan-multichar.ipynb (the version with the 2-minute cut).
3. Attach your datasets. In the notebook's right sidebar: Add Input · Datasets
· add (a) your GODSHAND kit dataset and (b) your saga-custom-characters refs
dataset.
4. (Optional) Add your HF token. Add-ons · Secrets · new secret named
HF_TOKEN · paste your token. Skipping this still works; downloads are just
slower.
5. Set the machine. Right sidebar: Accelerator = GPU T4 × 2, Internet = On.
6. Run All.
7. Confirm the setup log. You should see GODSHAND kit mounted· and then AUTO-
DERIVED from story: total=28 shots · that's the 2-minute cut building correctly.
8. Let it render. It renders shot by shot and skips any already finished.
··It runs on ONE T4, even on the "T4 × 2" machine. A built-in RAM guard
only ever launches one render server (two would exceed the 32

GB host
Project Tutorials · Step by Step (All Projects + Kit)

RAM and crash). So shots render one at a time, not in
parallel · this is
expected, not a bug.
The 2-minute cut (already configured for you)
28 shots, ~1:57 · the five opening scenes (i01_jungle ·
i05_between).
rejection_samples = 1 · one take per shot (fastest).
Net render time: ~4.5·5.5 hours on a single T4 (~8·9
min/shot).
If a session stops before finishing (resume)
With the free ~2 GPU-hours/week, it won't finish in one go ·
it stops cleanly at
the budget and saves Beholder_progress.zip + a STATUS.txt
listing what's left.
1. Next session: Add Input · Your Work · this notebook · its
Output.
2. Run All again · it detects finished clips and picks up
where it stopped.
3. When all 28 are done, it auto-stitches the final master
into the zip.
Honest limits
Guided notebook, not one-click; needs a Kaggle account (+
optional HF
token).
Single-T4 sequential rendering; ~8·9 min/shot.
Stylized AI output · occasional artifacts (hands, tiny
details).
Check each underlying model's license before selling what you
render.
2) Convergence Framework · ·499
Open the listing
What it is: a thinking framework + ready-made LLM prompts to
define the right
objective before you build · so you can decide in an hour
whether a goal is even
formalizable.
What you need

Project Tutorials · Step by Step (All Projects + Kit)

The kit ZIP (a PDF + a few markdown files). No install, no GPU.
Any LLM (ChatGPT / Claude / Gemini).
How to use it
1. Open Convergence_Under_Constraint.pdf · read the core method first.
2. Follow README_objective_function.md · walk Steps 0·8 to write your objective function.
3. Paste SystemPrompt_Code_Convergence_Deterministic.md into your LLM as a system prompt before coding.
4. Use AI_Code_Review_Prompt_v2.md to review code against the objective (not just syntax).
5. Study Trading_Bot_Convergence_Framework_v3.md as a fully worked example, then copy the pattern for your own system.
To make it demo-ready (before selling)
Apply it to 3·4 real goals, including one deliberately messy / non-formalizable one, and show it correctly flags the messy one.
Record a short worked example: real goal · run the framework · verdict.
Honest limits
It's a thinking discipline, not runnable code · the value is the judgment, not an executable.
3) · SafeScreen · ·1,999
Open the listing
What it is: a trained on-device content-moderation model + inference SDK · flags/masks violence, gore, and NSFW in images, with an OCR layer for text. Runs offline, no cloud.
··Redact secrets FIRST.
nsfw_fix.py contains a hardcoded Kaggle username + API key. Delete those lines and rotate the key

before you
Project Tutorials · Step by Step (All Projects + Kit)

zip or share anything.
What you need
Python + a fresh virtual environment. Runs on CPU
(onnxruntime) · no GPU
required.
How to run
1. Create a fresh venv and install the project's
dependencies.
2. Sanity check first: confirm toxic_detector.onnx loads and
classifies one image
end-to-end with onnxruntime on CPU.
3. Run the inference scripts: inference_onnx ,
inference_tflite , or batch_inference .
4. Build a held-out test set you did NOT train on · report
precision, recall, F1, a
confusion matrix, and false-positive rate · per class.
5. Live demo: a minimal Gradio or FastAPI page · upload an
image, get the
flagged label + confidence, fully offline. Screen-record it.
Honest limits
Per-class accuracy varies · only market the classes where
recall is genuinely
strong; flag the weak ones. Buyers must test on their own
data.
4) Solana Sniper · ·2,499
Open the listing
What it is: the full source + a rigorous 6-month paper-
trading study of a Solana
memecoin sniper (ingestion, ML signal layer, risk manager,
React/TS dashboard,
Monte Carlo risk analysis). Sold as a study, not a live
money-maker.
··Redact secrets FIRST. Delete .env , .env1 , and
gmgn_keys/gmgn_private.pem ;
rotate the wallet + API keys (assume burned); add a
.gitignore and a
clean .env.example .

Project Tutorials · Step by Step (All Projects + Kit)

How to run (paper mode only)
1. Hard safety rule: never connect real funds, real keys, or mainnet execution.
Paper / backtest only.
2. Set up a fresh environment and install dependencies.
3. Re-run the Monte Carlo / backtest harness on historical data.
4. Report the equity curve, win rate, and max drawdown · losing runs
included, honestly.
5. Reproduce the study's output from the shipped ZIP with a single command,
and record it.
Honest limits
Paper-tested only; live performance unverified. Not financial advice; past
results don't predict future results.
Handy notes for all four
Free tool to run/fix code: Antigravity (free agentic IDE) for the CPU projects;
fall back to Cursor (free) or aider if it throttles. GPU work (the film) stays on
Kaggle.
Always strip secrets (.env , .pem , keys) and add a .env.example before zipping
any project.
Record proof on a clean machine/account so a buyer's first run matches your
demo.
Fastest first rupee: publish Convergence (·499) first · it's clean, needs zero
redaction, and is the shortest path to a sale.
Project Tutorials · Step by Step (All Projects + Kit)