🎯

Render QA — Shot 1 HD Baseline (identity reference)

✅ First clean end-to-end HD chunk. The OOM fix held, postprocess + streaming grade completed, and the zip packaged. This page is the identity + quality baseline to diff future shots against — especially the motion-heavy test shot.

Measured specs (Shot 1, take_0)

Field	Value
Resolution	1536×1024 (HD, RealESRGAN 2× landed)
Codec / pixel format	h264 / yuv420p
Frames	57
Frame rate	16 fps
Duration	3.56 s
Bitrate / size	6.3 Mbps / 2.82 MB

Quality read

- No melt, no rainbow/color-breakup noise — the core curse is gone.
- Identity holds across all frames: clearly jack from `man_anchor.png`, including the hand-to-face beat.
- Film grade present: warm skin, cool concrete, red→blue practical lights, fine grain.
- Subtle believable performance (head turns, hand to face).

Identity strip (face crops)



Shot 1 face identity strip

Full-frame contact sheet



Shot 1 contact sheet

How to diff the motion-shot test against this

1. Render one motion-heavy shot (a run/search beat, or a two-character shot with julie).
2. Extract 5 frames evenly across the clip and crop the same face region into a strip.
3. Compare against the strip above: same face geometry, eye spacing, jawline, hairline? Any drift = identity problem.
4. Confirm grade + sharpness match and there's still no melt/rainbow under real movement.
5. If clean → bump `KIT_CHUNK_SIZE=12` and walk `KIT_CHUNK_INDEX` through the batches.

Open checks before scaling to all 435

- [ ] Compare take_0 vs take_1 (rejection_samples=2) and keep the stronger one.
- [ ] Render + diff one motion-heavy shot against this baseline.

- [ ] Then greenlight the full batched run.