

```
mysql> select * from emp;
-> $
Empty set (0.00 sec)
```

```
mysql> create trigger mytrigger2
-> before
-> insert
-> on emp
-> for each row
-> begin
-> if(new.salary<50000) then
-> signal sqlstate '10101' set message_text='salary is less than 50000';
-> end if;
-> end;
-> $
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> insert into emp values (1,30);
-> $
ERROR 1644 (10101): salary is less than 50000
mysql> select * from emp;
-> $
Empty set (0.00 sec)
```

```
mysql> insert into emp values (1,50030);
-> $
Query OK, 1 row affected (0.00 sec)

mysql> select * from emp;
-> $
+-----+-----+
| id | salary |
+-----+-----+
| 1 | 50030 |
+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> create trigger mytrigger3
-> before
-> update
-> on emp
-> for each row
-> begin
-> if(new.salary<50000) then
-> signal sqlstate '10101' set message_text='salary is less than 50000';
-> end if;
-> end;
-> $
Query OK, 0 rows affected (0.01 sec)

mysql> update emp set salary=20 where id =1;
-> $
ERROR 1644 (10101): salary is less than 50000
```