```
Database changed
mysql> create table client_mstr  ( id integer primary key, name varchar(20), bal_due integer );
Query OK, 0 rows affected (0.03 sec)
```

```
mysql> select * from client_mstr;
    -> $
+----+---------+---------+
| id | name    | bal_due |
+----+---------+---------+
|  1 | sahil   |    NULL |
|  2 | omkar   |    NULL |
|  3 | pratham |    NULL |
+----+---------+---------+
3 rows in set (0.00 sec)
```

```
mysql> create procedure up_bal_due (in my_id integer,in bal integer)
    -> begin
    ->
    -> if(bal<0) then
    -> signal sqlstate '10101' set message_text = 'balance less than 0';
    -> else
    -> update client_mstr set bal_due=bal where id=my_id;
    -> end if;
    ->
    -> end;
    -> $
Query OK, 0 rows affected (0.01 sec)
```

```
mysql> call up_bal_due(2,100);
    -> $
Query OK, 1 row affected (0.01 sec)

mysql> select * from client_mstr;
    -> $
+-----+----------+----------+
| id  | name     | bal_due  |
+-----+----------+----------+
|   1 | sahil    |     NULL |
|   2 | omkar    |      100 |
|   3 | pratham  |     NULL |
+-----+----------+----------+
3 rows in set (0.00 sec)
```

```
mysql> call up_bal_due(1,-8);
    -> $
ERROR 1644 (10101): balance less than 0
```