

Prefix Sum

Content

- Q Queries { sum L-R }
- Q Queries { sum L-R } even index
- special index .

Amreshwar	M S Haseeb Khan
Anil	Mahesh
ankit shukla	Manohar A N
ANUBHAV RAMNANI	MOHAMMAD ALI
Arunava Basak	Narayan
Arunkumar	Nikhil D
Ashish Kumar	Nutan
Bhavesh Pandey	Pranjul Kesharwani
Bhushan Ganesh Shelar	Prasanna Kumar D R
Deepshikha Arora	Praveen Kumar
Dev Raj Gaur	Priyank Varshney
Dhanashree Sagane	Rahul
Dhasthagiri Reddy	Rishav Ghosh
Dhruv	Sai Kiran JNR
Dipika Malik	Shaik Lal Jan Basha
Farzana kauser	Shambhavi Belligatti
Harikrishnan A	Shivam Shiv
Harshad Marathe	Shivanand Patil
Hemant Verma	Subhash
Induja	Suresh
Iti	Uddepta Saikia
jeevanantham	Ved Verma
Kanhu	

Real world Example

Stock portfolio Performance Tracking

Given an array representing daily profit or loss from a particular stock over a period of days.

Write a function that calculates the total profit or loss over a given range of days.

Prices [] = [0 1 2 3 4 5 6 7 8 9
-5, 10, 20, 40, 50, -10, 80, -90, -20, -10]

start day	End day	Net profit or loss	
0	9	65	
1	4	120	1 2 3 4 10, 20, 40, 50
0	0	-5	
7	9	-120	
2	7	90	

Q) Given an integer array with N elements & Q queries.


For each query L, R

- calculate the sum of all elements from index L to index R

<u>Range</u>	<u>Sum</u>	<u>Queries</u>
$A = [-3, 1, 2, 3, 4, 5, 2, 8, -9, 3, 1]$		

Query

<u>L</u>	<u>R</u>	<u>sum(L to R)</u>
4	8	9
3	7	10
1	3	12
0	4	14
7	7	-9



Brute force

```

for q → 0 to Q-1 {
    l = L[q]
    r = R[q]
    sum = 0
    for i → l to r {
        sum += A[i]
    }
    print(sum)
}
  
```

$A = [-3, 1, 2, 3, 4, 5, 2, 8, -9, 3, 1]$

$\rightarrow Q \text{ times}$

$\rightarrow (r-l+1) \text{ times}$
 Worst case sum all values
 $N \text{ times}$

TC: $O(Q * N)$
 SC: $O(1)$

Score board of Cricket after i^{th} over has completed.

0	1	2	3	4	5	6	7	8	9	10
0	2	8	14	29	31	49	65	79	88	97

How many runs were scored in 7^{th} over?

After 7^{th} over end = 65 runs

$$65 - 49 = 16$$

After 6^{th} over end = 49 runs

How many runs were scored from 6^{th} to 10^{th} over

0	1	2	3	4	5	6	7	8	9	10
0	2	8	14	29	31	49	65	79	88	97
After	10^{th}	→								97 runs
After	5^{th}	→								31 runs = 66 runs

How many runs were scored in just 10^{th} over?

0	1	2	3	4	5	6	7	8	9	10
0	2	8	14	29	31	49	65	79	88	97
After	10^{th}	over	→							97 runs
After	9^{th}	over	→							88 runs

$$97 - 88 = 9$$

How many runs were scored from 3rd to 6th over ?

0	1	2	3	4	5	6	7	8	9	10
0	2	8	14	29	31	49	65	79	88	97

$$49 - 8 = 41$$
$$S[6] - S[2] = 41$$

→ 49 runs scored [0-6]
- 8 runs scored [0-2]

How many runs were scored from 4th to 9th over ?

0	1	2	3	4	5	6	7	8	9	10
0	2	8	14	29	31	49	65	79	88	97

$$S[9] - S[3] = 88 - 14$$
$$= 74$$

→ Runs scored in cricket are provided in a cumulative manner .

→ Let's try to create cumulative sum array
prefix sum array .

How to create prefix sum array ?

Prefix sum \longrightarrow cumulative sum of the array.

$P[i]$ \longrightarrow sum of all elements from 0 to i

$$A = [\begin{matrix} 0 & 1 & 2 & 3 & 4 \\ 2 & 5 & -1 & 7 & 1 \end{matrix}]$$

$$P[0] = 2$$

$$P[1] = 2 + 5 = 7$$

$$P[2] = 2 + 5 + (-1) = 6$$

$$P[3] = 2 + 5 + (-1) + 7 = 13$$

$$P[4] = 2 + 5 + (-1) + 7 + 1 = 14$$

$$P = [\begin{matrix} 0 & 1 & 2 & 3 & 4 \\ 2 & 7 & 6 & 13 & 14 \end{matrix}]$$



Calculate the prefix sum array for

$$\begin{matrix} 10 & 32 & 6 & 12 & 20 & 1 \\ 0 & 1 & 2 & 3 & 4 & 5 \end{matrix}$$

$$10 \quad 42 \quad 48 \quad 60 \quad 80 \quad 81$$

Code to create prefix sum array ?

$p[i]$ → sum of all elements from 0 to i

Bruteforce → Do as the question says
Most straightforward approach

```
for i → 0 to N-1 {  
    psum = 0  
    for j → 0 to i {  
        psum += A[j]  
    }  
    print(psum)  
}
```

$A = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$

$T.C : O(N^2)$

$$\begin{aligned} p[0] &= A[0] \\ p[1] &= A[0] + A[1] \\ p[2] &= A[0] + A[1] + A[2] \\ p[3] &= A[0] + A[1] + A[2] + A[3] \\ p[4] &= A[0] + A[1] + A[2] + A[3] + A[4] \end{aligned}$$

$$\begin{aligned} p[0] &= A[0] \\ p[i] &= p[0] + A[1] & p[i] = p[i-1] + A[i] \\ p[2] &= p[1] + A[2] & \text{if } i > 0 \\ p[3] &= p[2] + A[3] & \text{if } i == 0 \rightarrow A[0] \\ p[4] &= p[3] + A[4] \end{aligned}$$

Optimised


```

P[N] // initialize prefix sum
P[0] = A[0]
for i → 1 to N-1 {
    P[i] = P[i-1] + A[i]
}

```

TC: O(N)
SC: O(N)

$$\begin{aligned}
 A &= [2, 5, -1, 7, 1] \\
 P &= [2, 7, 6, 13, 14]
 \end{aligned}$$



How to answer the queries ?

$$A = [\begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 & 6 & 7 & 8 & 9 \\ -3 & 6 & 2 & 4 & 5 & 2 & 8 & -9 & 3 & 1 \\ -3 & 3 & 5 & 9 & 14 & 16 & 24 & 15 & 18 & 19 \end{matrix}]$$

Query

L	R	sum(L to R)	
4	8	$P[8] - P[3]$	$18 - 9 = 9$
3	7	$P[7] - P[2]$	$15 - 5 = 10$
1	3	$P[3] - P[0]$	12
0	4	$P[4]$	14
7	7	$P[7] - P[6]$	$15 - 24 = -9$

$$\text{sum}[L, R] = P[R] - P[L-1]$$

if $L == 0$ $P[R]$

Optimized

1 3 6 2 4 5 2 8 9 3 1]

```
// Create Prefix sum array  
P[N] // initialize prefix sum  
P[0] = A[0]  
for i → 1 to N-1 {  
    P[i] = P[i-1] + A[i]  
}
```

TC: O(N)
SC: O(N)

```

for q → 0 to Q-1 { → Q times
    l = L[q]
    r = R[q]
    sum = 0
    if (l == 0) {
        sum = P[r]
    } else {
        sum = P[r] - P[l-1]
    }
    print(sum)
}

```

TC : $O(N+Q)$

SC : $O(N)$

$$\begin{aligned}
 A &= [1 \ 2 \ 3 \ \dots] \\
 L &= [0, 1, 1, 3, 2, 1] \\
 R &= [0, 2, 3, 3, 2, 3]
 \end{aligned}$$

$$\begin{aligned}
 A &= [1 \ \cancel{3} \ \cancel{6} \ \cancel{10}] \\
 P &= [1 \ 3 \ 6 \ 10]
 \end{aligned}$$

Can we improve space complexity ?

Yes we use the given $A[]$ as prefix sum array .

SC : $O(1)$

22:35

~~$A[0] = A[0]$~~

```

for i → 1 to N-1 {
    A[i] = A[i-1] + A[i]
}

```

TC

Given an array of size N and Q queries with start L and end R index.

Print the sum of all even indexed elements from L-R

$$A = [\begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 \\ 2 & 3 & 1 & 6 & 4 & 5 \end{matrix}]$$

<u>Query</u>		even indexed	
L	R	sum(L to R)	
1	3	1	1 2 3 3 1 6
2	5	5	
0	4	7	
3	3	0	

Bruteforce for every query iterate from $l \rightarrow r$
 if ($i \% 2 == 0$) → add to sum
 else ignore

$$A = [\begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 \\ 2 & 3 & 1 & 6 & 4 & 5 \end{matrix}]$$

$$P = [\begin{matrix} 2 & 2 & 3 & 3 & 7 & 7 \end{matrix}]$$

```
// Create Prefix sum array
P[N] // initialize prefix sum
P[0] = A[0]
for i → 1 to N-1 {
```

```

val = 0
if ( $i \% 2 == 0$ ) { // i at even index
    val = A[i]
}

```

$$P[i] = P[i-1] + \text{val} \quad \text{val} = 0$$

3

$$A = [\begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 \\ 2 & 3 & 1 & 6 & 4 & 5 \end{matrix}]$$

$$P = [\begin{matrix} 2 & 2 & 3 & 3 & 7 & 7 \end{matrix}]$$

Quiz \longrightarrow

0	1	2	3	4
2	4 ⁰	3	10 ⁵	5
2	2	5	5	10

$$A = [\begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 \\ 2 & 3 & 1 & 6 & 4 & 5 \end{matrix}]$$

$$P = [\begin{matrix} 2 & 2 & 3 & 3 & 7 & 7 \end{matrix}]$$

<u>Query</u>		even indexed	$\text{sum}(L \text{ to } R) = P[R] - P[L-1]$
L	R	$\text{sum}(L \text{ to } R)$	
1	3	$P[3] - P[0]$	$= 3 - 2 = 1$
2	5	$P[5] - P[1]$	$= 7 - 2 = 5$
0	4	$P[4]$	$= 7$
3	3	$P[3] - P[2]$	$= 3 - 3 = 0$

Pseudocode

```
// calculate Psum  
for qv → 0 to Q-1 { ← Q times  
    l = L[qv]  
    r = R[qv]  
    sum = 0  
    if (l==0) {  
        sum = P[r]  
    } else {  
        sum = P[r] - P[l-1]  
    }  
    print(sum)  
}
```

TC: O(N+Q)

Given an array of size N and Q queries with start L and end R index.

Print the sum of all odd indexed elements from L-R

$$A = [\begin{matrix} 0 & 1 & 2 & 3 & 4 & 5 \\ 2 & 3 & 1 & 6 & 4 & 5 \end{matrix}]$$

```
// Create Prefix sum array  
P[N] // initialize prefix sum  
P[0] = 0  
for i → 1 to N-1 {  
    val = 0  
    if (i%2 == 1) { // i at odd index  
        val = A[i]  
    }  
    P[i] = P[i-1] + val  
}
```

Special Index

Given an array of size N, count the no. of special index in the array.

Special indices are those after removing them

sum of all odd indexed elements = = sum of all even indexed elements

NOTE : after removal of index , indices will change

$$A = [4 \ 3 \ 2 \ 7 \ 6 \ -2]$$

i°	A	S_0	$= =$	S_E	cnt
0	3 2 7 6 -2 0 1 2 3 4 5	8	$= =$	8	+1
1	4 2 7 6 -2 0 1 2 3 4	8	\neq	9	
2	4 3 7 6 -2 0 1 2 3 4	9	$= =$	9	+1
3	4 3 2 6 -2 0 1 2 3 4	9	\neq	4	
4	4 3 2 7 -2 0 1 2 3 4	10	\neq	4	
5	4 3 2 7 6 0 1 2 3 4	10	\neq	12	

cnt = 2

$A =$	4	1	3	7	10	remove $i=2$
	0	1	2	3	4	
	0	1	7	10	3	sum of odd idx = 11

$A =$	0	1	2	3	4	-1	6	-2	7	8	9	8	remove $i=3$
	2	3	1	0	-1	2	-2	10	8	0	1	2	
	0	1	2	3	4	5	6	7	8	0	1	2	

sum of odd idx = 15

2	3	1	0	-1	2	-2	10	8
0	1	2	3	4	5	6	7	8

sum of all even idx = 8

Observation

$A =$	0	1	2	3	4	5	6	7	8	9	8	remove $i=3$	
	2	3	1	0	-1	2	-2	10	8	0	1	2	
	0	1	2	3	4	5	6	7	8	0	1	2	

sum of all odd idx

$$\begin{aligned}\text{sum of all odd idx} &= \text{sum of all odd idx (0-2)} \\ &\quad + \text{sum of all even idx (4-9)}\end{aligned}$$

$PO \rightarrow$ Prefix sum for all odd idx

$PE \rightarrow$ Prefix sum for all even idx

$$= PO[2] + PE[9] - PE[3]$$

$$\begin{aligned}\text{sum of all even idx} &= \text{sum of all even idx (0-2)} \\ &\quad + \text{sum of all odd idx (4-9)}\end{aligned}$$

$A =$	2	3	1	3	4	-5	6	-2	8	10	8
	2	3	1	0	-1	2	-2	10	8		
	0	1	2	3	4	5	6	7	8		

sum of all odd after removing i^{th} idx

$$\begin{aligned}&= \text{sum of odd (0, } i-1) + \text{sum of even (i+1, N-1)} \\ &\quad \text{PO}[i-1] + PE[N-1] - PE[i]\end{aligned}$$

sum of all even after removing i^{th} idx

$$= \text{sum of even (0, } i-1) + \text{sum of all odd (i+1, N-1)}$$

$$= PE[i-1] + PO[N-1] - PO[i]$$

Pseudocode

```
// PS for odd idx      PO[N]
// PS for even idx      PE[N]
se → sum of even idx
so → sum of odd idx
cnt = 0
for i → 0 to N-1 {
    if (i == 0) {
        so = PE[N-1] - PE[i]
        se = PO[N-1] - PO[i]
    } else {
        so = PO[i-1] + PE[N-1] - PE[i]
        se = PE[i-1] + PO[N-1] - PO[i]
    }
    if (se == so) {
        cnt += 1
    }
}
print(cnt)
```

TC : O(N)
SC : O(N)

0 1 2 3

$$\begin{array}{ccccccc}
 & 1 & 2 & 3 & \cancel{4} & \\
 & PO[2] & & & PE[3] - PE[3] & 0 \\
 & PO[i-1] & + & PE[N-1] - PE[i] & \\
 & PE[i-1] & + & PO[N-1] - PO[i] & \\
 & PE[2] & + & 0 &
 \end{array}$$

