

CoreJava Questions, Options & Answers

Q1. Carefully read the question and answer accordingly.

What will be the output for following code?

```
class Super
{
    static void show()
    {
        System.out.println("super class show method");
    }
    static class StaticMethods
    {
        void show()
        {
            System.out.println("sub class show method");
        }
    }
    public static void main(String[]args)
    {
        Super.show();
        new Super.StaticMethods().show();
    }
}
```

- A. super class show method sub class show method
- B. super class show method
- C. sub class show method super class show method
- D. Compilation Error

Answer: super class show method sub class show method

Q2. Carefully read the question and answer accordingly.

When one method is overridden in sub class the access specifier of the method in sub class should be equal as method in super class.

State True or False.

- A. FALSE

B. TRUE

Answer: FALSE

Q3. Carefully read the question and answer accordingly.

A class can be declared as _____ if you do not want the class to be subclassed. Using the _____ keyword we can abstract a class from its implementation

A. protected ,interface

B. final,interface

C. public,friend

D. final,protected

E. private,abstract

Answer: final,interface

Q4. Carefully read the question and answer accordingly.

The constructor of a class must not have a return type.

A. TRUE

B. FALSE

Answer: FALSE

Q5. Carefully read the question and answer accordingly.

Which of the following are true about constructors?

A. Constructors can be overloaded

B. Constructors can be overridden.

C. Constructor is a special type of method which may have return type.

D. Constructors should be called explicitly like methods

Answer: Constructors can be overloaded

Q6. Carefully read the question and answer accordingly.

A field with default access specifier can be accessed out side the package.

State True or False.

A. FALSE

B. TRUE

Answer: FALSE

Q7. Carefully read the question and answer accordingly.

_____ determines which member of a class can be used by other classes.

A. specifier

B. Inheritance

C. Implementation

D. Access specifier

E. Class

Answer: Access specifier

Q8. Carefully read the question and answer accordingly.

Which of the following statements are true about Method Overriding?

I: Signature must be same including return type

II: If the super class method is throwing the exception then overriding method should throw the same Exception

III: Overriding can be done in same class

IV: Overriding should be done in two different classes with no relation between the classes

A. I

B. II & IV

C. III

D. I & III

Answer: I

Q9. Carefully read the question and answer accordingly.

If display method in super class has a protected specifier then what should be the specifier for the overriding display method in sub class?

A. protected or default

B. protected or public

C. None of the listed options

D. private

Answer: protected or public

Q10. Carefully read the question and answer accordingly.

What will be the output for following code?

```
class Super
{
    int num=20;
    public void display()
    {
        System.out.println("super class method");
    }
}

public class ThisUse extends Super
{
    int num;
    public ThisUse(int num)
    {
        this.num=num;
    }
    public void display()
    {
        System.out.println("display method");
    }
    public void Show()
    {
        this.display();
        display();
        System.out.println(this.num);
        System.out.println(num);
    }
    public static void main(String[] args)
    {
        ThisUse o=new ThisUse(10);
        o.Show();
    }
}
```

```
}
```

A. super class method display method 20 20

B. display method display method 10 10

C. display method display method 20 20

D. super class method display method 10 10

Answer: display method display method 10 10

Q11. Carefully read the question and answer accordingly.

What will be the output of following code?

```
class Super2
{
    public void display()
    {
        System.out.println("super class display method");
    }
    public void exe()
    {
        System.out.println("super class exe method");
        display();
    }
}

public class InheritMethod extends Super2
{
    public void display()
    {

        System.out.println("sub class display method");
    }

    public static void main(String [] args)
    {

        InheritMethod o=new InheritMethod();

        o.exe();
    }
}
```

```
}
```

```
}
```

- A. super class exe method sub class display method
- B. super class exe method super class display method
- C. Compilation error
- D. None of the listed options

Answer: super class exe method sub class display method

Q12. Carefully read the question and answer accordingly.

Which of the following method is used to initialize the instance variable of a class.

- A. Class
- B. Public
- C. Constructor
- D. Destructor
- E. Variable

Answer: Constructor

Q13. Carefully read the question and answer accordingly.

Which of the following are true about protected access specifier?

- A. If one class is having protected method then the method is available for subclass which is present in another package
- B. A class can be declared as protected.
- C. All members of abstract class are by default protected
- D. Protected is default access modifier of a child class

Answer: If one class is having protected method then the method is available for subclass which is present in another package

Q14. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class Variables
{
public static void main(String[]args)
{
public int i=10;
System.out.println(i++);
}
}
```

- A. 10
- B. 11
- C. Compilation error
- D. None of the listed options

Answer: Compilation error

Q15. Carefully read the question and answer accordingly.

Constructor of an class is executed each time when an object of that class is created

- A. TRUE
- B. FALSE

Answer: TRUE

Q16. Carefully read the question and answer accordingly.

Which of the following correctly fits for the definition 'holding instances of other objects'?

- A. Aggregation
- B. Composition
- C. Generic
- D. Polymorphic

Answer: Aggregation

Q17. Carefully read the question and answer accordingly.

```
public abstract class Shape
{
```

```
private int x;  
private int y;  
public abstract void draw();  
public void setAnchor(int x, int y)  
{  
    this.x = x;  
    this.y = y;  
}  
}
```

Which two classes use the Shape class correctly?

1. public class Circle implements Shape {
 private int radius;
}
2. public abstract class Circle extends Shape {
 private int radius;
}
3. public class Circle extends Shape {
 private int radius;
 public void draw();
}
4. public class Circle extends Shape {
 private int radius;
 public void draw() { /* code here */ }
}

- A. 1&2
- B. 1&3
- C. 2&3
- D. 3&4
- E. 2&4

Answer: 2&4

Q18. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

If any method overrides one of its super class methods, we can invoke the overridden method through the this keyword.

- A. TRUE
- B. FALSE

Answer: FALSE

Q19. Carefully read the question and answer accordingly.

What will be the output for following code?

```
class super3{
int i=10;
public super3(int num){
i=num;
}
}
public class Inherite1 extends super3{
public Inherite1(int a){
super(a);
}
public void Exe(){
System.out.println(i);
}
}
public static void main(String[]args){
Inherite1 o=new Inherite1(50);
super3 s=new Inherite1(20);
System.out.println(s.i);
o.Exe();
}
}
```

- A. 10 50
- B. 20 50
- C. 20 10
- D. 10 20

Answer: 20 50

Q20. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

An abstract class cannot contain non abstract methods

A. TRUE

B. FALSE

Answer: FALSE

Q21. Carefully read the question and answer accordingly.

What is the output of below code:

```
package p1;
class Parent {
    public static void doWork() {
        System.out.println("Parent");
    }
}
class Child extends Parent {
    public static void doWork() {
        System.out.println("Child");
    }
}
class Test {
    public static void main(String[] args) {
        Child.doWork();
    }
}
```

A. Child Parent

B. Parent

C. Child

D. Parent Child

Answer: Child

Q22. Carefully read the question and answer accordingly.

```
interface A
{
    public abstract void aM1();
}
```

```
public abstract void aM2();
}
interface B extends A
{
public void bM1();
public void bM2();
}
public class Demo extends Object implements B
{
}
```

In above scenario class Demo must override which methods?

- A. public void aM1(){} public void aM2(){}
- B. public void bM1(){} public void bM2(){}
- C. public void aM1(){} public void aM2(){} public void bM1(){} public void bM2(){}
- D. public void aM1(){} public void bM2(){}

Answer: public void aM1(){} public void aM2(){} public void bM1(){} public void bM2(){}

Q23. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

The below code will compile & provide desired output:

```
package p1;
interface Bounceable {
void bounce();
void setBounceFactor(int bf);
private class BusinessLogic
{
int var1;
float var2;
double result(int var1,float var2){
return var1*var2;
}
}
}
class Test {
public static void main(String[] args) {
```

```
System.out.println(new Bounceable.BusinessLogic().result(12,12345.22F));  
}  
}
```

- A. TRUE
- B. FALSE

Answer: FALSE

Q24. Carefully read the question and answer accordingly.

Choose the correct option.

Statement I: When an abstract class is sub classed, the subclass should provide the implementation for all the abstract methods in its parent class.

Statement II: If the subclass does not implement the abstract method in its parent class, then the subclass must also be declared abstract.

- A. Statement I & II are TRUE
- B. Statement I is TRUE & II is FALSE
- C. Statement I is FALSE & II is TRUE
- D. Statement I & II are FASLE

Answer: Statement I & II are TRUE

Q25. Carefully read the question and answer accordingly.

Choose the correct option.

Statement I: A subclass inherits all of the “public” and “protected” members of its parent, no matter what package the subclass is in.

Statement II: If the subclass of any class is in the same package then it inherits the default access members of the parent.

- A. Statement I & II are TRUE
- B. Statement I is TRUE & II is FALSE
- C. Statement I is FALSE & II is TRUE
- D. Statement I & II are FASLE

Answer: Statement I & II are TRUE

Q26. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

The below code will compile & provide desired output:

```
package p1;
class Parent {
private int doWork(){
System.out.println("Do Work - Parent");
return 0;
}
}
class Child extends Parent {
public void doWork(){
System.out.println("Do Work - Child");
}
}
class Test{
public static void main(String[] args) {
new Child().doWork();
}
}
```

A. TRUE

B. FALSE

Answer: TRUE

Q27. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

If any class has at least one abstract method you must declare it as abstract class

A. TRUE

B. FALSE

Answer: TRUE

Q28. Carefully read the question and answer accordingly.

public interface Status

{

/* insert code here */ int MY_VALUE = 10;

```
}
```

Which are valid on commented line?

- 1.final
- 2.static
- 3.native
- 4.public

- A. 1&2
- B. 1&2&3
- C. 2&3
- D. 1&2&4
- E. 2&4

Answer: 1&2&4

Q29. Carefully read the question and answer accordingly.

Choose the correct option.

Statement I: When all methods in a class are abstract the class can be declared as an interface.

Choose the correct option.

Statement II: An interface defines a contract for classes to implement the behavior.

- A. Statement I & II are TRUE
- B. Statement I is TRUE & II is FALSE
- C. Statement I is FALSE & II is TRUE
- D. Statement I & II are FASLE

Answer: Statement I & II are TRUE

Q30. Carefully read the question and answer accordingly.

abstract class Vehicle

```
{  
    public int speed()  
{  
    return 0;  
}  
}
```

```
class Car extends Vehicle
{
    public int speed()
    {
        return 60;
    }
}
class RaceCar extends Car
{
    public int speed()
    {
        return 120;
    }
}
public class Demo
{
    public static void main(String [] args)
    {
        RaceCar racer = new RaceCar();
        Car car = new RaceCar();
        Vehicle vehicle = new RaceCar();
        System.out.println(racer.speed() + ", " + car.speed()+" , " + vehicle.speed());
    }
}
```

What is the result?

- A. 0, 0, 0
- B. 120, 60, 0
- C. 60,60,60
- D. 120, 120, 120

Answer: 120, 120, 120

Q31. Carefully read the question and answer accordingly.

What will be the output for following code

```
public class
MethodOverloading {
```

```

int m=10,n;
public void div(int a) throws Exception{
n=m/a;
System.out.println(n);
}
public void div(int a,int b) {
n=a/b;
}
public static void main(String[]args) throws Exception{
MethodOverloading o=new MethodOverloading();
o.div(0);
o.div(10,2);
}
}

```

- A. It will print ArithmeticException and prints 5
- B. It will give ArithmeticException
- C. It will print 5
- D. None of the listed options

Answer: It will give ArithmeticException

Q32. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

The below code will compile & provide desired output:

```

package p1;
abstract class LivingThings{
public abstract void resperate();
interface Living
{
public abstract void walk();
}
}
class Human implements LivingThings.Living{
@Override
public void walk() {
System.out.println("Human Can Walk");
}
}

```



```
}  
}  
class Test {  
    public static void main(String[] args) {  
        new Human().walk();  
    }  
}
```

- A. TRUE
- B. FALSE

Answer: TRUE

Q33. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

An overriding method can also return a subtype of the type returned by the overridden method.

- A. TRUE
- B. FALSE

Answer: TRUE

Q34. Carefully read the question and answer accordingly.

```
abstract public class Employee  
{  
    protected abstract double getSalesAmount();  
    public double getCommision() {  
        return getSalesAmount() * 0.15;  
    }  
}  
class Sales extends Employee  
{  
    // insert method here  
}
```

Which two methods, inserted independently, correctly complete the Sales class?

1. double getSalesAmount() { return 1230.45; }
2. public double getSalesAmount() { return 1230.45; }

3.private double getSalesAmount() { return 1230.45; }
4.protected double getSalesAmount() { return 1230.45; }

- A. 1&2
- B. 1&3
- C. 2&3
- D. 3&4
- E. 2&4

Answer: 2&4

Q35. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

The below code will compile & provide desired output:

```
package p1;  
interface A {  
    public abstract void methodOne();  
}  
interface B extends A {  
    public abstract void methodTwo();  
}  
class C implements B{  
    @Override  
    public void methodTwo() {  
        System.out.println("Method Two Body");  
    }  
}  
class Test {  
    public static void main(String[] args) {  
        new C().methodTwo();  
    }  
}
```

- A. TRUE
- B. FALSE

Answer: FALSE

Q36. Carefully read the question and answer accordingly.

interface B

```
{  
public void bM1();  
public void bM2();  
}
```

abstract class A implements B

```
{  
public abstract void aM1();  
public abstract void aM2();  
public void bM1(){}  
}
```

public class Demo extends A

```
{  
}
```

In above scenario class Demo must override which methods?

- A. public void aM2(){}
B. public void aM1(){}
C. public void bM2(){}
D. All of the listed options

Answer: All of the listed options

Q37. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

Interface can be used when common functionalities have to be implemented differently across multiple classes.

- A. TRUE
B. FALSE

Answer: TRUE

Q38. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

The below code will compile & provide desired output:

```
package p1;
interface A {
    public abstract void methodOne();
}
interface B{
    public abstract void methodTwo();
}
interface C{
    public abstract void methodTwo();
}
class D implements B,C,A{
    public void methodOne(){}
    public void methodTwo(){ System.out.println("Method Two");}
}
class Test {
    public static void main(String[] args) {
        new D().methodTwo();
    }
}
```

A. TRUE

B. FALSE

Answer: TRUE

Q39. Carefully read the question and answer accordingly.

```
public class Person
{
    private String name;
    public Person(String name) { this.name = name; }
    public boolean equals(Person p)
    {
        return p.name.equals(this.name);
    }
}
```

Which statement is true?

A. The equals method does NOT properly override the Object class's equals method.

- B. Compilation fails because the private attribute p.name cannot be accessed.
- C. This class must also implement the hashCode method as well.
- D. The code will compile as Object class's equals method is overridden.

Answer: The equals method does NOT properly override the Object class's equals method.

Q40. Carefully read the question and answer accordingly.

Which of the following keywords ensures that a method cannot be overridden?

- A. final
- B. protected
- C. static
- D. abstract

Answer: final

Q41. Carefully read the question and answer accordingly.

What is the output of below code:

```
package p1;
abstract class LivingThings{
    public abstract int walk();
}
class Human extends LivingThings{
    @Override
    public void walk() {
        System.out.println("Human Can Walk");
    }
}
class Test {
    public static void main(String[] args) {
        new Human().walk();
    }
}
```

- A. Human Can Walk
- B. Compilation Error
- C. Runtime Exception

D. No Output will be displayed

Answer: Compilation Error

Q42. Carefully read the question and answer accordingly.

What will be the output of following code?

```
class InterfaceDemo
{
    public static void main(String [] args)
    {
        new DigiCam().doCharge();
        new DigiCam(){
            public void writeData (String msg)
            {
                System.out.println("You are Sending: "+msg);
            }
        }.writeData("MyFamily.jpg");
    } //main
}

interface USB
{
    int readData();
    void writeData(String input);
    void doCharge();
}

abstract class DigiCam implements USB
{
    public int readData(){ return 0;}
    public void writeData(String input){}
    public void doCharge()
    {
        System.out.println("DigiCam do Charge");
    }
}
```

A. DigiCam do Charge You are Sending: MyFamily.jpg

B. Compilation Error

C. DigiCam do Charge

D. Runtime Error

Answer: DigiCam do Charge You are Sending: MyFamily.jpg

Q43. Carefully read the question and answer accordingly.

What is the output of below code:

```
package p1;
public class Test {
public static void main(String[] args) {
Test t1 = new Test();
Test t2 = new Test();
if (!t1.equals(t2))
System.out.println("they're not equal");
if (t1 instanceof Object)
System.out.println("t1's an Object");
}
}
```

- A. they're not equal
- B. t1's an Object
- C. they're not equal t1's an Object
- D. No Output Will be Displayed

Answer: they're not equal t1's an Object

Q44. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

A concrete class can extend more than one super class whether that super class is either concrete or abstract class

- A. TRUE
- B. FALSE

Answer: FALSE

Q45. Carefully read the question and answer accordingly.

```
public class Client1
{
public static void main(String [] args)
```

```

{
PenDrive p;
PenDrive.Vendor v1=new PenDrive.Vendor("WD",500);
System.out.println(v1.getName());
System.out.println(v1.getPrice());
}
}
class PenDrive
{
static class Vendor
{
String name;
int price;
public String getName(){ return name;}
public int getPrice(){ return price;}

Vendor(String name,int price)
{
this.name=name;
this.price=price;
}
}
}

```

What will be the output of the given code?

- A. Class cannot be defined inside another class
- B. Runtime Error.
- C. WD 500
- D. Compile Error.

Answer: WD 500

Q46. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

The super() call can only be used in constructor calls and not method calls.

- A. TRUE

B. FALSE

Answer: TRUE

Q47. Carefully read the question and answer accordingly.

Abstract classes can be used when

Statement I: Some implemented functionalities are common between classes

Statement II: Some functionalities need to be implemented in sub classes that extends the abstract class

A. Statement I & II are TRUE

B. Statement I is TRUE & II is FALSE

C. Statement I is FALSE & II is TRUE

D. Statement I & II are FALSE

Answer: Statement I & II are TRUE

Q48. Carefully read the question and answer accordingly.

class InterfaceDemo

```
{  
public static void main(String [] args)  
{  
DigiCam cam1=new DigiCam();  
cam1.doCharge();  
}//main  
}
```

interface USB

```
{  
int readData();  
boolean writeData(String input);  
void doCharge();  
}
```

class DigiCam implements USB

```
{  
public int readData(){ return 0;}  
public boolean writeData(String input){ return false; }  
void doCharge(){ return;}  
}
```

Which of the following is correct with respect to given code?

- A. Code will not compile due to weaker access privilege.
- B. Code will Compile without any Error
- C. Code will compile but wont print any message
- D. Runtime Exception

Answer: Code will not compile due to weaker access privilege.

Q49. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

Object class provides a method named getClass() which returns runtime class of an object.

- A. TRUE
- B. FALSE

Answer: TRUE

Q50. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class VariableDec1
{
    public static void main(String[]args)
    {
        int l=32;
        char c=65;
        char a=c+l;
        System.out.println(a);
    }
}
```

- A. 97
- B. a
- C. compilation error
- D. None of the listed options

Answer: compilation error

Q51. Carefully read the question and answer accordingly.

Which of the following code snippets make objects eligible for Garbage Collection?

Statement A: `String s = "new string"; s = s.replace('e', '3');`

Statement B: `String replaceable = "replaceable"; StringBuffer sb = new StringBuffer(replaceable); replaceable = null; sb = null;`

- A. Both Statements A and B
- B. Statement A alone
- C. Statement B alone
- D. Neither Statements A nor B

Answer: Both Statements A and B

Q52. Carefully read the question and answer accordingly.

Members of the classs are accessed by _____ operator

- A. address
- B. dot
- C. scope resolution
- D. none of these

Answer: dot

Q53. Carefully read the question and answer accordingly.

Which of the following is the correct syntax for suggesting that the JVM to performs garbage collection?

- A. `System.free();`
- B. `System.setGarbageCollection();`
- C. `System.out.gc();`
- D. `System.gc();`

Answer: `System.gc();`

Q54. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class VariableDec
{
    public static void main(String[]args)
```

```
{
int x = 1;
if(x>0 )
x = 3;
switch(x)
{
case 1: System.out.println(1);
case 0: System.out.println(0);
case 2: System.out.println(2);
break;
case 3: System.out.println(3);
default: System.out.println(4);
break;
}
}
}
```

- A. 1 0 2
- B. 3 4
- C. 4
- D. Compilation error

Answer: 3 4

Q55. Carefully read the question and answer accordingly.

_____ Operator is used to create an object.

- A. class
- B. new
- C. print
- D. main
- E. Object

Answer: new

Q56. Carefully read the question and answer accordingly.

Which of the following is not the Java keyword?

- A. extends
- B. implements
- C. throwed
- D. Integer
- E. Boolean

Answer: throwed

Q57. Carefully read the question and answer accordingly.

Find the keyword(s) which is not used to implement exception

- A. try
- B. catch
- C. finally
- D. access
- E. exception

Answer:

Q58. Carefully read the question and answer accordingly.

The ++ operator postfix and prefix has the same effect

- A. TRUE
- B. FALSE

Answer: FALSE

Q59. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class Operators
{
    public static void main(String[]args)
    {
        int i=12;
```

```
int j=13;
int k=++i-j--;
System.out.println(i);
System.out.println(j);
System.out.println(k);
}
}
```

A. 12,12,-1

B. 13,12,0

C. 13,13,0

D. 12,13,-1

Answer: 13,12,0

Q60. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class Variabledec {
    public static void main(String[]args){
        boolean x = true;
        int a;
        if(x) a = x ? 2: 1;
        else a = x ? 3: 4;
        System.out.println(a);
    }
}
```

A. 1

B. 3

C. 4

D. 2

Answer: 2

Q61. Carefully read the question and answer accordingly.

What is the correct structure of a java program?

I: import statement

II: class declaration

III: package statement

IV: method,variable declarations

A. III->I->II->IV.

B. I->III->II->IV

C. I->III->IV->II

D. I->II->III->IV

Answer: III->I->II->IV.

Q62. Carefully read the question and answer accordingly.

Garbage collector thread is a daemon thread.

State True or False.

A. TRUE

B. FALSE

Answer: TRUE

Q63. Carefully read the question and answer accordingly.

Garbage collection guarantee that a program will not run out of memory. State True or False.

A. FALSE

B. TRUE

Answer: FALSE

Q64. Carefully read the question and answer accordingly.

Statement A:finalize will always run before an object is garbage collected

Statement B:finalize method will be called only once by the garbage collector

which of the following is true?

A. Both Statements A and B are true

B. Statement A is true and Statement B is false

C. Statement A is false and Statement B is true

D. Both Statements A and B are false

Answer: Both Statements A and B are true

Q65. Carefully read the question and answer accordingly.

After which line the object initially referred by str ("Hello" String object) is eligible for garbage collection?

```
class Garbage{  
    public static void main(string[]args){  
        line 1:String str=new String("Hello");  
        line 2. String str1=str;  
        line 3.str=new String("Hi");  
        line 4.str1=new String("Hello Again");  
        5.return;  
    }  
}
```

- A. line 3
- B. line 4
- C. line 5
- D. line 1

Answer: line 4

Q66. Carefully read the question and answer accordingly.

How can you force garbage collection of an object?

- 1.Garbage collection cannot be forced
- 2.Call System.gc().
- 3.Call Runtime.gc().
- 4. Set all references to the object to new values(null, for example).

- A. Option 2
- B. Option 3
- C. Option 1
- D. Option 4

Answer: Option 1

Q67. Carefully read the question and answer accordingly.

Which of the below is invalid state of thread?

- A. Runnable
- B. Running
- C. Dead
- D. Blocked
- E. Stop

Answer: Stop

Q68. Carefully read the question and answer accordingly.

Predict the output of below code:

```
package p1;
class MyThread extends Thread {
    public void run(int a) {
        System.out.println("Important job running in MyThread");
    }
    public void run(String s) {
        System.out.println("String in run");
    }
}
class Test {
    public static void main(String[] args) {
        MyThread t1=new MyThread();
        t1.start();
    }
}
```

- A. Compile Error
- B. Important job running in MyThread
- C. String in run
- D. Important job running in MyThread String in run
- E. No Output

Answer: No Output

Q69. Carefully read the question and answer accordingly.

Which of these is not a benefit of Multithreading?

- A. Reduce response time of process.
- B. Support parallel operation of functions.
- C. Increase system efficiency.
- D. Requires less overheads compared to multitasking.
- E. None of the options.

Answer: None of the options.

Q70. Carefully read the question and answer accordingly.

You have created a Timeout class as an extension of Thread, the purpose of which is to print a "Time's Over" message if the Thread is not interrupted within 10 seconds of being started. Here is the run method that you have coded:

```
public void run() {  
    System.out.println("Start!");  
    try {  
        Thread.sleep(10000);  
        System.out.println("Time's Over!");  
    } catch (InterruptedException e) {  
        System.out.println("Interrupted!");  
    }  
}
```

} Given that a program creates and starts a Timeout object, which of the following statements is true?

- A. Exactly 10 seconds after the start method is called, "Time's Over!" will be printed.
- B. Exactly 10 seconds after the "Start!" is printed, "Time's Over!" will be printed.
- C. The delay between "Start!" being printed and "Time's Over!" will be 10 seconds plus or minus one tick of the system clock.
- D. If "Time's Over!" is printed, you can be sure that at least 10 seconds have elapsed since "Start!" was printed.

Answer: If "Time's Over!" is printed, you can be sure that at least 10 seconds have elapsed since "Start!" was printed.

Q71. Carefully read the question and answer accordingly.

Synchronization is achieved by using which of the below methods

- A. Synchronized blocks
- B. Synchronized methods

- C. Synchronized classes
- D. Synchronized abstract classes
- E. Synchronized interfaces

Answer:

Q72. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

The below code will compile & provide desired output:

```
package p1;
class MyThread extends Thread {
    public void run() {
        System.out.println("Important job running in MyThread");
    }
    public void run(String s) {
        System.out.println("String in run is " + s);
    }
}
class Test {
    public static void main(String[] args) {
        MyThread t1=new MyThread();
        t1.start();
    }
}
```

- A. TRUE
- B. FALSE

Answer: TRUE

Q73. Carefully read the question and answer accordingly.

What will be the output of below code:

```
package p1;
class MyThread extends Thread {
    public void run() {
        System.out.println("Important job running in MyThread");
    }
}
```

```
class Test {  
    public static void main(String[] args) {  
        MyThread t1=new MyThread();  
        t1.run();  
    }  
}
```

- A. Compile Error
- B. Important job running in MyThread
- C. Runtime Exception
- D. Non of the options

Answer: Important job running in MyThread

Q74. Carefully read the question and answer accordingly.

```
public class Threads  
{  
    public static void main (String[] args)  
    {  
        new Threads().go();  
    }  
    public void go()  
    {  
        Runnable r = new Runnable()  
        {  
            public void run()  
            {  
                System.out.print("Run");  
            }  
        };  
    }  
};
```

```
Thread t = new Thread(r);  
t.start();  
t.start();  
}  
}
```

What will be the result?

- A. An exception is thrown at runtime.
- B. The code executes normally and prints "Run".
- C. The code executes normally, but nothing is printed.
- D. Compilation fails.

Answer: An exception is thrown at runtime.

Q75. Carefully read the question and answer accordingly.

Inter thread communication is achieved using which of the below methods?

- A. wait()
- B. notify()
- C. notifyAll()
- D. all the options

Answer: all the options

Q76. Carefully read the question and answer accordingly.

Which of these is not valid method in Thread class

- A. void run()
- B. void start()
- C. boolean getPriority()
- D. boolean isAlive()

Answer: boolean getPriority()

Q77. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

Threads are small process which run in shared memory space within a process.

- A. TRUE
- B. FALSE

Answer: TRUE

Q78. Carefully read the question and answer accordingly.

Which of the following statements are true?

Statement1: When a thread is sleeping as a result of sleep(), it releases its locks.

Statement2: The Object.wait() method can be invoked only from a synchronized context.

A. Statement1 is TRUE but Statement2 is FALSE.

B. Statement2 is TRUE but Statement1 is FALSE.

C. BOTH Statement1 & Statement2 are TRUE.

D. BOTH Statement1 & Statement2 are FALSE.

Answer: Statement2 is TRUE but Statement1 is FALSE.

Q79. Carefully read the question and answer accordingly.

Which two statements are true?

1.It is possible for more than two threads to deadlock at once.

2.The JVM implementation guarantees that multiple threads cannot enter into a deadlocked state.

3.Deadlocked threads release once their sleep() method's sleep duration has expired.

4.If a piece of code is capable of deadlocking, you cannot eliminate the possibility of deadlocking by inserting invocations of Thread.yield().

A. 1&2

B. 1&3

C. 2&3

D. 1&4

E. 2&4

Answer: 1&4

Q80. Carefully read the question and answer accordingly.

public class TestDemo implements Runnable

{

public void run()

{

System.out.print("Runner");

}

```

public static void main(String[] args)
{
    Thread t = new Thread(new TestDemo());
    t.run();
    t.run();
    t.start();
}
}

```

What will be the result?

- A. You cannot call run() method using Thread class object.
- B. An exception is thrown at runtime.
- C. The code executes and prints "Runner".
- D. The code executes and prints "RunnerRunnerRunner".

Answer: The code executes and prints "RunnerRunnerRunner".

Q81. Carefully read the question and answer accordingly.

```

class Background implements Runnable{
    int i = 0;
    public int run(){
        while (true) {
            i++;
            System.out.println("i="+i);
        }
        return 1;
    }
}
//End class

```

- A. It will compile and the run method will print out the increasing value of i.
- B. It will compile and calling start will print out the increasing value of i.
- C. The code will cause an error at compile time.
- D. Compilation will cause an error because while cannot take a parameter of true.

Answer: The code will cause an error at compile time.

Q82. Carefully read the question and answer accordingly.

Java provides _____ ways to create Threads.

- A. One
- B. Two
- C. Three
- D. Four

Answer: Two

Q83. Carefully read the question and answer accordingly.

As per the below code find which statements are true.

```
public class Test {  
    public static void main(String[] args) {  
        Line 1: ArrayList<String> myList=new List<String>();  
        Line 2: String string = new String();  
        Line 3: myList.add("string");  
        Line 4: int index = myList.indexOf("string");  
        System.out.println(index);  
    }  
}
```

- A. Line 1 has compilation error
- B. Line 2 has run time exceptions
- C. In Line 4 null pointer exception will occur as String string contains null value
- D. Line 4 has neither error nor exceptions.

Answer:

Q84. Carefully read the question and answer accordingly.

The ArrayList<String> is immutable.

- A. TRUE
- B. FALSE

Answer: FALSE

Q85. Carefully read the question and answer accordingly.

Map is the super class of Dictionary class?

A. TRUE

B. FALSE

Answer: FALSE

Q86. Carefully read the question and answer accordingly.

Method keySet() in Map returns a set view of the keys contained in that map.

State True or False.

A. TRUE

B. FALSE

Answer: TRUE

Q87. Carefully read the question and answer accordingly.

Is "Array" a subclass of "Collection" ?

A. TRUE

B. FALSE

Answer: FALSE

Q88. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class Compare
{
    public static void main(String[]args)
    {
        String s=new String("abc");
        String s1=new String("abc");
        System.out.println(s.compareTo(s1));
    }
}
```

A. True

B. False

C. None of the listed options

Answer:

Q89. Carefully read the question and answer accordingly.

The LinkedList class supports two constructors.

A. TRUE

B. FALSE

Answer: TRUE

Q90. Carefully read the question and answer accordingly.

Consider the following statements about the Map type Objects:

Statement A: Changes made in the set view returned by keySet() will be reflected in the original map.

Statement B: All Map implementations keep the keys sorted.

Which of the following option is true regarding the above statements?

A. Both Statements A and B are true

B. Statement A is true and Statement B is false

C. Statement A is false and Statement B is true

D. Both Statements A and B are false

Answer: Statement A is true and Statement B is false

Q91. Carefully read the question and answer accordingly.

what is the way to iterate over the elements of a Map

A. for loop

B. list Iterator

C. foreach

D. Iterator

Answer:

Q92. Carefully read the question and answer accordingly.

Consider the following partial code:

```
java.util.Date date = new java.util.Date();
```

Which of the following statement is true regarding the above partial code?

- A. Creates a Date object with 0 as default value
- B. Creates a Date object with '01-01-1970 12:00:00 AM' as default value
- C. Creates a Date object with current date and time as default value
- D. Creates a Date object with current date alone as default value

Answer: Creates a Date object with current date and time as default value

Q93. Carefully read the question and answer accordingly.

Consider the following list of code:

- A) `Iterator iterator = hashMap.keySet().iterator();`
- B) `Iterator iterator = hashMap.iterator();`
- C) `Iterator iterator = hashMap.keySet().iterator();`
- D) `Iterator iterator = hashMap.entrySet().iterator();`
- E) `Iterator iterator = hashMap.entrySet.iterator();`

Assume that hashMap is an instance of HashMap type collection implementation.

Which of the following option gives the correct partial code about getting an Iterator to the HashMap entries?

- A. A
- B. B
- C. C
- D. D
- E. E

Answer: D

Q94. Carefully read the question and answer accordingly.

What is the return type of next() in Iterator?

- A. boolean
- B. void
- C. Object
- D. String

Answer: Object

Q95. Carefully read the question and answer accordingly.

foreach loop is the only option to iterate over a Map

A. TRUE

B. FALSE

Answer: FALSE

Q96. Carefully read the question and answer accordingly.

Which of the following are not List implementations?

1.Vector

2.Hashtable

3.LinkedList

4.Properties

A. 1&2

B. 1&3

C. 2&3

D. 1&4

E. 2&4

Answer: 2&4

Q97. Carefully read the question and answer accordingly.

Consider the following Statements:

Statement A: The Iterator interface declares only two methods: hasMoreElements and nextElement.

Statement B: The ListIterator interface extends both the List and Iterator interfaces.

Which of the following option is correct regarding above given statements?

A. Both the Statements A and B are true

B. Statement A is true and Statement B is false

C. Statement A is false and Statement B is true

D. Both the statements A and B are false.

Answer: Both the statements A and B are false.

Q98. Carefully read the question and answer accordingly.

State TRUE or FALSE.

```
line 1: public class Test {  
line 2: public static void main(String[] args) {  
line 3: Queue queue = new LinkedList();  
line 4: queue.add("Hello");  
line 5: queue.add("World");  
line 6: List list = new ArrayList(queue);  
line 7: System.out.println(list); }  
line 8: }
```

Above code will give run time error at line number 3.

A. TRUE

B. FALSE

Answer: FALSE

Q99. Carefully read the question and answer accordingly.

```
Iterator i= new HashMap().entrySet().iterator();
```

is this correct declaration

A. TRUE

B. FALSE

Answer: TRUE

Q100. Carefully read the question and answer accordingly.

Iterator is having previous() method.

State True or False.

A. FALSE

B. TRUE

Answer: FALSE

Q101. Carefully read the question and answer accordingly.

List<Integer> newList=new ArrayList<integer>(); will Above statement create a new object of Array list successfully ?

A. TRUE

B. FALSE

Answer: FALSE

Q102. Carefully read the question and answer accordingly.

Which collection class allows you to associate its elements with key values

A. java.util.Map

B. java.util.ArrayList

C. java.util.Dictionary

D. java.util.HashMap

Answer:

Q103. Carefully read the question and answer accordingly.

Under java.util package we have "Collections" as Class and "Collection" as Interface

A. TRUE

B. FALSE

Answer: TRUE

Q104. Carefully read the question and answer accordingly.

The add method of Set returns false if you try to add a duplicate element.

A. TRUE

B. FALSE

Answer: TRUE

Q105. Carefully read the question and answer accordingly.

Is this true or false. Map interface is derived from the Collection interface.

A. TRUE

B. FALSE

Answer: FALSE

Q106. Carefully read the question and answer accordingly.

LinkedList represents a collection that does not allow duplicate elements.

A. TRUE

B. FALSE

Answer: FALSE

Q107. Carefully read the question and answer accordingly.

What is the data type of m in the following code?

```
import java.util.*;
public class set1
{
    public static void main(String [] args)
    {
        Set s=new HashSet();
        s.add(20);
        s.add("abc");
        for( _____ m:s)
            System.out.println(m);
    }
}
```

A. int

B. String

C. Object

D. set1

Answer: Object

Q108. Carefully read the question and answer accordingly.

Which of these interface(s) are part of Java's core collection framework?

A. List

B. Set

C. SortedList

D. SortedQueue

Answer:

Q109. Carefully read the question and answer accordingly.

When comparable interface is used which method should be overridden?

- A. comparator
- B. compare
- C. compareTo
- D. compareWith

Answer: compareTo

Q110. Carefully read the question and answer accordingly.

TreeSet uses which two interfaces to sort the data

- A. Serializable
- B. SortTable
- C. SortedSet
- D. Comparable

Answer:

Q111. Carefully read the question and answer accordingly.

Which statement are true for the class HashSet?

- A. The elements in the collection are accessed using a non-unique key.
- B. The elements in the collection are guaranteed to be unique
- C. The elements in the collection are accessed using a unique key.
- D. HashSet allows at most one null element

Answer:

Q112. Carefully read the question and answer accordingly.

Enumeration is having remove() method.

State True or False.

- A. FALSE

B. TRUE

Answer: FALSE

Q113. Carefully read the question and answer accordingly.

Consider the following code:

```
01 import java.util.Set;
02 import java.util.TreeSet;
03
04 class TestSet {
05 public static void main(String[] args) {
06 Set set = new TreeSet<String>();
07 set.add("Green World");
08 set.add(1);
09 set.add("Green Peace");
10 System.out.println(set);
11 }
12 }
```

Which of the following option gives the output for the above code?

- A. Prints the output [Green World, 1, Green Peace] at line no 9
- B. Compilation error at line no 8
- C. Throws Runtime Exception
- D. Prints the output [Green World, Green Peace] at line no 9

Answer: Throws Runtime Exception

Q114. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class collection1{
public static void main(String[]args){
Collection c=new ArrayList();
c.add(10);
c.add("abc");
Collection l=new HashSet();
l.add(20);
l.add("abc");
l.add(30);
```

```
c.addAll(l);  
c.removeAll(l);  
System.out.println( c );  
}  
}
```

- A. [10,abc]
- B. [10]
- C. Compilation error
- D. [abc]

Answer: [10]

Q115. Carefully read the question and answer accordingly.
Which of these are interfaces in the collection framework

- A. Hash Map
- B. Array List
- C. Collection
- D. Sorted Map

Answer:

Q116. Carefully read the question and answer accordingly.
Which of the following are true statements?

- A. The Iterator interface declares only three methods: hasNext, next and remove.
- B. The ListIterator interface extends both the List and Iterator interfaces
- C. The ListIterator interface provides the ability to determine its position in the List.
- D. The ListIterator interface provides forward and backward iteration capabilities.

Answer:

Q117. Carefully read the question and answer accordingly.
which are the Basic features of implementations of interfaces in Collections Framework in java?

- A. All implementations are unsynchronized

- B. All implementations support having null elements.
- C. All implementations are serializable and cloneable
- D. all implementations are immutable and supports duplicates data

Answer:

Q118. Carefully read the question and answer accordingly.

Which of the following are synchronized?

- 1.Hashtable
- 2.Hashmap
- 3.Vector
- 4.ArrayList

A. 1&2

B. 1&3

C. 2&3

D. 1&4

E. 2&4

Answer: 1&3

Q119. Carefully read the question and answer accordingly.

What will be the output for following code?

```
import java.util.*;
public class StringTokens
{
    public static void main(String[]args)
    {
        String s="India is a\n developing country";
        StringTokenizer o=new StringTokenizer(s);
        System.out.println(o.countTokens());
    }
}
```

A. 4

B. 5

C. 6

D. None of the listed options

Answer: 5

Q120. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

StringBuilder is not thread-safe unlike StringBuffer

A. TRUE

B. FALSE

Answer: TRUE

Q121. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class StringCompare{  
    public static void main(String[]args){  
        if("string"=="string")  
            System.out.println("both strings are equal");  
        else  
            System.out.println("both strings are not equal");  
    }  
}
```

A. both strings are equal

B. both strings are not equal

C. compilation error

D. Runtime error

Answer: both strings are equal

Q122. Carefully read the question and answer accordingly.

endsWith() member methods of String class creates new String object. State True or False

A. TRUE

B. FALSE

Answer: FALSE

Q123. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class CompareStrings{
public static void main(String[]args){
String a=new String("string");
String s=new String("string");
if(a==s)
System.out.println("both strings are equal");
else
System.out.println("both strings are not equal");
}
}
```

- A. both strings are equal
- B. both strings are not equal
- C. compilation error
- D. Strings cannot be compare using == operator

Answer: both strings are not equal

Q124. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

String s = new String(); is valid statement in java

- A. TRUE
- B. FALSE

Answer: TRUE

Q125. Carefully read the question and answer accordingly.

What is the output of below code:

```
package p1;
public class Hackathon {
public static void main(String[] args) {
String x = "Java";
x.concat(" Rules!");
System.out.println("x = " + x);
}
```

```
}
```

A. x = Java Rules

B. x = Java

C. x = Rules

D. Error

Answer: x = Java

Q126. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

StringTokenizer implements the Enumeration interface

A. TRUE

B. FALSE

Answer: TRUE

Q127. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

The APIS of StringBuffer are synchronized unlike that of StringBuilder

A. TRUE

B. FALSE

Answer: TRUE

Q128. Carefully read the question and answer accordingly.

What is the output of below code:

```
package p1;
public class Hackathon {
    public static void main(String[] args) {
        String x = "Java";
        x.toUpperCase();
        System.out.println("x = " + x);
    }
}
```

- A. x = JAVA
- B. x=""
- C. x = Java
- D. x="JAVA"

Answer: x = Java

Q129. Carefully read the question and answer accordingly.

Consider the following code snippet:

```
String thought = "Green";  
StringBuffer bufferedThought = new StringBuffer(thought);  
String secondThought = bufferedThought.toString();  
System.out.println(thought == secondThought);
```

Which of the following option gives the output of the above code snippet?

- A. TRUE
- B. FALSE

Answer: FALSE

Q130. Carefully read the question and answer accordingly.

Choose the correct option.

Statement I: StringBuilder offers faster performance than StringBuffer

Statement II: All the methods available on StringBuffer are also available on StringBuilder

- A. Statement I & II are TRUE
- B. Statement I is TRUE & II is FALSE
- C. Statement I is FALSE & II is TRUE
- D. Statement I & II are FALSE

Answer: Statement I & II are TRUE

Q131. Carefully read the question and answer accordingly.

String class contains API used for

- A. Comparing strings
- B. Searching strings

C. Extracting strings

D. All of above

Answer: All of above

Q132. Carefully read the question and answer accordingly.

Choose the correct option.

Statement I: StringBuffer is efficient than "+" concatenation

Statement II: Using API's in StringBuffer the content and length of String can be changed which intern creates new object.

A. Statement I & II are TRUE

B. Statement I is TRUE & II is FALSE

C. Statement I is FALSE & II is TRUE

D. Statement I & II are FASLE

Answer: Statement I is TRUE & II is FALSE

Q133. Carefully read the question and answer accordingly.

State whether TRUE or FALSE.

String class do not provides a method which is used to compare two strings lexicographically.

A. TRUE

B. FALSE

Answer: FALSE

Q134. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class CompareStrings{
public static void main(String[]args){
if(" string ".trim()=="string")
System.out.println("both strings are equal");
else
System.out.println("both strings are not equal");
}
}
```

A. both strings are equal

- B. both strings are not equal
- C. compilation error
- D. Strings cannot be compare using == operator

Answer: both strings are not equal

Q135. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class StringBuffer1
{
    public static void main(String[]args)
    {
        StringBuffer s1=new StringBuffer("welcome");
        StringBuffer s2=new StringBuffer("welcome");
        System.out.println(s1.equals(s2));
        System.out.println(s1.equals(s1));
    }
}
```

- A. true false
- B. false true
- C. true true
- D. false false

Answer: false true

Q136. Carefully read the question and answer accordingly.

What will be the output for following code?

```
import java.io.*;
public class Exception1
{
    public static void main(String[]args)
    {
        System.out.println("A");

        try
        {
        }
    }
}
```

```
catch(IOException t)
{
    System.out.println("B");
}

System.out.println("C");
}
}
```

- A. Compile time error
- B. A
- C. A,C
- D. Runtime error

Answer: Compile time error

Q137. Carefully read the question and answer accordingly.

What will be the output of the program?

```
public class Test {
    public static void aMethod() throws Exception {
        try {
            throw new Exception();
        } finally {
            System.out.print("finally");
        }
    }
    public static void main(String args[]) {
        try {
            aMethod();
        } catch (Exception e) {
            System.out.print("exception ");
        }
        System.out.print("finished"); /* Line 24 */
    }
}
```

- A. exception finished

- B. Compilation fails
- C. finally
- D. finally exception finished

Answer: finally exception finished

Q138. Carefully read the question and answer accordingly.

At Point X in below code, which code is necessary to make the code compile?

```
public class Test
{
    class TestException extends Exception {}
    public void runTest() throws TestException {}
    public void test() /* Point X */
    {
        runTest();
    }
}
```

- A. throws RuntimeException
- B. catch (Exception e)
- C. throws Exception
- D. No code is necessary.

Answer: throws Exception

Q139. Carefully read the question and answer accordingly.

If you put a finally block after a try and its associated catch blocks, then once execution enters the try block, the code in that finally block will definitely be executed except in some circumstances. select the correct circumstance from given options:

- A. An exception arising in the finally block itself
- B. The use of System.exit()
- C. finally block will be always executed in any circumstances.
- D. The death of the thread

Answer:

Q140. Carefully read the question and answer accordingly.

What will be the output of the below code?

```
public class Test {  
    public static void main(String[] args) {  
        int a = 5, b = 0, c = 0;  
        String s = new String();  
        try {  
            System.out.print("hello ");  
            System.out.print(s.charAt(0));  
            c = a / b;  
        } catch (ArithmeticException ae) {  
            System.out.print(" Math problem occur");  
        } catch (StringIndexOutOfBoundsException se) {  
            System.out.print(" string problem occur");  
        } catch (Exception e) {  
            System.out.print(" problem occurs");  
        } finally {  
            System.out.print(" stopped");  
        }  
    }  
}
```

- A. hello 0 stopped
- B. hello 0 Math problem occur stopped
- C. hello Math problem occur string problem occur problem occurs stopped
- D. hello string problem occur stopped

Answer: hello string problem occur stopped

Q141. Carefully read the question and answer accordingly.

Within try block if System.exit(0) is called then also finally block is going to be executed.

State True or False.

- A. FALSE
- B. TRUE

Answer: FALSE

Q142. Carefully read the question and answer accordingly.

Which of the following are checked exceptions?

1. ClassNotFoundException
2. InterruptedException
3. NullPointerException
4. ArrayIndexOutOfBoundsException

A. 1&2

B. 1&3

C. 2&3

D. 1&4

E. 2&4

Answer: 1&2

Q143. Carefully read the question and answer accordingly.

which of these are the subclass of Exception class

A. IOException

B. Throwable

C. RuntimeException

D. FileNotFoundException

Answer:

Q144. Carefully read the question and answer accordingly.

what are true for RuntimeException

A. Runtime exceptions need not be explicitly caught in try catch block as it can occur anywhere in a program.

B. Runtime exceptions include arithmetic exceptions, pointer exceptions

C. RuntimeException is a class of I/O exception

D. RuntimeException are the exceptions which forces the programmer to catch them explicitly in try-catch block

Answer:

Q145. Carefully read the question and answer accordingly.

What will be the output of following code?

```
try
{
    System.out.println("Executing try");
}
System.out.println("After try");
catch (Exception ex)
{
    System.out.println("Executing catch");
}
```

- A. Executing try After try Executing catch
- B. Executing try Runtime Exception
- C. Compile Time Exception
- D. Runtime Exception

Answer: Compile Time Exception

Q146. Carefully read the question and answer accordingly.

Consider the following code:

```
class MyException extends Throwable { }
public class TestThrowable {
    public static void main(String args[]) {
        try {
            test();
        } catch(Throwable ie) {
            System.out.println("Exception");
        }
    }
}
```

```
static void test() throws Throwable {
    throw new MyException();
}
}
```

Which of the following option gives the output for the above code?

- A. Prints Exception

- B. Compiler time error User defined exceptions should extend Exception
- C. Compile time error Cannot use Throwable to catch the exception
- D. Run time error test() method does not throw a Throwable instance

Answer: Prints Exception

Q147. Carefully read the question and answer accordingly.
which are the Unchecked exceptions

- A. Class Cast Exception
- B. Array Index Out Of Bounds Exception
- C. ClassNotFoundException
- D. Number Format Exception

Answer:

Q148. Carefully read the question and answer accordingly.
What will be the output for following code?

```
public class Exception1
{
    public static void main(String[]args)
    {
        System.out.println("A");
        try
        {
            System.exit(0);
        }catch(Exception e)
        {
            System.out.println("B");
        }
        System.out.println("C");
    }
}
```

- A. A,C
- B. A

- C. Compilation error
- D. None of the listed options

Answer: A

Q149. Carefully read the question and answer accordingly.

Which is/are true among given statements

- A. A ClassNotFoundException is thrown when the reported class is not found by the ClassLoader in the CLASSPATH.
- B. NoClassDefFoundError means that the class was found by the ClassLoader however when trying to load the class, it ran into an error reading the class definition.
- C. NoClassDefFoundError is a subClass of ClassNotFoundException
- D. None of the options

Answer:

Q150. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class Exe3
{
    public static void main(String[]args)
    {
        try
        {
            int i=10;
            int j=i/0;
            return;
        }catch(Exception e)
        {
            System.out.println("welcome");
        }
        System.out.println("error");
    }
}
```

- 1.welcome
- 2.error
- 3.compilation error

- A. 1&2
- B. 1&2&3
- C. 1&3
- D. 2
- E. 2&3

Answer: 1&2

Q151. Carefully read the question and answer accordingly.

which are true for try block

- A. Try block always needed a catch block followed
- B. if exception occurs, control switches to following first Catch block
- C. catch block is not mandate always only finally followed by try can be executed
- D. after switching from try block to catch block the control never come back to try block to execute rest of the code

Answer:

Q152. Carefully read the question and answer accordingly.

What will be the output of following code?

```
public class Exception1{
public static void main(String args[]) {
int i=1, j=1;
try {
i++;
j--;
if(i/j > 1)
i++;
} catch(ArithmeticException e) {
System.out.println(0);
} catch(ArrayIndexOutOfBoundsException e) {
System.out.println(1);
} catch(Exception e) {
System.out.println(2);
}
finally {
```

```
System.out.println(3);  
}  
System.out.println(4);  
}  
}
```

1.0

2.1

3.3

4.4.

A. 1&2

B. 1&2&3

C. 1&3&4

D. 1&2&4

E. 2&4

Answer: 1&3&4

Q153. Carefully read the question and answer accordingly.

Consider the following code:

```
1 public class FinallyCatch {  
2     public static void main(String args[]) {  
3         try {  
4             throw new java.io.IOException();  
5         }  
6     }  
7 }
```

Which of the following is true regarding the above code?

A. Shows unhandled exception type IOException at line number 4

B. Shows unhandled exception type IOException at line number 5

C. Demands a finally block at line number 4

D. Demands a finally block at line number 5

Answer: Demands a finally block at line number 5

Q154. Carefully read the question and answer accordingly.

Which of the following exception is not mandatory to be handled in code?

- A. IOException
- B. FileNotFoundException
- C. SQLException
- D. NullPointerException

Answer: NullPointerException

Q155. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class Exception1{
public static void main(String args[]) {
int i=1, j=1;
try {
i++;
j--;
if(i/j > 1)
i++;
} catch(Exception e) {
System.out.println(2);
} catch(ArithmeticException e) {
System.out.println(0);
}
finally {
System.out.println(3);
}
}
}
```

- A. 2
- B. 3
- C. compilation error

Answer: compilation error

Q156. Carefully read the question and answer accordingly.

select true or false . Statement : Throwable is the super class of all exceptional type classes.

A. TRUE

B. FALSE

Answer: TRUE

Q157. Carefully read the question and answer accordingly.

try and throws keywords are used to manually throw an exception?

A. TRUE

B. FALSE

Answer: FALSE

Q158. Carefully read the question and answer accordingly.

RuntimeException is the superclass of those exceptions that can be thrown during the normal operation of the Java Virtual Machine.

A. TRUE

B. FALSE

Answer: TRUE

Q159. Carefully read the question and answer accordingly.

Which of the following statement is true regarding implementing user defined exception mechanisms?

Statement A: It is valid to derive a class from java.lang.Exception

Statement B: It is valid to derive a class from java.lang.RuntimeException

A. Both Statements A and B are true

B. Statement A is true and Statement B is false

C. Statement A is false and Statement B is true

D. Both Statements A and B are false

Answer: Both Statements A and B are true

Q160. Carefully read the question and answer accordingly.

Which of the following statement is true regarding try-catch-finally?

- A. An exception which is not handled by a catch block will be handled by subsequent catch blocks
- B. A catch block can have another try block nested inside
- C. Both catch block and finally block can throw exceptions
- D. All of the listed options

Answer: All of the listed options

Q161. Carefully read the question and answer accordingly.
Which of these keywords are a part of exception handling?

- A. try
- B. final
- C. thrown
- D. catch

Answer:

Q162. Carefully read the question and answer accordingly.
Error is the sub class of Throwable

- A. TRUE
- B. FALSE

Answer: TRUE

Q163. Carefully read the question and answer accordingly.
Which of these keywords is used to explicitly throw an exception?

- A. try
- B. finally
- C. throw
- D. throwable

Answer: throw

Q164. Carefully read the question and answer accordingly.
is it valid to place some code in between try and catch blocks.

- A. TRUE
- B. FALSE

Answer: FALSE

Q165. Carefully read the question and answer accordingly.
which are correct for checked exceptions

- A. A checked exception is a subclass of throwable class
- B. error and checked exceptions are same.
- C. Checked exceptions are the object of the Exception class or any of its subclasses except Runtime Exception class.
- D. All runtime exceptions are checked exceptions

Answer:

Q166. Carefully read the question and answer accordingly.
Try can be followed with either catch or finally.
State True or False.

- A. TRUE
- B. FALSE

Answer: TRUE

Q167. Carefully read the question and answer accordingly.
Which is the super class for Exception and Error?

- A. Throwable
- B. throws
- C. throw
- D. RuntimeException

Answer: Throwable

Q168. Carefully read the question and answer accordingly.
The finally block always executes when the try block exits.
State True or False.

- A. TRUE
- B. FALSE

Answer: TRUE

Q169. Carefully read the question and answer accordingly.

Select two runtime exceptions.

1. SQLException
2. NullPointerException
3. FileNotFoundException
4. ArrayIndexOutOfBoundsException
5. IOException

- A. 1&2
- B. 1&5
- C. 2&3
- D. 1&4
- E. 2&4

Answer: 2&4

Q170. Carefully read the question and answer accordingly.

Propagating exceptions across modules is not possible without throw and throws keyword. State True or False.

- A. TRUE
- B. FALSE

Answer: FALSE

Q171. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class Exe3 {  
    public static void main(String[] args){  
        try{  
            int i=10;  
            int j=i/0;  
            return;  
        }  
    }  
}
```

```
}catch(Exception e){  
try{  
System.out.println("welcome");  
return;  
}catch(Exception e1){  
}  
System.out.println("error");  
}  
}  
}
```

- A. welcome
- B. error
- C. compilation error
- D. None of the listed options

Answer: welcome

Q172. Carefully read the question and answer accordingly.

What will be the output for following code?

```
class super5{  
void Get()throws Exception{  
System.out.println("IOException");  
}  
}  
public class Exception2 extends super5{  
public static void main(String[]args){  
super5 o=new super5();  
try{  
o.Get();  
}catch(IOException e){  
}  
}  
}
```

- A. IOException
- B. compilation error

- C. Runtime error
- D. None of the listed options

Answer: compilation error

Q173. Carefully read the question and answer accordingly.

Serialization is representing object in a sequence of bytes. State True or False.

- A. TRUE
- B. FALSE

Answer: TRUE

Q174. Carefully read the question and answer accordingly.

Serialization is JVM independent.State True or False.

- A. TRUE
- B. FALSE

Answer: TRUE

Q175. Carefully read the question and answer accordingly.

Statement 1:static variables can be serialized

Statement2:transient variables cannot be serialized

which of the following is true?

- A. statement 1:true statement2:true
- B. statement 1:false statement2:true
- C. statement 1:false statement2:false
- D. statement 1:true statement2:false

Answer: statement 1:false statement2:true

Q176. Carefully read the question and answer accordingly.

select the correct statements about BufferedOutputStream class

- A. BufferedOutputStream class is a member of Java.io package
- B. setting up BufferedOutputSteaman , an application can write bytes to the underlying output stream without necessarily causing a call to the underlying system for each byte written.

C. it has flush() method

D. As bytes from the stream are read or skipped, the internal buffer is refilled as necessary from the contained input stream, many bytes at a time.

Answer:

Q177. Carefully read the question and answer accordingly.

DataInputStream is not necessarily safe for multithreaded access.

A. TRUE

B. FALSE

Answer: TRUE

Q178. Carefully read the question and answer accordingly.

Which of the following is a marker interface used for object serialization?

A. Runnable

B. Serializable

C. Externalizable

D. None of the listed options

Answer: Serializable

Q179. Carefully read the question and answer accordingly.

InputStream is the class used for stream of characters.

State True or False.

A. FALSE

B. TRUE

Answer: FALSE

Q180. Carefully read the question and answer accordingly.

BufferedWriter constructor CAN ACCEPT FileWriter Object as a parameter.

State True or False.

A. TRUE

B. FALSE

Answer: TRUE

Q181. Carefully read the question and answer accordingly.

Which of these class are the member class of java.io package?

- A. ObjectInput
- B. StringReader
- C. File
- D. String

Answer:

Q182. Carefully read the question and answer accordingly.

Which of these interface is not a member of java.io package?

- A. DataInput
- B. ObjectInput
- C. ObjectFilter
- D. FileFilter

Answer: ObjectFilter

Q183. Carefully read the question and answer accordingly.

Which of the following are abstract classes?

- 1.Reader
- 2.InputStreamReader
- 3.InputStream
- 4.OutputStream

- A. 1&2
- B. 1&2&3
- C. 1&3&4
- D. 1&2&4
- E. 2&4

Answer: 1&3&4

Q184. Carefully read the question and answer accordingly.

An ObjectInputStream deserializes objects previously written using an ObjectOutputStream.
State True or False.

A. TRUE

B. FALSE

Answer: TRUE

Q185. Carefully read the question and answer accordingly.

The InputStream.close() method closes this stream and releases all system resources

A. TRUE

B. FALSE

Answer: FALSE

Q186. Carefully read the question and answer accordingly.

State TRUE or FALSE.

getParent() gives the parent directory of the file and isFile() Tests whether the file denoted by the given abstract pathname is a normal file.

A. TRUE

B. FALSE

Answer: TRUE

Q187. Carefully read the question and answer accordingly.

InputStreamReader is sub class of FilterReader.

A. TRUE

B. FALSE

Answer: FALSE

Q188. Carefully read the question and answer accordingly.

isFile() returns true if called on a file or when called on a directory

A. TRUE

B. FALSE

Answer: FALSE

Q189. Carefully read the question and answer accordingly.

What is the output of this program?

```
1. import java.io.*;  
2. class files {  
3. public static void main(String args[]) {  
4. File obj = new File("/java/system");  
5. System.out.print(obj.getName());  
6. }  
7. }
```

- A. java/system
- B. /java/system
- C. system
- D. compilation error

Answer: system

Q190. Carefully read the question and answer accordingly.

Which of these class are related to input and output stream in terms of functioning?

- A. File
- B. Writer
- C. Reader
- D. OutputStream

Answer:

Q191. Carefully read the question and answer accordingly.

The _____ statement is used inside the switch to terminate a Statement sequence

- A. break
- B. Jump
- C. exit
- D. goto
- E. escape

Answer: break

Q192. Carefully read the question and answer accordingly.

The result of $10.987 + 30.765$ is _____.

- A. 10.98730.765
- B. 10.9873.765
- C. Compilation error
- D. 10.987

Answer: 10.98730.765

Q193. Carefully read the question and answer accordingly.

Data can be passed to the function _____

- A. by value
- B. by reference
- C. Both by value & reference
- D. none of these

Answer: by value

Q194. Carefully read the question and answer accordingly.

_____ is a multi way branch statement

- A. switch
- B. continue
- C. break
- D. label
- E. branch

Answer: switch

Q195. Carefully read the question and answer accordingly.

Which of the following is a loop construct that will always be executed once?

- A. switch

- B. for
- C. while
- D. do While
- E. for..each

Answer: do While

Q196. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class While {  
    static int i;  
    public static void main(String[]args){  
        System.out.println(i);  
        while(i<=5){  
            i++;  
        }  
        System.out.println(i);  
    }  
}
```

- A. compilation error
- B. 0,6
- C. 6,0
- D. 0,5

Answer: 0,6

Q197. Carefully read the question and answer accordingly.

What is the number of bytes used by Java primitive long

- A. The number of bytes is compiler dependent
- B. 2
- C. 4
- D. 8
- E. 64

Answer: 8

Q198. Carefully read the question and answer accordingly.

We can use Wrapper objects of type int, short, char in switch case.

State True or False.

A. TRUE

B. FALSE

Answer: TRUE

Q199. Carefully read the question and answer accordingly.

What happens when the following code is compiled and run. Select the one correct answer.

```
for(int i = 1; i < 3; i++)
```

```
for(int j = 3; j >= 1; j--)
```

```
assert i!=j : i;
```

A. The class compiles and runs, but does not print anything.

B. The number 1 gets printed with AssertionError

C. The number 2 gets printed with AssertionError

D. The number 3 gets printed with AssertionError

E. The program generates a compilation error.

Answer: The number 1 gets printed with AssertionError

Q200. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class WrapperClass12
```

```
{
```

```
public static void main(String[] args)
```

```
{
```

```
Boolean b=true;
```

```
boolean a=Boolean.parseBoolean("tTRUE");
```

```
System.out.println(b==a);
```

```
}
```

```
}
```

A. True

- B. False
- C. Compilation error
- D. Runtime Exception

Answer: True

Q201. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class WrapperClass1 {  
    public static void main(String[] args){  
        String s="10Bangalore";  
        int i=Integer.parseInt(s);  
        System.out.println(i);  
    }  
}
```

- A. 10Bangalore
- B. 10
- C. Compilation error
- D. Runtime Exception

Answer: Runtime Exception

Q202. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class While {  
    public static void main(String[] args){  
        int a='A';  
        int i=a+32;  
        while(a<='Z'){  
            a++;  
        }  
        System.out.println(i);  
        System.out.println(a);  
    }  
}
```

- A. A,Z

- B. a,z
- C. 91,97
- D. 97,91

Answer: 97,91

Q203. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class WrapperClass1 {  
    public static void main(String[]args){  
        Integer i=new Integer(10);  
        Integer j=new Integer(10);  
        System.out.println(i==j);  
    }  
}
```

- A. True
- B. False
- C. compilation error
- D. None of the listed options

Answer: False

Q204. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class Wrapper2 {  
    public static void main(String[]args){  
        Byte b=1;  
        Byte a=2;  
        System.out.println(a+b);  
    }  
}
```

- A. compiles and print 3
- B. compilation error
- C. Runtime Error
- D. compiles and prints 12

Answer: compiles and print 3

Q205. Carefully read the question and answer accordingly.

What will be the output for following code?

```
public class Wrapper11
{
    public static void main(String[] args)
    {
        Long l=100;
        System.out.println(l);
    }
}
```

- A. 100
- B. Compilation error
- C. code will execute with out printing
- D. runtime Exception

Answer: Compilation error

Q206. Carefully read the question and answer accordingly.

What will be the output of below code?

```
public class Test {
    public static void main(String[] args) {
        int i = 1;
        Integer l = new Integer(i);
        method(i);
        method(l);
    }
    static void method(Integer l) {
        System.out.print(" Wrapper");
    }
    static void method(int i) {
        System.out.print(" Primitive");
    }
}
```

- A. Primitive Wrapper

- B. Wrapper
- C. Primitive
- D. Wrapper Primitive
- E. None Of the options

Answer: Primitive Wrapper

Q207. Carefully read the question and answer accordingly.

What is the value of variable "I" after execution of following code?

```
public class Evaluate
{
    public static void main(String[]args)
    {
        int i=10;
        if(((i++)>12)&&(++i<15))
            System.out.println(i);
        else
            System.out.println(i);
    }
}
```

- A. 10
- B. 11
- C. 12
- D. None of the listed options

Answer: 11

Q208. Carefully read the question and answer accordingly.

Each case in switch statement should end with _____ statement

- A. default
- B. break
- C. continue
- D. new
- E. none

Answer: break

Q209. Carefully read the question and answer accordingly.

Type 1 & Type 3 driver types are not vendor specific implementation of Java driver. State True or False

- A. TRUE
- B. FALSE

Answer: TRUE

Q210. Carefully read the question and answer accordingly.

The JDBC-ODBC Bridge driver translates the JDBC API to the ODBC API and used with which of the following:

- A. JDBC drivers
- B. ODBC drivers
- C. Both A and B
- D. None of the above

Answer: ODBC drivers

Q211. Carefully read the question and answer accordingly.

A Java program cannot directly communicate with an ODBC driver because of which of the following:

- A. ODBC written in C language
- B. ODBC written in Java language
- C. ODBC written in C++ language
- D. ODBC written in Basic language

Answer: ODBC written in C language

Q212. Carefully read the question and answer accordingly.

Which statements about JDBC are true?

- 1.JDBC has 5 types of Drivers
- 2.JDBC stands for Java DataBase Connectivity
- 3.JDBC is an API to access relational databases, spreadsheets and flat files
- 4.JDBC is an API to bridge the object-relational mismatch between OO programs and relational databases

- A. 1&2
- B. 3&4
- C. 2&3
- D. 1&4
- E. 2&4

Answer: 2&3

Q213. Carefully read the question and answer accordingly.

Which type of driver converts JDBC calls into the network protocol used by the database management system directly?

- A. Type 1 driver
- B. Type 2 driver
- C. Type 3 driver
- D. Type 4 driver

Answer: Type 4 driver

Q214. Carefully read the question and answer accordingly.

Which type of Statement can execute parameterized queries?

- A. PreparedStatement
- B. ParameterizedStatement
- C. ParameterizedStatement and CallableStatement
- D. All kinds of Statements (i.e. which implement a sub interface of Statement)

Answer: PreparedStatement

Q215. Carefully read the question and answer accordingly.

Connection object can be initialized using which method of the Driver Manager class?

- A. putConnection()
- B. setConnection()
- C. Connection()
- D. getConnetion()

Answer: getConnection()

Q216. Carefully read the question and answer accordingly.

Which of the following is true with respect to code given below?

```
import java.sql.*;
public class OracleDemo
{
    public static void main(String [] args) throws SQLException, ClassNotFoundException
    {
        Class.forName("oracle.jdbc.driver.OracleDriver");
        Connection
        con=DriverManager.getConnection("jdbc:oracle:thin:@PC188681:1521:training","scott","tiger");
        Statement stmt=con.createStatement();
        ResultSet rs=stmt.executeQuery("SELECT * FROM Person");
        while(rs.next())
        {
            System.out.println(rs.getString("column1"));
        }
    }
}
```

- A. The code will not compile as no try catch block specified
- B. The code will display all values in column named column1
- C. Class.forName must be mentioned after Connection statement
- D. "SELECT * FROM Person" query must be passed as parameter to con.createStatement()

Answer: The code will display all values in column named column1

Q217. Carefully read the question and answer accordingly.

If your JDBC Connection is in auto-commit mode, which it is by default, then every SQL statement is committed to the database upon its completion. State True or False.

- A. TRUE
- B. FALSE

Answer: TRUE

Q218. Carefully read the question and answer accordingly.

How can you execute a stored procedure in the database?

- A. Call method execute() on a CallableStatement object
- B. Call method executeProcedure() on a Statement object
- C. Call method execute() on a StoredProcedure object
- D. Call method run() on a ProcedureCommand object

Answer: Call method execute() on a CallableStatement object

Q219. Carefully read the question and answer accordingly.

Consider the following statements:

Statement A: The PreparedStatement object enables you to execute parameterized queries.

Statement B: The SQL query can use the placeholders which are replaced by the INPUT parameters at runtime.

Which of the following option is True with respect to the above statements?

- A. Both Statement A and Statement B are True.
- B. Statement A is True and Statement B is False.
- C. Statement A is False and Statement B is True.
- D. Both Statements A and B are False.

Answer: Both Statement A and Statement B are True.

Q220. Carefully read the question and answer accordingly.

You are using JDBC-ODBC bridge driver to establish a connection with a database. You have created a DSN Mydsn. Which statement will you use to connect to the database?

- A. Connection cn=DriverManager.getConnection("jdbc:odbc");
- B. Connection cn=DriverManager.getConnection("jdbc:odbc:Mydsn", "username", "password");
- C. Connection cn=DriverManager.getConnection("jdbc:odbc ", "username", "password");
- D. Connection cn=DriverManager.getConnection("jdbc:odbc:dsn", "username", "password");

Answer: Connection cn=DriverManager.getConnection("jdbc:odbc:Mydsn", "username", "password");

Q221. Carefully read the question and answer accordingly.

Which of the following listed option gives the valid type of object to store a date and time combination using

JDBC API?

- A. java.util.Date
- B. java.sql.Date
- C. java.sql.Time
- D. java.sql.Timestamp

Answer: java.sql.Timestamp

Q222. Carefully read the question and answer accordingly.

Which method executes an SQL statement that may return multiple results?

- A. executeUpdate()
- B. executeQuery()
- C. execute()
- D. noexecute()

Answer: execute()

Q223. Carefully read the question and answer accordingly.

Which package contains classes that help in connecting to a database, sending SQL statements to the database, and processing the query results

- A. connection.sql
- B. db.sql
- C. pkg.sql
- D. java.sql

Answer: java.sql

Q224. Carefully read the question and answer accordingly.

Which method sets the query parameters of the PreparedStatement Object?

- A. putString()
- B. insertString()
- C. setString()
- D. setToString()

Answer: `setString()`

Q225. Carefully read the question and answer accordingly.

What is correct about DDL statements?

- A. DDL statements are treated as normal SQL statements, and are executed by calling the `execute()` method on a `Statement` (or a sub interface thereof) object
- B. To execute DDL statements, you have to install additional support files
- C. DDL statements cannot be executed by making use of JDBC, you should use the native database tools for this.
- D. Support for DDL statements will be a feature of a future release of JDBC

Answer: DDL statements are treated as normal SQL statements, and are executed by calling the `execute()` method on a `Statement` (or a sub interface thereof) object

Q226. Carefully read the question and answer accordingly.

What is the state of the parameters of the `PreparedStatement` object when the user clicks on the Query button?

- A. initialized
- B. started
- C. paused
- D. stopped

Answer: initialized

Q227. Carefully read the question and answer accordingly.

`executeUpdate()` & `execute()` are valid methods that can be used for executing DDL statements. State True or False

- A. TRUE
- B. FALSE

Answer: TRUE

Q228. Carefully read the question and answer accordingly.

Which object provides you with methods to access data from the table?

- A. ResultSet
- B. Parametrized
- C. TableStatement
- D. Condition

Answer: ResultSet

Q229. Carefully read the question and answer accordingly.

The method Class.forName() is a part of JDBC API. State True or False.

- A. TRUE
- B. FALSE

Answer: FALSE

Q230. Carefully read the question and answer accordingly.

Which object allows you to execute parametrized queries?

- A. ResultSet
- B. Parametrized
- C. PreparedStatement
- D. Condition

Answer: PreparedStatement

Q231. Carefully read the question and answer accordingly.

Which method executes a simple query and returns a single Result Set object?

- A. executeUpdate()
- B. executeQuery()
- C. execute()
- D. noexecute()

Answer: executeQuery()

Q232. Carefully read the question and answer accordingly.

Which packages contain the JDBC classes?

- A. java.jdbc and javax.jdbc
- B. java.jdbc and java.jdbc.sql
- C. java.sql and javax.sql
- D. java.rdb and javax.rdb

Answer: java.sql and javax.sql