Skip to main content

Thank you for visiting nature.com. You are using a browser version with limited support for CSS. To obtain the best experience, we recommend you use a more up to date browser (or turn off compatibility mode in Internet Explorer). In the meantime, to ensure continued support, we are displaying the site without styles and JavaScript.

Advertisement

nature electronics

- View all journals
- Search Q
- Login
- Explore content
- About the journal ~
- Publish with us

Subscribe

- Sign up for alerts •
- RSS feed

```
nature >
nature electronics >
articles >
```

- Article
- Published: 15 February 2019

Self-healing electronic skins for aquatic environments

- Yue Cao^{1,2 na1},
- Yu Jun Tan ORCID: orcid.org/0000-0002-3828-9490^{3,4 na1},

- Si Li^{3,4},
- Wang Wei Lee^{3,4},
- Hongchen Guo^{3,5},
- Yongqing Cai⁶,
- ...
- Chao Wang ORCID: orcid.org/0000-0002-0739-6066 &
- Benjamin C.-K. Tee ORCID: orcid.org/0000-0002-9180-4105^{3,4,7,8}

+Show authors

Nature Electronics volume 2, pages 75–82 (2019)

- 10k Accesses
- 161 Citations
- 165 Altmetric
- Metrics details

Abstract

Gelatinous underwater invertebrates such as jellyfish have organs that are transparent, stretchable, touch-sensitive and self-healing, which allow the creatures to navigate, camouflage themselves and, indeed, survive in aquatic environments. Artificial skins that emulate such functionality could be used to develop applications such as aquatic soft robots and water-resistant human—machine interfaces. Here we report a bio-inspired skin-like material that is transparent, electrically conductive and can autonomously self-heal in both dry and wet conditions. The material, which is composed of a fluorocarbon elastomer and a fluorine-rich ionic liquid, has an ionic conductivity that can be tuned to as high as 10^{-3} S cm⁻¹ and can withstand strains as high as 2,000%. Owing to ion—dipole interactions, it offers fast and repeatable electro-mechanical self-healing in wet, acidic and alkali environments. To illustrate the potential applications of the approach, we used our electronic skins to create touch, pressure and strain sensors. We also show that the material can be printed into soft and pliable ionic circuit boards.

This is a preview of subscription content

Access options

Rent or Buy article

Get time limited or full article access on ReadCube.

from \$8.99

Rent or Buy

All prices are NET prices.

Subscribe to Journal

Get full journal access for 1 year

92,52 €

only 7,71 € per issue

Subscribe

All prices are NET prices.

VAT will be added later in the checkout.

Tax calculation will be finalised during checkout.

Additional access options:

Log in

Learn about institutional subscriptions





Fig. 2: Tunable electrical and mechanical properties of the GLASSES material.










Fig. 4: Touch, pressure and strain sensors fabricated from GLASSES.





Data availability

The data that support the plots within this paper and other findings of this study are available from the corresponding author upon reasonable request.

References

1. Larson, C. et al. Highly stretchable electroluminescent skin for optical signaling and tactile sensing. *Science* **351**, 1071–1074 (2016).

- 2. **2.** Bauer, S. et al. 25th Anniversary Article: a soft future: from robots and sensor skin to energy harvesters. *Adv. Mater.* **26**, 149–162 (2014).
 - **3.** Morin, S. A. et al. Camouflage and display for soft machines. *Science* **337**, 828–832 (2012).
 - **4.** Yuk, H., Zhang, T., Parada, G. A., Liu, X. & Zhao, X. Skin-inspired hydrogel–elastomer hybrids with robust interfaces and functional microstructures. *Nat. Commun.* **7**, 12028 (2016).
 - **5.** Kim, C.-C., Lee, H.-H., Oh, K. H. & Sun, J.-Y. Highly stretchable, transparent ionic touch panel. *Science* **353**, 682–687 (2016).
 - **6.** Wang, S. et al. Skin electronics from scalable fabrication of an intrinsically stretchable transistor array. *Nature* **555**, 83–88 (2018).
 - **7.** Tee, B. C. K. et al. Tunable flexible pressure sensors using microstructured elastomer geometries for intuitive electronics. *Adv. Funct. Mater.* **24**, 5427–5434 (2014).
 - **8.** Gao, W. et al. Fully integrated wearable sensor arrays for multiplexed in situ perspiration analysis. *Nature* **529**, 509–514 (2016).
 - **9.** Schwartz, G. et al. Flexible polymer transistors with high pressure sensitivity for application in electronic skin and health monitoring. *Nat. Commun.* **4**, 1859 (2013).
 - **10.** Chen, L. Y. et al. Continuous wireless pressure monitoring and mapping with ultra-small passive sensors for health monitoring and critical care. *Nat. Commun.* **5**, 1–10 (2014).
 - **11.** Lipomi, D. J. et al. Skin-like pressure and strain sensors based on transparent elastic films of carbon nanotubes. *Nat. Nanotechnol.* **6**, 788–792 (2011).
 - **12.** Sekitani, T., Zschieschang, U., Klauk, H. & Someya, T. Flexible organic transistors and circuits with extreme bending stability. *Nat. Mater.* **9**, 1015–1022 (2010).
 - **13.** Kim, K. S. et al. Large-scale pattern growth of graphene films for stretchable transparent electrodes. *Nature* **457**, 706–710 (2009).

- **14.** Baik, S. et al. A wet-tolerant adhesive patch inspired by protuberances in suction cups of octopi. *Nature* **546**, 396–400 (2017).
- **15.** Tan, Y. J., Wu, J., Li, H. & Tee, B. C. K. Self-healing electronic materials for a smart and sustainable future. *ACS Appl. Mater. Interfaces* **10**, 15331–15345 (2018).
- **16.** Patrick, J. F., Robb, M. J., Sottos, N. R., Moore, J. S. & White, S. R. Polymers with autonomous life-cycle control. *Nature* **540**, 363–370 (2016).
- **17.** Oh, J. Y. et al. Intrinsically stretchable and healable semiconducting polymer for organic transistors. *Nature* **539**, 411–415 (2016).
- **18.** Bandodkar, A. J. et al. All-printed magnetically self-healing electrochemical devices. *Sci. Adv* **2**, e1601465 (2016).
- **19.** Tee, B. C. K., Wang, C., Allen, R. & Bao, Z. An electrically and mechanically self-healing composite with pressure- and flexion-sensitive properties for electronic skin applications. *Nat. Nanotechnol.* **7**, 825–832 (2012).
- **20.** Kang, J. et al. Tough and water-insensitive self-healing elastomer for robust electronic skin. *Adv. Mater.* **30**, 1706846 (2018).
- **21.** Cao, Y. et al. A highly stretchy, transparent elastomer with the capability to automatically self-heal underwater. *Adv. Mater.* **30**, 1804602 (2018).
- **22.** Lipomi, D. J. et al. Electronic properties of transparent conductive films of PEDOT:PSS on stretchable substrates. *Chem. Mater.* **24**, 373–382 (2012).
- 23. Keplinger, C. et al. Stretchable, transparent, ionic conductors. Science 341, 984–987 (2013).
- **24.** Sun, J.-Y., Keplinger, C., Whitesides, G. M. & Suo, Z. Ionic skin. *Adv. Mater.* **26**, 7608–7614 (2014).
- 25.

- Wirthl, D. et al. Instant tough bonding of hydrogels for soft machines and electronics. *Sci. Adv.* 3, 1–10 (2017).
- **26.** Taylor, D. L. & Het Panhuis, M. Self-healing hydrogels. *Adv. Mater.* **28**, 9060–9093 (2016).
- 27. Kaartvedt, S. et al. Social behaviour in mesopelagic jellyfish. Sci. Rep. 5, 11310 (2015).
- **28.** Johnsen, S. Transparent animals. *Sci. Am.* **282**, 80–89 (2000).
- **29.** Cao, Y. et al. A transparent, self-healing, highly stretchable ionic conductor. *Adv. Mater.* **29**, 1605099 (2017).
- **30.** Cordier, P., Tournilhac, F., Soulié-Ziakovic, C. & Leibler, L. Self-healing and thermoreversible rubber from supramolecular assembly. *Nature* **451**, 977–980 (2008).
- **31.** Li, C.-H. et al. A highly stretchable autonomous self-healing elastomer. *Nat. Chem.* **8**, 618–624 (2016).
- **32.** Earle, M. J. et al. The distillation and volatility of ionic liquids. *Nature* **439**, 831–834 (2006).
- **33.** Tee, B. C. K. et al. A skin-inspired organic digital mechanoreceptor. *Science* **350**, 313–316 (2015).
- **34.** Katzschmann, R. K., DelPreto, J., MacCurdy, R. & Rus, D. Exploration of underwater life with an acoustically controlled soft robotic fish. *Sci. Robot.* **3**, eaar3449 (2018).
- **35.** Li, H., Tan, Y. J., Leong, K. F. & Li, L. 3D bioprinting of highly thixotropic alginate/methylcellulose hydrogel with strong interface bonding. *ACS Appl. Mater. Interfaces* **9**, 20086–20097 (2017).

Acknowledgements

B.C.-K.T. is grateful for the support of a National Research Foundation Fellowship by the Singapore National Research Foundation (NRF) Prime Minister's Office, and the National University of Singapore (NUS) Startup Grant. H.C.G. acknowledges support from a NUS NGS Scholarship. C.W. acknowledges support from NSFC grant no. 21890731. We thank J.Y. Sun for discussions and S. Wang, J. Tan, H. Li and W. Yan for access to testing equipment.

Author information

Author notes

1. These authors contributed equally: Yue Cao, Yu Jun Tan.

Affiliations

 Key Lab of Organic Optoelectronics & Molecular Engineering, Department of Chemistry, Tsinghua University, Beijing, China

Yue Cao & Chao Wang

2. Department of Chemistry, University of California Riverside, Riverside, California, USA

Yue Cao

3. Department of Materials Science and Engineering (MSE), National University of Singapore, Singapore, Singapore

Yu Jun Tan, Si Li, Wang Wei Lee, Hongchen Guo & Benjamin C.-K. Tee

4. Biomedical Institute for Global Health and Research (BIGHEART), National University of Singapore, Singapore, Singapore

Yu Jun Tan, Si Li, Wang Wei Lee & Benjamin C.-K. Tee

5. Graduate School for Integrative Sciences and Engineering, National University of Singapore, Singapore, Singapore

Hongchen Guo

6. Institute Of High Performance Computing (IHPC), Agency for Science Technology and Research, Singapore, Singapore

Yongqing Cai

7. Department of Electrical and Computer Engineering (ECE), National University of Singapore, Singapore, Singapore

Benjamin C.-K. Tee

8. Institute of Materials Research and Engineering (IMRE), Agency for Science Technology and Research, Singapore, Singapore

Benjamin C.-K. Tee

Contributions

B.C.-K.T., C.W., Y.C., and Y.J.T. conceived and designed the experiments; Y.C., Y.J.T., S.L. and W.W.L. carried out experiments and collected the overall data; Y.C., Y.J.T. and H.C.G. contributed to materials fabrication and characterization. S.L., W.W.L. and Y.J.T. performed electrical properties characterization and worked on sensors demonstration. S.L. and Y.J.T. worked on transparent and self-healable soft PCB. Y.Q.C. contributed the DFT calculations. Y.J.T., B.C.-K.T., Y.C., S.L. and C.W. analysed all the data and co-wrote the paper. All authors discussed the results and commented on the manuscript.

Corresponding authors

Correspondence to Chao Wang or Benjamin C.-K. Tee.

Ethics declarations

Competing interests

The authors declare no competing interests.

Additional information

Publisher's note: Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Supplementary information

Supplementary Information

Supplementary Notes 1–4, Supplementary Tables 1–4 and Supplementary Figures 1–22

Supplementary Video 1

Autonomous self-healing of GLASSES. The video starts with a time-lapse capture with the transparent material laid on a picture, then a puncture is made through the material. The material is observed under a microscope for three days. It self-heals without any external stimuli such as pressure, temperature or organic solvents. After that, a new piece of material is bifurcated, and self-healed. The material can be stretched again after healing in ambient conditions for 24 hours.

Supplementary Video 2

Playing a snake game on the GLASSES touch panel. The position of touch and swipe actions of a finger can be sensed by the material for human–machine interactions.

Supplementary Video 3

The position of touch can be sensed by the transparent material by utilizing its surface capacitance system and external amplifying circuits, which is used to make a drawing panel.

Supplementary Video 4

Conformable pressure sensor linked to LEDs for visualization of changes in pressure and touch locations. When the fingertip touches the material, a surface capacitance is introduced. When the

fingertip presses down on the material, the contact area increases as the material is deformable, resulting in an increase in surface capacitance.

Supplementary Video 5

GLASSES material used as a strain sensor with optically encoded signal output. The frequency signal is changing with strain.

Supplementary Video 6

GLASSES is made into a strain sensor, and is transparent and able to send out optical communication information of its strain state. This video is a demonstration of an infrared communication system in air and water, and the signal–strain plot showing that the transmitted signal carrying information (frequency) is dependent on the strain. The display on the phone shows the balloon status. The infrared signal is directed through GLASSES only. As demonstrated in the beginning of the video, the signal is interrupted when the balloon is being tilted as the infrared LED is not aligned with the receiver. The status shows 'Expanding' when the balloon starts to expand, corresponding to a decrease in frequency output. We also show that the demonstration works when the GLASSES are submerged in water. After touching the water surface, the display changes to 'In water', correlating to a sudden increase of frequency output. When the frequency signal decrease again, the status changes to 'Expanding in water'.

Supplementary Video 7

Self-healed GLASSES (with LED) submerged in water as an unobtrusive soft 'robot' among small underwater creatures. The transparent materials allow light to transmit through them. The multiple self-healed regions remain intact underwater. The LED-embedded GLASSES mimics the bioluminescence of jellyfish underwater, sending messages to the shrimps that they react to by escaping from the bright 'jellyfish'. The same setup is repeated by using LEDs embedded in an opaque material, where the shrimps did not visibly react when the LEDs are turned on because the light cannot transmit through the material. The shrimps reacted only after the opaque material is 'toppled', when the light intensity suddenly increases.

Supplementary Video 8

GLASSES material can be printed into soft, stretchable, transparent PCB. The PCB can be mechanically twisted and stretched.

Rights and permissions

Reprints and Permissions

About this article

Cite this article

Cao, Y., Tan, Y.J., Li, S. *et al.* Self-healing electronic skins for aquatic environments. *Nat Electron* **2**, 75–82 (2019). https://doi.org/10.1038/s41928-019-0206-5

Received: 15 August 2018 Accepted: 18 January 2019 Published: 15 February 2019

Issue Date: February 2019 **DOI:** https://doi.org/10.1038/s41928-019-0206-5

Subjects

Electrical and electronic engineering • Ionic liquids • Sensors and biosensors • Soft materials

Further reading

 Self-powered multifunctional sensing based on super-elastic fibers by soluble-core thermal drawing

Mengxiao Chen

Zhe Wang

Lei Wei

Nature Communications (2021)

• Metasurfaces for bioelectronics and healthcare

Zhipeng Li

Xi Tian

John S. Ho

Nature Electronics (2021)

 Metal cation-ligand interaction modulated mono-network ionic conductive hydrogel for wearable strain sensor

Dongran Liang

Guanbing Zhou

Chongyi Chen

Journal of Materials Science (2021)

 Highly Transparent, Stretchable, and Self-Healable lonogel for Multifunctional Sensors, Triboelectric Nanogenerator, and Wearable Fibrous Electronics

Lijie Sun

Hongfei Huang

Zhengwei You

Advanced Fiber Materials (2021)

• Soft Tactile Sensing Skins for Robotics

Peter Roberts

Mason Zadan

Carmel Majidi

Current Robotics Reports (2021)

Nature Electronics (*Nat Electron*) ISSN 2520-1131 (online)

© 2021 Springer Nature Limited