Status	Finished
Started	Friday, 30 October 2026, 1:42 PM
Completed	Friday, 30 October 2026, 1:51 PM
Duration	8 mins 32 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for writing, we use _____

a. outfile = open(file = "c:\scores.txt", "w")

b. outfile = open(file = "c:\\scores.txt", "w")

c. outfile = open("c:\scores.txt", "w")

d. outfile = open("c:\\scores.txt", "w") ✓

The correct answer is:
outfile = open("c:\\scores.txt", "w")

Question **2**

Correct

Mark 1.00 out of 1.00

What does the encoding parameter in the open() function specify?

a. The size of the file

b. The mode of the file

c. The buffer size

d. The encoding format of the file ✓

The correct answer is: The encoding format of the file

Question **3**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

- a. move the file pointer to beginning of the file
- b. move the file pointer five characters behind from the current position
- c. move the file pointer five characters ahead from the current position ✓
- d. moves the file pointer to the end of a file

The correct answer is:
move the file pointer five characters ahead from the current position

Question **4**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

- a. reduce()
- b. shrink()
- c. truncate() ✓
- d. resize()

The correct answer is: truncate()

Question **5**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

- a. write_list()
- b. writelines() ✓
- c. write_all()
- d. write()

The correct answer is: writelines()

Question **6**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

- a. seek() ✓
- b. tell()
- c. ftell()
- d. fseek()

The correct answer is: seek()

Question **7**

Correct

Mark 1.00 out of 1.00

What is the result of the following code?

```
with open("example.txt", "r") as f:
    data = f.read()
print(data)
```

- a. Prints each line of the file
- b. Prints an error message
- c. Prints the entire content of the file ✓
- d. Prints the first 10 characters of the file

The correct answer is: Prints the entire content of the file

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

- a. Hello
- b. Hello, world! ✓
- c. An error is raised
- d. world

The correct answer is: Hello, world!

Question **9**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

a. infile = open(file = “a.txt”, “r”)

b. infile = open(“a.txt”, “r”) ✓

c. infile = open(file, “a.txt”, “r”)

d. infile = open(file = “a.txt”, “r”)

The correct answer is:
infile = open(“a.txt”, “r”)

Question **10**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

a. a list of single characters

b. a list of integers

c. a list of lines ✓

d. str

The correct answer is:
a list of lines

Question **11**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

a. readline()

b. readlines()

c. readchar()

d. read(size) ✓

The correct answer is: read(size)

Question **12**

Correct

Mark 1.00 out of 1.00

Select the correct method to write a list of lines to a file

- a. writelines(list) ✓
- b. write(list)
- c. writelist(list)
- d. None of the mentioned

The correct answer is: writelines(list)

Question **13**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

- a. An empty string ✓
- b. None
- c. 0
- d. EOFError

The correct answer is: An empty string

Question **14**

Correct

Mark 1.00 out of 1.00

What does the flush() method do in file handling?

- a. Closes the file
- b. Moves the file cursor to the beginning
- c. Deletes the file content
- d. Flushes the internal buffer to the file ✓

The correct answer is: Flushes the internal buffer to the file

Question **15**

Correct

Mark 1.00 out of 1.00

Which of the following methods is used to read a single line from a file?

a. readline() ✓
b. readline(size)
c. readlines()
d. read()

The correct answer is: readline()