VIT®
Vellore Institute of Technology
(Deemed to be University under section 3 of UGC Act, 1956)

Fall Semester 2021-22

Microprocessors and Interfacing LAB

CSE2006

Slot – L43+L44

Digital Assignment 3

Name: Ishan Sagar Jogalekar

Reg. No: 19BCE2250

1. Factorial of number -

Input:

Here value 9 as input. The value 9 is being stored in location 0000H. We are using n as variable data byte with value = 9 so that factorial of 9 will be calculated.

Flowchart:



Algorithm:

1) Input the Number whose factorial is to be find and Store that Number in CX Register (Condition for LOOP Instruction).
2) Insert 0001 in AX (Condition for MUL Instruction) and 0000 in DX.
3) Multiply CX with AX until CX become Zero (0) using LOOP Instruction.
4) Copy the content of AX to memory location 0600.
5) Copy the content of DX to memory location 0601.
6) Stop Execution.

Program:

```
.model small
.stack 64
.data
        A db 09h
.code
        mov ax, @data
        mov ds, ax
        lea si, A
        mov bx, [si]
        mov ax, 0001h
repeat:
        mul bx
        dec bx
        cmp bx, 00h
        jnz repeat
        mov ax, 4ch
int 21h
end
.end
Hlt
```



Output:


DOSBox 0.74-3, Cpu speed: 3000 cycles, Frameskip 0, Progra...
C:\>masm FACT.ASM
Microsoft (R) Macro Assembler Version 5.00
Copyright (C) Microsoft Corp 1981-1985, 1987. All rights reserved.
Object filename [FACT.OBJ]:
Source listing [NUL.LST]:
Cross-reference [NUL.CRF]:
51672 + 464872 Bytes symbol space free
0 Warning Errors
0 Severe Errors
C:\>link FACT.OBJ
Microsoft (R) Overlay Linker Version 3.60
Copyright (C) Microsoft Corp 1983-1987. All rights reserved.
Run File [FACT.EXE]:
List File [NUL.MAP]:
Libraries [.LIB]:
C:\>


DOSBox 0.74-3, Cpu speed: 3000 cycles, Frameskip 0, Progra...
C:\>debug FACT.EXE
-d
076A:0000 B8 6B 07 8E D8 8D 36 0C-00 8B 1C B8 01 00 F7 E3 .k....6.....
076A:0010 4B 83 FB 00 75 F8 B8 4C-00 CD 21 00 08 52 50 E8 K...u..L..!..RP.
076A:0020 0E 49 83 C4 04 50 E8 9F-0E 83 C4 04 3D FF FF 74 .I...P.....=..t
076A:0030 03 E9 11 01 B8 2F 00 50-8B 46 FC 8B 56 FE 05 0C ...../.P.F..V...
076A:0040 00 52 50 E8 EA 48 83 C4-04 50 E8 7B 0E 83 C4 04 .RP..H...P.{....
076A:0050 3D FF FF 74 03 E9 50 C5-00 00 11 00 6A 07 FF FF =..t..P.....j...
076A:0060 E4 40 50 8B C3 8C C2 05-0C 00 52 50 E8 C1 48 83 .@P.....RP..H.
076A:0070 C4 04 50 8D 86 FA FE 50-E8 17 73 83 C4 06 8B B6 ..P....P..s.....
-t
AX=076B BX=0000 CX=001D DX=0000 SP=0040 BP=0000 SI=0000 DI=0000
DS=075A ES=075A SS=076C CS=076A IP=0003 NV UP EI PL NZ NA PO NC
076A:0003 8ED8 MOV DS,AX
-t
AX=076B BX=0000 CX=001D DX=0000 SP=0040 BP=0000 SI=0000 DI=0000
DS=076B ES=075A SS=076C CS=076A IP=0005 NV UP EI PL NZ NA PO NC
076A:0005 8D360C00 LEA SI,[000C] DS:000C=5208


DOSBox 0.74-3, Cpu speed: 3000 cycles, Frameskip 0, Progra...
AX=CE38 BX=5206 CX=001D DX=1A48 SP=0040 BP=0000 SI=000C DI=0000
DS=076B ES=075A SS=076C CS=076A IP=0014 NV UP EI PL NZ NA PE NC
076A:0014 75F8 JNZ 000E
AX=CE38 BX=5206 CX=001D DX=1A48 SP=0040 BP=0000 SI=000C DI=0000
DS=076B ES=075A SS=076C CS=076A IP=000E NV UP EI PL NZ NA PE NC
076A:000E F7E3 MUL BX
AX=C550 BX=5206 CX=001D DX=4212 SP=0040 BP=0000 SI=000C DI=0000
DS=076B ES=075A SS=076C CS=076A IP=0010 OV UP EI PL NZ NA PE CY
076A:0010 4B DEC BX
AX=C550 BX=5205 CX=001D DX=4212 SP=0040 BP=0000 SI=000C DI=0000
DS=076B ES=075A SS=076C CS=076A IP=0011 NV UP EI PL NZ NA PE CY
076A:0011 83FB00 CMP BX,+00
AX=C550 BX=5205 CX=001D DX=4212 SP=0040 BP=0000 SI=000C DI=0000
DS=076B ES=075A SS=076C CS=076A IP=0014 NV UP EI PL NZ NA PE NC
076A:0014 75F8 JNZ 000E
AX=C550 BX=5205 CX=001D DX=4212 SP=0040 BP=0000 SI=000C DI=0000
DS=076B ES=075A SS=076C CS=076A IP=000E NV UP EI PL NZ NA PE NC
076A:000E F7E3 MUL BX

2. Fibonacci series –

Input:

Initialize counter with number of terms in series and load it to DB. Also considering default numbers as input 0H and 01H as starting of any Fibonacci series.

Flowchart:



Algorithm:

1. Move the value stored at offset 00H into CX- consider to be counter, and decrement it by 2.
2. Move 00H into AL
3. Move 500 into SI
4. Move AL into [SI]
5. Increment both AL and SI by 1, and store AL's value in [SI].
6. Move [SI-1]th value into AL
7. Move [SI]th value into AH
8. Move 00H into BH
9. Add BH and AH
10. Add BH again with AL
11. Increment SI by 1
12. Store BH into [SI]
13. Loop back to Step 6 till counter becomes 0
14. Stop

Program:

```
.MODEL SMALL

.DATA

RES DB ?

CNT DB 0AH

.CODE

START:

        MOV AX,@DATA

        MOV DS,AX

        LEA SI,RES

        MOV CL,CNT

        MOV AX,00H

        MOV BX,01H

L1:

        ADD AX,BX

        MOV [SI],AX

        MOV AX,BX

        MOV BX,[SI]
```

```
        INC SI
LOOP L1
INT 3H
END START
```



Output:





3.1 Largest number in given numbers-

Input:

Considering input of numbers in string initially stored in DB and dynamically stored in subsequent registers.

Flowchart:



Algorithm:

1. Initialize base address of the data segment. Using the displacements from this base address, store values in different registers.
2. Store offset 3000 in SI-register&offset3500inDIregister.

3. Load data from SI to register CL and set register CH to 00.
4. Load first number from next offset to register AL and decrease CL by 1.
5. Compare value of register AL with the data at next offset.
6. If that data is greater than value of register AL then update value of register AL to that data else no changes are required.
7. Increase the offset value for next comparison and decrease count by 1 and continue this till CL becomes 0. Store result, largest number stored in AL register, to offset address 3500, which is pointed to by DI register. Mov result to register BX.

Program:

```
data segment
STRING1 DB 08h,14h,05h,0Fh,09h
res db ?
data ends

code segment
assume cs:code, ds:data
start: mov ax, data
mov ds, ax
mov cx, 04h

mov bl, 00h
LEA SI, STRING1
up:
mov al, [SI]
cmp al, bl
jl nxt
mov bl, al
nxt:
inc si
dec cx
jnz up
```

```
mov res,bl
int 3
code ends
end start
```



Output:





3.2 Smallest number in given numbers-

Input:

Considering input of numbers in string initially stored in DB and dynamically stored in subsequent registers.

Flowchart:



Algorithm:

1. Initialize base address of the data segment. Using the displacements from this base address, store values in different registers.
2. Store offset 3000 in SI-register&offset3500inDIregister.
3. Load data from SI to register CL and set register CH to 00.
4. Load first number from next offset to register AL and decrease CL by 1.
5. Compare value of register AL with the data at next offset.
6. If that data is smaller than value of register AL then update value of register AL to that data else no changes are required.
7. Increase the offset value for next comparison and decrease count by 1 and continue this till CL becomes 0. Store result, largest number stored in AL register, to offset address 3500, which is pointed to by DI register. Mov result to BX register.

Program:

```
data segment
STRING1 DB 07h,13h,05h,0Bh,10h
res db ?
data ends
code segment
assume cs:code, ds:data
start: mov ax, data
mov ds, ax
mov cx, 04h
mov bl, 79h
LEA SI, STRING1
up:
mov al, [SI]
cmp al, bl
jge nxt
mov bl, al
nxt:
inc si
dec cx
```

```
        jnz up
        mov res,bl
        int 3
        code ends
end start
```



Output:





4.Bubble sort –

A. Ascending Order:

Input:

supplying 16-bit input in the data segment by creating an array called list using assemble directive method. Here we are using Data Word (DW) which means that we are using core digit value.

Flowchart:



Algorithm:

1. Load data from offset 500 to register CL (for count).
2. Travel from starting memory location to last and compare two numbers
3. If first number is greater than second number then swap them.
4. First pass fixes the position for last number.
5. Decrease the count by 1.
6. Again, travel from starting memory location to (last-1, by help of count) and compare two numbers
7. If first number is greater than second number then swap them.
8. Second pass fix the position for last two numbers.

9. Repeat.

Program:

```
DATA SEGMENT
STRING1 DB 19H,10H,50H,04H,32H
DATA ENDS
CODE SEGMENT
ASSUME CS:CODE,DS:DATA
START: MOV AX,DATA
MOV DS,AX
MOV CH,04H
UP2: MOV CL,04H
LEA SI,STRING1
UP1: MOV AL,[SI]
MOV BL,[SI+1]
CMP AL,BL
JC DOWN
MOV DL,[SI+1]
XCHG [SI],DL
MOV [SI+1],DL
DOWN: INC SI
DEC CL
JNZ UP1
DEC CH
JNZ UP2
INT 3
CODE ENDS
END START
```

DOSBox 0.74-3, Cpu speed: 3000 cycles, Frameskip 0, Progra...

File Edit Search View Options Help

C:\ASC.ASM

```
DATA SEGMENT
STRING1 DB 99H,12H,56H,45H,36H
DATA ENDS

CODE SEGMENT
ASSUME CS:CODE,DS:DATA
START: MOV AX,DATA
MOV DS,AX

MOV CH,04H

UP2: MOV CL,04H
LEA SI,STRING1

UP1: MOV AL,[SI]
MOV BL,[SI+1]
CMP AL,BL
JC DOWN
MOV DL,[SI+1]
XCHG [SI],DL
MOV [SI+1],DL
```

F1=Help | Line:1 Col:1

Output:

DOSBox 0.74-3, Cpu speed: 3000 cycles, Frameskip 0, Progra...

```
C:\>masm ASC.ASM
Microsoft (R) Macro Assembler Version 5.00
Copyright (C) Microsoft Corp 1981-1985, 1987.  All rights reserved.

Object filename [ASC.OBJ]:
Source listing  [NUL.LST]:
Cross-reference [NUL.CRF]:

  51614 + 464930 Bytes symbol space free

      0 Warning Errors
      0 Severe  Errors

C:\>link ASC.OBJ

Microsoft (R) Overlay Linker  Version 3.60
Copyright (C) Microsoft Corp 1983-1987.  All rights reserved.

Run File [ASC.EXE]:
List File [NUL.MAP]:
Libraries [.LIB]:
LINK : warning L4021: no stack segment

C:\>_
```

DOSBox 0.74-3, Cpu speed: 3000 cycles, Frameskip 0, Progra...

```
C:\>debug ASC.EXE
-g

AX=0732  BX=0050  CX=0000  DX=0010  SP=0000  BP=0000  SI=0004  DI=0000
DS=076A  ES=075A  SS=0769  CS=076B  IP=0027   NV UP EI PL ZR NA PE CY
076B:0027 CC            INT     3
-d ds:0000
076A:0000  04 10 19 32 50 00 00 00-00 00 00 00 00 00 00 00   ...2P...........
076A:0010  B8 6A 07 8E D8 B5 04 B1-04 8D 36 00 00 8A 04 8A   .j........6.....
076A:0020  5C 01 3A C3 72 08 8A 54-01 86 14 88 54 01 46 FE   \.:.r..T....T.F.
076A:0030  C9 75 EA FE CD 75 E0 CC-8B 46 FC 8B 56 FE 05 0C   .u...u...F..V...
076A:0040  00 52 50 E8 EA 48 83 C4-04 50 E8 7B 0E 83 C4 04   .RP..H...P.{....
076A:0050  3D FF FF 74 03 E9 ED 00-C4 5E FC 26 8A 47 0C 2A   =..t.....^.&.G.*
076A:0060  E4 40 50 8B C3 8C C2 05-0C 00 52 50 E8 C1 48 83   .@P.......RP..H.
076A:0070  C4 04 50 8D 86 FA FE 50-E8 17 73 83 C4 06 8B B6   ..P....P..s.....
-_
```

B. Descending Order:

Flowchart:



Algorithm:

1. Load data from offset 500 to register CL (for count).
2. Travel from starting memory location to last and compare two numbers
3. If first number is less than second number then swap them.
4. First pass fixes the position for last number.
5. Decrease the count by 1.
6. Again, travel from starting memory location to (last-1, by help of count) and compare two numbers
7. If first number is less than second number then swap them.
8. Second pass fix the position for last two numbers.
9. Repeat.

Program:

```
DATA SEGMENT

STRING1 DB 19H,10H,50H,04H,32H

DATA ENDS

CODE SEGMENT

ASSUME CS:CODE,DS:DATA
```

```
START: MOV AX,DATA
MOV DS,AX
MOV CH,04H
UP2: MOV CL,04H
LEA SI,STRING1
UP1:MOV AL,[SI]
MOV BL,[SI+1]
CMP AL,BL
JNC DOWN
MOV DL,[SI+1]
XCHG [SI],DL
MOV [SI+1],DL
DOWN: INC SI
DEC CL
JNZ UP1
DEC CH
JNZ UP2
INT 3
CODE ENDS
END START
```



Output:


DOSBox 0.74-3, Cpu speed: 3000 cycles, Frameskip 0, Progra...
C:\>masm DSC.ASM
Microsoft (R) Macro Assembler Version 5.00
Copyright (C) Microsoft Corp 1981-1985, 1987. All rights reserved.
Object filename [DSC.OBJ]:
Source listing [NUL.LST]:
Cross-reference [NUL.CRF]:
51614 + 464930 Bytes symbol space free
0 Warning Errors
0 Severe Errors
C:\>link DSC.OBJ
Microsoft (R) Overlay Linker Version 3.60
Copyright (C) Microsoft Corp 1983-1987. All rights reserved.
Run File [DSC.EXE]:
List File [NUL.MAP]:
Libraries [.LIB]:
LINK : warning L4021: no stack segment
C:\>


DOSBox 0.74-3, Cpu speed: 3000 cycles, Frameskip 0, Progra...
C:\>debug DSC.EXE
-g
AX=0710 BX=0004 CX=0000 DX=0019 SP=0000 BP=0000 SI=0004 DI=0000
DS=076A ES=075A SS=0769 CS=076B IP=0027 NV UP EI PL ZR NA PE NC
076B:0027 CC INT 3
-d ds:0000
076A:0000 50 32 19 10 04 00 00 00-00 00 00 00 00 00 00 00 P2..............
076A:0010 B8 6A 07 8E D8 B5 04 B1-04 8D 36 00 00 8A 04 8A .j........6.....
076A:0020 5C 01 3A C3 73 08 8A 54-01 86 14 88 54 01 46 FE \.:.s..T....T.F.
076A:0030 C9 75 EA FE CD 75 E0 CC-8B 46 FC 8B 56 FE 05 0C .u...u...F..V...
076A:0040 00 52 50 E8 EA 48 83 C4-04 50 E8 7B 0E 83 C4 04 .RP..H...P.{....
076A:0050 3D FF FF 74 03 E9 ED 00-C4 5E FC 26 8A 47 0C 2A =..t.....^.&.G.*
076A:0060 E4 40 50 8B C3 8C C2 05-0C 00 52 50 E8 C1 48 83 .@P.......RP..H.
076A:0070 C4 04 50 8D 86 FA FE 50-E8 17 73 83 C4 06 8B B6 ..P....P..s.....