

CCS4354 · TENSORS AND GRAPHS

Graph Neural Networks for Node Classification

A Comparative Study of GCN and GAT Architectures on the OGBN-Arxiv Citation Network

Technical Report

Group 07

23UG1-0095 , 23UG1-0061 , 23UG1-0054 , 23UG1-0010

Module: CCS4354 – Tensors and Graphs
Lecturer in Charge: Dr. Chameera De Silva
Teaching Assistant: Mr. Chamod Hewage
SLTC Research University
2026

Table of Contents

1. Introduction.....	3
1.1 Dataset Overview	3
2. Tensor Fundamentals	3
3. Graph Representation and Analysis	4
4. Data Preparation.....	5
5. Graph Neural Network Architecture	5
6. Model Training and Optimization.....	7
7. Model Evaluation	8
8. Explainability and Embedding Analysis.....	8
9. Graph Intelligence Dashboard.....	9
10. Conclusion	9
10.1 Limitations and Future Work.....	10
11. Individual Contributions.....	10
References	10

1. Introduction

This report documents the design, implementation, and evaluation of a node classification pipeline built on the OGBN-Arxiv citation network, completed as coursework for CCS4354 – Tensors and Graphs. OGBN-Arxiv represents a citation graph of scientific papers: each node is a paper, each directed edge represents one paper citing another, and the task is to predict which of 40 computer science subject categories a paper belongs to using both its own content and its position within the citation network.

Two Graph Neural Network architectures were implemented and compared: a Graph Convolutional Network (GCN) and a Graph Attention Network (GAT). The report follows the coursework's task structure — from foundational tensor operations, through graph analysis and data preparation, to model development, training, evaluation, explainability, and an interactive dashboard — with each section explaining both what was built and the reasoning behind key decisions.

1.1 Dataset Overview

Property	Value
Nodes (papers)	169,343
Edges (citations)	1,166,243
Node feature dimension	128
Number of classes	40 subject categories
Graph density	0.000041
Task	Node classification
Split type	Official OGB split (by publication year)

2. Tensor Fundamentals

Before working with graph data, the foundational PyTorch tensor operations that underpin every subsequent stage of the pipeline were demonstrated and explained. A tensor is a multi-dimensional array; in this project, node features are stored as a tensor of shape $[169,343, 128]$, meaning each paper is represented by a 128-dimensional feature vector derived from its title and abstract.

2.1 Operations Demonstrated

- Tensor creation — building tensors from lists and using constructors such as `zeros()`, `ones()`, `rand()`, and `eye()`.
- Indexing and slicing — accessing rows, columns, and sub-matrices using multi-dimensional indexing.
- Reshaping — rearranging tensor dimensions with `view()` and `reshape()` while preserving the total element count.
- Matrix multiplication — using `matmul()` / `@`, contrasted against element-wise multiplication.
- Broadcasting — applying operations across tensors of different but compatible shapes without explicit copying.
- Aggregation — `sum`, `mean`, and `max` operations along a specified dimension.

- GPU operations — moving tensors to CUDA with `.to('cuda')` and comparing CPU vs GPU execution time.

2.2 Relevance to Graph Neural Networks

Two of these operations are foundational to everything that follows. Matrix multiplication underlies every graph convolution layer, where the adjacency structure is combined with the feature matrix. Aggregation along a dimension is mechanically identical to how a GNN combines a node's neighbours into a single summary vector — the same sum/mean operation demonstrated here reappears, at scale, inside every GCN and GAT layer used later in this report.

3. Graph Representation and Analysis

3.1 Edge List Representation

PyTorch Geometric represents the graph using an `edge_index` tensor of shape `[2, num_edges]`. Each column represents one citation: row 0 holds the source paper and row 1 holds the target paper it cites.

```
edge_index[0] = [ 12, 45, 12, 90, ... ] (source)
edge_index[1] = [ 45, 88, 90, 3, ... ] (target)
```

3.2 Node Features

Each node carries a 128-dimensional feature vector, generated by averaging word embeddings from the paper's title and abstract. These features form the model's input signal alongside the graph structure.

3.3 Subgraph Visualization

A 2-hop neighbourhood subgraph around a sample node was extracted and visualised using NetworkX, since visualising the full 169,343-node graph is not practical. This provided an intuitive, human-readable view of local citation structure before any modelling began.

3.4 Structural Analysis

Degree Distribution

The out-degree and in-degree distributions were plotted on a log scale. The distribution is heavily right-skewed: most papers cite or are cited by only a small number of others, while a small number of highly-cited papers act as hub nodes. This is the classic power-law-like pattern characteristic of real-world citation networks.

Graph Density

Graph density was computed as the ratio of actual edges to all possible directed edges, yielding a value of approximately 0.000041. This confirms the graph is extremely sparse, which is expected — no single paper could realistically cite a meaningful fraction of 169,000 other papers.

Connected Components

Connected component analysis (performed on the undirected version of the graph via a sparse adjacency matrix for efficiency) showed the graph is largely one giant connected structure, with a small number of tiny isolated components — consistent with a small subset of papers that cite or are cited by very few others, such as niche topics or very recent publications.

4. Data Preparation

4.1 Features and Labels

Node features (`data.x`) and labels (`data.y`) were loaded directly from the OGB dataset object. Labels originally have shape `[N, 1]` and were squeezed to shape `[N]` to match the format expected by PyTorch's loss functions.

4.2 Train / Validation / Test Split

The official OGB split was used rather than a custom random split. This split is based on publication year — older papers form the training set, and newer papers form the test set.

Split	Node Count
Train	90,941
Validation	29,799
Test	48,603

This decision was deliberate for two reasons. First, it simulates a realistic deployment scenario — classifying a newly published paper using only knowledge from past papers. Second, it keeps results directly comparable to the published OGB leaderboard benchmarks; a random split would not only break that comparability but could also leak information across time.

4.3 Normalization

Feature statistics (min, max, mean, and per-dimension scale) were inspected before deciding on normalization. Since the provided embeddings were already small in magnitude and consistent across all 128 dimensions, no additional normalization was applied — avoiding the risk of discarding useful signal already encoded in the original feature magnitudes.

5. Graph Neural Network Architecture

Two architectures were implemented to satisfy the coursework's requirement for at least two GNN models: a Graph Convolutional Network (GCN) as the required baseline, and a Graph Attention Network (GAT) as the second architecture.

5.1 GCN — Graph Convolutional Network

GCN aggregates each node's neighbours using a fixed, degree-normalized average — every neighbour contributes proportionally to the final representation, regardless of its individual relevance.

```
class GCN(torch.nn.Module):
    def __init__(self, in_channels, hidden_channels, out_channels,
                  num_layers=3, dropout=0.5):
        super().__init__()
        self.convs = torch.nn.ModuleList()
        self.convs.append(GCNConv(in_channels, hidden_channels))
        for _ in range(num_layers - 2):
            self.convs.append(GCNConv(hidden_channels, hidden_channels))
        self.convs.append(GCNConv(hidden_channels, out_channels))
        self.dropout = dropout

    def forward(self, x, edge_index):
        for conv in self.convs[:-1]:
            x = conv(x, edge_index)
            x = F.relu(x)
            x = F.dropout(x, p=self.dropout, training=self.training)
        x = self.convs[-1](x, edge_index)
        return x
```

5.2 GAT — Graph Attention Network

GAT improves on GCN by learning attention weights per neighbour, rather than treating every neighbour equally. Eight attention heads allow the model to learn several independent notions of “importance” in parallel before combining them.

```
class GAT(torch.nn.Module):
    def __init__(self, in_channels, hidden_channels, out_channels,
                  heads=8, dropout=0.5):
        super().__init__()
        self.conv1 = GATConv(in_channels, hidden_channels,
                              heads=heads, dropout=dropout)
        self.conv2 = GATConv(hidden_channels * heads, out_channels,
                              heads=1, concat=False, dropout=dropout)
        self.dropout = dropout

    def forward(self, x, edge_index):
        x = F.dropout(x, p=self.dropout, training=self.training)
        x = self.conv1(x, edge_index)
        x = F.elu(x)
        x = F.dropout(x, p=self.dropout, training=self.training)
        x = self.conv2(x, edge_index)
        return x
```

5.3 Architecture and Hyperparameter Summary

Hyperparameter	GCN	GAT
Aggregation	Fixed, degree-normalized average	Learned attention weights per neighbour

Hyperparameter	GCN	GAT
Layers	3	2
Hidden dimension	256	32 per head (256 effective)
Attention heads	—	8
Activation	ReLU	ELU
Dropout	0.5	0.5
Input dimension	128	128
Output dimension	40	40

Three layers were used for GCN to allow each node's representation to incorporate information from up to 3-hop citation neighbours, while avoiding the over-smoothing effect associated with stacking too many graph convolution layers. GAT uses a smaller per-head hidden dimension (32) because concatenating 8 heads restores an effective width of 256, matching GCN for a fair comparison. Dropout of 0.5 and ReLU/ELU activations follow standard practice from the original GCN and GAT papers for citation network benchmarks.

6. Model Training and Optimization

6.1 Loss Function and Optimizer

CrossEntropyLoss was used for both models, as the standard choice for multi-class node classification. The Adam optimizer was chosen over plain SGD for its per-parameter adaptive learning rate, which converges reliably with less manual tuning — important given the limited tuning budget of a coursework project.

Setting	GCN	GAT
Loss function	CrossEntropyLoss	CrossEntropyLoss
Optimizer	Adam	Adam
Learning rate	0.01	0.005
Weight decay	5e-4	5e-4
Epochs	200	200

GAT was trained with a lower learning rate than GCN because its attention mechanism introduces additional learnable parameters (per-edge attention coefficients), which makes training less stable at higher rates.

6.2 Training Behaviour

Both models were trained for 200 epochs, with training and validation loss recorded at every epoch. Training loss decreased smoothly and consistently for both models, with validation loss tracking closely alongside it — indicating the models generalised reasonably well without severe overfitting within the given epoch budget.

6.3 Hyperparameter Tuning

A small learning-rate sweep was conducted for the GCN model to demonstrate the tuning process required by the coursework specification:

Learning Rate	Outcome
0.001	Underfit — had not fully converged within the epoch budget
0.01	Best validation accuracy achieved
0.05	Unstable — validation loss showed signs of divergence

7. Model Evaluation

Both models were evaluated on the validation and test sets using Accuracy, Precision, Recall, and F1-score. Precision, Recall, and F1 were macro-averaged — computed per class and then averaged — to treat all 40 categories equally despite their unequal sizes, giving a fairer picture than accuracy alone on an imbalanced multi-class problem.

7.1 Results Summary

Model	Split	Accuracy	Precision (macro)	Recall (macro)	F1 (macro)
GCN	Validation	0.5835	0.3905	0.3072	0.3167
GCN	Test	0.5254	0.3514	0.2869	0.2836
GAT	Validation	0.5601	0.3702	0.2391	0.2440
GAT	Test	0.5125	0.3296	0.2297	0.2238

7.2 Discussion

GCN outperformed GAT on the test set across every metric, achieving 52.5% accuracy versus GAT's 51.3%, and a notably higher macro-F1 (0.284 versus 0.224). This suggests that, on this benchmark and with the hyperparameters explored, GCN's simpler, fixed neighbourhood aggregation generalised slightly better than GAT's learned attention mechanism. GAT's additional attention parameters likely require either more training epochs or more extensive hyperparameter tuning to realise their full potential on this dataset.

Both models show a modest gap between validation and test performance (for example, GCN drops from 58.4% to 52.5% accuracy), which is expected given the OGB split's year-based structure — test-set papers are genuinely newer and structurally different from the papers the models were trained and validated on, rather than being drawn from the same time period.

8. Explainability and Embedding Analysis

Two explainability techniques were used to interpret model behaviour and confirm that predictions are grounded in meaningful graph structure rather than being an opaque black box: node embedding visualisation and GAT attention weight analysis.

8.1 Node Embedding Visualization (t-SNE)

The learned hidden-layer representations from the trained GCN model were extracted and reduced to two dimensions using t-SNE, applied to a representative sample of test-set nodes for computational efficiency. The resulting visualisation showed visually distinct clusters corresponding to different subject categories — evidence that the model has learned to group semantically similar papers together in its internal representation space, despite never being directly optimised to produce clusters.

8.2 GAT Attention Weight Analysis

For sample nodes, GAT's per-edge attention weights were extracted directly from its first convolutional layer. The analysis showed attention is not distributed equally across a node's citation neighbours — some neighbours consistently receive substantially higher attention weight than others, confirming the model learns which citation relationships carry more predictive signal rather than treating all neighbours as equally informative.

8.3 Interpretation

Together, these two analyses support the conclusion that both models' predictions are driven by meaningful combinations of node features and graph structure, rather than memorisation of individual node characteristics satisfying the coursework's requirement to explain, not just report, model behaviour.

9. Graph Intelligence Dashboard

An interactive dashboard was built using Streamlit to bring every stage of the analysis into a single, explorable interface, satisfying the coursework's requirement for a working dashboard deliverable.

9.1 Features

- Live graph statistics — node count, edge count, and graph density.
- Model performance metrics — a comparison table and bar chart of GCN vs. GAT across all four evaluation metrics.
- Node classification explorer — select a test-set node and view its true label, GCN's predicted label, and whether the prediction was correct.
- Embedding visualization — the t-SNE projection of learned node embeddings, rendered directly in the dashboard.

9.2 Implementation

The dashboard loads a precomputed results file (containing graph statistics, evaluation metrics, and embedding coordinates) rather than re-running inference live, keeping the interface fast and responsive. It was built and run locally using Streamlit within a Python virtual environment, launched via `streamlit run app.py`.

10. Conclusion

This project implemented a complete graph-based node classification pipeline on the OGBN-Arxiv citation network, covering tensor fundamentals, graph structural analysis, data preparation, two GNN architectures, training and optimisation, evaluation, explainability, and an interactive dashboard.

Both GCN and GAT classified research papers well above the random-guess baseline of approximately 2.5% for 40 classes, with GCN achieving the stronger overall result on this benchmark (52.5% test accuracy versus GAT's 51.3%). Embedding visualisation and attention weight analysis both confirmed the models' decisions are grounded in meaningful graph structure rather than being uninterpretable.

10.1 Limitations and Future Work

- A more extensive hyperparameter search across layer count, hidden dimension, and dropout could likely close or reverse the GCN/GAT performance gap.
- A third architecture, such as a Graph Isomorphism Network (GIN), could be added for the coursework's bonus marks.
- GNNExplainer-based subgraph extraction would provide finer-grained, per-prediction explanations beyond global embedding and attention analysis.
- Attention analysis was demonstrated on individual sample nodes; extending this to a larger, systematic sample would strengthen the explainability findings.

11. Individual Contributions

Member	Primary Contribution
Member 1	Tensor fundamentals notebook, dataset setup, presentation coordination
Member 2	Graph representation and analysis, data preparation, train/test split justification
Member 3	GNN architecture design (GCN and GAT), training loop implementation, hyperparameter tuning
Member 4	Model evaluation, explainability analysis, Streamlit dashboard, technical report compilation

References

Open Graph Benchmark — OGBN-Arxiv Dataset. <https://ogb.stanford.edu/docs/nodeprop/#ogbn-arxiv>

Kipf, T. N., & Welling, M. (2017). Semi-Supervised Classification with Graph Convolutional Networks. ICLR.

Veličković, P., Cucurull, G., Casanova, A., Romero, A., Liò, P., & Bengio, Y. (2018). Graph Attention Networks. ICLR.

PyTorch Geometric Documentation. <https://pytorch-geometric.readthedocs.io>

Hu, W., Fey, M., Zitnik, M., Dong, Y., Ren, H., Liu, B., Catasta, M., & Leskovec, J. (2020). Open Graph Benchmark: Datasets for Machine Learning on Graphs. NeurIPS.